



FCC TEST REPORT

REPORT NO.: RF930316R01

MODEL NO.: WRE54G

RECEIVED: Mar. 16, 2004

TESTED: Mar. 20 ~ Mar. 23, 2004

APPLICANT: Cisco-Linksys, LLC

ADDRESS: 121 Theory Drive, Irvine, CA 92612 (USA)

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 74 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST	9
4	TEST TYPES AND RESULTS	10
4.1	CONDUCTED EMISSION MEASUREMENT	10
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	10
4.1.2	TEST INSTRUMENTS	10
4.1.3	TEST PROCEDURES	11
4.1.4	DEVIATION FROM TEST STANDARD	11
4.1.5	TEST SETUP	12
4.1.6	EUT OPERATING CONDITIONS	12
4.1.7	TEST RESULTS	13
4.2	RADIATED EMISSION MEASUREMENT	19
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	19
4.2.2	TEST INSTRUMENTS	20
4.2.3	TEST PROCEDURES	21
4.2.4	DEVIATION FROM TEST STANDARD	21
4.2.5	TEST SETUP	22
4.2.6	EUT OPERATING CONDITIONS	22
4.2.7	TEST RESULTS	23
4.2.8	TEST RESULTS (FOR CCK)	25
4.2.9	TEST RESULTS (FOR OFDM)	31
4.3	6dB BANDWIDTH MEASUREMENT	37
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	37
4.3.2	TEST INSTRUMENTS	37
4.3.3	TEST PROCEDURE	38
4.3.4	DEVIATION FROM TEST STANDARD	38
4.3.5	TEST SETUP	38
4.3.6	EUT OPERATING CONDITIONS	38
4.3.7	TEST RESULTS	39
4.4	MAXIMUM PEAK OUTPUT POWER	47
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	47



4.4.2	TEST INSTRUMENTS	47
4.4.3	TEST PROCEDURES	48
4.4.4	DEVIATION FROM TEST STANDARD	48
4.4.5	TEST SETUP	48
4.4.6	EUT OPERATING CONDITIONS	48
4.4.7	TEST RESULTS	49
4.5	POWER SPECTRAL DENSITY MEASUREMENT	50
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	50
4.5.2	TEST INSTRUMENTS	50
4.5.3	TEST PROCEDURE	51
4.5.4	DEVIATION FROM TEST STANDARD	51
4.5.5	TEST SETUP	51
4.5.6	EUT OPERATING CONDITIONS	51
4.5.7	TEST RESULTS	52
4.6	BAND EDGES MEASUREMENT	60
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	60
4.6.2	TEST INSTRUMENTS	60
4.6.3	TEST PROCEDURE	60
4.6.4	DEVIATION FROM TEST STANDARD	60
4.6.5	EUT OPERATING CONDITION	61
4.6.6	TEST RESULTS (FOR CCK)	61
4.6.7	TEST RESULTS (FOR OFDM)	66
4.7	ANTENNA REQUIREMENT	71
4.7.1	STANDARD APPLICABLE	71
4.7.2	ANTENNA CONNECTED CONSTRUCTION	71
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	72
6	INFORMATION ON THE TESTING LABORATORIES	74



1 CERTIFICATION

PRODUCT : Wireless-G Range Expander
MODEL NO.: WRE54G
BRAND: Linksys
APPLICANT : Cisco-Linksys, LLC
TEST ITEM: ENGINEERING SAMPLE
STANDARDS : FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Mar. 20, 2004 to Mar. 23, 2004. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

PREPARED BY: Wendy Liao, **DATE:** Mar. 29, 2004
Wendy Liao

APPROVED BY: Ellis Wu, **DATE:** Mar. 29, 2004
Ellis Wu / Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -4.73dB at 2.141 MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.00dB at 400.01MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

NOTE: The information of measurement uncertainty is available upon the customer's request.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless-G Range Expander
MODEL NO.	WRE54G
POWER SUPPLY	3.3Vdc from power adapter
MODULATION TYPE	BPSK, QPSK, CCK, 16QAM, 64QAM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	IEEE 802.11b: 11/5.5/2/1Mbps IEEE 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	16.71dBm / 11b 15.42dBm / 11g
ANTENNA TYPE	Dipole antenna with 2dBi gain
DATA CABLE	NA
I/O PORTS	RJ45
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT was operated with following power adapter:

Brand:	UMEC
Model:	UP0051A-03
Input:	100-240Vac, 47-63Hz, 0.2A MAX.
Output:	3.3Vdc, 1.5A

- Fully compatible with the 802.11g standard to provide a wireless data rate of up to 54Mbps.
- Backwards compatible with the 802.11b standard to provide a wireless data rate of up to 11Mbps.
- Operates in the 2.4GHz frequency range.
- For more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1GHz, the channel 1, 6, and 11 were tested individually.
3. Transfer rate, 11Mbps with CCK technique and 6Mbps with OFDM technique, the worst cases, were chosen for final test.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an Wireless-G Range Expander. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4: 1992

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS



The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	Dell	PP01L	TW-09C748- 12800-19O-B220	FCC DoC Approved
2	WIRELESS LAN CARD	D-Link	DWL-G650	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA

NOTE: 1. All power cords of the above support units are non shielded (1.8m).
2. Item1, 2 act as a communication partner to transfer data.

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	838251/021	Jan. 04, 2005
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	100218	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100219	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100220	Dec. 09, 2004
*ROHDE & SCHWARZ 4-wire ISN	ENY41	837032/016	Nov. 19, 2004
*ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Nov. 19, 2004
Software	Cond-V2M3	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C10.01	May 01, 2004
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010770	Feb. 28, 2005
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010773	Feb. 28, 2005

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. “*”: These equipment are used for conducted telecom port test only (if tested).
 3. The test was performed in ADT Shielded Room No. 10.
 4. The VCCI Site Registration No. is C-1312.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under Limit - 20dB was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:** 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS


- Placed the EUT on the testing table.
- Prepared another notebook system to act as a communication partner and placed it outside of testing area.
- The communication partner run a test program to (provided by manufacturer) enable EUT under transmission/receiving condition continuously at specific channel frequency via an RJ45 cable.
- The communication partner sent data to EUT by command "PING".

4.1.7 TEST RESULTS

EUT	Wireless-G Range Expander	MODEL	WRE54G
MODE	Channel 1	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	47.30	-	47.40	-	64.79	54.79	-17.39	-
2	0.345	0.10	40.74	-	40.84	-	59.07	49.07	-18.23	-
3	0.982	0.20	42.38	-	42.58	-	56.00	46.00	-13.42	-
4	1.966	0.20	47.40	40.57	47.60	40.77	56.00	46.00	-8.40	-5.23
5	3.531	0.28	49.18	40.14	49.46	40.42	56.00	46.00	-6.54	-5.58
6	4.401	0.32	49.05	39.47	49.37	39.79	56.00	46.00	-6.63	-6.21
7	11.219	0.65	31.47	-	32.12	-	60.00	50.00	-27.88	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Range Expander	MODEL	WRE54G
MODE	Channel 1	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	45.11	-	45.21	-	64.79	54.79	-19.58	-
2	0.291	0.10	40.49	-	40.59	-	60.51	50.51	-19.92	-
3	0.869	0.18	39.65	-	39.83	-	56.00	46.00	-16.17	-
4	2.082	0.20	45.26	-	45.46	-	56.00	46.00	-10.54	-
5	3.703	0.29	43.81	-	44.10	-	56.00	46.00	-11.90	-
6	4.459	0.32	44.14	-	44.46	-	56.00	46.00	-11.54	-
7	25.230	1.00	31.68	-	32.68	-	60.00	50.00	-27.32	-


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Range Expander	MODEL	WRE54G
MODE	Channel 6	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	46.79	-	46.89	-	64.79	54.79	-17.90	-
2	0.345	0.10	42.04	-	42.14	-	59.07	49.07	-16.93	-
3	0.982	0.20	43.86	-	44.06	-	56.00	46.00	-11.94	-
4	2.141	0.21	48.32	41.06	48.53	41.27	56.00	46.00	-7.47	-4.73
5	4.164	0.31	49.03	39.98	49.34	40.29	56.00	46.00	-6.66	-5.71
6	4.918	0.35	47.31	38.88	47.66	39.23	56.00	46.00	-8.34	-6.77
7	11.543	0.66	30.27	-	30.93	-	60.00	50.00	-29.07	-


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Range Expander	MODEL	WRE54G
MODE	Channel 6	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.172	0.10	44.74	-	44.84	-	64.85	54.85	-20.01	-
2	0.291	0.10	40.57	-	40.67	-	60.51	50.51	-19.84	-
3	0.810	0.17	37.98	-	38.15	-	56.00	46.00	-17.85	-
4	2.083	0.20	45.08	-	45.28	-	56.00	46.00	-10.72	-
5	3.992	0.30	43.10	-	43.40	-	56.00	46.00	-12.60	-
6	4.455	0.32	43.90	-	44.22	-	56.00	46.00	-11.78	-
7	7.694	0.42	35.42	-	35.84	-	60.00	50.00	-24.16	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Range Expander	MODEL	WRE54G
MODE	Channel 11	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	46.73	-	46.83	-	64.79	54.79	-17.96	-
2	0.345	0.10	42.20	-	42.30	-	59.07	49.07	-16.77	-
3	0.810	0.17	43.66	-	43.83	-	56.00	46.00	-12.17	-
4	0.982	0.20	43.25	-	43.45	-	56.00	46.00	-12.55	-
5	2.022	0.20	47.85	40.73	48.05	40.93	56.00	46.00	-7.95	-5.07
6	3.703	0.29	48.91	39.75	49.20	40.04	56.00	46.00	-6.80	-5.96
7	4.859	0.34	47.78	38.70	48.12	39.04	56.00	46.00	-7.88	-6.96
8	25.230	1.20	31.45	-	32.65	-	60.00	50.00	-27.35	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Range Expander	MODEL	WRE54G
MODE	Channel 11	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	44.45	-	44.55	-	64.79	54.79	-20.24	-
2	0.810	0.17	40.25	-	40.42	-	56.00	46.00	-15.58	-
3	2.025	0.20	45.14	-	45.34	-	56.00	46.00	-10.66	-
4	3.703	0.29	43.79	-	44.08	-	56.00	46.00	-11.92	-
5	4.738	0.32	42.67	-	42.99	-	56.00	46.00	-13.01	-
6	23.566	0.94	27.90	-	28.84	-	60.00	50.00	-31.16	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
*HP Spectrum Analyzer	8593E	3911A07465	Jul. 07, 2004
*HP Preamplifier	8447D	2944A10386	Aug. 12, 2004
* HP Preamplifier	8449B	3008A01292	Aug. 11, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Jun. 26, 2004
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
*SCHAFFNER TEST RECEIVER	SCR 3501	409	Nov. 06, 2004
* SCHAFFNER BILOG Antenna	CBL6111C	2727	Jul. 15, 2004
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jun 30, 2004
* ADT. Turn Table	TT100	0201	NA
* ADT. Tower	AT100	0201	NA
* Software	ADT_Radiated_V5.14	NA	NA
* ANRITSU RF Switches	MP59B	6100237246	Oct. 17, 2004
* TIMES RF cable	LMR-600	CABLE-ST10-01	Oct. 17, 2004

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. "*" = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. 10.
5. The VCCI Site Registration No. is R-1625.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

EUT	Wireless-G Range Expander	Model	WRE54G
MODE	Channel 11	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	148.00	22.60 QP	43.50	-20.90	1.00 H	208	10.79	11.81
2	300.05	43.78 QP	46.00	-2.22	1.14 H	7	27.49	16.29
3	400.01	45.00 QP	46.00	-1.00	1.00 H	12	25.58	19.42
4	500.02	40.91 QP	46.00	-5.09	1.26 H	20	19.01	21.90
5	624.00	42.15 QP	46.00	-3.85	1.01 H	126	17.13	25.02
6	651.38	42.50 QP	46.00	-3.50	1.29 H	22	16.86	25.64
7	672.01	40.59 QP	46.00	-5.41	1.13 H	7	14.83	25.76
8	700.04	42.76 QP	46.00	-3.24	1.00 H	31	16.83	25.93
9	800.02	43.12 QP	46.00	-2.88	1.27 H	117	15.93	27.19
10	900.02	42.22 QP	46.00	-3.78	1.13 H	270	13.08	29.14

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Wireless-G Range Expander	Model	WRE54G
MODE	Channel 11	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	TESTED BY: Martin Lee	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	52.80	31.43 QP	40.00	-8.57	1.05 V	289	24.11	7.32
2	195.89	31.72 QP	43.50	-11.78	1.37 V	233	21.33	10.39
3	249.26	30.55 QP	46.00	-15.45	1.60 V	0	16.68	13.87
4	261.33	32.46 QP	46.00	-13.54	1.14 V	187	16.99	15.47
5	300.03	41.19 QP	46.00	-4.81	1.64 V	302	24.90	16.29
6	400.00	41.42 QP	46.00	-4.58	1.76 V	3	22.00	19.42
7	500.01	40.09 QP	46.00	-5.91	1.48 V	289	18.19	21.90
8	624.01	43.89 QP	46.00	-2.11	1.00 V	18	18.87	25.02
9	651.34	40.79 QP	46.00	-5.21	1.00 V	28	15.15	25.64
10	672.09	42.31 QP	46.00	-3.69	1.05 V	315	16.55	25.76
11	700.01	45.00 QP	46.00	-1.00	1.00 V	12	19.07	25.93
12	720.01	43.49 QP	46.00	-2.51	1.00 V	355	16.97	26.52
13	800.02	43.85 QP	46.00	-2.15	1.00 V	273	16.66	27.19
14	900.00	40.53 QP	46.00	-5.47	1.34 V	344	11.39	29.14

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

4.2.8 TEST RESULTS (FOR CCK)

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 1	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	46.24 PK	74.00	-27.76	1.00 H	35	15.44	30.80
1	2390.00	36.40 AV	54.00	-17.60	1.00 H	35	5.60	30.80
2	*2412.00	102.87 PK			1.00 H	35	72.17	30.70
2	*2412.00	93.03 AV			1.00 H	35	62.33	30.70
3	3216.00	45.86 PK	74.00	-28.14	1.47 H	51	12.10	33.76
3	3216.00	36.70 AV	54.00	-17.30	1.47 H	51	2.94	33.76
4	4824.00	55.92 PK	74.00	-18.08	1.60 H	253	19.40	36.52
4	4824.00	48.69 AV	54.00	-5.31	1.60 H	253	12.17	36.52
5	7236.00	56.92 PK	74.00	-17.08	1.59 H	268	15.66	41.26
5	7236.00	48.75 AV	54.00	-5.25	1.59 H	268	7.49	41.26

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 1	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.07 PK	74.00	-18.93	1.00 V	92	24.27	30.80
1	2390.00	46.40 AV	54.00	-7.60	1.00 V	92	15.60	30.80
2	*2412.00	111.70 PK			1.00 V	92	81.00	30.70
2	*2412.00	103.03 AV			1.00 V	92	72.33	30.70
3	3216.00	46.20 PK	74.00	-27.80	1.13 V	20	12.44	33.76
3	3216.00	39.86 AV	54.00	-14.14	1.13 V	20	6.10	33.76
4	4824.00	54.76 PK	74.00	-19.24	1.00 V	44	18.24	36.52
4	4824.00	51.26 AV	54.00	-2.74	1.00 V	44	14.74	36.52
5	7231.00	53.42 PK	74.00	-20.58	1.16 V	349	12.16	41.26
5	7231.00	43.11 AV	54.00	-10.89	1.16 V	349	1.85	41.26

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 6	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	99.89 PK			1.00 H	20	69.17	30.72
1	*2437.00	92.55 AV			1.00 H	20	61.83	30.72
2	3249.00	45.75 PK	74.00	-28.25	1.25 H	327	11.95	33.80
2	3249.00	36.41 AV	54.00	-17.59	1.25 H	327	2.61	33.80
3	4874.00	55.10 PK	74.00	-18.90	1.53 H	66	18.39	36.71
3	4874.00	46.60 AV	54.00	-7.40	1.53 H	66	9.89	36.71
4	6336.00	54.98 PK	74.00	-19.02	1.09 H	36	15.65	39.33
4	6336.00	49.16 AV	54.00	-4.84	1.09 H	36	9.83	39.33
5	7311.00	54.33 PK	74.00	-19.67	1.31 H	16	13.01	41.32
5	7311.00	42.71 AV	54.00	-11.29	1.31 H	16	1.39	41.32

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 6	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	109.72 PK			1.00 V	135	79.00	30.72
1	*2437.00	101.39 AV			1.00 V	135	70.67	30.72
2	3249.00	45.91 PK	74.00	-28.09	1.35 V	21	12.11	33.80
2	3249.00	39.25 AV	54.00	-14.75	1.35 V	21	5.45	33.80
3	4874.00	57.77 PK	74.00	-16.23	1.00 V	20	21.06	36.71
3	4874.00	47.77 AV	54.00	-6.23	1.00 V	20	11.06	36.71
4	7311.00	53.96 PK	74.00	-20.04	1.37 V	33	12.64	41.32
4	7311.00	46.13 AV	54.00	-7.87	1.37 V	33	4.81	41.32

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 11	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	100.74 PK			1.14 H	35	70.00	30.74
1	*2462.00	92.74 AV			1.14 H	35	62.00	30.74
2	2483.50	45.26 PK	74.00	-28.74	1.14 H	35	14.50	30.76
2	2483.50	37.26 AV	54.00	-16.74	1.14 H	35	6.50	30.76
3	4924.00	50.82 PK	74.00	-23.18	1.56 H	11	13.91	36.90
3	4924.00	40.79 AV	54.00	-13.21	1.56 H	11	3.88	36.90
4	7386.00	52.76 PK	74.00	-21.24	1.26 H	34	11.28	41.48
4	7386.00	40.92 AV	54.00	-13.08	1.26 H	34	-0.56	41.48

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 11	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.24 PK			1.08 V	351	78.50	30.74
1	*2462.00	102.41 AV			1.08 V	351	71.67	30.74
2	2483.50	53.76 PK	74.00	-20.24	1.08 V	351	23.00	30.76
2	2483.50	46.93 AV	54.00	-7.07	1.08 V	351	16.17	30.76
3	4924.00	53.91 PK	74.00	-20.09	1.08 V	358	17.00	36.90
3	4924.00	49.30 AV	54.00	-4.70	1.08 V	358	12.39	36.90
4	7386.00	52.09 PK	74.00	-21.91	1.23 V	105	10.61	41.48
4	7386.00	40.26 AV	54.00	-13.74	1.23 V	105	-1.22	41.48

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

4.2.9 TEST RESULTS (FOR OFDM)

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 1	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	45.02 PK	74.00	-28.98	1.11 H	115	14.22	30.80
1	2390.00	37.32 AV	54.00	-16.68	1.11 H	115	6.52	30.80
2	*2412.00	98.70 PK			1.11 H	115	68.00	30.70
2	*2412.00	91.00 AV			1.11 H	115	60.30	30.70
3	3216.00	46.35 PK	74.00	-27.65	1.07 H	324	12.59	33.76
3	3216.00	38.61 AV	54.00	-15.39	1.07 H	324	4.85	33.76
4	4824.00	50.09 PK	74.00	-23.91	1.33 H	48	13.57	36.52
4	4824.00	35.29 AV	54.00	-18.71	1.33 H	48	-1.23	36.52
5	6336.00	53.66 PK	74.00	-20.34	1.04 H	26	14.33	39.33
5	6336.00	41.23 AV	54.00	-12.77	1.04 H	26	1.90	39.33
6	7236.00	54.59 PK	74.00	-19.41	1.24 H	349	13.33	41.26
6	7236.00	39.92 AV	54.00	-14.08	1.24 H	349	-1.34	41.26

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 1	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	52.70 PK	74.00	-21.30	1.00 V	96	21.90	30.80
1	2390.00	44.35 AV	54.00	-9.65	1.00 V	96	13.55	30.80
2	*2412.00	106.38 PK			1.00 V	96	75.68	30.70
2	*2412.00	98.03 AV			1.00 V	96	67.33	30.70
3	3216.00	48.68 PK	74.00	-25.32	1.11 V	115	14.92	33.76
3	3216.00	44.38 AV	54.00	-9.62	1.11 V	115	10.62	33.76
4	4824.00	48.76 PK	74.00	-25.24	1.00 V	316	12.24	36.52
4	4824.00	46.92 AV	54.00	-7.08	1.00 V	316	10.40	36.52
5	7238.00	54.75 PK	74.00	-19.25	1.17 V	19	13.49	41.26
5	7238.00	38.62 AV	54.00	-15.38	1.17 V	19	-2.64	41.26

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 6	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	96.22 PK			1.00 H	43	65.50	30.72
1	*2437.00	89.96 AV			1.00 H	43	59.24	30.72
2	3249.00	44.58 PK	74.00	-29.42	1.27 H	20	10.78	33.80
2	3249.00	35.62 AV	54.00	-18.38	1.27 H	20	1.82	33.80
3	4874.00	52.57 PK	74.00	-21.43	1.30 H	344	15.86	36.71
3	4874.00	41.95 AV	54.00	-12.05	1.30 H	344	5.24	36.71
4	6336.00	52.26 PK	74.00	-21.74	1.30 H	344	12.93	39.33
4	6336.00	38.44 AV	54.00	-15.56	1.30 H	344	-0.89	39.33

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 6	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	106.32 PK			1.00 V	259	75.60	30.72
1	*2437.00	97.59 AV			1.00 V	259	66.87	30.72
2	3249.00	48.48 PK	74.00	-25.52	1.00 V	43	14.68	33.80
2	3249.00	41.68 AV	54.00	-12.32	1.00 V	43	7.88	33.80
3	4874.00	51.60 PK	74.00	-22.40	1.21 V	359	14.89	36.71
3	4874.00	45.57 AV	54.00	-8.43	1.21 V	359	8.86	36.71
4	6336.00	50.24 PK	74.00	-23.76	1.20 V	352	10.91	39.33
4	6336.00	39.21 AV	54.00	-14.79	1.20 V	352	-0.12	39.33

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 11	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	97.07 PK			1.42 H	254	66.33	30.74
1	*2462.00	88.42 AV			1.42 H	254	57.68	30.74
2	2483.50	46.21 PK	74.00	-27.79	1.42 H	254	15.45	30.76
2	2483.50	37.56 AV	54.00	-16.44	1.42 H	254	6.80	30.76
3	3282.00	44.43 PK	74.00	-29.57	1.00 H	281	10.60	33.84
3	3282.00	35.34 AV	54.00	-18.66	1.00 H	281	1.51	33.84
4	4924.00	53.14 PK	74.00	-20.86	1.38 H	22	16.23	36.90
4	4924.00	36.16 AV	54.00	-17.85	1.38 H	22	-0.76	36.90
5	7389.00	54.43 PK	74.00	-19.57	1.50 H	276	12.94	41.49
5	7389.00	40.27 AV	54.00	-13.73	1.50 H	276	-1.22	41.49

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Range Expander	Model	WRE54G
CHANNEL	Channel 11	FREQUENCY RANGE	1~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY: Martin Lee			

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.09 PK			1.00 V	93	76.35	30.74
1	*2462.00	99.71 AV			1.00 V	93	68.97	30.74
2	2483.50	56.23 PK	74.00	-17.77	1.00 V	93	25.47	30.76
2	2483.50	48.85 AV	54.00	-5.15	1.00 V	93	18.09	30.76
3	3282.00	46.63 PK	74.00	-27.37	1.47 V	36	12.80	33.84
3	3282.00	39.30 AV	54.00	-14.70	1.47 V	36	5.47	33.84
4	4924.00	52.77 PK	74.00	-21.23	1.00 V	332	15.86	36.90
4	4924.00	47.64 AV	54.00	-6.36	1.00 V	332	10.73	36.90
5	7378.00	53.91 PK	74.00	-20.09	1.00 V	142	12.45	41.46
5	7378.00	40.18 AV	54.00	-13.82	1.00 V	142	-1.28	41.46

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

EUT	Wireless-G Range Expander	MODEL	WRE54G
		TEST MODE	CCK
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	20deg. C, 62%RH, 991hPa
TESTED BY: Ansen Lei			


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	10.82	0.5	PASS
6	2437	10.78	0.5	PASS
11	2462	10.62	0.5	PASS

CH1



Delta 1 [T1]
 Ref Lvl 20 dBm
 Center 2.437 GHz
 Span 20 MHz
 RBW 100 kHz
 VBW 100 kHz
 SWT 5 ms
 RF Att 30 dB
 Unit dBm
 1MA
 1VIEW
 D1 3.28 dBm
 D2 -2.72 dBm
 F1
 F2
 -2.34 dBm
 2.43164930 GHz
 -0.20 dB
 10.78156313 MHz

CH11







EUT	Wireless-G Range Expander	MODEL	WRE54G
		TEST MODE	OFDM
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	20deg. C, 62%RH, 991hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.43	0.5	PASS
6	2437	16.47	0.5	PASS
11	2462	16.43	0.5	PASS


CH1



CH6



CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	C019167	Feb. 01, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

4.4.7 TEST RESULTS

EUT	Wireless-G Range Expander	MODEL	WRE54G
		TEST MODE	CCK
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	20deg. C, 62%RH, 991hPa
TESTED BY: Ansne Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.34	30	PASS
6	2437	16.71	30	PASS
11	2462	16.36	30	PASS

EUT	Wireless-G Range Expander	MODEL	WRE54G
		TEST MODE	OFDM
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	20deg. C, 62%RH, 991hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	15.29	30	PASS
6	2437	15.42	30	PASS
11	2462	15.31	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6




4.5.7 TEST RESULTS


EUT	Wireless-G Range Expander	MODEL	WRE54G
		TEST MODE	CCK
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	20deg. C, 62%RH, 991hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-9.22	8	PASS
6	2437	-9.19	8	PASS
11	2462	-9.22	8	PASS


CH1



CH6



CH11







EUT	Wireless-G Range Expander	MODEL	WRE54G
		TEST MODE	OFDM
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	20deg. C, 62%RH, 991hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-14.56	8	PASS
6	2437	-14.86	8	PASS
11	2462	-14.87	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz and 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation



4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS (FOR CCK)


The spectrum plots are attached on the following 4 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).


NOTE 1:


The band edge emission plot on the following 1-2 pages shows 55.16dB delta between carrier maximum power and local maximum emission in restrict band (2.3892GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 103.03dBuV/m, so the maximum field strength in restrict band is $103.03 - 55.16 = 47.87$ dBuV/m which is under 54dBuV/m limit.


NOTE 2:

The band edge emission plot on the following 3-4 pages shows 51.73dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 102.41dBuV/m, so the maximum field strength in restrict band is $102.41 - 51.73 = 50.68$ dBuV/m which is under 54dBuV/m limit.











4.6.7 TEST RESULTS (FOR OFDM)


The spectrum plots are attached on the following 4 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).


NOTE 1:


The band edge emission plot on the following 1-2 pages shows 49.43dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 98.03dBuV/m, so the maximum field strength in restrict band is $98.03 - 49.43 = 48.60$ dBuV/m which is under 54dBuV/m limit.


NOTE 2:

The band edge emission plot on the following 3-4 pages shows 49.43dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 99.71dBuV/m, so the maximum field strength in restrict band is $99.71 - 49.43 = 50.28$ dBuV/m which is under 54dBuV/m limit.











4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna type used in this product is Dipole Antenna with UFL antenna connector. The maximum Gain of this antenna is only 2.0dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Linko RF & Telecom Lab.

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.