

Appendix G: Specifications

Model	WRK54G
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.11g, IEEE 802.11b
Channels	11 Channels (US, Canada) 13 Channels (Europe) 14 Channels (Japan)
Ports/Buttons	Internet: One 10/100 RJ-45 Port LAN: Four 10/100 RJ-45 Switched Ports One Power Port One Reset Button
Cabling Type	Ethernet Network Cable
LEDs	Power, DMZ, WLAN, Ethernet (1-4), Internet
RF Power Output	20 dBm
UPnP able/cert	Able
Security Features	NAT Firewall, Internet Policy
Wireless Security	Wi-Fi Protected Access™ (WPA), WEP, Wireless MAC Filtering
Dimensions (W x H x D)	7.31" x 1.88" x 6.06" (186 mm x 48 mm x 154 mm)
Unit Weight	12 oz. (0.34 kg)
Power	External, 12V DC, 1.0A

Wireless-G Broadband Router

Certifications	FCC
Operating Temp.	0°C to 40°C (32°F to 104°F)
Storage Temp.	-20°C to 70°C (-4°F to 158°F)
Operating Humidity	10% to 85%, Non-Condensing
Storage Humidity	5% to 90%, Non-Condensing