



APPENDIX I

RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	Wireless-N Gigabit Router with Storage Link
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Max. output power	IEEE 802.11b mode: 17.82 dBm (60.58 mW) IEEE 802.11g mode: 18.86 dBm (76.83 mW) draft 802.11n Standard-20 MHz Channel mode: 19.39 dBm (86.93 mW) draft 802.11n Wide-40 MHz Channel mode: 17.06 dBm (50.82 mW)
Antenna gain (Max)	MIMO Mode: Antenna-Left Gain: 2.6 dBi for TX / RX (including cable loss) (Numeric gain: 1.82) Antenna-Right Gain: 2.3 dBi for TX / RX (including cable loss) (Numeric gain: 1.7) CDD Mode: Antenna-Left Gain: 2.6 dBi + 10 log (2) = 5.6 dBi (Numeric gain: 3.63) Antenna-Right Gain: 2.3 dBi + 10 log (2) = 5.3 dBi (Numeric gain: 3.38)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Remark:

1. The maximum output power is 19.39dBm (86.93 mW) at 2412MHz (with 3.63 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

TEST RESULTS

No non-compliance noted.

**Calculation**

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



IEEE 802.11b mode:

EUT output power = 60.58mW

Numeric Antenna gain = 3.63

→ Power density = $0.0438 \text{ mW} / \text{cm}^2$

IEEE 802.11g mode:

EUT output power = 76.83 mW

Numeric Antenna gain = 3.63

→ Power density = $0.0555 \text{ mW} / \text{cm}^2$

draft 802.11n Standard-20 MHz Channel mode:

EUT output power = 86.93mW

Numeric Antenna gain = 1.82

→ Power density = $0.0314 \text{ mW} / \text{cm}^2$

draft 802.11n Wide-40 MHz Channel mode:

EUT output power = 50.82mW

Numeric Antenna gain = 1.82

→ Power density = $0.0314 \text{ mW} / \text{cm}^2$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.)