



Exhibit: RF Exposure – FCC/ISED

FCC/ISED RF exposure evaluation of the
System in accordance with FCC 1.1310 & RSS-102

COMMERCIAL-IN-CONFIDENCE

FCC ID: Q8SRFIDENC1

IC: 4652A-RFIDENC1

Report File #: 7169014800C-000

Client	Dormakaba	
Product	Kiosk Secure RFID Encoder	
Standard(s)	FCC 1.1310 & RSS-102	

RF Exposure – ISED

The EUT contains an several types of transmitters as depicted in the table below.

Radiofrequency Radiation Exposure Evaluation: Mobile Devices

The power density can be calculate using the formula:

$$P_d = (P_{out} * G) / (4 * \pi * R^2)$$

where,

f = frequency in MHz

P_d = Power density in mW/cm²

P_{out} = Conducted output power to antenna in mW

G = Numeric Antenna Gain

π = 3.1416

R = uncontrolled distance of 20 cm as per normal operation.

Client	Dormakaba	 Canada
Product	Kiosk Secure RFID Encoder	
Standard(s)	FCC 1.1310 & RSS-102	

MPE Calculation (RFID):

<u>Prediction of MPE limit at a given distance</u>	
Equation from page 18 of OET Bulletin 65, Edition 97-01	
$S = \frac{PG}{4\pi R^2}$	
where:	S = power density P = power input to the antenna G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna
Maximum peak output power at antenna input terminal:	-30.40 (dBm)
Maximum peak output power at antenna input terminal:	0.000912011 (mW)
Number of Ports	1
Antenna gain(typical):	0
Antenna gain(total):	0 (dBi)
Maximum antenna gain:	1 (numeric)
Time Averaging:	100 (%)
Prediction distance:	20 (cm)
Prediction frequency:	13.56 (MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	0.978933354 (mW/cm²)
Power density at prediction frequency:	0.000000 (mW/cm²)
Margin of compliance:	-67.3 (dB)
This equates to	1.81439E-06 W/m²
RSS-102 Issue 5 limit	0.155568538 W/m²
FCC Percentage of limit	0.00002%
RSS-102 Percentage of limit	0.00117%
Note: This device does not exceed the 60 / f (GHz) in mW limit as per FCC KDB 447498 2(a)(i), so it is allowable to be used in portable exposure conditions with no restrictions on host platforms	

Note: The EIRP value was used based on the field strength reading determined at 3 meters and using a factor of 95.2.