

TEST REPORT

Applicant Name: NINGBO BAIHUANG ELECTRIC APPLIANCES CO., LTD.
Address: NO. 180, YANSHAN RD, HUXIMEN, HENGHE TOWN, CIXI,
NINGBO, China
Report Number: 2601T13683E-RF-00
FCC ID: Q92-BH-18C6

Test Standard (s)

FCC PART 15.231

Sample Description

Product Type: Remote Control Transmitter
Model No.: BH-18C6
Multiple Model(s) No.: BH-18C-6
Trade Mark: N/A
Date Received: 2026/06/04
Issue Date: 2026/07/31

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Wills Yu

Wills Yu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
SPECIAL ACCESSORIES	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC §1.1307 (B) & §2.1093 - RF EXPOSURE	9
APPLICABLE STANDARD	9
TEST RESULT:	9
FCC §15.203 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.205, §15.209, §15.231 (B) - RADIATED EMISSIONS	11
APPLICABLE STANDARD	11
EUT SETUP	11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	13
TEST PROCEDURE.....	13
FACTOR & OVER LIMIT/MARGIN CALCULATION	14
TEST DATA.....	14
FCC §15.231(A) (1) - DEACTIVATION TESTING	24
APPLICABLE STANDARD	24
TEST PROCEDURE.....	24
TEST DATA.....	24
FCC §15.231(C) - 20 DB EMISSION BANDWIDTH TESTING	26
APPLICABLE STANDARD	26
TEST PROCEDURE.....	26
TEST DATA.....	27
EUT PHOTOGRAPHS	29
TEST SETUP PHOTOGRAPHS	30

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2601T13683E-RF-00	Original Report	2026/07/31

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Remote Control Transmitter
Tested Model	BH-18C6
Multiple Model(s)	BH-18C-6
Frequency Range	433.92MHz
E-field strength@ Peak	82.29dBuV/m@3m
Modulation Technique	ASK
Voltage Range	DC 12V from battery
Sample number	3N1X-2 (RF Conducted Test) 3N1X-1 (RF Radiated Test) (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A
Note: The Multiple models are electrically identical with the test model except for model name and sales channel. Please refer to the declaration letter [#] for more detail, which was provided by manufacturer.	

Objective

All the test measurements were performed according to the measurement procedure described in ANSI C63.10-2020.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209, 15.35(c) and 15.231 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		52.29kHz(k=1.96, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.46dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.72dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.66dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Horizontal)	5.10dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Vertical)	6.28dB(k=2, 95% level of confidence)
	1GHz - 6GHz	6.18dB(k=2, 95% level of confidence)
	6GHz - 18GHz	6.62dB(k=2, 95% level of confidence)
	18GHz - 40GHz	6.66dB(k=2, 95% level of confidence)
Temperature		$\pm 0.4^{\circ}\text{C}$
Humidity		$\pm 2\%$
Supply voltages		DC $\pm 0.4\%$; AC $\pm 1\%$

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, test firm registration No.: 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing by manufacturer.

Special Accessories

No special accessories was used

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 1.1307 (b) & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	Conducted Emissions	Not Applicable
§15.205, §15.209, §15.231(b)	Radiated Emissions	Compliant
§15.231 (c)	20dB Emission Bandwidth	Compliant
§15.231 (a) (1)	Deactivation	Compliant

Not Applicable: The EUT is powered by battery only.

Note: The EUT have 6 keys, pre-scan all keys, the '1 on' key (detail refer EUT photo) has the maximum fundamental level, so it's the worst case which select to test.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2025/09/01	2026/08/31
Sonoma instrument	Pre-amplifier	310 N	186238	2025/09/08	2026/09/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Chamber A Cable	Cable A1	Cable A1	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A2	Cable A2	2025/09/08	2026/09/07
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Chamber A Cable	Cable A3	Cable A3	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A4	Cable A4	2025/09/08	2026/09/07
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
TDK	Chamber	Chamber A	2#	2023/07/12	2026/07/11
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2025/09/01	2026/08/31
A.H.System	Preamplifier	PAM-0118P	489	2025/09/08	2026/09/07
Schwarzbeck	Horn Antenna	BBHA9120D (1201)	1143	2023/07/26	2026/07/25
Unknown	Chamber B Cable	Cable B1	Cable B1	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B2	Cable B2	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B3	Cable B3	2025/09/08	2026/09/07
JD	Filter Switch Unit	DT7220FSU	DS79906	2025/08/12	2026/08/11
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2025/08/12	2026/08/11
Audix	EMI Test software	E3	191218 V9(c)	NCR	NCR
TDK	Chamber	Chamber B	1#	2023/07/14	2026/07/13
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV40	101942	2025/09/01	2026/08/31
Unknown	10dB Attenuator	Unknown	F-03-EM224	2026/06/24	2027/06/23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (b) & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.2 – 1-mW test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

Test Result:

For worst case:

Mode	Frequency (MHz)	Maximum E-Field (dBuV/m@3m)	Maximum EIRP		1-mW Test Exemption
			(dBm)	(mW)	
SRD	433.92	82.29	-12.91	0.051	Yes

Note: EIRP = E-Field – 95.2 @3m

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has a PCB antenna arrangement which was permanently attached. Fulfill the requirement of this section. Please refer to EUT photos.

Result: Compliant.

FCC §15.205, §15.209, §15.231 (b) - RADIATED EMISSIONS

Applicable Standard

FCC §15.205, §15.209, §15.231 (b)

According to FCC §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:


Fundamental frequency (MHz)	Field Strength of Fundamental (Microvolts /meter)	Field Strength of spurious emissions (Microvolts /meter)
40.66-40.70	2250	225
70-130	1250	125
130-174	1250 to 3750**	125 to 375**
174-260	3750	375
260-470	3750 to 12500**	375 to 1250**
Above 470	12500	1250



*Linear interpolations.

The above field strength limits are specified at a distance of 3-meters the tighter limits apply at the band edges.

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:**Above 1 GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15 § 15.209, 15.205 and 15.231.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	PK
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	PK
30 MHz – 1000 MHz	Other Emissions				
	/	/	120 kHz	QP	QP
	120 kHz	500 kHz	/	PK	PK
	Fundamental & Harmonics				
	1MHz	3 MHz	/	PK	PK
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)				
Above 1 GHz	Other Emissions				
	1MHz	3 MHz	/	PK	PK
	1MHz	≥10 Hz	/	PK	Average
	Harmonics				
	1MHz	3 MHz	/	PK	PK
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)				

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N1*L1+N2*L2+...Nn-1*Ln-1+Nn*Ln$,

Where N1 is number of type 1 pulses, L1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level / Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23.1~25.3 °C
Relative Humidity:	51~55 %
ATM Pressure:	99.8~101.6 kPa


The testing was performed by Alex Yan on 2026-06-27 for below 1GHz, Hugh Li on 2026-07-03 for above 1GHz and Ethan Bu on 2026-07-11 for duty cycle.

Test mode: Transmitting (Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

9 kHz-30MHz:


Note: When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.

Parallel (worst case)



Site : Chamber A
Condition : 3m
Project Number : 2601T13683E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.011	32.04	25.01	57.05	126.51	-69.46	Peak
2	0.026	29.33	22.81	52.14	119.42	-67.28	Peak
3	0.068	24.59	21.46	46.05	110.94	-64.89	Peak
4	0.085	23.06	20.98	44.04	109.03	-64.99	Peak
5	0.097	22.19	20.22	42.41	107.85	-65.44	Peak
6	0.143	19.44	20.29	39.73	104.47	-64.74	Peak




Site : Chamber A
 Condition : 3m
 Project Number : 2601T13683E-RF
 Test Mode : Transmitting
 Detector: Peak RBW/VBW: 10/30kHz
 Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.163	18.25	35.14	53.39	103.33	-49.94	Peak
2	0.550	5.78	35.21	40.99	72.77	-31.78	Peak
3	0.581	5.40	34.41	39.81	72.29	-32.48	Peak
4	0.795	2.76	34.64	37.40	69.50	-32.10	Peak
5	1.380	0.14	31.87	32.01	64.61	-32.60	Peak
6	1.551	-0.34	32.01	31.67	63.58	-31.91	Peak

30MHz – 1 GHz:


Note: When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.

Horizontal

Site : Chamber A
Condition : 3m Horizontal
Project Number : 2601T13683E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 120/500kHz
Tester : Alex Yan

	Freq Factor		Read	Limit	Over	Remark
	Level	Level	Line	Limit	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	31.098	-6.31	28.94	22.63	40.00	-17.37 Peak
2	122.834	-11.16	27.79	16.63	43.50	-26.87 Peak
3	612.333	-4.72	28.93	24.21	46.00	-21.79 Peak
4	716.996	-3.29	28.83	25.54	46.00	-20.46 Peak
5	934.727	-0.48	27.80	27.32	46.00	-18.68 Peak
6	977.037	0.11	27.27	27.38	54.00	-26.62 Peak

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2601T13683E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 120/500kHz
Tester : Alex Yan

	Freq	Factor	Read Level	Limit Level	Over Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.238	-5.87	28.75	22.88	40.00	-17.12	Peak
2	124.460	-11.13	27.79	16.66	43.50	-26.84	Peak
3	595.394	-5.17	29.19	24.02	46.00	-21.98	Peak
4	676.393	-3.29	28.65	25.36	46.00	-20.64	Peak
5	789.234	-2.19	28.60	26.41	46.00	-19.59	Peak
6	929.823	-0.50	27.92	27.42	46.00	-18.58	Peak

Field Strength of Peak								
Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
	Reading (dBμV)	Detector (PK/QP/AV)						
433.92	90.05	PK	H	-7.76	82.29	100.83	-18.54	Fundamental
433.92	77.80	PK	V	-7.76	70.04	100.83	-30.79	Fundamental
867.84	54.63	PK	H	-1.62	53.01	80.83	-27.82	Harmonic
867.84	45.01	PK	V	-1.62	43.39	80.83	-37.44	Harmonic

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

For harmonic, the test result of peak was less than the limit of average, so just peak values were recorded.

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m dBμV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.231		
					Limit (dBμV/m)	Margin (dB)	Comment
433.92	82.29	H	-9.22	73.07	80.83	-7.76	Fundamental
433.92	70.04	V	-9.22	60.82	80.83	-20.01	Fundamental

Note:

Corrected Amplitude = Peak level+ Duty Cycle Corrected Factor

Margin = Corrected Amplitude - Limit

Duty cycle (worst case):

Tp = 22.933ms

Ton1= 0.515ms*11= 5.665ms

Ton2= 0.162ms*14= 2.268ms


Ton= Ton1+ Ton2=7.933ms

Duty cycle = Ton/Tp = 7.933/22.933*100% = 34.59%

Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg(0.3459) = -9.22


Duty Cycle

Tp




ProjectNo.:2601T13683E-RF Tester:Ethan Bu
Date: 11.JUL.2026 17:14:47

The Number of Ton1
and Ton2 pulses




ProjectNo.:2601T13683E-RF Tester:Ethan Bu
Date: 11.JUL.2026 17:15:35

Ton1



ProjectNo.:2601T13683E-RF Tester:Ethan Bu
Date: 11.JUL.2026 17:16:37


Ton2



ProjectNo.:2601T13683E-RF Tester:Ethan Bu
Date: 11.JUL.2026 17:17:23

1 GHz - 5 GHz:


Note: The test result of peak was less than the limit of average, so just peak values were recorded.

Horizontal

Condition : Horizontal
Project No. : 2601T13683E-RF
Tester : Hugh Li
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 433.92MHz

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1301.760	-14.44	57.00	42.56	74.00	-31.44	Peak
2	1735.680	-13.97	52.85	38.88	80.83	-41.95	Peak
3	2169.600	-11.28	53.56	42.28	80.83	-38.55	Peak
4	2603.520	-10.74	52.88	42.14	80.83	-38.69	Peak

Vertical



Condition : Vertical
Project No. : 2601T13683E-RF
Tester : Hugh Li
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 433.92MHz

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1301.760	-14.44	57.75	43.31	74.00	-30.69	Peak
2	1735.680	-13.97	50.89	36.92	80.83	-43.91	Peak
3	2169.600	-11.28	51.89	40.61	80.83	-40.22	Peak
4	2603.520	-10.74	54.50	43.76	80.83	-37.07	Peak


FCC §15.231(a) (1) - DEACTIVATION TESTING

Applicable Standard

Per FCC §15.231(a) (1), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Test Procedure

1. The EUT is setting to the transmit mode, the waveform was received by the test antenna which was connected to the spectrum analyzer.
2. Set center frequency of spectrum analyzer=operating frequency.
3. Set the spectrum analyzer as RBW=1MHz/ VBW=3MHz/ Span=0Hz.
4. Repeat above procedures until all frequency measured was complete.



Test Data


Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	53 %
ATM Pressure:	101.3 kPa

The testing was performed by Ethan Bu on 2026-07-11.

Test mode: Transmitting

Test Result: Compliant. This product will cease transmission within 5 seconds after activation. Please refer to following plots.



ProjectNo.:2601T13683E-RF Tester:Ethan Bu
Date: 11.JUL.,2026 09:59:30

FCC §15.231(c) - 20 dB EMISSION BANDWIDTH TESTING

Applicable Standard

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.


Test Procedure

Test Method: ANSI C63.10-2020 Clause 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max-hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The dBc bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The dBc bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Test Data

Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	53 %
ATM Pressure:	101.3 kPa


The testing was performed by Ethan Bu on 2026-07-04.

Test Mode: Transmitting

Please refer to following table and plots.

Channel Frequency (MHz)	20dB Emission Bandwidth (kHz)	Limit (kHz)
433.92	16.44	1085

20 dB Emission Bandwidth



ProjectNo.:2601T13683E-RF Tester:Ethan Ba
Date: 4.JUL.2026 10:54:56

EUT PHOTOGRAPHS

Please refer to the attachment 2601T13683E-RF-EXP External photo and 2601T13683E-RF-INP Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2601T13683E-RF-TSP Test Setup photo.

******* END OF REPORT *******