MEASUREMENT REPORT

FCC PART 15.407 WLAN 802.11a/n/ac/ax

FCC ID:	Q9DAPEX057457
APPLICANT:	Hewlett Packard Enterprise Company
Application Type:	Certification
Product:	ACCESS POINT
Model No.:	APEX0574, APEX0575, APEX0577
Brand Name:	aruba a Hewlett Packard Enterprise company, Hewlett Packard Enterprise
FCC Classification:	Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s):	Part15 Subpart E (Section 15.407)
Test Procedure(s):	ANSI C63.10-2013, KDB 662911 D01v02r01
Test Date:	December 25, 2019 ~ March 31, 2020

Reviewed By: (Paddy Chen)

Approved By: (Chenz Ker)

Testing Laboratory 3261

The test results relate only to the samples tested.
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.
The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2003TW0002-U4	Rev. 01	Initial report	04-20-2020	Valid

CONTENTS

Description Page

General Information **6**

1. INTRODUCTION **7**

1.1. Scope 7
1.2. MRT Test Location 7

2. PRODUCT INFORMATION **8**

2.1. Equipment Description 8
2.2. Product Specification Subjective to this Report 8
2.3. Working Frequencies for this report 9
2.4. Description of Available Antennas 10
2.5. Description of Antenna RF Port 12
2.6. Test Mode 13
2.7. Description of Test Software 13
2.8. Duty Cycle 14
2.9. EMI Suppression Device(s)/Modifications 16
2.10. Labeling Requirements 16

3. DESCRIPTION OF TEST **17**

3.1. Measurement Procedure 17
3.2. AC Line Conducted Emissions 17
3.3. Radiated Emissions 18

4. ANTENNA REQUIREMENTS **19**

5. TEST EQUIPMENT CALIBRATION DATE **20**

6. MEASUREMENT UNCERTAINTY **21**

7. TEST RESULT **22**

7.1. Summary 22
7.2. 26dB Bandwidth Measurement 23
7.2.1. Test Limit 23
7.2.2. Test Procedure used 23
7.2.3. Test Setting 23
7.2.4. Test Setup 23
7.2.5. Test Result 24
7.3. 6dB Bandwidth Measurement 39
7.3.1. Test Limit 39
7.3.2. Test Procedure used 39

7.3.3. Test Setting 39
7.3.4. Test Setup 39
7.3.5. Test Result 40
7.4. Output Power Measurement 45
7.4.1. Test Limit 45
7.4.2. Test Procedure Used 45
7.4.3. Test Setting 45
7.4.4. Test Setup 46
7.4.5. Test Result 47
7.5. Transmit Power Control 48
7.5.1. Test Limit 48
7.5.2. Test Procedure Used 48
7.5.3. Test Setting 48
7.5.4. Test Setup 48
7.5.5. Test Result 48
7.6. Power Spectral Density Measurement 49
7.6.1. Test Limit 49
7.6.2. Test Procedure Used 49
7.6.3. Test Setting 49
7.6.4. Test Setup 50
7.6.5. Test Result 51
7.7. Frequency Stability Measurement 52
7.7.1. Test Limit 52
7.7.2. Test Procedure Used 52
7.7.3. Test Setup 53
7.7.4. Test Result 54
7.8. Radiated Spurious Emission Measurement 55
7.8.1. Test Limit 55
7.8.2. Test Procedure Used 55
7.8.3. Test Setting 55
7.8.4. Test Setup 57
7.8.5. Test Result 58
7.9. Radiated Restricted Band Edge Measurement 59
7.9.1. Test Limit 59
7.9.2. Test Procedure Used 60
7.9.3. Test Setting 60
7.9.4. Test Setup 61
7.9.5. Test Result 62
7.10. AC Conducted Emissions Measurement 63

7.10.1. Test Limit 63
7.10.2. Test Procedure 63
7.10.3. Test Setup 64
7.10.4. Test Result..... 65

8. CONCLUSION..... 67

Appendix A - Test Setup Photograph 68

Appendix B - EUT Photograph..... 69

General Information

Applicant:	Hewlett Packard Enterprise Company
Applicant Address:	3333 Scott Blvd, Santa Clara, CA 94089, USA
Manufacturer:	Hewlett Packard Enterprise Company
Manufacturer Address:	3333 Scott Blvd, Santa Clara, CA 94089, USA
Test Site:	MRT Technology (Taiwan) Co., Ltd
Test Site Address:	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
Test Device Serial No.:	APEX0574 Radiated sample S/N: DE201600CC, Conducted sample S/N: DE29A00066
	APEX0575 Radiated sample S/N: DE29A0078, Radiated sample S/N: DE29A0078
	APEX0577 Radiated sample S/N: DE29A00079, Conducted sample S/N: DE29A0002D

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Fuxing Rd., Taoyuan, Taiwan (R.O.C)

- **MRT facility is a FCC registered (Reg. No. 153292) test facility with the site description report on file and is designated by the FCC as an Accredited Test Film.**
- **MRT facility is an IC registered (MRT Reg. No. 21723-1) test laboratory with the site description on file at Industry Canada.**
- **MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (TAF) under the American Association for Laboratory Accreditation Program (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC, Industry Taiwan, EU and TELEC Rules.**

1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices includingintentional and/or unintentional radiators for compliance with the technical rules and regulations of the FederalCommunications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	ACCESS POINT
Model No.	APEX0574, APEX0575, APEX0577
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Bluetooth Specification	v4.2 single mode
Zigbee Specification	802.15.4
Software Version	F.1.01
Operating Temperature	-40 ~ 65 °C
Power Type	POE input
Operating Environment	Outdoor Use

Note 1: The difference between three models is that EUT use different antenna and appearance, other hardware and software are the same. Each model has its own power parameter value.

Note 2: The applicant provided one PoE adapter (Manufacturer: MICROSEMI & Model: 9001GO) for approval testing, it is not for sale.

2.2. Product Specification Subjective to this Report

Frequency Range:	For 802.11a/n-HT20/ac-VHT20/ax-HE20: 5180~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40/ax-HE40: 5190~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80/ax-HE80: 5210MHz, 5290MHz, 5530MHz, 5610MHz, 5690MHz, 5775MHz For 802.11ac-VHT160/ax-HE160: 5250MHz, 5570MHz
Type of Modulation:	802.11a/n/ac: OFDM 802.11ax: OFDMA
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 600Mbps 802.11ac: up to 1733.3Mbps 802.11ax: up to 4804Mbps

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11a/n-HT20/ac-VHT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550 MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80/ax-HE80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

802.11ac-VHT160/ax-HE160

Channel	Frequency	Channel	Frequency	Channel	Frequency
50	5250 MHz	114	5570 MHz	--	--

2.4. Description of Available Antennas

Model No.: APEX0574

Antenna No.	Antenna Type	Frequency Band (GHz)	Model No.	Max Peak Gain (dBi)	30 Degree Ant Gain (dBi)	BF Dir Gain (dBi)	CDD Dir Gain (dBi)	
							For Power	For PSD
Wi-Fi External Antenna List (2.4GHz 2*2 MIMO, 5GHz 4*4 MIMO)								
1 (Note 3)	Omni	2.4	ANT-2x2-2005	5.0	N/A	5.0	5.0	5.0
2 (Note 3)	Omni	5	ANT-2x2-5005	5.0	0	8.01	5.0	8.01
3 (Note 3)	Omni	5	ANT-2x2-5010	10.0	0	13.01	10.0	13.01
4 (Note 3)	Directional	2.4	ANT-2x2-2314	14.0	N/A	14.0	14.0	14.0
5 (Note 3)	Directional	5	ANT-3x3-5712	11.5	1.5	14.51	11.5	14.51
6 (Note 3)	Directional	5	ANT-4x4-5314	14.0	6.0	17.01	14.0	17.01
7 (Note 3)	Directional	5	MT-484052/NVH	16.0	3.0	19.01	16.0	19.01
8 (Note 3)	Directional	2.4	ANT-3x3-D608	7.5	N/A	10.51	7.5	10.51
		5		7.5	4.5	10.51	7.5	10.51
9 (Note 3)	Directional	2.4	ANT-3x3-D100	5.0	N/A	8.01	5.0	8.01
		5		5.0	4.0	8.01	5.0	8.01
Bluetooth Internal Antenna								
PCB		2.4		4.2				

Model No.: APEX0577

Antenna Type	Frequency Band (GHz)	Max Peak Gain (dBi)	30 Degree Ant Gain (dBi)	BF Dir Gain (dBi)	CDD Dir Gain (dBi)	
					For Power	For PSD
Wi-Fi Internal Antenna List (2.4GHz 2*2 MIMO, 5GHz 4*4 MIMO)						
Directional (Note 3)	2.4	6.8	N/A	6.80	6.8	6.80
Directional (Note 3)	5	5.6	5.6	8.60	5.6	8.60
Bluetooth Internal Antenna						
PCB	2.4	8.4				

Model No.: APEX0575

Antenna Type	Frequency Band (GHz)	Max Peak Gain (dBi)	30 Degree Ant Gain (dBi)	BF Dir Gain (dBi)	CDD Dir Gain (dBi)	
					For Power	For PSD
Wi-Fi Internal Antenna List (2.4GHz 2*2 MIMO, 5GHz 4*4 MIMO)						
Omni (Note 3)	2.4	3.4	N/A	3.4	3.4	3.4
Omni (Note 3)	5	5.0	-2.7	8.0	5.0	8.0
Bluetooth Internal Antenna						
PCB	2.4	6.0				

Note:

1. The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.
   For CDD transmissions, directional gain is calculated as follows, N_{ANT} = 2 or 4, N_{SS} = 1.
   If all antennas have the same gain, G_{ANT}, Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.
   - For power spectral density (PSD) measurements on all devices,
     Array Gain = 10 log (N_{ANT}/ N_{SS}) dB = 3.01;
   - For power measurements on IEEE 802.11 devices,
     Array Gain = 0 dB for $N_{ANT} \leq 4$;

   Abbreviation “Dir” means directional.
2. The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax, not include 802.11a/b/g.
   Directional gain = G_{ANT} + BF Gain, BF Gain was declared by the applicant.
3. These antennas have Cross-Polarized design, only each two outputs driving a pair of antennas that are cross-polarized, the detail see the antenna specification.
4. For APEX0574, low gain antenna (ANT-2x2-2005 & ANT-2x2-5005) was selected to perform all RF testing that can got maximum power setting, high gain different type antenna (ANT-2x2-5010 & MT-484052/NVH) was selected to perform radiated spurious emission and band edge testing. High gain antenna power setting will be reduced according to difference value of antenna gain declared by applicant.
5. For APEX0577 and APEX0575, its directional gain was declared by the applicant, the detail refers to antenna specification.

2.5. Description of Antenna RF Port

Antenna RF Port						
--	2.4GHz RF Port		5GHz RF Port			
Software Control Port	Ant 0	Ant 1	Ant 0	Ant 1	Ant 2	Ant 3
APEX0574						
						
APEX0577			APEX0575			

2.6. Test Mode

Test Mode	Mode 1: Transmit by 802.11a (6Mbps)
	Mode 2: Transmit by 802.11ac-VHT20 (MCS0)
	Mode 3: Transmit by 802.11ac-VHT40 (MCS0)
	Mode 4: Transmit by 802.11ac-VHT80 (MCS0)
	Mode 5: Transmit by 802.11ac-VHT160 (MCS0)
	Mode 6: Transmit by 802.11ax-HE20 (MCS0)
	Mode 7: Transmit by 802.11ax-HE40 (MCS0)
	Mode 8: Transmit by 802.11ax-HE80 (MCS0)
	Mode 9: Transmit by 802.11ax-HE160 (MCS0)

Note: 802.11n and 802.11ac have same modulation type, using same power parameter, after the assessment, we only showed worst case 802.11ac test data in this report.

2.7. Description of Test Software

The test utility software used during testing was “accessMTool”, and the version was “v3.0.0.7”. Detail power setting refer to operation description.

2.8. Duty Cycle

5GHz (NII) operation is possible in 20MHz, 40MHz and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle
802.11a	94.93%
802.11ac-VHT20	98.47%
802.11ac-VHT40	96.97%
802.11ac-VHT80	93.87%
802.11ac-VHT160	89.49%
802.11ax-HE20	97.76%
802.11ax-HE40	95.99%
802.11ax-HE80	92.38%
802.11ax-HE160	88.15%

Duty Cycle (T = Transmission Duration)

802.11a (T = 2.060ms)



802.11ac-VHT20 (T = 1.930ms)



802.11ac-VHT40 (T = 950.0us)



802.11ac-VHT80 (T = 459.0us)



802.11ac-VHT160 (T = 252.0us)



802.11ax-HE20 (T = 1.486ms)



802.11ax-HE40 (T = 771.3us)



802.11ax-HE80 (T = 400us)



802.11ax-HE160 (T = 232us)



2.9. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.10. Labeling Requirements

<u>Per 2.1074 & 15.19; Docket 95-19</u>

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphletsupplied to the user and be readily visible to the purchaser at the time of purchase. However, when the deviceis so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label andlabel location.

3. DESCRIPTION OF TEST

3.1. Measurement Procedure

The measurement procedure described in the document titled “American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices” (ANSI C63.10-2013) was used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remotecontrolled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated tomaximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by theresponsible party can be used with the device. The use of a permanently attached antenna or of an antennathat uses a unique coupling to the intentional radiator shall be considered sufficient to comply with theprovisions of this section."

Conclusion:

The product is defined as the professional installation of equipment by the manufacturer, there is no necessary to comply with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV 216	MRTTWA00019	1 year	2021/03/26
Two-Line V-Network	R&S	ENV 216	MRTTWA00020	1 year	2020/04/25
8-Wire ISN (T8)	R&S	ENY81	MRTTWA00018	1 year	2020/04/23
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2020/05/29
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00033	1 year	2020/05/30

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Acitve Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2020/04/29
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2020/06/04
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2020/04/22
Breitband Horn antenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2020/04/23
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2020/04/24
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2020/04/24
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2021/03/24
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/03/25
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2020/10/02
Antenna Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2020/04/22
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00032	1 year	2020/05/30

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2020/04/22
Wideband Radio Communication Taster	R&S	CMW 500	MRTTWA00041	1 year	2021/01/28
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2020/10/02
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2020/07/11
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2021/03/24
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00033	1 year	2020/05/30

Software	Version	Function
e3	9.160520a	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 150kHz~30MHz: 2.53dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 9kHz ~ 1GHz: 4.25dB 1GHz ~ 40GHz: 4.45dB

7. TEST RESULT

7.1. Summary

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(a)	26dB Bandwidth	N/A	Conducted	Pass	Section 7.2
15.407(e)	6dB Bandwidth	≥ 500kHz		Pass	Section 7.3
15.407(a)(1)(i), (2), (3)	Maximum Conducted Output Power	< 1Watt for NII-1 & NII-3 < 250mW for NII-2		Pass	Section 7.4
15.407(h)(1)	Transmit Power Control	< 24 dBm		N/A	Section 7.5
15.407(a)(1)(i), (2), (3), (5)	Peak Power Spectral Density	< 17dBm/MHz for NII-1 < 11dBm/MHz for NII-2 < 30dBm/500kHz for NII-3		Pass	Section 7.6
15.407(g)	Frequency Stability	± 20 ppm		Pass	Section 7.7
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Refer to Section 7.8	Radiated	Pass	Section 7.8 & 7.9
15.205, 15.209 15.407(b)(5), (6), (7)	General Field Strength Limits(Restricted Bands andRadiated Emission Limits)	Emissions in restrictedbands must meet theradiated limits detailed in15.209		Pass	
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.10

Notes:

1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
3) Test Items “26dB Bandwidth” & “6dB Bandwidth” have been assessed MIMO transmission, and showed the worst test data in this report.

7.2. 26dB Bandwidth Measurement

7.2.1.Test Limit

N/A

7.2.2.Test Procedure used

ANSI C63-2013 - Section 12.4.1

7.2.3.Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 26. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. VBW ≥ 3×RBW.
4. Detector = Peak.
5. Trace mode = max hold.

7.2.4.Test Setup



7.2.5.Test Result

Product	ACCESS POINT	Temperature	24°C
Test Engineer	Kevin Ker	Relative Humidity	59%
Test Site	SR2	Test Date	2020/01/09
Model No.	APEX0574	Test Item	Occupied Bandwidth

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0 / Ant 0 + 1 + 2 + 3					
802.11a	6Mbps	36	5180	21.19	16.74
802.11a	6Mbps	44	5220	21.22	16.73
802.11a	6Mbps	48	5240	21.11	16.71
802.11a	6Mbps	52	5260	21.26	16.72
802.11a	6Mbps	60	5300	21.06	16.72
802.11a	6Mbps	64	5320	21.03	16.72
802.11a	6Mbps	100	5500	21.12	16.72
802.11a	6Mbps	120	5600	21.13	16.76
802.11a	6Mbps	140	5700	21.14	16.74
802.11a	6Mbps	144	5720	21.09	16.73
802.11a	6Mbps	149	5745	21.14	16.77
802.11a	6Mbps	157	5785	21.13	16.71
802.11a	6Mbps	165	5825	21.27	16.78
802.11ac-VHT20	MCS0	36	5180	21.35	17.88
802.11ac-VHT20	MCS0	44	5220	21.43	17.88
802.11ac-VHT20	MCS0	48	5240	21.49	17.84
802.11ac-VHT20	MCS0	52	5260	21.31	17.87
802.11ac-VHT20	MCS0	60	5300	21.55	17.84
802.11ac-VHT20	MCS0	64	5320	21.42	17.85
802.11ac-VHT20	MCS0	100	5500	21.37	17.86
802.11ac-VHT20	MCS0	120	5600	21.34	17.87
802.11ac-VHT20	MCS0	140	5700	21.48	17.85
802.11ac-VHT20	MCS0	144	5720	21.41	17.85
802.11ac-VHT20	MCS0	149	5745	21.47	17.90
802.11ac-VHT20	MCS0	157	5785	21.43	17.89
802.11ac-VHT20	MCS0	165	5825	21.27	17.88
802.11ac-VHT40	MCS0	38	5190	39.92	36.34
802.11ac-VHT40	MCS0	46	5230	40.55	36.36

802.11ac-VHT40	MCS0	54	5270	39.98	36.28
802.11ac-VHT40	MCS0	62	5310	39.72	36.33
802.11ac-VHT40	MCS0	102	5510	39.78	36.34
802.11ac-VHT40	MCS0	118	5590	39.93	36.35
802.11ac-VHT40	MCS0	134	5670	40.08	36.30
802.11ac-VHT40	MCS0	142	5710	39.74	36.28
802.11ac-VHT40	MCS0	151	5755	39.94	36.36
802.11ac-VHT40	MCS0	159	5795	41.51	36.32
802.11ac-VHT80	MCS0	42	5210	81.50	75.79
802.11ac-VHT80	MCS0	58	5290	81.69	75.73
802.11ac-VHT80	MCS0	106	5530	81.19	75.76
802.11ac-VHT80	MCS0	122	5610	81.44	75.67
802.11ac-VHT80	MCS0	138	5690	81.73	75.67
802.11ac-VHT80	MCS0	155	5775	81.58	75.69
802.11ac-VHT160	MCS0	50	5250	163.30	154.05
802.11ac-VHT160	MCS0	114	5570	164.40	155.73
802.11ax-HE20	MCS0	36	5180	22.02	19.08
802.11ax-HE20	MCS0	44	5220	21.50	19.09
802.11ax-HE20	MCS0	48	5240	21.26	19.06
802.11ax-HE20	MCS0	52	5260	21.31	19.03
802.11ax-HE20	MCS0	60	5300	21.47	19.03
802.11ax-HE20	MCS0	64	5320	21.42	19.01
802.11ax-HE20	MCS0	100	5500	21.38	19.04
802.11ax-HE20	MCS0	120	5600	21.28	19.02
802.11ax-HE20	MCS0	140	5700	21.25	19.04
802.11ax-HE20	MCS0	144	5720	21.41	19.04
802.11ax-HE20	MCS0	149	5745	22.99	19.04
802.11ax-HE20	MCS0	157	5785	22.69	19.06
802.11ax-HE20	MCS0	165	5825	22.21	19.04
802.11ax-HE40	MCS0	38	5190	39.85	37.60
802.11ax-HE40	MCS0	46	5230	39.65	37.57
802.11ax-HE40	MCS0	54	5270	39.73	37.58
802.11ax-HE40	MCS0	62	5310	39.82	37.47
802.11ax-HE40	MCS0	102	5510	39.76	37.58
802.11ax-HE40	MCS0	118	5590	39.63	37.59
802.11ax-HE40	MCS0	134	5670	39.92	37.55
802.11ax-HE40	MCS0	142	5710	39.86	37.53

802.11ax-HE40	MCS0	151	5755	39.84	37.56
802.11ax-HE40	MCS0	159	5795	41.58	37.56
802.11ax-HE80	MCS0	42	5210	82.14	77.29
802.11ax-HE80	MCS0	58	5290	81.40	77.01
802.11ax-HE80	MCS0	106	5530	81.66	77.02
802.11ax-HE80	MCS0	122	5610	81.47	77.03
802.11ax-HE80	MCS0	138	5690	81.60	76.88
802.11ax-HE80	MCS0	155	5775	82.04	76.98
802.11ax-HE160	MCS0	50	5250	164.00	155.12
802.11ax-HE160	MCS0	114	5570	164.90	155.64

802.11a 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3

Channel 36 (5180MHz)



Channel 44 (5220MHz)



Channel 48 (5240MHz)



Channel 52 (5260MHz)

Channel 60 (5300MHz)



Channel 64 (5320MHz)

Channel 100 (5500MHz)



Channel 120 (5600MHz)

802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3

Channel 140 (5700MHz)

Channel 144 (5720MHz)

Channel 149 (5745MHz)



Channel 157 (5785MHz)



Channel 165 (5825MHz)



802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3

Channel 36 (5180MHz)



Channel 44 (5220MHz)



Channel 48 (5240MHz)



Channel 52 (5260MHz)



Channel 60 (5300MHz)



Channel 64 (5320MHz)

Channel 100 (5500MHz)



Channel 120 (5600MHz)



802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3

Channel 140 (5700MHz)

Channel 144 (5720MHz)

Channel 149 (5745MHz)



Channel 157 (5785MHz)



Channel 165 (5825MHz)



802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3

Channel 38 (5190MHz)



Channel 46 (5230MHz)



Channel 54 (5270MHz)



Channel 62 (5310MHz)



Channel 102 (5510MHz)



Channel 118 (5590MHz)



Channel 134 (5670MHz)



Channel 142 (5710MHz)



802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3

Channel 151 (5755MHz)



Channel 159 (5795MHz)



802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3

Channel 42 (5210MHz)



Channel 58 (5290MHz)



Channel 106 (5530MHz)



Channel 122 (5610MHz)



Channel 138 (5690MHz)



Channel 155 (5775MHz)



802.11ac-VHT160 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3	
Channel 50 (5250MHz)	**Channel 114 (5570MHz)**