RF MEASUREMENT REPORT

FCC ID:	Q9DAPIN0725
Applicant:	Hewlett Packard Enterprise Company
Product:	ACCESS POINT
Model No.:	APIN0725
Trademark:	Hewlett Packard Enterprise
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part 15 Subpart C (Section 15.247)
Result:	Complies
Received Date:	2024-12-20
Test Date:	2025-01-04 ~ 2025-02-25

Reviewed By: Jame Yuan

Approved By: Robin Wu

ACCREDITED
TESTING LABORATORY
CERTIFICATE #3628.01

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2412RSU035-U4	V01	Initial Report	2025-04-22	Valid

CONTENTS

Description Page

1. General Information 5

1.1. Applicant 5
1.2. Manufacturer 5
1.3. Testing Facility 5
1.4. Product Information 6
1.5. Radio Specification under Test 6
1.6. Working Frequencies 7
1.7. Antenna Details 7

2. Test Configuration 8

2.1. Test Mode 8
2.2. Test System Connection Diagram 9
2.3. Test Software 9
2.4. Applied Standards 10
2.5. Test Environment Condition 10

3. Antenna Requirements 11

4. Measuring Instrument 12

5. Decision Rules and Measurement Uncertainty 13

5.1. Decision Rules 13
5.2. Measurement Uncertainty 13

6. Test Result 14

6.1. Summary 14
6.2. 6dB Bandwidth Measurement 15
6.2.1. Test Limit 15
6.2.2. Test Procedure 15
6.2.3. Test Setting 15
6.2.4. Test Setup 15
6.2.5. Test Result 15
6.3. Output Power Measurement 16
6.3.1. Test Limit 16
6.3.2. Test Procedure 16
6.3.3. Test Setting 16
6.3.4. Test Setup 16
6.3.5. Test Result 16
6.4. Power Spectral Density Measurement 17
6.4.1. Test Limit 17

6.4.2. Test Procedure 17
6.4.3. Test Setting 17
6.4.4. Test Setup 17
6.4.5. Test Result 18
6.5. Conducted Band Edge and Out-of-Band Emissions Measurement 19
6.5.1. Test Limit 19
6.5.2. Test Procedure 19
6.5.3. Test Settitng 19
6.5.4. Test Setup 20
6.5.5. Test Result 20
6.6. Radiated Spurious Emission Measurement 21
6.6.1. Test Limit 21
6.6.2. Test Procedure 21
6.6.3. Test Setting 21
6.6.4. Test Setup 23
6.6.5. Test Result 24
6.7. Radiated Restricted Band Edge Measurement 25
6.7.1. Test Limit 25
6.7.2. Test Procedure 26
6.7.3. Test Setting 26
6.7.4. Test Setup 27
6.7.5. Test Result 28
6.8. AC Conducted Emissions Measurement 29
6.8.1. Test Limit 29
6.8.2. Test Setup 29
6.8.3. Test Result 29

Appendix A – Test Result 30

A.1 Duty Cycle Test Result 30
A.2 6dB Bandwidth Test Result 32
A.3 Output Power Test Result 38
A.4 Power Spectral Density Test Result 39
A.5 Conducted Band Edge and Out-of-Band Emissions Test Result 46
A.6 Radiated Spurious Emission Test Result 67
A.7 Radiated Restricted Band Edge Test Result 80
A.8 AC Conducted Emissions Test Result 152

Appendix B – Test Setup Photograph 156

Appendix C – EUT Photograph 157

1. General Information

1.1. Applicant

Hewlett Packard Enterprise Company

6280 America Center Drive, San Jose CA 95002, United States

1.2. Manufacturer

Hewlett Packard Enterprise Company

6280 America Center Drive, San Jose CA 95002, United States

1.3. Testing Facility

☒	**Test Site – MRT Suzhou Laboratory**
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China **Laboratory Location (Suzhou - SIP)** 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China **Laboratory Location (Suzhou - Wujiang)** Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People's Republic of China
	Laboratory Accreditations
	A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: ☐R-20025 ☐G-20034 ☐C-20020 ☐T-20020 ☐R-20141 ☐G-20134 ☐C-20103 ☐T-20104
☐	**Test Site – MRT Shenzhen Laboratory**
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
☐	**Test Site – MRT Taiwan Laboratory**
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	ACCESS POINT
Model No.	APIN0725
Serial No.	CNT4MPP016 (Conducted) CNT4MPP00W (Radiated)
Software Version	Broadcom BCA: 17.10 RC369.61
Wi-Fi Specification	802.11a/b/g/n/ac/ax/be
Bluetooth Specification	BLE only
Antenna Information	Refer to Section 1.7
Power Type	PoE Input
Operating Temperature	0 ~ 50 °C
Operating Environment	Indoor Use
Accessory	
PoE Inject	Model: ADH-30CR BB Input: 100-240V ~ 1.0A, 50-60Hz Output: 55.0V, 0.55A 30.25W
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Radio Specification under Test

Frequency Range	802.11b/g/n-HT20/ax-HE20/be-EHT20: 2412 ~ 2462MHz	
Channel Number	802.11b/g/n-HT20/ax-HE20/be-EHT20: 11	
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM 802.11ax/be: OFDMA	
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 144.4Mbps 802.11ax: up to 286.8Mbps 802.11be: up to 344Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11b/g/n-HT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

1.7. Antenna Details

Antenna Type	Frequency Band (MHz)	T_X Paths	Uncorrelated Gain (dBi)
PIFA & Dipole	2400 ~ 2483.5	2	3.81
PIFA & Dipole	5150 ~ 5895	2	4.66
PIFA & Dipole	5925 ~ 7125	2	4.84

Notes:

1. The EUT supports Cyclic Delay Diversity (CDD) mode.
2. The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax/be, not include 802.11a/b/g.
3. For beamforming operation, Aruba OS automatically backs power down based on CDD power.
4. The two antennas are cross-polarized.
5. The detail calculation method of directional gain refers to antenna specification provided by the applicant.

2. Test Configuration

2.1. Test Mode

CDD Mode
Mode 1: Transmit by 802.11b (1Mbps)
Mode 2: Transmit by 802.11g (6Mbps)
Mode 3: Transmit by 802.11n-HT20_N_{SS}=1 (MCS0)
Mode 4: Transmit by 802.11ax-HE20_N_{SS}=1 (MCS0)
Mode 5: Transmit by 802.11be-EHT20_N_{SS}=1 (MCS0)
Notes: 1. The modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. For CDD mode, this device supports 2 N_{SS} and power level is the same of spatial multiplexing. The worst case is N_{SS}=1. 3. For beamforming operation, manufacturer automatically backs power down based on CDD power. Therefore, only the CDD mode was evaluated in this report.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram



No.	Cable Type	Cable Spec.	Length
A	Ethernet Cable	Non-Shielded, Cat 6	>10.0m
B	Ethernet Cable	Non-Shielded, Cat 6	1.2m
No.	Product	Manufacturer	Model No.
1	USB Flash	SanDisk	16G
2	Notebook	DELL	Latitude 5491

2.3. Test Software

The test utility software used during testing was “accessMTool”, and the version was 3.3.0.6.
Final power setting please refer to operational description.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached.**
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Thermohygrometer	testo	608-H1	MRTSUE11330	1 year	2025-06-24	WJ-SR2
Shielding Room	TDK	WJ-SR2	MRTSUE07124	N/A	N/A	WJ-SR2
Signal Analyzer	Keysight	N9020B	MRTSUE07037	1 year	2025-09-03	WJ-SR2
USB Power Sensor	Keysight	U2021XA	MRTSUE07141	1 year	2025-03-23	WJ-SR2
Attenuator	MVE	MVE2213	MRTSUE11086	1 year	2025-06-05	WJ-SR2
Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2025-02-03	WJ-SR2
Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2026-01-20	WJ-SR2
TRILOG Broad Band Antenna	Schwarzbeck	VULB 9163	MRTSUE07097	1 year	2025-04-24	WJ-AC2
Preamplifier	EMCI	EMC118A45SE	MRTSUE07102	1 year	2025-04-11	WJ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE07103	1 year	2025-04-14	WJ-AC2
Horn Antenna	RFSPIN	DRH18-E	MRTSUE07105	1 year	2025-05-12	WJ-AC2
Anechoic Chamber	TDK	WJ-AC2	MRTSUE07117	1 year	2025-05-14	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11315	1 year	2025-06-24	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11332	1 year	2025-06-24	WJ-AC2
Active Loop Antenna	Schwarzbeck	FMZB 1519-60 D	MRTSUE07076	1 year	2025-11-19	WJ-AC2
Broadband Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE07100	1 year	2025-04-24	WJ-AC2
EMI Test Receiver	R&S	ESR3	MRTSUE07112	1 year	2025-04-21	WJ-SR5
Shielding Room	TDK	WJ-SR5	MRTSUE07127	N/A	N/A	WJ-SR5
Thermohygrometer	testo	608-H1	MRTSUE11317	1 year	2025-06-24	WJ-SR5
Two-Line V-Network	R&S	ENV216	MRTSUE07202	1 year	2025-05-26	WJ-SR5

Software	Version	Function
e3	230711	RE & CE
CONTROLLER CO3000	v 1.03.02	RE Antenna & Turntable
BenchVue Power Meter	2018.1	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.02dB 150kHz~30MHz: 2.56dB
Radiated Emission Measurement
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.35dB Coplanar: 9kHz~30MHz: 2.37dB Horizontal: 30MHz~200MHz: 3.46dB 200MHz~1GHz: 3.78dB 1GHz~40GHz: 4.97dB Vertical: 30MHz~200MHz: 4.07dB 200MHz~1GHz: 5.28dB 1GHz~40GHz: 4.78dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.5dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.3dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.5dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.6%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Notes:

1. The analyzer plots shown in this section were captured using a correction table to account for cable and attenuator losses in the system connecting the EUT to the analyzer across relevant frequencies.
2. For radiated emission tests, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 6dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW ≥ 3 × RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize.

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.2.3.2

6.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.

6.4.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.10.5

6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.
8. Sweep time = auto couple.
9. Don’t use sweep triggering. Allow sweep to “free run”.
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add 10 log (1/x), where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

6.5.3. Test Settitng

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW ≥ 3 x RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10Hz

   If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.

802.11b	82 Hz	802.11g	510 Hz	802.11n-HT20	560 Hz
802.11ax-HE20	680 Hz	802.11be-EHT20	680 Hz	--	--

4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to “Voltage” regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.6.4. Test Setup

Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1] 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

6.7.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.

   If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.

802.11b	82 Hz	802.11g	510 Hz	802.11n-HT20	560 Hz
802.11ax-HE20	680 Hz	802.11be-EHT20	680 Hz	--	--

4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement

6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBμV)	AV (dBμV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50
Note 1: The lower limit shall apply at the transition frequencies. Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.		

6.8.2. Test Setup



6.8.3. Test Result

Refer to Appendix A.8.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	WJ-SR2	Test Engineer	Jake Lan
Test Date	2025-01-10		

Test Mode	Duty Cycle
802.11b	94.96%
802.11g	94.90%
802.11n-HT20	94.72%
802.11ax-HE20	97.64%
802.11be-EHT20	97.65%

Duty Cycle (T = Transmission Duration)

802.11b (T = 12.43ms)



802.11g (T = 2.064ms)



802.11n-HT20 (T = 1.921ms)



802.11ax-HE20 (T = 1.492ms)



Duty Cycle (T = Transmission Duration)	
802.11be-EHT20 (T = 1.497ms)	
	

A.2 6dB Bandwidth Test Result

Test Site	WJ-SR2	Test Engineer	Jake Lan
Test Date	2025-01-20		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	1Mbps	01	2412	7.075	≥ 0.5
11b	1Mbps	06	2437	7.070	≥ 0.5
11b	1Mbps	11	2462	7.071	≥ 0.5
11g	6Mbps	01	2412	16.370	≥ 0.5
11g	6Mbps	06	2437	16.350	≥ 0.5
11g	6Mbps	11	2462	16.350	≥ 0.5
11n-HT20	MCS0	01	2412	17.600	≥ 0.5
11n-HT20	MCS0	06	2437	17.570	≥ 0.5
11n-HT20	MCS0	11	2462	17.600	≥ 0.5
11ax-HE20	MCS0	01	2412	18.930	≥ 0.5
11ax-HE20	MCS0	06	2437	18.860	≥ 0.5
11ax-HE20	MCS0	11	2462	18.860	≥ 0.5
11be-EHT20	MCS0	01	2412	18.920	≥ 0.5
11be-EHT20	MCS0	06	2437	18.910	≥ 0.5
11be-EHT20	MCS0	11	2462	18.860	≥ 0.5

802.11b 6dB Bandwidth

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11g 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11ax-HE20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.1be-EHT20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

A.3 Output Power Test Result

Test Site	WJ-SR2	Test Engineer	Jake Lan
Test Date	2025-02-25		

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)		Total Average Power (dBm)	Limit (dBm)
				Ant 0	Ant 1		
11b	1Mbps	01	2412	19.63	19.87	22.76	≤ 30.00
11b	1Mbps	06	2437	19.51	20.43	23.00	≤ 30.00
11b	1Mbps	11	2462	18.96	18.08	21.55	≤ 30.00
11g	6Mbps	01	2412	17.61	17.25	20.44	≤ 30.00
11g	6Mbps	06	2437	18.34	18.37	21.37	≤ 30.00
11g	6Mbps	10	2457	18.68	17.63	21.20	≤ 30.00
11g	6Mbps	11	2462	15.90	15.14	18.55	≤ 30.00
11n-HT20	MCS0	01	2412	17.01	16.68	19.86	≤ 30.00
11n-HT20	MCS0	06	2437	17.91	17.81	20.87	≤ 30.00
11n-HT20	MCS0	10	2457	18.19	17.14	20.71	≤ 30.00
11n-HT20	MCS0	11	2462	15.01	14.30	17.68	≤ 30.00
11ax-HE20	MCS0	01	2412	16.40	15.86	19.15	≤ 30.00
11ax-HE20	MCS0	06	2437	17.74	17.54	20.65	≤ 30.00
11ax-HE20	MCS0	10	2457	16.59	16.14	19.38	≤ 30.00
11ax-HE20	MCS0	11	2462	14.07	13.62	16.86	≤ 30.00
11be-EHT20	MCS0	01	2412	16.47	15.77	19.14	≤ 30.00
11be-EHT20	MCS0	06	2437	18.19	17.82	21.02	≤ 30.00
11be-EHT20	MCS0	10	2457	16.65	15.88	19.29	≤ 30.00
11be-EHT20	MCS0	11	2462	14.62	14.17	17.41	≤ 30.00

Note: Total Average Power (dBm) = $10*\log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)}\}$ (dBm).

A.4 Power Spectral Density Test Result

Test Site	WJ-SR2	Test Engineer	Jake Lan
Test Date	2025-01-11		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	PSD (dBm / 10kHz)		Duty Cycle (%)	10*log (1/x)	Total PSD (dBm/10kHz)	Limit (dBm/3kHz)
				Ant 0	Ant 1				
11b	1Mbps	01	2412	-5.775	-5.954	94.95	0.23	-2.63	≤ 8.00
11b	1Mbps	06	2437	-6.107	-5.261	94.95	0.23	-2.43	≤ 8.00
11b	1Mbps	11	2462	-7.353	-7.610	94.95	0.23	-4.24	≤ 8.00
11g	6Mbps	01	2412	-11.966	-12.242	94.90	0.23	-8.86	≤ 8.00
11g	6Mbps	06	2437	-11.661	-11.533	94.90	0.23	-8.36	≤ 8.00
11g	6Mbps	11	2462	-13.851	-14.714	94.90	0.23	-11.02	≤ 8.00
11n-HT20	MCS0	01	2412	-12.522	-13.117	94.72	0.24	-9.56	≤ 8.00
11n-HT20	MCS0	06	2437	-11.398	-12.197	94.72	0.24	-8.53	≤ 8.00
11n-HT20	MCS0	11	2462	-14.491	-15.207	94.72	0.24	-11.59	≤ 8.00
11ax-HE20	MCS0	01	2412	-14.153	-14.522	97.64	0.10	-11.22	≤ 8.00
11ax-HE20	MCS0	06	2437	-12.778	-13.580	97.64	0.10	-10.05	≤ 8.00
11ax-HE20	MCS0	11	2462	-16.513	-17.037	97.64	0.10	-13.65	≤ 8.00
11be-EHT20	MCS0	01	2412	-14.202	-14.930	97.65	0.10	-11.44	≤ 8.00
11be-EHT20	MCS0	06	2437	-12.511	-12.657	97.65	0.10	-9.47	≤ 8.00
11be-EHT20	MCS0	11	2462	-15.962	-16.336	97.65	0.10	-13.03	≤ 8.00

Note: When EUT duty cycle ≥ 98%, Total PSD (dBm / 10kHz) = 10*log {$10^{(\text{Ant 0 PSD}/10)}$ + $10^{(\text{Ant 1 PSD}/10)}$} (dBm / 10kHz).

When EUT duty cycle < 98%, Total PSD (dBm / 10kHz) = 10*log {$10^{(\text{Ant 0 PSD}/10)}$ + $10^{(\text{Ant 1 PSD}/10)}$} (dBm / 10kHz) + 10*log (1/Duty Cycle).

802.11b - AVGPSD - Ant 0

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11g - AVGPSD - Ant 0

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11n-HT20 - AVGPSD - Ant 0

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11ax-HE20 - AVGPSD - Ant 0

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11be-EHT20 - AVGPSD - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11b - AVGPSD - Ant 1

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11g - AVGPSD - Ant 1

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11n-HT20 - AVGPSD - Ant 1

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11ax-HE20 - AVGPSD - Ant 1

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11be-EHT20 - AVGPSD - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

A.5 Conducted Band Edge and Out-of-Band Emissions Test Result

Test Site	WJ-SR2	Test Engineer	Jake Lan
Test Date	2025-02-11 ~ 2025-02-15		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	Limit
11b	1Mbps	01	2412	30dBc
11b	1Mbps	06	2437	30dBc
11b	1Mbps	11	2462	30dBc
11g	6Mbps	01	2412	30dBc
11g	6Mbps	06	2437	30dBc
11g	6Mbps	11	2462	30dBc
11n-HT20	MCS0	01	2412	30dBc
11n-HT20	MCS0	06	2437	30dBc
11n-HT20	MCS0	11	2462	30dBc
11ax-HE20	MCS0	01	2412	30dBc
11ax-HE20	MCS0	06	2437	30dBc
11ax-HE20	MCS0	11	2462	30dBc
11be-EHT20	MCS0	01	2412	30dBc
11be-EHT20	MCS0	06	2437	30dBc
11be-EHT20	MCS0	11	2462	30dBc

802.11b Out-of-Band Emissions – Ant 0

Channel 01 (2412MHz)

Reference Level



Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Reference Level



Spurious Emission



802.11b Out-of-Band Emissions – Ant 0	
Channel 11 (2462MHz)	
Reference Level	High Band Edge
	
Spurious Emission	
	

802.11g Out-of-Band Emissions – Ant 0

Channel 01 (2412MHz)

Reference Level



Low Band Edge



Spurious Emission



Channel 06 (2437MHz)

Reference Level



Spurious Emission