

RF MEASUREMENT REPORT

FCC ID: Q9DAPIN0735

Applicant: Hewlett Packard Enterprise Company

Product: ACCESS POINT

Model No.: APIN0735

Trademark:  , 

FCC Classification: Unlicensed National Information Infrastructure (NII)


FCC Rule Part(s): Part 15 Subpart E (Section 15.407)

Result: Complies

Received Date: 2023-11-09


Test Date: 2023-11-14 ~ 2024-04-12

Reviewed By:



Jame Yuan

Approved By:



Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB789033. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2311RSU031-U4	V01	Initial Report	2024-04-17	Valid

CONTENTS

Description	Page
1. General Information	6
1.1. Applicant	6
1.2. Manufacturer	6
1.3. Testing Facility	6
1.4. Product Information	7
1.5. Radio Specification under Test	8
1.6. Working Frequencies	10
1.7. Description of Antenna RF Port	11
1.8. Antenna Details	12
2. Test Configuration	13
2.1. Test Mode	13
2.2. Test System Connection Diagram	14
2.3. Test Software	14
2.4. Applied Standards	15
2.5. Test Environment Condition	15
3. Antenna Requirements	16
4. Measuring Instrument	17
5. Decision Rules and Measurement Uncertainty	18
5.1. Decision Rules	18
5.2. Measurement Uncertainty	18
6. Test Result	19
6.1. Summary	19
6.2. 26dB & 99% Bandwidth Measurement	20
6.2.1. Test Limit	20
6.2.2. Test Procedure	20
6.2.3. Test Setting	20
6.2.4. Test Setup	20
6.2.5. Test Result	21
6.3. 6dB Bandwidth Measurement	22
6.3.1. Test Limit	22
6.3.2. Test Procedure	22
6.3.3. Test Setting	22
6.3.4. Test Setup	22
6.3.5. Test Result	22
6.4. Output Power Measurement	23

6.4.1.	Test Limit.....	23
6.4.2.	Test Procedure	23
6.4.3.	Test Setting	23
6.4.4.	Test Setup.....	23
6.4.5.	Test Result	23
6.5.	Transmit Power Control Measurement.....	24
6.5.1.	Test Limit.....	24
6.5.2.	Test Procedure	24
6.5.3.	Test Setting	24
6.5.4.	Test Setup.....	24
6.5.5.	Test Result	24
6.6.	Power Spectral Density Measurement	25
6.6.1.	Test Limit.....	25
6.6.2.	Test Procedure	25
6.6.3.	Test Setting	25
6.6.4.	Test Setup.....	26
6.6.5.	Test Result	26
6.7.	Frequency Stability Measurement.....	27
6.7.1.	Test Limit.....	27
6.7.2.	Test Procedure	27
6.7.3.	Test Setup.....	27
6.7.4.	Test Result	28
6.8.	Radiated Spurious Emission Measurement	29
6.8.1.	Test Limit.....	29
6.8.2.	Test Procedure	29
6.8.3.	Test Setting	29
6.8.4.	Test Setup.....	31
6.8.5.	Test Result	32
6.9.	Radiated Restricted Band Edge Measurement	33
6.9.1.	Test Limit.....	33
6.9.2.	Test Procedure	35
6.9.3.	Test Setting	35
6.9.4.	Test Setup.....	36
6.9.5.	Test Result	36
6.10.	AC Conducted Emissions Measurement.....	37
6.10.1.	Test Limit.....	37
6.10.2.	Test Setup.....	37
6.10.3.	Test Result	37

Appendix A – Test Result.....	38
--------------------------------------	-----------

A.1	Duty Cycle Test Result.....	38
A.2	26dB Bandwidth Test Result	41
A.3	6dB Bandwidth Test Result	65
A.4	Output Power Test Result	73
A.5	Power Spectral Density Test Result.....	77
A.6	Frequency Stability Test Result.....	126
A.7	Radiated Spurious Emission Test Result.....	127
A.8	Radiated Restricted Band Edge Test Result.....	242
A.9	AC Conducted Emissions Test Result	472
Appendix B – Test Setup Photograph		474
Appendix C – EUT Photograph		475

1. General Information

1.1. Applicant

Hewlett Packard Enterprise Company

6280 America Center Drive, San Jose CA 95002, United States

1.2. Manufacturer

Hewlett Packard Enterprise Company

6280 America Center Drive, San Jose CA 95002, United States

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China Laboratory Accreditations A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: ☐ R-20025 ☐ G-20034 ☐ C-20020 ☐ T-20020 ☐ R-20141 ☐ G-20134 ☐ C-20103 ☐ T-20104
☐	Test Site – MRT Shenzhen Laboratory Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China Laboratory Accreditations A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
☐	Test Site – MRT Taiwan Laboratory Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) Laboratory Accreditations TAF: 3261 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	ACCESS POINT
Model No.	APIN0735
Serial No.	CNRJM52002
Software Version	V1.6
Wi-Fi Specification	802.11a/b/g/n/ac/ax/be
Bluetooth Specification	BLE only
ZigBee Specification	802.15.4
GNSS Specification	GPS, Galileo
Antenna Information	Refer to Section 1.8
Power Type	AC Adapter Input or PoE Input
Operating Environment	Indoor Use
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	


1.5. Radio Specification under Test

Frequency Range	For 802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20: 5180~5240MHz, 5260~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40: 5190~5230MHz, 5270~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80/ax-HE80/be-EHT80: 5210MHz, 5290MHz, 5530MHz, 5610 MHz, 5690MHz, 5775MHz For 802.11ac-VHT160/ax-HE160/be-EHT160: 5250MHz, 5570MHz		
Type of Modulation	802.11a/n/ac: OFDM 802.11ax/be: OFDMA		
Data Rate	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ac: up to 1732Mbps 802.11ax: up to 2402Mbps 802.11be: up to 2882Mbps		
Support RU	☒ Full RU	☒ Partial RU	☐ Single RU
			☐ Multi RU
			☒ Channel Puncturing



Note: Only 802.11be-EHT80 and 802.11be-EHT160 support channel puncturing function.

Punctured Transmission Details

80MHz bandwidth (20MHz / RU242 punctured)



160MHz bandwidth (20MHz / RU242 punctured and 40MHz / RU484 punctured)



1.6. Working Frequencies

802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz


802.11ac-VHT80/ax-HE80/be-EHT80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

802.11ac-VHT160/ax-HE160/be-EHT160

Channel	Frequency	Channel	Frequency	Channel	Frequency
50	5250 MHz	114	5570 MHz	--	--

1.7. Description of Antenna RF Port

				
Antenna Port	RF Spec.			
	Wi-Fi 2.4G	Wi-Fi 5G	Wi-Fi 6G	BLE/ZigBee
Ant 1	--	--	● (Radio 2)	--
Ant 4	--	--	● (Radio 2)	--
Ant 2	● (Radio 0)	● (Radio 1)	--	--
Ant 5	● (Radio 0)	● (Radio 1)	--	--
Ant 3	--	--	--	● (Core 1)
Ant 6	--	--	--	● (Core 0)
Ant 8	--	--	--	● (Core 1)
Ant 7	GNSS			

1.8. Antenna Details

Antenna Type	Frequency Band (GHz)	Tx Paths	Directional Gain (dBi)	
			Uncorrelated	Correlated
Wi-Fi Antennas (Ant 2 & Ant 5)				
PIFA	5.15 ~ 5.9	2	4.08	4.08
Note: 1, The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated. 2, The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax/be, not include 802.11a/b/g. 3, For beamforming operation, Aruba OS automatically backs power down based on CDD power. 4, The antennas are cross-polarized, so the correlated gain equals to the uncorrelated gain. 5, The detail calculation method of directional gain refers to antenna specification provided by the applicant.				


2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11a (6Mbps)
Mode 2: Transmit by 802.11ac-VHT20_Nss=1 (MCS0)
Mode 3: Transmit by 802.11ac-VHT40_Nss=1 (MCS0)
Mode 4: Transmit by 802.11ac-VHT80_Nss=1 (MCS0)
Mode 5: Transmit by 802.11ac-VHT160_Nss=1 (MCS0)
Mode 6: Transmit by 802.11ax-HE20_Nss=1 (MCS0)
Mode 7: Transmit by 802.11ax-HE40_Nss=1 (MCS0)
Mode 8: Transmit by 802.11ax-HE80_Nss=1 (MCS0)
Mode 9: Transmit by 802.11ax-HE160_Nss=1 (MCS0)
Mode 10: Transmit by 802.11be-EHT20_Nss=1 (MCS0)
Mode 11: Transmit by 802.11be-EHT40_Nss=1 (MCS0)
Mode 12: Transmit by 802.11be-EHT80_Nss=1 (MCS0)
Mode 13: Transmit by 802.11be-EHT160_Nss=1 (MCS0)
Note: 1. All modes of operation and data rates were investigated, so all RF test requirements shall be executed at the worst data rate. 2. 802.11n and 802.11ac have same modulation type and same power value, so we only show 802.11ac test data in report. 3. For CDD mode, this device supports 2 Nss and power level is the same of spatial multiplexing. The worst case is Nss=1. 4. For beamforming operation, manufacturer automatically backs power down based on CDD power. Therefore, only the CDD mode was evaluated in this report. 5. For Puncturing operation, Aruba OS automatically backs power down based on a $10 \cdot \log(\text{Partial_RU} / \text{Full_RU})$ factor based on CDD power.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.



2.3. Test Software

The test utility software used during testing was “accessMTool”, and the version was 3.3.0.6.

Note: Final power setting please refer to operational description.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.407
- KDB 789033 D02v02r01
- KDB 662911 D01v02r01
- KDB 662911 D02v01
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2024-05-15	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2024-05-23	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2024-10-11	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2024-05-07	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2024-04-20	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11263	1 year	2024-11-07	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2024-11-04	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2024-01-12	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2025-01-11	WZ-AC2
Active Loop Antenna	Schwarzbeck	FMZB 1519-60 D	MRTSUE07076	1 year	2024-12-04	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE06402	1 year	2024-05-31	WZ-SR5
Shielding Room	HUAMING	WZ-SR5	MRTSUE06442	N/A	N/A	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2024-05-23	WZ-SR5
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2024-05-23	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11092	1 year	2024-06-08	WZ-SR5
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	5 years	2026-12-20	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2024-05-31	WZ-SR2
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2024-05-23	WZ-SR2
Four-Line V-Network	R&S	ENV432	MRTSUE06615	1 year	2024-09-27	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2024-09-27	WZ-SR2
Temperature Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2024-09-27	WZ-TR3
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2024-05-31	WZ-TR3
Attenuator	MVE	MVE2213	MRTSUE11092	1 year	2024-06-08	WZ-TR3
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2024-05-23	WZ-TR3

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
Controller_MF 7802	1.02	RE Antenna & Turntable
BenchVue Power Meter	2018.1	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.
(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Emission Measurement
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.61dB Coplanar: 9kHz~30MHz: 2.62dB Horizontal: 30MHz~200MHz: 3.79dB 200MHz~1GHz: 3.91dB 1GHz~40GHz: 4.99dB Vertical: 30MHz~200MHz: 4.06dB 200MHz~1GHz: 5.21dB 1GHz~40GHz: 4.90dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.2dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.4dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.2dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.7%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.407(a)	26dB Bandwidth	Conducted	Pass
15.407(e)	6dB Bandwidth		Pass
15.407(a)(1)(ii), (2), (3)(i)	Maximum Conducted Output Power		Pass
15.407(h)(1)	Transmit Power Control		Pass
15.407(g)	Frequency Stability		Pass
15.407(a)(1)(ii), (2), (3)(i), (13)	Peak Power Spectral Density		Pass
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Radiated	Pass
15.205, 15.209 15.407(b)(8), (9), (10)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)		Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Remark:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.
- For Puncturing operation, Aruba OS automatically backs power down based on a $10 \cdot \log(\text{Partial_RU} / \text{Full_RU})$ factor based on CDD power, we evaluated "Peak Power Spectral Density", "Radiated Restricted Band Edge" and "Radiated Spurious Emission" items.
- For Radiated Restricted Band Edge testing, by pre-scan, the result is getting better when puncture position is closer the restricted band, so we select the puncture position away from the restricted band to do the test.

6.2. 26dB & 99% Bandwidth Measurement

6.2.1. Test Limit

N/A

6.2.2. Test Procedure

KDB 789033 D02v02r01- Section II)C)1) (26dB Bandwidth)

KDB 789033 D02v02r01- Section II)D) (99% Bandwidth)

6.2.3. Test Setting


26dB Bandwidth

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth
2. RBW = approximately 1% of the emission bandwidth.
3. VBW > RBW
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission.
Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

99% Bandwidth

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 1% to 5% of the OBW
3. $VBW \geq 3 \times RBW$
4. Span = 1.5 times to 5 times the OBW
5. Detector = peak
6. Trace mode = max hold
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument.

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. 6dB Bandwidth Measurement

6.3.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


6.3.2. Test Procedure

KDB 789033 D02v02r01- Section II)C)2)

6.3.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 100 kHz.
3. VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Output Power Measurement

6.4.1. Test Limit

For the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm).

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

6.4.2. Test Procedure


KDB 789033D02v02r01- Section II)E)3)b) Method PM-G

6.4.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Transmit Power Control Measurement

6.5.1. Test Limit

The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm.


6.5.2. Test Procedure

KDB 789033 D02v02r01- Section II)E)3)b) Method PM-G

6.5.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

6.5.4. Test Setup



6.5.5. Test Result

Device supports TPC mechanism, details refer to the operational description.

6.6. Power Spectral Density Measurement

6.6.1. Test Limit

For the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


6.6.2. Test Procedure

KDB 789033 D02v02r01-Section II)F)

6.6.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz (510kHz, if measurement bandwidth of Maximum PSD is specified in 500 kHz)
4. VBW = $3 \times \text{RBW}$
5. Number of sweep points $\geq 2 \times (\text{span} / \text{RBW})$
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.
10. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
11. Add $10 \cdot \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add $10 \cdot \log(1/0.25) = 6 \text{ dB}$ if the duty cycle is 25 percent.

6.6.4. Test Setup



6.6.5. Test Result

Refer to Appendix A.5.

6.7. Frequency Stability Measurement

6.7.1. Test Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

6.7.2. Test Procedure

Frequency Stability Under Temperature Variations:


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

6.7.3. Test Setup



6.7.4. Test Result

Refer to Appendix A.6.

6.8. Radiated Spurious Emission Measurement

6.8.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.8.2. Test Procedure

KDB 789033 D02v02r01- Section II)G)

6.8.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10Hz

If the EUT duty cycle is $< 98\%$, set $\text{VBW} \geq 1/T$. T is the minimum transmission duration.


802.11a	VBW = 510Hz	802.11ax-HE80	VBW = 2700Hz
802.11ac-VHT20	VBW = 560Hz	802.11ax-HE160	VBW = 4300Hz
802.11ac-VHT40	VBW = 1100Hz	802.11be-EHT20	VBW = 680Hz
802.11ac-VHT80	VBW = 2200Hz	802.11be-EHT40	VBW = 1300Hz
802.11ac-VHT160	VBW = 4300Hz	802.11be-EHT80	VBW = 2700Hz
802.11ax-HE20	VBW = 680Hz	802.11be-EHT160	VBW = 4300Hz
802.11ax-HE40	VBW = 1300Hz	--	--

4. Average-VBW Type was set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto


7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.8.4. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.8.5. Test Result

Refer to Appendix A.7.

6.9. Radiated Restricted Band Edge Measurement

6.9.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

For 15.407(b) requirement:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Refer to KDB 789033 D02v02r01 G)2)c), as specified in § 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a maximum emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in § 15.407(b)(4)). However, an out-of-band emission that complies with both the peak and average limits of § 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz maximum emission limit.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.9.2. Test Procedure

KDB 789033 D02v02r01- Section II)G)

6.9.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.

If the EUT duty cycle is $< 98\%$, set $\text{VBW} \geq 1/T$. T is the minimum transmission duration.

802.11a	VBW = 510Hz	802.11ax-HE80	VBW = 2700Hz
802.11ac-VHT20	VBW = 560Hz	802.11ax-HE160	VBW = 4300Hz
802.11ac-VHT40	VBW = 1100Hz	802.11be-EHT20	VBW = 680Hz
802.11ac-VHT80	VBW = 2200Hz	802.11be-EHT40	VBW = 1300Hz
802.11ac-VHT160	VBW = 4300Hz	802.11be-EHT80	VBW = 2700Hz
802.11ax-HE20	VBW = 680Hz	802.11be-EHT160	VBW = 4300Hz
802.11ax-HE40	VBW = 1300Hz	--	--

4. Average-VBW Type was set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.9.4. Test Setup



6.9.5. Test Result

Refer to Appendix A.8.

6.10. AC Conducted Emissions Measurement


6.10.1. Test Limit

FCC Part 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.10.2. Test Setup



6.10.3. Test Result


Refer to Appendix A.9.

Appendix A – Test Result

A.1 Duty Cycle Test Result


Test Site	WZ-SR5	Test Engineer	Luis Yang
Test Date	2023-11-16		

Test Mode	Duty Cycle	Test Mode	Duty Cycle
802.11a	94.94%	802.11ax-HE80	92.68%
802.11ac-VHT20	98.27%	802.11ax-HE160	88.01%
802.11ac-VHT40	96.65%	802.11be-EHT20	97.78%
802.11ac-VHT80	93.50%	802.11be-EHT40	96.03%
802.11ac-VHT160	88.45%	802.11be-EHT80	92.57%
802.11ax-HE20	97.71%	802.11be-EHT160	87.89%
802.11ax-HE40	95.97%	--	--




Duty Cycle (T = Transmission Duration)


802.11ac-VHT160 (T = 251.2µs)




802.11ax-HE20 (T = 1.493ms)




802.11ax-HE40 (T = 785.3µs)




802.11ax-HE80 (T = 405.0µs)




802.11ax-HE160 (T = 240.8µs)




802.11be-EHT20 (T = 1.497ms)



802.11be-EHT40 (T = 778.9µs)




802.11be-EHT80 (T = 408.8µs)



Duty Cycle (T = Transmission Duration)

802.11be-EHT160 (T = 239.5µs)



A.2 26dB Bandwidth Test Result

Test Site	WZ-SR5	Test Engineer	Luis Yang
Test Date	2023-12-04~2023-12-08		

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	6Mbps	36	5180	21.36	16.831
11a	6Mbps	44	5220	21.63	16.832
11a	6Mbps	48	5240	21.33	16.815
11a	6Mbps	52	5260	21.42	16.817
11a	6Mbps	60	5300	21.55	16.840
11a	6Mbps	64	5320	21.53	16.869
11a	6Mbps	100	5500	21.48	16.841
11a	6Mbps	116	5580	21.56	16.831
11a	6Mbps	140	5700	21.57	16.911
11a	6Mbps	144	5720	21.56	16.828
11a	6Mbps	149	5745	21.56	16.857
11a	6Mbps	157	5785	21.53	16.901
11a	6Mbps	165	5825	22.94	16.976
11ac-VHT20	MCS0	36	5180	21.77	17.979
11ac-VHT20	MCS0	44	5220	21.73	17.930
11ac-VHT20	MCS0	48	5240	21.92	18.033
11ac-VHT20	MCS0	52	5260	21.68	17.973
11ac-VHT20	MCS0	60	5300	21.80	18.014
11ac-VHT20	MCS0	64	5320	21.53	17.959
11ac-VHT20	MCS0	100	5500	21.78	18.030
11ac-VHT20	MCS0	116	5580	21.64	17.970
11ac-VHT20	MCS0	140	5700	21.75	17.982
11ac-VHT20	MCS0	144	5720	21.73	18.021
11ac-VHT20	MCS0	149	5745	21.84	18.032
11ac-VHT20	MCS0	157	5785	21.57	17.997
11ac-VHT20	MCS0	165	5825	22.33	18.036

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11ac-VHT40	MCS0	38	5190	40.05	36.311
11ac-VHT40	MCS0	46	5230	40.16	36.373
11ac-VHT40	MCS0	54	5270	39.84	36.354
11ac-VHT40	MCS0	62	5310	40.04	36.336
11ac-VHT40	MCS0	102	5510	39.97	36.377
11ac-VHT40	MCS0	110	5550	39.88	36.355
11ac-VHT40	MCS0	134	5670	40.07	36.317
11ac-VHT40	MCS0	142	5710	40.07	36.363
11ac-VHT40	MCS0	151	5755	40.20	36.377
11ac-VHT40	MCS0	159	5795	40.32	36.362
11ac-VHT80	MCS0	42	5210	81.28	75.641
11ac-VHT80	MCS0	58	5290	81.08	75.654
11ac-VHT80	MCS0	106	5530	81.31	75.676
11ac-VHT80	MCS0	122	5610	81.47	75.891
11ac-VHT80	MCS0	138	5690	82.13	75.924
11ac-VHT80	MCS0	155	5775	81.87	75.891
11ac-VHT160	MCS0	50	5250	163.70	154.550
11ac-VHT160	MCS0	114	5570	163.80	154.100
11ax-HE20	MCS0	36	5180	21.55	19.073
11ax-HE20	MCS0	44	5220	21.64	19.054
11ax-HE20	MCS0	48	5240	21.34	19.045
11ax-HE20	MCS0	52	5260	21.59	19.134
11ax-HE20	MCS0	60	5300	21.47	19.122
11ax-HE20	MCS0	64	5320	21.63	19.120
11ax-HE20	MCS0	100	5500	21.59	19.099
11ax-HE20	MCS0	116	5580	21.62	19.085
11ax-HE20	MCS0	140	5700	21.65	19.090
11ax-HE20	MCS0	144	5720	21.71	19.111
11ax-HE20	MCS0	149	5745	21.94	19.103
11ax-HE20	MCS0	157	5785	21.68	19.080
11ax-HE20	MCS0	165	5825	21.57	19.137

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11ax-HE40	MCS0	38	5190	39.87	37.733
11ax-HE40	MCS0	46	5230	40.15	37.723
11ax-HE40	MCS0	54	5270	40.38	37.773
11ax-HE40	MCS0	62	5310	39.89	37.716
11ax-HE40	MCS0	102	5510	40.24	37.697
11ax-HE40	MCS0	110	5550	40.55	37.687
11ax-HE40	MCS0	134	5670	40.57	37.692
11ax-HE40	MCS0	142	5710	40.82	37.754
11ax-HE40	MCS0	151	5755	40.91	37.743
11ax-HE40	MCS0	159	5795	40.63	37.720
11ax-HE80	MCS0	42	5210	81.29	77.206
11ax-HE80	MCS0	58	5290	81.36	77.144
11ax-HE80	MCS0	106	5530	81.16	77.069
11ax-HE80	MCS0	122	5610	81.95	77.258
11ax-HE80	MCS0	138	5690	81.14	77.224
11ax-HE80	MCS0	155	5775	81.89	77.227
11ax-HE160	MCS0	50	5250	163.30	156.220
11ax-HE160	MCS0	114	5570	163.50	156.210
11be-EHT20	MCS0	36	5180	21.69	19.089
11be-EHT20	MCS0	44	5220	21.51	19.082
11be-EHT20	MCS0	48	5240	21.44	19.093
11be-EHT20	MCS0	52	5260	21.47	19.101
11be-EHT20	MCS0	60	5300	21.31	19.055
11be-EHT20	MCS0	64	5320	21.57	19.099
11be-EHT20	MCS0	100	5500	21.55	19.138
11be-EHT20	MCS0	116	5580	21.64	19.104
11be-EHT20	MCS0	140	5700	21.73	19.084
11be-EHT20	MCS0	144	5720	21.50	19.131
11be-EHT20	MCS0	149	5745	21.71	19.090
11be-EHT20	MCS0	157	5785	21.71	19.129
11be-EHT20	MCS0	165	5825	21.76	19.134

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11be-EHT40	MCS0	38	5190	40.48	37.668
11be-EHT40	MCS0	46	5230	40.71	37.671
11be-EHT40	MCS0	54	5270	40.77	37.710
11be-EHT40	MCS0	62	5310	40.74	37.687
11be-EHT40	MCS0	102	5510	40.62	37.716
11be-EHT40	MCS0	110	5550	40.62	37.733
11be-EHT40	MCS0	134	5670	40.54	37.761
11be-EHT40	MCS0	142	5710	40.84	37.752
11be-EHT40	MCS0	151	5755	40.56	37.739
11be-EHT40	MCS0	159	5795	40.50	37.742
11be-EHT80	MCS0	42	5210	81.48	77.147
11be-EHT80	MCS0	58	5290	81.82	77.221
11be-EHT80	MCS0	106	5530	81.14	77.067
11be-EHT80	MCS0	122	5610	81.42	77.205
11be-EHT80	MCS0	138	5690	81.25	77.359
11be-EHT80	MCS0	155	5775	81.40	77.277
11be-EHT160	MCS0	50	5250	163.90	156.300
11be-EHT160	MCS0	114	5570	163.40	155.800


Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	F _H (MHz)	Limit (MHz)
802.11a	6Mbps	48	5240	5248.41	< 5250
802.11ac-VHT20	MCS0	48	5240	5249.02	< 5250
802.11ac-VHT40	MCS0	46	5230	5248.19	< 5250
802.11ac-VHT80	MCS0	42	5210	5247.82	< 5250
802.11ax-HE20	MCS0	48	5240	5249.52	< 5250
802.11ax-HE40	MCS0	46	5230	5248.86	< 5250
802.11ax-HE80	MCS0	42	5210	5248.60	< 5250
802.11be-EHT20	MCS0	48	5240	5249.55	< 5250
802.11be-EHT40	MCS0	46	5230	5248.84	< 5250
802.11be-EHT80	MCS0	42	5210	5248.57	< 5250

Note: $F_H = \text{Centre frequency} + 99\% \text{ OBW} / 2$.


For example, 802.11a 5240MHz, $F_H = 5240 \text{ MHz} + 16.815 \text{ MHz} / 2 = 5248.41 \text{ MHz}$.

802.11a 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)



Channel 100 (5500MHz)




Channel 116 (5580MHz)




802.11a 26dB Bandwidth & 99% Bandwidth


Channel 140 (5700MHz)




Channel 144 (5720MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)



Channel 100 (5500MHz)




Channel 116 (5580MHz)




802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth


Channel 140 (5700MHz)




Channel 144 (5720MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth


Channel 38 (5190MHz)




Channel 46 (5230MHz)




Channel 54 (5270MHz)




Channel 62 (5310MHz)




Channel 102 (5510MHz)




Channel 110 (5550MHz)




Channel 134 (5670MHz)




Channel 142 (5710MHz)






802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth


Channel 42 (5210MHz)




Channel 58 (5290MHz)




Channel 106 (5530MHz)




Channel 122 (5610MHz)



Channel 138 (5690MHz)




Channel 155 (5775MHz)




802.11ac-VHT160 26dB Bandwidth & 99% Bandwidth

Channel 50 (5250MHz)




Channel 114 (5570MHz)




802.11ax-HE20 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)



Channel 100 (5500MHz)




Channel 116 (5580MHz)




802.11ax-HE20 26dB Bandwidth & 99% Bandwidth


Channel 140 (5700MHz)




Channel 144(5720MHz)



Channel 149 (5745MHz)



Channel 157 (5785MHz)



Channel 165 (5825MHz)

