RF MEASUREMENT REPORT

FCC ID:	Q9DAPINR503
Applicant:	Hewlett Packard Enterprise Company
Product:	ACCESS POINT
Model No.:	APINR503
Trademark:	aruba a Hewlett Packard Enterprise company, Hewlett Packard Enterprise
FCC Classification:	Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s):	Part 15 Subpart E (Section 15.407)
Result:	Complies
Received Date:	2022-08-18
Test Date:	2022-11-22 ~ 2022-12-12

Reviewed By: Jame Yuan

Approved By: Robin Wu

ilac-MRA

ACCREDITED
TESTING LABORATORY
CERTIFICATE #3628.01

The test results relate only to the samples tested.
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB789033 and KDB 291074. Test results reported herein relate only to the item(s) tested.
The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2208RSU013-U1	Rev. 01	Initial Report	2022-12-12	Valid

CONTENTS

Description Page

1. General Information 6

1.1. Applicant 6
1.2. Manufacturer 6
1.3. Testing Facility 6
1.4. Product Information 7
1.5. Radio Specification under Test 7
1.6. Working Frequencies 8
1.7. Antenna Details 9

2. Test Configuration 10

2.1. Test Mode 10
2.2. Test System Connection Diagram 11
2.3. Applied Standards 11
2.4. Test Environment Condition 12

3. Antenna Requirements 13

4. Measuring Instrument 14

5. Decision Rules and Measurement Uncertainty 15

5.1. Decision Rules 15
5.2. Measurement Uncertainty 15

6. Test Result 16

6.1. Summary 16
6.2. 26dB & 99% Bandwidth Measurement 17
6.2.1. Test Limit 17
6.2.2. Test Procedure 17
6.2.3. Test Setting 17
6.2.4. Test Setup 17
6.2.5. Test Result 18
6.3. 6dB Bandwidth Measurement 19
6.3.1. Test Limit 19
6.3.2. Test Procedure 19
6.3.3. Test Setting 19
6.3.4. Test Setup 19
6.3.5. Test Result 19
6.4. Output Power Measurement 20
6.4.1. Test Limit 20
6.4.2. Test Procedure 20

6.4.3. Test Setting 20
6.4.4. Test Setup 20
6.4.5. Test Result 20
6.5. Power Spectral Density Measurement 21
6.5.1. Test Limit 21
6.5.2. Test Procedure 21
6.5.3. Test Setting 21
6.5.4. Test Setup 21
6.5.5. Test Result 21
6.6. Frequency Stability Measurement 22
6.6.1. Test Limit 22
6.6.2. Test Procedure 22
6.6.3. Test Setup 22
6.6.4. Test Result 23
6.7. Radiated Spurious Emission Measurement 24
6.7.1. Test Limit 24
6.7.2. Test Procedure 24
6.7.3. Test Setting 25
6.7.4. Test Setup 26
6.7.5. Test Result 27
6.8. Radiated Restricted Band Edge Measurement 28
6.8.1. Test Limit 28
6.8.2. Test Procedure 28
6.8.3. Test Setting 28
6.8.4. Test Setup 29
6.8.5. Test Result 29
6.9. AC Conducted Emissions Measurement 30
6.9.1. Test Limit 30
6.9.2. Test Setup 30
6.9.3. Test Result 30

Appendix A – Test Result 31

A.1 Duty Cycle Test Result 31
A.2 26dB & 99% Bandwidth Test Result 33
A.3 6dB Bandwidth Test Result 39
A.4 Output Power Test Result 45
A.5 Power Spectral Density Test Result 46
A.6 Frequency Stability Test Result 57
A.7 Radiated Spurious Emission Test Result 58
A.8 Radiated Restricted Band Edge Test Result 85

A.9 AC Conducted Emissions Test Result 109

Appendix B – Test Setup Photograph 111

Appendix C – EUT Photograph 112

1. General Information

1.1. Applicant

Hewlett Packard Enterprise Company

3333 Scott Blvd, Santa Clara, CA 95054, USA

1.2. Manufacturer

Hewlett Packard Enterprise Company

3333 Scott Blvd, Santa Clara, CA 95054, USA

1.3. Testing Facility

☒	**Test Site – MRT Suzhou Laboratory**				
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China **Laboratory Location (Suzhou - SIP)** 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China				
	Laboratory Accreditations				
	A2LA: 3628.01		CNAS: L10551		
	FCC: CN1166		ISED: CN0001		
	VCCI:	☐R-20025	☐G-20034	☐C-20020	☐T-20020
		☐R-20141	☐G-20134	☐C-20103	☐T-20104
☐	**Test Site – MRT Shenzhen Laboratory**				
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China				
	Laboratory Accreditations				
	A2LA: 3628.02		CNAS: L10551		
	FCC: CN1284		ISED: CN0105		
☐	**Test Site – MRT Taiwan Laboratory**				
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
	Laboratory Accreditations				
	TAF: L3261-190725				
	FCC: 291082, TW3261		ISED: TW3261		

1.4. Product Information

Product Name	ACCESS POINT
Model No.	APINR503
Serial No.	CNP3LF5088
Software Version	F.1.02
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Operating Temperature	0 ~ 40 °C
Antenna Information	Refer to Section 1.7
Power Type	AC/DC adapter input
Operating Environment	Indoor Use
Accessory	
Adapter	Model: WB-18Q12R Input: 100-240V ~ 50/60Hz, 0.6A Max Output: 12.0V, 1.5A, 18W
Remark: 1. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer. 2. AC/DC adapter is not for sale that is declared by the applicant.	

1.5. Radio Specification under Test

Frequency Range	For 802.11a/n-HT20/ac-VHT20/ax-HE20: 5845MHz, 5865MHz, 5885MHz For 802.11n-HT40/ac-VHT40/ax-HE40: 5835MHz, 5875MHz For 802.11ac-VHT80/ax-HE80: 5855MHz
Type of Modulation	802.11a/n/ac: OFDM 802.11ax: OFDMA
Data Rate	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ac: up to 866.6Mbps 802.11ax: up to 1201Mbps

1.6. Working Frequencies

802.11a/n-HT20/ac-VHT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
169	5845 MHz	173	5865 MHz	177	5885 MHz

802.11n-HT40/ac-VHT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
167	5835 MHz	175	5875 MHz	--	--

802.11ac-VHT80/ax-HE80

Channel	Frequency	Channel	Frequency	Channel	Frequency
171	5855 MHz	--	--	--	--

1.7. Antenna Details

Antenna Type	Frequency Band (GHz)	Max Peak Gain (dBi)	CDD Dir Gain (dBi)		BF Dir Gain (dBi)
			For Power	For PSD	
Wi-Fi Antenna (2*2 MIMO)					
PIFA	2.4 ~ 2.5	3.14	3.14	6.11	6.11
	5.15 ~ 5.85	3.91	3.91	6.92	6.92
	5.85 ~ 5.895	3.71	3.71	6.57	6.57

Note:

1, The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

2, The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax, not include 802.11a/b/g.

3. For beamforming operation, Aruba OS automatically backs power down based on a 10log(N) factor based on CDD power.

4. The detail calculation method of directional gain refer to page 10 of antenna specification.

2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11a (6Mbps)
Mode 2: Transmit by 802.11ac-VHT20 (MCS0)
Mode 3: Transmit by 802.11ac-VHT40 (MCS0)
Mode 4: Transmit by 802.11ac-VHT80 (MCS0)
Mode 5: Transmit by 802.11ax-HE20 (MCS0)
Mode 6: Transmit by 802.11ax-HE40 (MCS0)
Mode 7: Transmit by 802.11ax-HE80 (MCS0)

Note 1: 802.11n and 802.11ac have same modulation type and same power value, so we only show 802.11ac test data in report.

Note 2: All modes of operation and data rates were investigated, so all RF test requirements shall be executed at the worst data rate.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.



Cable Type		Cable Spec.	Length
A	Power Cable	Non-Shielding	1.5m
B	Ethernet Cable	Non-Shielding, Cat 5e	>10.0m
C	USB Cable	Shielding	>10.0m
Product		Manufacturer	Model No.
1	USB Flash Disk	SanDisk	N/A
2	AC Adapter	APD	WB-18Q12R
3	Notebook	Dell	Latitude 5491
4	Notebook	Dell	P137G

Note 1: The test utility software used during testing was “accessMTool”, and the version was “3.2.1.5”.

Note 2: Detail power setting refer to operation description.

2.3. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.407
- KDB 789033 D02v02r01
- KDB 291074 D02v01
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.4. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

KDB 291074 DR01: An Indoor Access point in the U-NII-4 band (5.850-5.895 GHz) and U-NII -3 & -4 span channels must use an integrated antenna

- The antenna of the device is built in and locked inside the enclosure.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Last Cali. Date	Cali. Due Date	Test Site
Signal Generator	Agilent	E4438C	MRTSUE06081	1 year	2023-02-14	WZ-SR5
Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2023-04-06	WZ-SR5
Bluetooth Test Set	Anritsu	MT8852B	MRTSUE06389	1 year	2023-06-01	WZ-SR5
Thermohygrometer	testo	608-H1	MRTSUE06402	1 year	2023-06-06	WZ-SR5
Shielding Room	HUAMING	WZ-SR5	MRTSUE06442	N/A	N/A	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2023-06-04	WZ-SR5
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2023-06-04	WZ-SR5
Temperature Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2023-10-08	WZ-TR3
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2023-06-06	WZ-TR3
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2023-09-06	WZ-TR3
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2023-05-20	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2023-06-04	WZ-AC2
Thermohygrometer	Mingle	ETH529	MRTSUE06170	1 year	2022-12-01	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2023-10-13	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2023-05-08	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2023-04-21	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11038	1 year	2023-11-01	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2023-11-05	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2023-01-13	WZ-AC2
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2023-09-29	WZ-AC2
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2022-12-29	WZ-AC1
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2023-09-29	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2023-06-21	WZ-AC1
Anechoic Chamber	TDK	WZ-AC1	MRTSUE06212	1 year	2023-04-21	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE06403	1 year	2023-06-06	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE11039	1 year	2023-11-01	WZ-AC1
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2023-06-04	WZ-SR2
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	5 years	2026-12-20	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2023-06-06	WZ-SR2
Four-Line V-Network	R&S	ENV432	MRTSUE06615	1 year	2023-10-08	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2023-10-27	WZ-SR2

Software	Version	Function
EMI Software	V3	EMI Test Software
Controller_MF 7802	1.02	RE Antenna & Turntable

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Disturbance
The maximum measurement uncertainty is evaluated as: Horizontal: 30MHz~200MHz: 3.85dB 200MHz~1GHz: 4.36dB 1GHz~40GHz: 4.98dB Vertical: 30MHz~200MHz: 4.06dB 200MHz~1GHz: 5.28dB 1GHz~40GHz: 4.91dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.3dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.5dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.3dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 3.2%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.407(a)	26dB Bandwidth	Conducted	Pass
15.407(e)	6dB Bandwidth		Pass
15.407(a)(3)(ii)	Maximum Conducted Output Power		Pass
15.407(a)(3)(ii)	Peak Power Spectral Density		Pass
15.407(b)(5)	Undesirable Emissions	Radiated	Pass
15.205, 15.209 15.407(b)(5)(i), (8), (9)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)		Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Notes:

1. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
2. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.
3. EUT supports one configuration only in 802.11ax full RU mode.

6.2. 26dB & 99% Bandwidth Measurement

6.2.1. Test Limit

N/A

6.2.2. Test Procedure

KDB 789033 D02v02r01- Section C.1 (26dB Bandwidth)

KDB 789033 D02v02r01- Section D (99% Bandwidth)

6.2.3. Test Setting

26dB Bandwidth

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 26. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold.

99% Bandwidth

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1% to 5% of the OBW
4. Set VBW ≥ 3×RBW
5. Detector = Peak.
6. Use the 99% power bandwidth function of the instrument.

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. 6dB Bandwidth Measurement

6.3.1. Test Limit

The minimum 6dBbandwidth shall be at least 500 kHz.

6.3.2. Test Procedure

KDB 789033 D02v02r01- Section C.2

6.3.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 100 kHz.
3. VBW ≥ 3 × RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Output Power Measurement

6.4.1. Test Limit

For an indoor access point operating in the 5.850-5.895 GHz band, the maximum e.i.r.p. over the frequency band of operation must not exceed 36 dBm. Indoor access points operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands must not exceed an e.i.r.p. of 36 dBm.

6.4.2. Test Procedure

KDB 789033D02v02r01- Section E)3)b) Method PM-G

6.4.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Power Spectral Density Measurement

6.5.1. Test Limit

For an indoor access point operating in the 5.850-5.895 GHz band, the maximum power spectral density must not exceed 20 dBm e.i.r.p. in any 1-megahertz band.

6.5.2. Test Procedure

KDB 789033 D02v02r01-SectionF

6.5.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz
4. VBW = 3 × RBW
5. Number of sweep points ≥ 2 × (span / RBW)
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
10. Add 10*log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add 10*log(1/0.25) = 6 dB if the duty cycle is 25 percent.

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Frequency Stability Measurement

6.6.1. Test Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

6.6.2. Test Procedure

Frequency Stability Under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation (±15%) and endpoint, record the maximum frequency change.

6.6.3. Test Setup



6.6.4. Test Result

Refer to Appendix A.6.

6.7. Radiated Spurious Emission Measurement

6.7.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency	Field Strength	Measured Distance
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

For transmitters operating solely in the 5.850-5.895 GHz band or operating on a channel that spans across 5.725-5.895 GHz:

For an indoor access point or subordinate device, all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of 15 dBm/MHz and shall decrease linearly to an e.i.r.p. of −7 dBm/MHz at or above 5.925 GHz.

For a client device or indoor access point or subordinate device, all emissions below 5.725 GHz shall not exceed an e.i.r.p. of −27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz.

6.7.2. Test Procedure

KDB 789033 D02v02r01- Section G.

6.7.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.

If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.

802.11a	VBW = 470Hz	802.11ax-HE20	VBW = 680Hz
802.11ac-VHT20	VBW = 510Hz	802.11ax-HE40	VBW = 1.3kHz
802.11ac-VHT40	VBW = 1.1kHz	802.11ax-HE80	VBW = 2.7kHz
802.11ac-VHT80	VBW = 2.2kHz	N/A	N/A

4. Detector = Peak

5. Sweep time = auto

6. Trace mode = max hold

7. Trace was allowed to stabilize

6.7.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.7.5. Test Result

Refer to Appendix A.7.

6.8. Radiated Restricted Band Edge Measurement

6.8.1. Test Limit

For transmitters operating solely in the 5.850-5.895 GHz band or operating on a channel that spans across 5.725-5.895 GHz:

For an indoor access point or subordinate device, all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of 15 dBm/MHz and shall decrease linearly to an e.i.r.p. of −7 dBm/MHz at or above 5.925 GHz.

For a client device or indoor access point or subordinate device, all emissions below 5.725 GHz shall not exceed an e.i.r.p. of −27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz.

6.8.2. Test Procedure

KDB 789033 D02v02r01- Section G

6.8.3. Test Setting

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10Hz
4. If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration

802.11a	VBW = 470Hz	802.11ax-HE20	VBW = 680Hz
802.11ac-VHT20	VBW = 510Hz	802.11ax-HE40	VBW = 1.3kHz
802.11ac-VHT40	VBW = 1.1kHz	802.11ax-HE80	VBW = 2.7kHz
802.11ac-VHT80	VBW = 2.2kHz	N/A	N/A

5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.8.4. Test Setup



6.8.5. Test Result

Refer to Appendix A.8.

6.9. AC Conducted Emissions Measurement

6.9.1. Test Limit

FCC Part 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50
Note 1: The lower limit shall apply at the transition frequencies. Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.		

6.9.2. Test Setup



6.9.3. Test Result

Refer to Appendix A.9.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2022-11-30		

Test Mode	Duty Cycle
802.11a	95.16%
802.11ac-VHT20	98.42%
802.11ac-VHT40	96.95%
802.11ac-VHT80	93.88%
802.11ax-HE20	97.96%
802.11ax-HE40	96.04%
802.11ax-HE80	92.60%

Duty Cycle (T = Transmission Duration)

802.11a (T = 2.065ms)



802.11ac-VHT20 (T = 1.926ms)



802.11ac-VHT40 (T = 952.0μs)



802.11ac-VHT80 (T = 460.0μs)



802.11ax-HE20 (T = 1.488ms)



802.11ax-HE40 (T = 780.5μs)



802.11ax-HE80 (T = 413.0μs)



A.2 26dB & 99% Bandwidth Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2022-11-22		

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	99% Bandwidth (MHz)	26dB Bandwidth (MHz)
11a	6Mbps	169	5845	16.867	21.57
11a	6Mbps	173	5865	17.131	26.95
11a	6Mbps	177	5885	17.231	27.15
11ac-VHT20	MCS0	169	5845	17.948	21.68
11ac-VHT20	MCS0	173	5865	17.989	22.53
11ac-VHT20	MCS0	177	5885	18.233	26.44
11ac-VHT40	MCS0	167	5835	36.478	45.95
11ac-VHT40	MCS0	175	5875	36.603	51.22
11ac-VHT80	MCS0	171	5855	75.982	99.73
11ax-HE20	MCS0	169	5845	19.063	21.80
11ax-HE20	MCS0	173	5865	19.097	22.56
11ax-HE20	MCS0	177	5885	19.100	22.89
11ax-HE40	MCS0	167	5835	37.623	39.88
11ax-HE40	MCS0	175	5875	37.614	40.06
11ax-HE80	MCS0	171	5855	76.915	81.35

802.11a 26dB & 99% Bandwidth	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ac-VHT20 26dB & 99% Bandwidth	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ac-VHT40 26dB & 99% Bandwidth	
Channel 167 (5835MHz)	Channel 175(5875MHz)
	
802.11ac-VHT80 26dB & 99% Bandwidth	
Channel 171 (5855MHz)	
	

802.11ax-HE20 26dB & 99% Bandwidth	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ax-HE40 26dB & 99% Bandwidth	
Channel 167 (5835MHz)	Channel 175(5875MHz)
	
802.11ax-HE80 26dB & 99% Bandwidth	
Channel 171 (5855MHz)	
	

A.3 6dB Bandwidth Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2022-11-22		

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11a	6Mbps	169	5845	16.38	≥ 0.5
11a	6Mbps	173	5865	16.37	≥ 0.5
11a	6Mbps	177	5885	16.37	≥ 0.5
11ac-VHT20	MCS0	169	5845	17.60	≥ 0.5
11ac-VHT20	MCS0	173	5865	17.60	≥ 0.5
11ac-VHT20	MCS0	177	5885	17.62	≥ 0.5
11ac-VHT40	MCS0	167	5835	36.37	≥ 0.5
11ac-VHT40	MCS0	175	5875	36.36	≥ 0.5
11ac-VHT80	MCS0	171	5855	75.48	≥ 0.5
11ax-HE20	MCS0	169	5845	19.00	≥ 0.5
11ax-HE20	MCS0	173	5865	19.00	≥ 0.5
11ax-HE20	MCS0	177	5885	19.00	≥ 0.5
11ax-HE40	MCS0	167	5835	37.44	≥ 0.5
11ax-HE40	MCS0	175	5875	37.46	≥ 0.5
11ax-HE80	MCS0	171	5855	76.92	≥ 0.5

802.11a 6dB Bandwidth	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ac-VHT20 6dB Bandwidth	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ac-VHT40 6dB Bandwidth	
Channel 167 (5835MHz)	Channel 175(5875MHz)
	
802.11ac-VHT80 6dB Bandwidth	
Channel 171 (5855MHz)	
	

802.11ax-HE20 6dB Bandwidth	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ax-HE40 6dB Bandwidth	
Channel 167 (5835MHz)	Channel 175(5875MHz)
	
802.11ax-HE80 6dB Bandwidth	
Channel 171 (5855MHz)	
	

A.4 Output Power Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2022-11-22		

Test Mode	Data Rate MCS	Channel No.	Freq. (MHz)	Average Power (dBm)		Total Average Power (dBm)	EIRP Power (dBm)	Power Limit (dBm)
				Ant 0	Ant 1			
11a	6Mbps	169	5845	18.28	18.10	21.20	24.91	≤ 36.00
11a	6Mbps	173	5865	18.26	18.16	21.22	24.93	≤ 36.00
11a	6Mbps	177	5885	18.31	18.18	21.26	24.97	≤ 36.00
11ac-VHT20	MCS0	169	5845	18.39	18.04	21.23	24.94	≤ 36.00
11ac-VHT20	MCS0	173	5865	18.33	18.27	21.31	25.02	≤ 36.00
11ac-VHT20	MCS0	177	5885	18.31	18.22	21.28	24.99	≤ 36.00
11ac-VHT40	MCS0	167	5835	18.23	17.31	20.80	24.51	≤ 36.00
11ac-VHT40	MCS0	175	5875	18.21	17.44	20.85	24.56	≤ 36.00
11ac-VHT80	MCS0	171	5855	18.32	17.69	21.03	24.74	≤ 36.00
11ax-HE20	MCS0	169	5845	18.38	18.16	21.28	24.99	≤ 36.00
11ax-HE20	MCS0	173	5865	18.45	18.35	21.41	25.12	≤ 36.00
11ax-HE20	MCS0	177	5885	18.00	18.27	21.15	24.86	≤ 36.00
11ax-HE40	MCS0	167	5835	18.31	17.48	20.93	24.64	≤ 36.00
11ax-HE40	MCS0	175	5875	18.30	17.46	20.91	24.62	≤ 36.00
11ax-HE80	MCS0	171	5855	18.22	17.61	20.94	24.65	≤ 36.00

Note 1: Total Average Power (dBm) = 10*log {$10^{(\text{Ant 0 Average Power /10})}$ + $10^{(\text{Ant 1 Average Power /10})}$.

Note 2: EIRP Power (dBm) = Total Average Power (dBm) + Directional Gain (dBi).

A.5 Power Spectral Density Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2022-11-22		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	AVPSD (dBm/MHz)		Duty Cycle (%)	Total PSD (dBm/ MHz)	EIRP PSD (dBm/ MHz)	EIRP PSD Limit (dBm/MHz)
				Ant 0	Ant 1				
11a	6Mbps	169	5845	6.553	6.539	95.16	9.77	16.34	≤ 20.00
11a	6Mbps	173	5865	7.038	6.707	95.16	10.10	16.67	≤ 20.00
11a	6Mbps	177	5885	6.805	6.681	95.16	9.97	16.54	≤ 20.00
11ac-VHT20	MCS0	169	5845	6.555	6.326	98.42	9.45	16.09	≤ 20.00
11ac-VHT20	MCS0	173	5865	6.624	6.255	98.42	9.45	16.09	≤ 20.00
11ac-VHT20	MCS0	177	5885	6.652	6.411	98.42	9.54	16.18	≤ 20.00
11ac-VHT40	MCS0	167	5835	3.589	2.720	96.95	6.32	12.89	≤ 20.00
11ac-VHT40	MCS0	175	5875	3.820	2.834	96.95	6.50	13.07	≤ 20.00
11ac-VHT80	MCS0	171	5855	0.689	0.378	93.88	3.82	10.39	≤ 20.00
11ax-HE20	MCS0	169	5845	6.249	6.173	97.96	9.31	15.88	≤ 20.00
11ax-HE20	MCS0	173	5865	6.492	6.126	97.96	9.41	15.98	≤ 20.00
11ax-HE20	MCS0	177	5885	6.021	6.125	97.96	9.17	15.74	≤ 20.00
11ax-HE40	MCS0	167	5835	3.505	2.600	96.04	6.26	12.83	≤ 20.00
11ax-HE40	MCS0	175	5875	3.292	2.674	96.04	6.18	12.75	≤ 20.00
11ax-HE80	MCS0	171	5855	0.697	-0.054	92.60	3.68	10.25	≤ 20.00

Note 1: When EUT duty cycle < 98%, the total PSD (dBm/MHz) =10*log {$10^{(\text{Ant 0 AVGPSD}/10)}$ + $10^{(\text{Ant 1 AVGPSD}/10)}$} +10*log (1/Duty cycle).

When EUT duty cycle ≥ 98%, the total PSD (dBm/MHz) =10*log {$10^{(\text{Ant 0 AVGPSD}/10)}$ + $10^{(\text{Ant 1 AVGPSD}/10)}$}.

Note 2: EIRP PSD (dBm/MHz) = Total PSD (dBm/MHz) + Directional Gain (dBi).

Note 3: For Channels span the 5.725-5.850 GHz and 5.850-5.895 GHz bands, we record the maximum level of 5.725-5.850 GHz and 5.850-5.895 GHz with RBW=1MHz, and the level complied with the 5.850-5.895 GHz EIRP PSD Limit.

802.11a Power Spectral Density - Ant 0	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ac-VHT20 Power Spectral Density - Ant 0	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)	
	

802.11ac-VHT40 Power Spectral Density - Ant 0	
Channel 167 (5835MHz)	Channel 175 (5875MHz)
	
802.11ac-VHT80 Power Spectral Density - Ant 0	
Channel 171 (5855MHz)	
	

802.11ax-HE20 Power Spectral Density - Ant 0	
Channel 169 (5845MHz)	Channel 173 (5865MHz)
	
Channel 177 (5885MHz)