RF MEASUREMENT REPORT

FCC ID:	Q9DASIN0305
Applicant:	Hewlett Packard Enterprise
Product:	HPE Aruba User Experience Sensor
Model No.:	ASIN0305
Trademark:	Hewlett Packard Enterprise , HPE aruba networking
FCC Classification:	Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s):	Part 15 Subpart E (Section 15.407)
Result:	Complies
Received Date:	2023-06-15
Test Date:	2023-07-11 ~ 2023-10-25

Reviewed By: Jame Yuan

Approved By: Robin Wu

ACCREDITED
TESTING LABORATORY
CERTIFICATE #3628.01

The test results relate only to the samples tested.
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB789033. Test results reported herein relate only to the item(s) tested.
The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2306RSU027-U14	V01	Initial Report	2023-09-22	Invalid
2306RSU027-U14	V02	Add 1-18GHz test plot of RSE	2023-10-30	Invalid
2306RSU027-U14	V03	Add Spot-check Error description	2023-12-15	Valid

Note 1: The product is a variation on the existing ASIN0306 (FCC ID: Q9DASIN0306).

The differences are shown in the table below.

Parts of Product	Modification
PCB	Remove LTE/GPS module and its antenna & Remove the super-capacitor
Others	No Change

The applicant remeasured a set of antenna gain data that slightly different than before.

Frequency Band (MHz)	LTE Version (ASIN0306)		Non-LTE Version (ASIN0305)	
	Uncorrelated	Correlated	Uncorrelated	Correlated
2G/5G				
2450	2.1	5.0	2.2	5.0
5150	3.5	6.5	4.3	7.1
5500	3.5	6.3	4.8	7.8
5850	3.5	6.0	4.4	7.3
5895	3.6	6.2	4.5	7.5
2G/6G				
2450	2.0	4.8	1.3	4.2
5925	2.7	5.5	2.5	5.3
6500	3.1	6.0	3.7	6.7
7000	3.2	6.1	2.7	5.6
ZigBee / BLE				
2450	2.3		2.3	

Note 2: Spot-check tests were done on these items (Radiated Spurious Emission & Radiated Restricted Band Edge) based on worst-case results reported in the original FCC ID filing.

Other test data refer to original test report no. 2306RSU027-U4.

CONTENTS

Description Page

1. General Information 6

1.1. Applicant 6
1.2. Manufacturer 6
1.3. Testing Facility 6
1.4. Product Information 7
1.5. Radio Specification under Test 7
1.6. Working Frequencies 8
1.7. Antenna Details 9

2. Test Configuration 10

2.1. Test Mode 10
2.2. Test System Connection Diagram 11
2.3. Test Software 11
2.4. Applied Standards 12
2.5. Test Environment Condition 12

3. Antenna Requirements 13

4. Measuring Instrument 14

5. Decision Rules and Measurement Uncertainty 16

5.1. Decision Rules 16
5.2. Measurement Uncertainty 16

6. Test Result 17

6.1. Summary 17
6.2. 26dB & 99% Bandwidth Measurement 18
6.2.1. Test Limit 18
6.2.2. Test Procedure 18
6.2.3. Test Setting 18
6.2.4. Test Setup 18
6.2.5. Test Result 19
6.3. 6dB Bandwidth Measurement 20
6.3.1. Test Limit 20
6.3.2. Test Procedure 20
6.3.3. Test Setting 20
6.3.4. Test Setup 20
6.3.5. Test Result 20
6.4. Output Power Measurement 21
6.4.1. Test Limit 21

6.4.2. Test Procedure 21
6.4.3. Test Setting 21
6.4.4. Test Setup 21
6.4.5. Test Result 21
6.5. Transmit Power Control Measurement 22
6.5.1. Test Limit 22
6.5.2. Test Procedure 22
6.5.3. Test Setting 22
6.5.4. Test Setup 22
6.5.5. Test Result 22
6.6. Power Spectral Density Measurement 23
6.6.1. Test Limit 23
6.6.2. Test Procedure 23
6.6.3. Test Setting 23
6.6.4. Test Setup 24
6.6.5. Test Result 24
6.7. Frequency Stability Measurement 25
6.7.1. Test Limit 25
6.7.2. Test Procedure 25
6.7.3. Test Setup 25
6.7.4. Test Result 26
6.8. Radiated Spurious Emission Measurement 27
6.8.1. Test Limit 27
6.8.2. Test Procedure 27
6.8.3. Test Setting 27
6.8.4. Test Setup 29
6.8.5. Test Result 30
6.9. Radiated Restricted Band Edge Measurement 31
6.9.1. Test Limit 31
6.9.2. Test Procedure 33
6.9.3. Test Setting 33
6.9.4. Test Setup 34
6.9.5. Test Result 34
6.10. AC Conducted Emissions Measurement 35
6.10.1. Test Limit 35
6.10.2. Test Setup 35
6.10.3. Test Result 35

Appendix A – Test Result 36

A.1 Duty Cycle Test Result 36

A.2 26dB Bandwidth Test Result 38
A.3 6dB Bandwidth Test Result 56
A.4 Output Power Test Result 62
A.5 Power Spectral Density Test Result 65
A.6 Frequency Stability Test Result 98
A.7 Radiated Spurious Emission Test Result 99
A.8 Radiated Restricted Band Edge Test Result 189
A.9 AC Conducted Emissions Test Result 316

Appendix B – Test Setup Photograph 318

Appendix C – EUT Photograph 319

1. General Information

1.1. Applicant

Hewlett Packard Enterprise

6280 America Center Drive, San Jose CA 95002, United States

1.2. Manufacturer

Hewlett Packard Enterprise

6280 America Center Drive, San Jose CA 95002, United States

1.3. Testing Facility

☒	**Test Site – MRT Suzhou Laboratory**				
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China **Laboratory Location (Suzhou - SIP)** 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China				
	Laboratory Accreditations				
	A2LA: 3628.01		CNAS: L10551		
	FCC: CN1166		ISED: CN0001		
	VCCI:	☐R-20025	☐G-20034	☐C-20020	☐T-20020
		☐R-20141	☐G-20134	☐C-20103	☐T-20104
☐	**Test Site – MRT Shenzhen Laboratory**				
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China				
	Laboratory Accreditations				
	A2LA: 3628.02		CNAS: L10551		
	FCC: CN1284		ISED: CN0105		
☐	**Test Site – MRT Taiwan Laboratory**				
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
	Laboratory Accreditations				
	TAF: 3261				
	FCC: 291082, TW3261		ISED: TW3261		

1.4. Product Information

Product Name	HPE Aruba User Experience Sensor
Model No.	ASIN0305
Serial No.	CNQJLPL01P
Software Version	6.5GA
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Bluetooth Specification	BLE only
ZigBee Specification	802.15.4
Power Type	AC/DC Adapter
Operating Temperature	0 ~ 40 °C
Operating Environment	Indoor Use
Accessories	
AC/DC Adapter	Model No.: WB-12G12R Input: 100-240V, 50/60Hz, 0.3A Max Output: 12.0V⎓1.0A 12.0W
Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Radio Specification under Test

Frequency Range	For 802.11a/n-HT20/ac-VHT20/ax-HE20: 5180~5240MHz, 5260~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40/ax-HE40: 5190~5230MHz, 5270~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80/ax-HE80: 5210MHz, 5290MHz, 5530MHz, 5610 MHz, 5690MHz, 5775MHz	
Type of Modulation	802.11a/n/ac: OFDM 802.11ax: OFDMA	
Data Rate	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ac: up to 866.6Mbps 802.11ax: up to 1201Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11a/n-HT20/ac-VHT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80/ax-HE80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

1.7. Antenna Details

Antenna Type	Frequency Band (MHz)	T_X Paths	Directional Gain (dBi)		Beamforming Gain (dBi)
			Uncorrelated	Correlated	
Wi-Fi Antennas (Radio 0)					
PIFA Antenna	2400 ~ 2483.5	2	2.2	5.0	5.0
	5150 ~ 5250	2	4.3	7.1	7.1
	5250 ~ 5350	2	4.3	7.1	7.1
	5470 ~ 5725	2	4.8	7.8	7.8
	5725 ~ 5850	2	4.4	7.3	7.3
	5850 ~ 5895	2	4.5	7.5	7.5
Wi-Fi Antennas (Radio 1)					
PIFA Antenna	2400 ~ 2483.5	2	1.3	4.2	4.2
	5925 ~ 6425	2	2.5	5.3	5.3
	6425 ~ 6525	2	3.7	6.7	6.7
	6525 ~ 6875	2	3.7	6.7	6.7
	6875 ~ 7125	2	2.7	5.6	5.6
Bluetooth / ZigBee Antenna					
PIFA Antenna	2400 ~ 2483.5	1	2.3	--	--

Note:

1, The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

2, The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax, not include 802.11a/b/g.

3, The antenna gain is from antenna report that was provided by the applicant.

2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11a (6Mbps)
Mode 2: Transmit by 802.11ac-VHT20 (MCS0) _N_{SS}=1 (MIMO Mode)
Mode 3: Transmit by 802.11ac-VHT40 (MCS0) _N_{SS}=1 (MIMO Mode)
Mode 4: Transmit by 802.11ac-VHT80 (MCS0) _N_{SS}=1 (MIMO Mode)
Mode 5: Transmit by 802.11ax-HE20 (MCS0) _N_{SS}=1 (MIMO Mode)
Mode 6: Transmit by 802.11ax-HE40 (MCS0) _N_{SS}=1 (MIMO Mode)
Mode 7: Transmit by 802.11ax-HE80 (MCS0) _N_{SS}=1 (MIMO Mode)
Note 1: All modes of operation and data rates were investigated, so all RF test requirements shall be executed at the worst data rate. Note 2: For beamforming operation, manufacturer automatically backs power down based on a 10log(N_{ANT}) factor based on CDD power. Therefore, only the CDD mode was evaluated in this report. Note 3: 802.11n and 802.11ac have same modulation type and same power value, so we only show 802.11ac test data in report.

Radio Working Mode

Work Groups	Wi-Fi Radio 0	Wi-Fi Radio 1	IOT
1	2.4G	6G	BLE or ZigBee
2	5G	2.4G	BLE or ZigBee
3	5G	6G	BLE or ZigBee

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram – Radiated Emission testing & AC Conducted Emissions



Cable Type		Cable Description	
A	Ethernet Cable	Non shielded, > 10m	
B	Power Cable	Non shielded, 1.6m	
Product		**Manufacturer**	**Model No.**
1	Notebook	Dell	Latitude 5491

2.3. Test Software

The test utility software used during testing was “accessMTool”, and the version was 3.2.1.5.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.407
- KDB 789033 D02v02r01
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached.**
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2023-12-28	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2023-08-22	WZ-AC1
Preamplifier	Agilent	83017A	MRTSUE06076	1 year	2024-05-07	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2024-06-09	WZ-AC1
Anechoic Chamber	TDK	WZ-AC1	MRTSUE06212	1 year	2024-04-20	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE06403	1 year	2024-05-31	WZ-AC1
Signal Analyzer	Keysight	N9010B	MRTSUE06607	1 year	2023-12-28	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE11039	1 year	2023-11-01	WZ-AC1
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2023-09-29	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2023-11-05	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2024-01-12	WZ-AC2
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2024-05-15	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2024-05-23	WZ-AC2
Thermohygrometer	Mingle	ETH529	MRTSUE06170	1 year	2023-11-27	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2023-10-13	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2024-05-07	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2024-04-20	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11038	1 year	2023-11-01	WZ-AC2
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2024-05-23	WZ-SR2
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	5 years	2026-12-20	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2024-05-31	WZ-SR2
Four-Line V-Network	R&S	ENV432	MRTSUE06615	1 year	2023-10-08	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2023-10-27	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06402	1 year	2024-05-31	WZ-SR5
Shielding Room	HUAMING	WZ-SR5	MRTSUE06442	N/A	N/A	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2024-05-23	WZ-SR5
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2024-05-23	WZ-SR5
Temperature Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2023-10-08	WZ-TR3
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2024-05-31	WZ-TR3
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2023-09-06	WZ-TR3

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
Controller_MF 7802	2.03C	RE Antenna & Turntable
Controller_MF 7802	1.02	RE Antenna & Turntable
BenchVue Power Meter	2018.1	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
Measurement Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Disturbance
Measurement Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): Coaxial: 9kHz~30MHz: 2.59dB Coplanar: 9kHz~30MHz: 2.60dB Horizontal: 30MHz~200MHz: 3.85dB 200MHz~1GHz: 4.36dB 1GHz~40GHz: 4.98dB Vertical: 30MHz~200MHz: 4.06dB 200MHz~1GHz: 5.28dB 1GHz~40GHz: 4.91dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.3dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.5dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.3dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 3.2%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.407(a)	26dB Bandwidth	Conducted	Pass
15.407(e)	6dB Bandwidth		Pass
15.407(a)(1)(ii), (2), (3)(i)	Maximum Conducted Output Power		Pass
15.407(h)(1)	Transmit Power Control		Pass
15.407(a)(1)(ii), (2), (3)(i), (12)	Peak Power Spectral Density		Pass
15.407(g)	Frequency Stability		Pass
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Radiated	Pass
15.205, 15.209 15.407(b)(8), (9), (10)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)		Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Remark:

1. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part ofthe system to connect the EUT to the analyzer at all frequencies of interest.
2. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 26dB & 99% Bandwidth Measurement

6.2.1. Test Limit

N/A

6.2.2. Test Procedure

KDB 789033 D02v02r01- Section II)C)1) (26dB Bandwidth)

KDB 789033 D02v02r01- Section II)D) (99% Bandwidth)

6.2.3. Test Setting

26dB Bandwidth

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth
2. RBW = approximately 1% of the emission bandwidth.
3. VBW > RBW
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

99% Bandwidth

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 1% to 5% of the OBW
3. VBW ≥ 3 × RBW
4. Span = 1.5 times to 5 times the OBW
5. Detector = peak
6. Trace mode = max hold
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument.

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. 6dB Bandwidth Measurement

6.3.1. Test Limit

The minimum 6dBbandwidth shall be at least 500 kHz.

6.3.2. Test Procedure

KDB 789033 D02v02r01- Section II)C)2)

6.3.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 100 kHz.
3. VBW ≥ 3 × RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Output Power Measurement

6.4.1. Test Limit

For client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm).

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

6.4.2. Test Procedure

KDB 789033D02v02r01- Section II)E)3)b) Method PM-G

6.4.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Transmit Power Control Measurement

6.5.1. Test Limit

The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm.

6.5.2. Test Procedure

KDB 789033 D02v01- Section II)E)3)b) Method PM-G

6.5.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

6.5.4. Test Setup



6.5.5. Test Result

Device supports TPC mechanism, details refer to the operational description.

6.6. Power Spectral Density Measurement

6.6.1. Test Limit

For client device in the 5.15-5.25 GHz, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

6.6.2. Test Procedure

KDB 789033 D02v02r01-Section II)F)

6.6.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz (510kHz, if measurement bandwidth of Maximum PSD is specified in 500 kHz)
4. VBW = 3 × RBW
5. Number of sweep points ≥ 2 × (span / RBW)
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.
10. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
11. Add 10*log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add 10*log(1/0.25) = 6 dB if the duty cycle is 25 percent.

6.6.4. Test Setup



6.6.5. Test Result

Refer to Appendix A.5.

6.7. Frequency Stability Measurement

6.7.1. Test Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

6.7.2. Test Procedure

Frequency Stability Under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation (±15%) and endpoint, recordthe maximum frequency change.

6.7.3. Test Setup



6.7.4. Test Result

Refer to Appendix A.6.

6.8. Radiated Spurious Emission Measurement

6.8.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.8.2. Test Procedure

KDB 789033 D02v02r01- Section II)G)

6.8.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. Span was set greater than 1MHz

3. RBW = as specified in Table 1

4. Detector = CISPR quasi-peak

5. Sweep time = auto couple

6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. RBW = 1MHz

3. VBW = 3MHz

4. Detector = peak

5. Sweep time = auto couple

6. Trace mode = max hold

7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. RBW = 1MHz

3. VBW; If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.

If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.

802.11a	10Hz	802.11ac-VHT20	10Hz	802.11ac-VHT40	10Hz
802.11ac-VHT80	10Hz	802.11ax-HE20	10Hz	802.11ax-HE40	10Hz
802.11ax-HE80	10Hz	--	--	--	--

4. Detector = Peak

5. Sweep time = auto

6. Trace mode = max hold

7. Trace was allowed to stabilize

6.8.4. Test Setup

Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.8.5. Test Result

Refer to Appendix A.7.

6.9. Radiated Restricted Band Edge Measurement

6.9.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1] 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])
13.36 - 13.41	--	--	--

For 15.407(b) requirement:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Refer to KDB 789033 D02v02r01 G)2)c), as specified in § 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a maximum emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in § 15.407(b)(4)). However, an out-of-band emission that complies with both the peak and average limits of § 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz maximum emission limit.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.9.2. Test Procedure

KDB 789033 D02v02r01- Section II)G)

6.9.3. Test Setting

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.

If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.

802.11a	10Hz	802.11ac-VHT20	10Hz	802.11ac-VHT40	10Hz
802.11ac-VHT80	10Hz	802.11ax-HE20	10Hz	802.11ax-HE40	10Hz
802.11ax-HE80	10Hz	--	--	--	--

4. If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.9.4. Test Setup



6.9.5. Test Result

Refer to Appendix A.8.

6.10. AC Conducted Emissions Measurement

6.10.1. Test Limit

FCC Part 15.207 Limits		
Frequency (MHz)	QP (dBμV)	AV (dBμV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50
Note 1: The lower limit shall apply at the transition frequencies. Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.		

6.10.2. Test Setup



6.10.3. Test Result

Refer to Appendix A.9.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	WZ-SR5	Test Engineer	Luis Yang
Test Date	2023-07-11		

Test Mode	Duty Cycle
802.11a	99.01%
802.11ac-VHT20	98.99%
802.11ac-VHT40	98.76%
802.11ac-VHT80	98.76%
802.11ax-HE20	98.77%
802.11ax-HE40	98.77%
802.11ax-HE80	98.77%

Duty Cycle (T = Transmission Duration)

802.11a (T = 3.006ms)



802.11ac-VHT20 (T = 3.043ms)



802.11ac-VHT40 (T = 3.021ms)



802.11ac-VHT80 (T = 3.021ms)



Duty Cycle (T = Transmission Duration)	
802.11ax-HE20 (T = 3.051ms)	802.11ax-HE40 (T = 3.043ms)
	
802.11ax-HE80 (T = 3.043ms)	
	

A.2 26dB Bandwidth Test Result

Test Site	WZ-SR5	Test Engineer	Luis Yang
Test Date	2023-07-11~2023-08-01		

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	6Mbps	36	5180	21.85	17.859
11a	6Mbps	44	5220	21.80	16.840
11a	6Mbps	48	5240	21.73	16.821
11a	6Mbps	52	5260	21.84	16.850
11a	6Mbps	60	5300	21.33	16.819
11a	6Mbps	64	5320	21.35	16.807
11a	6Mbps	100	5500	21.40	16.780
11a	6Mbps	116	5580	21.33	16.786
11a	6Mbps	140	5700	32.69	17.395
11a	6Mbps	144	5720	31.54	17.530
11a	6Mbps	149	5745	37.96	17.820
11a	6Mbps	157	5785	35.72	18.167
11a	6Mbps	165	5825	37.07	17.980
11ac-VHT20	MCS0	36	5180	21.78	17.976
11ac-VHT20	MCS0	44	5220	21.52	17.948
11ac-VHT20	MCS0	48	5240	21.51	17.942
11ac-VHT20	MCS0	52	5260	21.81	17.967
11ac-VHT20	MCS0	60	5300	21.60	17.982
11ac-VHT20	MCS0	64	5320	21.47	17.894
11ac-VHT20	MCS0	100	5500	21.35	17.886
11ac-VHT20	MCS0	116	5580	21.58	17.899
11ac-VHT20	MCS0	140	5700	26.49	18.120
11ac-VHT20	MCS0	144	5720	28.21	18.169
11ac-VHT20	MCS0	149	5745	29.19	18.365
11ac-VHT20	MCS0	157	5785	32.84	18.448
11ac-VHT20	MCS0	165	5825	30.69	18.411

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11ac-VHT40	MCS0	38	5190	39.81	36.297
11ac-VHT40	MCS0	46	5230	41.27	36.340
11ac-VHT40	MCS0	54	5270	39.77	36.300
11ac-VHT40	MCS0	62	5310	39.80	36.314
11ac-VHT40	MCS0	102	5510	40.00	36.259
11ac-VHT40	MCS0	110	5550	40.07	36.360
11ac-VHT40	MCS0	134	5670	39.75	36.262
11ac-VHT40	MCS0	142	5710	60.13	36.799
11ac-VHT40	MCS0	151	5755	67.36	36.681
11ac-VHT40	MCS0	159	5795	66.30	36.670
11ac-VHT80	MCS0	42	5210	81.47	75.689
11ac-VHT80	MCS0	58	5290	81.12	75.715
11ac-VHT80	MCS0	106	5530	81.18	75.619
11ac-VHT80	MCS0	122	5610	94.89	75.933
11ac-VHT80	MCS0	138	5690	114.40	76.110
11ac-VHT80	MCS0	155	5775	117.30	76.195
11ax-HE20	MCS0	36	5180	21.38	19.047
11ax-HE20	MCS0	44	5220	21.37	19.005
11ax-HE20	MCS0	48	5240	21.36	19.027
11ax-HE20	MCS0	52	5260	21.13	19.032
11ax-HE20	MCS0	60	5300	21.35	19.061
11ax-HE20	MCS0	64	5320	21.44	19.026
11ax-HE20	MCS0	100	5500	21.65	19.040
11ax-HE20	MCS0	116	5580	21.66	19.001
11ax-HE20	MCS0	140	5700	21.58	19.045
11ax-HE20	MCS0	144	5720	24.71	19.150
11ax-HE20	MCS0	149	5745	29.11	19.185
11ax-HE20	MCS0	157	5785	30.84	19.234
11ax-HE20	MCS0	165	5825	26.07	19.168

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11ax-HE40	MCS0	38	5190	39.84	37.511
11ax-HE40	MCS0	46	5230	39.81	37.578
11ax-HE40	MCS0	54	5270	39.67	37.563
11ax-HE40	MCS0	62	5310	39.98	37.577
11ax-HE40	MCS0	102	5510	39.77	37.606
11ax-HE40	MCS0	110	5550	39.88	37.633
11ax-HE40	MCS0	134	5670	40.10	37.549
11ax-HE40	MCS0	142	5710	45.32	37.719
11ax-HE40	MCS0	151	5755	53.04	37.777
11ax-HE40	MCS0	159	5795	55.55	37.841
11ax-HE80	MCS0	42	5210	81.01	76.974
11ax-HE80	MCS0	58	5290	81.40	76.898
11ax-HE80	MCS0	106	5530	81.62	76.879
11ax-HE80	MCS0	122	5610	80.94	77.004
11ax-HE80	MCS0	138	5690	80.37	77.173
11ax-HE80	MCS0	155	5775	112.50	77.490

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	F_H (MHz)	Limit (MHz)
802.11a	6Mbps	48	5240	5248.41	< 5250
802.11ac-VHT20	MCS0	48	5240	5248.97	< 5250
802.11ac-VHT40	MCS0	46	5230	5248.17	< 5250
802.11ac-VHT80	MCS0	42	5210	5247.85	< 5250
802.11ax-HE20	MCS0	48	5240	5249.51	< 5250
802.11ax-HE40	MCS0	46	5230	5248.79	< 5250
802.11ax-HE80	MCS0	42	5210	5248.49	< 5250

Note: F_H = Centre frequency + 99% OBW / 2.

For example, 802.11a 5240MHz, F_H = 5240 MHz + 16.821 MHz / 2 = 5248.41 MHz.

802.11a 26dB & 99% Bandwidth	
Channel 36 (5180MHz)	Channel 44 (5220MHz)
	
Channel 48 (5240MHz)	Channel 52 (5260MHz)
	
Channel 60 (5300MHz)	Channel 64 (5320MHz)
	

Channel 100 (5500MHz)



Channel 116 (5580MHz)



Channel 140 (5700MHz)



Channel 144(5720MHz)



Channel 149 (5745MHz)

Channel 157 (5785MHz)

802.11a 26dB & 99% Bandwidth	
Channel 165 (5825MHz)	
	

802.11ac-VHT20 26dB & 99% Bandwidth

Channel 36 (5180MHz)



Channel 44 (5220MHz)



Channel 48 (5240MHz)



Channel 52 (5260MHz)

Channel 60 (5300MHz)



Channel 64 (5320MHz)



802.11ac-VHT20 26dB & 99% Bandwidth

Channel 100 (5500MHz)



Channel 116 (5580MHz)



Channel 140 (5700MHz)



Channel 144(5720MHz)

Channel 149 (5745MHz)



Channel 157 (5785MHz)

802.11ac-VHT20 26dB & 99% Bandwidth	
Channel 165 (5825MHz)	
	

802.11ac-VHT40 26dB & 99% Bandwidth

Channel 38 (5190MHz)



Channel 46 (5230MHz)



Channel 54 (5270MHz)



Channel 62 (5310MHz)



Channel 102 (5510MHz)



Channel 110 (5550MHz)

802.11ac-VHT40 26dB & 99% Bandwidth	
Channel 134 (5670MHz)	Channel 142(5710MHz)
	
Channel 151 (5755MHz)	Channel 159 (5795MHz)
	

802.11ac-VHT80 26dB & 99% Bandwidth	
Channel 42 (5210MHz)	Channel 58 (5290MHz)
	
Channel 106 (5530MHz)	Channel 122 (5610MHz)
	
Channel 138 (5690MHz)	Channel 155 (5775MHz)
	

802.11ax-HE20 26dB & 99% Bandwidth	
Channel 36 (5180MHz)	Channel 44 (5220MHz)
	
Channel 48 (5240MHz)	Channel 52 (5260MHz)
	
Channel 60 (5300MHz)	Channel 64 (5320MHz)
	

802.11ax-HE20 26dB & 99% Bandwidth

Channel 100 (5500MHz)



Channel 116 (5580MHz)



Channel 140 (5700MHz)



Channel 144(5720MHz)



Channel 149 (5745MHz)



Channel 157 (5785MHz)

802.11ax-HE20 26dB & 99% Bandwidth	
Channel 165 (5825MHz)	
	

802.11ax-HE40 26dB & 99% Bandwidth

Channel 38 (5190MHz)



Channel 46 (5230MHz)



Channel 54 (5270MHz)



Channel 62 (5310MHz)



Channel 102 (5510MHz)



Channel 110 (5550MHz)



802.11ax-HE40 26dB & 99% Bandwidth	
Channel 134 (5670MHz)	Channel 142(5710MHz)
	
Channel 151 (5755MHz)	Channel 159 (5795MHz)