

FCC PART 90 TEST REPORT

For

Northfield Telecommunications, Inc. d/b/a Advanced Wireless Communications

20809 Kensington Blvd, Lakeville, Minnesota, 55044-8385, USA

FCC ID: Q9SAWR4002

Report Type: Original Report	Product Type: Two-way radio
Test Engineer: Gavin Xu 	
Report Number: RDG160728007-00A	
Report Date: 2016-09-13	
Reviewed By: Ivan Cao Assistant Manager 	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliant Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §1.1310 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1046 & §90.205- RF OUTPUT POWER.....	9
APPLICABLE STANDARD	9
TEST PROCEDURE	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST DATA	10
FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST DATA	11
FCC §2.1049 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK	17
APPLICABLE STANDARD	17
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST PROCEDURE	18
TEST DATA	19
FCC §2.1051& §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	24
APPLICABLE STANDARD	24
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST PROCEDURE	25
TEST DATA	25
FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS	28
APPLICABLE STANDARD	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST PROCEDURE	28
TEST DATA	29
FCC §2.1055 & §90.213- FREQUENCY STABILITY.....	31
APPLICABLE STANDARD	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST PROCEDURE	31
TEST DATA	31

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR.....33

APPLICABLE STANDARD33

TEST EQUIPMENT LIST AND DETAILS.....33

TEST PROCEDURE33

TEST DATA34

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Northfield Telecommunications, Inc. d/b/a Advanced Wireless Communications* 's product, model number: AWR4000 (FCC ID: Q9SAWR4002) (the "EUT") in this report was a *Two-way radio*, which was measured approximately: 14.8 cm (L) x 5 cm (W) x 2.8 cm (H), rated input voltage: DC3.7 V from rechargeable Li-ion battery or DC6V charging from charger.

Adapter Information:

Model : SSA021F060080USD

Input : 100-240V~50-60Hz, 0.2A

Output : DC 6V, 0.8A

Note: The series product, models AWR4000 and AWR4002 are electrically identical, the differences between them are the model name, we selected AWR4000 for fully testing, the details were explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 160728007 (Assigned by BACL, Dongguan). The EUT was received on 2016-08-01.

Objective

This test report is prepared on behalf of *Northfield Telecommunications, Inc. d/b/a Advanced Wireless Communications* in accordance with Part 2, Part 90 of the Federal Communications Commission rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS submissions with FCC ID: Q9SAWR4002.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 90 – PRIVATE LAND MOBILE RADIO SERVICES

Applicable Standards: TIA-603-D.

All emissions measurement was performed and Bay Area Compliant Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliant Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliant Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in Compliant with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode.


EUT Specification:

Operating Frequency Band	450-470 MHz
Modulation Mode	FM
Channel Spacing	6.25 kHz, 12.5 kHz
Rated Output Power	High power level: 2.0 W Low power level: 1.0 W

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Pro instrument	DC Power Supply	pps3300	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
FCC§1.1310 & §2.1093	RF exposure	Compliant
§2.1046;§90.205	RF Output Power	Compliant
§2.1047;§90.207	Modulation Characteristic	Compliant
§2.1049;§90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliant
§2.1051;§90.210	Spurious Emission at Antenna Terminal	Compliant
§2.1053;§90.210	Spurious Radiated Emissions	Compliant
§2.1055; §90.213	Frequency Stability	Compliant
§90.214	Transient Frequency Behavior	Compliant

FCC §1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG160728007-20A.

FCC §2.1046 & §90.205- RF OUTPUT POWER**Applicable Standard**

FCC §2.1046 and §90.205.

Test Procedure

Conducted RF Output Power:

TIA-603-D section 2.2.1

Radiated method:

ANSI/TIA 603-D section 2.2.17

Spectrum Analyzer Setting:

R B/W	Video B/W
100 kHz	300 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(10dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
Giga	Signal Generator	1026	320408	2014-05-09	2015-05-09
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.6°C
Relative Humidity:	43 %
ATM Pressure:	99.8 kPa

The testing was performed by Gavin Xu on 2016-09-12.

Test Result: Compliant. Please refer to following tables

Conducted Power:

Modulation Mode	Channel Spacing	f_c	Conducted Output Power (W)		Note
		MHz	High Power Level	Low Power Level	
FM	12.5 kHz	450.0125	1.98	1.01	Not for FCC Review
		460.0125	2.06	1.02	/
		469.9875	2.03	1.00	/
	6.25 kHz	450.0125	2.01	1.00	Not for FCC Review
		460.0125	2.03	1.01	/
		469.9875	2.00	0.98	/

Note: the rated output power is 2.0 Watts.

ERP:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	
Channel Spacing: 12.5 kHz, High Power						
450.0125	V	110.47	31.7	0.0	0.7	31.0
460.0125	V	110.31	31.8	0.0	0.7	31.1
469.9875	V	110.26	32.1	0.0	0.7	31.4
Channel Spacing: 6.25 kHz, High Power						
450.0125	V	110.33	31.6	0.0	0.7	30.9
460.0125	V	109.89	31.4	0.0	0.7	30.7
469.9875	V	110.26	32.1	0.0	0.7	31.4

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain

FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC**Applicable Standard**

FCC§2.1047 & §90.207:

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Procedure

Test Method: TIA/EIA-603D 2.2.3

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	RF Communications Test Set	8920A	00 235	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(10dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.6°C
Relative Humidity:	43 %
ATM Pressure:	99.8 kPa


The testing was performed by Gavin Xu on 2016-09-12.

Test Result: Compliant. Please refer to following table and plots.

MODULATION LIMITING


Carrier Frequency: 460.0125 MHz, Channel Spacing = 12.5 kHz

Audio Frequency (Hz)	Instantaneous		Steady-state		Limit [kHz]
	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	
300	1.909	0.141	1.893	0.114	2.5
400	2.034	0.159	1.997	0.141	2.5
500	1.971	0.185	1.953	0.166	2.5
600	2.068	0.199	2.029	0.181	2.5
700	1.961	0.229	1.946	0.203	2.5
800	2.025	0.244	2.003	0.218	2.5
900	2.032	0.253	2.011	0.235	2.5
1000	2.053	0.278	2.029	0.253	2.5
1200	1.931	0.342	1.895	0.317	2.5
1400	2.055	0.362	2.031	0.337	2.5
1600	2.027	0.382	1.997	0.359	2.5
1800	2.117	0.446	2.097	0.426	2.5
2000	1.963	0.458	1.927	0.431	2.5
2200	1.941	0.472	1.905	0.447	2.5
2400	2.031	0.522	2.009	0.504	2.5
2600	1.743	0.514	1.721	0.489	2.5
2800	1.829	0.532	1.784	0.514	2.5
3000	1.652	0.498	1.612	0.476	2.5



Carrier Frequency: 460.0125 MHz, Channel Spacing = 6.25 kHz


Audio Frequency (Hz)	Instantaneous		Steady-state		Result
	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	
300	0.958	0.079	0.941	0.069	Pass
400	0.971	0.085	0.951	0.073	Pass
500	0.981	0.095	0.969	0.082	Pass
600	1.048	0.105	1.037	0.094	Pass
700	1.139	0.117	1.124	0.106	Pass
800	1.137	0.117	1.119	0.107	Pass
900	1.075	0.131	1.058	0.114	Pass
1000	1.047	0.135	1.031	0.119	Pass
1200	1.023	0.145	1.009	0.128	Pass
1400	1.028	0.154	1.012	0.142	Pass
1600	1.04	0.19	1.025	0.175	Pass
1800	1.056	0.224	1.043	0.211	Pass
2000	0.995	0.238	0.983	0.227	Pass
2200	1.002	0.232	0.989	0.219	Pass
2400	1.017	0.214	1.004	0.203	Pass
2600	0.911	0.21	0.896	0.196	Pass
2800	0.904	0.198	0.889	0.188	Pass
3000	0.798	0.198	0.784	0.179	Pass



Audio Frequency Response


Carrier Frequency: 460.0125 MHz, Channel Spacing = 12.5 kHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-10.66
400	-7.47
500	-5.35
600	-3.71
700	-2.43
800	-1.67
900	-0.94
1000	0.00
1200	2.11
1400	2.82
1600	3.63
1800	5.03
2000	5.17
2200	5.65
2400	6.64
2600	6.27
2800	6.74
3000	6.26



Carrier Frequency: 460.0125 MHz, Channel Spacing = 6.25 kHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-10.84
400	-7.71
500	-5.53
600	-3.72
700	-2.53
800	-1.86
900	-1.03
1000	0.00
1200	1.91
1400	2.41
1600	3.31
1800	5.02
2000	5.13
2200	5.39
2400	6.47
2600	6.68
2800	6.59
3000	6.23



Audio Frequency Low Pass Filter Response

Carrier Frequency: 460.0125 MHz, Channel Spacing = 12.5 kHz

Audio Frequency	Response Attenuation	Limit
kHz	dB	dB
3.0	-2.7	0.0
3.5	-9.2	-6.7
4.0	-15.1	-12.5
5.0	-25.4	-22.2
7.0	-39.3	-36.8
10.0	-55.2	-52.3
15.0	-72.8	-69.9
20.0	-85.6	-82.5
30.0	-85.5	-82.5
50.0	-85.8	-82.5
70.0	-85.4	-82.5



FCC §2.1049 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

Applicable Standard

FCC §2.1049, §90.209 and §90.210

Applicable Emission Masks

Frequency band (MHz)	Mask for equipment with audio low pass filter	Mask for equipment without audio low pass filter
Below 25	A or B	A or C
25-50	B	C
72-76	B	C
150-174	B, D, or E	C, D or E
150 paging only	B	C
220-222	F	F
421-512	B, D, or E	C, D, or E
450 paging only	B	G
806-809/851-854	B	H
809-824/854-869	B	G
896-901/935-940	I	J
902-928	K	K
929-930	B	G
4940-4990 MHz	L or M	L or M
5850-5925		
All other bands	B	C

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is the lesser attenuation.

(4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

Emission Mask E—6.25 kHz or less channel bandwidth equipment. For transmitters designed to operate with a 6.25 kHz or less bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 3.0 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least $30 + 16.67(f_d - 3 \text{ kHz})$ or $55 + 10 \log(P)$ or 65 dB, whichever is the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least $55 + 10 \log(P)$ or 65 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2016-05-09	2017-05-09
HP	RF Communications Test Set	8920A	00 235	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(10dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Test Data**Environmental Conditions**

Temperature:	28.6°C
Relative Humidity:	43 %
ATM Pressure:	99.8 kPa


The testing was performed by Gavin Xu on 2016-09-09.

Test Result: Compliant. Please refer to the following tables and plots.

Modulation Mode	Channel Spacing	f_c	99% Occupied Bandwidth	26 dB Bandwidth	Power level
		MHz	kHz	kHz	
FM	12.5 kHz	460.0125	10.20	10.40	High
			10.10	10.40	Low
	6.25 kHz	460.0125	5.10	5.30	High
			5.10	5.30	Low


FM Mode

Occupied Bandwidth –12.5kHz, 460.0125 MHz, High Power Level




Date: 9.SEP.2016 13:32:07

Emission Mask - Type D




Date: 9.SEP.2016 13:29:48

Occupied Bandwidth –12.5kHz, 460.0125 MHz, Low Power Level




Date: 9.SEP.2016 13:39:28


Emission Mask - Type D



Date: 9.SEP.2016 13:40:49


Occupied Bandwidth – 6.25kHz, 460.0125MHz, High Power Level

Date: 9.SEP.2016 13:33:43

Emission Mask - Type E


Date: 9.SEP.2016 13:35:02

Occupied Bandwidth –6.25kHz, 460.0125 MHz, Low Power Level



Date: 9.SEP.2016 13:38:04

Emission Mask - Type E



Date: 9.SEP.2016 13:36:55

FCC §2.1051& §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

Emission Mask E—6.25 kHz or less channel bandwidth equipment. For transmitters designed to operate with a 6.25 kHz or less bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 3.0 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least $30 + 16.67(f_d - 3 \text{ kHz})$ or $55 + 10 \log (P)$ or 65 dB, whichever is the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least $55 + 10 \log (P)$ or 65 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	831259/019	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(10dB)	53-20-34	LN749	2016-05-08	2017-05-08
Mini-Circuits	HIGH PASS FILTER	BHP-550+	YZU15801121	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Adjust the spectrum analyzer for the following settings:

- 1) Resolution Bandwidth = 100 kHz for spurious emissions below 1 GHz, and 1 MHz for spurious emissions above 1 GHz.
- 2) Video Bandwidth ≥ 3 times the resolution bandwidth.
- 3) Sweep Speed ≤ 2000 Hz per second.
- 4) Detector Mode = mean or average power.

Test Data**Environmental Conditions**


Temperature:	28.6°C
Relative Humidity:	43%
ATM Pressure:	99.8 kPa

The testing was performed by Gavin Xu on 2016-09-09.


Note: For conducted spurious emissions were tested at high rated power, which was the worst case. And there was a band reject filter between the EUT and test equipment when testing.

460.0125MHz – FM Mode, 12.5 kHz

Fundamental test
with Band Reject
Filter




Date: 9.SEP.2016 13:27:47




Date: 9.SEP.2016 13:26:54

460.0125 MHz – 4FSK Mode, 6.25 kHz



Date: 9.SEP.2016 13:24:41



Date: 9.SEP.2016 13:26:00

FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §2.1053 and §22.359 and §90.210

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Signal Generator	1026	320408	2015-11-23	2016-11-22
R&S	EMI Test Receiver	ESCI	100224	2016-08-03	2017-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
Mini-Circuits	HIGH PASS FILTER	BHP-550+	YZU15801121	2016-05-06	2017-05-06
Weinschel Corp	Terminal Load(100W)	1440-3	MD447	/	/

* **Statement of Traceability:** Bay Area Compliant Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

For part 90:

Spurious emissions in dB = $10 \log_{10}(\text{TXpwr in Watts}/0.001)$ - the absolute level

Spurious attenuation limit in dB = $50 + 10 \log_{10}(\text{power out in Watts})$ for EUT with a 12.5 kHz channel bandwidth.

Spurious attenuation limit in dB = $55 + 10 \log_{10}$ (power out in Watts) for EUT with a 6.25 kHz channel bandwidth.

Test Data

Environmental Conditions

Temperature:	30.6°C
Relative Humidity:	51%
ATM Pressure:	99.6kPa

The testing was performed by Gavin Xu on 2016-08-03

Test Mode: Transmitting (FM mode, high power level)

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 460.0125 MHz, Channel Spacing: 6.25 kHz								
920.025	H	37.76	-36.1	0.0	1	-37.1	-25.0	12.1
920.025	V	46.26	-24.3	0.0	1	-25.3	-25.0	0.3
1380.038	H	55.19	-45.3	8.8	1.4	-37.9	-25.0	12.9
1380.038	V	62.75	-37.6	8.8	1.4	-30.2	-25.0	5.2
1840.050	H	52.01	-47.8	11.4	1.3	-37.7	-25.0	12.7
1840.050	V	64.37	-35.4	11.4	1.3	-25.3	-25.0	0.3
2300.063	H	53.34	-42.9	11.2	2.3	-34.0	-25.0	9.0
2300.063	V	59.56	-36.2	11.2	2.3	-27.3	-25.0	2.3
2760.075	H	55.44	-42.2	13.1	2.3	-31.4	-25.0	6.4
2760.075	V	54.56	-43.8	13.1	2.3	-33.0	-25.0	8.0
3220.088	H	51.46	-46	13.6	2.2	-34.6	-25.0	9.6
3220.088	V	55.30	-41.4	13.6	2.2	-30.0	-25.0	5.0
3680.100	H	54.98	-40	14.0	2.3	-28.3	-25.0	3.3
3680.100	V	56.89	-37.7	14.0	2.3	-26.0	-25.0	1.0
4140.113	H	52.16	-42.5	13.8	2.9	-31.6	-25.0	6.6
4140.113	V	51.43	-42.8	13.8	2.9	-31.9	-25.0	6.9
4600.125	H	55.94	-36.8	14.2	2.7	-25.3	-25.0	0.3
4600.125	V	53.51	-40.1	14.2	2.7	-28.6	-25.0	3.6

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 460.0125 MHz, Channel Spacing: 12.5 kHz								
920.025	H	41.70	-32.2	0.0	1	-33.2	-20.0	13.2
920.025	V	44.77	-25.8	0.0	1	-26.8	-20.0	6.8
1380.038	H	55.45	-45.1	8.8	1.4	-37.7	-20.0	17.7
1380.038	V	64.16	-36.2	8.8	1.4	-28.8	-20.0	8.8
1840.050	H	55.37	-44.4	11.4	1.3	-34.3	-20.0	14.3
1840.050	V	69.29	-30.5	11.4	1.3	-20.4	-20.0	0.4
2300.063	H	53.23	-43	11.2	2.3	-34.1	-20.0	14.1
2300.063	V	56.96	-38.8	11.2	2.3	-29.9	-20.0	9.9
2760.075	H	54.43	-43.2	13.1	2.3	-32.4	-20.0	12.4
2760.075	V	54.64	-43.7	13.1	2.3	-32.9	-20.0	12.9
3220.088	H	51.77	-45.7	13.6	2.2	-34.3	-20.0	14.3
3220.088	V	56.37	-40.3	13.6	2.2	-28.9	-20.0	8.9
3680.100	H	53.77	-41.2	14.0	2.3	-29.5	-20.0	9.5
3680.100	V	56.24	-38.3	14.0	2.3	-26.6	-20.0	6.6
4140.113	H	53.78	-40.9	13.8	2.9	-30.0	-20.0	10.0
4140.113	V	54.96	-39.3	13.8	2.9	-28.4	-20.0	8.4
4600.125	H	57.93	-34.9	14.2	2.7	-23.4	-20.0	3.4
4600.125	V	52.90	-40.7	14.2	2.7	-29.2	-20.0	9.2

Note1: For radiated spurious emissions were tested at high rated power, which was the worst case.

Note2: The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.

Note3: Absolute Level = SG Level - Cable loss + Antenna Gain
Margin = Limit-Absolute Level

FCC §2.1055 & §90.213- FREQUENCY STABILITY

Applicable Standard

FCC §2.1055, §90.213

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-4	2015-09-10	2016-09-09
UNI-T	Multimeter	UT39A	M130199938	2016-04-10	2017-04-10
Weinschel Corp	Attenuator(10dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliant Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The power leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

Test Data

Environmental Conditions

Temperature:	28.6°C
Relative Humidity:	43 %
ATM Pressure:	99.8kPa

The testing was performed by Gavin Xu on 2016-09-09.

Test Mode: Transmitting

Reference Frequency: 460.0125MHz, 12.5 kHz, Limit: 2.5 ppm			
Temperature	Voltage	Reading	Frequency Error
°C	V _{DC}	MHz	ppm
-30	3.7	460.012533	0.07
-20		460.012529	0.06
-10		460.012539	0.08
0		460.012537	0.08
10		460.012531	0.07
20		460.012534	0.07
30		460.012525	0.05
40		460.012539	0.08
50		460.012537	0.08
25	3.5	460.012534	0.07
25	4.2	460.012532	0.07

Reference Frequency: 460.0125MHz, 6.25 kHz, Limit: 1.0ppm			
Temperature	Voltage	Reading	Frequency Error
°C	V _{DC}	MHz	ppm
-30	3.7	460.012542	0.09
-20		460.012558	0.13
-10		460.012559	0.13
0		460.012551	0.11
10		460.012548	0.10
20		460.012553	0.12
30		460.012556	0.12
40		460.012561	0.13
50		460.012542	0.09
25	3.5	460.012552	0.11
25	4.2	460.012555	0.12

Note: The extreme voltage is declared by the manufacturer.

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR

Applicable Standard

Regulations: FCC §90.214

Test method: ANSI/TIA-603-D 2010, section 2.2.19.3

Test Equipment List and Details


Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2016-05-09	2017-05-09
HP	Signal Generator	E4422B	MY41000355	2015-11-23	2016-11-22
Cheng Du Ou Li Tong	Two way power splitter	EMPD-T- 2-10-1000	OE01201041	2016-05-06	2017-05-06
Weinschel Corp	Attenuator(10dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

* Statement of Traceability: Bay Area Compliant Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- Connect the EUT and test equipment as shown on the following block diagram.
- Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- Turn on the transmitter.
- Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P_0 .
- Turn off the transmitter.
- Adjust the RF level of the signal generator to provide RF power equal to P_0 . This signal generator RF level shall be maintained throughout the rest of the measurement.
- Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ± 4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to "Video", and tune the "trigger level" on suitable level. Then set the "trigger offset" to -10ms for turn on and -15ms for turn off.
- Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on} . The trace should be maintained within the allowed divisions during the period t_1 and t_2 .

- k) Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t_3 .



Test Data

Environmental Conditions


Temperature:	28.6°C
Relative Humidity:	43 %
ATM Pressure:	99.8kPa

The testing was performed by Gavin Xu on 2016-09-09.


Channel Spacing (kHz)	Transient Period (ms)	Maximum frequency difference	Result
6.25	$<10(t_1)$	± 6.25 kHz	Pass
	$<25(t_2)$	± 3.125 kHz	
	$<10(t_3)$	± 6.25 kHz	
12.5	$<10(t_1)$	± 12.5 kHz	Pass
	$<25(t_2)$	± 6.25 kHz	
	$<10(t_3)$	± 12.5 kHz	

Please refer to the following plots.


Turn on – 460.0125 MHz, 12.5 kHz, High Power




Turn off – 460.0125 MHz, 12.5 kHz, High Power



Turn on – 460.0125 MHz, 6.25 kHz, High Power



Turn off – 460.0125 MHz, 6.25 kHz, High Power



***** END OF REPORT *****