

Test Report No.:
FCC2021-0032-DFS

RF Test Report

EUT : Promethean WIFI Module (Titanium)
MODEL : AP-WIFI-BC
BRAND NAME : Promethean
APPLICANT : Promethean Limited
Classification Of Test : N/A

CVC Testing Technology Co., Ltd.



Client	Name : Promethean Limited		
	Address : Promethean House,Lower Philips Rd,whitebirk Industrial Estate,Blackburn,Bb1 5th United Kingdom		
Manufacturer	Name : Guangzhou Lango Electronics Technology Co.,Ltd.		
	Address : 4/f. NO.136. Gaopu Road. Tianhe District. Guangzhou. 510663. P.R. China		
Equipment Under Test	Name : Promethean WIFI Module (Titanium)		
	Model/Type: AP-WIFI-BC		
	Trade mark : Promethean		
	SerialNO.:N/A		
	Sampe NO.:3-1		
Date of Receipt.	2021.11.08	Date of Testing	2021.11.08 ~ 2021.12.17
Test Specification			Test Result
FCC Part 15, Subpart E, Section 15.407 KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02 KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r02			PASS
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied.		
	Issue Date: 2021.12.17		
Tested by:	Reviewed by:	Approved by:	
Xu ZhenFei Name Signature	Liu YongHai Name Signature	Chen HuaWen Name Signature	
Other Aspects: NONE.			
Abbreviations:OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

1 SUMMARY OF TEST RESULTS.....	5
1.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
1.2 TEST LOCATION.....	6
2 GENERAL INFORMATION.....	7
2.1 GENERAL PRODUCT INFORMATION.....	7
2.2 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	7
2.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	7
2.4 DESCRIPTION OF SUPPORT UNITS.....	8
3 REQUIREMENTS AND PARAMETERS FOR DFS TEST.....	9
3.1 APPLICABILITY OF DFS REQUIREMENTS.....	9
3.2 DETECTION THRESHOLD VALUES.....	10
3.3 DFS RESPONSE REQUIREMENT VALUES.....	10
3.4 PARAMETERS OF DFS TEST SIGNALS.....	11
4 TEST RESULTS.....	12
4.1 TEST SETUP OF DFS.....	12
4.2 DFS DETECTION THRESHOLD.....	13
4.3 CHANNEL LOADING.....	14
4.4 CHANNEL CLOSING TRANSMISSION AND CHANNEL MOVE TIME.....	15
4.5 NON- OCCUPANCY PERIOD.....	16
5 PHOTOGRAPHS OF THE EUT.....	18



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCC2021-0032-DFS	Original release	2021.12.17



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

FCC STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.407	Channel Move Time	PASS	8.203 sec
15.407	Channel Closing Transmission Time	PASS	200+aggregate of 23.4ms over remaining 10s period.
15.407	Non-Occupancy Period and Client Beacon Test	PASS	≥30 min

Note: Since the product is client without radar detection function, only Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period and Client Beacon Test are required to be performed



1.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Antenna Port Conducted Test				
Equipment	Model No.	Serial Number	Manufacturer	Cal. Due
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 30	104408	2022.5.09
#3Shielding room	MORI	443	N/A	2023.5.19
Analog signal Generator(100kHz ~ 40GHz)	Rohde&Schwarz	SMB 100A	181934	2022.5.09
Vector signal Generator(9kHz ~ 6GHz)	Rohde&Schwarz	SGT 100A	111724	2022.5.09
RF control unit(BT/WiFi)	Tonscend	JS0806-2-8CH	20E8060261	2022.5.09
DC power supply	Rohde&Schwarz	HMC8041-G	101206	2022.5.09
Temperature and humidity meter	/	C193561457	C193561457	2022.5.24

1.2 TEST LOCATION

The tests and measurements refer to this report were performed by EMC testing Lab. of CVC Testing Technology Co., Ltd.

Address: No.3,TiantaiyiRoad,KaitaiAvenue,ScienceCity,Guangzhou,China

Post Code: 510663 Tel: 020-32293888

FAX: 020-32293889 E-mail: office@cvc.org.cn

Test Firm Registration Number: 937273

CN Number: 26239 Wireless Test Site Registration Number : CN0103



2 GENERAL INFORMATION

2.1 GENERAL PRODUCT INFORMATION

PRODUCT	Promethean WIFI Module (Titanium)
BRAND	Promethean
MODEL	AP-WIFI-BC
ADDITIONAL MODEL	N/A
FCC ID	QAM-AP-WIFI-BC
POWER SUPPLY	DC 12V From Host Unit
OPERATING FREQUENCY	5250 – 5350MHz, 5470~5725MHz
ANTENNA TYPE	5250 – 5350MHz, External antenna, 4.95dBi Gain 5470 ~ 5725MHz, External antenna, 4.95dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A
Remark: 1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. EUT photo refer to the attached file (External Photos report and Internal Photos report)	

2.2 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC Part 15, Subpart E, Section 15.407

KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r02

All test items have been performed and recorded as per the above standards

2.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

BANDWIDTH	CHANNEL	TEST TYPE AND LIMIT
80MHz	CH106	Channel Move Time
		Channel Closing Transmission Time
		Non-Occupancy Period and Client Beacon Test

This test was investigated for different bandwidth (20MHz, 40MHz and 80MHz). The following plots was done on 80MHz as a representative



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support Equipment							
NO	Description	Brand	Model No.	Serial Number	Supplied by		
1	Flat Panel Monitor	DELL	U2720QM	CN-043V8R-WSL00-07D-403L-A02	Lab		
2	Adapter	GSP	GSCV2000S012 V24V	G1087-V1	Lab		
3	Wireless router	ZTE	MF282	N/A	Lab		
Support Cable							
NO	Description	Quantity (Number)	Length (m)	Detachable (Yes/ No)	Shielded (Yes/ No)	Cores (Number)	Supplied by
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A



3 REQUIREMENTS AND PARAMETERS FOR DFS TEST

3.1 APPLICABILITY OF DFS REQUIREMENTS

APPLICABILITY OF DFS REQUIREMENTS PRIOR TO USE A CHANNEL

REQUIREMENT	OPERATIONAL MODE		
	MASTER	CLIENT WITHOUT RADAR DETECTION	CLIENT WITH RADAR DETECTION
Non-Occupancy Period	✓	✓	✓
DFS Detection Threshold	✓	Not required	✓
Channel Availability Check Time	✓	Not required	Not required
Uniform Spreading	✓	Not required	Not required
U-NII Detection Bandwidth	✓	Not required	✓

APPLICABILITY OF DFS REQUIREMENTS DURING NORMAL OPERATION

REQUIREMENT	OPERATIONAL MODE		
	MASTER	CLIENT WITHOUT RADAR DETECTION	CLIENT WITH RADAR DETECTION
DFS Detection Threshold	✓	Not required	✓
Channel Closing Transmission Time	✓	✓	✓
Channel Move Time	✓	✓	✓
U-NII Detection Bandwidth	✓	Not required	✓



3.2 DETECTION THRESHOLD VALUES

DFS DETECTION THRESHOLDS FOR MASTER DEVICES AND CLIENT DEVICES WITH RADAR DETECTION

MAXIMUM TRANSMIT POWER	VALUE (SEE Note 1 and 2)
≥ 200 milliwatt	-64 dBm
< 200 milliwatt	-62 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

3.3 DFS Response Requirement Values

PARAMETER	VALUE
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	100% of the UNII transmission power bandwidth. See Note 3.

Note 1: The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:

- For the Short Pulse Radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar Burst generated.
- For the Long Pulse Radar Test Signal this instant is the end of the 12 second period defining the Radar Waveform.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 1 is used and for each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.



3.4 PARAMETERS OF DFS TEST SIGNALS

Step intervals of 0.1 microsecond for Pulse Width, 1 microsecond for PRI, 1 MHz for chirp width and 1 for the number of pulses will be utilized for the random determination of specific test waveforms.

Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A Test B	$\text{Roundup} \left\{ \begin{array}{l} \left(\frac{1}{360} \right) \cdot \\ \left(\frac{19 \cdot 10^9}{\text{PRI}_{\mu\text{sec}}} \right) \end{array} \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

LONG PULSE RADAR TEST WAVEFORM


RADAR TYPE	PULSE WIDTH (μsec)	CHIRP WIDTH (MHz)	PRI (μsec)	NUMBER OF PULSES PER BURST	NUMBER OF BURSTS	MINIMUM PERCENTAGE OF SUCCESSFUL DETECTION	MINIMUM NUMBER OF TRIALS
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

FREQUENCY HOPPING RADAR TEST WAVEFORM

RADAR TYPE	PULSE WIDTH (μsec)	PRI (μsec)	PULSES PER HOP	HOPPING RATE (kHz)	HOPPING SEQUENCE LENGTH (msec)	MINIMUM PERCENTAGE OF SUCCESSFUL DETECTION	MINIMUM NUMBER OF TRIALS
6	1	333	9	0.333	300	70%	30


4 TEST RESULTS

4.1 Test Setup of DFS




4.2 DFS Detection Threshold

The Required detection threshold is $-59.05.00\text{dBm} = -64 + 4.95\text{dBi}$. The conducted radar burst level is set to -59.39dBm .



4.3 Channel loading

The radar signal was the same as transmitted channels, and injected into the antenna port of AP (master) with radar signal, measured the channel shutdown. The slave transmitted the test data to master, the transmitted duty cycle is 20.413%.




Note: Traffic signal: from slave transmit to master.



4.4 Channel Closing Transmission and Channel Move Time

Radar Signal 0




NOTE:

- 1.T0 denotes the Start of Rader Singnl Time.
- 2.T1 denotes the Start of Channel Move Time.
- 3.T2 denotes the Start of Channel Move Time + 200ms.
- 4.T3 denotes the End of Channel Move Time.
- 5.Per Bin Time = Sweep time (13000ms) / Sweep Point Bins (10000)
- 6.Channel Closing Transmission Time(200 + 0ms) = 200+ ON Bins* Per Bin Time



4.5 Non-Occupancy Period

- 1) Test results demonstrating an associated client link is established with the master on a test frequency
- 2) The client and DFS-certified master device are associated, and system testing will be performed with channel-loading for a non-occupancy period test.
- 3). The device transmits one type of radar as specified in the DFS Order.
- 4) The test frequency has been monitored to ensure no transmission of any type has occurred for 30 minutes;
Note: If the client moves with the master, the device is considered compliant if nothing appears in the client non-occupancy period test. For devices that shut down (rather than moving channels), no beacons should appear;
- 5)An analyzer plot that contains a single 30-minute sweep on the original test frequency.






Master was off.

During the 30 minutes observation time, The UUT did not make any transmissions in the DFS band after UUT power up

NON-ASSOCIATED TEST





5 PHOTOGRAPHS OF THE EUT

Please refer to the attached file (External Photos report and Internal Photos).

Important

- (1) The test report is valid with the official seal of the laboratory and the signatures of Test engineer, Author and Reviewer simultaneously.
- (2) The test report is invalid if altered.
- (3) Any photocopies or part photocopies in the test report are forbidden without the written permission from the laboratory.
- (4) Objections to the test report must be submitted to the laboratory within 15 days.
- (5) Generally, commission test is responsible for the tested samples only.

Address of the laboratory:

CVC Testing Technology Co., Ltd.

Address: No.3, Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, China

Post Code: 510663 Tel: 020-32293888

FAX: 020-32293889 E-mail: office@cvc.org.cn