

Blade 2 Antenna Regulatory Infomation

Description : Triple-band Antenna(Main+Aux)
Samsung Electronics CO., LTD P/N: BA42-00045A / BA42-00047A
BA42-00046A/ BA42-00048A

Wistron NeWeb P/N: 81.CAO15.001/81.CAO15.005
81.CAO15.002/ 81.CAO15.006
81.CAO15.003/81.CAO15.007
81.CAO15.004/81.CAO15.008

Wistron NeWeb Corporation

**No. 10-1,Li-hsin Road I,
Science-base Industrial Park,
Hsinchu 300,Taiwan, R.O.C.
Tel: 886-3-6667799#6545
Fax: 886-3-6667711**

Provided by Wistron NeWeb Corp.	Reviewed by Wistron NeWeb Corp.
<i>Justin Chang</i>	<i>Weili Cheng</i>

I. Antenna Type

Position	Main Antenna (Right-side Antenna)	Aux Antenna (Left-side Antenna)
Antenna Type	PIFA	PIFA
Material	Metal sheet	Metal sheet

Peak Gain

Antenna Gain		2G4 ISM (2.400 GHz - 2.4835 GHz)			U-NII (4.90 GHz - 5.350 GHz)			HyperLAN (5.470 GHz - 5.825 GHz)		
		2.40 GHz	2.45 GHz	2.50 GHz	4.9 GHz	5.15 GHz	5.35 GHz	5.47 GHz	5.6475 GHz	5.825 GHz
Aux	Peak dBi	1.22	1.03	1.03	1.52	1.35	1.34	2.36	1.76	1.48
	Avg dBi	-1.44	-1.67	-1.43	-2.03	-2.75	-2.61	-2.00	-2.16	-2.04
Main	Peak dBi	1.04	1.04	1.15	2.64	2.43	2.22	3.20	3.07	2.20
	Avg dBi	-1.45	-1.54	-1.39	-1.77	-1.59	-2.04	-1.17	-1.24	-1.38

II. Antenna Model Number

Model number: CAO-S

III. Manufacturing Info


Wistron NeWeb Corporation
No. 10-1, Li-hsin Road I,
Science-base Industrial Park,
Hsinchu 300, Taiwan, R.O.C.

IV. Antenna Dimensions (Mechanical drawings) (See Next 8 Pages)

單位: mm

Item	Parts Description	Material	Vendor	Item	Parts Description	Amount	Material	Color	P/N	Vendor
A	助焊劑	NC--700	旺興達	C	0.88D Ø 1.37mm	1	Cable	White	J12B1481-3	Junkosha
B	錫 條	Sn63/37	星光	D	MMCX Jack connector	1	銅鍍金	Golden	25-122A (第二代)	Aliner

E	Ø2.5mmShrink Tube	1	橡 膠	Black		長葆
F	Connector	1	銅鍍金	Golden	20278-101R-32	I-PEX



	記號	變更內容	年月日	氏名	檢印		

品名	WN-MMCX(母)-1.37W-IPEX-240mm-015			圖番	WN-MMCX(母)-1.37W-IPEX-240mm-015
	客戶	Wistron NeWeb Corp.		料號	
設計	制圖	驗圖	承認	材料	Coaxial Cable
啓基	曹敏			顏色	White
				日期	2003.03.27
版本號: A.0				副本號:	


注: 1. 加裝連接器時需準確對齊使用專用具嵌合、在治具上需探知中心導體位置是否正確.

2. 外觀上不允許有割痕、被覆脫落...等現象發生.

單位: mm

Item	Parts Description	Material	Vendor	Item	Parts Description	Amount	Material	Color	P/N	Vendor
A	助焊劑	NC-700	旺興達	C	0.88D ϕ 1.37mm	1	Cable	Black	J12B1481-3	Junkosha
B	錫 條	Sn63/37	星光	D	MMCX Plug connector	1	銅鍍金	Golden	25-122A (第二代)	Aliner

E	ϕ 2.5mmShrink Tube	1	橡 膠	Black		長葆
F	Connector	1	銅鍍金	Golden	20278-101R-32	1-PEX



記號	變更內容	年月日	氏名	檢印	


品名	WN-MMCX(子)-1.37B-1PEX-219mm-016		圖番	WN-MMCX(子)-1.37B-1PEX-219mm-016	
客戶	Wistron NeWeb Corp.		料號		
設計	制圖	驗圖	承認	材料	Coaxial Cable
啓碁	曹敏			顏色	Black
			日期	2003.03.27	

版本號: A.0		副本號:
----------	--	------

- 注: 1. 加裝連接器時需準確對齊使用專用治具嵌合、在治具上需探知中心導體位置是否正確.
2. 外觀上不允許有割痕、被覆脫落...等現象發生.


PART NUMBER BLOCK	
PART NUMBER	REV
57.CA015.003	0A

REVISIONS		
REV	DESCRIPTION	DATE
0A	APPROVE SHEET	04/15/03



YEAR _____
MONTH _____
DATE _____
SERIAL NO. _____
VER NO. _____

DETAIL OF LABEL
SCALE : 2/1



		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN mm AND TOLERANCES ARE:							
		INTEGRAL DIMENSIONS ± 0.12		ANGULAR DIMENSIONS ± 1°					
		1 PLACE DECIMAL ± 0.15		HOLES UNDER Ø5.00 ± 0.05					
		2 PLACE DECIMALS ± 0.10							
		MATERIAL: NA				DWG TITLE			
		FINISH: NA				OUTLINE, RIGHT-2, CAO-S			
		THIRD ANGLE PROJECTION		DRAWN	ARSENE YU	04/15/03		SIZE	DWG NO.
91.CA015.003	CAO-S			ENGR	ARSENE YU	04/15/03		A4	57.CA015.003
NEXT ASSY	USED ON			APVD				SCALE	1/1
APPLICATION								SHEET	1 OF 1





啟碁科技股份有限公司

No. 10-1, Li-hsin Road 1, Science-based Industrial Park,
Hsinchu 300, Taiwan, R.O.C.
Tel: 886-3-6667799 Fax: 886-3-6667711

PART NUMBER BLOCK	
PART NUMBER	REV
57.CA015.004	0A

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
0A	APPROVE SHEET	04/15/03	



CABLE LENGTH : 490±3
COLOR : BLACK


MOLEX CONNECTOR

CUSTOMER P/N

YEAR
MONTH
DATE
SERIAL NO.
VER NO.

XXXX-XXXXXX
XXXXXX XXXXX X11

DETAIL OF LABEL
SCALE : 2/1



		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN .mm AND TOLERANCES ARE:		DRAWN		SIZE		DWG NO.		REV	
		1 PLACE DECIMAL ± 0.2		ENGR		A4		57.CA015.004		0A	
		2 PLACE DECIMALS ± 0.10		ARSENE YU							
		ANGULAR DIMENSIONS ± 1°		ARSENE YU							
		HOLES UNDER Ø5.00 ± 0.05		ARSENE YU							
		MATERIAL: NA		04/15/03							
		FINISH: NA		04/15/03							
		THIRD ANGLE PROJECTION		SCALE							
				APVD							
				APPLICATION							
				CAO-S							
				USED ON							
				NEXT ASSY							
				APPLICATION							


Wistron
Wistron NewWeb Corp.
No. 10~11, U-Tsai Road I, Science-based Industrial Park,
Hsinchu 300, Taiwan, R.O.C.
Tel: 886-3-6667739 Fax: 886-3-6667711

OUTLINE, LEFT-2, CAO-S

SCALE 1/1 SHEET 1 OF 1

單位: mm				Item	Parts Description	Material	Vendor	Item	Parts Description	Amount	Material	Color	P/N	Vendor
				A	助焊劑	NC--700	旺興達	C	0.88DØ1.37mm	1	Cable	White	J12B1481-3	Junkosha
				B	錫 條	Sn63/37	星光	D	MMCX Jack connector	1	銅鍍金	Golden	25-122A (第二代)	Molex

E	Ø2.5mmShrink Tube	1	橡 膠	Black		長葆
F	Connector	1	銅鍍金	Golden	20278-101R-32	I-PEX




- 注: 1．加裝連接器時需準確對齊使用專用具嵌合、在治具上需探知中心導體位置是否正確.
- 2．外觀上不允許有刮痕、被覆脫落...等現象發生．

品名		WN-MMCX(母)-1.37W-IPEx-240mm-026		圖 番	WN-MMCX(母)-1.37W-IPEx-240mm-026	
客戶		Wistron NeWeb Corp.		料號		
設計	制圖	驗圖	承認	材料	Coaxial Cable	
啓碁				顏色	White	
				日期	2003.04.15	
版本號: A.0					副本號:	

單位: mm

Item	Parts Description	Material	Vendor	Item	Parts Description	Amount	Material	Color	P/N	Vendor
A	助焊劑	NC-700	旺興達	C	0.88D ϕ 1.37mm	1	Cable	Black	J12B1481-3	Junkosha
B	錫 條	Sn63/37	星光	D	MMCX Plug connector	1	銅鍍金	Golden	25-122A (第二代)	Molex

E	ϕ 2.5mmShrink Tube	1	橡 膠	Black		長葆
F	Connector	1	銅鍍金	Golden	20278-101R-32	I-PEX




- 注: 1. 加裝連接器時需準確對齊使用專用治具嵌合、在治具上需探知中心導體位置是否正確.
2. 外觀上不允許有割痕、被覆脫落...等現象發生.

品名	WN-MMCX(子)-1.37B-IPEX-219mm-025	圖番	WN-MMCX(子)-1.37B-IPEX-219mm-025				
客戶	Wistron NeWeb Corp.	料號		年月日	氏名	檢印	
設計	制圖	驗圖	承認	材料	Coaxial Cable		
啓碁	曹敏			顏色	Black		
		日期	2003.04.15				
版本號: A.0				副本號:			

單位: mm


Item	Parts Description	Amount	Material	Color	P/N	Vendor
C	0.88Dø 1.37mm	1	Cable	White	J12B1481-3	Junkosha
D	MMCX Jack connector	1	銅鍍金	Golden	25-122A (第二代)	Aliner
E	ø 2.5mmShrink Tube	1	橡 膠	Black		長葆
F	Connector	1	銅鍍金	Golden	U.FL-JP-088-A-240	HRS



	記號	變更內容	年月日	氏名	檢印			
品名	C A9106157			圖 番	C A9106157			
客戶	Wistron NeWeb Corp.			料號				
設計	制圖	驗圖	承認	材料	Coaxial Cable			
啓基	曹敏			顏色	White			
				日期	2003.03.27			
版本號: A.0					副本號:			

單位: mm


Item	Parts Description	Amount	Material	Color	P/N	Vendor
C	0.88D Ø 1.37mm	1	Cable	Black	J12B1481-3	Junkosha
D	MMCX Plug connector	1	銅鍍金	Golden	73415-4650 (第二代)	Molex
E	Ø 2.5mm Shrink Tube	1	橡 膠	Black		長 葆
F	Connector	1	銅鍍金	Golden	U.FL-JP-088-A-560	HRS



品名	C A9106157	圖番	C A9106157	料號	Coaxial Cable	顏色	Black	日期	2003.03.27	版本號: A.0	副本號:								
												客戶	Wistron NeWeb Corp.	設計	制圖	驗圖	承認		
																		啓基	曹敏
記號	變更內容	年月日	氏名	檢印															

單位: mm

Item	Parts Description	Amount	Material	Color	P/N	Vendor
C	0.88Dø 1.37mm	1	Cable	White	J12B1481-3	Junkosha
D	MMCX Jack connector	1	銅鍍金	Golden	73415-4640 (第二代)	Molex
E	ø 2.5mmShrink Tube	1	橡 膠	Black		長葆
F	Connector	1	銅鍍金	Golden	U-FL-LP-088-A-240	HRS



	記號	變更內容	年月日	氏名	檢印				
品名	C A9106157			圖番	C A9106157				
客戶	Wistron NeWeb Corp.			料號					
設計	制圖	驗圖	承認	材料	Coaxial Cable				
啓碁	曹敏			顏色	White				
				日期	2003.03.27				
版本號: A.0				副本號:					

V. Pictures of Antennas

Aux Antenna (LCD Side)	Main Antenna (LCD Side)
	
Aux System Cable	Main System Cable
	

VI. Cable Length

Left-side antenna(Aux): 490mm Φ 1.37mm(LCD Side)+219mm Φ 1.37mm(System Side)
Right-side antenna(Main): 325mm Φ 1.37mm(LCD Side)+240mm Φ 1.37mm(System Side)
(From the center of connector to the end of cable)

VII. Cable Loss (including connector)

Unit: dB	2G4 band	U-NII band	HyperLAN band
Left Side	2.12	3.34	3.64
Right Side	1.73	2.75	2.92

XI. Antenna Material





Main antenna	Aux antenna
1. Stamped metal 2. Junkosha cable and MMCX connector 3. Junkosha cable and IPEX connector (Junkosha cable and HRS connector)	1. Stamped metal 2. Junkosha cable and MMCX connector 3. Junkosha cable and IPEX connector (Junkosha cable and HRS connector)

X. Connector Info (general description)


Description (Cable)	Inner Conductor: AWG#30(7/0.102), Silver plating annealed copper wire Dielectric core: D0.88mm Outer conductor: 16/5/0.05 D1.13mm, Silver plating annealed copper wire Jacket: D1.37mm		
Requirements	Characteristic impedance: 50(+2,-2)ohm Nominal capacitance: 97pF/m Conductor resistance of inner conductor at 330K(20°C): 1000ohm/km MAX Insulation resistance: 1000mega-ohm.km MIN Dielectric withstand voltage: no breakdown at AC1000V for 1min.		
Ratings	Rated voltage: AC60Vrms Nominal characteristics impedance: 50ohm VSWR: 1.3MAX DC~3GHz, 1.7MAX 3~6GHz		
Electric characteristics	Contact resistance	10mA MAX(DC or 1000Hz)	Center contact 74mohm MAX. Outer contact 27mohm MAX.
	Insulation resistance	100V DC	500Mohm MIN
	Voltage proof	200V AC for 1 min. Current leakage 2mA MAX	No flashover or breakdown

Platform: BladII-Latitude LCD module
Supplier: Wistron NeWeb coporation
Date: 2003/4/15

2G4 ISM (2.400 GHz - 2.4835 GHz) Antenna Radiation Patterns



2G4 ISM (2.400 GHz - 2.4835 GHz)			
CONFIG	FREQ GHz	Avg dBi	Pk dBi
Left Horz	2.4	-3.22	0.77
	2.45	-3.33	0.61
	2.5	-3.01	1.01
Left Vert	2.4	-3.59	-0.34
	2.45	-4.03	-0.07
	2.5	-3.88	0.58
Right Horz	2.4	-2.96	0.90
	2.45	-3.21	1.02
	2.5	-3.01	0.45
Right Vert	2.4	-3.75	-1.13
	2.45	-3.83	0.34
	2.5	-3.37	0.26







VSWR open = lid/keyboard angle 110°


Note: The outer circle approximately represents the 0 dBi gain circle.

Platform: BladII-Latitude LCD module
Supplier: Wistron NeWeb coporation
Date: 2003/4/15

U-NII (5.150 GHz - 5.350 GHz) Antenna Radiation Patterns



U-NII (4.90 GHz - 5.350 GHz)			
CONFIG	FREQ GHz	Avg dBi	Pk dBi
Left Horz	4.9	-4.18	0.94
	5.15	-6.29	-0.94
	5.35	-5.33	0.10
Left Horz	4.9	-3.85	0.80
	5.15	-3.79	1.34
	5.35	-4.05	0.87
Right Horz	4.9	-3.36	2.64
	5.15	-3.47	2.41
	5.35	-3.89	2.20
Right Horz	4.9	-3.36	-0.09
	5.15	-3.86	1.41
	5.35	-3.36	0.55




VSWR open = lid/keyboard angle 110°

Note: The outer circle approximately represents the 0 dBi gain circle.


Platform: BladII-Latitude LCD module
Supplier: Wistron NeWeb coporation
Date: 2003/4/15

HyperLAN (5.470 GHz - 5.725 GHz) Antenna Radiation Patterns


Left Horizontal




Left Vertical




Right Horizontal



Right Vertical



HyperLAN (5.470 GHz - 5.825 GHz)			
CONFIG	FREQ GHz	Avg dBi	Pk dBi
Left Horz	5.47	-5.23	1.14
	5.6475	-5.53	-0.30
	5.825	-5.62	0.31
Left Horz	5.47	-3.14	2.35
	5.6475	-3.19	1.76
	5.825	-3.01	1.48
Right Horz	5.47	-3.31	3.19
	5.6475	-3.87	1.25
	5.825	-4.02	2.01
Right Horz	5.47	-3.22	2.05
	5.6475	-2.74	3.06
	5.825	-2.91	2.08



VSWR open = lid/keyboard angle 110°

Note: The outer circle approximately represents the 0 dBi gain circle.