



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AF012608-001 Date : 2005 June 09

Application No. : LF208001(0)

Client : Kid Galaxy Inc.
One Sundial Ave,
Suite 310 Manchester,
NH 03103, U.S.A.

Sample Description : One(1) submitted sample stated to be RC Buggies - Caterpillar
of Model No. 10412
Rating : 2 x 1.5V AAA size batteries
No. of submitted sample : Two (2) piece (s)***

Date Received : 2005 May 13

Test Period : 2005 May 13 – 2005 May 31

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – July 2004
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Daisy Chui
EMC Engineer - EL. Division

Page 1 of 11

FCC ID : QEA104124-9T

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing,
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test.....	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document.....	10
5.1	Bandwidth.....	10
5.2	Duty Cycle.....	10
6	Appendices.....	11



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for RC Buggies – Caterpillar. Operating at 49.860 MHz which is controlled by a crystal. The EUT is powered by 2 x 1.5V AAA size battery. Once it turn on, it will transmit a radio signal to the receiver.

The brief circuit description is listed as follows :

- X1, Q3 and associated circuit act as local oscillator.
- Q1 and associated circuit act as RF amplifier.
- U1 and associated circuit act as control signal encoder.



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	2GB05000535-0001



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart C**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
49.860	V	62.0	10.3	-6.0	66.3	80.0	-13.7
99.720	H	10.9	9.2	-	20.1	43.5	-23.4
149.580	H	9.3	11.9	-	21.2	43.5	-22.3
199.440	H	13.2	9.2	-	22.4	43.5	-21.1
* 249.300	H	13.3	9.7	-	23.0	46.0	-23.0
299.160	H	9.5	13.9	-	23.4	46.0	-22.6
349.020	H	8.2	14.9	-	23.1	46.0	-22.9
398.880	H	9.7	14.9	-	24.6	46.0	-21.4
448.740	H	7.1	17.7	-	24.8	46.0	-21.2
498.600	H	8.0	17.7	-	25.7	46.0	-20.3



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt 2.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10 kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26 dB below the carrier level. It meets the requirement of Section 15.235(b).

a. Duty Cycle

The duty cycle is simply the on-time divided by the period :

The duration of one cycle = 1 ms

Effective period of the cycle = 0.5 ms x 1

= 0.5 ms

Duty Cycle = 0.5 ms / 1 ms

= 0.5

Therefore, the average factor is found by $20 \log_{10} 0.5 = -6.0 \text{ dB}$



TEST REPORT

Report No. : AF012608-001

Date : 2005 June 09

6 Appendices

A1	Photos of the set-up of Radiated Emissions	1 page
A2	Photos of External Configurations	1 page
A3	Photos of Internal Configurations	1 page
A4	ID Label/Location	1 page
A5	Bandwidth Plot	1 page
A6	Average Factor	2 pages
A7	Block Diagram	1 page
A8	Schematics Diagram	1 page
A9	User Manual	1 page
A10	Operation Description	1 page

***** End of Report *****