

FCC PART 15.227 EMI MEASUREMENT AND TEST REPORT

For

Newmen Technology Corp., Ltd.

No.1 Newmen Road, TongSheng Village, LongHua, ShenZhen, China

FCC ID: QF5MS-037OR

April 22, 2005

This Report Concerns: ☒ Original Report	Equipment Type: Transmitter, Wireless Mouse
Test Engineer: Jandy Su 	
Report No.: RSZ05041301	
Test Date: April 15, 2005	
Reviewed By: Chris Zeng 	
Prepared By: Bay Area Compliance Lab Corp. (ShenZhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: The test report is specially limited to the above company and this particular sample only.
It may not be duplicated without prior written consent of Bay Area Compliance Lab Corp.
(ShenZhen). This report **must not** be used by the client to claim product certification,
approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
SPECIAL ACCESSORIES	4
EQUIPMENT MODIFICATIONS	4
CONFIGURATION OF TEST SETUP	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
§15.203 - ANTENNA REQUIREMENT.....	7
STANDARD APPLICABLE	7
§15.205, §15.209, §15.227(A) - RADIATED EMISSIONS TEST	8
MEASUREMENT UNCERTAINTY	8
EUT SETUP.....	8
TEST RECEIVER SETUP	8
TEST EQUIPMENT LIST AND DETAILS.....	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST RESULTS SUMMARY	9
TEST DATA	10
§15.227(B) - OUT OF BAND EMISSION	11

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The Newmen Technology Corp., Ltd.'s product, model number: MS-037OR or the "EUT" as referred to in this report is a Transmitter of Wireless Mouse. The EUT is measured approximately 12cm L x 7cm W x 4cm H. rated input voltage: DC 3V battery.

** The test data gathered are from production sample, serial number: 050000001, provided by the manufacturer.*

Objective

This Type approval report is prepared on behalf of *Newmen Technology Corp., Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A , B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules, sec 15.203, 15.205, 15.209 and sec 15.227.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Lab Corp. (ShenZhen) to collect radiated and conducted emission measurement data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China.

Test site at Bay Area Compliance Lab Corp. (ShenZhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

N/A.

Special Accessories

N/A.

Equipment Modifications


BACL has not done any modification on the EUT.

Configuration of Test Setup



Wireless Mouse Transmitter

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

Results reported relate only to the product tested, serial number: 0501000001.

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna requirement	Pass
§15.205	Restricted Band of operation	Pass
§15.209	Radiated Emission Limit	Pass
§15.227(a)	Field Strength	Pass
§15.227(b)	Out of Band Emission	Pass

§15.203 - ANTENNA REQUIREMENT

Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a permanent antenna, fulfill the requirement of this section.

Test Result: Pass

§15.205, §15.209, §15.227(a) - RADIATED EMISSIONS TEST

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

The fundamental data was recorded in average detection mode: set the VBW AVE on, then record the data.

EUT Setup

The radiated emission tests were performed in the chamber A test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part 15 Subpart C section 15.227 limits.

Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated from 27 to 1000 MHz.

During the radiated emission test, the test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>
Below 30 MHz	10 kHz	10 kHz
30 – 1000 MHz	100 kHz	100 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Test Receiver	ESCI	100035	2004-9-15	2005-9-14
HP	Amplifier	8447E	1937A01046	2004-9-1	2005-8-31
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2004-4-19	2005-4-18
ETS	Passive Loop Antenna	6512	00029604	2005-2-12	2006-2-11

* **Statement of Traceability:** BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.227, with the worst margin reading of:

-8.98 dB at 177.420 MHz in the Horizontal polarization.

Test Data**Environmental Conditions**

Temperature:	22° C
Relative Humidity:	58%
ATM Pressure:	1016mbar

Testing was performed by Jandy Su on 2005-4-15.

Test Mode: Transmitting

Meter					Antenna	Cable	Amplifier	Corr.	FCC PART 15.227&15.209		
Frequency	Reading	Direction	Height	Polar	Loss	loss	Gain	Ampl.			
MHz	dBuV/m	Degree	Meter	H / V	dB/m	dB	dB	dBuV/m	Limit dBuV/m	Margin dB	Remark
177.420	49.62	270	1.0	H	11.9	1.20	28.20	34.52	43.5	-8.98	Spurious Emission
126.120	46.19	90	1.2	H	14.4	1.10	28.50	33.19	43.5	-10.31	Spurious Emission
126.120	45.88	45	1.2	V	14.4	1.10	28.50	32.88	43.5	-10.62	Spurious Emission
108.160	48.15	60	1.2	V	12.2	1.00	28.50	32.85	43.5	-10.65	Harmonics
62.940	47.63	60	1.0	V	8.1	0.75	28.70	27.78	40.0	-12.22	Spurious Emission
62.940	45.96	90	1.2	H	8.1	0.75	28.70	26.11	40.0	-13.89	Spurious Emission
54.090	40.91	45	1.0	H	8.5	1.61	26.27	24.75	40.0	-15.25	Harmonics
94.260	46.87	45	1.2	H	7.7	0.91	28.60	26.88	43.5	-16.62	Spurious Emission
94.260	46.52	60	1.0	V	7.7	0.91	28.60	26.53	43.5	-16.97	Spurious Emission
81.135	35.65	60	1.0	H	8.4	1.42	26.22	19.25	40.0	-20.75	Harmonics
54.090	35.26	45	1.0	V	8.5	1.61	26.27	19.10	40.0	-20.90	Harmonics
81.135	29.75	60	1.0	V	8.4	1.42	26.22	13.35	40.0	-26.65	Harmonics
27.045	53.03	45	1.0	H	24.1	1.37	26.44	52.06	80.0	-27.94	Fund(AV)
27.045	58.46	45	1.0	H	24.1	1.37	26.44	57.49	100.0	-42.51	Fund(PK)
27.045	38.10	45	1.0	V	24.1	1.37	26.44	37.13	80.0	-42.87	Fund(AV)
27.045	48.65	45	1.0	V	24.1	1.37	26.44	47.68	100.0	-52.32	Fund(PK)


Test Result: Pass

§15.227(b) - Out of Band Emission


The result has been complied with the 15.227(b), see the following plot:

Frequency MHz	Emission dB μ V/m	Limit dB μ V/m
26.96	19.77	40
27.28	16.57	40

Test Result: Pass



Date: 15.APR.2005 12:23:57



Date: 15.APR.2005 12:25:04