

**SK TECH CO., LTD.**

Page 1 of 10

Certificate of Compliance

Test Report No.:	SKTTRT-041117-005		
NVLAP CODE:	200220-0		
Applicant:	UNIPION Co.,Ltd.		
Applicant Address:	330RM JUAN SIBUM COMPLEX 17-1, JUAN-DONG, NAM-GU, INCHEON, KOREA		
Device Under Test:	RF Card Door Lock		
FCC ID:	QGOCFR-1700	Model No.:	CFR-1700
Receipt No.:	SKTEU04-0562	Date of receipt:	AUG 30, 2004
Date of Issue:	NOV 17, 2004		
Location of Testing:	SK TECH CO., LTD. 820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea		
Test Procedure:	ANSI C63.4 / 2003		
Test Specification:	FCC Title 47, Part 15 Subpart C		
Equipment Class:	Part 15 Low Power Transmitter Below 1705kHz		
Test Result:	The above-mentioned device has been tested and passed.		
Tested & Reported by: Chang-Min, Moon		Approved by: Jae-Kyung, Bae	
 2004.11.17 Signature Date		 2004.11.17 Signature Date	
Other Aspects:			
Abbreviations:	· OK, Pass = passed · Fail = failed · N/A = not applicable		

- This test report is not permitted to copy partly without our permission.
- This test result is dependent on only equipment to be used.
- This test result is based on a single evaluation of one sample of the above mentioned.
- This test report must not be used to claim product endorsement by NVLAP or any agency of the U.S Government.
- We certify that this test report has been based on the measurement standards that is traceable to the national or International standards.



NVLAP Lab. Code: 200220-0



>> CONTENTS <<

1. GENERAL3

2. TEST SITE3

 2.1 Location 3

 2.2 List of Test and Measurement Instruments 4

 2.3 Test Date 4

 2.4 Test Environment 4

3. DESCRIPTION OF The EQUIPMENT UNDER TEST5

 3.1 Rating and Physical Characteristics 5

 3.2 Submitted Documents 5

4. MEASUREMENT CONDITIONS6

 4.1 Description of test configuration 6

 4.2 List of Peripherals 6

 4.3 Type of used Cables 6

 4.4 Uncertainty 6

5. TEST AND MEASUREMENTS7

 5.1 ANTENNA REQUIREMENT7

 5.1.1 Regulation 7

 5.1.2 Result 7

 5.2 RADIATED EMISSIONS8

 5.2.1 Regulation 8

 5.2.2 Measurement Procedure 8

 5.2.3 Calculation of the filed strength limits 9

 5.2.4 Test Results 9

 Table 1: Measured values of the Field strength (below 30MHz) 10

 Table 2: Measured values of the Field strength (above 30MHz) 10



1. GENERAL

These tests were performed using the test procedure outlined in ANSI C63.4, 2003 for intentional radiators, and in accordance with the limits set forth in FCC Part 15.209.

The EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards.

We attest to the accuracy of data. All measurements reported herein were performed by SK Tech Co., Ltd. and were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. TEST SITE

SK TECH Co., Ltd.

2.1 Location

820-2, Wolmoon Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea

This test site is in compliance with ISO/IEC 17025 for general requirements for the competence of testing and calibration laboratories.

This laboratory is accredited by NVLAP for NVLAP Lab. Code: 200220-0 and DATech for DAR-Registration No.: TTI-P-G155/97-10



2.2 List of Test and Measurement Instruments

Equipment Type	Manufacturer	Model No.	Serial No.	Cal. Due Date
EMI Test Receiver	Rohde&Schwarz	ESVS 10	825120/013	10, 2004
EMI Test Receiver	Rohde&Schwarz	ESVS 10	834468/008	10, 2004
EMC Spectrum Analyzer	Agilent	E7405A	US40240203	01, 2005
Amplifier	H.P	8447F	3113A05153	08, 2005
LOOP ANTENNA	Rohde & Schwarz	HFH2-Z2	8630481019	10, 2005
Log Periodic Antenna	Schwarzbeck	UHALP9107	1819	04, 2005
Biconical Antenna	Schwarzbeck	BBA9106	91031626	10, 2004
Horn Antenna	Schwarzbeck	SAS-200/571	304	05, 2005
Antenna Mast	TOKIN	5907	N/A	N/A
Antenna & Turntable controller	TOKIN	5906	N/A	N/A
50Ω Switcher	Anritsu	MP59B	6100214538	N/A

2.3 Test Date

Date of Application : August 30, 2004

Date of Test : August 31, 2004 ~ October 21, 2004

2.4 Test Environment

See each test item's description.



3. DESCRIPTION OF THE EQUIPMENT UNDER TEST

The product specification described herein was obtained from the product data sheet or user's manual.

3.1 Rating and Physical Characteristics

	Transceiver (EUT)	Receiver(EUT)
Type (Model No.)	CFR-1700	
Type(intended Purpose)	RF Card reading	Remote control receiving
Power source	Alkaline Battery (DC 6V: 1.5V*8, 6V parallel)	
RF Card Active Distance	5 cm	-
Local Oscillator	-	-
Operating frequency	0.125MHz	433.92MHz
Type of Modulation	FSK	AM
Rated Output	< 19.2 μ V/m@300m	-

3.2 Submitted Documents

Block diagram

Schematic diagram

Part List

User manual



4. MEASUREMENT CONDITIONS

4.1 Description of test configuration

The EUT was tested in a typical fashion. During preliminary emission tests the EUT was operated in continuous TRANSMITTING and READING mode for finding worst case emission mode. Therefore, final qualification testing was completed with EUT operated in both of the continuous modes.

4.2 List of Peripherals

Equipment Type	Manufacture	Model	Serial Number
----------------	-------------	-------	---------------

The EUT was tested as a stand-alone device.

4.3 Type of Used Cables

Description	Length	Type of shield	Manufacturer
-------------	--------	----------------	--------------

None

4.4 Uncertainty

Radiated disturbance

Uc (Combined standard Uncertainty) = ± 2.37 dB

Expanded uncertainty U = KUc = ± 4.74 dB (K = 2)



5. TEST AND MEASUREMENTS

Summary of Test Results

Requirement	CFR Section	Report Section	Test Result
Antenna Requirement	15.203	5.1	PASS
Radiated Spurious Emissions	15.209	5.2	PASS

5.1 ANTENNA REQUIREMENT

5.1.1 Regulation

FCC section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31 (d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

5.1.2 Result: **PASS**

The transmitter has an integral loop coil antenna and meets the requirements of this section.



5.2 RADIATED EMISSIONS

5.2.1 Regulation

- Emissions below 30MHz

According to §15.209, the field strength of emissions from intentional radiators operated under this frequency band shall not exceed the following:

frequency (MHz)	Field strength	Calculation of Field strength (uV/m)	Calculation of Field strength (dBuV/m)
0.009 – 0.490	2400/F(kHz) (uV/m @ 300m)	266.7 – 4.9 (uV/m @ 300m)	48.5 – 13.8 (dBuV/m @ 300m)
0.490 – 1.705	24000/F(kHz) (uV/m @ 30m)	49.0 – 14.1 (uV/m @ 30m)	33.8 – 23.0 (dBuV/m @ 30m)
1.705 – 30.0	30 (uV/m @ 30m)	30 (uV/m @ 30m)	29.5 (dBuV/m @ 30m)

- Emissions above 30MHz

The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in §15.209.

Frequency (MHz)	Field strength (uV/m @ 3m)	Field strength (dBuV/m @ 3m)
30–88	100	40.0
88–216	150	43.5
216–960	200	46.0
Above 960	500	54.0

The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector and above 1000 MHz are based on the average value of measured emissions.

5.2.2 Measurement Procedure

For tabletop equipment, the EUT is placed on a 1 meter by 1.5 meters wide and 0.8 meter high nonconductive table that sits on a flush mounted metal turntable. Preview tests are performed to determine the "worst case" mode of operation. With the EUT operating in "worst case" mode, emissions from the unit are maximized by adjusting the polarization and height of the receive antenna and rotating the EUT on the turntable.

The initial step in collecting radiated data is a peak scan of the measurement range with an EMI test receiver under closer distances as given in the rule. The significant peaks are then measured with the appropriate detectors (QP, AV and PK).



5.2.3 Calculation of the field strength limits

- Emissions below 30MHz

No special calculation for obtaining the field strength in dBuV/m is necessary, because the EMI receiver and the active loop antenna operate as a system, where the reading gives directly the field strength result (dBuV/m). The gain, antenna factors and cable losses are already taken into consideration.

For test distance other than what is specified, but fulfilling the requirements of section 15.31 (f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40dB/decade (inverse lineardistance for field strength measurements).

All following emission measurements were performed using the test receiver's average detector and peak detector function.

The basic equation is as follow ;

$$FS = RA + DF$$

Where

FS = Field strength in dBuV/m

RA = Receiver Amplitude in dBuV/m

DF = Distance Extrapolation Factor in dB

Where $DF = 20\log(D_{test}/D_{spec})$ where D_{test} = Test Distance and D_{spec} = Specified Distance

$DF = 40\log(3m/300m) = -80dB$ (Frequency : 0.009 ~ 0.490MHz)

$DF = 40\log(3m/30m) = -40dB$ (Frequency : 0.490 ~ 30MHz)

5.2.4 Test Results:

PASS

The results of the field strength of the fundamental and spurious/harmonic emissions are shown in Table 1. The worst-case emission level is 67.6 dBuV/m @ 3m at 0.125 MHz, This is 58.1 dB below the specified limit.

