

Certification Test Report

**FCC ID: QHC-OW35PE
IC: 4393B-OW35PE**

**FCC Rule Part: 15.247
IC Radio Standards Specification: RSS-247**

ACS Report Number: 15-0132.W06.1A

**Manufacturer: Itron, Inc.
Model: 574161**

**Test Begin Date: June 24, 2015
Test End Date: July 24, 2015**

Report Issue Date: August 6, 2015



FOR THE SCOPE OF ACCREDITATION UNDER LAB Code 200612-0

This report is not be used to claim certification, approval, or endorsement by NVLAP, NIST or any government agency.

Reviewed by:

A handwritten signature in black ink, appearing to read "Kirby Munroe", is written over a horizontal line.

**Kirby Munroe
Director, Wireless Certifications
ACS, Inc.**

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

This report contains 23 pages

TABLE OF CONTENTS

1	GENERAL	3
1.1	PURPOSE.....	3
1.2	PRODUCT DESCRIPTION	3
1.3	TEST METHODOLOGY AND CONSIDERATIONS	4
2	TEST FACILITIES.....	5
2.1	LOCATION	5
2.2	LABORATORY ACCREDITATIONS/RECOGNITIONS/CERTIFICATIONS	5
2.3	RADIATED EMISSIONS TEST SITE DESCRIPTION	6
2.3.1	<i>Semi-Anechoic Chamber Test Site</i>	6
2.3.2	<i>Open Area Tests Site (OATS)</i>	7
2.4	CONDUCTED EMISSIONS TEST SITE DESCRIPTION	8
3	APPLICABLE STANDARD REFERENCES.....	8
4	LIST OF TEST EQUIPMENT.....	9
5	SUPPORT EQUIPMENT.....	10
6	EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM	10
7	SUMMARY OF TESTS.....	11
7.1	ANTENNA REQUIREMENT – FCC: SECTION 15.203	11
7.2	POWER LINE CONDUCTED EMISSIONS – FCC 15.207, IC: RSS-GEN 8.8	11
7.2.1	<i>Measurement Procedure</i>	11
7.2.2	<i>Measurement Results</i>	11
7.3	PEAK OUTPUT POWER - FCC 15.247(B)(2) IC: RSS-247 5.4(1)	13
7.3.1	<i>Measurement Procedure (Conducted Method)</i>	13
7.3.2	<i>Measurement Results</i>	13
7.4	CHANNEL USAGE REQUIREMENTS	14
7.4.1	<i>Carrier Frequency Separation – FCC 15.247(a)(1) IC: RSS-247 5.1(2)</i>	14
7.4.1.1	<i>Measurement Procedure</i>	14
7.4.1.2	<i>Measurement Results</i>	14
7.4.2	<i>Number of Hopping Channels – FCC 15.247(a)(1)(i) IC: RSS-247 5.1(3)</i>	15
7.4.2.1	<i>Measurement Procedure</i>	15
7.4.2.2	<i>Measurement Results</i>	15
7.4.3	<i>Channel Dwell Time – FCC 15.247(a)(1)(i) IC: RSS-247 5.1(3)</i>	16
7.4.3.1	<i>Measurement Procedure</i>	16
7.4.3.2	<i>Measurement Results</i>	16
7.4.4	<i>20dB / 99% Bandwidth - FCC 15.247(a)(1)(i) IC: RSS-247 5.1(3)</i>	17
7.4.4.1	<i>Measurement Procedure</i>	17
7.4.4.2	<i>Measurement Results</i>	17
7.5	BAND-EDGE COMPLIANCE AND SPURIOUS EMISSIONS	19
7.5.1	<i>Band-Edge Compliance of RF Conducted Emissions - FCC 15.247(d); IC RSS-247 5.5</i>	19
7.5.1.1	<i>Measurement Procedure</i>	19
7.5.1.2	<i>Measurement Results</i>	19
7.5.2	<i>RF Conducted Spurious Emissions - FCC 15.247(d); IC RSS-247 5.5</i>	20
7.5.2.1	<i>Measurement Procedure</i>	20
7.5.2.2	<i>Measurement Results</i>	20
7.5.3	<i>Radiated Spurious Emissions - FCC 15.205, 15.209; RSS-Gen 8.9/8.10</i>	21
7.5.3.1	<i>Measurement Procedure</i>	21
7.5.3.2	<i>Duty Cycle Correction</i>	21
7.5.3.3	<i>Measurement Results</i>	21
7.5.3.4	<i>Sample Calculation:</i>	22
8	CONCLUSION.....	23

1 GENERAL

1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-247 Certification for modular approval certification.

1.2 Product description

The 574161 is a module that is integrated in a variety of electricity meter form factors. The 574161 includes (1) 900 MHz FHSS radio and either an on-board Sierra Wireless LTE modem HL7518, FCC ID: N7NHL7518 or on-board Sierra Wireless LTE modem HL7548, FCC ID: N7NHL7548 / IC: 2417C-HL7548. The Sierra Wireless CDMA modems HL7518 and HL7548 are modular approved and not covered under the scope of this report. The Sierra Wireless CDMA modem HL7518 is not available for use in Canada.

The 574161 is designed to be integrated into 1S, 2S, 3S, 4S, 9S, 12S, 16S, 36S, and 45S electric utility meter forms and be collocated and transmit simultaneously with the on-board Sierra Wireless LTE modem HL7518, FCC ID: N7NHL7518 or Sierra Wireless LTE modem HL7548, FCC ID: N7NHL7548 / IC: 2417C-HL7548, and separate Itron module ITR24 FCC ID: SK9ITR24 / IC: 864G-ITR24.

Technical Information:

Detail	Description
Frequency Range	910.0 - 921.8 MHz
Number of Channels	50
Modulation Format	FSK
Operating Voltage	120/240V AC (Via supply of host meter)
Antenna Type / Gain	Taoglas PC91.07.0100A.db 915MHz PCB Antenna / 2.7dBi gain

Manufacturer Information:

Itron
4400 Old Canton Road
Suite 300
Jackson, MS 39211

EUT Serial Numbers: F22J0026C01

Test Sample Condition: The test samples were provided in good working order with no visible defects.

1.3 Test Methodology and Considerations

The 574161 is designed to be integrated into 1S, 2S, 3S, 4S, 9S, 12S, 16S, 36S, and 45S electric utility meter forms and be collocated and transmit simultaneously with the on-board Sierra Wireless LTE modem HL7518, FCC ID: N7NHL7518 or Sierra Wireless LTE modem HL7548, FCC ID: N7NHL7548 / IC: 2417C-HL7548, and separate Itron module ITR24 FCC ID: SK9ITR24 / IC: 864G-ITR24.

For radiated emissions the EUT was tested stand-alone and in three orthogonal orientations. The worst case orientation was determined to be Y orientation. All modes of operation, including all available data rates, were evaluated. The data presented in this report represents the worst case where applicable.

Radiated inter-modulation testing was performed for all combinations of simultaneous transmission and found to be in compliance.

Software power setting during test: 30

2 TEST FACILITIES

2.1 Location

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions
5015 B.U. Bowman Drive
Buford, GA 30518
Phone: (770) 831-8048
Fax: (770) 831-8598

2.2 Laboratory Accreditations/Recognitions/Certifications

ACS is accredited to ISO/IEC 17025 by the National Institute of Standards and Technology under their National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 200612-0. Unless otherwise specified, all tests methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

The Semi-Anechoic Chamber Test Site, Open Area Test Site (OATS) and Conducted Emissions Site have been fully described, submitted to, and accepted by the FCC, Industry Canada and the Japanese Voluntary Control Council for Interference by information technology equipment.

FCC Registration Number: 511277

Industry Canada Lab Code: IC 4175A

VCCI Member Number: 1831

- VCCI OATS Registration Number R-1526
- VCCI Conducted Emissions Site Registration Number: C-1608

2.3 Radiated Emissions Test Site Description

2.3.1 Semi-Anechoic Chamber Test Site

The Semi-Anechoic Chamber Test Site consists of a 20' x 30' x 18' shielded enclosure. The chamber is lined with Toyo Ferrite Grid Absorber, model number FFG-1000. The ferrite tile grid is 101 x 101 x 19mm thick and weighs approximately 550 grams. These tiles are mounted on steel panels and installed directly on the inner walls of the chamber.

The turntable is 150cm in diameter and is located 160cm from the back wall of the chamber. The chamber is grounded via 1 – 8' copper ground rod, installed at the center of the back wall, it is bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is all steel, flush mounted table installed in an all steel frame. The table is remotely operated from inside the control room located 25' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Behind the turntable is a 3' x 6' x 4' deep shielded pit used for support equipment if necessary. The pit is equipped with 1 – 4" PVC chases from the turntable to the pit that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit.

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3-1 below:




Figure 2.3-1: Semi-Anechoic Chamber Test Site

2.3.2 Open Area Tests Site (OATS)

The open area test site consists of a 40' x 66' concrete pad covered with a perforated electro-plated galvanized sheet metal. The perforations in the sheet metal are 1/8" holes that are staggered every 3/16". The individual sheets are placed to overlap each other by 1/4" and are riveted together to provide a continuous seam. Rivets are spaced every 3" in a 3 x 20 meter perimeter around the antenna mast and EUT area. Rivets in the remaining area are spaced as necessary to properly secure the ground plane and maintain the electrical continuity.

The entire ground plane extends 12' beyond the turntable edge and 16' beyond the antenna mast when set to a 10 meter measurement distance. The ground plane is grounded via 4 – 8' copper ground rods, each installed at a corner of the ground plane and bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is an all aluminum 10' flush mounted table installed in an all aluminum frame. The table is remotely operated from inside the control room located 40' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Adjacent to the turntable is a 7' x 7' square and 4' deep concrete pit used for support equipment if necessary. The pit is equipped with 5 – 4" PVC chases from the pit to the control room that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit. The pit is covered with 2 sheets of 1/4" diamond style re-enforced steel sheets. The sheets are painted to match the perforated steel ground plane; however the underside edges have been masked off to maintain the electrical continuity of the ground plane. All reflecting objects are located outside of the ellipse defined in ANSI C63.4.

A diagram of the Open Area Test Site is shown in Figure 2.3-2 below:




Figure 2.3-2: Open Area Test Site

2.4 Conducted Emissions Test Site Description

The AC mains conducted EMI site is located in the main EMC lab. It consists of an 8' x 8' solid aluminum horizontal ground reference plane (GRP) bonded every 3" to an 8' X 8' vertical ground plane.

The site is of sufficient size to test table top and floor standing equipment in accordance with section 6.1.4 of ANSI C63.4.

A diagram of the room is shown below in figure 2.4-1:




Figure 2.4-1: AC Mains Conducted EMI Site

3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2015
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2015
- ❖ Industry Canada Radio Standards Specification: RSS-247 – Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices, Issue 1, May 2015.
- ❖ Industry Canada Radio Standards Specification: RSS-GEN – General Requirements for Compliance of Radio Apparatus, Issue 4, Nov 2014.

4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

Table 4-1: Test Equipment

AssetID	Manufacturer	Model #	Equipment Type	Serial #	Last Calibration Date	Calibration Due Date
1	Rohde & Schwarz	ESMI - Display	Spectrum Analyzers	833771/007	7/11/2014	7/11/2015
1	Rohde & Schwarz	ESMI - Display	Spectrum Analyzers	833771/007	7/14/2015	7/14/2016
2	Rohde & Schwarz	ESMI-Receiver	Spectrum Analyzers	839587/003	7/11/2014	7/11/2015
2	Rohde & Schwarz	ESMI-Receiver	Spectrum Analyzers	839587/003	7/14/2015	7/14/2016
30	Spectrum Technologies	DRH-0118	Antennas	970102	4/30/2015	4/30/2017
40	EMCO	3104	Antennas	3211	2/10/2015	2/10/2017
73	Agilent	8447D	Amplifiers	2727A05624	7/15/2014	7/15/2015
73	Agilent	8447D	Amplifiers	2727A05624	7/15/2015	7/15/2016
167	ACS	Chamber EMI Cable Set	Cable Set	167	10/28/2014	10/28/2015
168	Hewlett Packard	11947A	Attenuators	44829	1/19/2015	1/19/2016
267	Agilent	N1911A	Meters	MY45100129	7/30/2013	7/30/2015
268	Agilent	N1921A	Sensors	MY45240184	7/30/2013	7/30/2015
292	Florida RF Cables	SMR-290AW-480.0-SMR	Cables	None	3/3/2015	3/3/2016
316	Rohde Schwarz	ESH3-Z5	LISN	861189-010	10/30/2014	10/30/2015
324	ACS	Belden	Cables	8214	5/5/2015	5/5/2016
331	Microwave Circuits	H1G513G1	Filters	31417	5/20/2015	5/20/2016
338	Hewlett Packard	8449B	Amplifiers	3008A01111	7/30/2013	7/30/2015
340	Aeroflex/Weinschel	AS-20	Attenuators	7136	7/14/2014	7/14/2015
340	Aeroflex/Weinschel	AS-20	Attenuators	7136	7/13/2015	7/13/2016
412	Electro Metrics	LPA-25	Antennas	1241	7/24/2014	7/24/2016
422	Florida RF	SMS-200AW-72.0-SMR	Cables	805	11/5/2014	11/5/2015
616	Florida RF Cables	SMRE-200W-12.0-SMRE	Cables	N/A	9/10/2014	9/10/2015
622	Rohde & Schwarz	FSV40	Analyzers	101338	7/12/2014	7/12/2015
622	Rohde & Schwarz	FSV40	Analyzers	101338	7/15/2015	7/15/2016
RE112	Rohde & Schwarz	ESIB26	Receiver	836119/012	10/30/2014	10/30/2015

NOTE: All testing was performed during the active calibration cycle of the equipment used.

5 SUPPORT EQUIPMENT

Table 5-1: Support Equipment

Item	Equipment Type	Manufacturer	Model Number	Serial Number
1	AC Power Board	Itron	AC Filter Module	F2160017C01

6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM




Figure 6-1: Test Setup Block Diagram

7 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

7.1 Antenna Requirement – FCC: Section 15.203

The antenna is a Taoglas PCB antenna with 2.7dBi gain. The antenna coupling is u.fl which satisfies the requirements of 15.203.

7.2 Power Line Conducted Emissions – FCC 15.207, IC: RSS-Gen 8.8

7.2.1 Measurement Procedure

ANSI C63.4 sections 6 and 7 were the guiding documents for this evaluation. Conducted emissions were performed from 150kHz to 30MHz with the spectrum analyzer's resolution bandwidth set to 9kHz and the video bandwidth set to 30kHz. The calculation for the conducted emissions is as follows:

Corrected Reading = Analyzer Reading + LISN Loss + Cable Loss

Margin = Applicable Limit - Corrected Reading

7.2.2 Measurement Results

Table 7.2.2-1: Conducted EMI Results Line 1

Frequency (MHz)	Corrected Reading		Limit (dBuV)	Margin (dB)	Line	Correction (dB)
	Quasi-Peak (dBuV)	Average (dBuV)				
0.173222	---	32.53	54.70	22.17	L1	10.1
0.173222	49.02	---	64.72	15.70	L1	10.1
0.327354	---	35.28	49.30	14.02	L1	10.1
0.327354	50.65	---	59.33	8.68	L1	10.1
0.387275	---	37.02	47.96	10.94	L1	10.1
0.387275	54.50	---	57.99	3.49	L1	10.1
0.452706	---	29.36	46.75	17.39	L1	10.1
0.452706	44.11	---	56.76	12.65	L1	10.1
0.453707	---	29.48	46.74	17.26	L1	10.1
0.453707	44.29	---	56.75	12.46	L1	10.1
0.714028	---	27.11	46.00	18.89	L1	10.1
0.714028	42.50	---	56.00	13.50	L1	10.1

Table 7.2.2-2: Conducted EMI Results Line 2

Frequency (MHz)	Corrected Reading		Limit (dBuV)	Margin (dB)	Line	Correction (dB)
	Quasi-Peak (dBuV)	Average (dBuV)				
0.200180	---	36.92	53.42	16.50	N	10.1
0.200180	53.32	---	63.45	10.13	N	10.1
0.259018	---	43.01	51.22	8.21	N	10.1
0.259018	58.70	---	61.26	2.56	N	10.1
0.268537	---	39.13	50.92	11.79	N	10.1
0.268537	56.90	---	60.96	4.06	N	10.1
0.403307	---	31.55	47.64	16.09	N	10.1
0.403307	50.85	---	57.67	6.82	N	10.1
0.512726	---	27.94	46.00	18.06	N	10.1
0.512726	47.36	---	56.00	8.64	N	10.1
0.808818	---	24.78	46.00	21.22	N	10.1
0.808818	41.56	---	56.00	14.44	N	10.1

7.3 Peak Output Power - FCC 15.247(b)(2) IC: RSS-247 5.4(1)**7.3.1 Measurement Procedure (Conducted Method)**

The RF output port of the EUT was directly connected to the input of a peak power meter with suitable attenuation. The device employs ≥ 50 channels therefore the power is limited to 1 Watt.

All data rates were evaluated and worst case reported.

7.3.2 Measurement Results**Table 7.3.2-1: RF Output Power**

Frequency [MHz]	Level [dBm]
910	21.23
917	21.25
921.8	21.06

7.4 Channel Usage Requirements

7.4.1 Carrier Frequency Separation – FCC 15.247(a)(1) IC: RSS-247 5.1(2)

7.4.1.1 Measurement Procedure

The RF output port of the EUT was directly connected to the input of the spectrum analyzer with suitable attenuation. The span of the spectrum analyzer was set wide enough to capture two adjacent peaks. The RBW was set to approximately 30% of the channel spacing and the VBW was set to $\geq$ RBW.

7.4.1.2 Measurement Results




Figure 7.4.1.2-1: Carrier Frequency Separation

7.4.2 Number of Hopping Channels – FCC 15.247(a)(1)(i) IC: RSS-247 5.1(3)

7.4.2.1 Measurement Procedure

The RF output port of the EUT was directly connected to the input of the spectrum analyzer with suitable attenuation. The span of the spectrum analyzer was set wide enough to capture the frequency band of operation. The RBW was set to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller and VBW set to $\geq$ RBW.

7.4.2.2 Measurement Results




Figure 7.4.2.2-1: Number of Hopping Channels

7.4.3 Channel Dwell Time – FCC 15.247(a)(1)(i) IC: RSS-247 5.1(3)

7.4.3.1 Measurement Procedure

The RF output port of the EUT was directly connected to the input of the spectrum analyzer. The span of the spectrum analyzer display was set 0 Hz centered on a hopping channel. The RBW of the spectrum analyzer was set to $\leq$ the EUT channel spacing and VBW set to $\geq$ RBW. The Marker Delta function of the analyzer was utilized to determine the dwell time.

7.4.3.2 Measurement Results

Table 7.4.3.2-1: Channel Dwell Time

Single Occurrence	Number of Occurrences / 20s	Total Dwell Time (ms)
57.02	1	57.02




Figure 7.4.3.2-1: Dwell Time

Detailed description of timing provided in the theory of operation.




Figure 7.4.4.2-3: 20dB BW High Channel




Figure 7.4.4.2-4: 99% OBW Low Channel




Figure 7.4.4.2-5: 99% OBW Mid Channel




Figure 7.4.4.2-6: 99% OBW High Channel

鯨

7.5 Band-Edge Compliance and Spurious Emissions

7.5.1 Band-Edge Compliance of RF Conducted Emissions - FCC 15.247(d); IC RSS-247 5.5

7.5.1.1 Measurement Procedure

The RF output port of the EUT was directly connected to the input of the spectrum analyzer with suitable attenuation. The EUT was investigated at the lowest and highest channel available to determine band-edge compliance. For each measurement the spectrum analyzer's RBW was set to 100 kHz, and the VBW was set to 300 kHz.

7.5.1.2 Measurement Results

NON-HOPPING MODE:




Figure 7.5.1.2-1: Lower Band-edge




Figure 7.5.1.2-2: Upper Band-edge

HOPPING MODE:




Figure 7.5.1.2-3: Lower Band-edge




Figure 7.5.1.2-4: Upper Band-edge

7.5.2 RF Conducted Spurious Emissions - FCC 15.247(d); IC RSS-247 5.5

7.5.2.1 Measurement Procedure

The RF output port of the EUT was directly connected to the input of the spectrum analyzer with suitable attenuation. The EUT was investigated for conducted spurious emissions from 30MHz to 10GHz, 10 times the highest fundamental frequency. Measurements were made at the low, center and high channels of the EUT. For each measurement, the spectrum analyzer's RBW was set to 100kHz. A peak detector function was used with the trace set to max hold.

7.5.2.2 Measurement Results




Figure 7.5.2.2-1: 30 MHz – 10 GHz – LCH




Figure 7.5.2.2-2: 30 MHz – 10 GHz – MCH




Figure 7.5.2.2-3: 30 MHz – 10 GHz – HCH

7.5.3 Radiated Spurious Emissions - FCC 15.205, 15.209; RSS-Gen 8.9/8.10

7.5.3.1 Measurement Procedure

Radiated emissions tests were made over the frequency range of 30MHz to 10GHz, 10 times the highest fundamental frequency.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000MHz, peak and average measurements were made with RBW and VBW of 1 MHz and 3MHz respectively.

The EUT was caused to generate a continuous modulated carrier on the hopping channel.

Each emission found to be in a restricted band was compared to the applicable radiated emission limits.

Radiated spurious emissions were evaluated for all data rates with worst case data provided.

7.5.3.2 Duty Cycle Correction

For average radiated measurements, using a 57.02% duty cycle, the measured level was reduced by a factor 4.87dB. The duty cycle correction factor is determined using the formula: $20\log(57.02/100) = -4.87\text{dB}$. A detailed analysis of the duty cycle timing is provided in the Theory of Operation accompanying the application for certification.

7.5.3.3 Measurement Results

Table 7.5.3.3-1: Radiated Spurious Emissions Tabulated Data

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
2730	48.21	38.48	H	-4.61	43.60	29.00	74.0	54.0	30.4	25.0
2730	49.36	40.36	V	-4.61	44.75	30.88	74.0	54.0	29.3	23.1
Middle Channel										
2751	48.37	38.17	H	-4.53	43.84	28.78	74.0	54.0	30.2	25.2
2751	48.53	39.57	V	-4.53	44.00	30.18	74.0	54.0	30.0	23.8
4585	48.67	38.53	H	0.72	49.39	34.38	74.0	54.0	24.6	19.6
4585	47.72	37.62	V	0.72	48.44	33.47	74.0	54.0	25.6	20.5
High Channel										
2765.4	47.38	37.72	H	-4.47	42.91	28.39	74.0	54.0	31.1	25.6
2765.4	48.16	39.24	V	-4.47	43.69	29.91	74.0	54.0	30.3	24.1

7.5.3.4 Sample Calculation:

$$R_C = R_U + CF_T$$

Where:

CF_T	=	Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)
R_U	=	Uncorrected Reading
R_C	=	Corrected Level
AF	=	Antenna Factor
CA	=	Cable Attenuation
AG	=	Amplifier Gain
DC	=	Duty Cycle Correction Factor

Example Calculation: Peak

Corrected Level: $48.21 - 4.61 = 43.60\text{dBuV/m}$

Margin: $74\text{dBuV/m} - 43.60\text{dBuV/m} = 30.4\text{dB}$

Example Calculation: Average

Corrected Level: $38.48 - 4.61 - 4.87 = 29.00\text{dBuV}$

Margin: $54\text{dBuV} - 29.00\text{dBuV} = 25.0\text{dB}$

8 CONCLUSION

In the opinion of ACS, Inc. the 574161, manufactured by Itron, Inc. meets the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-247.

END REPORT