

CommScope Technologies LLC

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Band 5 Radio Module, Model: RPM-A5A11-B05

REPORT NUMBER

104326151MPK-002

ISSUE DATE

October 30, 2020

REVISED DATE

N/A

PAGES

9

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)**

Report Number: 104326151MPK-002

Project Number: G104326151

Report Issue Date: October 30, 2020

Product Designation: Band 5 Radio Module

Model Tested: RPM-A5A11-B05

FCC ID: QHYRPM-A5A11-B05

to

47CFR 2.1091

for

CommScope Technologies LLC

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

CommScope Technologies LLC
250 Apollo Drive
Chelmsford, MA 01824

Report prepared by:



Minh Ly / Project Engineer

Report reviewed by:



Krishna Vemuri / EMC Manager

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 104326151MPK-002	
Equipment Under Test:	Band 5 Radio Module
Trade Name:	CommScope Technologies LLC
Model(s) Tested:	RPM-A5A11-B05
Applicant:	CommScope Technologies LLC
Contact:	Elowra Khan
Address:	CommScope Technologies LLC 250 Apollo Drive Chelmsford, MA 01824
Country:	USA
Tel. Number:	(972) 952-9846
Email:	Elowra.khan@commscope.com
Applicable Regulation:	47CFR 2.1091

TABLE OF CONTENTS

<i>CommScope Technologies LLC</i>	1
1.0 RF Exposure Summary	5
2.0 RF Exposure Limits	5
3.0 Test Results (Mobile Configuration)	6
4.0 Document History	9

1.0 RF Exposure Summary

Test	Reference FCC	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 was followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The EUT, Model: RPM-A5A11-B05 consists of Band 5 Radio module only. For RF exposure compliance refer reports # 104326151MPK-001.

3.3 Maximum RF Power

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
864 - 894	21.58	3.0	Conducted power measurements were taken from Report # 104326151MPK-001.

¹As declared by the manufacturer.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for RPM-A5A11-B05 radio.

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	Results
869 - 894	24.58	287.1	0.0571	0.596	Complies

¹Note: Antenna gains below 0 are considered as 0dBi.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewer Initials	Date	Change
1.0/ G104326151	ML	KV	October 30, 2020	Original document