

FCC RADIO TEST REPORT

Applicant..... : Sunrich Technology (H.K.) Ltd.

Address..... : Room 1302, Eastern Centre, 1065 King's Road Quarry Bay Hong Kong China

Manufacturer..... : Sunrich Technology (H.K.) Ltd.

Address..... : Room 1302, Eastern Centre, 1065 King's Road Quarry Bay Hong Kong China

Factory..... : Sunrich Technology (H.K.) Ltd.

Address..... : Room 1302, Eastern Centre, 1065 King's Road Quarry Bay Hong Kong China

Product Name..... : USB Bluetooth Adapter

Brand Name..... : N/A

Model No. : U2-R33-BT10-11-00011 (B-200), U2-R33-BT10-xx-xxxxx (B-200)

("x" represents 0-9/A-Z) (For model difference refer to section 2)

FCC ID..... : QIJ-B200


Measurement Standard..... : 47 CFR FCC Part 15, Subpart C (Section 15.247)

Receipt Date of Samples..... : March 03, 2026

Date of Tested..... : March 04, 2026 to April 01, 2026

Date of Report..... : April 24, 2026

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Alina Guo / Project Engineer



Approved by

Iori Fan / Authorized Signatory

Table of Contents

1. Summary of Test Result	4
2. General Description of EUT	5
3. Test Channels and Modes Detail.....	8
4. Configuration of EUT	8
5. Modification of EUT	8
6. Description of Support Device	9
7. Test Facility and Location	10
8. Applicable Standards and References	11
9. Deviations and Abnormalities from Standard Conditions.....	11
10. Test Conditions	12
11. Measurement Uncertainty	13
12. Sample Calculations	14
13. Test Items and Results	15
13.1 Conducted Emissions Measurement.....	15
13.2 Radiated Spurious Emissions and Restricted Bands Measurement	19
13.3 Channel Separation test.....	41
13.4 20dB Bandwidth	45
13.5 Hopping Channel Number	49
13.6 Time of Occupancy (Dwell Time).....	51
13.7 Maximum Peak Output Power	55
13.8 Band Edge Conducted Spurious Emission Measurement.....	59
13.9 Antenna Requirement	64
14. Test Equipment List.....	65

1. Summary of Test Result

FCC Rules	Description of Test	Result	Remarks
§15.247(a)(1)	Channel Separation test	PASS	---
§15.247(a)(1)	20dB Bandwidth	PASS	---
§15.247(a)(1)(iii)	Hopping Channel Number	PASS	---
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	PASS	---
§15.247(b)	Max Peak output Power test	PASS	---
§15.247(d)	Band edge test	PASS	---
§15.207 (a)	AC Power Conducted Emission	PASS	---
§15.247(d), §15.209, §15.205	Radiated Emission	PASS	---
§15.203	Antenna Requirement	PASS	---
§15.247(d)	Conducted Spurious Emission	PASS	---

2. General Description of EUT

Product Information	
Product Name:	USB Bluetooth Adapter
Main Model Name:	U2-R33-BT10-11-00011 (B-200)
Additional Model Name:	U2-R33-BT10-xx-xxxxx (B-200) "x" represents 0-9/A-Z
Model Difference:	These models have the same circuit schematic, construction, PCB Layout and critical components. The differences are model number due to trading purpose.
S/N:	2603-0934
Brand Name:	N/A
Hardware Version:	Rev.A
Software Version:	202512
Rating:	USB port: DC 5V
Typical arrangement:	Table-top
I/O Port:	Refer to the user manual
Accessories Information	
Adapter:	N/A
Cable:	N/A
Other:	N/A
Additional Information	
Note:	According to the model differences and the requirements of the manufacturer, all the tests items were performed on model U2-R33-BT10-11-00011 (B-200).
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification (Bluetooth)	
Bluetooth Version:	V5.4
Frequency Range:	2402-2480MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channel:	79 (refer to following channel list for details)
Channel Space:	1MHz
Antenna Type:	PCB Antenna
Number of Antenna	1
Antenna Gain:	2.6 dBi (Declared by the manufacturer)
Receiver Category:	Category 2
Note: This EUT only support to BDR/EDR feature.	


Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

3. Test Channels and Modes Detail

No.	Mode	Channel	Frequency (MHz)	Modulation
1.	TX	Hopping	2402-2480	GFSK / $\pi/4$ -DQPSK / 8DPSK
2.	TX	Low	2402	GFSK / $\pi/4$ -DQPSK / 8DPSK
3.	TX	Mid	2441	GFSK / $\pi/4$ -DQPSK / 8DPSK
4.	TX	High	2480	GFSK / $\pi/4$ -DQPSK / 8DPSK
5.	BT Link	---	---	---

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

4. Configuration of EUT



5. Modification of EUT

No modifications are made to the EUT during all test items.

6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Brand	M/N	S/N	Cable Specification	Remarks
1.	Laptop	Lenovo	R720-15 1KBN	PF0Z35FH	I/P: AC 100-240V 50-60Hz, 1.5A O/P: DC 20V 6.75A	Provide by the Lab
2.	Adapter of Laptop	Delta	ADL135N DC3A	---	Power cord: 1.10m unshielded DC Line: 1.15m unshielded with a core	Provide by the Lab

No.	Test Software	Modulation	Power Setting
1.	RTKBT_RFVerifyTool	GFSK	0X41
2.		$\pi/4$ -DQPSK	0X40
3.		8DPSK	0X3F

7. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	The Laboratory has been assessed and proved to be in compliance with CNAS/CL01 Listed by CNAS, August 13, 2018 The Certificate Registration Number is L5795. The Certificate is valid until August 13, 2030 The Laboratory has been assessed and proved to be in compliance with ISO17025 Listed by A2LA, November 01, 2017 The Certificate Registration Number is 4429.01 The Certificate is valid until December 31, 2027 Listed by FCC, November 06, 2017 Test Firm Registration Number: 907417 Listed by Industry Canada, June 08, 2017 The Certificate Registration Number. Is 46405-9743A
Test Site Location	:	Room 101, 1101, Building 2, No. 61, Hongmei Section, Wangsha Road, Hongmei Town, Dongguan, Guangdong, People's Republic of China

8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Test Standards:

47 CFR Part 15, Subpart C, 15.247

ANSI C63.10-2020+Cor 1-2023

References Test Guidance:

DTS KDB 558074 D01 15.247 Meas Guidance v05r02

Remark:

The EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

10. Test Conditions

No.	Test Item	Test Mode	Test Voltage	Tested by	Remarks
1.	Channel Separation test	1	AC 120V / 60Hz	Sean	See note 1
2.	20dB Bandwidth	2-4	AC 120V / 60Hz	Sean	See note 1
3.	Hopping Channel Number	1	AC 120V / 60Hz	Sean	See note 1
4.	Time of Occupancy (Dwell Time)	1	AC 120V / 60Hz	Sean	See note 1
5.	Max Peak output Power test	2-4	AC 120V / 60Hz	Sean	See note 1
6.	Band edge test	1-4	AC 120V / 60Hz	Sean	See note 1
7.	AC Power Conducted Emission	1	AC 120V / 60Hz	Sean	See note 1
8.	Radiated Emission	1-4	AC 120V / 60Hz	Sean	See note 1
9.	Antenna Requirement	---	---	---	---
10.	Conducted Spurious Emission	1-4	AC 120V / 60Hz	Sean	See note 1

Note:

1. The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35℃, 30~70%, 86~106kPa.
2. AC 120V / 60Hz come from laptop, only the worst case was recorded in the report.

11. Measurement Uncertainty

No.	Test Item	Frequency	Uncertainty	Remarks
1.	Conducted Emission	150KHz ~ 30MHz	±2.46 dB	---
2.	Radiated Emission	9kHz ~ 30MHz	±5.63 dB	---
		30MHz ~ 1GHz	±5.63 dB	---
		1GHz ~ 18GHz	±5.16 dB	---
		18GHz ~ 40GHz	±5.16 dB	---
3.	Conducted Spurious Emissions	10Hz ~ 40GHz	±1.06 dB	---
4.	RF Output Power	10Hz ~ 40GHz	±1.08 dB	---
5.	Power Spectral Density	10Hz ~ 40GHz	±1.08 dB	---
6.	Occupied Channel Bandwidth	---	±0.71 %	---
7.	Dwell time	---	±2ms	---

Note:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

12. Sample Calculations

Conducted Emission						
Freq. (MHz)	Reading Level (dBUV)	Correct Factor (dB)	Measurement (dBUV)	Limit (dBUV)	Over (dB)	Detector
0.1660	31.00	10.60	41.60	65.16	-23.56	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver Reading Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation Measurement = Reading + Corrector Factor Limit = Limit stated in standard Margin = Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Radiated Spurious Emissions and Restricted Bands						
Freq. (MHz)	Reading Level (dBUV)	Correct Factor (dB/m)	Measurement (dBUV/m)	Limit (dBUV/m)	Over (dB)	Detector
65.8900	26.20	-7.90	18.30	40.00	-21.70	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver Reading Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier Measurement = Reading + Corrector Factor Limit = Limit stated in standard Over = Margin, which calculated by Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

13. Test Items and Results

13.1 Conducted Emissions Measurement


LIMITS

According to the requirements of FCC PART 15.207, the limits are as follows:

Frequency (MHz)	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

- Note:
1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
 2. The lower limit shall apply at the transition frequencies.
 3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

TEST RESULTS

PASS


Please refer to the following pages.

M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Phase: L1	Detector: QP & AVG
Test Mode: 1	

Conducted Emission Measurement

Date: 2026/3/5

Time: 10:47:56




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1779	27.19	20.81	48.00	64.58	-16.58	QP	
2	0.1779	11.69	20.81	32.50	54.58	-22.08	AVG	
3	0.2660	30.63	21.07	51.70	61.24	-9.54	QP	
4	0.2660	15.63	21.07	36.70	51.24	-14.54	AVG	
5	0.3899	20.84	21.16	42.00	58.07	-16.07	QP	
6	0.3899	6.74	21.16	27.90	48.07	-20.17	AVG	
7	0.5100	15.54	21.16	36.70	56.00	-19.30	QP	
8	0.5100	7.14	21.16	28.30	46.00	-17.70	AVG	
9	1.0339	22.35	21.15	43.50	56.00	-12.50	QP	
10	1.0339	0.75	21.15	21.90	46.00	-24.10	AVG	
11	19.7099	24.33	20.37	44.70	60.00	-15.30	QP	
12 *	19.7099	23.33	20.37	43.70	50.00	-6.30	AVG	

M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Phase: N	Detector: QP & AVG
Test Mode: 1	

Conducted Emission Measurement

Date: 2026/3/5

Time: 10:53:29



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1740	25.64	20.76	46.40	64.77	-18.37	QP	
2	0.1740	11.64	20.76	32.40	54.77	-22.37	AVG	
3 *	0.2540	32.01	20.99	53.00	61.63	-8.63	QP	
4	0.2540	21.41	20.99	42.40	51.63	-9.23	AVG	
5	0.3940	21.57	21.13	42.70	57.98	-15.28	QP	
6	0.3940	8.77	21.13	29.90	47.98	-18.08	AVG	
7	0.5060	16.48	21.12	37.60	56.00	-18.40	QP	
8	0.5060	9.78	21.12	30.90	46.00	-15.10	AVG	
9	1.0300	19.48	21.12	40.60	56.00	-15.40	QP	
10	1.0300	1.58	21.12	22.70	46.00	-23.30	AVG	
11	19.5859	24.80	20.30	45.10	60.00	-14.90	QP	
12	19.5859	20.60	20.30	40.90	50.00	-9.10	AVG	

13.2 Radiated Spurious Emissions and Restricted Bands Measurement


LIMITS

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)
		$\mu\text{V/m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500


- Remark:
- (1) Emission level $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$.
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
 - (5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



TEST PROCEDURES

- Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- For the radiated emission test above 1GHz:

The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.
- g. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and packet type.

The worst case was found when the EUT was positioned on X axis for radiated emission.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Detector	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

TEST RESULTS

PASS

Please refer to the following pages of the worst case.


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: QP
Test Mode: 4	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 18:21:00

80.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		190.0500	39.30	-10.00	29.30	43.50	-14.20	QP	
2		215.2700	34.32	-9.12	25.20	43.50	-18.30	QP	
3	*	393.7500	37.64	-4.54	33.10	46.00	-12.90	QP	
4		568.3500	30.09	-1.09	29.00	46.00	-17.00	QP	
5		600.3600	30.51	-0.41	30.10	46.00	-15.90	QP	
6		941.8000	27.44	4.16	31.60	46.00	-14.40	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: QP
Test Mode: 4	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 18:14:45



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	144.4600	44.23	-12.83	31.40	43.50	-12.10	QP	
2		191.9900	34.73	-9.83	24.90	43.50	-18.60	QP	
3		405.3900	29.89	-4.29	25.60	46.00	-20.40	QP	
4		460.6800	29.67	-3.37	26.30	46.00	-19.70	QP	
5		838.0100	26.13	3.37	29.50	46.00	-16.50	QP	
6		941.8000	27.44	4.16	31.60	46.00	-14.40	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: GFSK (Low Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 17:32:48



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector Comment
1		4804.000	36.31	3.80	40.11	74.00	-33.89	peak
2		4804.000	27.46	3.80	31.26	54.00	-22.74	AVG
3		7206.000	36.82	8.66	45.48	74.00	-28.52	peak
4		7206.000	27.57	8.66	36.23	54.00	-17.77	AVG
5		17898.000	38.47	20.26	58.73	74.00	-15.27	peak
6	*	17898.000	27.33	20.26	47.59	54.00	-6.41	AVG


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: GFSK (Low Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 17:39:28

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	35.69	3.80	39.49	74.00	-34.51	peak	
2		4804.000	26.82	3.80	30.62	54.00	-23.38	AVG	
3		7206.000	35.76	8.66	44.42	74.00	-29.58	peak	
4		7206.000	26.59	8.66	35.25	54.00	-18.75	AVG	
5		17932.000	39.30	20.42	59.72	74.00	-14.28	peak	
6	*	17932.000	27.11	20.42	47.53	54.00	-6.47	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: GFSK (Low Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/28

Time: 14:21:33

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector Comment
1		19216.000	45.50	7.09	52.59	74.00	-21.41	peak
2	*	19216.000	35.97	7.09	43.06	54.00	-10.94	AVG
3		21618.000	46.04	4.98	51.02	74.00	-22.98	peak
4		21618.000	37.15	4.98	42.13	54.00	-11.87	AVG


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: GFSK (Low Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/28

Time: 14:28:46

106.0 dBuV/m




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		19216.000	46.54	7.09	53.63	74.00	-20.37	peak	
2	*	19216.000	36.99	7.09	44.08	54.00	-9.92	AVG	
3		21618.000	47.08	4.98	52.06	74.00	-21.94	peak	
4		21618.000	38.25	4.98	43.23	54.00	-10.77	AVG	

M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: GFSK (Middle Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 17:53:42



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		4880.000	36.65	4.05	40.70	74.00	-33.30	peak	
2		4880.000	27.56	4.05	31.61	54.00	-22.39	AVG	
3		7320.000	35.69	9.01	44.70	74.00	-29.30	peak	
4		7320.000	26.41	9.01	35.42	54.00	-18.58	AVG	
5		17983.000	38.82	20.66	59.48	74.00	-14.52	peak	
6	*	17983.000	26.92	20.66	47.58	54.00	-6.42	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: GFSK (Middle Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 17:46:01

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4880.000	36.24	4.05	40.29	74.00	-33.71	peak
2		4880.000	27.24	4.05	31.29	54.00	-22.71	AVG
3		7320.000	36.79	9.01	45.80	74.00	-28.20	peak
4		7320.000	26.34	9.01	35.35	54.00	-18.65	AVG
5		17983.000	38.26	20.66	58.92	74.00	-15.08	peak
6	*	17983.000	26.85	20.66	47.51	54.00	-6.49	AVG


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: GFSK (Middle Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/28

Time: 14:42:40

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		19528.000	43.39	6.67	50.06	74.00	-23.94	peak	
2		19528.000	33.42	6.67	40.09	54.00	-13.91	AVG	
3		21969.000	44.21	5.45	49.66	74.00	-24.34	peak	
4	*	21969.000	34.78	5.45	40.23	54.00	-13.77	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: GFSK (Middle Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/28

Time: 14:35:51

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		19528.000	43.21	6.67	49.88	74.00	-24.12	peak
2		19528.000	33.56	6.67	40.23	54.00	-13.77	AVG
3		21969.000	44.04	5.45	49.49	74.00	-24.51	peak
4	*	21969.000	34.91	5.45	40.36	54.00	-13.64	AVG


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: GFSK (High Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 18:00:17

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	35.70	4.30	40.00	74.00	-34.00	peak	
2		4960.000	26.73	4.30	31.03	54.00	-22.97	AVG	
3		7440.000	36.11	9.60	45.71	74.00	-28.29	peak	
4		7440.000	25.69	9.60	35.29	54.00	-18.71	AVG	
5		17881.000	39.52	20.18	59.70	74.00	-14.30	peak	
6	*	17881.000	27.37	20.18	47.55	54.00	-6.45	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: GFSK (High Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 18:07:56

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	36.25	4.30	40.55	74.00	-33.45	peak	
2		4960.000	27.33	4.30	31.63	54.00	-22.37	AVG	
3		7440.000	35.29	9.60	44.89	74.00	-29.11	peak	
4		7440.000	25.67	9.60	35.27	54.00	-18.73	AVG	
5		17983.000	39.95	20.66	60.61	74.00	-13.39	peak	
6	*	17983.000	26.87	20.66	47.53	54.00	-6.47	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: GFSK (High Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/28

Time: 14:49:53

106.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		19840.000	44.12	6.57	50.69	74.00	-23.31	peak	
2	*	19840.000	34.95	6.57	41.52	54.00	-12.48	AVG	
3		22320.000	45.27	5.53	50.80	74.00	-23.20	peak	
4		22320.000	35.78	5.53	41.31	54.00	-12.69	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: GFSK (High Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/28

Time: 14:56:58

106.0 dBuV/m



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	19840.000	42.82	6.57	49.39	74.00	-24.61	peak	
2	19840.000	33.59	6.57	40.16	54.00	-13.84	AVG	
3	22320.000	44.27	5.53	49.80	74.00	-24.20	peak	
4 *	22320.000	35.12	5.53	40.65	54.00	-13.35	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: Band Edge GFSK (Low Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 16:08:00

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2374.032	45.67	-2.99	42.68	74.00	-31.32	peak	
2		2374.032	36.55	-2.99	33.56	54.00	-20.44	AVG	
3		2390.000	46.21	-2.98	43.23	74.00	-30.77	peak	
4	*	2390.000	37.17	-2.98	34.19	54.00	-19.81	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: Band Edge GFSK (Low Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 16:15:13

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2341.680	46.76	-3.04	43.72	74.00	-30.28	peak	
2	*	2341.680	37.56	-3.04	34.52	54.00	-19.48	AVG	
3		2390.000	42.88	-2.98	39.90	74.00	-34.10	peak	
4		2390.000	33.71	-2.98	30.73	54.00	-23.27	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Horizontal	Detector: PK, AVG
Test Mode: Band Edge GFSK (High Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 16:22:42

106.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2483.500	48.71	-2.84	45.87	74.00	-28.13	peak	
2		2483.500	37.96	-2.84	35.12	54.00	-18.88	AVG	
3		2486.488	47.69	-2.83	44.86	74.00	-29.14	peak	
4	*	2486.488	38.12	-2.83	35.29	54.00	-18.71	AVG	


M/N: U2-R33-BT10-11-00011 (B-200)	Testing Voltage: AC 120V / 60Hz
Polarization: Vertical	Detector: PK, AVG
Test Mode: Band Edge GFSK (High Channel)	Distance: 3m

Radiated Emission Measurement

Date: 2026/3/27

Time: 16:29:00

106.0 dBuV/m




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2483.500	44.22	-2.83	41.39	74.00	-32.61	peak	
2		2483.500	35.39	-2.83	32.56	54.00	-21.44	AVG	
3		2489.008	45.95	-2.83	43.12	74.00	-30.88	peak	
4	*	2489.008	37.18	-2.83	34.35	54.00	-19.65	AVG	

13.3 Channel Separation test

LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES


- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- Set to the maximum power setting and enable the EUT transmit continuously.
- Enable the EUT hopping function.
- Set spectrum analyzer and perform testing according to ANSI C63.10 clause 7.8.2.


TEST RESULTS

PASS

Please refer to the following tables.

Modulation	Channel	Frequency (MHz)	Hopping Separation Measurement (MHz)	Hopping Separation Limit (MHz)	Test Result
GFSK	Low	2402	1.008	>0.643	Pass
	Mid	2441	0.996	>0.643	Pass
	High	2480	0.960	>0.643	Pass
$\pi/4$ -DQPSK	Low	2402	0.999	>0.913	Pass
	Mid	2441	1.005	>0.915	Pass
	High	2480	0.993	>0.916	Pass
8DPSK	Low	2402	0.999	>0.902	Pass
	Mid	2441	0.996	>0.903	Pass
	High	2480	1.002	>0.904	Pass






13.4 20dB Bandwidth

LIMIT

N/A

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES


- a. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- b. Set to the maximum power setting and enable the EUT transmit continuously.
- c. Set spectrum analyzer and perform testing according to ANSI C63.10 clause 6.9.2.

TEST RESULTS


PASS

Please refer to the following tables.


Modulation	Channel	Frequency (MHz)	20dB Measurement (MHz)	Limit (MHz)	Remark
GFSK	Low	2402	0.9642	N/A	Reporting only
	Mid	2441	0.9643	N/A	
	High	2480	0.9631	N/A	
$\pi/4$ -DQPSK	Low	2402	1.370	N/A	
	Mid	2441	1.371	N/A	
	High	2480	1.328	N/A	
8DPSK	Low	2402	1.353	N/A	
	Mid	2441	1.354	N/A	
	High	2480	1.355	N/A	




8DPSK / Low Channel



8DPSK / Mid Channel



8DPSK / High Channel




13.5 Hopping Channel Number

LIMIT

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- Set to the maximum power setting and enable the EUT transmit continuously.
- Enable the EUT hopping function.
- Set spectrum analyzer and perform testing according to ANSI C63.10 clause 7.8.3.


TEST RESULTS

PASS

Please refer to the following table.

Modulation	Number of Hopping Channels Measurement	Limit	Test Result
GFSK	79	≥ 15	PASS
$\pi/4$ -DQPSK	79	≥ 15	PASS
8DPSK	79	≥ 15	PASS

The worst case: GFSK




13.6 Time of Occupancy (Dwell Time)

LIMIT

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES


- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- Set to the maximum power setting and enable the EUT transmit continuously.
- Enable the EUT hopping function.
- Set spectrum analyzer and perform testing according to ANSI C63.10 clause 7.8.4.


TEST RESULTS

PASS

Please refer to the following tables.

Modulation	Packet	Frequency (MHz)	Dwell Time Measurement (msec)	Limit (msec)	Test Result
GFSK	DH1	2402	$0.383 \text{ (ms)} * (1600 / (2 * 79)) * 31.6 = 122.56$	400	Pass
	DH3	2402	$1.638 \text{ (ms)} * (1600 / (4 * 79)) * 31.6 = 262.08$	400	Pass
	DH5	2402	$2.887 \text{ (ms)} * (1600 / (6 * 79)) * 31.6 = 307.95$	400	Pass
$\pi/4$ -DQPSK	2-DH1	2402	$0.391 \text{ (ms)} * (1600 / (2 * 79)) * 31.6 = 125.12$	400	Pass
	2-DH3	2402	$1.644 \text{ (ms)} * (1600 / (4 * 79)) * 31.6 = 263.04$	400	Pass
	2-DH5	2402	$2.892 \text{ (ms)} * (1600 / (6 * 79)) * 31.6 = 308.48$	400	Pass
8DPSK	3-DH1	2402	$0.391 \text{ (ms)} * (1600 / (2 * 79)) * 31.6 = 125.12$	400	Pass
	3-DH3	2402	$1.642 \text{ (ms)} * (1600 / (4 * 79)) * 31.6 = 262.72$	400	Pass
	3-DH5	2402	$2.894 \text{ (ms)} * (1600 / (6 * 79)) * 31.6 = 308.69$	400	Pass






13.7 Maximum Peak Output Power

LIMIT

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES


- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- Set to the maximum power setting and enable the EUT transmit continuously.
- Set spectrum analyzer and perform testing according to ANSI C63.10 clause 7.8.5.


TEST RESULTS

PASS

Please refer to the following tables.

Modulation	Frequency (MHz)	Peak Power output Measurement (dBm)	Peak Power output Measurement (mW)	Peak Power Limit (dBm)	Test Result
GFSK	2402.00	0.743	1.19	21	Pass
	2441.00	1.434	1.39	21	Pass
	2480.00	0.241	1.06	21	Pass
$\pi/4$ -DQPSK	2402.00	0.537	1.13	21	Pass
	2441.00	1.239	1.33	21	Pass
	2480.00	0.250	1.06	21	Pass
8DPSK	2402.00	0.287	1.07	21	Pass
	2441.00	1.094	1.29	21	Pass
	2480.00	-0.193	0.96	21	Pass






13.8 Band Edge Conducted Spurious Emission Measurement

LIMIT

In any 100KHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- Set to the maximum power setting and enable the EUT transmit continuously.
- Set spectrum analyzer and perform testing according to ANSI C63.10 clause 7.8.6 and 6.10.
- Enable hopping function of the EUT and then repeat steps above.


TEST RESULTS

PASS


Please refer to the following test plots.

Band Edge


GFSK / Low / 2402




GFSK / Hopping



GFSK / High / 2480




GFSK / Hopping




Band Edge


$\pi/4$ -DQPSK / Low / 2402




$\pi/4$ -DQPSK / Hopping



$\pi/4$ -DQPSK / High / 2480




$\pi/4$ -DQPSK / Hopping




Band Edge


8DPSK / Low / 2402




8DPSK / Hopping



8DPSK / High / 2480




8DPSK / Hopping



Conducted Spurious Emission (the worst case)


GFSK / Low Channel / 30MHz~26.5GHz



GFSK / Mid Channel / 30MHz~26.5GHz



GFSK / High Channel / 30MHz~26.5GHz



13.9 Antenna Requirement

STANDARD APPLICABLE

According to of FCC part 15C section 15.203 and 15.247:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

ANTENNA CONNECTED CONSTRUCTION

The antenna is PCB antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 2.6dBi, Therefore, the antenna is considered to meet the requirement.

14. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	101152	Aug. 21, 2025	1 Year
2.	L.I.S.N	Rohde & Schwarz	ENV 216	101317	Aug. 21, 2025	1 Year
3.	L.I.S.N	Schwarzbeck	NNLK8129	00558	Aug. 23, 2025	1 Year
4.	RF Switching Unit	Compliance Direction Systems Inc.	RSU-M2	38311	Aug. 21, 2025	1 Year
5.	Test Receiver	Rohde & Schwarz	ESCI7	100837	Aug. 21, 2025	1 Year
6.	Spectrum Analyzer	Keysight	N9020A	MY50510314	Aug. 21, 2025	1 Year
7.	Spectrum Analyzer	Keysight	N9020A	MY54200831	Aug. 22, 2025	1 Year
8.	Spectrum Analyzer	Keysight	N9010B	MY62170254	Aug. 21, 2025	1 Year
9.	Antenna	Schwarzbeck	VULB9163	01552	Aug. 16, 2025	2 Year
10.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-272	Aug. 16, 2025	2 Year
11.	Horn Antenna	COM-Power	AH-118	071078	Aug. 16, 2025	2 Year
12.	Pre-Amplifier	HP	HP 8447D	1145A00203	Aug. 21, 2025	1 Year
13.	Pre-Amplifier	HP	HP 8449B	3008A00964	Aug. 23, 2025	1 Year
14.	Communication Tester	Rohde & Schwarz	CMW500	109851	Aug. 28, 2025	1 Year
15.	Power Sensor	DARE	RPR3006W	15I00041SNO 64	Aug. 28, 2025	1 Year
16.	Horn Antenna	COM-Power	AH-840	10100020	Aug. 28, 2025	2 Year
17.	Temperature & Humidity Chamber	Wanshun	SS-HWHS-80	N/A	Aug. 09, 2025	1 Year
18.	DC Source	ZHAOXIN	KXN305D	N/A	Aug. 23, 2025	1 Year
19.	Temporary antenna connector	TESCOM	SS402	N/A	N/A	N/A
20.	Chamber	YIHENG	9*6*6m	N/A	Sep. 22, 2025	2 Year
21.	Test Software	MWRF	MTS 8310, V2.0.0.0	N/A	N/A	N/A
22.	Test Software	EZ	EZ_EMIC, NTC-3A1.1	N/A	N/A	N/A

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End---