

Huawei Technologies Co., Ltd.

RF TEST REPORT

Report Type:

FCC Part 15.247 & ISSED RSS-247 RF report

Model:

HUAWEI Board-65, HUAWEI Board-65A

REPORT NUMBER:

181001259SHA-004

ISSUE DATE:

December 25, 2018

DOCUMENT CONTROL NUMBER:

TTRF15.247-01_V1 © 2018 Intertek



Applicant: Huawei Technologies Co., Ltd.
Administration Building, Huawei Base, Bantian, Longgang District,
Shenzhen 518129 China

Manufacturer: Huawei Technologies Co., Ltd.
Administration Building, Huawei Base, Bantian, Longgang District,
Shenzhen 518129 China

Product Name: Videoconferencing Endpoint

Type/Model: HUAWEI Board-65, HUAWEI Board-65A

FCC ID: QIS-BOARD

IC: 6369A-BOARD

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2017): Radio Frequency Devices (Subpart C)


ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-247 Issue 2 (February 2017): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5 (April 2018): General Requirements for Compliance of Radio Apparatus

PREPARED BY:

Project Engineer
Wade Zhang

REVIEWED BY:

Reviewer
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY	5
MEASUREMENT RESULT SUMMARY	6
1 GENERAL INFORMATION	7
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7
1.2 TECHNICAL SPECIFICATION	7
1.3 FREQUENCY HOPPING SYSTEM REQUIREMENT	8
1.4 DESCRIPTION OF TEST FACILITY	10
2 TEST SPECIFICATIONS	11
2.1 STANDARDS OR SPECIFICATION	11
2.2 MODE OF OPERATION DURING THE TEST	11
2.3 TEST SOFTWARE LIST	12
2.4 TEST PERIPHERALS LIST	12
2.5 TEST ENVIRONMENT CONDITION	12
2.6 INSTRUMENT LIST	13
2.7 MEASUREMENT UNCERTAINTY	14
3 20DB BANDWIDTH	15
3.1 LIMIT	15
3.2 MEASUREMENT PROCEDURE	15
3.3 TEST CONFIGURATION	16
3.4 TEST RESULTS OF 20dB BANDWIDTH	16
4 CARRIER FREQUENCY SEPARATION	17
4.1 LIMIT	17
4.2 TEST CONFIGURATION	17
4.3 TEST PROCEDURE AND TEST SETUP	17
4.4 TEST RESULTS OF CARRIER FREQUENCY SEPARATION	17
5 OUTPUT POWER	18
5.1 LIMIT	18
5.2 TEST CONFIGURATION	18
5.3 MEASUREMENT PROCEDURE	18
5.4 TEST RESULTS OF OUTPUT POWER	18
6 RADIATED EMISSIONS	19
6.1 LIMIT	19
6.2 MEASUREMENT PROCEDURE	19
6.3 TEST CONFIGURATION	21
6.4 TEST RESULTS OF RADIATED EMISSIONS	23
7 CONDUCTED SPURIOUS EMISSIONS & BAND EDGE	26
7.1 LIMIT	26
7.2 TEST CONFIGURATION	26
7.3 MEASUREMENT PROCEDURE	26
7.4 TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS & BAND EDGE	27
8 POWER LINE CONDUCTED EMISSION	28
8.1 LIMIT	28
8.2 TEST CONFIGURATION	28
8.3 MEASUREMENT PROCEDURE	29

TEST REPORT

8.4	TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....	30
9	NUMBER OF HOPPING FREQUENCIES	32
9.1	LIMIT	32
9.2	TEST CONFIGURATION	32
9.3	TEST PROCEDURE AND TEST SETUP	32
9.4	TEST RESULTS OF NUMBER OF HOPPING FREQUENCIES	32
10	DWELL TIME	33
10.1	LIMIT	33
10.2	TEST CONFIGURATION	33
10.3	TEST PROCEDURE AND TEST SETUP	33
10.4	TEST RESULTS OF DWELL TIME	34
11	OCCUPIED BANDWIDTH	35
11.1	LIMIT	35
11.2	MEASUREMENT PROCEDURE	35
11.3	TEST CONFIGURATION	35
11.4	THE RESULTS OF OCCUPIED BANDWIDTH	35
12	ANTENNA REQUIREMENT	36

Revision History

Report No.	Version	Description	Issued Date
181001259SHA-004	Rev. 01	Initial issue of report	December 25, 2018

Measurement result summary

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
20 dB Bandwidth	15.247(a)(1)	RSS-247 Issue 2 Clause 5.1	Pass
Carrier Frequency Separation	15.247(a)(1)	RSS-247 Issue 2 Clause 5.1	Pass
Output power	15.247(b)(1)	RSS-247 Issue 2 Clause 5.4	Pass
Radiated Emissions	15.205 & 15.209	RSS-Gen Issue 5 Clause 8.9&8.10	Pass
Conducted Spurious Emissions & Band Edge	15.247(d)	RSS-247 Issue 2 Clause 5.5	Pass
Power line conducted emission	15.207	RSS-Gen Issue 5 Clause 8.8	Pass
Number of Hopping Frequencies	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5.1	Pass
Dwell time	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5.1	Pass
Occupied bandwidth	-	RSS-Gen Issue 5 Clause 6.6	Tested
Antenna requirement	15.203	-	Pass

Notes:

1: NA =Not Applicable

2. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Videoconferencing Endpoint
Type/Model:	HUAWEI Board-65, HUAWEI Board-65A
Description of EUT:	The EUT is a Videoconferencing Endpoint which was install a wireless module, there have two models, and they are electrically identical except touch screen.
Rating:	AC 100-240V, 50/60Hz
EUT type:	☐ Table top ☒ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	October 19, 2018
Date of test:	December 13, 2018 ~ December 20, 2018

1.2 Technical Specification

Frequency Range:	2400MHz ~ 2483.5MHz
Support Standards:	Bluetooth BR+EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Channel Number:	79 (0 - 78)
Data Rate:	1Mbps
Channel Separation:	1MHz

Antenna information:			
No.	Antenna Type	Gain (dBi)	Note
1	Internal PIFA Antenna	3.2dBi Max	/

1.3 Frequency Hopping System Requirement

Test Requirement: Section 15.247 (a)(1), (g), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES;

i.e. the shift register is initialized with nine ones.


- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

TEST REPORT

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

1.4 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab Registration code No.: 2042B-1
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	NVLAP Accreditation Lab NVLAP LAB CODE: 200849-0
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2017)

ANSI C63.10 (2013)

RSS-247 Issue 2 (February 2017)

RSS-Gen Issue 5 (April 2018)

2.2 Mode of operation during the test

While testing the transmitter mode of the EUT, the internal modulation is applied. All the functions of the host device except the BT module were set on stand-by mode. The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

The worst-case modulation configuration:

Worst Modulation Used for Conformance Testing			
Bluetooth Mode	Data Rate	Packet Type	Worst Mode
GFSK	BR-1Mbps	DH1,DH3,DH5	BR-1Mbps DH5 EDR-2Mbps 2DH5 EDR-3Mbps 3DH5
$\pi/4$ DQPSK	EDR-2Mbps	2DH1,2DH3,2DH5	
8DPSK	EDR-3Mbps	3DH1,3DH3,3DH5	
Note: The BR-1Mbps DH5 mode was chosen for radiation emission bellow 1GHz and Conducted emission testing as representative in this report.			

The power setting parameter:

The worst-case power setting parameter			
Test software Version	adb command		
Modulation Mode	2402MHz	2441MHz	2480MHz
BR-1Mbps	max	max	max
EDR-2Mbps	max	max	max
EDR-3Mbps	max	max	max

TEST REPORT

The HUAWEI Board-65 was chosen as a representative, and there have the following test mode:

Radiated test mode:

Mode 1: EUT transmitted signal with internal antenna;

Conducted test mode:

Mode 2: EUT transmitted signal from PCBA RF port connected to SPA directly;

We have verified all test modes and choose the worst mode 1 for radiated test and mode 2 for conducted test as representatively to list the results in this report.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Laptop computer	HP ProBook 6470b	100-240V AC, 50/60Hz FCC DOC

2.5 Test environment condition:

Test items	Temperature	Humidity
20 dB Bandwidth	23°C	52% RH
Output power		
Carrier Frequency Separation		
Number of Hopping Frequencies		
Dwell time		
Occupied bandwidth		
Conducted Spurious Emissions & Band Edge	22°C	53% RH
Power line conducted emission		
Radiated Emissions	22°C	55% RH

2.6 Instrument list

Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2019-09-12
☒	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2019-05-30
☒	Pre-amplifier	R&S	Pre-amp 18	EC5262	2019-06-20
☒	Horn antenna	R&S	HF 906	EC 3049	2019-11-17
☒	Horn antenna	ETS	3117	EC 4792-1	2019-01-09
☒	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2020-07-09
☒	Pre-amplifier	R&S	Pre-amp 18	EC5262	2019-06-20
☒	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2019-03-07
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2019-03-05
☒	Power sensor	Agilent	U2021XA	EC 5338-1	2019-03-05
☒	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2019-03-05
☒	Vector Signal Generator	Agilent	N5182B	EC 5175	2019-03-05
☒	Power meter	Keysight	N1911A	EC 4318	2019-05-12
☒	Radio Communication Tester	R&S	CMW500	EC 5944	2019-12-07
☒	Mobile Test System	LitePoint	IQxel	EC 5176	2019-01-09
☒	Test Receiver	R&S	ESCI 7	EC 4501	2019-09-12
☒	Spectrum analyzer	Agilent	E7402A	EC 2254	2019-09-12
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3323	2019-06-14
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3324	2019-04-09
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3325	2019-03-23
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3326	2019-03-28

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

3 20dB bandwidth

Test result: Pass

3.1 Limit

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.


3.2 Measurement Procedure

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - xx]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker

TEST REPORT

- amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.3 Test Configuration



3.4 Test Results of 20dB bandwidth

Please refer to Appendix A.

4 Carrier Frequency Separation


Test result: Pass

4.1 Limit

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

4.2 Test Configuration



4.3 Test Procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

4.4 Test Results of Carrier Frequency Separation

Please refer to Appendix A.

5 Output power


Test result: Pass

5.1 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.2 Test Configuration



5.3 Measurement Procedure

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW ≥ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

5.4 Test Results of Output Power

Please refer to Appendix A.

6 Radiated Emissions

Test result: Pass

6.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

6.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 3 x RBW (Duty cycle $\geq$ 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported

6.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:





For Radiated emission above 1GHz:



6.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

The worst waveform from 30MHz to 1000MHz is listed as below:



TEST REPORT

Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	76.56	40.70	8.50	49.60	8.90	PK
H	122.63	40.30	9.40	54.00	13.70	PK
H	294.81	49.20	15.30	56.90	7.70	PK
V	71.22	43.50	8.10	49.60	6.10	PK
V	122.63	41.60	9.40	54.00	12.40	PK
V	294.81	48.30	15.30	56.90	8.60	PK

Test result of 1GHz to 25GHz:

GFSK (DH5) Modulation:

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.00	30.70	97.40	Fundamental	/	PK
	H	2390.00	30.20	48.70	74.00	25.30	PK
	H	2390.00	30.20	43.10	54.00	10.90	AV
	H	4804.00	-1.50	45.60	74.00	28.40	PK
M	V	2441.00	30.70	99.50	Fundamental	/	PK
	V	4882.00	-1.10	46.70	74.00	27.30	PK
H	H	2480.00	30.70	96.70	Fundamental	/	PK
	V	2483.50	31.52	48.10	74.00	25.90	PK
	V	2483.50	31.52	41.70	54.00	12.30	AV
	V	4960.00	-0.80	46.60	74.00	27.40	PK

π /4DQPSK (2DH5) Modulation:

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.00	30.70	95.50	Fundamental	/	PK
	H	2390.00	30.20	47.30	74.00	26.70	PK
	H	2390.00	30.20	41.30	54.00	12.70	AV
	H	4804.00	-1.50	45.50	74.00	28.50	PK
M	V	2441.00	30.70	96.80	Fundamental	/	PK
	V	4882.00	-1.10	44.50	74.00	29.50	PK
H	H	2480.00	30.70	95.30	Fundamental	/	PK

TEST REPORT

	V	2483.50	31.52	47.30	74.00	26.70	PK
	V	2483.50	31.52	40.50	54.00	13.50	AV
	V	4960.00	-0.80	46.30	74.00	27.70	PK

8DPSK (3DH5) Modulation:

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.00	30.70	95.10	Fundamental	/	PK
	H	2390.00	30.20	47.40	74.00	26.60	PK
	H	2390.00	30.20	41.60	54.00	12.40	AV
	H	4804.00	-1.50	46.40	74.00	27.60	PK
M	V	2441.00	30.70	96.20	Fundamental	/	PK
	V	4882.00	-1.10	46.80	74.00	27.20	PK
H	H	2480.00	30.70	95.40	Fundamental	/	PK
	V	2483.50	31.52	46.80	74.00	27.20	PK
	V	2483.50	31.52	41.20	54.00	12.80	AV
	V	4960.00	-0.80	45.90	74.00	28.10	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.


7 Conducted Spurious Emissions & Band Edge

Test result: Pass

7.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Measurement Procedure

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e)
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3. of ANSI C63.10.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6 of ANSI C63.10, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100 kHz
 - 6) Video bandwidth: 300 kHz
 - 7) Detector: Peak
 - 8) Trace: Max hold

TEST REPORT

- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.
- g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- h) Repeat step c) through step e) for every applicable modulation.
- i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).
- j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

7.4 Test Results of Conducted Spurious Emissions & Band Edge

Please refer to Appendix A

8 Power line conducted emission


Test result: Pass

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

8.2 Test Configuration



TEST REPORT**8.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

8.4 Test Results of Power line conducted emission

The worst result is listed as below:

Test Curve:

L Line




Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.150	47.50	79.00	31.50	34.00	66.00	32.00
0.750	32.10	73.00	40.90	25.10	60.00	34.90
7.930	43.40	73.00	29.60	37.50	60.00	22.50

Test Curve:

N Line



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.150	46.90	79.00	32.10	32.90	66.00	33.10
0.770	32.20	73.00	40.80	24.90	60.00	35.10
8.938	41.50	73.00	31.50	34.70	60.00	25.30

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.


9 Number of Hopping Frequencies

Test result: Pass

9.1 Limit

Number of Hopping Frequencies in the 2400-2483.5 MHz band shall use at least 15 channels.

9.2 Test Configuration



9.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

9.4 Test Results of Number of Hopping Frequencies

Please refer to Appendix A


10 Dwell Time

Test result: Pass

10.1 Limit

The dwell time on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

10.2 Test Configuration



10.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) $\times$ (period specified in the requirements / analyzer sweep time)

TEST REPORT

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

10.4 Test Results of Dwell Time

Please refer to Appendix A

11 Occupied Bandwidth

Test result: **Tested**

11.1 Limit

None


11.2 Measurement Procedure

The occupied bandwidth per RSS-Gen Issue 5 Clause 6.6 was measured using the Spectrum Analyzer.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

11.3 Test Configuration



11.4 The results of Occupied Bandwidth

Please refer to Appendix A

12 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses used a no-standard electrical connector or permanently attached antenna from antenna to the intentional radiator, so it can comply with the provisions of this section.

***** END *****

TEST REPORT

Appendix A: Transmitter Test results

1.1 RF Output Power

1.1.1 Test Result and Data

BT Maximum Output Power				
Mode	Test Frequency (MHz)	Packet Type	Power (dBm)	Result
GFSK	2402	DH5	4.74	Pass
GFSK	2441	DH5	6.86	Pass
GFSK	2480	DH5	3.70	Pass
DQPSK	2402	2DH5	2.32	Pass
DQPSK	2441	2DH5	4.78	Pass
DQPSK	2480	2DH5	2.60	Pass
8DPSK	2402	3DH5	2.69	Pass
8DPSK	2441	3DH5	5.15	Pass
8DPSK	2480	3DH5	2.90	Pass

The maximum EIRP = 6.86dBm+3.2dBi = 10.06dBm = 0.010W which is lower than the limit of 4W listed in RSS-247.

GFSK,2402MHz,DH5



GFSK,2441MHz,DH5



GFSK,2480MHz,DH5



DQPSK,2402MHz,2DH5



DQPSK,2441MHz,2DH5



DQPSK,2480MHz,2DH5



TEST REPORT

8DPSK,2402MHz,3DH5



8DPSK,2441MHz,3DH5



8DPSK,2480MHz,3DH5



TEST REPORT

1.2 20dB Down Bandwidth

1.2.1 Test Result and Data

BT Occupied 20dB Bandwidth				
Mode	Test Frequency (MHz)	Packet Type	20dB Bandwidth (kHz)	Result
GFSK	2402	DH5	936.2	Pass
GFSK	2441	DH5	962.3	Pass
GFSK	2480	DH5	930.5	Pass
DQPSK	2402	2DH5	1357.0	Pass
DQPSK	2441	2DH5	1360.2	Pass
DQPSK	2480	2DH5	1358.4	Pass
8DPSK	2402	3DH5	1312.4	Pass
8DPSK	2441	3DH5	1301.7	Pass
8DPSK	2480	3DH5	1311.6	Pass

GFSK,2402MHz,DH5




GFSK,2441MHz,DH5



GFSK,2480MHz,DH5



DQPSK,2402MHz,2DH5



DQPSK,2441MHz,2DH5



DQPSK,2480MHz,2DH5



TEST REPORT

8DPSK,2402MHz,3DH5



8DPSK,2441MHz,3DH5



8DPSK,2480MHz,3DH5



TEST REPORT

1.3 99% BandWidth

1.3.1 Test Result and Data

BT 99% Occupied Bandwidth				
Mode	Test Frequency (MHz)	Packet Type	99% Occupied Bandwidth (kHz)	Result
GFSK	2402	DH5	898.11	Pass
GFSK	2441	DH5	896.58	Pass
GFSK	2480	DH5	877.44	Pass
DQPSK	2402	2DH5	1217.05	Pass
DQPSK	2441	2DH5	1202.02	Pass
DQPSK	2480	2DH5	1216.04	Pass
8DPSK	2402	3DH5	1195.78	Pass
8DPSK	2441	3DH5	1220.71	Pass
8DPSK	2480	3DH5	1217.18	Pass

GFSK,2402MHz,DH5




GFSK,2441MHz,DH5



GFSK,2480MHz,DH5



DQPSK,2402MHz,2DH5



DQPSK,2441MHz,2DH5



DQPSK,2480MHz,2DH5



TEST REPORT

8DPSK,2402MHz,3DH5



8DPSK,2441MHz,3DH5



8DPSK,2480MHz,3DH5



TEST REPORT

1.4 Transmitter Spurious Emission

1.4.1 Test Result and Data

BT Transmitter Spurious Emission					
Mode	Test Frequency (MHz)	Packet Type	Frequency Range	Power (dBm)	Result
GFSK	2402	DH5	0.009MHz~2380MHz	-58.40	Pass
GFSK	2402	DH5	10000MHz~25000MHz	-51.56	Pass
GFSK	2402	DH5	2410MHz~10000MHz	-55.08	Pass
GFSK	2402	DH5	Band Edge	-39.49	Pass
GFSK	2441	DH5	0.009MHz~2300MHz	-57.94	Pass
GFSK	2441	DH5	10000MHz~25000MHz	-51.68	Pass
GFSK	2441	DH5	2500MHz~10000MHz	-55.91	Pass
GFSK	2441	DH5	Band Edge	-60.15	Pass
GFSK	2480	DH5	0.009MHz~2475MHz	-57.06	Pass
GFSK	2480	DH5	10000MHz~25000MHz	-51.34	Pass
GFSK	2480	DH5	2505MHz~10000MHz	-56.25	Pass
GFSK	2480	DH5	Band Edge	-50.70	Pass
DQPSK	2402	2DH5	0.009MHz~2380MHz	-57.94	Pass
DQPSK	2402	2DH5	10000MHz~25000MHz	-51.40	Pass
DQPSK	2402	2DH5	2410MHz~10000MHz	-55.85	Pass
DQPSK	2402	2DH5	Band Edge	-46.19	Pass
DQPSK	2441	2DH5	0.009MHz~2300MHz	-58.54	Pass
DQPSK	2441	2DH5	10000MHz~25000MHz	-51.53	Pass
DQPSK	2441	2DH5	2500MHz~10000MHz	-55.34	Pass
DQPSK	2441	2DH5	Band Edge	-60.25	Pass
DQPSK	2480	2DH5	0.009MHz~2475MHz	-58.19	Pass
DQPSK	2480	2DH5	10000MHz~25000MHz	-50.83	Pass
DQPSK	2480	2DH5	2505MHz~10000MHz	-55.14	Pass
DQPSK	2480	2DH5	Band Edge	-56.84	Pass
8DPSK	2402	3DH5	0.009MHz~2380MHz	-58.85	Pass
8DPSK	2402	3DH5	10000MHz~25000MHz	-51.99	Pass

TEST REPORT

8DPSK	2402	3DH5	2410MHz~10000MHz	-55.58	Pass
8DPSK	2402	3DH5	Band Edge	-44.21	Pass
8DPSK	2441	3DH5	0.009MHz~2300MHz	-59.26	Pass
8DPSK	2441	3DH5	10000MHz~25000MHz	-51.26	Pass
8DPSK	2441	3DH5	2500MHz~10000MHz	-55.30	Pass
8DPSK	2441	3DH5	Band Edge	-59.85	Pass
8DPSK	2480	3DH5	0.009MHz~2475MHz	-58.69	Pass
8DPSK	2480	3DH5	10000MHz~25000MHz	-52.26	Pass
8DPSK	2480	3DH5	2505MHz~10000MHz	-55.82	Pass
8DPSK	2480	3DH5	Band Edge	-57.35	Pass

GFSK,2402MHz,DH5,Plot 1,Band Edge




GFSK,2402MHz,DH5,Plot 2,0.009MHz~2380 MHz



GFSK,2402MHz,DH5,Plot 3,2410MHz~10000 MHz



GFSK,2402MHz,DH5,Plot 4,10000MHz~2500 0MHz



GFSK,2441MHz,DH5,Plot 1,Band Edge




GFSK,2441MHz,DH5,Plot 2,0.009MHz~2300 MHz



GFSK,2441MHz,DH5,Plot 3,2500MHz~10000
MHz



GFSK,2441MHz,DH5,Plot 4,10000MHz~2500
0MHz



GFSK,2480MHz,DH5,Plot 1,Band Edge




GFSK,2480MHz,DH5,Plot 2,0.009MHz~2475
MHz



GFSK,2480MHz,DH5,Plot 3,2505MHz~10000
MHz



GFSK,2480MHz,DH5,Plot 4,10000MHz~2500
0MHz



DQPSK,2402MHz,2DH5,Plot 1,Band
Edge



DQPSK,2402MHz,2DH5,Plot 2,0.009MHz~23
80MHz



DQPSK,2402MHz,2DH5,Plot 3,2410MHz~100
00MHz



DQPSK,2402MHz,2DH5,Plot 4,10000MHz~25
000MHz



DQPSK,2441MHz,2DH5,Plot 1,Band
Edge



DQPSK,2441MHz,2DH5,Plot 2,0.009MHz~23
00MHz



DQPSK,2441MHz,2DH5,Plot 3,2500MHz~10000MHz



DQPSK,2441MHz,2DH5,Plot 4,10000MHz~25000MHz



DQPSK,2480MHz,2DH5,Plot 1,Band Edge




DQPSK,2480MHz,2DH5,Plot 2,0.009MHz~2475MHz



DQPSK,2480MHz,2DH5,Plot 3,2505MHz~10000MHz



DQPSK,2480MHz,2DH5,Plot 4,10000MHz~25000MHz



8DPSK,2402MHz,3DH5,Plot 1,Band
Edge



8DPSK,2402MHz,3DH5,Plot 2,0.009MHz~23
80MHz



8DPSK,2402MHz,3DH5,Plot 3,2410MHz~100
00MHz




8DPSK,2402MHz,3DH5,Plot 4,10000MHz~25
000MHz



8DPSK,2441MHz,3DH5,Plot 1,Band
Edge



8DPSK,2441MHz,3DH5,Plot 2,0.009MHz~23
00MHz




TEST REPORT

8DPSK,2441MHz,3DH5,Plot 3,2500MHz~10000MHz



8DPSK,2441MHz,3DH5,Plot 4,10000MHz~25000MHz



8DPSK,2480MHz,3DH5,Plot 1,Band Edge



8DPSK,2480MHz,3DH5,Plot 2,0.009MHz~2475MHz



8DPSK,2480MHz,3DH5,Plot 3,2505MHz~10000MHz



8DPSK,2480MHz,3DH5,Plot 4,10000MHz~25000MHz



TEST REPORT

1.5 Frequency Band Edge

1.5.1 Test Result and Data

BT Frequency Band Edges-Conducted						
Mode	Test Range (MHz)	Packet Type	Hopping Mode	Band Edge (dBm)	Limit	Result
GFSK	2380~2420	DH5	Hopping On	-59.56	-14.687	Pass
GFSK	2463.5~2503.5	DH5	Hopping On	-59.24	-13.504	Pass
DQPSK	2380~2420	2DH5	Hopping On	-60.11	-17.729	Pass
DQPSK	2463.5~2503.5	2DH5	Hopping On	-59.52	-16.756	Pass
8DPSK	2380~2420	3DH5	Hopping On	-59.41	-17.474	Pass
8DPSK	2463.5~2503.5	3DH5	Hopping On	-59.17	-16.632	Pass

GFSK,Hopping,DH5,Band Edge HighRange



GFSK,Hopping,DH5,Band Edge LowRange



DQPSK,Hopping,2DH5,Band Edge HighRange



DQPSK,Hopping,2DH5,Band Edge LowRange



8DPSK,Hopping,3DH5,Band Edge HighRange



8DPSK,Hopping,3DH5,Band Edge LowRange



TEST REPORT

1.6 Dwell Time

1.6.1 Test Result and Data

BT Dwell Time						
Mode	Test Frequency (MHz)	Packet Type	Transmission Time (ms)	Number	Dwell Time (ms)	Result
GFSK	2402	DH1	0.370	320	118.28	Pass
GFSK	2402	DH3	1.628	160	260.54	Pass
GFSK	2402	DH5	2.877	90	258.94	Pass

GFSK,2402,DH1,Transmission Number



GFSK,2402,DH1,Transmission Time



GFSK,2402,DH3,Transmission Number



GFSK,2402,DH3,Transmission Time



GFSK,2402,DH5,Transmission Number



GFSK,2402,DH5,Transmission Time



TEST REPORT

1.7 Carrier Frequency Separation

1.7.1 Test Result and Data

BT Carrier Frequency Separation					
Mode	Test Frequency (MHz)	Packet Type	Range	Separation (kHz)	Result
GFSK	Hopping	DH5	2401.5MHz~2403.5MHz	1007	Pass
GFSK	Hopping	DH5	2440.5MHz~2442.5MHz	997	Pass
GFSK	Hopping	DH5	2478.5MHz~2480.5MHz	991	Pass
DQPSK	Hopping	2DH5	2401.5MHz~2403.5MHz	1245	Pass
DQPSK	Hopping	2DH5	2440.5MHz~2442.5MHz	999	Pass
DQPSK	Hopping	2DH5	2478.5MHz~2480.5MHz	1001	Pass
8DPSK	Hopping	3DH5	2401.5MHz~2403.5MHz	995	Pass
8DPSK	Hopping	3DH5	2440.5MHz~2442.5MHz	1005	Pass
8DPSK	Hopping	3DH5	2478.5MHz~2480.5MHz	987	Pass

GFSK,Hopping,DH5,2401.5~2403.5MHz



GFSK,Hopping,DH5,2440.5~2442.5MHz



GFSK,Hopping,DH5,2478.5~2480.5MHz



DQPSK,Hopping,2DH5,2401.5~2403.5MHz



DQPSK,Hopping,2DH5,2440.5~2442.5MHz



DQPSK,Hopping,2DH5,2478.5~2480.5MHz



TEST REPORT

8DPSK,Hopping,3DH5,2401.5~2403.5MHz



8DPSK, Hopping, 3DH5, 2440.5~2442.5MHz



8DPSK,Hopping,3DH5,2478.5~2480.5MHz




TEST REPORT

1.8 Hopping Channel Numbers

1.8.1 Test Result and Data

BT Number Of Hopping Channels				
Mode	Test Frequency	Packet Type	Channel Numbers	Result
GFSK	Hopping	DH5	79	Pass
DQPSK	Hopping	2DH5	79	Pass
8DPSK	Hopping	3DH5	79	Pass


GFSK,Hopping,DH5,2400~2426.5MHz



GFSK,Hopping,DH5,2400~2483.5MHz



GFSK,Hopping,DH5,2426.5~2454.5MHz



GFSK,Hopping,DH5,2454.5~2483.5MHz



DQPSK,Hopping,2DH5,2400~2426.5MHz




DQPSK,Hopping,2DH5,2400~2483.5MHz



DQPSK,Hopping,2DH5,2426.5~2454.5MHz

DQPSK,Hopping,2DH5,2454.5~2483.5MHz


TEST REPORT



8DPSK,Hopping,3DH5,2400~2426.5MHz



8DPSK,Hopping,3DH5,2400~2483.5MHz



8DPSK,Hopping,3DH5,2426.5~2454.5MHz



8DPSK,Hopping,3DH5,2454.5~2483.5MHz

