



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170300257101
Page: 1 of 25

TEST REPORT

Application No.: SZEM1703002571RG
Applicant: Huawei Technologies Co.,Ltd.
Address of Applicant: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Manufacturer: Huawei Technologies Co.,Ltd.
Address of Manufacturer: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Factory: Huawei Technologies Co.,Ltd.
Address of Factory: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Equipment Under Test (EUT):
EUT Name: Huawei MediaPad T3 10 (MediaPad T3 10 for short)
Model No.: AGS-W09
Trade mark: HUAWEI
FCC ID: QISAGS-W09
Standards: 47 CFR Part 15,Subpart B:2016
Date of Receipt: 2017-04-05
Date of Test: 2017-04-10 to 2017-04-17
Date of Issue: 2017-04-18

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.




Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-04-18		Original

Authorized for issue by:			
Tested By			
		Gray Gao /Project Engineer	2017-04-17
Checked By			
		Eric Fu /Reviewer	2017-04-18



2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Radiated Disturbance (30MHz-1GHz)	47 CFR Part 15,Subpart B:2016	ANSI C63.4	Class B	Pass
Conducted Disturbance at Mains Terminals (150kHz-30MHz)	47 CFR Part 15,Subpart B:2016	ANSI C63.4	Class B	Pass
Radiated Disturbance (above 1GHz)	47 CFR Part 15,Subpart B:2016	ANSI C63.4	Class B	Pass

InternalSource	UpperFrequency
Below 1.705MHz	30MHz
1.705MHz to 108MHz	1GHz
108MHz to 500MHz	2GHz
500MHz to 1GHz	5GHz
Above 1GHz	5th harmonic of the highest frequency or 40GHz, whichever is lower



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 MEASUREMENT UNCERTAINTY	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST	7
6 EMISSION TEST RESULTS	9
6.1 RADIATED DISTURBANCE(30MHZ-1GHZ)	9
6.1.1 E.U.T. Operation	10
6.1.2 Test Setup Diagram	10
6.1.3 Measurement Data	10
6.2 CONDUCTED DISTURBANCE AT MAINS TERMINALS(150kHz-30MHz)	15
6.2.1 E.U.T. Operation	15
6.2.2 Test Setup Diagram	15
6.2.3 Measurement Data	15
6.3 RADIATED DISTURBANCE(ABOVE 1GHZ)	20
6.3.1 E.U.T. Operation	20
6.3.2 Test Setup Diagram	20
6.3.3 Measurement Data	20
7 PHOTOGRAPHS	25
7.1 EUT CONSTRUCTIONAL DETAILS	25



4 General Information

4.1 Details of E.U.T.

Power supply: Model No. : HW-050100U01
AC input: 100-240V 50/60Hz,0.2A
DC output: 5V 1A
Cable: USB cable: 100cm unshielded.

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conduction emission	3.0dB (150kHz to 30MHz)
2	Radiated emission	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-6GHz)
3	Temperature test	1 °C
4	Humidity test	3%



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Radiated Disturbance(30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2016-05-13	2017-05-13
EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESR	SEM004-03	2016-04-25	2017-04-25
Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-07-06	2017-07-06

Conducted Disturbance at Mains Terminals(150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	GB-88	SEM001-06	2016-05-13	2017-05-13
LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25

Radiated Disturbance(above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
Horn Antenna(1-18GHz)	Rohde & Schwarz	HF907	SEM003-06	2015-06-14	2018-06-14
Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170300257101

Page: 8 of 25

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2016-05-18	2017-05-18



6 Emission Test Results

6.1 Radiated Disturbance(30MHz-1GHz)

Test Requirement:	47 CFR Part 15, Subpart B:2016
Test Method:	ANSI C63.4
Frequency Range:	30MHz to 1GHz
Measurement Distance:	10m
Limit:	
30MHz -88MHz	29.5(dB μ V/m) quasi-peak
88MHz-216MHz	33.1(dB μ V/m) quasi-peak
216MHz-960MHz	35.6(dB μ V/m) quasi-peak
960MHz-1000MHz	43.5(dB μ V/m) quasi-peak
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30M to1000MHz

6.1.1 E.U.T. Operation


Operating Environment:

Temperature: 24.0 °C Humidity: 54 % RH Atmospheric Pressure: 1020 mbar

a: playing MP4 + earphone + battery + adapter
 Pretest these mode to find the worst case:
 b: camera(Front) + earphone + battery + adapter
 c: camera(Rear) + earphone + battery + adapter
 d: Transfer data between the EUT and the PC

The worst case for final test:
 b: camera(Front) + earphone + battery + adapter
 d: Transfer data between the EUT and the PC

6.1.2 Test Setup Diagram




6.1.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:b; Polarization:Horizontal




Condition: 10m HORIZONTAL

Job No. : 02571RG

Test Mode: b

	Freq	Cable	Ant	Preamp	Read	Limit	Over
	MHz	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	47.99	6.86	12.83	33.00	27.77	14.46	29.50 -15.04
2	86.50	7.17	8.64	32.84	33.71	16.68	29.50 -12.82
3	137.90	7.39	12.61	32.75	28.85	16.10	33.00 -16.90
4	192.42	7.56	9.67	32.71	31.07	15.59	33.00 -17.41
5	687.15	9.12	19.97	32.60	27.86	24.35	35.60 -11.25
6 pp	929.01	9.52	22.59	32.50	26.97	26.58	35.60 -9.02

Mode:b; Polarization:Vertical




Condition: 10m VERTICAL

Job No. : 02571RG

Test Mode: b

	Freq	Cable	Ant	Preamp	Read		Limit	Over
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.75	6.70	12.57	32.97	34.83	21.13	29.50	-8.37
2	67.20	6.96	10.58	32.91	30.62	15.25	29.50	-14.25
3	86.50	7.17	8.64	32.84	33.43	16.40	29.50	-13.10
4	169.01	7.50	12.51	32.72	31.12	18.41	33.00	-14.59
5	276.12	7.98	12.04	32.62	31.92	19.32	35.60	-16.28
6 pp	952.09	9.58	22.74	32.50	27.87	27.69	35.60	-7.91

Mode:d; Polarization:Horizontal




Condition: 10m HORIZONTAL

Job No. : 02571RG

Test Mode: d

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	53.75	6.98	12.47	32.98	41.90	28.37	29.50	-1.13
2	155.91	7.48	13.40	32.74	28.69	16.83	33.00	-16.17
3	257.42	7.89	11.42	32.64	34.74	21.41	35.60	-14.19
4	302.48	8.06	12.73	32.60	32.70	20.89	35.60	-14.71
5	361.71	8.30	14.10	32.60	31.86	21.66	35.60	-13.94
6	645.12	9.01	19.48	32.60	28.27	24.16	35.60	-11.44

Mode:d; Polarization:Vertical



Condition: 10m VERTICAL
Job No. : 02571RG
Test Mode: d

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	54.10	6.98	12.44	32.98	41.51	27.95	29.50	-1.55
2	156.46	7.48	13.40	32.74	32.18	20.32	33.00	-12.68
3	302.48	8.06	12.73	32.60	38.98	27.17	35.60	-8.43
4	362.98	8.30	14.13	32.60	33.39	23.22	35.60	-12.38
5	396.24	8.30	14.79	32.60	32.33	22.82	35.60	-12.78
6	942.13	9.56	22.68	32.50	27.73	27.47	35.60	-8.13

6.2 Conducted Disturbance at Mains Terminals(150kHz-30MHz)

Test Requirement:	47 CFR Part 15, Subpart B:2016
Test Method:	ANSI C63.4
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5M-5MHz	56dB(μV) quasi-peak, 46dB(μV) average
5M-30MHz	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz


6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 25.0 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

- a: playing MP4 + earphone + battery + adapter
- Pretest these mode to find the worst case:
- b: camera(Front) + earphone + battery + adapter
- c: camera(Rear) + earphone + battery + adapter
- d: Transfer data between the EUT and the PC
- The worst case for final test:
- b: camera(Front) + earphone + battery + adapter
- d: Transfer data between the EUT and the PC


6.2.2 Test Setup Diagram



6.2.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.


Mode:b; Line:Live Line



Site : Shielding Room
Condition : CE LINE
Job No. : 02571RG
Test Mode : b

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.15080	0.02	9.64	45.81	55.47	65.96	-10.48	QP
2	0.15080	0.02	9.64	26.08	35.74	55.96	-20.22	AVERAGE
3	0.20614	0.02	9.64	21.03	30.69	53.36	-22.67	AVERAGE
4	0.20614	0.02	9.64	38.94	48.60	63.36	-14.76	QP
5	0.30028	0.02	9.64	33.12	42.78	60.24	-17.45	QP
6	0.30028	0.02	9.64	15.47	25.13	50.24	-25.11	AVERAGE
7	0.73519	0.03	9.65	20.82	30.50	46.00	-15.50	AVERAGE
8	0.73519	0.03	9.65	32.34	42.01	56.00	-13.99	QP
9	1.331	0.03	9.66	34.68	44.37	56.00	-11.63	QP
10	1.331	0.03	9.66	21.15	30.84	46.00	-15.16	AVERAGE
11	11.021	0.14	9.88	21.58	31.60	50.00	-18.40	AVERAGE
12	11.021	0.14	9.88	32.48	42.50	60.00	-17.50	QP


Mode:b; Line:Neutral Line



Site : Shielding Room
Condition : CE NEUTRAL
Job No. : 02571RG
Test Mode : b

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15080	0.02	9.64	43.60	53.26	65.96	-12.70	QP
2	0.15080	0.02	9.64	23.65	33.31	55.96	-22.65	AVERAGE
3	0.22437	0.02	9.63	35.92	45.57	62.66	-17.09	QP
4	0.22437	0.02	9.63	17.33	26.98	52.66	-25.68	AVERAGE
5	0.73519	0.03	9.64	31.80	41.47	56.00	-14.53	QP
6	0.73519	0.03	9.64	18.07	27.74	46.00	-18.26	AVERAGE
7	1.032	0.03	9.64	32.89	42.56	56.00	-13.44	QP
8	1.032	0.03	9.64	21.38	31.05	46.00	-14.95	AVERAGE
9	2.066	0.03	9.66	15.73	25.42	46.00	-20.58	AVERAGE
10	2.066	0.03	9.66	24.55	34.24	56.00	-21.76	QP
11	10.905	0.14	9.87	22.82	32.83	50.00	-17.17	AVERAGE
12	10.905	0.14	9.87	32.67	42.68	60.00	-17.32	QP


Mode:d; Line:Live Line



Site : Shielding Room
Condition : CE LINE
Job No. : 02571RG
Test Mode : d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.17034	0.02	9.64	44.66	54.32	64.94	-10.63	QP
2	0.17034	0.02	9.64	14.34	24.00	54.94	-30.95	AVERAGE
3	0.22556	0.02	9.64	5.28	14.94	52.61	-37.67	AVERAGE
4	0.22556	0.02	9.64	36.57	46.23	62.61	-16.38	QP
5	0.60112	0.02	9.65	22.30	31.97	56.00	-24.03	QP
6	0.60112	0.02	9.65	6.04	15.72	46.00	-30.28	AVERAGE
7	1.456	0.03	9.66	9.43	19.12	46.00	-26.88	AVERAGE
8	1.456	0.03	9.66	19.20	28.89	56.00	-27.11	QP
9	2.962	0.03	9.69	15.09	24.80	56.00	-31.20	QP
10	2.962	0.03	9.69	7.41	17.13	46.00	-28.87	AVERAGE
11	11.498	0.15	9.89	11.41	21.44	50.00	-28.56	AVERAGE
12	11.498	0.15	9.89	17.88	27.92	60.00	-32.08	QP

Mode:d; Line:Neutral Line



Site : Shielding Room
Condition : CE NEUTRAL
Job No. : 02571RG
Test Mode : d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.17678	0.02	9.63	44.91	54.56	64.64	-10.07	QP
2	0.17678	0.02	9.63	21.15	30.80	54.64	-23.83	AVERAGE
3	0.23784	0.02	9.63	21.21	30.86	52.17	-21.31	AVERAGE
4	0.23784	0.02	9.63	35.65	45.30	62.17	-16.87	QP
5	0.30998	0.02	9.63	29.93	39.58	59.97	-20.39	QP
6	0.30998	0.02	9.63	16.20	25.85	49.97	-24.12	AVERAGE
7	1.619	0.03	9.65	10.69	20.37	46.00	-25.63	AVERAGE
8	1.619	0.03	9.65	21.32	31.00	56.00	-25.00	QP
9	3.584	0.02	9.68	13.44	23.14	56.00	-32.86	QP
10	3.584	0.02	9.68	4.92	14.63	46.00	-31.37	AVERAGE
11	13.695	0.15	9.94	16.30	26.39	50.00	-23.61	AVERAGE
12	13.695	0.15	9.94	22.65	32.74	60.00	-27.26	QP


6.3 Radiated Disturbance(above 1GHz)

Test Requirement: 47 CFR Part 15, Subpart B:2016
Test Method: ANSI C63.4
Frequency Range: Above 1GHz
Measurement Distance: 3m
Limit:
Above 1GHz 74(dBμV/m) peak, 54(dBμV/m) average
Detector: Peak for pre-scan (1000kHz resolution bandwidth) 1000M to 18000MHz

6.3.1 E.U.T. Operation

Operating Environment:
Temperature: 24.0 °C Humidity: 58 % RH Atmospheric Pressure: 1020 mbar
a: playing MP4 + earphone + battery + adapter
Pretest these mode to find the worst case:
b: camera(Front) + earphone + battery + adapter
c: camera(Rear) + earphone + battery + adapter
d: Transfer data between the EUT and the PC
The worst case for final test:
b: camera(Front) + earphone + battery + adapter
d: Transfer data between the EUT and the PC

6.3.2 Test Setup Diagram




6.3.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:b; Polarization:Horizontal



Condition: 3m Horizontal


Job No: : 02571RG

Mode: : b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2376.003	5.33	29.04	37.96	43.31	39.72	74.00	-34.28	Peak
2	3725.315	6.49	32.85	37.97	43.97	45.34	74.00	-28.66	Peak
3 pp	5585.026	8.34	34.45	38.38	43.60	48.01	74.00	-25.99	Peak



Mode:b; Polarization:Vertical




Condition: 3m Vertical
Job No: : 02571RG
Mode: : b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2141.481	5.14	28.29	37.99	43.25	38.69	74.00	-35.31	Peak
2	3725.315	6.49	32.85	37.97	42.97	44.34	74.00	-29.66	Peak
3 pp	5726.896	8.48	34.54	38.35	43.59	48.26	74.00	-25.74	Peak



Mode:d; Polarization:Horizontal



Condition: 3m Horizontal


Job No: : 02571RG

Mode: : d

	Freq	Cable	Ant	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1796.617	4.81	27.05	38.02	49.06	42.90	74.00	-31.10 Peak
2	2388.809	5.34	29.07	37.96	50.40	46.85	74.00	-27.15 Peak
3 pp	5349.948	8.18	34.43	38.43	45.98	50.16	74.00	-23.84 Peak



Mode:d; Polarization:Vertical



Condition: 3m Vertical

Job No: : 02571RG

Mode: : d

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1996.946	5.01	27.79	38.00	53.09	47.89	74.00	-26.11	Peak
2	pp 2397.385	5.34	29.10	37.96	57.28	53.76	74.00	-20.24	Peak
3	3199.044	6.08	31.68	37.92	50.53	50.37	74.00	-23.63	Peak



7 Photographs

7.1 EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1703002571RG.