



中国认可  
国际互认  
检测  
TESTING  
CNAS L0310



## FCC SAR Compliance Test Report

**Product Name:** Smart Phone

**Model:** BND-L24, BND-L34

**Report No.:** SYBH(Z-SAR)005102017-2

**FCC ID:** QISBND-L24

|      |                           |                             |
|------|---------------------------|-----------------------------|
|      | APPROVED<br>(Lab Manager) | PREPARED<br>(Test Engineer) |
| BY   | <i>Wei Huanbin</i>        | <i>Zhang Chao</i>           |
| DATE | 2017-11-19                | 2017-11-19                  |

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

**(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)**

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,  
Shenzhen, 518129, P.R.C  
Tel: +86 755 28780808 Fax: +86 755 89652518

---

※ ※ **Notice** ※ ※

1. The laboratory has passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01 & 2174.02 & 2174.03
3. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
4. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
5. The test report is invalid if there is any evidence of erasure and/or falsification.
6. The test report is only valid for the test samples.
7. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

# Table of Contents

|                                                                       |           |
|-----------------------------------------------------------------------|-----------|
| <b>Table of Contents</b>                                              | <b>3</b>  |
| <b>1 General Information</b>                                          | <b>6</b>  |
| 1.1 Statement of Compliance                                           | 6         |
| 1.2 RF exposure limits                                                | 7         |
| 1.3 EUT Description                                                   | 8         |
| 1.3.1 General Description                                             | 10        |
| 1.3.2 Dynamic antenna switching specification                         | 12        |
| 1.3.3 Dynamic antenna tuning Test Configurations                      | 12        |
| 1.3.4 Power reduction specification                                   | 13        |
| 1.4 Test specification(s)                                             | 15        |
| 1.5 Testing laboratory                                                | 15        |
| 1.6 Applicant and Manufacturer                                        | 15        |
| 1.7 Application details                                               | 15        |
| 1.8 Ambient Condition                                                 | 15        |
| <b>2 SAR Measurement System</b>                                       | <b>16</b> |
| 2.1 SAR Measurement Set-up                                            | 16        |
| 2.2 Test environment                                                  | 17        |
| 2.3 Data Acquisition Electronics description                          | 17        |
| 2.4 Probe description                                                 | 18        |
| 2.5 Phantom description                                               | 19        |
| 2.6 Device holder description                                         | 20        |
| 2.7 Test Equipment List                                               | 21        |
| <b>3 SAR Measurement Procedure</b>                                    | <b>22</b> |
| 3.1 Scanning procedure                                                | 22        |
| 3.2 Spatial Peak SAR Evaluation                                       | 23        |
| 3.3 Data Storage and Evaluation                                       | 24        |
| <b>4 System Verification Procedure</b>                                | <b>26</b> |
| 4.1 Tissue Verification                                               | 26        |
| 4.2 System Check                                                      | 30        |
| 4.3 System check Procedure                                            | 31        |
| <b>5 SAR measurement variability and uncertainty</b>                  | <b>32</b> |
| 5.1 SAR measurement variability                                       | 32        |
| 5.2 SAR measurement uncertainty                                       | 32        |
| <b>6 SAR Test Configuration</b>                                       | <b>33</b> |
| 6.1 Test Positions Configuration                                      | 33        |
| 6.1.1 General considerations                                          | 33        |
| 6.1.2 Head Exposure Condition                                         | 33        |
| 6.1.3 Body-worn Exposure Condition                                    | 34        |
| 6.1.4 Hotspot Exposure Condition                                      | 34        |
| 6.1.5 Product specific 10-g Exposure Condition                        | 35        |
| 6.1.6 Capacitive proximity sensor power reduction test configurations | 35        |
| 6.1.7 Infrared proximity sensor power reduction test Configuration    | 45        |
| 6.2 3G SAR Test Reduction Procedure                                   | 48        |
| 6.3 GSM Test Configuration                                            | 48        |
| 6.4 UMTS Test Configuration                                           | 49        |
| 6.5 LTE Test Configuration                                            | 55        |
| 6.6 WiFi Test Configuration                                           | 57        |
| 6.6.1 Initial Test Position Procedure                                 | 57        |
| 6.6.2 Initial Test Configuration Procedure                            | 57        |
| 6.6.3 Sub Test Configuration Procedure                                | 57        |
| 6.6.4 WiFi 2.4G SAR Test Procedures                                   | 58        |
| 6.7 BT Test Configuration                                             | 58        |
| <b>7 SAR Measurement Results</b>                                      | <b>59</b> |
| 7.1 Conducted power measurements                                      | 59        |
| 7.1.1 Conducted power measurements of GSM850 (Second Antenna)         | 60        |

|        |                                                                     |     |
|--------|---------------------------------------------------------------------|-----|
| 7.1.2  | Conducted power measurements of GSM1900 (Second Antenna) .....      | 61  |
| 7.1.3  | Conducted power measurements of UMTS Band II (Second Antenna) ..... | 62  |
| 7.1.4  | Conducted power measurements of UMTS Band IV (Second Antenna) ..... | 64  |
| 7.1.5  | Conducted power measurements of UMTS Band V (Second Antenna) .....  | 66  |
| 7.1.6  | Conducted power measurements of LTE Band II (Second Antenna) .....  | 68  |
| 7.1.7  | Conducted power measurements of LTE Band IV (Second Antenna) .....  | 77  |
| 7.1.8  | Conducted power measurements of LTE Band V(Second Antenna) .....    | 86  |
| 7.1.9  | Conducted power measurements of LTE Band VII (Second Antenna) ..... | 92  |
| 7.1.10 | Conducted power measurements of LTE Band XII (Second Antenna) ..... | 98  |
| 7.1.11 | Conducted power measurements of LTE Band XVII (Second Antenna)..... | 104 |
| 7.1.12 | Conducted power measurements of GSM850 (Main Antenna) .....         | 107 |
| 7.1.13 | Conducted power measurements of GSM1900 (Main Antenna) .....        | 108 |
| 7.1.14 | Conducted power measurements of UMTS Band II (Main Antenna) .....   | 109 |
| 7.1.15 | Conducted power measurements of UMTS Band IV (Main Antenna).....    | 111 |
| 7.1.16 | Conducted power measurements of UMTS Band V (Main Antenna).....     | 113 |
| 7.1.17 | Conducted power measurements of LTE Band II (Main Antenna).....     | 114 |
| 7.1.18 | Conducted power measurements of LTE Band IV (Main Antenna) .....    | 126 |
| 7.1.19 | Conducted power measurements of LTE Band V(Main Antenna) .....      | 138 |
| 7.1.20 | Conducted power measurements of LTE Band VII (Main Antenna) .....   | 142 |
| 7.1.21 | Conducted power measurements of LTE Band XII (Main Antenna) .....   | 150 |
| 7.1.22 | Conducted power measurements of LTE Band XVII (Main Antenna) .....  | 152 |
| 7.1.23 | Conducted power measurements of WiFi 2.4G.....                      | 153 |
| 7.1.24 | Conducted power measurements of BT .....                            | 154 |
| 7.2    | SAR measurement Results.....                                        | 155 |
| 7.2.1  | SAR measurement Result of GSM850 (Second Antenna) .....             | 157 |
| 7.2.2  | SAR measurement Result of GSM1900 (Second Antenna) .....            | 159 |
| 7.2.3  | SAR measurement Result of UMTS Band II(Second Antenna) .....        | 161 |
| 7.2.4  | SAR measurement Result of UMTS Band IV(Second Antenna).....         | 163 |
| 7.2.5  | SAR measurement Result of UMTS Band V(Second Antenna).....          | 165 |
| 7.2.6  | SAR measurement Result of LTE Band II(Second Antenna) .....         | 167 |
| 7.2.7  | SAR measurement Result of LTE Band IV(Second Antenna) .....         | 170 |
| 7.2.8  | SAR measurement Result of LTE Band V(Second Antenna) .....          | 173 |
| 7.2.9  | SAR measurement Result of LTE Band VII(Second Antenna) .....        | 176 |
| 7.2.10 | SAR measurement Result of LTE Band XII(Second Antenna) .....        | 179 |
| 7.2.11 | SAR measurement Result of LTE Band XVII(Second Antenna).....        | 181 |
| 7.2.12 | SAR measurement Result of GSM850(Main Antenna).....                 | 182 |
| 7.2.13 | SAR measurement Result of GSM1900(Main Antenna).....                | 184 |
| 7.2.14 | SAR measurement Result of UMTS Band II(Main Antenna) .....          | 187 |
| 7.2.15 | SAR measurement Result of UMTS Band IV(Main Antenna) .....          | 191 |
| 7.2.16 | SAR measurement Result of UMTS Band V(Main Antenna).....            | 195 |
| 7.2.17 | SAR measurement Result of LTE Band II (Main Antenna).....           | 196 |
| 7.2.18 | SAR measurement Result of LTE Band IV(Main Antenna) .....           | 201 |
| 7.2.19 | SAR measurement Result of LTE Band V(Main Antenna) .....            | 206 |
| 7.2.20 | SAR measurement Result of LTE Band VII(Main Antenna) .....          | 209 |
| 7.2.21 | SAR measurement Result of LTE Band XII(Main Antenna) .....          | 212 |
| 7.2.22 | SAR measurement Result of LTE Band XVII(Main Antenna) .....         | 213 |
| 7.2.23 | SAR measurement Result of WiFi 2.4G .....                           | 214 |
| 7.3    | Multiple Transmitter Evaluation.....                                | 216 |
| 7.3.1  | Stand-alone SAR test exclusion.....                                 | 217 |
| 7.3.2  | Simultaneous Transmission Possibilities .....                       | 218 |
| 7.3.3  | SAR Summation Scenario .....                                        | 219 |
| 7.3.4  | Simultaneous Transmission Conclusion .....                          | 219 |
|        | Appendix A. System Check Plots .....                                | 220 |
|        | Appendix B. SAR Measurement Plots .....                             | 220 |
|        | Appendix C. Calibration Certificate .....                           | 220 |
|        | Appendix D. Photo documentation .....                               | 220 |
|        | <b>End</b> .....                                                    | 220 |

---

※ ※ Modified History ※ ※

| REV.    | DESCRIPTION                  | ISSUED<br>DATE | REMARK     |
|---------|------------------------------|----------------|------------|
| Rev.1.0 | Initial Test Report Release. | 2017-11-19     | Zhang Chao |
|         |                              |                |            |
|         |                              |                |            |
|         |                              |                |            |
|         |                              |                |            |

## 1 General Information

### 1.1 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for BND-L24, BND-L34 is as below Table 1.

| Band                                                                                                                                                                                                                               | Max Reported SAR(W/kg) |                           |                       |                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|---------------------------|-----------------------|------------------------------|
|                                                                                                                                                                                                                                    | 1-g Head SAR           | 1-g Body-worn SAR(15mm) * | 1-g Hotspot SAR(10mm) | Product Specific 10-g SAR ** |
| GSM850                                                                                                                                                                                                                             | 1.00                   | 0.48                      | 0.59                  | /                            |
| GSM1900                                                                                                                                                                                                                            | 0.44                   | 0.50                      | 0.95                  | 0.26                         |
| UMTS Band II                                                                                                                                                                                                                       | 0.81                   | <b>1.11</b>               | 1.03                  | 1.43                         |
| UMTS Band IV                                                                                                                                                                                                                       | <b>1.11</b>            | 0.86                      | <b>1.27</b>           | 2.27                         |
| UMTS Band V                                                                                                                                                                                                                        | 0.86                   | 0.49                      | 0.65                  | /                            |
| LTE Band II                                                                                                                                                                                                                        | 0.71                   | 1.05                      | 0.80                  | <b>2.40</b>                  |
| LTE Band IV                                                                                                                                                                                                                        | 0.95                   | 0.88                      | 0.79                  | 1.97                         |
| LTE Band V                                                                                                                                                                                                                         | 0.97                   | 0.42                      | 0.52                  | /                            |
| LTE Band VII                                                                                                                                                                                                                       | 0.95                   | 0.29                      | 0.19                  | /                            |
| LTE Band XII                                                                                                                                                                                                                       | 1.01                   | 0.38                      | 0.45                  | /                            |
| LTE Band XVII                                                                                                                                                                                                                      | /                      | /                         | /                     | /                            |
| WiFi 2.4G                                                                                                                                                                                                                          | 0.32                   | 0.07                      | 0.18                  | /                            |
| BT                                                                                                                                                                                                                                 | /                      | /                         | /                     | /                            |
| <b>The highest reported SAR for head, body-worn, hotspot, simultaneous transmission and product specific 10-g SAR exposure conditions are 1.11W/kg, 1.11W/kg, 1.27W/kg, 1.43W/kg and 2.40 W/kg respectively per KDB690783 D01.</b> |                        |                           |                       |                              |

Table 1:Summary of test result

Note:

- 1)\* For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and that positions the handset a minimum of 15mm from the body. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.
- 2) According to TCB workshop October,2014 RF Exposure Procedures Update(Overlapping LTE Bands):
  - a) Main and Second Antenna SAR for LTE Band 17 (Frequency range:704-716 MHz) is covered by LTE Band 12 (Frequency range:699-716 MHz) due to similar frequency range,same maximum tune up limit and same channel bandwidth.

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits according to the FCC rule §2.1093, the ANSI C95.1:1992/IEEE C95.1:1991, the NCRP Report Number 86 for uncontrolled environment, according to the Industry Canada Radio Standards Specification RSS-102 for General Population/Uncontrolled exposure, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013.

## 1.2 RF exposure limits

| Human Exposure                                         | Uncontrolled Environment<br>General Population | Controlled Environment<br>Occupational |
|--------------------------------------------------------|------------------------------------------------|----------------------------------------|
| <b>Spatial Peak SAR*</b><br>(Brain/Body/Arms/Legs)     | <b>1.60 W/kg</b>                               | 8.00 W/kg                              |
| <b>Spatial Average SAR**</b><br>(Whole Body)           | 0.08 W/kg                                      | 0.40 W/kg                              |
| <b>Spatial Peak SAR***</b><br>(Hands/Feet/Ankle/Wrist) | <b>4.00 W/kg</b>                               | 20.00 W/kg                             |

Table 2: RF exposure limits

The limit applied in this test report is shown in **bold** letters

Notes:

- \* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
- \*\* The Spatial Average value of the SAR averaged over the whole body.
- \*\*\* The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

### 1.3 EUT Description

| Device Information:              |                                                                                                                                              |             |           |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------|
| Product Name:                    | Smart Phone                                                                                                                                  |             |           |
| Model:                           | BND-L24, BND-L34                                                                                                                             |             |           |
| FCC ID :                         | QISBND-L24                                                                                                                                   |             |           |
| SN.:                             | 1#: R9G0117901000016<br>2#: R9G0117901000047<br>3#: R9G0117901000102<br>4#: R9G0117901000304<br>5#: R9G0117901000020<br>6#: R9G0117901000191 |             |           |
| Device Type :                    | Portable device                                                                                                                              |             |           |
| Device Phase:                    | Identical Prototype                                                                                                                          |             |           |
| Exposure Category:               | Uncontrolled environment / general population                                                                                                |             |           |
| Hardware Version :               | HL4BNDM                                                                                                                                      |             |           |
| Software Version :               | BND-L24C900B088                                                                                                                              |             |           |
| Antenna Type :                   | Internal antenna                                                                                                                             |             |           |
| Others Accessories               | Headset                                                                                                                                      |             |           |
| Device Operating Configurations: |                                                                                                                                              |             |           |
| Supporting Mode(s)               | GSM 850/1900, UMTS Band II/IV/V, LTE Band II/IV/V/VII/XII/XVII, WiFi 2.4G; BT                                                                |             |           |
| Test Modulation                  | GSM(GMSK/8PSK), UMTS(QPSK), LTE(QPSK/16QAM), WiFi(DSSS/OFDM), BT(GFSK)                                                                       |             |           |
| Device Class                     | B                                                                                                                                            |             |           |
| Operating Frequency Range(s)     | Band                                                                                                                                         | Tx (MHz)    | Rx (MHz)  |
|                                  | GSM850                                                                                                                                       | 824-849     | 869-894   |
|                                  | PCS1900                                                                                                                                      | 1850-1910   | 1930-1990 |
|                                  | UMTS Band II                                                                                                                                 | 1850-1910   | 1930-1990 |
|                                  | UMTS Band IV                                                                                                                                 | 1710–1755   | 2110–2155 |
|                                  | UMTS Band V                                                                                                                                  | 824-849     | 869-894   |
|                                  | LTE Band II                                                                                                                                  | 1850-1910   | 1930-1990 |
|                                  | LTE Band IV                                                                                                                                  | 1710–1755   | 2110–2155 |
|                                  | LTE Band V                                                                                                                                   | 824-849     | 869-894   |
|                                  | LTE Band VII                                                                                                                                 | 2500-2570   | 2620-2690 |
|                                  | LTE Band XII                                                                                                                                 | 699-716     | 729-746   |
|                                  | LTE Band XVII                                                                                                                                | 704-716     | 734-746   |
|                                  | BT                                                                                                                                           | 2400-2483.5 |           |
|                                  | WiFi 2.4G                                                                                                                                    | 2412-2462   |           |
| GPRS Multislot Class(12)         | Max Number of Timeslots in Uplink:                                                                                                           |             | 4         |
|                                  | Max Number of Timeslots in Downlink:                                                                                                         |             | 4         |
|                                  | Max Total Timeslot:                                                                                                                          |             | 5         |
| EGPRS Multislot Class(12)        | Max Number of Timeslots in Uplink:                                                                                                           |             | 4         |
|                                  | Max Number of Timeslots in Downlink:                                                                                                         |             | 4         |
|                                  | Max Total Timeslot:                                                                                                                          |             | 5         |
| HSDPA UE Category                | 14                                                                                                                                           |             |           |
| HSUPA UE Category                | 6                                                                                                                                            |             |           |
| DC-HSDPA UE Category             | 24                                                                                                                                           |             |           |
| Power Class:                     | 4,tested with power level 5(GSM850)                                                                                                          |             |           |
|                                  | 1,tested with power level 0(GSM1900)                                                                                                         |             |           |
|                                  | 3, tested with power control “all 1”(UMTS Band II)                                                                                           |             |           |

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
|                               | 3, tested with power control "all 1"(UMTS Band IV)   |
|                               | 3, tested with power control "all 1"(UMTS Band V)    |
|                               | 3, tested with power control all Max.(LTE Band II)   |
|                               | 3, tested with power control all Max.(LTE Band IV)   |
|                               | 3, tested with power control all Max.(LTE Band V)    |
|                               | 3, tested with power control all Max.(LTE Band VII)  |
|                               | 3, tested with power control all Max.(LTE Band XII)  |
|                               | 3, tested with power control all Max.(LTE Band XVII) |
| Test Channels (low-mid-high): | 128-190-251(GSM850)                                  |
|                               | 512-661-810(GSM1900)                                 |
|                               | 9262-9400-9538(UMTS Band II)                         |
|                               | 1312-1413-1513(UMTS Band IV)                         |
|                               | 4132-4182-4233(UMTS Band V)                          |
|                               | 18607-18900-19193(LTE Band II BW=1.4MHz)             |
|                               | 18615-18900-19185(LTE Band II BW=3MHz)               |
|                               | 18625-18900-19175(LTE Band II BW=5MHz)               |
|                               | 18650-18900-19150(LTE Band II BW=10MHz)              |
|                               | 18675-18900-19125(LTE Band II BW=15MHz)              |
|                               | 18700-18900-19100(LTE Band II BW=20MHz)              |
|                               | 19957-20175-20393(LTE Band IV BW=1.4MHz)             |
|                               | 19965-20175-20385(LTE Band IV BW=3MHz)               |
|                               | 19975-20175-20375(LTE Band IV BW=5MHz)               |
|                               | 20000-20175-20350 (LTE Band IV BW=10MHz)             |
|                               | 20025-20175-20325 (LTE Band IV BW=15MHz)             |
|                               | 20050-20175-20300(LTE Band IV BW=20MHz)              |
|                               | 20407-20525-20643(LTE Band V BW=1.4MHz)              |
|                               | 20415-20525-20635(LTE Band V BW=3MHz)                |
|                               | 20425-20525-20625(LTE Band V BW=5MHz)                |
|                               | 20450-20525-20600(LTE Band V BW=10MHz)               |
|                               | 20775-21100-21425(LTE Band VII BW=5MHz)              |
|                               | 20800-21100-21400(LTE Band VII BW=10MHz)             |
|                               | 20825-21100-21375(LTE Band VII BW=15MHz)             |
|                               | 20850-21100-21350 (LTE Band VII BW=20MHz)            |
|                               | 23017-23095-23173(LTE Band XII BW=1.4MHz)            |
|                               | 23025-23095-23165(LTE Band XII BW=3MHz)              |
|                               | 23035-23095-23155(LTE Band XII BW=5MHz)              |
|                               | 23060-23095-23130(LTE Band XII BW=10MHz)             |
|                               | 23755-23790-23825(LTE Band XVII BW=5MHz)             |
|                               | 23780-23790-23800(LTE Band XVII BW=10MHz)            |
|                               | 802.11b/g/n 20M:1-6-11                               |
|                               | 802.11n 40M:3-6-9                                    |
|                               | BT: 0-19-39-78                                       |

Table 3: Device information and operating configuration

### 1.3.1 General Description

BND-L24, BND-L34 is subscriber equipment in the GSM/UMTS/LTE system. The GSM frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900. but only GSM850/1900 test data included in this report.

The UMTS frequency band is band I and band II and band IV and band V ,but only band II and Band IV and Band V test data included in this report.

The LTE frequency band is Band II band IV and band V and band VII and Band XII and Band XVII,all Bands test data included in this report.

The Mobile Phone implements such functions as RF signal receiving/transmitting, LTE/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS and Wi-Fi etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

Battery information :

| Name               | Manufacture                        | Description                                                                      |
|--------------------|------------------------------------|----------------------------------------------------------------------------------|
| Li-Polymer Battery | Desay Battery Co., Ltd.            | Battery Model: HB356687ECW<br>Rated capacity: 3240mAh<br>Nominal Voltage: +3.82V |
|                    | Sunwoda Electronic Co., LTD        |                                                                                  |
|                    | SCUD (FUJIAN) Electronics Co., Ltd |                                                                                  |

### Difference description:

The difference between BND-L24 and BND-L34 is show in the below table:

|                      |                            | Model: BND-L24               | Model: BND-L34               |
|----------------------|----------------------------|------------------------------|------------------------------|
| Brand                | Brand name                 | Honor                        | HUAWEI                       |
| Licensed Frequency   | LTE BAND                   | FDD:B2/B4/B5/B7/B12/B17 same | FDD:B2/B4/B5/B7/B12/B17 same |
|                      | UMTS BAND                  | B1/B2/B4/B5 same             | B1/B2/B4/B5 same             |
|                      | GSM                        | 850/900/1800/1900 same       | 850/900/1800/1900 same       |
|                      | Antenna                    | Same                         | same                         |
| Unlicensed Frequency | Bluetooth                  | BT4.1 same                   | BT4.1 same                   |
|                      | 2.4G Wi-Fi                 | Same                         | same                         |
|                      | Antenna                    | Same                         | same                         |
| Hardware             | Ram / Rom                  | 3GB+32GB                     | 4GB+64GB                     |
|                      | PCB                        | Same                         | same                         |
|                      | USB Port                   | Same                         | same                         |
| Appearance           | Dimension                  | Same(156.5x75.3x7.6mm)       | Same(156.5x75.3x7.6mm)       |
| Accessory            | Battery                    | Same 3340mAh(typical)        | Same 3340mAh(typical)        |
|                      | External Charger           | Same                         | same                         |
|                      | USB label                  | Same                         | same                         |
|                      | Earphone                   | Same                         | same                         |
| others               | Decorative parts of Camera | Get the details in below     | Get the details in below     |

The difference of decorative parts of Camera:

Bond-L24



Bond-L34



**According to the difference description above, full test is performed on BND-L24. BND-L34 shares the same test data of BND-L24.**

### 1.3.2 Dynamic antenna switching specification

The device has two 2G/3G/4G Tx antennas (Main Antenna and Second Antenna). It can transmit from either Main Antenna or Second Antenna, but they can not transmit simultaneously.

SAR test procedure for dynamic antenna switching is as below:

During the SAR test, the Main Antenna (Ant 1) and Second Antenna (Ant2) are set to the MAX transmit power level respectively and test the SAR respectively in all applicable RF exposure conditions. Some AT commands are supplied to fix the operation state and choose the antenna, and some test scripts are supplied to fix the modem state so that only one TX antenna and one modem is chosen and tested at a time. We can ensure that all independent antennas and modems are completely covered by the appropriate SAR measurements and all simultaneous transmission possibilities are fully considered.

### 1.3.3 Dynamic antenna tuning Test Configurations

The device also supports the dynamic antenna tuning function to optimize transmission efficiency for 1710MHz~2700MHz frequency operations, especially in any hand usage scenario.

**The dynamic antenna tuning function is only applicable for some frequency bands of the 2G/3G/4G main Tx antenna: GSM1900, UMTS Band II/IV, LTE Band II/IV/VII;** which is located in the bottom part of the device. The 2G/3G/4G main antenna has two fixed states for these tuning bands: the state 1 and state 2. Two states shares the same antenna, RF path, test channel and conductive power. The software will choose better RSSI as the working state of the main TX antenna based on the RSSI comparison and switch algorithm.

The antenna tuning and operating parameters are implemented using a fixed table look-up mechanism that is fully contained within the approved transmitter; therefore, antenna tuning is static and remains unchanged for the same device operating configurations. PAG is not required per KDB388624D02.

SAR test procedure for dynamic antenna tuning is as below:

- a) Firstly, some test script are used to fix the tuning state at state1 or state 2, so that only one antenna tuning state is chosen at a time for SAR test.
- b) Secondly, in order to reduce the number of SAR tests required to demonstrate compliance for the two tuning states, one single point zoom scan SAR measurement between state1 and state 2 for each antenna tuning band and applicable RF exposure condition is considered to identify the higher SAR tuning state that need the full set of normally required SAR measurements and allow SAR test reduction for the other lower SAR conditions.
- c) Thirdly, full normally required SAR measurements are performed for the chosen higher SAR tuning state. The SAR worst case will also be checked for the other state in each antenna tuning band and applicable RF exposure condition to ensure the SAR compliance

### 1.3.4 Power reduction specification

#### 1) Power reduction triggered by specific use conditions(2G&3G&4G Second antenna)

This device uses the receiver to indicate whether the user is making a voice call in head scenario or not. The selection between head and body power levels is based on the receiver detection mechanism.

The following tables summarize the key power reduction information triggered by specific use conditions. The detailed full power and reduced conducted power measurement results are provided in Section 7 of this report:

| Band          | Power Reduction Level Amount (dB)         |                                      |                                                                                       |
|---------------|-------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|
|               | Second Antenna                            |                                      |                                                                                       |
|               | Second antenna only,<br>Receiver on(Head) | Second antenna only,<br>Receiver off | Second antenna+WiFi antenna<br>Simultaneous Transmission<br>(wifi station or hotspot) |
| GSM850        | 3.0                                       | 0                                    | 5.0                                                                                   |
| GSM1900       | 2.0                                       | 0                                    | 5.0                                                                                   |
| UMTS Band II  | 3.0                                       | 0                                    | 6.0                                                                                   |
| UMTS Band IV  | 2.0                                       | 0                                    | 4.0                                                                                   |
| UMTS Band V   | 3.5                                       | 0                                    | 6.0                                                                                   |
| LTE Band II   | 4.4                                       | 0                                    | 6.4                                                                                   |
| LTE Band IV   | 2.0                                       | 0                                    | 5.5                                                                                   |
| LTE Band V    | 3.5                                       | 0                                    | 6.5                                                                                   |
| LTE Band VII  | 6.5                                       | 0                                    | 8.3                                                                                   |
| LTE Band XII  | 2.5                                       | 0                                    | 6.0                                                                                   |
| LTE Band XVII | 2.5                                       | 0                                    | 6.0                                                                                   |

The SAR test plan is as below:

- For Head SAR test of 2G/3G/4G Second Antenna, Standalone Head SAR should be evaluated at power level A(Audio Receiver on). In the LTE and UMTS VOIP test mode, as the test lab can not simulate the actual user scenarios to trigger the receiver on. A test script is used to trigger the receiver on during the test. The TX power and SAR value during the test is the same as the actual user scenarios.
- For Body /Hotspot Product Specific 10-g SAR test of 2G/3G/4G Second Antenna, Standalone Body SAR should be evaluated at power level B (Audio Receiver off) ;

## 2) Power reduction triggered by proximity sensor and hotspot (2G&3G&4G Main antenna)

This device uses a capacitive proximity sensor that share the same metallic electrode as the transmitting antenna to facilitate triggering in typical user interactivity with the device per KDB616217.

Due to the operating configurations and exposure conditions required by the device, the proximity sensor is used to indicate when the device is held close to a user's body exposure condition. It utilizes the proximity sensor to reduce the output power in specific wireless and operating modes to ensure SAR compliance for the following scenarios: To reduce the output power of main antennas during body operating configurations.

A fixed level power reduction is also applied for some frequency bands when hotspot mode becomes active. When the hotspot is disabled, the power value will be recovered.

The following tables summarize the key power reduction information. The detailed full power and reduced tune-up specifications and conducted power measurement results are provided in Section 6.1.6 and Section 7 of this report.

| Band         | Power Reduction Level Amount (dB) |            |                                      |                                                      |
|--------------|-----------------------------------|------------|--------------------------------------|------------------------------------------------------|
|              | Main Antenna                      |            |                                      |                                                      |
|              | Full power<br>(Other conditions)  | Hotspot on | Receiver off,<br>proximity sensor on | Receiver off,<br>hotspot on +<br>proximity sensor on |
| GSM 1900     | 0                                 | 0          | 2.0                                  | 2.0                                                  |
| UMTS Band II | 0                                 | 3.0        | 2.0                                  | 5.0                                                  |
| UMTS Band IV | 0                                 | 3.0        | 2.0                                  | 6.0                                                  |
| LTE Band II  | 0                                 | 4.3        | 2.0                                  | 6.2                                                  |
| LTE Band IV  | 0                                 | 4.0        | 2.0                                  | 5.5                                                  |
| LTE Band V   | 0                                 | 0          | 2.0                                  | 2.0                                                  |
| LTE Band VII | 0                                 | 5.0        | 2.0                                  | 7.0                                                  |

## 3) Power reduction triggered by infrared proximity sensor(WiFi antenna)

The device uses an infrared proximity sensor to reduce the output power of WiFi antenna when WiFi and 2G&3G&4G antenna voice mode transmit simultaneously in held-to-ear scenario.

The following tables summarize the key power reduction information. The detailed full power and reduced tune-up specifications and conducted power measurement results are provided in Section 6.1.7 and Section 7 of this report.

| Band                   | Power Reduction Level Amount (dB) |                                                             |                                           |
|------------------------|-----------------------------------|-------------------------------------------------------------|-------------------------------------------|
|                        | WiFi Antenna only                 | WiFi Antenna and 2G&3G&4G antenna simultaneous transmission |                                           |
|                        |                                   | infrared proximity sensor off                               | infrared proximity sensor on (Voice mode) |
| WiFi 2.4G 802.11b      | 0                                 | 0                                                           | 5.5                                       |
| WiFi 2.4G 802.11g      | 0                                 | 0                                                           | 6.0                                       |
| WiFi 2.4G 802.11n(20M) | 0                                 | 0                                                           | 6.0                                       |
| WiFi 2.4G 802.11n(40M) | 0                                 | 0                                                           | 3.5                                       |

#### 1.4 Test specification(s)

|                                  |                                                                                                                                                                             |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI C95.1:1992 /IEEE C95.1:1991 | Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.( IEEE Std C95.1-1991)                                              |
| IEEE Std 1528-2013               | Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques |
| KDB941225 D01                    | 3G SAR Procedures v03r01                                                                                                                                                    |
| KDB941225 D05                    | SAR for LTE Devices v02r05                                                                                                                                                  |
| KDB941225 D06                    | Hotspot SAR v02r01                                                                                                                                                          |
| KDB447498 D01                    | General RF Exposure Guidance v06                                                                                                                                            |
| KDB648474 D04                    | Handsets SAR v01r03                                                                                                                                                         |
| KDB248227 D01                    | SAR Guidance for IEEE 802.11 Wi-Fi SAR v02r02                                                                                                                               |
| KDB865664 D01                    | SAR measurement 100 MHz to 6 GHz v01r04                                                                                                                                     |
| KDB865664 D02                    | SAR Reporting v01r02                                                                                                                                                        |
| KDB690783 D01                    | SAR Listings on Grants v01r03                                                                                                                                               |
| KDB616217 D04                    | SAR for laptop and tablets v01r02                                                                                                                                           |

#### 1.5 Testing laboratory

|                        |                                                                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Site              | The Reliability Laboratory of Huawei Technologies Co., Ltd.                                                                                                          |
| Test Location          | Section G1, Huawei Base Bantian, Longgang District, Shenzhen 518129, P.R. China                                                                                      |
| Telephone              | +86 755 28780808                                                                                                                                                     |
| Fax                    | +86 755 89652518                                                                                                                                                     |
| State of accreditation | The Test laboratory (area of testing) is accredited according to ISO/IEC 17025.<br>CNAS Registration number: L0310<br>A2LA TESTING CERT #2174.01 & 2174.02 & 2174.03 |

#### 1.6 Applicant and Manufacturer

|              |                                                                                                                             |
|--------------|-----------------------------------------------------------------------------------------------------------------------------|
| Company Name | HUAWEI TECHNOLOGIES CO., LTD                                                                                                |
| Address      | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C |

#### 1.7 Application details


|                    |            |
|--------------------|------------|
| Start Date of test | 2017-10-04 |
| End Date of test   | 2017-11-14 |

#### 1.8 Ambient Condition

|                     |             |
|---------------------|-------------|
| Ambient temperature | 20°C – 24°C |
| Relative Humidity   | 30% – 70%   |

## 2 SAR Measurement System

### 2.1 SAR Measurement Set-up



The DASY system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- A unit to operate the optical surface detector which is connected to the EOC.
- The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5/6 measurement server.
- The DASY measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 7.
- DASY software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- System check dipoles allowing to validate the proper functioning of the system.

## 2.2 Test environment

The DASY measurement system is placed at the head end of a room with dimensions: 5 x 2.5 x 3 m<sup>3</sup>, the SAM phantom is placed in a distance of 75 cm from the side walls and 1.1m from the rear wall. Above the test system a 1.5 x 1.5 m<sup>2</sup> array of pyramid absorbers is installed to reduce reflections from the ceiling.

Picture 1 of the photo documentation shows a complete view of the test environment.

The system allows the measurement of SAR values larger than 0.005 mW/g.

## 2.3 Data Acquisition Electronics description

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.


### DAE4

|                       |                          |                                                                                      |
|-----------------------|--------------------------|--------------------------------------------------------------------------------------|
| Input Impedance       | 200MOhm                  |  |
| The Inputs            | symmetrical and floating |                                                                                      |
| Common mode rejection | above 80 dB              |                                                                                      |

## 2.4 Probe description

These probes are specially designed and calibrated for use in liquids with high permittivities. They should not be used in air, since the spherical isotropy in air is poor ( $\pm 2$  dB). The dosimetric probes have special calibrations in various liquids at different frequencies.

### Isotropic E-Field Probe ES3DV3 for Dosimetric Measurements

|               |                                                                                                                                                                                    |                                                                                      |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core<br>Interleaved sensors<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |  |
| Calibration   | ISO/IEC 17025 calibration service available.                                                                                                                                       |                                                                                      |
| Frequency     | 10 MHz to 4 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 4 GHz)                                                                                                                         |                                                                                      |
| Directivity   | $\pm 0.2$ dB in HSL (rotation around probe axis)<br>$\pm 0.3$ dB in tissue material (rotation normal to probe axis)                                                                |                                                                                      |
| Dynamic range | 5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB                                                                                                                                 |                                                                                      |
| Dimensions    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 3.9 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 2.0 mm                                                     |                                                                                      |
| Application   | General dosimetry up to 4 GHz<br>Dosimetry in strong gradient fields<br>Compliance tests of mobile phones                                                                          |                                                                                      |

### Isotropic E-Field Probe EX3DV4 for Dosimetric Measurements


|               |                                                                                                                                                                                                              |                                                                                       |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE)                                                  |  |
| Calibration   | ISO/IEC 17025 calibration service available.                                                                                                                                                                 |                                                                                       |
| Frequency     | 10 MHz to >6 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)                                                                                                                                                  |                                                                                       |
| Directivity   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                                                                          |                                                                                       |
| Dynamic range | 10 $\mu$ W/g to > 100 mW/g;<br>Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)                                                                                                                      |                                                                                       |
| Dimensions    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                                                                         |                                                                                       |
| Application   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields).<br>Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30% |                                                                                       |

## 2.5 Phantom description

### SAM Twin Phantom

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                        |                                                                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|-------------------------------------------------------------------------------------|
| Shell Thickness                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 2mm±0.2mm;The ear region:6.0±0.2mm                     |  |
| Filling Volume                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Approximately 25 liters                                |                                                                                     |
| Dimensions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Length:1000mm; Width:500mm;<br>Height: adjustable feet |                                                                                     |
| Measurement Areas                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Left hand<br>Right hand<br>Flat phantom                |                                                                                     |
| <p>The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible. Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.</p> |                                                        |                                                                                     |

The following figure shows the definition of reference point:



### ELI4 Phantom

|                                                                                                                                                                                                                                                                       |                                     |                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|---------------------------------------------------------------------------------------|
| Shell Thickness                                                                                                                                                                                                                                                       | 2mm±0.2mm                           |  |
| Filling Volume                                                                                                                                                                                                                                                        | Approximately 30 liters             |                                                                                       |
| Dimensions                                                                                                                                                                                                                                                            | Major axis:600mm; Minor axis:400mm; |                                                                                       |
| Measurement Areas                                                                                                                                                                                                                                                     | Flat phantom                        |                                                                                       |
| <p>The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30MHz to 6GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209-2 and all known tissue simulating liquids.</p> |                                     |                                                                                       |

The phantom shell material is resistant to all ingredients used in the tissue-equivalent liquid recipes. The shell of the phantom including ear spacers is constructed from low permittivity and low loss material, with a relative permittivity  $2 \leq \epsilon_r \leq 5$  at  $\leq 3$  GHz,  $3 \leq \epsilon_r \leq 4$  at  $> 3$  GHz and a loss tangent  $\leq 0.05$ .

## 2.6 Device holder description

The DASY device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of  $65^\circ$ . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used.



The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\sigma = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

The device holder permits the device to be positioned with a tolerance of  $\pm 1^\circ$  in the tilt angle.

Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values.

Therefore those devices are normally only tested at the flat part of the SAM.

## 2.7 Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

|                                     | Manufacturer  | Device                               | Type      | Serial number | Date of last calibration* | Valid period |
|-------------------------------------|---------------|--------------------------------------|-----------|---------------|---------------------------|--------------|
| <input checked="" type="checkbox"/> | SPEAG         | Dosimetric E-Field Probe             | EX3DV4    | 3744          | 2017-07-24                | One year     |
| <input checked="" type="checkbox"/> | SPEAG         | Dosimetric E-Field Probe             | ES3DV3    | 3168          | 2017-09-28                | One year     |
| <input checked="" type="checkbox"/> | SPEAG         | Dosimetric E-Field Probe             | EX3DV4    | 3578          | 2017-05-05                | One year     |
| <input checked="" type="checkbox"/> | SPEAG         | 750MHz Dipole                        | D750V3    | 1078          | 2017-06-20                | Three years  |
| <input checked="" type="checkbox"/> | SPEAG         | 835MHz Dipole                        | D835V2    | 4d059         | 2016-04-20                | Three years  |
| <input checked="" type="checkbox"/> | SPEAG         | 1750MHz Dipole                       | D1750V2   | 1123          | 2017-07-27                | Three years  |
| <input checked="" type="checkbox"/> | SPEAG         | 1900MHz Dipole                       | D1900V2   | 5d142         | 2017-06-21                | Three years  |
| <input checked="" type="checkbox"/> | SPEAG         | 2450MHz Dipole                       | D2450V2   | 860           | 2016-11-23                | Three years  |
| <input checked="" type="checkbox"/> | SPEAG         | 2600MHz Dipole                       | D2600V2   | 1021          | 2017-07-21                | Three years  |
| <input checked="" type="checkbox"/> | SPEAG         | Data acquisition electronics         | DAE4      | 852           | 2017-04-27                | One year     |
| <input checked="" type="checkbox"/> | SPEAG         | Data acquisition electronics         | DAE4      | 1492          | 2017-09-25                | One year     |
| <input checked="" type="checkbox"/> | SPEAG         | Data acquisition electronics         | DAE4      | 1236          | 2017-07-21                | One year     |
| <input checked="" type="checkbox"/> | SPEAG         | Software                             | DASY5     | N/A           | NCR                       | NCR          |
| <input checked="" type="checkbox"/> | SPEAG         | Twin Phantom                         | SAM1      | TP-1475       | NCR                       | NCR          |
| <input checked="" type="checkbox"/> | SPEAG         | Twin Phantom                         | SAM2      | TP-1474       | NCR                       | NCR          |
| <input checked="" type="checkbox"/> | SPEAG         | Twin Phantom                         | SAM3      | TP-1597       | NCR                       | NCR          |
| <input checked="" type="checkbox"/> | SPEAG         | Twin Phantom                         | SAM4      | TP-1620       | NCR                       | NCR          |
| <input type="checkbox"/>            | SPEAG         | Twin Phantom                         | SAM5      | TP-1894       | NCR                       | NCR          |
| <input type="checkbox"/>            | SPEAG         | Twin Phantom                         | SAM6      | TP-1892       | NCR                       | NCR          |
| <input checked="" type="checkbox"/> | R & S         | Universal Radio Communication Tester | CMU 200   | 111379        | 2016-12-29                | One year     |
| <input checked="" type="checkbox"/> | R & S         | WideBand Radio Communication Tester  | CMW 500   | 158850        | 2017-06-13                | One year     |
| <input checked="" type="checkbox"/> | Agilent       | Wireless Connectivity Test Set       | N4010A    | MY49081592    | 2017-07-31                | One year     |
| <input checked="" type="checkbox"/> | Agilent       | Signal Analyzer                      | N9030A    | MY49431698    | 2017-07-31                | One year     |
| <input checked="" type="checkbox"/> | Agilent       | Network Analyser                     | E5071C    | MY46213349    | 2016-12-30                | One year     |
| <input checked="" type="checkbox"/> | Agilent       | Dielectric Probe Kit                 | 85070E    | 2484          | NCR                       | NCR          |
| <input checked="" type="checkbox"/> | Agilent       | Signal Generator                     | E8257D    | MY49281095    | 2017-02-15                | One year     |
| <input checked="" type="checkbox"/> | MINI-CIRCUITS | Amplifier                            | ZHL-42W   | QA1402001     | NCR                       | NCR          |
| <input checked="" type="checkbox"/> | SHX           | Directional Coupler                  | DDTO-4-20 | 07122401      | 2017-08-07                | One year     |
| <input checked="" type="checkbox"/> | AR            | Directional Coupler                  | DC7144AM1 | 0423264       | 2017-04-12                | NCR          |
| <input checked="" type="checkbox"/> | R & S         | Power Meter                          | NRP       | 100740        | 2017-07-17                | One year     |
| <input checked="" type="checkbox"/> | R & S         | Power Meter Sensor                   | NRP-Z11   | 106288        | 2017-07-17                | One year     |
| <input checked="" type="checkbox"/> | Agilent       | Power Meter                          | E4417A    | MY45101339    | 2016-12-30                | One year     |
| <input checked="" type="checkbox"/> | Agilent       | Power Meter Sensor                   | E9321A    | MY44420359    | 2016-12-30                | One year     |

Note: 1) Per KDB865664D01 requirements for dipole calibration, the test laboratory has adopted three-year extended calibration interval. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- There is no physical damage on the dipole;
- System check with specific dipole is within 10% of calibrated value;
- The most recent return-loss result, measured at least annually, deviates by no more than 20% from the previous measurement.
- The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

3) \*All the equipments are within the valid period when the tests are performed.

## 3 SAR Measurement Procedure

### 3.1 Scanning procedure

The DASY installation includes predefined files with recommended procedures for measurements and system check. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

- The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max. +/- 5 %.
- The “surface check” measurement tests the optical surface detection system of the DASY5/6 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above  $\pm 0.1\text{mm}$ ). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within  $\pm 30^\circ$ .)
- The “area scan” measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The standard scan uses large grid spacing for faster measurement. Standard grid spacing for head measurements is 15 mm in x- and y- dimension ( $\leq 2\text{GHz}$ ), 12 mm in x- and y- dimension (2-4 GHz) and 10mm in x- and y- dimension (4-6GHz). If a finer resolution is needed, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation. Results of this coarse scan are shown in Appendix B.
- A “zoom scan” measures the field in a volume around the 2D peak SAR value acquired in the previous “coarse” scan. This is a fine grid with maximum scan spatial resolution:  $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}} \leq 2\text{GHz} - \leq 8\text{mm}$ , 2-4GHz -  $\leq 5\text{ mm}$  and 4-6 GHz- $\leq 4\text{mm}$ ;  $\Delta z_{\text{zoom}} \leq 3\text{GHz} - \leq 5\text{ mm}$ , 3-4 GHz-  $\leq 4\text{mm}$  and 4-6GHz- $\leq 2\text{mm}$  where the robot additionally moves the probe along the z-axis away from the bottom of the Phantom. DASY is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in Appendix B. Test results relevant for the specified standard (see chapter 1.4.) are shown in table form in chapter 7.2.
- A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 2 mm steps. This measurement shows the continuity of the liquid and can - depending in the field strength – also show the liquid depth. A z-axis scan of the measurement with maximum SAR value is shown in Appendix B.

The following table summarizes the area scan and zoom scan resolutions per FCC KDB 865664D01:

| Frequency | Maximun Area Scan resolution<br>( $\Delta x_{area}$ , $\Delta y_{area}$ ) | Maximun Zoom Scan spatial resolution<br>( $\Delta x_{zoom}$ , $\Delta y_{zoom}$ ) | Maximun Zoom Scan spatial resolution |                        |                              | Minimum zoom scan volume<br>(x,y,z) |
|-----------|---------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------|------------------------|------------------------------|-------------------------------------|
|           |                                                                           |                                                                                   | Uniform Grid                         | Graded Grad            |                              |                                     |
|           |                                                                           |                                                                                   | $\Delta z_{Zoom}(n)$                 | $\Delta z_{Zoom}(1)^*$ | $\Delta z_{Zoom}(n>1)^*$     |                                     |
| ≤2GHz     | ≤15mm                                                                     | ≤8mm                                                                              | ≤5mm                                 | ≤4mm                   | ≤1.5* $\Delta z_{Zoom}(n-1)$ | ≥30mm                               |
| 2-3GHz    | ≤12mm                                                                     | ≤5mm                                                                              | ≤5mm                                 | ≤4mm                   | ≤1.5* $\Delta z_{Zoom}(n-1)$ | ≥30mm                               |
| 3-4GHz    | ≤12mm                                                                     | ≤5mm                                                                              | ≤4mm                                 | ≤3mm                   | ≤1.5* $\Delta z_{Zoom}(n-1)$ | ≥28mm                               |
| 4-5GHz    | ≤10mm                                                                     | ≤4mm                                                                              | ≤3mm                                 | ≤2.5mm                 | ≤1.5* $\Delta z_{Zoom}(n-1)$ | ≥25mm                               |
| 5-6GHz    | ≤10mm                                                                     | ≤4mm                                                                              | ≤2mm                                 | ≤2mm                   | ≤1.5* $\Delta z_{Zoom}(n-1)$ | ≥22mm                               |

### 3.2 Spatial Peak SAR Evaluation

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of 5 x 5 x 7 points( with 8mm horizontal resolution) or 7 x 7 x 7 points( with 5mm horizontal resolution) or 8 x 8 x 7 points( with 4mm horizontal resolution). The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting 'Graph Evaluated'.
- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR - values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.
- All neighboring volumes are evaluated until no neighboring volume with a higher average value is found.

#### Extrapolation

The extrapolation is based on a least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

#### Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computermathematik, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff ].

#### Volume Averaging

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

#### Advanced Extrapolation

DASY5/6 uses the advanced extrapolation option which is able to compensates boundary effects on E-field probes.

### 3.3 Data Storage and Evaluation

#### Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension "DAE4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

#### Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

|                    |                           |                                         |
|--------------------|---------------------------|-----------------------------------------|
| Probe parameters:  | - Sensitivity             | $\text{Norm}_i, a_{i0}, a_{i1}, a_{i2}$ |
|                    | - Conversion factor       | $\text{ConvF}_i$                        |
|                    | - Diode compression point | $\text{Dcpi}$                           |
| Device parameters: | - Frequency               | $f$                                     |
|                    | - Crest factor            | $cf$                                    |
| Media parameters:  | - Conductivity            | $\sigma$                                |
|                    | - Density                 | $\rho$                                  |

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf/dcpi$$

|      |        |                                                   |                  |
|------|--------|---------------------------------------------------|------------------|
| with | $V_i$  | = compensated signal of channel i                 | (i = x, y, z)    |
|      | $U_i$  | = input signal of channel i                       | (i = x, y, z)    |
|      | $cf$   | = crest factor of exciting field (DASY parameter) |                  |
|      | $dcpi$ | = diode compression point                         | (DASY parameter) |

From the compensated input signals the primary field data for each channel can be evaluated:

$$\begin{aligned} \text{E-field probes:} \quad E_i &= (V_i / \text{Norm}_i \cdot \text{ConvF})^{1/2} \\ \text{H-field probes:} \quad H_i &= (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2)/f \end{aligned}$$

with  $V_i$  = compensated signal of channel i (i = x, y, z)  
 $\text{Norm}_i$  = sensor sensitivity of channel i (i = x, y, z)  
 [mV/(V/m)<sup>2</sup>] for E-field Probes  
 $\text{ConvF}$  = sensitivity enhancement in solution  
 $a_{ij}$  = sensor sensitivity factors for H-field probes  
 $f$  = carrier frequency [GHz]  
 $E_i$  = electric field strength of channel i in V/m  
 $H_i$  = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = (E_{\text{tot}}^2 \cdot \sigma) / (\rho \cdot 1000)$$

with  $\text{SAR}$  = local specific absorption rate in mW/g  
 $E_{\text{tot}}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \quad \text{or} \quad P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

with  $P_{\text{pwe}}$  = equivalent power density of a plane wave in mW/cm<sup>2</sup>  
 $E_{\text{tot}}$  = total electric field strength in V/m  
 $H_{\text{tot}}$  = total magnetic field strength in A/m

## 4 System Verification Procedure

### 4.1 Tissue Verification

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within  $\pm 5\%$  of the target values.

The following materials are used for producing the tissue-equivalent materials.

| Ingredients (% of weight) | Head Tissue |       |       |        |      |        |
|---------------------------|-------------|-------|-------|--------|------|--------|
| Frequency Band (MHz)      | 750         | 835   | 1750  | 1900   | 2450 | 2600   |
| Water                     | 39.2        | 41.45 | 52.64 | 55.242 | 62.7 | 55.242 |
| Salt (NaCl)               | 2.7         | 1.45  | 0.36  | 0.306  | 0.5  | 0.306  |
| Sugar                     | 57.0        | 56.0  | 0.0   | 0.0    | 0.0  | 0.0    |
| HEC                       | 0.0         | 1.0   | 0.0   | 0.0    | 0.0  | 0.0    |
| Bactericide               | 0.0         | 0.1   | 0.0   | 0.0    | 0.0  | 0.0    |
| Triton X-100              | 0.0         | 0.0   | 0.0   | 0.0    | 0.0  | 0.0    |
| DGBE                      | 0.0         | 0.0   | 47.0  | 44.542 | 36.8 | 44.452 |
| Ingredients (% of weight) | Body Tissue |       |       |        |      |        |
| Frequency Band (MHz)      | 750         | 835   | 1750  | 1900   | 2450 | 2600   |
| Water                     | 50.3        | 52.4  | 69.91 | 69.91  | 73.2 | 64.493 |
| Salt (NaCl)               | 1.60        | 1.40  | 0.13  | 0.13   | 0.04 | 0.024  |
| Sugar                     | 47.0        | 45.0  | 0.0   | 0.0    | 0.0  | 0.0    |
| HEC                       | 0.0         | 1.0   | 0.0   | 0.0    | 0.0  | 0.0    |
| Bactericide               | 0.0         | 0.1   | 0.0   | 0.0    | 0.0  | 0.0    |
| Triton X-100              | 0.0         | 0.0   | 0.0   | 0.0    | 0.0  | 0.0    |
| DGBE                      | 0.0         | 0.0   | 29.96 | 29.96  | 26.7 | 32.252 |

#### ☒ Simulating Head Liquid (HBBL600-6000MHz), Manufactured by SPEAG:

| Ingredients | (% by weight) |
|-------------|---------------|
| Water       | 50-65%        |
| Mineral oil | 10-30%        |
| Emulsifiers | 8-25%         |
| Sodium salt | 0-1.5%        |

#### ☒ Simulating Body Liquid (MBBL600-6000MHz), Manufactured by SPEAG:

| Ingredients                     | (% by weight) |
|---------------------------------|---------------|
| Water                           | 60-80%        |
| Esters, Emulsifiers, Inhibitors | 20-40%        |
| Sodium salt                     | 0-1.5%        |

Table 4: Tissue Dielectric Properties

Salt: 99+% Pure Sodium Chloride; Sugar: 98+% Pure Sucrose; Water: De-ionized, 16M $\Omega$ + resistivity  
 HEC: Hydroxyethyl Cellulose; DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]  
 Triton X-100(ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

| Tissue Type  | Target Frequency | Target Tissue |                     | Measured Tissue |                     | Deviation (Within +/-5% ) |                | Liquid Temp. | Test Date  |
|--------------|------------------|---------------|---------------------|-----------------|---------------------|---------------------------|----------------|--------------|------------|
|              |                  | Permit-tivity | Conduc-tivity [S/m] | Permit-tivity   | Conduc-tivity [S/m] | $\Delta\epsilon_r$        | $\Delta\sigma$ |              |            |
| 750MHz Head  | 705              | 42.14         | 0.89                | 41.65           | 0.874               | -1.16%                    | -1.83%         | 21.8°C       | 2017/10/23 |
|              | 710              | 42.11         | 0.89                | 41.63           | 0.876               | -1.14%                    | -1.63%         |              |            |
|              | 750              | 41.90         | 0.89                | 41.53           | 0.890               | -0.88%                    | -0.02%         |              |            |
| 835MHz Head  | 825              | 41.60         | 0.90                | 41.44           | 0.909               | -0.38%                    | 1.02%          | 21.8°C       | 2017/10/16 |
|              | 835              | 41.50         | 0.90                | 41.41           | 0.913               | -0.22%                    | 1.39%          |              |            |
|              | 850              | 41.50         | 0.92                | 41.36           | 0.918               | -0.34%                    | -0.18%         |              |            |
| 835MHz Head  | 825              | 41.60         | 0.90                | 41.38           | 0.926               | -0.53%                    | 2.84%          | 21.8°C       | 2017/10/20 |
|              | 835              | 41.50         | 0.90                | 41.34           | 0.929               | -0.41%                    | 3.26%          |              |            |
|              | 850              | 41.50         | 0.92                | 41.24           | 0.935               | -0.63%                    | 1.62%          |              |            |
| 1750MHz Head | 1710             | 40.10         | 1.35                | 38.89           | 1.386               | -3.02%                    | 2.67%          | 21.8°C       | 2017/10/14 |
|              | 1730             | 40.10         | 1.36                | 38.84           | 1.397               | -3.14%                    | 2.72%          |              |            |
|              | 1750             | 40.10         | 1.37                | 38.80           | 1.407               | -3.24%                    | 2.70%          |              |            |
|              | 1800             | 40.00         | 1.40                | 38.71           | 1.435               | -3.23%                    | 2.50%          |              |            |
| 1750MHz Head | 1710             | 40.10         | 1.35                | 39.08           | 1.336               | -2.54%                    | -1.04%         | 21.6°C       | 2017/10/20 |
|              | 1730             | 40.10         | 1.36                | 39.06           | 1.347               | -2.59%                    | -0.96%         |              |            |
|              | 1750             | 40.10         | 1.37                | 39.03           | 1.356               | -2.67%                    | -1.02%         |              |            |
|              | 1800             | 40.00         | 1.40                | 38.97           | 1.386               | -2.58%                    | -1.00%         |              |            |
| 1900MHz Head | 1850             | 40.00         | 1.40                | 39.32           | 1.347               | -1.70%                    | -3.79%         | 20.8°C       | 2017/10/10 |
|              | 1880             | 40.00         | 1.40                | 39.26           | 1.365               | -1.85%                    | -2.50%         |              |            |
|              | 1900             | 40.00         | 1.40                | 39.23           | 1.375               | -1.93%                    | -1.79%         |              |            |
|              | 1910             | 40.00         | 1.40                | 39.21           | 1.381               | -1.98%                    | -1.36%         |              |            |
| 1900MHz Head | 1850             | 40.00         | 1.40                | 39.06           | 1.407               | -2.35%                    | 0.50%          | 21.5°C       | 2017/10/17 |
|              | 1880             | 40.00         | 1.40                | 39.02           | 1.425               | -2.45%                    | 1.79%          |              |            |
|              | 1900             | 40.00         | 1.40                | 39.00           | 1.436               | -2.50%                    | 2.57%          |              |            |
|              | 1910             | 40.00         | 1.40                | 38.99           | 1.442               | -2.52%                    | 3.00%          |              |            |
| 1900MHz Head | 1850             | 40.00         | 1.40                | 41.39           | 1.410               | 3.48%                     | 0.71%          | 22.1°C       | 2017/11/2  |
|              | 1880             | 40.00         | 1.40                | 41.30           | 1.433               | 3.25%                     | 2.36%          |              |            |
|              | 1900             | 40.00         | 1.40                | 41.28           | 1.441               | 3.20%                     | 2.93%          |              |            |
|              | 1910             | 40.00         | 1.40                | 41.24           | 1.450               | 3.10%                     | 3.57%          |              |            |
| 2450MHz Head | 2410             | 39.30         | 1.76                | 40.67           | 1.827               | 3.49%                     | 3.81%          | 21.9°C       | 2017/11/11 |
|              | 2435             | 39.20         | 1.79                | 40.66           | 1.849               | 3.72%                     | 3.30%          |              |            |
|              | 2450             | 39.20         | 1.80                | 40.61           | 1.860               | 3.60%                     | 3.33%          |              |            |
|              | 2460             | 39.20         | 1.81                | 40.59           | 1.868               | 3.55%                     | 3.20%          |              |            |
| 2600MHz Head | 2510             | 39.12         | 1.86                | 39.14           | 1.916               | 0.05%                     | 3.01%          | 22°C         | 2017/10/21 |
|              | 2535             | 39.10         | 1.89                | 39.14           | 1.938               | 0.10%                     | 2.54%          |              |            |
|              | 2560             | 39.00         | 1.92                | 39.11           | 1.963               | 0.28%                     | 2.40%          |              |            |
|              | 2600             | 39.00         | 1.96                | 39.08           | 1.996               | 0.18%                     | 1.84%          |              |            |

|                 |      |       |      |       |       |        |        |        |            |
|-----------------|------|-------|------|-------|-------|--------|--------|--------|------------|
| 750MHz<br>Body  | 705  | 55.70 | 0.96 | 53.63 | 0.929 | -3.72% | -3.19% | 21.8°C | 2017/10/23 |
|                 | 710  | 55.70 | 0.96 | 53.62 | 0.932 | -3.73% | -2.92% |        |            |
|                 | 750  | 55.50 | 0.96 | 53.50 | 0.950 | -3.60% | -1.00% |        |            |
| 835MHz<br>Body  | 825  | 55.20 | 0.97 | 53.69 | 0.966 | -2.74% | -0.39% | 21.8°C | 2017/10/17 |
|                 | 835  | 55.20 | 0.97 | 53.65 | 0.971 | -2.81% | 0.09%  |        |            |
|                 | 850  | 55.20 | 0.99 | 53.61 | 0.978 | -2.88% | -1.17% |        |            |
| 835MHz<br>Body  | 825  | 55.20 | 0.97 | 53.44 | 0.958 | -3.19% | -1.28% | 22.0°C | 2017/10/25 |
|                 | 835  | 55.20 | 0.97 | 53.41 | 0.962 | -3.24% | -0.77% |        |            |
|                 | 850  | 55.20 | 0.99 | 53.37 | 0.969 | -3.32% | -2.08% |        |            |
| 1750MHz<br>Body | 1710 | 53.50 | 1.46 | 53.36 | 1.410 | -0.26% | -3.42% | 21.8°C | 2017/10/14 |
|                 | 1730 | 53.50 | 1.48 | 53.30 | 1.425 | -0.37% | -3.72% |        |            |
|                 | 1750 | 53.40 | 1.49 | 53.25 | 1.438 | -0.28% | -3.49% |        |            |
|                 | 1800 | 53.30 | 1.52 | 53.19 | 1.469 | -0.21% | -3.36% |        |            |
| 1750MHz<br>Body | 1710 | 53.50 | 1.46 | 52.85 | 1.485 | -1.21% | 1.71%  | 22.4°C | 2017/10/16 |
|                 | 1730 | 53.50 | 1.48 | 52.85 | 1.497 | -1.21% | 1.15%  |        |            |
|                 | 1750 | 53.40 | 1.49 | 52.85 | 1.509 | -1.03% | 1.28%  |        |            |
|                 | 1800 | 53.30 | 1.52 | 52.83 | 1.547 | -0.88% | 1.78%  |        |            |
| 1750MHz<br>Body | 1710 | 53.50 | 1.46 | 53.28 | 1.401 | -0.41% | -4.04% | 21.8°C | 2017/10/26 |
|                 | 1730 | 53.50 | 1.48 | 53.22 | 1.415 | -0.52% | -4.39% |        |            |
|                 | 1750 | 53.40 | 1.49 | 53.17 | 1.428 | -0.43% | -4.16% |        |            |
|                 | 1800 | 53.30 | 1.52 | 53.11 | 1.459 | -0.36% | -4.01% |        |            |
| 1750MHz<br>Body | 1710 | 53.50 | 1.46 | 51.51 | 1.415 | -3.72% | -3.08% | 21.9°C | 2017/11/14 |
|                 | 1730 | 53.50 | 1.48 | 51.43 | 1.426 | -3.87% | -3.65% |        |            |
|                 | 1750 | 53.40 | 1.49 | 51.43 | 1.440 | -3.70% | -3.36% |        |            |
|                 | 1800 | 53.30 | 1.52 | 51.43 | 1.476 | -3.51% | -2.89% |        |            |
| 1750MHz<br>Body | 1710 | 53.50 | 1.46 | 51.31 | 1.411 | -4.09% | -3.36% | 21.8°C | 2017/11/14 |
|                 | 1730 | 53.50 | 1.48 | 51.23 | 1.426 | -4.24% | -3.65% |        |            |
|                 | 1750 | 53.40 | 1.49 | 51.23 | 1.440 | -4.06% | -3.36% |        |            |
|                 | 1800 | 53.30 | 1.52 | 51.23 | 1.476 | -3.88% | -2.89% |        |            |
| 1900MHz<br>Body | 1850 | 53.30 | 1.52 | 51.40 | 1.445 | -3.56% | -4.93% | 21.2°C | 2017/10/13 |
|                 | 1880 | 53.30 | 1.52 | 51.29 | 1.452 | -3.77% | -4.47% |        |            |
|                 | 1900 | 53.30 | 1.52 | 51.26 | 1.468 | -3.83% | -3.42% |        |            |
|                 | 1910 | 53.30 | 1.52 | 51.26 | 1.476 | -3.83% | -2.89% |        |            |
| 1900MHz<br>Body | 1850 | 53.30 | 1.52 | 52.60 | 1.465 | -1.31% | -3.62% | 22.6°C | 2017/10/18 |
|                 | 1880 | 53.30 | 1.52 | 52.52 | 1.487 | -1.46% | -2.17% |        |            |
|                 | 1900 | 53.30 | 1.52 | 52.47 | 1.499 | -1.56% | -1.38% |        |            |
|                 | 1910 | 53.30 | 1.52 | 52.45 | 1.506 | -1.59% | -0.92% |        |            |
| 1900MHz<br>Body | 1850 | 53.30 | 1.52 | 51.48 | 1.488 | -3.41% | -2.11% | 21.6°C | 2017/10/25 |
|                 | 1880 | 53.30 | 1.52 | 51.43 | 1.508 | -3.51% | -0.79% |        |            |
|                 | 1900 | 53.30 | 1.52 | 51.39 | 1.520 | -3.58% | 0.00%  |        |            |
|                 | 1910 | 53.30 | 1.52 | 51.37 | 1.526 | -3.62% | 0.39%  |        |            |
| 1900MHz<br>Body | 1850 | 53.30 | 1.52 | 51.86 | 1.478 | -2.70% | -2.76% | 21.6°C | 2017/11/13 |
|                 | 1880 | 53.30 | 1.52 | 51.75 | 1.512 | -2.91% | -0.53% |        |            |
|                 | 1900 | 53.30 | 1.52 | 51.67 | 1.534 | -3.06% | 0.86%  |        |            |
|                 | 1910 | 53.30 | 1.52 | 51.65 | 1.544 | -3.10% | 1.58%  |        |            |
| 2450MHz<br>Body | 2410 | 52.80 | 1.91 | 54.28 | 1.914 | 2.80%  | 0.21%  | 21.9°C | 2017/11/10 |
|                 | 2435 | 52.70 | 1.94 | 54.24 | 1.935 | 2.92%  | -0.26% |        |            |
|                 | 2450 | 52.70 | 1.95 | 54.21 | 1.948 | 2.87%  | -0.10% |        |            |
|                 | 2460 | 52.70 | 1.96 | 54.19 | 1.957 | 2.83%  | -0.15% |        |            |
| 2600MHz<br>Body | 2510 | 52.62 | 2.03 | 50.71 | 2.024 | -3.63% | -0.30% | 21.3°C | 2017/10/23 |
|                 | 2535 | 52.59 | 2.07 | 50.74 | 2.048 | -3.52% | -1.06% |        |            |
|                 | 2560 | 52.57 | 2.09 | 50.68 | 2.069 | -3.60% | -1.00% |        |            |
|                 | 2600 | 52.50 | 2.16 | 50.59 | 2.109 | -3.64% | -2.36% |        |            |
| 2600MHz<br>Body | 2510 | 52.62 | 2.03 | 51.17 | 2.013 | -2.76% | -0.84% | 22.1°C | 2017/11/14 |
|                 | 2535 | 52.59 | 2.07 | 51.08 | 2.031 | -2.87% | -1.88% |        |            |

|  |      |       |      |       |       |        |        |  |  |
|--|------|-------|------|-------|-------|--------|--------|--|--|
|  | 2560 | 52.57 | 2.09 | 51.09 | 2.050 | -2.82% | -1.91% |  |  |
|  | 2600 | 52.50 | 2.16 | 51.01 | 2.088 | -2.84% | -3.33% |  |  |

Table 5: Measured Tissue Parameter

Note: 1) The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

2) KDB 865664 was ensured to be applied for probe calibration frequencies greater than or equal to 50MHz of the EUT frequencies.

3) The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies. The SAR test plots may slightly differ from the table above since the DASY rounds to three significant digits.

## 4.2 System Check


The system check is performed for verifying the accuracy of the complete measurement system and performance of the software. The system check is performed with tissue equivalent material according to IEEE P1528 (described above). The following table shows system check results for all frequency bands and tissue liquids used during the tests(Graphic Plot(s) see Appendix A).

| System Check | Target SAR<br>(Normalized to 1W) |                | Measured SAR<br>(Normalized to 1W) |                | Deviation<br>(Within +/-10% ) |               | Liquid Temp. | Test Date  |
|--------------|----------------------------------|----------------|------------------------------------|----------------|-------------------------------|---------------|--------------|------------|
|              | 1-g<br>(mW/g)                    | 10-g<br>(mW/g) | 1-g<br>(mW/g)                      | 10-g<br>(mW/g) | $\Delta$ 1-g                  | $\Delta$ 10-g |              |            |
| 750MHz Head  | 8.39                             | 5.47           | 8.52                               | 5.60           | 1.55%                         | 2.38%         | 21.8°C       | 2017/10/23 |
| 835MHz Head  | 9.30                             | 6.05           | 9.52                               | 6.16           | 2.37%                         | 1.82%         | 21.8°C       | 2017/10/16 |
| 835MHz Head  | 9.30                             | 6.05           | 9.32                               | 6.04           | 0.22%                         | -0.17%        | 21.8°C       | 2017/10/20 |
| 1750MHz Head | 36.60                            | 19.40          | 36.00                              | 19.12          | -1.64%                        | -1.44%        | 21.6°C       | 2017/10/14 |
| 1750MHz Head | 36.60                            | 19.40          | 34.88                              | 18.32          | -4.70%                        | -5.57%        | 21.8°C       | 2017/10/20 |
| 1900MHz Head | 40.30                            | 21.00          | 40.80                              | 21.16          | 1.24%                         | 0.76%         | 20.8°C       | 2017/10/10 |
| 1900MHz Head | 40.30                            | 21.00          | 42.00                              | 21.68          | 4.22%                         | 3.24%         | 21.5°C       | 2017/10/17 |
| 1900MHz Head | 40.30                            | 21.00          | 39.48                              | 20.44          | -2.03%                        | -2.67%        | 22.1°C       | 2017/11/2  |
| 2450MHz Head | 51.90                            | 24.40          | 52.00                              | 24.12          | 0.19%                         | -1.15%        | 21.9°C       | 2017/11/11 |
| 2600MHz Head | 58.70                            | 26.10          | 54.80                              | 24.88          | -6.64%                        | -4.67%        | 22.0°C       | 2017/10/21 |
|              |                                  |                |                                    |                |                               |               |              |            |
| 750MHz Body  | 8.67                             | 5.71           | 8.48                               | 5.72           | -2.19%                        | 0.18%         | 21.8°C       | 2017/10/23 |
| 835MHz Body  | 9.41                             | 6.20           | 9.20                               | 6.16           | -2.23%                        | -0.65%        | 21.8°C       | 2017/10/17 |
| 835MHz Body  | 9.41                             | 6.20           | 9.92                               | 6.68           | 5.42%                         | 7.74%         | 22.0°C       | 2017/10/25 |
| 1750MHz Body | 36.40                            | 19.40          | 35.08                              | 18.80          | -3.63%                        | -3.09%        | 21.8°C       | 2017/10/14 |
| 1750MHz Body | 36.40                            | 19.40          | 37.28                              | 19.72          | 2.42%                         | 1.65%         | 22.4°C       | 2017/10/16 |
| 1750MHz Body | 36.40                            | 19.40          | 34.88                              | 18.68          | -4.18%                        | -3.71%        | 21.8°C       | 2017/10/26 |
| 1750MHz Body | 36.40                            | 19.40          | 37.72                              | 20.20          | 3.63%                         | 4.12%         | 21.9°C       | 2017/11/14 |
| 1750MHz Body | 36.40                            | 19.40          | 35.88                              | 19.04          | -1.43%                        | -1.86%        | 21.8°C       | 2017/11/14 |
| 1900MHz Body | 40.40                            | 21.30          | 38.48                              | 19.68          | -4.75%                        | -7.61%        | 21.2°C       | 2017/10/13 |
| 1900MHz Body | 40.40                            | 21.30          | 37.80                              | 19.48          | -6.44%                        | -8.54%        | 22.6°C       | 2017/10/18 |
| 1900MHz Body | 40.40                            | 21.30          | 40.00                              | 20.60          | -0.99%                        | -3.29%        | 21.6°C       | 2017/10/25 |
| 1900MHz Body | 40.40                            | 21.30          | 38.36                              | 20.36          | -5.05%                        | -4.41%        | 21.6°C       | 2017/11/13 |
| 2450MHz Body | 50.60                            | 23.80          | 53.20                              | 24.88          | 5.14%                         | 4.54%         | 21.9°C       | 2017/11/10 |
| 2600MHz Body | 55.90                            | 24.90          | 52.40                              | 23.28          | -6.26%                        | -6.51%        | 21.3°C       | 2017/10/23 |
| 2600MHz Body | 55.90                            | 24.90          | 56.00                              | 24.64          | 0.18%                         | -1.04%        | 22.1°C       | 2017/11/14 |

Table 6: System Check Results

### 4.3 System check Procedure

The system check is performed by using a system check dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a plexiglass spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 250 mW(below 3GHz) or 100mW(3-6GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system check to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system check to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot). System check results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system.



## 5 SAR measurement variability and uncertainty

### 5.1 SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The detailed repeated measurement results are shown in Section 7.2.

### 5.2 SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04, when the highest measured 1-g SAR within a frequency band is  $< 1.5$  W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

## 6 SAR Test Configuration

### 6.1 Test Positions Configuration

#### 6.1.1 General considerations

Per IEEE 1528-2013, two imaginary lines on the handset were established: the vertical centerline and the horizontal line (See Figure 1).




Figure 1 Hand Vertical Center & Horizontal Line Reference Points

#### 6.1.2 Head Exposure Condition

Per IEEE 1528-2013, Head SAR measurements were made in the “cheek” position (See Figure 2) and the “tilt” position (See Figure 3). The device should be tested in both positions on left and right sides of the SAM phantom.




Figure 2 Front, Side and Top View of Cheek Position



Figure 3 Front, Side and Top View of Tilt 15° Position

Note:

M Mouth reference point

LE Left ear reference point (ERP)

RE Right ear reference point(ERP)

### 6.1.3 Body-worn Exposure Condition

Body-worn operating configurations are tested with the holder attached to the device and positioned against a flat phantom with test separation distance of 15mm in a normal use configuration (See Figure 4). Per FCC KDB648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 4 Test position for Body-Worn device

### 6.1.4 Hotspot Exposure Condition

Per FCC KDB 941225D06, The SAR test separation distance for hotspot mode is determined according to device form factor. When the overall length and width of a device is  $> 9 \text{ cm} \times 5 \text{ cm}$ , a test separation distance of 10 mm is required for hotspot mode SAR measurements. A test separation distance of 5 mm or less is required for smaller devices. Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge; for the data modes, wireless technologies and frequency bands supporting hotspot mode. The SAR results are used to determine simultaneous transmission SAR test exclusion for hotspot mode; otherwise, simultaneous transmission SAR measurement is required.

### 6.1.5 Product specific 10-g Exposure Condition

Per FCC KDB 648474D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the device is marketed as “Phablet”.

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at  $\leq 25$  mm from that surface or edge, in direct contact with a flat phantom, for product specific 10-g SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, product specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.

### 6.1.6 Capacitive proximity sensor power reduction test configurations

This device uses a proximity sensor that shares the same metallic electrode as the main transmitting antenna to facilitate triggering in typical user interactivity with the device.

Due to the operating configurations and exposure conditions required by the device, the proximity sensor is used to indicate when the device is held close to a user’s body exposure condition. It utilizes the proximity sensor to reduce the output power in specific wireless and operating modes of main antenna to ensure SAR compliance.

The following tables summarize the key power reduction information for proximity sensor. The test procedures in KDB 616217 should be applied to determine proximity sensor triggering distances, and sensor coverage for normal and tilt positions. To ensure all production units are compliant, it is generally necessary to reduce the triggering distance determined from the triggering tests by 1 mm, or more if it is necessary, and use the smallest distance for movements to and from the phantom, minus 1 mm, as the sensor triggering distance for determining the SAR measurement distance.

| Band         | Power Reduction Level Amount (dB) |            |                                       |                                                     |
|--------------|-----------------------------------|------------|---------------------------------------|-----------------------------------------------------|
|              | Main Antenna                      |            |                                       |                                                     |
|              | Full power<br>(Other conditions)  | Hotspot on | Receiver off +<br>proximity sensor on | Receiver off+<br>hotspot on+<br>proximity sensor on |
| GSM 1900     | 0                                 | 0          | 2.0                                   | 2.0                                                 |
| UMTS Band II | 0                                 | 3.0        | 2.0                                   | 5.0                                                 |
| UMTS Band IV | 0                                 | 3.0        | 2.0                                   | 6.0                                                 |
| LTE Band II  | 0                                 | 4.3        | 2.0                                   | 6.2                                                 |
| LTE Band IV  | 0                                 | 4.0        | 2.0                                   | 5.5                                                 |
| LTE Band V   | 0                                 | 0          | 2.0                                   | 2.0                                                 |
| LTE Band VII | 0                                 | 5.0        | 2.0                                   | 7.0                                                 |

| Band         | Sensor Trigger Distance                                 |
|--------------|---------------------------------------------------------|
| GSM1900      | Front side:12mm<br>Back side: 14mm<br>Bottom side: 13mm |
| UMTS Band II | Front side:12mm<br>Back side: 14mm<br>Bottom side: 13mm |
| UMTS Band IV | Front side:12mm<br>Back side: 14mm<br>Bottom side: 13mm |
| LTE Band II  | Front side:12mm<br>Back side: 14mm<br>Bottom side: 13mm |
| LTE Band IV  | Front side:12mm<br>Back side: 14mm<br>Bottom side: 13mm |
| LTE Band V   | Front side:12mm<br>Back side: 14mm<br>Bottom side: 13mm |
| LTE Band VII | Front side:12mm<br>Back side: 14mm<br>Bottom side: 13mm |

Note:

- 1) Since the capacitive proximity sensor triggering distance for the front side is 12mm, a conservative distance of 11mm was required for additional SAR test at maximum power level with sensor off.
- 2) Since the capacitive proximity sensor triggering distance for the back side is 14mm, a conservative distance of 13mm was required for additional SAR test at maximum power level with sensor off.
- 3) Since the capacitive proximity sensor triggering distance for the bottom side is 13mm, a conservative distance of 12mm was required for additional SAR test at maximum power level with sensor off.
- 4) SAR tests with proximity sensor power reduction are only required for the sides of frequency bands in the table above. For the other sides or other frequency bands of the device, SAR is still tested at the maximum power level with sensor off.

## 1) Procedures for determining proximity sensor triggering distances

The device was tested by the test lab to determine the proximity sensor triggering distances for the front side, back side and bottom side of the device. To ensure all production units are compliant, the smallest separation distance determined by the sensor triggering minus 1 mm, must be used as the test separation distance for SAR testing.

the proximity sensor triggering distance measurement method are as below:



Picture: Proximity sensor triggering distances assessment Bottom Side




Picture: Proximity sensor triggering distances assessment Front Side and Back side

**Table: Summary of Trigger Distances**


| Band(MHz)    | Trigger distance-Front Side |                          | Trigger distance-Back Side |                          | Trigger distance-Bottom Side |                          |
|--------------|-----------------------------|--------------------------|----------------------------|--------------------------|------------------------------|--------------------------|
|              | Moving toward phantom       | Moving away from phantom | Moving toward phantom      | Moving away from phantom | Moving toward phantom        | Moving away from phantom |
| GSM1900      | 12mm                        | 14mm                     | 14mm                       | 16mm                     | 13mm                         | 15mm                     |
| UMTS Band II | 12mm                        | 14mm                     | 14mm                       | 16mm                     | 13mm                         | 15mm                     |
| UMTS Band IV | 12mm                        | 14mm                     | 14mm                       | 16mm                     | 13mm                         | 15mm                     |
| LTE Band II  | 12mm                        | 14mm                     | 14mm                       | 16mm                     | 13mm                         | 15mm                     |
| LTE Band IV  | 12mm                        | 14mm                     | 14mm                       | 16mm                     | 13mm                         | 15mm                     |
| LTE Band V   | 12mm                        | 14mm                     | 14mm                       | 16mm                     | 13mm                         | 15mm                     |
| LTE Band VII | 12mm                        | 14mm                     | 14mm                       | 16mm                     | 13mm                         | 15mm                     |

The detailed conducted power measurement data to determine the triggering distances is as below:


The DUT(Front side) is moved towards the flat phantom(hotspot off):




The DUT(back side) is moved towards the flat phantom(hotspot off):




The DUT(bottom side) is moved towards the flat phantom(hotspot off):




The DUT(Front side) is moved away from the flat phantom(hotspot off):




The DUT(back side) is moved away from the flat phantom(hotspot off):




The DUT(bottom side) is moved away from the flat phantom(hotspot off):




The DUT(Front side) is moved towards the flat phantom(hotspot on):




The DUT(back side) is moved towards the flat phantom(hotspot on):




The DUT(bottom side) is moved towards the flat phantom(hotspot on):




The DUT(Front side) is moved away from the flat phantom(hotspot on):



The DUT(back side) is moved away from the flat phantom(hotspot on):



The DUT(bottom side) is moved away from the flat phantom(hotspot on):



**Conclusion:** It can be ensured that the proximity sensor can be valid triggered.

## 2) Procedures for determining antenna and proximity sensor coverage


There is no spatial offset between the Main antenna and the proximity sensor element, so procedures for determining the proximity sensor coverage does not need to be assessed per KDB616217.

## 3) Procedures for determining device tilt angle influences to proximity sensor triggering

The DUT was positioned directly below the flat phantom at the minimum measured trigger distance with Bottom side parallel to the base of the flat phantom for each band.

The EUT was rotated about Bottom side for angles up to  $\pm 45^\circ$ . If the output power increased during the rotation the DUT was moved 1mm toward the phantom and the rotation repeated. This procedure was repeated until the power remained reduced for all angles up to  $\pm 45^\circ$ .

The proximity sensor triggering tilt angle measurement method are as below:



**Table: Summary of Tablet Tilt Angle Influence to Proximity Sensor Triggering(Bottom side)**

| Band(MHz)    | Minimum trigger distance at which power reduction was maintained over $\pm 45^\circ$ | Power Reduction Status |      |      |      |     |    |    |     |     |     |     |  |
|--------------|--------------------------------------------------------------------------------------|------------------------|------|------|------|-----|----|----|-----|-----|-----|-----|--|
|              |                                                                                      | -45°                   | -35° | -25° | -15° | -5° | 0° | 5° | 15° | 25° | 35° | 45° |  |
| GSM1900      | 13mm                                                                                 | on                     | on   | on   | on   | on  | on | on | on  | on  | on  | on  |  |
| UMTS Band II | 13mm                                                                                 | on                     | on   | on   | on   | on  | on | on | on  | on  | on  | on  |  |
| UMTS Band IV | 13mm                                                                                 | on                     | on   | on   | on   | on  | on | on | on  | on  | on  | on  |  |
| LTE Band II  | 13mm                                                                                 | on                     | on   | on   | on   | on  | on | on | on  | on  | on  | on  |  |
| LTE Band IV  | 13mm                                                                                 | on                     | on   | on   | on   | on  | on | on | on  | on  | on  | on  |  |
| LTE Band V   | 13mm                                                                                 | on                     | on   | on   | on   | on  | on | on | on  | on  | on  | on  |  |
| LTE Band VII | 13mm                                                                                 | on                     | on   | on   | on   | on  | on | on | on  | on  | on  | on  |  |

**Conclusion:** It can be ensured that the proximity sensor can be valid triggered for the DUT tilt coverage exposure condition (GSM1900,UMTS Band II/IV,LTE Band II/IV/V/VII of Main Antenna)

## 6.1.7 Infrared proximity sensor power reduction test Configuration

The device uses an infrared proximity sensor to reduce the output power of WiFi antenna when WiFi and 2G&3G&4G antenna voice mode transmit simultaneously in held-to-ear scenario or body front side scenario.

A specific external test software and chipset based internal test modes are used in sensor triggering power measurement validation tests. It can be ensured that the unmodified settings in production units, including maximum output power, amplifier gain and other RF performance or tuning parameters, are used for SAR measurement.

In this section, the following procedure is used to determine the triggering distances, coverage and tilt angle influences per FCC KDB 616217 D04 §6.

### 1) Procedures for determining proximity sensor triggering distances

The procedure per FCC KDB 616217 D04 §6.2 is used to determine the triggering distances. As the proximity sensor locates on the front face of the device and detects objects approaching only from the front side, so triggering distance only need to be checked for the front side when device is under voice mode(WiFi and 2G&3G&4G antenna voice mode transmit simultaneously in held-to-ear scenario or body front side scenario).

FCC KDB 616217 D04v01§6.2, the proximity sensor triggering distance measurement results are as below:






Figure : Proximity sensor triggering distances assessment (Front side only)

The DUT is moved towards from the flat phantom (WiFi + 2G&3G&4G antenna voice mode simultaneous transmission ):



The DUT is moved away from the flat phantom(WiFi + 2G&3G&4G antenna voice mode simultaneous transmission):



## 2) Procedures for determining antenna and proximity sensor coverage

The IR proximity sensor triggering power reduction is only applicable for the front side, not including the edges. For front side view, there is no spatial offset between the WiFi antenna and the proximity sensor element. The scene does not exist when the antenna is next to the user but the sensor is laterally further away, so procedures for determining the proximity sensor coverage per FCC KDB 616217§6.3 does not need to be assessed.

### 3) Procedures for determining device tilt angle influences to proximity sensor triggering

The following procedure is used to determine the triggering angle. Distance need to be check when device under voice mode so that sensor is working.

For Head exposure condition, device tilt angle influences to proximity sensor triggering is determined as below:

Firstly, the DUT was positioned directly touch the Head SAM phantom (Left&Right hand touch cheek position). Rotate the DUT around the ear reference point of the phantom in 5° increments until the DUT is 15° tilted or more away from the touch cheek position at 0° .

Secondly, the DUT is positioned at 15° or more away from the touch cheek position and moved towards the SAM phantom in 5° increments until the DUT directly touch the SAM phantom at 0° (Left & Right hand touch cheek position).

The DUT is moved towards and away from SAM phantom:

| Angle between phantom to DUT in degree                               | 0° | 5° | 10° | 15° | 20° | 25° | 30° |
|----------------------------------------------------------------------|----|----|-----|-----|-----|-----|-----|
| Condition of Sensor power reduction (Wi-Fi + 2G&3G&4G antenna voice) | on | on | on  | on  | on  | on  | on  |

**Conclusion:** Based on the validation results above, angle tilt coverage can ensure that the proximity sensor is valid triggered for all required Head test positions (Left/Right Hand Touched cheek and Left/Right Hand tilted 15°).

### 4) Summary SAR test Plan for Infrared Proximity sensor power reduction scenarios

a) For Head SAR compliance: The device not supports VoWiFi function. Head SAR for Wi-Fi antenna is evaluated at reduced power levels according to the real usage scenarios.

b) For other scenarios: Standalone SAR compliance for Wi-Fi antenna is still tested at the maximum output power level without any power reduction. The more conservative SAR results are used to ensure Body SAR compliance for both standalone and simultaneous transmission scenarios. So additional SAR test at the sensor triggering distance minus 1mm with the maximum output power level per KDB 616217D04 is not required.

## 6.2 3G SAR Test Reduction Procedure

Per KDB941225 D01v03, in the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the secondary mode. This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as “otherwise” in the applicable procedures; SAR measurement is required for the secondary mode.

## 6.3 GSM Test Configuration

SAR tests for GSM850 and GSM1900, a communication link is set up with a base station by air link. Using CMU200 the power lever is set to “5” and “0” in SAR of GSM850 and GSM1900. The tests in the band of GSM850 and GSM1900 are performed in the mode of GPRS/EGPRS function. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslot is 5. The EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink, and at most 4 timeslots in downlink, the maximum total timeslot is 5.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

## 6.4 UMTS Test Configuration

### 1) Output Power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1’s” for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are required in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

### 2) WCDMA

#### a. Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

#### b. Body SAR Measurements-

SAR for body-worn accessory configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode

### 3) HSDPA

SAR for body exposure configurations is measured according to the “Body SAR Measurements” procedures of 3G device. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the secondary mode. This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as “otherwise” in the applicable procedures; SAR measurement is required for the secondary mode.

Per KDB941225 D01v03, the 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures for the highest reported SAR body exposure configuration in 12.2 kbps RMC.

HSDPA should be configured according to UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HAPRQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission condition, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. The  $\beta_c$  and  $\beta_d$  gain factors for DPCCH and DPDCH were set according to the values in the below table,  $\beta_{hs}$  for HS-DPCCH is set automatically to the correct value when  $\Delta ACK$ ,  $\Delta NACK$ ,  $\Delta CQI = 8$ . The variation of the  $\beta_c / \beta_d$  ratio causes a power reduction at sub-tests 2 - 4.

| Sub-test <sup>↗</sup> | $\beta_c$ <sup>↗</sup> | $\beta_d$ <sup>↗</sup> | $\beta_d$ (SF) <sup>↗</sup> | $\beta_c/\beta_d$ <sup>↗</sup> | $\beta_{hs}(1)$ <sup>↗</sup> | CM(dB)(2) <sup>↗</sup> | MPR (dB) <sup>↗</sup> |
|-----------------------|------------------------|------------------------|-----------------------------|--------------------------------|------------------------------|------------------------|-----------------------|
| 1 <sup>↗</sup>        | 2/15 <sup>↗</sup>      | 15/15 <sup>↗</sup>     | 64 <sup>↗</sup>             | 2/15 <sup>↗</sup>              | 4/15 <sup>↗</sup>            | 0.0 <sup>↗</sup>       | 0 <sup>↗</sup>        |
| 2 <sup>↗</sup>        | 12/15(3) <sup>↗</sup>  | 15/15(3) <sup>↗</sup>  | 64 <sup>↗</sup>             | 12/15(3) <sup>↗</sup>          | 24/15 <sup>↗</sup>           | 1.0 <sup>↗</sup>       | 0 <sup>↗</sup>        |
| 3 <sup>↗</sup>        | 15/15 <sup>↗</sup>     | 8/15 <sup>↗</sup>      | 64 <sup>↗</sup>             | 15/8 <sup>↗</sup>              | 30/15 <sup>↗</sup>           | 1.5 <sup>↗</sup>       | 0.5 <sup>↗</sup>      |
| 4 <sup>↗</sup>        | 15/15 <sup>↗</sup>     | 4/15 <sup>↗</sup>      | 64 <sup>↗</sup>             | 15/4 <sup>↗</sup>              | 30/15 <sup>↗</sup>           | 1.5 <sup>↗</sup>       | 0.5 <sup>↗</sup>      |

Note 1:  $\Delta ACK$ ,  $\Delta NACK$  and  $\Delta CQI = 8$       $A_{hs} = \beta_{hs}/\beta_c = 30/15$       $\beta_{hs} = 30/15 * \beta_c$   
Note 2: CM=1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.  
Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$

Table 7: Sub-tests for UMTS Release 5 HSDPA

The measurements were performed with a Fixed Reference Channel (FRC) and H-Set 1 QPSK.

| Parameter                        | Value       |
|----------------------------------|-------------|
| Nominal average inf. bit rate    | 534 kbit/s  |
| Inter-TTI Distance               | 3 TTI's     |
| Number of HARQ Processes         | 2 Processes |
| Information Bit Payload          | 3202 Bits   |
| MAC-d PDU size                   | 336 Bits    |
| Number Code Blocks               | 1 Block     |
| Binary Channel Bits Per TTI      | 4800 Bits   |
| Total Available SMLs in UE       | 19200 SMLs  |
| Number of SMLs per HARQ Process  | 9600 SMLs   |
| Coding Rate                      | 0.67        |
| Number of Physical Channel Codes | 5           |

Table 8: settings of required H-Set 1 QPSK acc. to 3GPP 34.121

| HS-DSCH Category | Maximum HS-DSCH Codes Received | Minimum Inter-TTI Interval | Maximum HS-DSCH Transport Block Bits/HS-DSCH TTI | Total Soft Channel Bits |
|------------------|--------------------------------|----------------------------|--------------------------------------------------|-------------------------|
| 1                | 5                              | 3                          | 7298                                             | 19200                   |
| 2                | 5                              | 3                          | 7298                                             | 28800                   |
| 3                | 5                              | 2                          | 7298                                             | 28800                   |
| 4                | 5                              | 2                          | 7298                                             | 38400                   |
| 5                | 5                              | 1                          | 7298                                             | 57600                   |
| 6                | 5                              | 1                          | 7298                                             | 67200                   |
| 7                | 10                             | 1                          | 14411                                            | 115200                  |
| 8                | 10                             | 1                          | 14411                                            | 134400                  |
| 9                | 15                             | 1                          | 25251                                            | 172800                  |
| 10               | 15                             | 1                          | 27952                                            | 172800                  |
| 11               | 5                              | 2                          | 3630                                             | 14400                   |
| 12               | 5                              | 1                          | 3630                                             | 28800                   |
| 13               | 15                             | 1                          | 34800                                            | 259200                  |
| 14               | 15                             | 1                          | 42196                                            | 259200                  |
| 15               | 15                             | 1                          | 23370                                            | 345600                  |
| 16               | 15                             | 1                          | 27952                                            | 345600                  |

Table 9: HSDPA UE category

#### 4) HSUPA

SAR for body exposure configurations is measured according to the “Body SAR Measurements” procedures of 3G device. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/4$  dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the secondary mode.

Per KDB941225 D01v03, the 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures for the highest reported body exposure SAR configuration in 12.2 kbps RMC.

Due to inner loop power control requirements in HSDPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSDPA should be configured according to the values indicated below as well as other applicable procedures described in the ‘WCDMA Handset’ and ‘Release 5 HSDPA Data Device’ sections of 3G device.

| Sub-test <sup>⌘</sup> | $\beta_c$ <sup>⌘</sup> | $\beta_d$ <sup>⌘</sup> | $\beta_d$ (SF) <sup>⌘</sup> | $\beta_c/\beta_d$ <sup>⌘</sup> | $\beta_{hs}$ <sup>(1)⌘</sup> | $\beta_{ec}$ <sup>⌘</sup> | $\beta_{ed}$ <sup>⌘</sup>                                                    | $\beta_{ec}$ <sup>(SF)<br/>⌘</sup> | $\beta_{ed}$ <sup>(code<br/>⌘</sup> | CM <sup>(2)⌘</sup><br>(dB) <sup>⌘</sup> | MP<br>R <sup>⌘</sup><br>(dB) <sup>⌘</sup> | AG <sup>(4)<br/>⌘</sup><br>Inde<br>x <sup>⌘</sup> | E-<br>TFC<br>I <sup>⌘</sup> |
|-----------------------|------------------------|------------------------|-----------------------------|--------------------------------|------------------------------|---------------------------|------------------------------------------------------------------------------|------------------------------------|-------------------------------------|-----------------------------------------|-------------------------------------------|---------------------------------------------------|-----------------------------|
| 1 <sup>⌘</sup>        | 11/15 <sup>(3)⌘</sup>  | 15/15 <sup>(3)⌘</sup>  | 64 <sup>⌘</sup>             | 11/15 <sup>(3)⌘</sup>          | 22/15 <sup>⌘</sup>           | 209/22<br>5 <sup>⌘</sup>  | 1039/225 <sup>⌘</sup>                                                        | 4 <sup>⌘</sup>                     | 1 <sup>⌘</sup>                      | 1.0 <sup>⌘</sup>                        | 0.0 <sup>⌘</sup>                          | 20 <sup>⌘</sup>                                   | 75 <sup>⌘</sup>             |
| 2 <sup>⌘</sup>        | 6/15 <sup>⌘</sup>      | 15/15 <sup>⌘</sup>     | 64 <sup>⌘</sup>             | 6/15 <sup>⌘</sup>              | 12/15 <sup>⌘</sup>           | 12/15 <sup>⌘</sup>        | 94/75 <sup>⌘</sup>                                                           | 4 <sup>⌘</sup>                     | 1 <sup>⌘</sup>                      | 3.0 <sup>⌘</sup>                        | 2.0 <sup>⌘</sup>                          | 12 <sup>⌘</sup>                                   | 67 <sup>⌘</sup>             |
| 3 <sup>⌘</sup>        | 15/15 <sup>⌘</sup>     | 9/15 <sup>⌘</sup>      | 64 <sup>⌘</sup>             | 15/9 <sup>⌘</sup>              | 30/15 <sup>⌘</sup>           | 30/15 <sup>⌘</sup>        | $\beta_{ed1}:47/1$<br>5 <sup>⌘</sup><br>$\beta_{ed2}:47/1$<br>5 <sup>⌘</sup> | 4 <sup>⌘</sup>                     | 2 <sup>⌘</sup>                      | 2.0 <sup>⌘</sup>                        | 1.0 <sup>⌘</sup>                          | 15 <sup>⌘</sup>                                   | 92 <sup>⌘</sup>             |
| 4 <sup>⌘</sup>        | 2/15 <sup>⌘</sup>      | 15/15 <sup>⌘</sup>     | 64 <sup>⌘</sup>             | 2/15 <sup>⌘</sup>              | 4/15 <sup>⌘</sup>            | 2/15 <sup>⌘</sup>         | 56/75 <sup>⌘</sup>                                                           | 4 <sup>⌘</sup>                     | 1 <sup>⌘</sup>                      | 3.0 <sup>⌘</sup>                        | 2.0 <sup>⌘</sup>                          | 17 <sup>⌘</sup>                                   | 71 <sup>⌘</sup>             |
| 5 <sup>⌘</sup>        | 15/15 <sup>(4)⌘</sup>  | 15/15 <sup>(4)⌘</sup>  | 64 <sup>⌘</sup>             | 15/15 <sup>(4)⌘</sup>          | 30/15 <sup>⌘</sup>           | 24/15 <sup>⌘</sup>        | 134/15 <sup>⌘</sup>                                                          | 4 <sup>⌘</sup>                     | 1 <sup>⌘</sup>                      | 1.0 <sup>⌘</sup>                        | 0.0 <sup>⌘</sup>                          | 21 <sup>⌘</sup>                                   | 81 <sup>⌘</sup>             |

Note 1:  $\Delta$  ACK,  $\Delta$  NACK and  $\Delta$  CQI = 8  $A_{hs} = \beta_{hs}/\beta_c = 30/15$   $\beta_{hs} = 30/15 * \beta_c$ <sup>⌘</sup>

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference<sup>⌘</sup>

Note 3 : For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ <sup>⌘</sup>

Note 4 : For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ <sup>⌘</sup>

Note 5 : Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g<sup>⌘</sup>

Note 6:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.<sup>⌘</sup>

Table 10: Subtests for UMTS Release 6 HSUPA

| UE E-DCH Category | Maximum E-DCH Codes Transmitted | Number of HARQ Processes | E-DCH TTI(ms) | Minimum Spreading Factor | Maximum E-DCH Transport Block Bits | Max Rate (Mbps) |
|-------------------|---------------------------------|--------------------------|---------------|--------------------------|------------------------------------|-----------------|
| 1                 | 1                               | 4                        | 10            | 4                        | 7110                               | 0.7296          |
| 2                 | 2                               | 8                        | 2             | 4                        | 2798                               | 1.4592          |
|                   | 2                               | 4                        | 10            | 4                        | 14484                              |                 |
| 3                 | 2                               | 4                        | 10            | 4                        | 14484                              | 1.4592          |
| 4                 | 2                               | 8                        | 2             | 2                        | 5772                               | 2.9185          |
|                   | 2                               | 4                        | 10            | 2                        | 20000                              | 2.00            |
| 5                 | 2                               | 4                        | 10            | 2                        | 20000                              | 2.00            |
| 6<br>(No DPDCH)   | 4                               | 8                        | 10            | 2SF2&2SF                 | 11484                              | 5.76            |
|                   | 4                               | 4                        | 2             | 4                        | 20000                              | 2.00            |
| 7<br>(No DPDCH)   | 4                               | 8                        | 2             | 2SF2&2SF                 | 22996                              | ?               |
|                   | 4                               | 4                        | 10            | 4                        | 20000                              | ?               |

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4. UE categories 1 to 6 support QPSK only. UE category 7 supports QPSK and 16QAM. (TS25.306-7.3.0).

Table 11: HSUPA UE category

## 5) DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a Second serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS 34.108 v9.5.0. A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0

**Table E.5.0: Levels for HSDPA connection setup**

| Parameter During Connection setup | Unit | Value |
|-----------------------------------|------|-------|
| P-CPICH_Ec/Ior                    | dB   | -10   |
| P-CCPCH and SCH_Ec/Ior            | dB   | -12   |
| PICH_Ec/Ior                       | dB   | -15   |
| HS-PDSCH                          | dB   | off   |
| HS-SCCH_1                         | dB   | off   |
| DPCH_Ec/Ior                       | dB   | -5    |
| OCNS_Ec/Ior                       | dB   | -3.1  |

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13

The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.

The measurements were performed with a Fixed Reference Channel (FRC) H-Set 12 with QPSK

| Parameter                        | Value       |
|----------------------------------|-------------|
| Nominal average inf. bit rate    | 60 kbit/s   |
| Inter-TTI Distance               | 1 TTI's     |
| Number of HARQ Processes         | 6 Processes |
| Information Bit Payload          | 120 Bits    |
| Number Code Blocks               | 1 Block     |
| Binary Channel Bits Per TTI      | 960 Bits    |
| Total Available SMLs in UE       | 19200 SMLs  |
| Number of SMLs per HARQ Process  | 3200 SMLs   |
| Coding Rate                      | 0.15        |
| Number of Physical Channel Codes | 1           |

Table 12: settings of required H-Set 12 QPSK acc. to 3GPP 34.121

Note:

- 1.The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table above.
- 2.Maximum number of transmission is limited to 1,i.e.,retransmission is not allowed. The redundancy and constellation version 0 shall be used.




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 5 procedures. A summary of subtest settings are illustrated below:

| Sub-test <sup>o</sup> | $\beta_c$ <sup>o</sup> | $\beta_d$ <sup>o</sup> | $\beta_d$ (SF) <sup>o</sup> | $\beta_c/\beta_d$ <sup>o</sup> | $\beta_{hs}(1)$ <sup>o</sup> | CM(dB)(2) <sup>o</sup> | MPR(dB) <sup>o</sup> |
|-----------------------|------------------------|------------------------|-----------------------------|--------------------------------|------------------------------|------------------------|----------------------|
| 1 <sup>o</sup>        | 2/15 <sup>o</sup>      | 15/15 <sup>o</sup>     | 64 <sup>o</sup>             | 2/15 <sup>o</sup>              | 4/15 <sup>o</sup>            | 0.0 <sup>o</sup>       | 0 <sup>o</sup>       |
| 2 <sup>o</sup>        | 12/15(3) <sup>o</sup>  | 15/15(3) <sup>o</sup>  | 64 <sup>o</sup>             | 12/15(3) <sup>o</sup>          | 24/15 <sup>o</sup>           | 1.0 <sup>o</sup>       | 0 <sup>o</sup>       |
| 3 <sup>o</sup>        | 15/15 <sup>o</sup>     | 8/15 <sup>o</sup>      | 64 <sup>o</sup>             | 15/8 <sup>o</sup>              | 30/15 <sup>o</sup>           | 1.5 <sup>o</sup>       | 0.5 <sup>o</sup>     |
| 4 <sup>o</sup>        | 15/15 <sup>o</sup>     | 4/15 <sup>o</sup>      | 64 <sup>o</sup>             | 15/4 <sup>o</sup>              | 30/15 <sup>o</sup>           | 1.5 <sup>o</sup>       | 0.5 <sup>o</sup>     |

Note 1:  $\Delta ACK$ ,  $\Delta NACK$  and  $\Delta CQI=8$        $A_{hs} = \beta_{hs}/\beta_c = 30/15$        $\beta_{hs} = 30/15 * \beta_c$ <sup>o</sup>  
Note 2: CM=1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.<sup>o</sup>  
Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ <sup>o</sup>

Up commands are set continuously to set the UE to Max power.

Note:

- 1.The Dual Carriers transmission only applies to HSDPA physical channels
- 2.The Dual Carriers belong to the same Node and are on adjacent carriers.
- 3.The Dual Carriers do not support MIMO to serve UEs configured for dual cell operation
- 4.The Dual Carriers operate in the same frequency band .
- 5.The device doesn't support the modulation of 16QAM in uplink but 64QAM in downlink for DC-HSDPA mode.
- 6.The device doesn't support carrier aggregation for it just can operate in Release 8.

## 6.5 LTE Test Configuration

SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05. The CMW500 WideBand Radio Communication Tester was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR test were performed with the same number of RB and RB offsets transmitting on all TTI frames (Maximum TTI)

### 1) Spectrum Plots for RB configurations

A properly configured base station simulator was used for LTE output power measurements and SAR testing. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 2) MPR

When MPR is implemented permanently within the UE, regardless of network requirements, only those RB configurations allowed by 3GPP for the channel bandwidth and modulation combinations may be tested with MPR active. Configurations with RB allocations less than the RB thresholds required by 3GPP must be tested without MPR.

The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

**Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3**

| Modulation | Channel bandwidth / Transmission bandwidth (RB) |         |       |        |        |        | MPR (dB) |
|------------|-------------------------------------------------|---------|-------|--------|--------|--------|----------|
|            | 1.4 MHz                                         | 3.0 MHz | 5 MHz | 10 MHz | 15 MHz | 20 MHz |          |
| QPSK       | > 5                                             | > 4     | > 8   | > 12   | > 16   | > 18   | ≤ 1      |
| 16 QAM     | ≤ 5                                             | ≤ 4     | ≤ 8   | ≤ 12   | ≤ 16   | ≤ 18   | ≤ 1      |
| 16 QAM     | > 5                                             | > 4     | > 8   | > 12   | > 16   | > 18   | ≤ 2      |

### 3) A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by using Network Signalling Value of "NS\_01" on the base station simulator.

### 4) LTE procedures for SAR testing

#### A) Largest channel bandwidth standalone SAR test requirements

##### i) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

ii) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in i) are applied to measure the SAR for QPSK with 50% RB allocation.

iii) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in i) and ii) are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

iv) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is  $> \frac{1}{2}$  dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45$  W/kg.

B) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is  $> \frac{1}{2}$  dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is  $> 1.45$  W/kg.

## 6.6 WiFi Test Configuration

For WiFi SAR testing, a communication link is set up with the testing software for WiFi mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. The test procedures in KDB 248227D01 are applied.

### 6.6.1 Initial Test Position Procedure

For exposure condition with multiple test position, such as handsets operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all position in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4 \text{ W/kg}$ , no additional testing for the remaining test position is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is  $\leq 0.8 \text{ W/kg}$  or all test position are measured. For all positions/configurations tested using the initial test position and subsequent test positions, when the *reported* SAR is  $> 0.8 \text{ W/kg}$ , SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the *reported* SAR is  $\leq 1.2 \text{ W/kg}$  or all required channels are tested.

### 6.6.2 Initial Test Configuration Procedure

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required (see section 5.3.2 of KDB 248227D01v02). SAR test reduction of subsequent highest output test channels is based on the *reported* SAR of the initial test configuration.

For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.

When the *reported* SAR of the initial test configuration is  $> 0.8 \text{ W/kg}$ , SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until the *reported* SAR is  $\leq 1.2 \text{ W/kg}$  or all required channels are tested.

### 6.6.3 Sub Test Configuration Procedure

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units.

When the highest reported SAR for the initial test configuration, according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2 \text{ W/kg}$ , SAR is not required for that subsequent test configuration.

## 6.6.4 WiFi 2.4G SAR Test Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions.

### A) 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the *reported* SAR of the highest measured maximum output power channel (section 3.1 of of KDB 248227D01v02) for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the *reported* SAR is  $> 0.8$  W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any *reported* SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

### B) 2.4GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3 of of KDB 248227D01v02). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

## 6.7 BT Test Configuration

For BT SAR testing, the is set to the DUT continuous transmitting with maximum output power using the Wireless Connectivity Test Set N4010A. Per October 2016 TCB Worksop Notes, the BT SAR was scaled to the 100% transmission duty cycle to determine compliance. Refer to section 7.1 for the time-domain plot and calculation for the duty cylce of the device.

## 7 SAR Measurement Results

### 7.1 Conducted power measurements

For the measurements a Rohde & Schwarz Radio Communication Tester CMU 200&CMW500 was used. SAR drift measured at the same position in liquid before and after each SAR test as below 7.2 chapter.

Note: CMU200 measures GSM peak and average output power for active timeslots. For SAR the timebased average power is relevant. The difference in between depends on the duty cycle of the TDMA signal :

| No. of timeslots                                    | 1       | 2       | 3       | 4       |
|-----------------------------------------------------|---------|---------|---------|---------|
| Duty Cycle                                          | 1:8.3   | 1:4.1   | 1:2.77  | 1:2.08  |
| timebased avg. power compared to slotted avg. power | -9.19dB | -6.13dB | -4.42dB | -3.18dB |

The signalling modes differ as follows:

| mode | coding scheme | modulation |
|------|---------------|------------|
| GPRS | CS1 to CS4    | GMSK       |
| EDGE | MCS1 to MCS4  | GMSK       |
| EDGE | MCS5 to MCS9  | 8PSK       |

Apart from modulation change (GMSK/8PSK) coding schemes differ in code rate without influence on the RF signal. Therefore one coding scheme per mode was selected for conducted power measurements.

### 7.1.1 Conducted power measurements of GSM850 (Second Antenna)

| GSM850            |            | Burst-Averaged output Power (dBm) |              |              |              | Division Factors | Frame-Averaged output Power (dBm) |              |              |              |
|-------------------|------------|-----------------------------------|--------------|--------------|--------------|------------------|-----------------------------------|--------------|--------------|--------------|
|                   |            | Tune-up                           | 128CH        | 190CH        | 251CH        |                  | Tune-up                           | 128CH        | 190CH        | 251CH        |
| GSM (CS)          |            | 33.50                             | 32.45        | 32.40        | 32.34        | -9.19            | 24.31                             | 23.26        | 23.21        | 23.15        |
| GPRS /EDGE (GMSK) | 1 Tx Slot  | 33.50                             | 32.45        | 32.40        | 32.35        | -9.19            | 24.31                             | 23.26        | 23.21        | 23.16        |
|                   | 2 Tx Slots | <b>31.50</b>                      | <b>30.40</b> | <b>30.36</b> | <b>30.29</b> | <b>-6.13</b>     | <b>25.37</b>                      | <b>24.27</b> | <b>24.23</b> | <b>24.16</b> |
|                   | 3 Tx Slots | 29.50                             | 28.37        | 28.31        | 28.25        | -4.42            | 25.08                             | 23.95        | 23.89        | 23.83        |
|                   | 4 Tx Slots | 27.50                             | 26.29        | 26.26        | 26.17        | -3.18            | 24.32                             | 23.11        | 23.08        | 22.99        |
| EDGE (8PSK)       | 1 Tx Slot  | 27.00                             | 26.08        | 26.04        | 25.97        | -9.19            | 17.81                             | 16.89        | 16.85        | 16.78        |
|                   | 2 Tx Slots | 25.00                             | 23.68        | 23.75        | 23.70        | -6.13            | 18.87                             | 17.55        | 17.62        | 17.57        |
|                   | 3 Tx Slots | 23.00                             | 21.60        | 21.70        | 21.60        | -4.42            | 18.58                             | 17.18        | 17.28        | 17.18        |
|                   | 4 Tx Slots | 21.00                             | 19.57        | 19.62        | 19.67        | -3.18            | 17.82                             | 16.39        | 16.44        | 16.49        |

Table 13:Conducted power measurement results of GSM850 (Full power)

| GSM850   | Burst-Averaged output Power (dBm) |       |       |       | Division Factors | Frame-Averaged output Power (dBm) |       |       |       |
|----------|-----------------------------------|-------|-------|-------|------------------|-----------------------------------|-------|-------|-------|
|          | Tune-up                           | 128CH | 190CH | 251CH |                  | Tune-up                           | 128CH | 190CH | 251CH |
| GSM (CS) | 30.50                             | 29.37 | 29.34 | 29.28 | -9.19            | 21.31                             | 20.18 | 20.15 | 20.09 |

Table 14:Conducted power measurement results of GSM850 (Receiver on, voice mode)

| GSM850            |            | Burst-Averaged output Power (dBm) |              |              |              | Division Factors | Frame-Averaged output Power (dBm) |              |              |              |
|-------------------|------------|-----------------------------------|--------------|--------------|--------------|------------------|-----------------------------------|--------------|--------------|--------------|
|                   |            | Tune-up                           | 128CH        | 190CH        | 251CH        |                  | Tune-up                           | 128CH        | 190CH        | 251CH        |
| GSM (CS)          |            | 28.50                             | 27.36        | 27.33        | 27.26        | -9.19            | 19.31                             | 18.17        | 18.14        | 18.07        |
| GPRS /EDGE (GMSK) | 1 Tx Slot  | 28.50                             | 27.32        | 27.31        | 27.22        | -9.19            | 19.31                             | 18.13        | 18.12        | 18.03        |
|                   | 2 Tx Slots | <b>26.50</b>                      | <b>25.34</b> | <b>25.30</b> | <b>25.23</b> | <b>-6.13</b>     | <b>20.37</b>                      | <b>19.21</b> | <b>19.17</b> | <b>19.10</b> |
|                   | 3 Tx Slots | 24.50                             | 23.28        | 23.25        | 23.18        | -4.42            | 20.08                             | 18.86        | 18.83        | 18.76        |
|                   | 4 Tx Slots | 22.50                             | 21.30        | 21.23        | 21.15        | -3.18            | 19.32                             | 18.12        | 18.05        | 17.97        |
| EDGE (8PSK)       | 1 Tx Slot  | 24.50                             | 24.02        | 24.01        | 24.02        | -9.19            | 15.31                             | 14.83        | 14.82        | 14.83        |
|                   | 2 Tx Slots | 22.50                             | 21.92        | 21.90        | 21.83        | -6.13            | 16.37                             | 15.79        | 15.77        | 15.70        |
|                   | 3 Tx Slots | 20.50                             | 19.91        | 19.87        | 19.81        | -4.42            | 16.08                             | 15.49        | 15.45        | 15.39        |
|                   | 4 Tx Slots | 18.50                             | 17.73        | 17.73        | 17.62        | -3.18            | 15.32                             | 14.55        | 14.55        | 14.44        |

Table 15:Conducted power measurement results of GSM850 (Second antenna+WiFi antenna Simultaneous Transmission)

Note:

- 1) The conducted power of GSM850 is measured with RMS detector.
- 2) Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- 3) Per KDB941225 D01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

### 7.1.2 Conducted power measurements of GSM1900 (Second Antenna)

| GSM1900           |            | Burst-Averaged output Power (dBm) |              |              |              | Division Factors | Frame-Averaged output Power (dBm) |              |              |              |
|-------------------|------------|-----------------------------------|--------------|--------------|--------------|------------------|-----------------------------------|--------------|--------------|--------------|
|                   |            | Tune-up                           | 512CH        | 661CH        | 810CH        |                  | Tune-up                           | 512CH        | 661CH        | 810CH        |
| GSM (CS)          |            | 30.00                             | 28.74        | 28.44        | 28.37        | -9.19            | 20.81                             | 19.55        | 19.25        | 19.18        |
| GPRS /EDGE (GMSK) | 1 Tx Slot  | 30.00                             | 28.68        | 28.43        | 28.38        | -9.19            | 20.81                             | 19.49        | 19.24        | 19.19        |
|                   | 2 Tx Slots | <b>28.00</b>                      | <b>26.49</b> | <b>26.30</b> | <b>26.35</b> | <b>-6.13</b>     | <b>21.87</b>                      | <b>20.36</b> | <b>20.17</b> | <b>20.22</b> |
|                   | 3 Tx Slots | 26.00                             | 24.46        | 24.29        | 24.28        | -4.42            | 21.58                             | 20.04        | 19.87        | 19.86        |
|                   | 4 Tx Slots | 24.00                             | 22.80        | 22.67        | 22.72        | -3.18            | 20.82                             | 19.62        | 19.49        | 19.54        |
| EDGE (8PSK)       | 1 Tx Slot  | 25.50                             | 23.93        | 23.79        | 23.89        | -9.19            | 16.31                             | 14.74        | 14.60        | 14.70        |
|                   | 2 Tx Slots | 23.50                             | 21.85        | 21.79        | 21.82        | -6.13            | 17.37                             | 15.72        | 15.66        | 15.69        |
|                   | 3 Tx Slots | 21.00                             | 19.35        | 19.16        | 19.74        | -4.42            | 16.58                             | 14.93        | 14.74        | 15.32        |
|                   | 4 Tx Slots | 19.50                             | 17.79        | 17.72        | 17.61        | -3.18            | 16.32                             | 14.61        | 14.54        | 14.43        |

Table 16:Conducted power measurement results of GSM1900 (Full power)

| GSM1900  | Burst-Averaged output Power (dBm) |       |       |       | Division Factors | Frame-Averaged output Power (dBm) |       |       |       |
|----------|-----------------------------------|-------|-------|-------|------------------|-----------------------------------|-------|-------|-------|
|          | Tune-up                           | 512CH | 661CH | 810CH |                  | Tune-up                           | 512CH | 661CH | 810CH |
| GSM (CS) | 28.00                             | 26.46 | 26.31 | 26.37 | -9.19            | 18.81                             | 17.27 | 17.12 | 17.18 |

Table 17: Conducted power measurement results of GSM1900 (Receiver on,voice mode)

| GSM1900           |            | Burst-Averaged output Power (dBm) |              |              |              | Division Factors | Frame-Averaged output Power (dBm) |              |              |              |
|-------------------|------------|-----------------------------------|--------------|--------------|--------------|------------------|-----------------------------------|--------------|--------------|--------------|
|                   |            | Tune-up                           | 512CH        | 661CH        | 810CH        |                  | Tune-up                           | 512CH        | 661CH        | 810CH        |
| GSM (CS)          |            | 25.00                             | 23.42        | 23.31        | 23.32        | -9.19            | 15.81                             | 14.23        | 14.12        | 14.13        |
| GPRS /EDGE (GMSK) | 1 Tx Slot  | 25.00                             | 23.46        | 23.32        | 23.33        | -9.19            | 15.81                             | 14.27        | 14.13        | 14.14        |
|                   | 2 Tx Slots | <b>23.00</b>                      | <b>21.41</b> | <b>21.31</b> | <b>21.35</b> | <b>-6.13</b>     | <b>16.87</b>                      | <b>15.28</b> | <b>15.18</b> | <b>15.22</b> |
|                   | 3 Tx Slots | 21.00                             | 19.52        | 19.40        | 19.54        | -4.42            | 16.58                             | 15.1         | 14.98        | 15.12        |
|                   | 4 Tx Slots | 19.00                             | 18.01        | 17.94        | 18.05        | -3.18            | 15.82                             | 14.83        | 14.76        | 14.87        |
| EDGE (8PSK)       | 1 Tx Slot  | 25.00                             | 23.76        | 23.51        | 23.71        | -9.19            | 15.81                             | 14.57        | 14.32        | 14.52        |
|                   | 2 Tx Slots | 23.00                             | 21.64        | 21.30        | 21.61        | -6.13            | 16.87                             | 15.51        | 15.17        | 15.48        |
|                   | 3 Tx Slots | 20.50                             | 19.39        | 19.18        | 19.71        | -4.42            | 16.08                             | 14.97        | 14.76        | 15.29        |
|                   | 4 Tx Slots | 19.00                             | 17.71        | 17.54        | 17.58        | -3.18            | 15.82                             | 14.53        | 14.36        | 14.40        |

Table 18:Conducted power measurement results of GSM1900 (Second antenna+WiFi antenna Simultaneous Transmission)

Note:

- 1) The conducted power of GSM1900 is measured with RMS detector.
- 2) Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- 3) Per KDB941225 D01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

### 7.1.3 Conducted power measurements of UMTS Band II (Second Antenna)

| UMTS1900<br>(Band II) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 9262CH              | 9400CH       | 9538CH       |
| WCDMA                 | 12.2kbps RMC | <b>20.00</b> | <b>18.63</b>        | <b>18.77</b> | <b>18.87</b> |
|                       | 12.2kbps AMR | 20.00        | 18.49               | 18.72        | 18.95        |
| HSDPA                 | Subtest 1    | 19.00        | 17.56               | 17.70        | 17.83        |
|                       | Subtest 2    | 19.00        | 17.33               | 17.48        | 17.64        |
|                       | Subtest 3    | 18.50        | 17.87               | 16.91        | 17.03        |
|                       | Subtest 4    | 18.50        | 17.95               | 16.90        | 17.02        |
| HSUPA                 | Subtest 1    | 19.00        | 17.24               | 17.48        | 17.01        |
|                       | Subtest 2    | 16.00        | 14.36               | 14.67        | 14.87        |
|                       | Subtest 3    | 17.00        | 15.73               | 15.82        | 15.77        |
|                       | Subtest 4    | 16.00        | 14.83               | 15.22        | 15.23        |
|                       | Subtest 5    | 19.00        | 17.54               | 17.69        | 17.83        |
| DC-HSDPA              | Subtest 1    | 19.00        | 17.63               | 17.76        | 17.89        |
|                       | Subtest 2    | 19.00        | 17.44               | 17.55        | 17.70        |
|                       | Subtest 3    | 18.50        | 17.95               | 16.99        | 17.12        |
|                       | Subtest 4    | 18.50        | 18.03               | 16.99        | 17.09        |

Table 19: Conducted power measurement results of UMTS Band II (Receiver on)

| UMTS1900<br>(Band II) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 9262CH              | 9400CH       | 9538CH       |
| WCDMA                 | 12.2kbps RMC | <b>23.00</b> | <b>21.63</b>        | <b>21.80</b> | <b>21.89</b> |
|                       | 12.2kbps AMR | 23.00        | 21.55               | 21.81        | 21.83        |
| HSDPA                 | Subtest 1    | 22.00        | 20.60               | 20.78        | 20.87        |
|                       | Subtest 2    | 22.00        | 20.36               | 20.55        | 20.64        |
|                       | Subtest 3    | 21.50        | 19.83               | 19.98        | 20.10        |
|                       | Subtest 4    | 21.50        | 19.82               | 19.98        | 20.08        |
| HSUPA                 | Subtest 1    | 22.00        | 20.32               | 20.52        | 20.07        |
|                       | Subtest 2    | 19.00        | 17.39               | 17.62        | 17.71        |
|                       | Subtest 3    | 20.00        | 18.54               | 18.58        | 18.57        |
|                       | Subtest 4    | 19.00        | 17.85               | 18.07        | 18.31        |
|                       | Subtest 5    | 22.00        | 20.49               | 20.70        | 20.83        |
| DC-HSDPA              | Subtest 1    | 22.00        | 20.68               | 20.88        | 20.94        |
|                       | Subtest 2    | 22.00        | 20.44               | 20.64        | 20.71        |
|                       | Subtest 3    | 21.50        | 19.90               | 20.08        | 20.17        |
|                       | Subtest 4    | 21.50        | 19.90               | 20.07        | 20.18        |

Table 20: Conducted power measurement results of UMTS Band II (Full power)

| UMTS1900<br>(Band II) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 9262CH              | 9400CH       | 9538CH       |
| WCDMA                 | 12.2kbps RMC | <b>17.00</b> | <b>15.57</b>        | <b>15.75</b> | <b>15.91</b> |
|                       | 12.2kbps AMR | 17.00        | 15.46               | 15.74        | 15.84        |
| HSDPA                 | Subtest 1    | 16.00        | 14.81               | 14.75        | 14.89        |
|                       | Subtest 2    | 16.00        | 14.26               | 14.48        | 14.61        |
|                       | Subtest 3    | 15.50        | 14.11               | 14.05        | 14.23        |
|                       | Subtest 4    | 15.50        | 14.22               | 14.38        | 14.25        |
| HSUPA                 | Subtest 1    | 15.50        | 15.47               | 13.82        | 13.96        |
|                       | Subtest 2    | 13.00        | 12.34               | 11.66        | 12.05        |
|                       | Subtest 3    | 14.00        | 13.19               | 12.94        | 13.06        |
|                       | Subtest 4    | 13.00        | 13.00               | 12.33        | 12.40        |
|                       | Subtest 5    | 16.00        | 14.55               | 14.70        | 14.80        |
| DC-HSDPA              | Subtest 1    | 16.00        | 14.87               | 14.85        | 14.97        |
|                       | Subtest 2    | 16.00        | 14.32               | 14.54        | 14.71        |
|                       | Subtest 3    | 15.50        | 14.21               | 14.15        | 14.31        |
|                       | Subtest 4    | 15.50        | 14.31               | 14.44        | 14.32        |

Table 21: Conducted power measurement results of UMTS Band II (Second antenna+WiFi antenna Simultaneous Transmission)

Note:

- 1) The conducted power of UMTS Band II is measured with RMS detector.
- 2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).
- 3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the Second mode.

#### 7.1.4 Conducted power measurements of UMTS Band IV (Second Antenna)

| UMTS1700<br>(Band IV) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 1312CH              | 1413CH       | 1513CH       |
| WCDMA                 | 12.2kbps RMC | <b>21.00</b> | <b>19.95</b>        | <b>19.92</b> | <b>19.96</b> |
|                       | 12.2kbps AMR | 21.00        | 19.91               | 19.80        | 19.81        |
| HSDPA                 | Subtest 1    | 20.00        | 19.02               | 18.90        | 18.92        |
|                       | Subtest 2    | 20.00        | 18.70               | 18.68        | 18.71        |
|                       | Subtest 3    | 19.50        | 18.11               | 18.13        | 18.12        |
|                       | Subtest 4    | 19.50        | 18.10               | 18.10        | 18.10        |
| HSUPA                 | Subtest 1    | 20.00        | 18.05               | 18.41        | 18.37        |
|                       | Subtest 2    | 17.00        | 15.68               | 15.63        | 15.72        |
|                       | Subtest 3    | 18.00        | 17.11               | 17.11        | 17.14        |
|                       | Subtest 4    | 17.00        | 16.21               | 16.18        | 16.27        |
|                       | Subtest 5    | 20.00        | 18.87               | 18.86        | 18.84        |
| DC-HSDPA              | Subtest 1    | 20.00        | 19.10               | 19.00        | 19.03        |
|                       | Subtest 2    | 20.00        | 18.76               | 18.74        | 18.78        |
|                       | Subtest 3    | 19.50        | 18.19               | 18.20        | 18.21        |
|                       | Subtest 4    | 19.50        | 18.19               | 18.20        | 18.17        |

Table 22: Conducted power measurement results of UMTS Band IV (Receiver on)

| UMTS1700<br>(Band IV) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 1312CH              | 1413CH       | 1513CH       |
| WCDMA                 | 12.2kbps RMC | <b>23.00</b> | <b>21.97</b>        | <b>21.95</b> | <b>21.87</b> |
|                       | 12.2kbps AMR | 23.00        | 21.95               | 21.85        | 21.80        |
| HSDPA                 | Subtest 1    | 22.00        | 20.99               | 20.91        | 20.84        |
|                       | Subtest 2    | 22.00        | 20.79               | 20.69        | 20.62        |
|                       | Subtest 3    | 21.50        | 20.20               | 20.12        | 20.07        |
|                       | Subtest 4    | 21.50        | 20.19               | 20.11        | 20.05        |
| HSUPA                 | Subtest 1    | 22.00        | 20.58               | 20.28        | 20.41        |
|                       | Subtest 2    | 19.00        | 17.66               | 17.67        | 17.57        |
|                       | Subtest 3    | 20.00        | 19.06               | 18.23        | 18.96        |
|                       | Subtest 4    | 19.00        | 17.88               | 17.96        | 17.68        |
|                       | Subtest 5    | 22.00        | 20.81               | 20.84        | 20.66        |
| DC-HSDPA              | Subtest 1    | 22.00        | 21.08               | 21.00        | 20.90        |
|                       | Subtest 2    | 22.00        | 20.89               | 20.77        | 20.67        |
|                       | Subtest 3    | 21.50        | 20.26               | 20.23        | 20.16        |
|                       | Subtest 4    | 21.50        | 20.26               | 20.22        | 20.15        |

Table 23: Conducted power measurement results of UMTS Band IV (Full power)

| UMTS1700<br>(Band IV) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 1312CH              | 1413CH       | 1513CH       |
| WCDMA                 | 12.2kbps RMC | <b>19.00</b> | <b>17.93</b>        | <b>17.90</b> | <b>17.95</b> |
|                       | 12.2kbps AMR | 19.00        | 17.90               | 17.84        | 17.81        |
| HSDPA                 | Subtest 1    | 18.00        | 16.90               | 16.90        | 16.91        |
|                       | Subtest 2    | 18.00        | 16.65               | 16.66        | 16.66        |
|                       | Subtest 3    | 17.50        | 16.49               | 16.45        | 16.43        |
|                       | Subtest 4    | 17.50        | 16.51               | 16.49        | 16.46        |
| HSUPA                 | Subtest 1    | 18.00        | 16.62               | 16.71        | 16.69        |
|                       | Subtest 2    | 15.00        | 13.52               | 13.39        | 13.59        |
|                       | Subtest 3    | 16.00        | 15.08               | 15.14        | 15.13        |
|                       | Subtest 4    | 15.00        | 13.96               | 13.83        | 14.01        |
|                       | Subtest 5    | 18.00        | 16.83               | 16.87        | 16.86        |
| DC-HSDPA              | Subtest 1    | 18.00        | 17.01               | 16.98        | 17.02        |
|                       | Subtest 2    | 18.00        | 16.71               | 16.76        | 16.76        |
|                       | Subtest 3    | 17.50        | 16.56               | 16.50        | 16.49        |
|                       | Subtest 4    | 17.50        | 16.57               | 16.57        | 16.53        |

Table 24: Conducted power measurement results of UMTS Band IV (Second antenna+WiFi antenna Simultaneous Transmission)

Note:

- 1) The conducted power of UMTS Band IV is measured with RMS detector.
- 2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).
- 3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the Second mode.

### 7.1.5 Conducted power measurements of UMTS Band V (Second Antenna)

| UMTS850<br>(Band V) |              | Tune-up      | Average Power (dBm) |              |              |
|---------------------|--------------|--------------|---------------------|--------------|--------------|
|                     |              |              | 4132CH              | 4182CH       | 4233CH       |
| WCDMA               | 12.2kbps RMC | <b>20.50</b> | <b>19.33</b>        | <b>19.34</b> | <b>19.38</b> |
|                     | 12.2kbps AMR | 20.50        | 19.35               | 19.36        | 19.39        |
| HSDPA               | Subtest 1    | 19.50        | 18.35               | 18.34        | 18.37        |
|                     | Subtest 2    | 19.50        | 18.11               | 18.14        | 18.13        |
|                     | Subtest 3    | 19.00        | 17.45               | 17.46        | 17.48        |
|                     | Subtest 4    | 19.00        | 17.73               | 17.82        | 17.68        |
| HSUPA               | Subtest 1    | 19.00        | 17.93               | 17.45        | 17.50        |
|                     | Subtest 2    | 16.50        | 15.16               | 15.24        | 15.29        |
|                     | Subtest 3    | 17.50        | 16.45               | 16.58        | 16.52        |
|                     | Subtest 4    | 17.50        | 15.71               | 15.76        | 15.80        |
|                     | Subtest 5    | 19.00        | 18.24               | 18.26        | 18.28        |
| DC-HSDPA            | Subtest 1    | 19.50        | 18.42               | 18.43        | 18.44        |
|                     | Subtest 2    | 19.50        | 18.17               | 18.23        | 18.22        |
|                     | Subtest 3    | 19.00        | 17.51               | 17.56        | 17.55        |
|                     | Subtest 4    | 19.00        | 17.80               | 17.91        | 17.77        |

Table 25: Conducted power measurement results of UMTS Band V (Receiver on)

| UMTS850<br>(Band V) |              | Tune-up      | Average Power (dBm) |              |              |
|---------------------|--------------|--------------|---------------------|--------------|--------------|
|                     |              |              | 4132CH              | 4182CH       | 4233CH       |
| WCDMA               | 12.2kbps RMC | <b>24.00</b> | <b>22.86</b>        | <b>22.87</b> | <b>22.85</b> |
|                     | 12.2kbps AMR | 24.00        | 22.85               | 22.90        | 22.81        |
| HSDPA               | Subtest 1    | 23.00        | 21.85               | 21.86        | 21.85        |
|                     | Subtest 2    | 23.00        | 21.64               | 21.65        | 21.67        |
|                     | Subtest 3    | 22.50        | 20.96               | 21.01        | 21.00        |
|                     | Subtest 4    | 22.50        | 20.96               | 20.98        | 20.98        |
| HSUPA               | Subtest 1    | 22.50        | 21.04               | 21.18        | 21.12        |
|                     | Subtest 2    | 20.00        | 18.81               | 18.71        | 18.68        |
|                     | Subtest 3    | 21.00        | 19.17               | 19.19        | 19.14        |
|                     | Subtest 4    | 21.00        | 19.11               | 19.17        | 19.05        |
|                     | Subtest 5    | 22.50        | 21.79               | 21.76        | 21.76        |
| DC-HSDPA            | Subtest 1    | 23.00        | 21.91               | 21.92        | 21.94        |
|                     | Subtest 2    | 23.00        | 21.71               | 21.72        | 21.76        |
|                     | Subtest 3    | 22.50        | 21.02               | 21.11        | 21.07        |
|                     | Subtest 4    | 22.50        | 21.02               | 21.03        | 21.04        |

Table 26: Conducted power measurement results of UMTS Band V (Full power)

| UMTS850<br>(Band V) |              | Tune-up      | Average Power (dBm) |              |              |
|---------------------|--------------|--------------|---------------------|--------------|--------------|
|                     |              |              | 4132CH              | 4182CH       | 4233CH       |
| WCDMA               | 12.2kbps RMC | <b>18.00</b> | <b>16.87</b>        | <b>16.85</b> | <b>16.86</b> |
|                     | 12.2kbps AMR | 18.00        | 16.92               | 16.81        | 16.91        |
| HSDPA               | Subtest 1    | 17.00        | 15.84               | 15.86        | 15.87        |
|                     | Subtest 2    | 17.00        | 15.62               | 15.65        | 15.65        |
|                     | Subtest 3    | 16.50        | 15.13               | 15.29        | 15.19        |
|                     | Subtest 4    | 16.50        | 15.12               | 15.28        | 15.19        |
| HSUPA               | Subtest 1    | 16.50        | 15.06               | 15.85        | 15.03        |
|                     | Subtest 2    | 14.00        | 12.54               | 12.65        | 12.64        |
|                     | Subtest 3    | 15.00        | 13.37               | 13.58        | 13.45        |
|                     | Subtest 4    | 15.00        | 13.07               | 13.25        | 13.22        |
|                     | Subtest 5    | 16.50        | 15.76               | 15.80        | 15.82        |
| DC-HSDPA            | Subtest 1    | 17.00        | 15.93               | 15.93        | 15.92        |
|                     | Subtest 2    | 17.00        | 15.69               | 15.75        | 15.73        |
|                     | Subtest 3    | 16.50        | 15.20               | 15.34        | 15.30        |
|                     | Subtest 4    | 16.50        | 15.22               | 15.33        | 15.24        |

Table 27: Conducted power measurement results of UMTS Band V (Second antenna+WiFi antenna Simultaneous Transmission)

Note:

- 1) The conducted power of UMTS Band V is measured with RMS detector.
- 2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).
- 3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the Second mode.

### 7.1.6 Conducted power measurements of LTE Band II (Second Antenna)

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18607CH              | 18900CH | 19193CH |
| 1.4MHz      | QPSK       | 1       | 0         | 19.00   | 18.22                | 17.71   | 17.97   |
|             |            | 1       | 3         | 19.00   | 18.28                | 17.84   | 18.03   |
|             |            | 1       | 5         | 19.00   | 18.15                | 17.73   | 18.04   |
|             |            | 3       | 0         | 19.00   | 18.19                | 17.76   | 17.88   |
|             |            | 3       | 2         | 19.00   | 18.20                | 17.74   | 17.89   |
|             |            | 3       | 3         | 19.00   | 18.15                | 17.70   | 17.92   |
|             |            | 6       | 0         | 19.00   | 18.16                | 17.73   | 17.87   |
|             | 16QAM      | 1       | 0         | 19.40   | 18.22                | 17.60   | 18.02   |
|             |            | 1       | 3         | 19.40   | 18.27                | 17.76   | 17.81   |
|             |            | 1       | 5         | 19.40   | 17.90                | 17.66   | 18.12   |
|             |            | 3       | 0         | 19.40   | 18.22                | 17.87   | 17.92   |
|             |            | 3       | 2         | 19.40   | 18.12                | 17.87   | 17.97   |
|             |            | 3       | 3         | 19.40   | 18.19                | 17.80   | 17.91   |
|             |            | 6       | 0         | 19.40   | 18.15                | 17.76   | 17.88   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18615CH              | 18900CH | 19185CH |
| 3MHz        | QPSK       | 1       | 0         | 19.00   | 18.08                | 17.56   | 17.67   |
|             |            | 1       | 7         | 19.00   | 18.17                | 17.76   | 17.94   |
|             |            | 1       | 14        | 19.00   | 17.96                | 17.62   | 17.83   |
|             |            | 8       | 0         | 19.00   | 18.12                | 17.68   | 17.68   |
|             |            | 8       | 4         | 19.00   | 18.21                | 17.72   | 17.78   |
|             |            | 8       | 7         | 19.00   | 18.14                | 17.70   | 17.78   |
|             |            | 15      | 0         | 19.00   | 18.16                | 17.67   | 17.73   |
|             | 16QAM      | 1       | 0         | 19.40   | 17.95                | 17.48   | 17.83   |
|             |            | 1       | 7         | 19.40   | 18.24                | 17.74   | 18.10   |
|             |            | 1       | 14        | 19.40   | 17.92                | 17.60   | 18.08   |
|             |            | 8       | 0         | 19.40   | 18.15                | 17.67   | 17.62   |
|             |            | 8       | 4         | 19.40   | 18.17                | 17.71   | 17.71   |
|             |            | 8       | 7         | 19.40   | 18.11                | 17.69   | 17.71   |
|             |            | 15      | 0         | 19.40   | 18.09                | 17.68   | 17.72   |

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18625CH              | 18900CH | 19175CH |
| 5MHz        | QPSK       | 1       | 0         | 19.00   | 18.25                | 17.51   | 17.45   |
|             |            | 1       | 13        | 19.00   | 18.62                | 17.91   | 17.97   |
|             |            | 1       | 24        | 19.00   | 18.35                | 17.65   | 17.94   |
|             |            | 12      | 0         | 19.00   | 18.43                | 17.71   | 17.69   |
|             |            | 12      | 6         | 19.00   | 18.54                | 17.89   | 17.94   |
|             |            | 12      | 13        | 19.00   | 18.49                | 17.84   | 17.93   |
|             |            | 25      | 0         | 19.00   | 18.41                | 17.76   | 17.86   |
|             | 16QAM      | 1       | 0         | 19.40   | 18.48                | 17.96   | 17.83   |
|             |            | 1       | 13        | 19.40   | 18.80                | 18.38   | 18.36   |
|             |            | 1       | 24        | 19.40   | 18.54                | 18.12   | 18.27   |
|             |            | 12      | 0         | 19.40   | 18.41                | 17.78   | 17.65   |
|             |            | 12      | 6         | 19.40   | 18.54                | 17.99   | 17.91   |
|             |            | 12      | 13        | 19.40   | 18.46                | 17.92   | 17.94   |
|             |            | 25      | 0         | 19.40   | 18.41                | 17.81   | 17.82   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18650CH              | 18900CH | 19150CH |
| 10MHz       | QPSK       | 1       | 0         | 19.00   | 18.83                | 18.05   | 18.56   |
|             |            | 1       | 25        | 19.00   | 18.89                | 17.98   | 17.74   |
|             |            | 1       | 49        | 19.00   | 18.50                | 18.11   | 17.84   |
|             |            | 25      | 0         | 19.00   | 18.52                | 17.64   | 17.74   |
|             |            | 25      | 13        | 19.00   | 18.77                | 17.83   | 17.69   |
|             |            | 25      | 25        | 19.00   | 18.73                | 17.97   | 17.78   |
|             |            | 50      | 0         | 19.00   | 18.61                | 17.88   | 17.81   |
|             | 16QAM      | 1       | 0         | 19.40   | 18.89                | 18.30   | 18.59   |
|             |            | 1       | 25        | 19.40   | 18.91                | 18.23   | 17.76   |
|             |            | 1       | 49        | 19.40   | 18.59                | 18.50   | 17.87   |
|             |            | 25      | 0         | 19.40   | 18.45                | 17.65   | 17.66   |
|             |            | 25      | 13        | 19.40   | 18.74                | 17.84   | 17.61   |
|             |            | 25      | 25        | 19.40   | 18.66                | 17.97   | 17.71   |
|             |            | 50      | 0         | 19.40   | 18.55                | 17.84   | 17.72   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 18675CH      | 18900CH      | 19125CH      |
| 15MHz     | QPSK       | 1       | 0         | 19.00   | 18.03        | 17.13        | 18.46        |
|           |            | 1       | 38        | 19.00   | 18.95        | 17.93        | 17.81        |
|           |            | 1       | 74        | 19.00   | 17.97        | 18.06        | 17.46        |
|           |            | 36      | 0         | 19.00   | 18.56        | 17.59        | 18.22        |
|           |            | 36      | 18        | 19.00   | 18.82        | 17.96        | 17.83        |
|           |            | 36      | 39        | 19.00   | 18.46        | 18.11        | 17.52        |
|           |            | 75      | 0         | 19.00   | 18.50        | 17.74        | 17.94        |
|           | 16QAM      | 1       | 0         | 19.40   | 18.19        | 17.46        | 18.73        |
|           |            | 1       | 38        | 19.40   | 19.13        | 18.21        | 18.07        |
|           |            | 1       | 74        | 19.40   | 18.19        | 18.33        | 17.82        |
|           |            | 36      | 0         | 19.40   | 18.49        | 17.60        | 18.22        |
|           |            | 36      | 18        | 19.40   | 18.77        | 17.98        | 17.84        |
|           |            | 36      | 39        | 19.40   | 18.47        | 18.14        | 17.53        |
|           |            | 75      | 0         | 19.40   | 18.48        | 17.74        | 17.94        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 18700CH      | 18900CH      | 19100CH      |
| 20MHz     | QPSK       | 1       | 0         | 19.00   | 17.93        | 17.24        | 18.61        |
|           |            | 1       | 50        | 19.00   | <b>18.93</b> | 18.02        | 18.21        |
|           |            | 1       | 99        | 19.00   | 17.25        | 18.44        | 17.36        |
|           |            | 50      | 0         | 19.00   | 18.49        | 17.44        | <b>18.58</b> |
|           |            | 50      | 25        | 19.00   | <b>18.52</b> | 17.90        | 18.13        |
|           |            | 50      | 50        | 19.00   | 18.02        | <b>18.17</b> | 17.56        |
|           |            | 100     | 0         | 19.00   | 18.25        | 17.69        | 18.12        |
|           | 16QAM      | 1       | 0         | 19.40   | 18.29        | 17.47        | 19.06        |
|           |            | 1       | 50        | 19.40   | 19.33        | 18.22        | 18.71        |
|           |            | 1       | 99        | 19.40   | 17.63        | 18.64        | 17.90        |
|           |            | 50      | 0         | 19.40   | 18.42        | 17.42        | 18.58        |
|           |            | 50      | 25        | 19.40   | 18.46        | 17.88        | 18.13        |
|           |            | 50      | 50        | 19.40   | 17.99        | 18.15        | 17.56        |
|           |            | 100     | 0         | 19.40   | 18.22        | 17.67        | 18.05        |

Table 28: Conducted power measurement results of LTE Band II (Receiver on)

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18607CH              | 18900CH | 19193CH |
| 1.4MHz      | QPSK       | 1       | 0         | 23.40   | 22.48                | 22.03   | 22.44   |
|             |            | 1       | 3         | 23.40   | 22.53                | 22.11   | 22.48   |
|             |            | 1       | 5         | 23.40   | 22.40                | 22.13   | 22.41   |
|             |            | 3       | 0         | 23.40   | 22.46                | 22.11   | 22.37   |
|             |            | 3       | 2         | 23.40   | 22.48                | 22.10   | 22.43   |
|             |            | 3       | 3         | 23.40   | 22.44                | 22.04   | 22.38   |
|             |            | 6       | 0         | 22.50   | 21.56                | 21.03   | 21.48   |
|             | 16QAM      | 1       | 0         | 22.50   | 21.61                | 20.90   | 21.29   |
|             |            | 1       | 3         | 22.50   | 21.67                | 20.99   | 21.35   |
|             |            | 1       | 5         | 22.50   | 21.49                | 20.95   | 21.38   |
|             |            | 3       | 0         | 22.50   | 21.63                | 21.11   | 21.30   |
|             |            | 3       | 2         | 22.50   | 21.63                | 21.10   | 21.36   |
|             |            | 3       | 3         | 22.50   | 21.61                | 21.06   | 21.35   |
|             |            | 6       | 0         | 21.50   | 20.43                | 20.13   | 20.32   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18615CH              | 18900CH | 19185CH |
| 3MHz        | QPSK       | 1       | 0         | 23.40   | 22.46                | 21.92   | 22.08   |
|             |            | 1       | 7         | 23.40   | 22.61                | 22.14   | 22.31   |
|             |            | 1       | 14        | 23.40   | 22.49                | 21.99   | 22.27   |
|             |            | 8       | 0         | 22.50   | 21.59                | 21.11   | 21.28   |
|             |            | 8       | 4         | 22.50   | 21.61                | 21.11   | 21.41   |
|             |            | 8       | 7         | 22.50   | 21.55                | 21.14   | 21.25   |
|             |            | 15      | 0         | 22.50   | 21.57                | 21.02   | 21.30   |
|             | 16QAM      | 1       | 0         | 22.50   | 21.34                | 20.70   | 21.11   |
|             |            | 1       | 7         | 22.50   | 21.46                | 20.98   | 21.42   |
|             |            | 1       | 14        | 22.50   | 21.41                | 20.80   | 21.33   |
|             |            | 8       | 0         | 21.50   | 20.53                | 20.00   | 20.12   |
|             |            | 8       | 4         | 21.50   | 20.50                | 20.06   | 20.22   |
|             |            | 8       | 7         | 21.50   | 20.45                | 20.04   | 20.23   |
|             |            | 15      | 0         | 21.50   | 20.55                | 20.04   | 20.15   |

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18625CH              | 18900CH | 19175CH |
| 5MHz        | QPSK       | 1       | 0         | 23.40   | 22.49                | 21.84   | 21.71   |
|             |            | 1       | 13        | 23.40   | 22.81                | 22.23   | 22.30   |
|             |            | 1       | 24        | 23.40   | 22.57                | 21.97   | 22.24   |
|             |            | 12      | 0         | 22.50   | 21.77                | 20.97   | 20.90   |
|             |            | 12      | 6         | 22.50   | 21.88                | 21.16   | 21.16   |
|             |            | 12      | 13        | 22.50   | 21.83                | 21.12   | 21.18   |
|             |            | 25      | 0         | 22.50   | 21.76                | 21.04   | 21.08   |
|             | 16QAM      | 1       | 0         | 22.50   | 21.55                | 21.04   | 20.93   |
|             |            | 1       | 13        | 22.50   | 21.89                | 21.40   | 21.56   |
|             |            | 1       | 24        | 22.50   | 21.66                | 21.15   | 21.49   |
|             |            | 12      | 0         | 21.50   | 20.77                | 19.98   | 19.96   |
|             |            | 12      | 6         | 21.50   | 20.89                | 20.19   | 20.17   |
|             |            | 12      | 13        | 21.50   | 20.84                | 20.13   | 20.19   |
|             |            | 25      | 0         | 21.50   | 20.66                | 20.04   | 20.09   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18650CH              | 18900CH | 19150CH |
| 10MHz       | QPSK       | 1       | 0         | 23.40   | 23.37                | 22.35   | 22.70   |
|             |            | 1       | 25        | 23.40   | 23.10                | 22.25   | 21.92   |
|             |            | 1       | 49        | 23.40   | 22.81                | 22.41   | 22.22   |
|             |            | 25      | 0         | 22.50   | 21.83                | 20.89   | 20.85   |
|             |            | 25      | 13        | 22.50   | 22.08                | 21.09   | 20.87   |
|             |            | 25      | 25        | 22.50   | 21.98                | 21.24   | 21.00   |
|             |            | 50      | 0         | 22.50   | 21.88                | 21.16   | 21.01   |
|             | 16QAM      | 1       | 0         | 22.50   | 22.35                | 21.38   | 21.85   |
|             |            | 1       | 25        | 22.50   | 22.32                | 21.28   | 21.03   |
|             |            | 1       | 49        | 22.50   | 21.95                | 21.42   | 21.31   |
|             |            | 25      | 0         | 21.50   | 20.72                | 19.89   | 19.89   |
|             |            | 25      | 13        | 21.50   | 20.96                | 20.10   | 19.85   |
|             |            | 25      | 25        | 21.50   | 20.86                | 20.23   | 19.98   |
|             |            | 50      | 0         | 21.50   | 20.78                | 20.10   | 19.98   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|-----------|------------|---------|-----------|---------|--------------|---------|---------|
|           |            |         |           |         | 18675CH      | 18900CH | 19125CH |
| 15MHz     | QPSK       | 1       | 0         | 23.40   | 22.28        | 21.49   | 22.60   |
|           |            | 1       | 38        | 23.40   | 23.13        | 22.26   | 21.99   |
|           |            | 1       | 74        | 23.40   | 22.16        | 22.42   | 21.97   |
|           |            | 36      | 0         | 22.50   | 21.87        | 20.84   | 21.37   |
|           |            | 36      | 18        | 22.50   | 22.11        | 21.21   | 21.01   |
|           |            | 36      | 39        | 22.50   | 21.72        | 21.38   | 20.81   |
|           |            | 75      | 0         | 22.50   | 21.77        | 21.01   | 21.19   |
|           | 16QAM      | 1       | 0         | 22.50   | 21.49        | 20.68   | 21.67   |
|           |            | 1       | 38        | 22.50   | 22.39        | 21.40   | 20.98   |
|           |            | 1       | 74        | 22.50   | 21.38        | 21.57   | 20.79   |
|           |            | 36      | 0         | 21.50   | 20.80        | 19.85   | 20.39   |
|           |            | 36      | 18        | 21.50   | 21.04        | 20.23   | 20.04   |
|           |            | 36      | 39        | 21.50   | 20.72        | 20.39   | 19.82   |
|           |            | 75      | 0         | 21.50   | 20.76        | 20.00   | 20.20   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|           |            |         |           |         | 18700CH      | 18900CH | 19100CH |
| 20MHz     | QPSK       | 1       | 0         | 23.00   | 21.79        | 21.40   | 22.38   |
|           |            | 1       | 50        | 23.00   | <b>22.39</b> | 21.53   | 22.14   |
|           |            | 1       | 99        | 23.00   | 21.30        | 21.71   | 21.13   |
|           |            | 50      | 0         | 22.50   | 21.90        | 21.26   | 21.80   |
|           |            | 50      | 25        | 22.50   | <b>21.92</b> | 21.62   | 21.34   |
|           |            | 50      | 50        | 22.50   | 21.45        | 21.45   | 21.75   |
|           |            | 100     | 0         | 22.50   | 21.58        | 21.39   | 21.35   |
|           | 16QAM      | 1       | 0         | 22.50   | 21.62        | 20.76   | 22.00   |
|           |            | 1       | 50        | 22.50   | 22.41        | 21.46   | 21.57   |
|           |            | 1       | 99        | 22.50   | 20.76        | 22.02   | 21.09   |
|           |            | 50      | 0         | 21.00   | 20.78        | 19.63   | 20.76   |
|           |            | 50      | 25        | 21.00   | 20.81        | 20.15   | 20.33   |
|           |            | 50      | 50        | 21.00   | 20.28        | 20.42   | 19.85   |
|           |            | 100     | 0         | 21.00   | 20.55        | 19.97   | 20.34   |

Table 29: Conducted power measurement results of LTE Band II (Full power)

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18607CH              | 18900CH | 19193CH |
| 1.4MHz      | QPSK       | 1       | 0         | 17.00   | 15.75                | 15.19   | 15.25   |
|             |            | 1       | 3         | 17.00   | 15.94                | 15.33   | 15.46   |
|             |            | 1       | 5         | 17.00   | 15.84                | 15.21   | 15.46   |
|             |            | 3       | 0         | 17.00   | 15.84                | 15.20   | 15.32   |
|             |            | 3       | 2         | 17.00   | 15.94                | 15.28   | 15.45   |
|             |            | 3       | 3         | 17.00   | 15.90                | 15.22   | 15.49   |
|             |            | 6       | 0         | 17.00   | 15.89                | 15.23   | 15.41   |
|             | 16QAM      | 1       | 0         | 17.00   | 15.92                | 15.48   | 15.34   |
|             |            | 1       | 3         | 17.00   | 16.10                | 15.59   | 15.60   |
|             |            | 1       | 5         | 17.00   | 16.01                | 15.49   | 15.57   |
|             |            | 3       | 0         | 17.00   | 15.97                | 15.31   | 15.56   |
|             |            | 3       | 2         | 17.00   | 16.01                | 15.39   | 15.62   |
|             |            | 3       | 3         | 17.00   | 15.97                | 15.37   | 15.68   |
|             |            | 6       | 0         | 17.00   | 15.89                | 15.18   | 15.44   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18615CH              | 18900CH | 19185CH |
| 3MHz        | QPSK       | 1       | 0         | 17.00   | 15.64                | 15.04   | 15.22   |
|             |            | 1       | 7         | 17.00   | 16.07                | 15.40   | 15.35   |
|             |            | 1       | 14        | 17.00   | 15.82                | 15.15   | 15.37   |
|             |            | 8       | 0         | 17.00   | 15.87                | 15.08   | 15.05   |
|             |            | 8       | 4         | 17.00   | 15.97                | 15.24   | 15.26   |
|             |            | 8       | 7         | 17.00   | 15.94                | 15.23   | 15.31   |
|             |            | 15      | 0         | 17.00   | 15.91                | 15.18   | 15.20   |
|             | 16QAM      | 1       | 0         | 17.00   | 15.88                | 15.24   | 15.73   |
|             |            | 1       | 7         | 17.00   | 16.34                | 15.44   | 15.26   |
|             |            | 1       | 14        | 17.00   | 16.12                | 15.21   | 15.23   |
|             |            | 8       | 0         | 17.00   | 15.88                | 15.02   | 15.48   |
|             |            | 8       | 4         | 17.00   | 15.99                | 15.19   | 15.22   |
|             |            | 8       | 7         | 17.00   | 15.96                | 15.17   | 15.27   |
|             |            | 15      | 0         | 17.00   | 15.92                | 15.14   | 15.12   |

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18625CH              | 18900CH | 19175CH |
| 5MHz        | QPSK       | 1       | 0         | 17.00   | 15.87                | 15.11   | 15.10   |
|             |            | 1       | 13        | 17.00   | 16.35                | 15.56   | 15.63   |
|             |            | 1       | 24        | 17.00   | 16.03                | 15.27   | 15.46   |
|             |            | 12      | 0         | 17.00   | 16.11                | 15.32   | 15.33   |
|             |            | 12      | 6         | 17.00   | 16.23                | 15.52   | 15.58   |
|             |            | 12      | 13        | 17.00   | 16.17                | 15.47   | 15.54   |
|             |            | 25      | 0         | 17.00   | 16.08                | 15.38   | 15.48   |
|             | 16QAM      | 1       | 0         | 17.00   | 16.16                | 15.52   | 15.38   |
|             |            | 1       | 13        | 17.00   | 16.54                | 16.02   | 15.94   |
|             |            | 1       | 24        | 17.00   | 16.20                | 15.70   | 15.80   |
|             |            | 12      | 0         | 17.00   | 16.10                | 15.34   | 15.32   |
|             |            | 12      | 6         | 17.00   | 16.22                | 15.58   | 15.56   |
|             |            | 12      | 13        | 17.00   | 16.14                | 15.50   | 15.54   |
|             |            | 25      | 0         | 17.00   | 16.01                | 15.35   | 15.48   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18650CH              | 18900CH | 19150CH |
| 10MHz       | QPSK       | 1       | 0         | 17.00   | 16.52                | 15.71   | 16.17   |
|             |            | 1       | 25        | 17.00   | 16.58                | 15.63   | 15.38   |
|             |            | 1       | 49        | 17.00   | 16.22                | 15.67   | 15.39   |
|             |            | 25      | 0         | 17.00   | 16.16                | 15.23   | 15.29   |
|             |            | 25      | 13        | 17.00   | 16.43                | 15.45   | 15.32   |
|             |            | 25      | 25        | 17.00   | 16.38                | 15.57   | 15.37   |
|             |            | 50      | 0         | 17.00   | 16.25                | 15.49   | 15.42   |
|             | 16QAM      | 1       | 0         | 17.00   | 16.79                | 15.99   | 16.45   |
|             |            | 1       | 25        | 17.00   | 16.75                | 15.94   | 15.65   |
|             |            | 1       | 49        | 17.00   | 16.53                | 16.01   | 15.71   |
|             |            | 25      | 0         | 17.00   | 16.12                | 15.26   | 15.26   |
|             |            | 25      | 13        | 17.00   | 16.39                | 15.48   | 15.28   |
|             |            | 25      | 25        | 17.00   | 16.28                | 15.61   | 15.35   |
|             |            | 50      | 0         | 17.00   | 16.14                | 15.48   | 15.42   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|-----------|------------|---------|-----------|---------|--------------|---------|---------|
|           |            |         |           |         | 18675CH      | 18900CH | 19125CH |
| 15MHz     | QPSK       | 1       | 0         | 16.70   | 15.56        | 14.76   | 16.01   |
|           |            | 1       | 38        | 16.70   | 16.62        | 15.58   | 15.48   |
|           |            | 1       | 74        | 16.70   | 15.39        | 15.55   | 15.07   |
|           |            | 36      | 0         | 16.70   | 16.15        | 15.13   | 15.82   |
|           |            | 36      | 18        | 16.70   | 16.48        | 15.42   | 15.42   |
|           |            | 36      | 39        | 16.70   | 16.11        | 15.67   | 15.17   |
|           |            | 75      | 0         | 16.70   | 16.15        | 15.29   | 15.62   |
|           | 16QAM      | 1       | 0         | 17.10   | 15.87        | 15.30   | 16.33   |
|           |            | 1       | 38        | 17.10   | 16.95        | 15.85   | 15.79   |
|           |            | 1       | 74        | 17.10   | 15.81        | 15.83   | 15.38   |
|           |            | 36      | 0         | 16.50   | 16.16        | 15.16   | 15.80   |
|           |            | 36      | 18        | 16.50   | 16.44        | 15.45   | 15.40   |
|           |            | 36      | 39        | 16.50   | 16.14        | 15.71   | 15.17   |
|           |            | 75      | 0         | 16.50   | 16.15        | 15.34   | 15.65   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|           |            |         |           |         | 18700CH      | 18900CH | 19100CH |
| 20MHz     | QPSK       | 1       | 0         | 16.70   | 15.53        | 14.73   | 16.06   |
|           |            | 1       | 50        | 16.70   | <b>16.66</b> | 15.54   | 15.83   |
|           |            | 1       | 99        | 16.70   | 14.72        | 15.84   | 14.87   |
|           |            | 50      | 0         | 16.70   | 16.13        | 15.04   | 16.16   |
|           |            | 50      | 25        | 16.70   | <b>16.19</b> | 15.48   | 15.75   |
|           |            | 50      | 50        | 16.70   | 15.58        | 15.77   | 15.21   |
|           |            | 100     | 0         | 16.70   | 15.89        | 15.30   | 15.76   |
|           | 16QAM      | 1       | 0         | 17.10   | 15.87        | 15.21   | 16.47   |
|           |            | 1       | 50        | 17.10   | 17.10        | 16.03   | 16.17   |
|           |            | 1       | 99        | 17.10   | 15.19        | 16.30   | 15.24   |
|           |            | 50      | 0         | 16.50   | 16.07        | 14.98   | 16.16   |
|           |            | 50      | 25        | 16.50   | 16.19        | 15.48   | 15.76   |
|           |            | 50      | 50        | 16.50   | 15.59        | 15.73   | 15.24   |
|           |            | 100     | 0         | 16.50   | 15.90        | 15.22   | 15.73   |

Table 30: Conducted power measurement results of LTE Band II (Second antenna+WiFi antenna Simultaneous Transmission)

### 7.1.7 Conducted power measurements of LTE Band IV (Second Antenna)

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19957CH              | 20175CH | 20393CH |
| 1.4MHz      | QPSK       | 1       | 0         | 21.50   | 19.60                | 19.87   | 20.47   |
|             |            | 1       | 3         | 21.50   | 19.56                | 19.90   | 20.46   |
|             |            | 1       | 5         | 21.50   | 19.57                | 19.70   | 20.38   |
|             |            | 3       | 0         | 21.50   | 19.56                | 19.83   | 20.41   |
|             |            | 3       | 2         | 21.50   | 19.58                | 19.80   | 20.39   |
|             |            | 3       | 3         | 21.50   | 19.54                | 19.75   | 20.35   |
|             |            | 6       | 0         | 21.50   | 19.58                | 19.78   | 20.37   |
|             | 16QAM      | 1       | 0         | 21.50   | 19.53                | 19.83   | 20.44   |
|             |            | 1       | 3         | 21.50   | 19.58                | 20.04   | 20.49   |
|             |            | 1       | 5         | 21.50   | 19.59                | 19.72   | 20.35   |
|             |            | 3       | 0         | 21.50   | 19.64                | 19.91   | 20.38   |
|             |            | 3       | 2         | 21.50   | 19.65                | 19.84   | 20.36   |
|             |            | 3       | 3         | 21.50   | 19.62                | 19.83   | 20.32   |
|             |            | 6       | 0         | 21.50   | 19.63                | 19.75   | 20.40   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
| 3MHz        | QPSK       | 1       | 0         | 21.50   | 19.55                | 19.70   | 20.37   |
|             |            | 1       | 7         | 21.50   | 19.69                | 19.86   | 20.42   |
|             |            | 1       | 14        | 21.50   | 19.62                | 19.54   | 20.12   |
|             |            | 8       | 0         | 21.50   | 19.56                | 19.84   | 20.44   |
|             |            | 8       | 4         | 21.50   | 19.64                | 19.78   | 20.44   |
|             |            | 8       | 7         | 21.50   | 19.65                | 19.68   | 20.33   |
|             |            | 15      | 0         | 21.50   | 19.63                | 19.77   | 20.40   |
|             | 16QAM      | 1       | 0         | 21.50   | 19.54                | 19.75   | 20.44   |
|             |            | 1       | 7         | 21.50   | 19.73                | 19.68   | 20.58   |
|             |            | 1       | 14        | 21.50   | 19.56                | 19.59   | 20.17   |
|             |            | 8       | 0         | 21.50   | 19.55                | 19.76   | 20.37   |
|             |            | 8       | 4         | 21.50   | 19.58                | 19.75   | 20.39   |
|             |            | 8       | 7         | 21.50   | 19.60                | 19.64   | 20.27   |
|             |            | 15      | 0         | 21.50   | 19.61                | 19.72   | 20.37   |

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19975CH              | 20175CH | 20375CH |
| 5MHz        | QPSK       | 1       | 0         | 21.50   | 19.68                | 19.99   | 20.40   |
|             |            | 1       | 13        | 21.50   | 20.10                | 20.16   | 20.73   |
|             |            | 1       | 24        | 21.50   | 19.83                | 19.64   | 20.25   |
|             |            | 12      | 0         | 21.50   | 19.86                | 20.16   | 20.59   |
|             |            | 12      | 6         | 21.50   | 19.99                | 20.17   | 20.67   |
|             |            | 12      | 13        | 21.50   | 19.95                | 19.95   | 20.49   |
|             |            | 25      | 0         | 21.50   | 19.88                | 20.09   | 20.60   |
|             | 16QAM      | 1       | 0         | 21.50   | 19.90                | 20.28   | 20.78   |
|             |            | 1       | 13        | 21.50   | 20.34                | 20.44   | 20.97   |
|             |            | 1       | 24        | 21.50   | 20.07                | 19.88   | 20.55   |
|             |            | 12      | 0         | 21.50   | 19.89                | 20.17   | 20.53   |
|             |            | 12      | 6         | 21.50   | 20.06                | 20.16   | 20.62   |
|             |            | 12      | 13        | 21.50   | 20.02                | 19.93   | 20.35   |
|             |            | 25      | 0         | 21.50   | 19.90                | 19.97   | 20.48   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 20000CH              | 20175CH | 20350CH |
| 10MHz       | QPSK       | 1       | 0         | 21.50   | 20.17                | 20.51   | 20.53   |
|             |            | 1       | 25        | 21.50   | 20.30                | 20.22   | 20.65   |
|             |            | 1       | 49        | 21.50   | 20.54                | 20.35   | 20.69   |
|             |            | 25      | 0         | 21.50   | 19.95                | 20.19   | 20.35   |
|             |            | 25      | 13        | 21.50   | 20.18                | 20.09   | 20.47   |
|             |            | 25      | 25        | 21.50   | 20.20                | 19.94   | 20.44   |
|             |            | 50      | 0         | 21.50   | 20.14                | 20.02   | 20.44   |
|             | 16QAM      | 1       | 0         | 21.50   | 20.45                | 20.73   | 20.60   |
|             |            | 1       | 25        | 21.50   | 20.51                | 20.50   | 20.71   |
|             |            | 1       | 49        | 21.50   | 20.72                | 20.62   | 20.72   |
|             |            | 25      | 0         | 21.50   | 19.87                | 20.04   | 20.33   |
|             |            | 25      | 13        | 21.50   | 20.10                | 20.01   | 20.46   |
|             |            | 25      | 25        | 21.50   | 20.12                | 19.81   | 20.40   |
|             |            | 50      | 0         | 21.50   | 20.10                | 19.89   | 20.34   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 20025CH      | 20175CH      | 20325CH      |
| 15MHz     | QPSK       | 1       | 0         | 21.50   | 19.57        | 20.28        | 20.11        |
|           |            | 1       | 38        | 21.50   | 20.41        | 20.22        | 20.56        |
|           |            | 1       | 74        | 21.50   | 20.12        | 19.99        | 20.39        |
|           |            | 36      | 0         | 21.50   | 20.10        | 20.22        | 20.33        |
|           |            | 36      | 18        | 21.50   | 20.32        | 20.25        | 20.53        |
|           |            | 36      | 39        | 21.50   | 20.33        | 20.05        | 20.57        |
|           |            | 75      | 0         | 21.50   | 20.27        | 20.08        | 20.40        |
|           | 16QAM      | 1       | 0         | 21.50   | 19.91        | 20.49        | 20.15        |
|           |            | 1       | 38        | 21.50   | 20.79        | 20.48        | 20.60        |
|           |            | 1       | 74        | 21.50   | 20.45        | 20.24        | 20.39        |
|           |            | 36      | 0         | 21.50   | 20.08        | 20.21        | 20.23        |
|           |            | 36      | 18        | 21.50   | 20.25        | 20.19        | 20.42        |
|           |            | 36      | 39        | 21.50   | 20.31        | 20.00        | 20.46        |
|           |            | 75      | 0         | 21.50   | 20.23        | 19.99        | 20.34        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 20050CH      | 20175CH      | 20300CH      |
| 20MHz     | QPSK       | 1       | 0         | 21.00   | 19.90        | <b>20.40</b> | 20.12        |
|           |            | 1       | 50        | 21.00   | <b>20.57</b> | 20.25        | <b>20.48</b> |
|           |            | 1       | 99        | 21.00   | 20.12        | 19.96        | 20.38        |
|           |            | 50      | 0         | 21.00   | 20.15        | <b>20.21</b> | 20.14        |
|           |            | 50      | 25        | 21.00   | <b>20.33</b> | 20.04        | 20.30        |
|           |            | 50      | 50        | 21.00   | 20.28        | 20.20        | <b>20.39</b> |
|           |            | 100     | 0         | 21.00   | 20.24        | 20.11        | <b>20.29</b> |
|           | 16QAM      | 1       | 0         | 21.00   | 20.26        | 20.67        | 20.27        |
|           |            | 1       | 50        | 21.00   | 20.94        | 20.49        | 20.60        |
|           |            | 1       | 99        | 21.00   | 20.44        | 20.32        | 20.46        |
|           |            | 50      | 0         | 21.00   | 20.06        | 20.13        | 20.12        |
|           |            | 50      | 25        | 21.00   | 20.32        | 19.98        | 20.24        |
|           |            | 50      | 50        | 21.00   | 20.20        | 19.86        | 20.37        |
|           |            | 100     | 0         | 21.00   | 20.17        | 20.07        | 20.25        |

Table 31: Conducted power measurement results of LTE Band IV (Receiver on)

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19957CH              | 20175CH | 20393CH |
| 1.4MHz      | QPSK       | 1       | 0         | 23.50   | 21.95                | 22.11   | 22.49   |
|             |            | 1       | 3         | 23.50   | 22.00                | 22.11   | 22.36   |
|             |            | 1       | 5         | 23.50   | 21.94                | 22.00   | 22.27   |
|             |            | 3       | 0         | 23.50   | 21.95                | 22.05   | 22.38   |
|             |            | 3       | 2         | 23.50   | 21.92                | 22.05   | 22.40   |
|             |            | 3       | 3         | 23.50   | 21.89                | 22.02   | 22.28   |
|             |            | 6       | 0         | 22.50   | 21.04                | 21.23   | 21.52   |
|             | 16QAM      | 1       | 0         | 22.50   | 21.13                | 21.41   | 21.64   |
|             |            | 1       | 3         | 22.50   | 21.21                | 21.43   | 21.62   |
|             |            | 1       | 5         | 22.50   | 21.14                | 20.90   | 21.53   |
|             |            | 3       | 0         | 22.50   | 21.27                | 21.23   | 21.66   |
|             |            | 3       | 2         | 22.50   | 21.01                | 21.23   | 21.64   |
|             |            | 3       | 3         | 22.50   | 20.99                | 21.21   | 21.61   |
|             |            | 6       | 0         | 21.50   | 20.17                | 20.25   | 20.67   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19965CH              | 20175CH | 20385CH |
| 3MHz        | QPSK       | 1       | 0         | 23.50   | 21.88                | 22.08   | 22.48   |
|             |            | 1       | 7         | 23.50   | 22.09                | 22.12   | 22.38   |
|             |            | 1       | 14        | 23.50   | 21.94                | 21.79   | 22.12   |
|             |            | 8       | 0         | 22.50   | 21.03                | 21.26   | 21.64   |
|             |            | 8       | 4         | 22.50   | 21.13                | 21.24   | 21.58   |
|             |            | 8       | 7         | 22.50   | 21.15                | 21.13   | 21.50   |
|             |            | 15      | 0         | 22.50   | 21.13                | 21.18   | 21.54   |
|             | 16QAM      | 1       | 0         | 22.50   | 21.11                | 21.27   | 21.63   |
|             |            | 1       | 7         | 22.50   | 21.32                | 21.33   | 21.64   |
|             |            | 1       | 14        | 22.50   | 21.03                | 21.01   | 21.33   |
|             |            | 8       | 0         | 21.50   | 20.29                | 20.14   | 20.81   |
|             |            | 8       | 4         | 21.50   | 20.36                | 20.10   | 20.81   |
|             |            | 8       | 7         | 21.50   | 20.35                | 19.99   | 20.64   |
|             |            | 15      | 0         | 21.50   | 20.34                | 20.13   | 20.78   |

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19975CH              | 20175CH | 20375CH |
| 5MHz        | QPSK       | 1       | 0         | 23.50   | 22.03                | 22.31   | 22.40   |
|             |            | 1       | 13        | 23.50   | 22.45                | 22.41   | 22.64   |
|             |            | 1       | 24        | 23.50   | 22.19                | 21.86   | 22.19   |
|             |            | 12      | 0         | 22.50   | 21.32                | 21.58   | 21.79   |
|             |            | 12      | 6         | 22.50   | 21.47                | 21.52   | 21.80   |
|             |            | 12      | 13        | 22.50   | 21.44                | 21.29   | 21.60   |
|             |            | 25      | 0         | 22.50   | 21.32                | 21.45   | 21.74   |
|             | 16QAM      | 1       | 0         | 22.50   | 21.33                | 21.72   | 21.84   |
|             |            | 1       | 13        | 22.50   | 21.75                | 21.83   | 22.11   |
|             |            | 1       | 24        | 22.50   | 21.55                | 21.29   | 21.61   |
|             |            | 12      | 0         | 21.50   | 20.54                | 20.52   | 20.94   |
|             |            | 12      | 6         | 21.50   | 20.70                | 20.56   | 20.94   |
|             |            | 12      | 13        | 21.50   | 20.61                | 20.35   | 20.74   |
|             |            | 25      | 0         | 21.50   | 20.51                | 20.37   | 20.92   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 20000CH              | 20175CH | 20350CH |
| 10MHz       | QPSK       | 1       | 0         | 23.50   | 22.29                | 22.76   | 22.65   |
|             |            | 1       | 25        | 23.50   | 22.63                | 22.43   | 22.69   |
|             |            | 1       | 49        | 23.50   | 22.81                | 22.44   | 22.59   |
|             |            | 25      | 0         | 22.50   | 21.41                | 21.58   | 21.60   |
|             |            | 25      | 13        | 22.50   | 21.59                | 21.46   | 21.67   |
|             |            | 25      | 25        | 22.50   | 21.67                | 21.31   | 21.62   |
|             |            | 50      | 0         | 22.50   | 21.61                | 21.40   | 21.58   |
|             | 16QAM      | 1       | 0         | 22.50   | 21.67                | 22.29   | 21.81   |
|             |            | 1       | 25        | 22.50   | 21.94                | 21.90   | 21.93   |
|             |            | 1       | 49        | 22.50   | 22.21                | 21.93   | 21.84   |
|             |            | 25      | 0         | 21.50   | 20.53                | 20.45   | 20.71   |
|             |            | 25      | 13        | 21.50   | 20.50                | 20.43   | 20.83   |
|             |            | 25      | 25        | 21.50   | 20.58                | 20.47   | 20.79   |
|             |            | 50      | 0         | 21.50   | 20.48                | 20.29   | 20.74   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|-----------|------------|---------|-----------|---------|--------------|---------|---------|
|           |            |         |           |         | 20025CH      | 20175CH | 20325CH |
| 15MHz     | QPSK       | 1       | 0         | 23.50   | 21.98        | 22.45   | 21.93   |
|           |            | 1       | 38        | 23.50   | 22.81        | 22.40   | 22.62   |
|           |            | 1       | 74        | 23.50   | 22.49        | 21.93   | 22.34   |
|           |            | 36      | 0         | 22.50   | 21.56        | 21.69   | 21.47   |
|           |            | 36      | 18        | 22.50   | 21.79        | 21.71   | 21.72   |
|           |            | 36      | 39        | 22.50   | 21.85        | 21.43   | 21.75   |
|           |            | 75      | 0         | 22.50   | 21.78        | 21.49   | 21.65   |
|           | 16QAM      | 1       | 0         | 22.50   | 21.35        | 21.86   | 21.23   |
|           |            | 1       | 38        | 22.50   | 22.22        | 21.76   | 21.85   |
|           |            | 1       | 74        | 22.50   | 21.98        | 21.35   | 21.55   |
|           |            | 36      | 0         | 21.50   | 20.44        | 20.62   | 20.60   |
|           |            | 36      | 18        | 21.50   | 20.68        | 20.62   | 20.75   |
|           |            | 36      | 39        | 21.50   | 20.73        | 20.60   | 20.84   |
|           |            | 75      | 0         | 21.50   | 20.67        | 20.37   | 20.71   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|           |            |         |           |         | 20050CH      | 20175CH | 20300CH |
| 20MHz     | QPSK       | 1       | 0         | 23.00   | 21.21        | 21.71   | 21.26   |
|           |            | 1       | 50        | 23.00   | <b>22.94</b> | 22.44   | 22.52   |
|           |            | 1       | 99        | 23.00   | 22.31        | 21.90   | 22.29   |
|           |            | 50      | 0         | 22.50   | 21.61        | 21.69   | 21.33   |
|           |            | 50      | 25        | 22.50   | <b>21.88</b> | 21.47   | 21.48   |
|           |            | 50      | 50        | 22.50   | 21.77        | 21.41   | 21.58   |
|           |            | 100     | 0         | 22.50   | 21.71        | 21.60   | 21.54   |
|           | 16QAM      | 1       | 0         | 22.50   | 21.44        | 22.13   | 21.59   |
|           |            | 1       | 50        | 22.50   | 22.21        | 22.07   | 22.00   |
|           |            | 1       | 99        | 22.50   | 21.65        | 21.51   | 21.79   |
|           |            | 50      | 0         | 21.50   | 20.48        | 20.61   | 20.49   |
|           |            | 50      | 25        | 21.50   | 20.70        | 20.38   | 20.59   |
|           |            | 50      | 50        | 21.50   | 20.65        | 20.52   | 20.75   |
|           |            | 100     | 0         | 21.50   | 20.60        | 20.47   | 20.60   |

Table 32: Conducted power measurement results of LTE Band IV (Full power)

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19957CH              | 20175CH | 20393CH |
| 1.4MHz      | QPSK       | 1       | 0         | 18.00   | 16.19                | 16.63   | 17.43   |
|             |            | 1       | 3         | 18.00   | 16.29                | 16.62   | 17.41   |
|             |            | 1       | 5         | 18.00   | 16.28                | 16.47   | 17.29   |
|             |            | 3       | 0         | 18.00   | 16.21                | 16.60   | 17.40   |
|             |            | 3       | 2         | 18.00   | 16.26                | 16.58   | 17.39   |
|             |            | 3       | 3         | 18.00   | 16.24                | 16.55   | 17.34   |
|             |            | 6       | 0         | 18.00   | 16.22                | 16.55   | 17.37   |
|             | 16QAM      | 1       | 0         | 18.00   | 16.26                | 16.84   | 17.51   |
|             |            | 1       | 3         | 18.00   | 16.39                | 16.84   | 17.54   |
|             |            | 1       | 5         | 18.00   | 16.34                | 16.69   | 17.45   |
|             |            | 3       | 0         | 18.00   | 16.27                | 16.60   | 17.43   |
|             |            | 3       | 2         | 18.00   | 16.31                | 16.57   | 17.41   |
|             |            | 3       | 3         | 18.00   | 16.34                | 16.52   | 17.37   |
|             |            | 6       | 0         | 18.00   | 16.27                | 16.51   | 17.31   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19965CH              | 20175CH | 20385CH |
| 3MHz        | QPSK       | 1       | 0         | 18.00   | 16.08                | 16.55   | 17.32   |
|             |            | 1       | 7         | 18.00   | 16.47                | 16.67   | 17.52   |
|             |            | 1       | 14        | 18.00   | 16.31                | 16.19   | 17.21   |
|             |            | 8       | 0         | 18.00   | 16.26                | 16.56   | 17.39   |
|             |            | 8       | 4         | 18.00   | 16.35                | 16.53   | 17.34   |
|             |            | 8       | 7         | 18.00   | 16.35                | 16.43   | 17.29   |
|             |            | 15      | 0         | 18.00   | 16.35                | 16.50   | 17.28   |
|             | 16QAM      | 1       | 0         | 18.00   | 16.31                | 16.71   | 17.34   |
|             |            | 1       | 7         | 18.00   | 16.72                | 16.83   | 17.55   |
|             |            | 1       | 14        | 18.00   | 16.55                | 16.32   | 17.26   |
|             |            | 8       | 0         | 18.00   | 16.23                | 16.52   | 17.29   |
|             |            | 8       | 4         | 18.00   | 16.34                | 16.48   | 17.24   |
|             |            | 8       | 7         | 18.00   | 16.33                | 16.39   | 17.20   |
|             |            | 15      | 0         | 18.00   | 16.27                | 16.45   | 17.16   |

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19975CH              | 20175CH | 20375CH |
| 5MHz        | QPSK       | 1       | 0         | 18.00   | 16.59                | 17.00   | 17.14   |
|             |            | 1       | 13        | 18.00   | 17.09                | 17.19   | 17.42   |
|             |            | 1       | 24        | 18.00   | 16.87                | 16.57   | 16.93   |
|             |            | 12      | 0         | 18.00   | 16.83                | 17.18   | 17.29   |
|             |            | 12      | 6         | 18.00   | 17.01                | 17.13   | 17.33   |
|             |            | 12      | 13        | 18.00   | 16.95                | 16.90   | 17.12   |
|             |            | 25      | 0         | 18.00   | 16.90                | 17.04   | 17.22   |
|             | 16QAM      | 1       | 0         | 18.00   | 16.71                | 17.31   | 17.29   |
|             |            | 1       | 13        | 18.00   | 17.19                | 17.48   | 17.56   |
|             |            | 1       | 24        | 18.00   | 16.97                | 16.85   | 17.13   |
|             |            | 12      | 0         | 18.00   | 16.82                | 17.21   | 17.35   |
|             |            | 12      | 6         | 18.00   | 17.04                | 17.13   | 17.39   |
|             |            | 12      | 13        | 18.00   | 16.98                | 16.94   | 17.19   |
|             |            | 25      | 0         | 18.00   | 16.81                | 17.00   | 17.25   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 20000CH              | 20175CH | 20350CH |
| 10MHz       | QPSK       | 1       | 0         | 18.00   | 17.00                | 17.62   | 17.28   |
|             |            | 1       | 25        | 18.00   | 17.35                | 17.22   | 17.39   |
|             |            | 1       | 49        | 18.00   | 17.62                | 17.03   | 17.42   |
|             |            | 25      | 0         | 18.00   | 16.92                | 17.19   | 17.12   |
|             |            | 25      | 13        | 18.00   | 17.19                | 17.09   | 17.27   |
|             |            | 25      | 25        | 18.00   | 17.25                | 16.84   | 17.16   |
|             |            | 50      | 0         | 18.00   | 17.14                | 16.95   | 17.14   |
|             | 16QAM      | 1       | 0         | 18.00   | 17.26                | 17.84   | 17.49   |
|             |            | 1       | 25        | 18.00   | 17.58                | 17.43   | 17.61   |
|             |            | 1       | 49        | 18.00   | 17.87                | 17.11   | 17.49   |
|             |            | 25      | 0         | 18.00   | 16.86                | 17.12   | 17.04   |
|             |            | 25      | 13        | 18.00   | 17.09                | 17.01   | 17.19   |
|             |            | 25      | 25        | 18.00   | 17.15                | 16.77   | 17.14   |
|             |            | 50      | 0         | 18.00   | 17.05                | 16.84   | 17.10   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|-----------|------------|---------|-----------|---------|--------------|---------|---------|
|           |            |         |           |         | 20025CH      | 20175CH | 20325CH |
| 15MHz     | QPSK       | 1       | 0         | 18.00   | 16.63        | 17.37   | 16.73   |
|           |            | 1       | 38        | 18.00   | 17.59        | 17.22   | 17.26   |
|           |            | 1       | 74        | 18.00   | 17.31        | 16.57   | 17.08   |
|           |            | 36      | 0         | 18.00   | 17.07        | 17.34   | 17.00   |
|           |            | 36      | 18        | 18.00   | 17.40        | 17.11   | 17.20   |
|           |            | 36      | 39        | 18.00   | 17.48        | 16.95   | 17.23   |
|           |            | 75      | 0         | 18.00   | 17.33        | 17.08   | 17.11   |
|           | 16QAM      | 1       | 0         | 18.00   | 16.80        | 17.51   | 16.89   |
|           |            | 1       | 38        | 18.00   | 17.73        | 17.37   | 17.42   |
|           |            | 1       | 74        | 18.00   | 17.47        | 16.82   | 17.16   |
|           |            | 36      | 0         | 18.00   | 17.00        | 17.34   | 16.87   |
|           |            | 36      | 18        | 18.00   | 17.33        | 17.04   | 17.07   |
|           |            | 36      | 39        | 18.00   | 17.40        | 16.90   | 17.17   |
|           |            | 75      | 0         | 18.00   | 17.23        | 17.06   | 17.00   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|           |            |         |           |         | 20050CH      | 20175CH | 20300CH |
| 20MHz     | QPSK       | 1       | 0         | 18.00   | 16.81        | 17.34   | 16.73   |
|           |            | 1       | 50        | 18.00   | <b>17.49</b> | 17.26   | 17.28   |
|           |            | 1       | 99        | 18.00   | 16.70        | 16.61   | 17.12   |
|           |            | 50      | 0         | 18.00   | 17.08        | 17.27   | 16.88   |
|           |            | 50      | 25        | 18.00   | <b>17.31</b> | 17.04   | 17.01   |
|           |            | 50      | 50        | 18.00   | 17.15        | 16.92   | 17.14   |
|           |            | 100     | 0         | 18.00   | 17.13        | 17.17   | 16.97   |
|           | 16QAM      | 1       | 0         | 18.00   | 17.12        | 17.69   | 16.96   |
|           |            | 1       | 50        | 18.00   | 17.68        | 17.58   | 17.45   |
|           |            | 1       | 99        | 18.00   | 16.92        | 17.01   | 17.33   |
|           |            | 50      | 0         | 18.00   | 17.00        | 17.30   | 16.81   |
|           |            | 50      | 25        | 18.00   | 17.17        | 16.91   | 16.94   |
|           |            | 50      | 50        | 18.00   | 17.06        | 16.86   | 17.06   |
|           |            | 100     | 0         | 18.00   | 17.08        | 17.09   | 16.93   |

Table 33: Conducted power measurement results of LTE Band IV (Second antenna+WiFi antenna Simultaneous Transmission)

### 7.1.8 Conducted power measurements of LTE Band V(Second Antenna)

| LTE Band V |            |         |           |         | Conducted Power(dBm) |         |         |
|------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20407CH              | 20525CH | 20643CH |
| 1.4MHz     | QPSK       | 1       | 0         | 20.50   | 19.08                | 19.28   | 19.40   |
|            |            | 1       | 3         | 20.50   | 19.33                | 19.35   | 19.55   |
|            |            | 1       | 5         | 20.50   | 19.23                | 19.25   | 19.44   |
|            |            | 3       | 0         | 20.50   | 19.17                | 19.30   | 19.37   |
|            |            | 3       | 2         | 20.50   | 19.27                | 19.32   | 19.51   |
|            |            | 3       | 3         | 20.50   | 19.24                | 19.27   | 19.48   |
|            |            | 6       | 0         | 20.50   | 19.21                | 19.27   | 19.48   |
|            | 16QAM      | 1       | 0         | 20.50   | 19.22                | 19.46   | 19.47   |
|            |            | 1       | 3         | 20.50   | 19.36                | 19.52   | 19.72   |
|            |            | 1       | 5         | 20.50   | 19.37                | 19.43   | 19.54   |
|            |            | 3       | 0         | 20.50   | 19.21                | 19.32   | 19.49   |
|            |            | 3       | 2         | 20.50   | 19.30                | 19.33   | 19.53   |
|            |            | 3       | 3         | 20.50   | 19.26                | 19.28   | 19.50   |
|            |            | 6       | 0         | 20.50   | 19.23                | 19.15   | 19.43   |
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20415CH              | 20525CH | 20635CH |
| 3MHz       | QPSK       | 1       | 0         | 20.50   | 18.90                | 19.17   | 19.33   |
|            |            | 1       | 7         | 20.50   | 19.36                | 19.39   | 19.58   |
|            |            | 1       | 14        | 20.50   | 19.20                | 19.17   | 19.19   |
|            |            | 8       | 0         | 20.50   | 19.21                | 19.23   | 19.39   |
|            |            | 8       | 4         | 20.50   | 19.33                | 19.26   | 19.40   |
|            |            | 8       | 7         | 20.50   | 19.32                | 19.26   | 19.34   |
|            |            | 15      | 0         | 20.50   | 19.26                | 19.20   | 19.38   |
|            | 16QAM      | 1       | 0         | 20.50   | 19.03                | 19.14   | 19.41   |
|            |            | 1       | 7         | 20.50   | 19.48                | 19.35   | 19.52   |
|            |            | 1       | 14        | 20.50   | 19.28                | 19.22   | 19.21   |
|            |            | 8       | 0         | 20.50   | 19.21                | 19.10   | 19.26   |
|            |            | 8       | 4         | 20.50   | 19.33                | 19.14   | 19.26   |
|            |            | 8       | 7         | 20.50   | 19.32                | 19.14   | 19.21   |
|            |            | 15      | 0         | 20.50   | 19.20                | 19.17   | 19.22   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 20425CH      | 20525CH      | 20625CH      |
| 5MHz      | QPSK       | 1       | 0         | 20.50   | 18.94        | 18.99        | 19.38        |
|           |            | 1       | 13        | 20.50   | 19.57        | 19.32        | 19.48        |
|           |            | 1       | 24        | 20.50   | 18.91        | 19.03        | 19.00        |
|           |            | 12      | 0         | 20.50   | 19.30        | 19.17        | 19.50        |
|           |            | 12      | 6         | 20.50   | 19.46        | 19.25        | 19.49        |
|           |            | 12      | 13        | 20.50   | 19.21        | 19.18        | 19.22        |
|           |            | 25      | 0         | 20.50   | 19.25        | 19.19        | 19.33        |
|           | 16QAM      | 1       | 0         | 20.50   | 19.18        | 19.29        | 19.66        |
|           |            | 1       | 13        | 20.50   | 19.76        | 19.61        | 19.72        |
|           |            | 1       | 24        | 20.50   | 19.13        | 19.36        | 19.28        |
|           |            | 12      | 0         | 20.50   | 19.26        | 19.22        | 19.41        |
|           |            | 12      | 6         | 20.50   | 19.41        | 19.28        | 19.40        |
|           |            | 12      | 13        | 20.50   | 19.16        | 19.21        | 19.14        |
|           |            | 25      | 0         | 20.50   | 19.15        | 19.16        | 19.23        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 20450CH      | 20525CH      | 20600CH      |
| 10MHz     | QPSK       | 1       | 0         | 20.50   | 18.82        | 18.85        | 19.15        |
|           |            | 1       | 25        | 20.50   | 19.35        | 19.34        | <b>19.62</b> |
|           |            | 1       | 49        | 20.50   | 18.67        | 19.10        | 18.77        |
|           |            | 25      | 0         | 20.50   | 19.20        | 19.02        | 19.37        |
|           |            | 25      | 13        | 20.50   | <b>19.22</b> | <b>19.18</b> | <b>19.47</b> |
|           |            | 25      | 25        | 20.50   | 19.01        | 19.13        | 19.16        |
|           |            | 50      | 0         | 20.50   | 19.08        | 19.13        | 19.30        |
|           | 16QAM      | 1       | 0         | 20.50   | 18.94        | 19.00        | 19.26        |
|           |            | 1       | 25        | 20.50   | 19.47        | 19.52        | 19.70        |
|           |            | 1       | 49        | 20.50   | 18.84        | 19.30        | 18.67        |
|           |            | 25      | 0         | 20.50   | 19.07        | 19.03        | 19.27        |
|           |            | 25      | 13        | 20.50   | 19.10        | 19.19        | 19.36        |
|           |            | 25      | 25        | 20.50   | 18.89        | 19.14        | 19.05        |
|           |            | 50      | 0         | 20.50   | 18.94        | 19.09        | 19.19        |

Table 34: Conducted power measurement results of LTE Band V (Receiver on)

| LTE Band V |            |         |           |         | Conducted Power(dBm) |         |         |
|------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20407CH              | 20525CH | 20643CH |
| 1.4MHz     | QPSK       | 1       | 0         | 24.00   | 22.56                | 22.61   | 22.76   |
|            |            | 1       | 3         | 24.00   | 22.71                | 22.69   | 22.82   |
|            |            | 1       | 5         | 24.00   | 22.55                | 22.54   | 22.60   |
|            |            | 3       | 0         | 24.00   | 22.62                | 22.60   | 22.73   |
|            |            | 3       | 2         | 24.00   | 22.64                | 22.63   | 22.70   |
|            |            | 3       | 3         | 24.00   | 22.58                | 22.57   | 22.60   |
|            |            | 6       | 0         | 23.00   | 21.66                | 21.69   | 21.77   |
|            | 16QAM      | 1       | 0         | 23.00   | 21.66                | 22.00   | 21.85   |
|            |            | 1       | 3         | 23.00   | 21.80                | 22.05   | 21.91   |
|            |            | 1       | 5         | 23.00   | 21.60                | 21.92   | 21.70   |
|            |            | 3       | 0         | 23.00   | 21.61                | 21.70   | 21.86   |
|            |            | 3       | 2         | 23.00   | 21.64                | 21.76   | 21.86   |
|            |            | 3       | 3         | 23.00   | 21.56                | 21.70   | 21.81   |
|            |            | 6       | 0         | 22.00   | 20.70                | 20.71   | 20.81   |
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20415CH              | 20525CH | 20635CH |
| 3MHz       | QPSK       | 1       | 0         | 24.00   | 22.37                | 22.38   | 22.68   |
|            |            | 1       | 7         | 24.00   | 22.82                | 22.72   | 22.82   |
|            |            | 1       | 14        | 24.00   | 22.44                | 22.48   | 22.40   |
|            |            | 8       | 0         | 23.00   | 21.63                | 21.62   | 21.72   |
|            |            | 8       | 4         | 23.00   | 21.77                | 21.70   | 21.77   |
|            |            | 8       | 7         | 23.00   | 21.74                | 21.68   | 21.66   |
|            |            | 15      | 0         | 23.00   | 21.69                | 21.62   | 21.72   |
|            | 16QAM      | 1       | 0         | 23.00   | 21.48                | 21.66   | 21.68   |
|            |            | 1       | 7         | 23.00   | 21.93                | 22.02   | 21.93   |
|            |            | 1       | 14        | 23.00   | 21.58                | 21.74   | 21.45   |
|            |            | 8       | 0         | 22.00   | 20.63                | 20.66   | 20.69   |
|            |            | 8       | 4         | 22.00   | 20.78                | 20.73   | 20.76   |
|            |            | 8       | 7         | 22.00   | 20.75                | 20.71   | 20.65   |
|            |            | 15      | 0         | 22.00   | 20.61                | 20.67   | 20.74   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 20425CH | 20525CH | 20625CH      |
| 5MHz      | QPSK       | 1       | 0         | 24.00   | 22.40   | 22.27   | 22.69        |
|           |            | 1       | 13        | 24.00   | 22.80   | 22.65   | 22.81        |
|           |            | 1       | 24        | 24.00   | 22.25   | 22.45   | 22.20        |
|           |            | 12      | 0         | 23.00   | 21.70   | 21.58   | 21.90        |
|           |            | 12      | 6         | 23.00   | 21.84   | 21.69   | 21.87        |
|           |            | 12      | 13        | 23.00   | 21.56   | 21.63   | 21.57        |
|           |            | 25      | 0         | 23.00   | 21.63   | 21.63   | 21.71        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.47   | 21.56   | 22.02        |
|           |            | 1       | 13        | 23.00   | 21.88   | 21.97   | 22.14        |
|           |            | 1       | 24        | 23.00   | 21.30   | 21.67   | 21.55        |
|           |            | 12      | 0         | 22.00   | 20.70   | 20.66   | 20.86        |
|           |            | 12      | 6         | 22.00   | 20.87   | 20.77   | 20.85        |
|           |            | 12      | 13        | 22.00   | 20.59   | 20.70   | 20.57        |
|           |            | 25      | 0         | 22.00   | 20.60   | 20.68   | 20.70        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 20450CH | 20525CH | 20600CH      |
| 10MHz     | QPSK       | 1       | 0         | 24.00   | 22.12   | 22.06   | 22.54        |
|           |            | 1       | 25        | 24.00   | 22.78   | 22.65   | <b>22.99</b> |
|           |            | 1       | 49        | 24.00   | 22.01   | 22.46   | 22.13        |
|           |            | 25      | 0         | 23.00   | 21.57   | 21.44   | 21.82        |
|           |            | 25      | 13        | 23.00   | 21.62   | 21.64   | <b>21.92</b> |
|           |            | 25      | 25        | 23.00   | 21.41   | 21.58   | 21.58        |
|           |            | 50      | 0         | 23.00   | 21.46   | 21.56   | 21.74        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.51   | 21.24   | 21.52        |
|           |            | 1       | 25        | 23.00   | 22.12   | 21.89   | 22.07        |
|           |            | 1       | 49        | 23.00   | 21.34   | 21.60   | 21.16        |
|           |            | 25      | 0         | 22.00   | 20.55   | 20.43   | 20.78        |
|           |            | 25      | 13        | 22.00   | 20.61   | 20.64   | 20.89        |
|           |            | 25      | 25        | 22.00   | 20.39   | 20.58   | 20.56        |
|           |            | 50      | 0         | 22.00   | 20.46   | 20.55   | 20.73        |

Table 35: Conducted power measurement results of LTE Band V (Full power)

| LTE Band V |            |         |           |         | Conducted Power(dBm) |         |         |
|------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20407CH              | 20525CH | 20643CH |
| 1.4MHz     | QPSK       | 1       | 0         | 17.50   | 16.09                | 16.37   | 16.53   |
|            |            | 1       | 3         | 17.50   | 16.35                | 16.49   | 16.58   |
|            |            | 1       | 5         | 17.50   | 16.26                | 16.37   | 16.48   |
|            |            | 3       | 0         | 17.50   | 16.16                | 16.40   | 16.56   |
|            |            | 3       | 2         | 17.50   | 16.29                | 16.44   | 16.52   |
|            |            | 3       | 3         | 17.50   | 16.26                | 16.39   | 16.50   |
|            |            | 6       | 0         | 17.50   | 16.20                | 16.38   | 16.49   |
|            | 16QAM      | 1       | 0         | 17.50   | 16.14                | 16.64   | 16.50   |
|            |            | 1       | 3         | 17.50   | 16.41                | 16.78   | 16.56   |
|            |            | 1       | 5         | 17.50   | 16.36                | 16.68   | 16.49   |
|            |            | 3       | 0         | 17.50   | 16.27                | 16.46   | 16.60   |
|            |            | 3       | 2         | 17.50   | 16.39                | 16.50   | 16.58   |
|            |            | 3       | 3         | 17.50   | 16.38                | 16.45   | 16.56   |
|            |            | 6       | 0         | 17.50   | 16.30                | 16.31   | 16.45   |
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20415CH              | 20525CH | 20635CH |
| 3MHz       | QPSK       | 1       | 0         | 17.50   | 15.86                | 16.16   | 16.42   |
|            |            | 1       | 7         | 17.50   | 16.42                | 16.50   | 16.74   |
|            |            | 1       | 14        | 17.50   | 16.19                | 16.17   | 16.29   |
|            |            | 8       | 0         | 17.50   | 16.21                | 16.29   | 16.49   |
|            |            | 8       | 4         | 17.50   | 16.37                | 16.36   | 16.54   |
|            |            | 8       | 7         | 17.50   | 16.35                | 16.34   | 16.43   |
|            |            | 15      | 0         | 17.50   | 16.26                | 16.27   | 16.48   |
|            | 16QAM      | 1       | 0         | 17.50   | 16.04                | 16.38   | 16.42   |
|            |            | 1       | 7         | 17.50   | 16.62                | 16.72   | 16.76   |
|            |            | 1       | 14        | 17.50   | 16.38                | 16.35   | 16.32   |
|            |            | 8       | 0         | 17.50   | 16.20                | 16.24   | 16.44   |
|            |            | 8       | 4         | 17.50   | 16.36                | 16.29   | 16.49   |
|            |            | 8       | 7         | 17.50   | 16.35                | 16.29   | 16.38   |
|            |            | 15      | 0         | 17.50   | 16.20                | 16.32   | 16.43   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 20425CH | 20525CH | 20625CH      |
| 5MHz      | QPSK       | 1       | 0         | 17.50   | 15.90   | 16.07   | 16.47        |
|           |            | 1       | 13        | 17.50   | 16.60   | 16.43   | 16.61        |
|           |            | 1       | 24        | 17.50   | 15.90   | 16.12   | 16.10        |
|           |            | 12      | 0         | 17.50   | 16.27   | 16.27   | 16.60        |
|           |            | 12      | 6         | 17.50   | 16.46   | 16.36   | 16.61        |
|           |            | 12      | 13        | 17.50   | 16.23   | 16.29   | 16.35        |
|           |            | 25      | 0         | 17.50   | 16.24   | 16.29   | 16.45        |
|           | 16QAM      | 1       | 0         | 17.50   | 16.12   | 16.36   | 16.83        |
|           |            | 1       | 13        | 17.50   | 16.86   | 16.72   | 16.96        |
|           |            | 1       | 24        | 17.50   | 16.17   | 16.39   | 16.45        |
|           |            | 12      | 0         | 17.50   | 16.34   | 16.33   | 16.58        |
|           |            | 12      | 6         | 17.50   | 16.50   | 16.41   | 16.62        |
|           |            | 12      | 13        | 17.50   | 16.27   | 16.34   | 16.34        |
|           |            | 25      | 0         | 17.50   | 16.19   | 16.26   | 16.38        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 20450CH | 20525CH | 20600CH      |
| 10MHz     | QPSK       | 1       | 0         | 17.50   | 15.75   | 15.90   | 16.20        |
|           |            | 1       | 25        | 17.50   | 16.40   | 16.43   | <b>16.75</b> |
|           |            | 1       | 49        | 17.50   | 15.77   | 16.14   | 15.89        |
|           |            | 25      | 0         | 17.50   | 16.22   | 16.14   | 16.45        |
|           |            | 25      | 13        | 17.50   | 16.29   | 16.31   | <b>16.58</b> |
|           |            | 25      | 25        | 17.50   | 16.14   | 16.24   | 16.29        |
|           |            | 50      | 0         | 17.50   | 16.11   | 16.24   | 16.40        |
|           | 16QAM      | 1       | 0         | 17.50   | 16.06   | 16.11   | 16.36        |
|           |            | 1       | 25        | 17.50   | 16.73   | 16.59   | 16.91        |
|           |            | 1       | 49        | 17.50   | 16.10   | 16.37   | 16.08        |
|           |            | 25      | 0         | 17.50   | 16.16   | 16.11   | 16.41        |
|           |            | 25      | 13        | 17.50   | 16.21   | 16.28   | 16.54        |
|           |            | 25      | 25        | 17.50   | 16.08   | 16.21   | 16.23        |
|           |            | 50      | 0         | 17.50   | 16.04   | 16.18   | 16.35        |

Table 36: Conducted power measurement results of LTE Band V (Second antenna+WiFi antenna Simultaneous Transmission)

### 7.1.9 Conducted power measurements of LTE Band VII (Second Antenna)

| LTE Band VII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20775CH              | 21100CH | 21425CH |
| 5MHz         | QPSK       | 1       | 0         | 16.00   | 15.19                | 15.52   | 15.11   |
|              |            | 1       | 13        | 16.00   | 15.26                | 15.35   | 15.07   |
|              |            | 1       | 24        | 16.00   | 15.13                | 15.35   | 14.99   |
|              |            | 12      | 0         | 16.00   | 15.11                | 15.23   | 14.94   |
|              |            | 12      | 6         | 16.00   | 15.16                | 15.37   | 14.99   |
|              |            | 12      | 13        | 16.00   | 14.96                | 15.12   | 14.79   |
|              |            | 25      | 0         | 16.00   | 14.98                | 15.12   | 14.88   |
|              | 16QAM      | 1       | 0         | 16.00   | 15.48                | 15.99   | 15.63   |
|              |            | 1       | 13        | 16.00   | 15.53                | 15.75   | 15.52   |
|              |            | 1       | 24        | 16.00   | 15.38                | 15.79   | 15.42   |
|              |            | 12      | 0         | 16.00   | 15.15                | 15.37   | 14.87   |
|              |            | 12      | 6         | 16.00   | 15.25                | 15.51   | 14.92   |
|              |            | 12      | 13        | 16.00   | 15.08                | 15.25   | 14.72   |
|              |            | 25      | 0         | 16.00   | 14.97                | 15.17   | 14.79   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20800CH              | 21100CH | 21400CH |
| 10MHz        | QPSK       | 1       | 0         | 16.00   | 15.18                | 15.41   | 14.67   |
|              |            | 1       | 25        | 16.00   | 15.19                | 15.40   | 14.98   |
|              |            | 1       | 49        | 16.00   | 14.88                | 15.33   | 15.04   |
|              |            | 25      | 0         | 16.00   | 15.01                | 15.14   | 14.62   |
|              |            | 25      | 13        | 16.00   | 15.01                | 15.22   | 14.81   |
|              |            | 25      | 25        | 16.00   | 14.84                | 15.08   | 14.84   |
|              |            | 50      | 0         | 16.00   | 15.05                | 15.06   | 14.75   |
|              | 16QAM      | 1       | 0         | 16.00   | 15.51                | 15.69   | 14.85   |
|              |            | 1       | 25        | 16.00   | 15.54                | 15.69   | 15.09   |
|              |            | 1       | 49        | 16.00   | 15.19                | 15.57   | 15.21   |
|              |            | 25      | 0         | 16.00   | 15.00                | 15.17   | 14.57   |
|              |            | 25      | 13        | 16.00   | 15.01                | 15.23   | 14.83   |
|              |            | 25      | 25        | 16.00   | 14.84                | 15.10   | 14.80   |
|              |            | 50      | 0         | 16.00   | 15.04                | 15.05   | 14.68   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 20825CH      | 21100CH      | 21375CH      |
| 15MHz     | QPSK       | 1       | 0         | 16.00   | 14.97        | 14.97        | 14.34        |
|           |            | 1       | 38        | 16.00   | 15.05        | 15.39        | 14.89        |
|           |            | 1       | 74        | 16.00   | 14.31        | 14.89        | 14.95        |
|           |            | 36      | 0         | 16.00   | 15.03        | 15.02        | 14.25        |
|           |            | 36      | 18        | 16.00   | 14.91        | 15.28        | 14.63        |
|           |            | 36      | 39        | 16.00   | 14.37        | 14.94        | 14.70        |
|           |            | 75      | 0         | 16.00   | 14.77        | 14.94        | 14.63        |
|           | 16QAM      | 1       | 0         | 16.00   | 15.27        | 15.28        | 14.62        |
|           |            | 1       | 38        | 16.00   | 15.41        | 15.69        | 15.17        |
|           |            | 1       | 74        | 16.00   | 14.69        | 15.26        | 15.22        |
|           |            | 36      | 0         | 16.00   | 15.05        | 15.05        | 14.19        |
|           |            | 36      | 18        | 16.00   | 14.93        | 15.31        | 14.57        |
|           |            | 36      | 39        | 16.00   | 14.40        | 14.97        | 14.64        |
|           |            | 75      | 0         | 16.00   | 14.78        | 14.93        | 14.58        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 20850CH      | 21100CH      | 21350CH      |
| 20MHz     | QPSK       | 1       | 0         | 16.00   | <b>15.32</b> | 15.18        | 14.53        |
|           |            | 1       | 50        | 16.00   | 14.85        | <b>15.48</b> | 14.67        |
|           |            | 1       | 99        | 16.00   | 14.69        | 14.98        | <b>15.13</b> |
|           |            | 50      | 0         | 16.00   | <b>15.02</b> | 14.97        | 14.43        |
|           |            | 50      | 25        | 16.00   | 14.69        | <b>15.23</b> | 14.60        |
|           |            | 50      | 50        | 16.00   | 14.31        | 15.06        | <b>14.67</b> |
|           |            | 100     | 0         | 16.00   | 14.78        | <b>14.98</b> | 14.61        |
|           | 16QAM      | 1       | 0         | 16.00   | 15.60        | 15.66        | 14.95        |
|           |            | 1       | 50        | 16.00   | 15.20        | 15.92        | 15.05        |
|           |            | 1       | 99        | 16.00   | 15.06        | 15.44        | 15.67        |
|           |            | 50      | 0         | 16.00   | 14.98        | 14.96        | 14.45        |
|           |            | 50      | 25        | 16.00   | 14.66        | 15.21        | 14.63        |
|           |            | 50      | 50        | 16.00   | 14.28        | 15.05        | 14.69        |
|           |            | 100     | 0         | 16.00   | 14.72        | 14.97        | 14.60        |

Table 37: Conducted power measurement results of LTE Band VII (Receiver on)

| LTE Band VII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20775CH              | 21100CH | 21425CH |
| 5MHz         | QPSK       | 1       | 0         | 22.50   | 21.70                | 22.06   | 21.69   |
|              |            | 1       | 13        | 22.50   | 21.68                | 21.99   | 21.56   |
|              |            | 1       | 24        | 22.50   | 21.52                | 21.89   | 21.34   |
|              |            | 12      | 0         | 21.50   | 20.75                | 21.00   | 20.75   |
|              |            | 12      | 6         | 21.50   | 20.85                | 21.04   | 20.79   |
|              |            | 12      | 13        | 21.50   | 20.70                | 20.87   | 20.61   |
|              |            | 25      | 0         | 21.50   | 20.70                | 20.90   | 20.65   |
|              | 16QAM      | 1       | 0         | 21.50   | 21.00                | 21.46   | 21.13   |
|              |            | 1       | 13        | 21.50   | 20.93                | 21.24   | 21.03   |
|              |            | 1       | 24        | 21.50   | 20.83                | 21.27   | 20.91   |
|              |            | 12      | 0         | 21.50   | 21.10                | 21.39   | 21.07   |
|              |            | 12      | 6         | 21.50   | 21.16                | 21.45   | 21.12   |
|              |            | 12      | 13        | 21.50   | 21.00                | 21.33   | 20.90   |
|              |            | 25      | 0         | 21.50   | 20.97                | 21.28   | 20.97   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20800CH              | 21100CH | 21400CH |
| 10MHz        | QPSK       | 1       | 0         | 22.50   | 21.64                | 21.99   | 21.30   |
|              |            | 1       | 25        | 22.50   | 21.56                | 22.03   | 21.51   |
|              |            | 1       | 49        | 22.50   | 21.22                | 21.84   | 21.36   |
|              |            | 25      | 0         | 21.50   | 20.73                | 20.90   | 20.46   |
|              |            | 25      | 13        | 21.50   | 20.64                | 20.94   | 20.58   |
|              |            | 25      | 25        | 21.50   | 20.42                | 20.83   | 20.64   |
|              |            | 50      | 0         | 21.50   | 20.75                | 20.82   | 20.56   |
|              | 16QAM      | 1       | 0         | 21.50   | 21.03                | 21.23   | 20.55   |
|              |            | 1       | 25        | 21.50   | 20.91                | 21.14   | 20.76   |
|              |            | 1       | 49        | 21.50   | 20.69                | 21.01   | 20.83   |
|              |            | 25      | 0         | 21.50   | 20.97                | 21.35   | 20.75   |
|              |            | 25      | 13        | 21.50   | 20.90                | 21.37   | 20.89   |
|              |            | 25      | 25        | 21.50   | 20.68                | 21.21   | 20.87   |
|              |            | 50      | 0         | 21.50   | 21.04                | 21.20   | 20.90   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel      | Channel |
|-----------|------------|---------|-----------|---------|---------|--------------|---------|
|           |            |         |           |         | 20825CH | 21100CH      | 21375CH |
| 15MHz     | QPSK       | 1       | 0         | 22.50   | 21.44   | 21.70        | 20.85   |
|           |            | 1       | 38        | 22.50   | 21.37   | 22.04        | 21.31   |
|           |            | 1       | 74        | 22.50   | 20.80   | 21.50        | 21.20   |
|           |            | 36      | 0         | 21.50   | 20.71   | 20.82        | 20.11   |
|           |            | 36      | 18        | 21.50   | 20.49   | 20.94        | 20.39   |
|           |            | 36      | 39        | 21.50   | 20.01   | 20.69        | 20.49   |
|           |            | 75      | 0         | 21.50   | 20.47   | 20.70        | 20.37   |
|           | 16QAM      | 1       | 0         | 21.50   | 20.84   | 21.08        | 20.20   |
|           |            | 1       | 38        | 21.50   | 20.79   | 21.30        | 20.68   |
|           |            | 1       | 74        | 21.50   | 20.25   | 20.83        | 20.73   |
|           |            | 36      | 0         | 21.50   | 20.94   | 21.21        | 20.45   |
|           |            | 36      | 18        | 21.50   | 20.77   | 21.34        | 20.76   |
|           |            | 36      | 39        | 21.50   | 20.44   | 21.05        | 20.83   |
|           |            | 75      | 0         | 21.50   | 20.71   | 21.09        | 20.73   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel      | Channel |
|           |            |         |           |         | 20850CH | 21100CH      | 21350CH |
| 20MHz     | QPSK       | 1       | 0         | 22.50   | 21.63   | 21.67        | 21.05   |
|           |            | 1       | 50        | 22.50   | 21.08   | <b>22.04</b> | 21.16   |
|           |            | 1       | 99        | 22.50   | 21.06   | 21.47        | 21.37   |
|           |            | 50      | 0         | 21.50   | 20.55   | 20.75        | 20.11   |
|           |            | 50      | 25        | 21.50   | 20.18   | <b>20.87</b> | 20.36   |
|           |            | 50      | 50        | 21.50   | 19.89   | 20.67        | 20.45   |
|           |            | 100     | 0         | 21.50   | 20.27   | 20.67        | 20.39   |
|           | 16QAM      | 1       | 0         | 21.50   | 21.06   | 20.97        | 20.59   |
|           |            | 1       | 50        | 21.50   | 20.63   | 21.15        | 20.74   |
|           |            | 1       | 99        | 21.50   | 20.65   | 20.60        | 21.07   |
|           |            | 50      | 0         | 21.50   | 20.89   | 21.10        | 20.46   |
|           |            | 50      | 25        | 21.50   | 20.57   | 21.26        | 20.73   |
|           |            | 50      | 50        | 21.50   | 20.29   | 21.05        | 20.76   |
|           |            | 100     | 0         | 21.50   | 20.60   | 21.04        | 20.70   |

Table 38: Conducted power measurement results of LTE Band VII (Full power)

| LTE Band VII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20775CH              | 21100CH | 21425CH |
| 5MHz         | QPSK       | 1       | 0         | 14.20   | 13.31                | 13.54   | 13.29   |
|              |            | 1       | 13        | 14.20   | 13.40                | 13.41   | 13.16   |
|              |            | 1       | 24        | 14.20   | 13.27                | 13.33   | 13.18   |
|              |            | 12      | 0         | 14.20   | 13.17                | 13.29   | 13.06   |
|              |            | 12      | 6         | 14.20   | 13.24                | 13.43   | 13.11   |
|              |            | 12      | 13        | 14.20   | 12.99                | 13.21   | 12.92   |
|              |            | 25      | 0         | 14.20   | 13.06                | 13.20   | 13.00   |
|              | 16QAM      | 1       | 0         | 14.20   | 13.48                | 14.07   | 13.69   |
|              |            | 1       | 13        | 14.20   | 13.49                | 13.88   | 13.59   |
|              |            | 1       | 24        | 14.20   | 13.38                | 13.83   | 13.56   |
|              |            | 12      | 0         | 14.20   | 13.17                | 13.36   | 13.00   |
|              |            | 12      | 6         | 14.20   | 13.27                | 13.51   | 13.04   |
|              |            | 12      | 13        | 14.20   | 13.02                | 13.29   | 12.88   |
|              |            | 25      | 0         | 14.20   | 12.98                | 13.15   | 12.91   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20800CH              | 21100CH | 21400CH |
| 10MHz        | QPSK       | 1       | 0         | 14.20   | 13.10                | 13.40   | 12.74   |
|              |            | 1       | 25        | 14.20   | 13.24                | 13.48   | 13.09   |
|              |            | 1       | 49        | 14.20   | 12.90                | 13.36   | 13.26   |
|              |            | 25      | 0         | 14.20   | 12.92                | 13.18   | 12.70   |
|              |            | 25      | 13        | 14.20   | 13.03                | 13.28   | 12.91   |
|              |            | 25      | 25        | 14.20   | 12.89                | 13.15   | 12.94   |
|              |            | 50      | 0         | 14.20   | 12.99                | 13.12   | 12.84   |
|              | 16QAM      | 1       | 0         | 14.20   | 13.61                | 13.97   | 13.02   |
|              |            | 1       | 25        | 14.20   | 13.76                | 14.05   | 13.30   |
|              |            | 1       | 49        | 14.20   | 13.31                | 13.91   | 13.47   |
|              |            | 25      | 0         | 14.20   | 12.89                | 13.19   | 12.64   |
|              |            | 25      | 13        | 14.20   | 13.00                | 13.28   | 12.85   |
|              |            | 25      | 25        | 14.20   | 12.85                | 13.17   | 12.87   |
|              |            | 50      | 0         | 14.20   | 12.97                | 13.13   | 12.76   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel      | Channel |
|-----------|------------|---------|-----------|---------|---------|--------------|---------|
|           |            |         |           |         | 20825CH | 21100CH      | 21375CH |
| 15MHz     | QPSK       | 1       | 0         | 14.20   | 12.92   | 12.96        | 12.24   |
|           |            | 1       | 38        | 14.20   | 13.13   | 13.47        | 12.90   |
|           |            | 1       | 74        | 14.20   | 12.34   | 12.97        | 12.98   |
|           |            | 36      | 0         | 14.20   | 12.99   | 13.04        | 12.31   |
|           |            | 36      | 18        | 14.20   | 12.99   | 13.32        | 12.69   |
|           |            | 36      | 39        | 14.20   | 12.47   | 13.04        | 12.76   |
|           |            | 75      | 0         | 14.20   | 12.76   | 12.99        | 12.71   |
|           | 16QAM      | 1       | 0         | 14.20   | 13.16   | 13.31        | 12.56   |
|           |            | 1       | 38        | 14.20   | 13.34   | 13.87        | 13.21   |
|           |            | 1       | 74        | 14.20   | 12.63   | 13.29        | 13.34   |
|           |            | 36      | 0         | 14.20   | 12.93   | 13.10        | 12.27   |
|           |            | 36      | 18        | 14.20   | 12.92   | 13.38        | 12.65   |
|           |            | 36      | 39        | 14.20   | 12.39   | 13.07        | 12.72   |
|           |            | 75      | 0         | 14.20   | 12.70   | 12.99        | 12.64   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel      | Channel |
|           |            |         |           |         | 20850CH | 21100CH      | 21350CH |
| 20MHz     | QPSK       | 1       | 0         | 14.20   | 13.23   | 13.04        | 12.53   |
|           |            | 1       | 50        | 14.20   | 12.90   | <b>13.49</b> | 12.67   |
|           |            | 1       | 99        | 14.20   | 12.64   | 12.94        | 13.18   |
|           |            | 50      | 0         | 14.20   | 12.91   | 12.94        | 12.40   |
|           |            | 50      | 25        | 14.20   | 12.69   | <b>13.27</b> | 12.65   |
|           |            | 50      | 50        | 14.20   | 12.29   | 13.11        | 12.71   |
|           |            | 100     | 0         | 14.20   | 12.67   | 12.96        | 12.65   |
|           | 16QAM      | 1       | 0         | 14.20   | 13.64   | 13.42        | 12.88   |
|           |            | 1       | 50        | 14.20   | 13.30   | 13.72        | 12.99   |
|           |            | 1       | 99        | 14.20   | 12.96   | 13.19        | 13.60   |
|           |            | 50      | 0         | 14.20   | 12.87   | 12.93        | 12.39   |
|           |            | 50      | 25        | 14.20   | 12.63   | 13.21        | 12.63   |
|           |            | 50      | 50        | 14.20   | 12.24   | 13.07        | 12.70   |
|           |            | 100     | 0         | 14.20   | 12.63   | 12.97        | 12.59   |

Table 39: Conducted power measurement results of LTE Band VII (Second antenna+WiFi antenna Simultaneous Transmission)

### 7.1.10 Conducted power measurements of LTE Band XII (Second Antenna)

| LTE Band XII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23017CH              | 23095CH | 23173CH |
| 1.4MHz       | QPSK       | 1       | 0         | 21.50   | 20.48                | 20.52   | 20.26   |
|              |            | 1       | 3         | 21.50   | 20.61                | 20.71   | 20.42   |
|              |            | 1       | 5         | 21.50   | 20.58                | 20.65   | 20.38   |
|              |            | 3       | 0         | 21.50   | 20.56                | 20.58   | 20.29   |
|              |            | 3       | 2         | 21.50   | 20.61                | 20.69   | 20.32   |
|              |            | 3       | 3         | 21.50   | 20.56                | 20.66   | 20.35   |
|              | 16QAM      | 6       | 0         | 21.50   | 20.50                | 20.65   | 20.29   |
|              |            | 1       | 0         | 21.50   | 20.62                | 20.75   | 20.30   |
|              |            | 1       | 3         | 21.50   | 20.73                | 20.98   | 20.45   |
|              |            | 1       | 5         | 21.50   | 20.67                | 20.91   | 20.41   |
|              |            | 3       | 0         | 21.50   | 20.59                | 20.56   | 20.29   |
|              |            | 3       | 2         | 21.50   | 20.64                | 20.65   | 20.33   |
|              |            | 3       | 3         | 21.50   | 20.58                | 20.63   | 20.37   |
|              |            | 6       | 0         | 21.50   | 20.54                | 20.57   | 20.23   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23025CH              | 23095CH | 23165CH |
| 3MHz         | QPSK       | 1       | 0         | 21.50   | 20.25                | 20.18   | 20.25   |
|              |            | 1       | 7         | 21.50   | 20.62                | 20.77   | 20.52   |
|              |            | 1       | 14        | 21.50   | 20.13                | 20.46   | 20.11   |
|              |            | 8       | 0         | 21.50   | 20.45                | 20.48   | 20.27   |
|              |            | 8       | 4         | 21.50   | 20.52                | 20.67   | 20.30   |
|              |            | 8       | 7         | 21.50   | 20.29                | 20.59   | 20.21   |
|              |            | 15      | 0         | 21.50   | 20.33                | 20.52   | 20.26   |
|              | 16QAM      | 1       | 0         | 21.50   | 20.46                | 20.30   | 20.35   |
|              |            | 1       | 7         | 21.50   | 20.83                | 20.94   | 20.59   |
|              |            | 1       | 14        | 21.50   | 20.33                | 20.58   | 20.13   |
|              |            | 8       | 0         | 21.50   | 20.41                | 20.49   | 20.19   |
|              |            | 8       | 4         | 21.50   | 20.48                | 20.68   | 20.23   |
|              |            | 8       | 7         | 21.50   | 20.26                | 20.60   | 20.13   |
|              |            | 15      | 0         | 21.50   | 20.26                | 20.50   | 20.24   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 23035CH      | 23095CH      | 23155CH      |
| 5MHz      | QPSK       | 1       | 0         | 21.50   | 20.20        | 20.00        | 20.41        |
|           |            | 1       | 13        | 21.50   | 20.50        | 20.65        | 20.40        |
|           |            | 1       | 24        | 21.50   | 19.79        | 20.31        | 19.91        |
|           |            | 12      | 0         | 21.50   | 20.34        | 20.34        | 20.48        |
|           |            | 12      | 6         | 21.50   | 20.42        | 20.57        | 20.38        |
|           |            | 12      | 13        | 21.50   | 20.08        | 20.55        | 20.13        |
|           |            | 25      | 0         | 21.50   | 20.21        | 20.46        | 20.31        |
|           | 16QAM      | 1       | 0         | 21.50   | 20.53        | 20.46        | 20.76        |
|           |            | 1       | 13        | 21.50   | 20.83        | 21.09        | 20.72        |
|           |            | 1       | 24        | 21.50   | 20.11        | 20.76        | 20.26        |
|           |            | 12      | 0         | 21.50   | 20.36        | 20.34        | 20.42        |
|           |            | 12      | 6         | 21.50   | 20.39        | 20.57        | 20.30        |
|           |            | 12      | 13        | 21.50   | 20.10        | 20.54        | 20.08        |
|           |            | 25      | 0         | 21.50   | 20.17        | 20.42        | 20.25        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 23060CH      | 23095CH      | 23130CH      |
| 10MHz     | QPSK       | 1       | 0         | 21.50   | 20.03        | 19.78        | 20.04        |
|           |            | 1       | 25        | 21.50   | <b>20.30</b> | <b>20.77</b> | <b>20.87</b> |
|           |            | 1       | 49        | 21.50   | 20.08        | 19.91        | 19.59        |
|           |            | 25      | 0         | 21.50   | 20.12        | 20.15        | 20.49        |
|           |            | 25      | 13        | 21.50   | <b>20.14</b> | <b>20.49</b> | <b>20.55</b> |
|           |            | 25      | 25        | 21.50   | 20.08        | 20.34        | 20.07        |
|           |            | 50      | 0         | 21.50   | 20.09        | 20.20        | 20.30        |
|           | 16QAM      | 1       | 0         | 21.50   | 20.21        | 19.99        | 20.13        |
|           |            | 1       | 25        | 21.50   | 20.58        | 21.07        | 20.91        |
|           |            | 1       | 49        | 21.50   | 20.39        | 20.05        | 19.65        |
|           |            | 25      | 0         | 21.50   | 20.06        | 20.12        | 20.43        |
|           |            | 25      | 13        | 21.50   | 20.08        | 20.45        | 20.49        |
|           |            | 25      | 25        | 21.50   | 20.04        | 20.30        | 20.01        |
|           |            | 50      | 0         | 21.50   | 20.05        | 20.15        | 20.23        |

Table 40: Conducted power measurement results of LTE Band XII (Receiver on)

| LTE Band XII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23017CH              | 23095CH | 23173CH |
| 1.4MHz       | QPSK       | 1       | 0         | 24.00   | 22.86                | 22.82   | 22.54   |
|              |            | 1       | 3         | 24.00   | 22.95                | 22.98   | 22.65   |
|              |            | 1       | 5         | 24.00   | 22.85                | 22.99   | 22.61   |
|              |            | 3       | 0         | 24.00   | 22.88                | 22.92   | 22.52   |
|              |            | 3       | 2         | 24.00   | 22.92                | 23.02   | 22.55   |
|              |            | 3       | 3         | 24.00   | 22.86                | 23.00   | 22.57   |
|              |            | 6       | 0         | 23.00   | 21.96                | 22.13   | 21.69   |
|              | 16QAM      | 1       | 0         | 22.50   | 21.89                | 22.17   | 21.48   |
|              |            | 1       | 3         | 22.50   | 21.98                | 22.42   | 21.68   |
|              |            | 1       | 5         | 22.50   | 21.88                | 22.38   | 21.65   |
|              |            | 3       | 0         | 22.50   | 22.05                | 22.08   | 21.63   |
|              |            | 3       | 2         | 22.50   | 22.04                | 22.20   | 21.68   |
|              |            | 3       | 3         | 22.50   | 21.99                | 22.16   | 21.70   |
|              |            | 6       | 0         | 22.00   | 21.08                | 21.13   | 20.66   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23025CH              | 23095CH | 23165CH |
| 3MHz         | QPSK       | 1       | 0         | 24.00   | 22.70                | 22.59   | 22.61   |
|              |            | 1       | 7         | 24.00   | 22.97                | 23.10   | 22.71   |
|              |            | 1       | 14        | 24.00   | 22.59                | 22.89   | 22.40   |
|              |            | 8       | 0         | 23.00   | 21.96                | 21.96   | 21.67   |
|              |            | 8       | 4         | 23.00   | 22.01                | 22.14   | 21.69   |
|              |            | 8       | 7         | 23.00   | 21.80                | 22.07   | 21.61   |
|              |            | 15      | 0         | 23.00   | 21.86                | 22.02   | 21.67   |
|              | 16QAM      | 1       | 0         | 22.50   | 21.86                | 21.68   | 21.59   |
|              |            | 1       | 7         | 22.50   | 22.22                | 22.23   | 21.74   |
|              |            | 1       | 14        | 22.50   | 21.76                | 21.98   | 21.45   |
|              |            | 8       | 0         | 22.00   | 20.98                | 20.90   | 20.63   |
|              |            | 8       | 4         | 22.00   | 21.05                | 21.15   | 20.65   |
|              |            | 8       | 7         | 22.00   | 20.75                | 21.01   | 20.56   |
|              |            | 15      | 0         | 22.00   | 20.74                | 21.00   | 20.63   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 23035CH | 23095CH | 23155CH      |
| 5MHz      | QPSK       | 1       | 0         | 24.00   | 22.57   | 22.39   | 22.74        |
|           |            | 1       | 13        | 24.00   | 22.84   | 23.00   | 22.67        |
|           |            | 1       | 24        | 24.00   | 22.21   | 22.76   | 22.26        |
|           |            | 12      | 0         | 23.00   | 21.82   | 21.83   | 21.91        |
|           |            | 12      | 6         | 23.00   | 21.87   | 22.07   | 21.81        |
|           |            | 12      | 13        | 23.00   | 21.52   | 22.05   | 21.56        |
|           |            | 25      | 0         | 23.00   | 21.68   | 21.96   | 21.74        |
|           | 16QAM      | 1       | 0         | 22.50   | 21.76   | 21.62   | 22.17        |
|           |            | 1       | 13        | 22.50   | 22.03   | 22.25   | 22.08        |
|           |            | 1       | 24        | 22.50   | 21.34   | 21.94   | 21.68        |
|           |            | 12      | 0         | 22.00   | 20.91   | 20.82   | 20.85        |
|           |            | 12      | 6         | 22.00   | 20.92   | 21.12   | 20.77        |
|           |            | 12      | 13        | 22.00   | 20.57   | 21.09   | 20.51        |
|           |            | 25      | 0         | 22.00   | 20.66   | 20.94   | 20.73        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 23060CH | 23095CH | 23130CH      |
| 10MHz     | QPSK       | 1       | 0         | 24.00   | 22.45   | 22.21   | 22.45        |
|           |            | 1       | 25        | 24.00   | 22.58   | 23.02   | <b>23.09</b> |
|           |            | 1       | 49        | 24.00   | 22.51   | 22.31   | 22.03        |
|           |            | 25      | 0         | 23.00   | 21.60   | 21.64   | 22.00        |
|           |            | 25      | 13        | 23.00   | 21.61   | 21.97   | <b>22.04</b> |
|           |            | 25      | 25        | 23.00   | 21.59   | 21.86   | 21.56        |
|           |            | 50      | 0         | 23.00   | 21.60   | 21.72   | 21.76        |
|           | 16QAM      | 1       | 0         | 22.50   | 21.68   | 21.59   | 21.54        |
|           |            | 1       | 25        | 22.50   | 21.85   | 22.45   | 22.19        |
|           |            | 1       | 49        | 22.50   | 21.80   | 21.58   | 20.99        |
|           |            | 25      | 0         | 22.00   | 20.51   | 20.56   | 20.93        |
|           |            | 25      | 13        | 22.00   | 20.53   | 20.90   | 20.95        |
|           |            | 25      | 25        | 22.00   | 20.51   | 20.78   | 20.45        |
|           |            | 50      | 0         | 22.00   | 20.53   | 20.61   | 20.73        |

Table 41: Conducted power measurement results of LTE Band XII (Full power)

| LTE Band XII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23017CH              | 23095CH | 23173CH |
| 1.4MHz       | QPSK       | 1       | 0         | 18.00   | 17.05                | 17.24   | 17.01   |
|              |            | 1       | 3         | 18.00   | 17.19                | 17.35   | 17.12   |
|              |            | 1       | 5         | 18.00   | 17.12                | 17.27   | 17.08   |
|              |            | 3       | 0         | 18.00   | 17.07                | 17.29   | 16.99   |
|              |            | 3       | 2         | 18.00   | 17.18                | 17.33   | 17.00   |
|              |            | 3       | 3         | 18.00   | 17.15                | 17.29   | 17.03   |
|              |            | 6       | 0         | 18.00   | 17.09                | 17.26   | 16.99   |
|              | 16QAM      | 1       | 0         | 18.00   | 17.13                | 17.53   | 16.99   |
|              |            | 1       | 3         | 18.00   | 17.27                | 17.64   | 17.13   |
|              |            | 1       | 5         | 18.00   | 17.17                | 17.58   | 17.08   |
|              |            | 3       | 0         | 18.00   | 17.14                | 17.32   | 17.08   |
|              |            | 3       | 2         | 18.00   | 17.23                | 17.35   | 17.10   |
|              |            | 3       | 3         | 18.00   | 17.16                | 17.31   | 17.13   |
|              |            | 6       | 0         | 18.00   | 17.10                | 17.23   | 17.09   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23025CH              | 23095CH | 23165CH |
| 3MHz         | QPSK       | 1       | 0         | 18.00   | 16.86                | 16.92   | 16.93   |
|              |            | 1       | 7         | 18.00   | 17.22                | 17.43   | 17.19   |
|              |            | 1       | 14        | 18.00   | 16.84                | 17.20   | 16.79   |
|              |            | 8       | 0         | 18.00   | 17.05                | 17.17   | 16.99   |
|              |            | 8       | 4         | 18.00   | 17.11                | 17.28   | 17.01   |
|              |            | 8       | 7         | 18.00   | 16.95                | 17.26   | 16.92   |
|              |            | 15      | 0         | 18.00   | 16.98                | 17.21   | 16.98   |
|              | 16QAM      | 1       | 0         | 18.00   | 17.05                | 16.92   | 16.88   |
|              |            | 1       | 7         | 18.00   | 17.39                | 17.44   | 17.14   |
|              |            | 1       | 14        | 18.00   | 17.05                | 17.23   | 16.77   |
|              |            | 8       | 0         | 18.00   | 17.02                | 17.12   | 16.94   |
|              |            | 8       | 4         | 18.00   | 17.07                | 17.24   | 16.96   |
|              |            | 8       | 7         | 18.00   | 16.92                | 17.20   | 16.87   |
|              |            | 15      | 0         | 18.00   | 16.94                | 17.23   | 16.95   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 23035CH | 23095CH | 23155CH      |
| 5MHz      | QPSK       | 1       | 0         | 18.00   | 16.75   | 16.76   | 17.10        |
|           |            | 1       | 13        | 18.00   | 17.17   | 17.32   | 17.12        |
|           |            | 1       | 24        | 18.00   | 16.48   | 17.03   | 16.59        |
|           |            | 12      | 0         | 18.00   | 16.94   | 17.05   | 17.17        |
|           |            | 12      | 6         | 18.00   | 17.09   | 17.27   | 17.07        |
|           |            | 12      | 13        | 18.00   | 16.77   | 17.24   | 16.84        |
|           |            | 25      | 0         | 18.00   | 16.87   | 17.15   | 16.99        |
|           | 16QAM      | 1       | 0         | 18.00   | 17.01   | 17.04   | 17.38        |
|           |            | 1       | 13        | 18.00   | 17.35   | 17.63   | 17.40        |
|           |            | 1       | 24        | 18.00   | 16.66   | 17.33   | 16.88        |
|           |            | 12      | 0         | 18.00   | 16.92   | 17.07   | 17.08        |
|           |            | 12      | 6         | 18.00   | 17.04   | 17.27   | 17.03        |
|           |            | 12      | 13        | 18.00   | 16.73   | 17.24   | 16.84        |
|           |            | 25      | 0         | 18.00   | 16.83   | 17.10   | 16.96        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 23060CH | 23095CH | 23130CH      |
| 10MHz     | QPSK       | 1       | 0         | 18.00   | 16.59   | 16.49   | 16.73        |
|           |            | 1       | 25        | 18.00   | 16.98   | 17.40   | <b>17.51</b> |
|           |            | 1       | 49        | 18.00   | 16.74   | 16.61   | 16.26        |
|           |            | 25      | 0         | 18.00   | 16.79   | 16.84   | 17.17        |
|           |            | 25      | 13        | 18.00   | 16.83   | 17.17   | <b>17.23</b> |
|           |            | 25      | 25        | 18.00   | 16.79   | 17.03   | 16.77        |
|           |            | 50      | 0         | 18.00   | 16.78   | 16.90   | 17.00        |
|           | 16QAM      | 1       | 0         | 18.00   | 16.90   | 16.65   | 16.69        |
|           |            | 1       | 25        | 18.00   | 17.23   | 17.66   | 17.54        |
|           |            | 1       | 49        | 18.00   | 17.00   | 16.87   | 16.29        |
|           |            | 25      | 0         | 18.00   | 16.72   | 16.81   | 17.10        |
|           |            | 25      | 13        | 18.00   | 16.75   | 17.12   | 17.15        |
|           |            | 25      | 25        | 18.00   | 16.71   | 17.00   | 16.69        |
|           |            | 50      | 0         | 18.00   | 16.72   | 16.83   | 16.94        |

Table 42: Conducted power measurement results of LTE Band XII (Second antenna+WiFi antennaSimultaneous Transmission)

### 7.1.11 Conducted power measurements of LTE Band XVII (Second Antenna)

| LTE Band XVII |            |         |           |         | Conducted Power(dBm) |         |         |
|---------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23755CH              | 23790CH | 23825CH |
| 5MHz          | QPSK       | 1       | 0         | 21.50   | 19.91                | 20.54   | 20.45   |
|               |            | 1       | 13        | 21.50   | 20.70                | 20.91   | 20.45   |
|               |            | 1       | 24        | 21.50   | 20.53                | 20.19   | 20.00   |
|               |            | 12      | 0         | 21.50   | 20.31                | 20.79   | 20.52   |
|               |            | 12      | 6         | 21.50   | 20.56                | 20.87   | 20.48   |
|               |            | 12      | 13        | 21.50   | 20.62                | 20.54   | 20.28   |
|               |            | 25      | 0         | 21.50   | 20.44                | 20.69   | 20.43   |
|               | 16QAM      | 1       | 0         | 21.50   | 20.14                | 20.91   | 20.89   |
|               |            | 1       | 13        | 21.50   | 20.89                | 21.27   | 20.84   |
|               |            | 1       | 24        | 21.50   | 20.66                | 20.52   | 20.44   |
|               |            | 12      | 0         | 21.50   | 20.32                | 20.85   | 20.51   |
|               |            | 12      | 6         | 21.50   | 20.57                | 20.95   | 20.48   |
|               |            | 12      | 13        | 21.50   | 20.56                | 20.60   | 20.21   |
|               |            | 25      | 0         | 21.50   | 20.38                | 20.74   | 20.36   |
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23780CH              | 23790CH | 23800CH |
| 10MHz         | QPSK       | 1       | 0         | 21.50   | 19.79                | 19.92   | 20.19   |
|               |            | 1       | 25        | 21.50   | 20.98                | 21.04   | 20.93   |
|               |            | 1       | 49        | 21.50   | 19.77                | 19.68   | 19.73   |
|               |            | 25      | 0         | 21.50   | 20.42                | 20.53   | 20.62   |
|               |            | 25      | 13        | 21.50   | 20.73                | 20.76   | 20.70   |
|               |            | 25      | 25        | 21.50   | 20.43                | 20.29   | 20.20   |
|               |            | 50      | 0         | 21.50   | 20.44                | 20.44   | 20.39   |
|               | 16QAM      | 1       | 0         | 21.50   | 19.94                | 20.15   | 20.24   |
|               |            | 1       | 25        | 21.50   | 21.21                | 21.20   | 20.97   |
|               |            | 1       | 49        | 21.50   | 20.02                | 19.91   | 19.84   |
|               |            | 25      | 0         | 21.50   | 20.33                | 20.45   | 20.51   |
|               |            | 25      | 13        | 21.50   | 20.67                | 20.72   | 20.60   |
|               |            | 25      | 25        | 21.50   | 20.31                | 20.24   | 20.12   |
|               |            | 50      | 0         | 21.50   | 20.34                | 20.27   | 20.34   |

Table 43: Conducted power measurement results of LTE Band XVII (Receiver on)

| LTE Band XVII |            |         |           |         | Conducted Power(dBm) |         |         |
|---------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23755CH              | 23790CH | 23825CH |
| 5MHz          | QPSK       | 1       | 0         | 24.00   | 22.31                | 22.96   | 22.83   |
|               |            | 1       | 13        | 24.00   | 23.03                | 23.24   | 22.80   |
|               |            | 1       | 24        | 24.00   | 22.89                | 22.65   | 22.39   |
|               |            | 12      | 0         | 23.00   | 21.83                | 22.28   | 22.00   |
|               |            | 12      | 6         | 23.00   | 22.08                | 22.43   | 21.94   |
|               |            | 12      | 13        | 23.00   | 22.11                | 22.04   | 21.69   |
|               |            | 25      | 0         | 23.00   | 22.03                | 22.25   | 21.85   |
|               | 16QAM      | 1       | 0         | 23.00   | 21.57                | 22.30   | 22.07   |
|               |            | 1       | 13        | 23.00   | 22.30                | 22.62   | 22.00   |
|               |            | 1       | 24        | 23.00   | 22.11                | 21.92   | 21.66   |
|               |            | 12      | 0         | 22.00   | 20.74                | 21.29   | 20.97   |
|               |            | 12      | 6         | 22.00   | 21.10                | 21.34   | 20.91   |
|               |            | 12      | 13        | 22.00   | 21.07                | 21.14   | 20.68   |
|               |            | 25      | 0         | 22.00   | 20.88                | 21.23   | 20.84   |
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23780CH              | 23790CH | 23800CH |
| 10MHz         | QPSK       | 1       | 0         | 24.00   | 22.27                | 22.33   | 22.64   |
|               |            | 1       | 25        | 24.00   | 23.32                | 23.28   | 23.23   |
|               |            | 1       | 49        | 24.00   | 22.36                | 22.15   | 22.11   |
|               |            | 25      | 0         | 23.00   | 21.90                | 22.02   | 22.13   |
|               |            | 25      | 13        | 23.00   | 22.30                | 22.20   | 22.11   |
|               |            | 25      | 25        | 23.00   | 21.89                | 21.73   | 21.68   |
|               |            | 50      | 0         | 23.00   | 21.95                | 21.93   | 21.93   |
|               | 16QAM      | 1       | 0         | 23.00   | 21.52                | 21.61   | 21.75   |
|               |            | 1       | 25        | 23.00   | 22.57                | 22.71   | 22.48   |
|               |            | 1       | 49        | 23.00   | 21.53                | 21.38   | 21.24   |
|               |            | 25      | 0         | 22.00   | 20.87                | 21.00   | 21.09   |
|               |            | 25      | 13        | 22.00   | 21.25                | 21.26   | 21.15   |
|               |            | 25      | 25        | 22.00   | 20.82                | 20.75   | 20.63   |
|               |            | 50      | 0         | 22.00   | 20.92                | 20.86   | 20.84   |

Table 44: Conducted power measurement results of LTE Band XVII (Full power)

| LTE Band XVII |            |         |           |         | Conducted Power(dBm) |         |         |
|---------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23755CH              | 23790CH | 23825CH |
| 5MHz          | QPSK       | 1       | 0         | 18.00   | 16.34                | 16.85   | 16.91   |
|               |            | 1       | 13        | 18.00   | 17.13                | 17.27   | 16.98   |
|               |            | 1       | 24        | 18.00   | 16.93                | 16.63   | 16.35   |
|               |            | 12      | 0         | 18.00   | 16.68                | 17.15   | 16.92   |
|               |            | 12      | 6         | 18.00   | 16.98                | 17.33   | 16.84   |
|               |            | 12      | 13        | 18.00   | 16.90                | 16.99   | 16.59   |
|               |            | 25      | 0         | 18.00   | 16.83                | 17.19   | 16.84   |
|               | 16QAM      | 1       | 0         | 18.00   | 16.46                | 17.08   | 17.33   |
|               |            | 1       | 13        | 18.00   | 17.20                | 17.54   | 17.32   |
|               |            | 1       | 24        | 18.00   | 16.90                | 16.88   | 16.83   |
|               |            | 12      | 0         | 18.00   | 16.68                | 17.17   | 16.89   |
|               |            | 12      | 6         | 18.00   | 16.93                | 17.34   | 16.87   |
|               |            | 12      | 13        | 18.00   | 17.00                | 17.01   | 16.57   |
|               |            | 25      | 0         | 18.00   | 16.86                | 17.12   | 16.74   |
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23780CH              | 23790CH | 23800CH |
| 10MHz         | QPSK       | 1       | 0         | 18.00   | 16.14                | 16.28   | 16.56   |
|               |            | 1       | 25        | 18.00   | 17.35                | 17.29   | 17.30   |
|               |            | 1       | 49        | 18.00   | 16.27                | 16.08   | 16.02   |
|               |            | 25      | 0         | 18.00   | 16.72                | 16.95   | 16.93   |
|               |            | 25      | 13        | 18.00   | 17.10                | 17.13   | 17.08   |
|               |            | 25      | 25        | 18.00   | 16.77                | 16.65   | 16.63   |
|               |            | 50      | 0         | 18.00   | 16.78                | 16.81   | 16.85   |
|               | 16QAM      | 1       | 0         | 18.00   | 16.38                | 16.42   | 16.56   |
|               |            | 1       | 25        | 18.00   | 17.56                | 17.56   | 17.42   |
|               |            | 1       | 49        | 18.00   | 16.54                | 16.29   | 16.15   |
|               |            | 25      | 0         | 18.00   | 16.67                | 16.86   | 16.89   |
|               |            | 25      | 13        | 18.00   | 16.96                | 17.10   | 17.01   |
|               |            | 25      | 25        | 18.00   | 16.67                | 16.71   | 16.52   |
|               |            | 50      | 0         | 18.00   | 16.69                | 16.73   | 16.73   |

Table 45: Conducted power measurement results of LTE Band XVII (Second antenna+WiFi antenna Simultaneous Transmission)

### 7.1.12 Conducted power measurements of GSM850 (Main Antenna)

| GSM850            |                   | Burst-Averaged output Power (dBm) |              |              |              | Division Factors | Frame-Averaged output Power (dBm) |              |              |              |
|-------------------|-------------------|-----------------------------------|--------------|--------------|--------------|------------------|-----------------------------------|--------------|--------------|--------------|
|                   |                   | Tune-up                           | 128CH        | 190CH        | 251CH        |                  | Tune-up                           | 128CH        | 190CH        | 251CH        |
| GSM (CS)          |                   | 33.50                             | 32.58        | 32.57        | 32.57        | -9.19            | 24.31                             | 23.39        | 23.38        | 23.38        |
| GPRS /EDGE (GMSK) | 1 Tx Slot         | 33.50                             | 32.16        | 32.30        | 32.26        | -9.19            | 24.31                             | 22.97        | 23.11        | 23.07        |
|                   | <b>2 Tx Slots</b> | <b>31.50</b>                      | <b>30.43</b> | <b>30.44</b> | <b>30.42</b> | <b>-6.13</b>     | <b>25.37</b>                      | <b>24.30</b> | <b>24.31</b> | <b>24.29</b> |
|                   | 3 Tx Slots        | 29.50                             | 28.46        | 28.47        | 28.40        | -4.42            | 25.08                             | 24.04        | 24.05        | 23.98        |
|                   | 4 Tx Slots        | 27.50                             | 26.40        | 26.37        | 26.33        | -3.18            | 24.32                             | 23.22        | 23.19        | 23.15        |
| EDGE (8PSK)       | 1 Tx Slot         | 27.00                             | 26.29        | 26.24        | 26.17        | -9.19            | 17.81                             | 17.10        | 17.05        | 16.98        |
|                   | 2 Tx Slots        | 25.00                             | 24.03        | 24.02        | 23.71        | -6.13            | 18.87                             | 17.90        | 17.89        | 17.58        |
|                   | 3 Tx Slots        | 23.00                             | 21.94        | 21.85        | 21.82        | -4.42            | 18.58                             | 17.52        | 17.43        | 17.40        |
|                   | 4 Tx Slots        | 21.00                             | 19.89        | 19.86        | 19.72        | -3.18            | 17.82                             | 16.71        | 16.68        | 16.54        |

Table 46: Conducted power measurement results of GSM850

Note:

- 1) The conducted power of GSM850 is measured with RMS detector.
- 2) Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- 3) Per KDB941225 D01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

### 7.1.13 Conducted power measurements of GSM1900 (Main Antenna)

| GSM1900           |            | Burst-Averaged output Power (dBm) |              |              |              | Division Factors | Frame-Averaged output Power (dBm) |              |              |              |
|-------------------|------------|-----------------------------------|--------------|--------------|--------------|------------------|-----------------------------------|--------------|--------------|--------------|
|                   |            | Tune-up                           | 512CH        | 661CH        | 810CH        |                  | Tune-up                           | 512CH        | 661CH        | 810CH        |
| GSM (CS)          |            | <b>30.00</b>                      | <b>29.21</b> | <b>28.87</b> | <b>28.57</b> | <b>-9.19</b>     | <b>20.81</b>                      | <b>20.02</b> | <b>19.68</b> | <b>19.38</b> |
| GPRS /EDGE (GMSK) | 1 Tx Slot  | 30.00                             | 29.20        | 28.90        | 28.59        | -9.19            | 20.81                             | 20.01        | 19.71        | 19.40        |
|                   | 2 Tx Slots | 28.00                             | 26.77        | 26.74        | 26.67        | -6.13            | 21.87                             | 20.64        | 20.61        | 20.54        |
|                   | 3 Tx Slots | 26.00                             | 24.95        | 24.74        | 24.68        | -4.42            | 21.58                             | 20.53        | 20.32        | 20.26        |
|                   | 4 Tx Slots | 24.50                             | 23.36        | 23.18        | 23.14        | -3.18            | 21.32                             | 20.18        | 20.00        | 19.96        |
| EDGE (8PSK)       | 1 Tx Slot  | 26.00                             | 25.03        | 24.61        | 24.55        | -9.19            | 16.81                             | 15.84        | 15.42        | 15.36        |
|                   | 2 Tx Slots | 24.00                             | 22.86        | 22.45        | 22.34        | -6.13            | 17.87                             | 16.73        | 16.32        | 16.21        |
|                   | 3 Tx Slots | 21.50                             | 20.47        | 20.09        | 20.17        | -4.42            | 17.08                             | 16.05        | 15.67        | 15.75        |
|                   | 4 Tx Slots | 20.00                             | 18.81        | 18.56        | 18.35        | -3.18            | 16.82                             | 15.63        | 15.38        | 15.17        |

Table 47: Conducted power measurement results of GSM1900 (Full power)

| GSM1900           |                   | Burst-Averaged output Power (dBm) |              |              |              | Division Factors | Frame-Averaged output Power (dBm) |              |              |              |
|-------------------|-------------------|-----------------------------------|--------------|--------------|--------------|------------------|-----------------------------------|--------------|--------------|--------------|
|                   |                   | Tune-up                           | 512CH        | 661CH        | 810CH        |                  | Tune-up                           | 512CH        | 661CH        | 810CH        |
| GSM (CS)          |                   | 28.00                             | 26.97        | 26.75        | 26.74        | -9.19            | 18.81                             | 17.78        | 17.56        | 17.55        |
| GPRS /EDGE (GMSK) | 1 Tx Slot         | 28.00                             | 26.98        | 26.77        | 26.75        | -9.19            | 18.81                             | 17.79        | 17.58        | 17.56        |
|                   | <b>2 Tx Slots</b> | <b>26.00</b>                      | <b>25.00</b> | <b>24.77</b> | <b>24.71</b> | <b>-6.13</b>     | <b>19.87</b>                      | <b>18.87</b> | <b>18.64</b> | <b>18.58</b> |
|                   | 3 Tx Slots        | 24.00                             | 22.89        | 22.71        | 22.70        | -4.42            | 19.58                             | 18.47        | 18.29        | 18.28        |
|                   | 4 Tx Slots        | 22.50                             | 21.46        | 21.32        | 21.26        | -3.18            | 19.32                             | 18.28        | 18.14        | 18.08        |
| EDGE (8PSK)       | 1 Tx Slot         | 26.00                             | 25.03        | 24.61        | 24.55        | -9.19            | 16.81                             | 15.84        | 15.42        | 15.36        |
|                   | 2 Tx Slots        | 24.00                             | 22.86        | 22.45        | 22.34        | -6.13            | 17.87                             | 16.73        | 16.32        | 16.21        |
|                   | 3 Tx Slots        | 21.50                             | 20.47        | 20.09        | 20.17        | -4.42            | 17.08                             | 16.05        | 15.67        | 15.75        |
|                   | 4 Tx Slots        | 20.00                             | 18.81        | 18.56        | 18.35        | -3.18            | 16.82                             | 15.63        | 15.38        | 15.17        |

Table 48: Conducted power measurement results of GSM1900 (Proximity sensor on)

Note:

- 1) The conducted power of GSM1900 is measured with RMS detector.
- 2) Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- 3) Per KDB941225 D01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

#### 7.1.14 Conducted power measurements of UMTS Band II (Main Antenna)

| UMTS1900<br>(Band II) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 9262CH              | 9400CH       | 9538CH       |
| WCDMA                 | 12.2kbps RMC | <b>24.00</b> | <b>22.92</b>        | <b>22.91</b> | <b>23.01</b> |
|                       | 12.2kbps AMR | 24.00        | 22.98               | 22.96        | 23.09        |
| HSDPA                 | Subtest 1    | 23.00        | 22.19               | 22.13        | 22.17        |
|                       | Subtest 2    | 23.00        | 22.11               | 22.14        | 22.19        |
|                       | Subtest 3    | 22.00        | 21.54               | 21.77        | 21.22        |
|                       | Subtest 4    | 22.00        | 21.53               | 21.75        | 21.22        |
| HSUPA                 | Subtest 1    | 22.00        | 21.41               | 21.84        | 21.46        |
|                       | Subtest 2    | 19.50        | 18.62               | 18.81        | 19.12        |
|                       | Subtest 3    | 20.50        | 19.31               | 19.79        | 19.85        |
|                       | Subtest 4    | 20.00        | 19.19               | 19.35        | 19.17        |
|                       | Subtest 5    | 22.50        | 21.89               | 21.88        | 21.98        |
| DC-HSDPA              | Subtest 1    | 23.00        | 22.25               | 22.46        | 22.89        |
|                       | Subtest 2    | 23.00        | 22.21               | 22.43        | 22.75        |
|                       | Subtest 3    | 22.00        | 21.53               | 21.75        | 21.21        |
|                       | Subtest 4    | 22.00        | 21.51               | 21.71        | 21.28        |

Table 49: Conducted power measurement results of UMTS Band II (Full power)

| UMTS1900<br>(Band II) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 9262CH              | 9400CH       | 9538CH       |
| WCDMA                 | 12.2kbps RMC | <b>21.00</b> | <b>20.01</b>        | <b>19.97</b> | <b>20.13</b> |
|                       | 12.2kbps AMR | 21.00        | 19.97               | 20.00        | 20.06        |
| HSDPA                 | Subtest 1    | 20.00        | 18.99               | 18.89        | 19.13        |
|                       | Subtest 2    | 20.00        | 18.79               | 18.67        | 18.91        |
|                       | Subtest 3    | 19.00        | 18.22               | 18.11        | 18.32        |
|                       | Subtest 4    | 19.00        | 18.21               | 18.10        | 18.30        |
| HSUPA                 | Subtest 1    | 20.00        | 18.79               | 18.67        | 18.33        |
|                       | Subtest 2    | 16.50        | 15.81               | 15.77        | 16.02        |
|                       | Subtest 3    | 18.00        | 17.13               | 17.01        | 17.13        |
|                       | Subtest 4    | 17.00        | 16.24               | 16.36        | 16.54        |
|                       | Subtest 5    | 20.00        | 18.96               | 18.84        | 19.06        |
| DC-HSDPA              | Subtest 1    | 20.00        | 18.83               | 18.75        | 19.27        |
|                       | Subtest 2    | 20.00        | 18.97               | 18.60        | 18.83        |
|                       | Subtest 3    | 19.50        | 18.04               | 18.04        | 18.33        |
|                       | Subtest 4    | 19.50        | 18.22               | 18.00        | 18.25        |

Table 50: Conducted power measurement results of UMTS Band II (Hotspot on)

| UMTS1900<br>(Band II) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 9262CH              | 9400CH       | 9538CH       |
| WCDMA                 | 12.2kbps RMC | <b>22.00</b> | <b>20.92</b>        | <b>20.97</b> | <b>21.11</b> |
|                       | 12.2kbps AMR | 22.00        | 20.91               | 20.98        | 21.09        |
| HSDPA                 | Subtest 1    | 21.00        | 19.88               | 19.90        | 20.04        |
|                       | Subtest 2    | 21.00        | 19.64               | 19.66        | 19.82        |
|                       | Subtest 3    | 20.00        | 19.07               | 19.08        | 19.26        |
|                       | Subtest 4    | 20.00        | 19.07               | 19.07        | 19.24        |
| HSUPA                 | Subtest 1    | 20.00        | 19.40               | 19.83        | 19.41        |
|                       | Subtest 2    | 17.50        | 16.80               | 16.96        | 16.80        |
|                       | Subtest 3    | 19.00        | 17.90               | 17.90        | 17.59        |
|                       | Subtest 4    | 18.00        | 17.30               | 16.81        | 17.21        |
|                       | Subtest 5    | 21.00        | 19.83               | 19.89        | 20.02        |
| DC-HSDPA              | Subtest 1    | 21.00        | 19.95               | 19.72        | 20.16        |
|                       | Subtest 2    | 21.00        | 19.76               | 19.80        | 19.75        |
|                       | Subtest 3    | 20.50        | 18.91               | 19.01        | 19.31        |
|                       | Subtest 4    | 20.50        | 19.15               | 18.89        | 19.12        |

Table 51: Conducted power measurement results of UMTS Band II (Proximity sensor on)

| UMTS1900<br>(Band II) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 9262CH              | 9400CH       | 9538CH       |
| WCDMA                 | 12.2kbps RMC | <b>19.00</b> | <b>17.92</b>        | <b>17.92</b> | <b>18.07</b> |
|                       | 12.2kbps AMR | 19.00        | 17.93               | 17.94        | 18.05        |
| HSDPA                 | Subtest 1    | 18.00        | 16.90               | 16.96        | 17.13        |
|                       | Subtest 2    | 18.00        | 16.64               | 16.71        | 16.86        |
|                       | Subtest 3    | 17.00        | 16.43               | 16.22        | 16.30        |
|                       | Subtest 4    | 17.00        | 16.36               | 16.23        | 16.32        |
| HSUPA                 | Subtest 1    | 17.00        | 15.80               | 16.04        | 17.00        |
|                       | Subtest 2    | 14.50        | 13.58               | 13.71        | 13.89        |
|                       | Subtest 3    | 15.50        | 14.56               | 14.61        | 14.29        |
|                       | Subtest 4    | 15.00        | 14.12               | 14.41        | 14.56        |
|                       | Subtest 5    | 17.50        | 16.81               | 16.87        | 16.89        |
| DC-HSDPA              | Subtest 1    | 18.00        | 16.89               | 17.02        | 17.14        |
|                       | Subtest 2    | 18.00        | 16.61               | 16.61        | 16.83        |
|                       | Subtest 3    | 17.00        | 16.51               | 16.34        | 16.14        |
|                       | Subtest 4    | 17.00        | 16.31               | 16.43        | 16.46        |

Table 52: Conducted power measurement results of UMTS Band II (Proximity sensor on+hotspot on)

Note:

- 1) The conducted power of UMTS Band II is measured with RMS detector.
- 2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).
- 3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the Second mode.

### 7.1.15 Conducted power measurements of UMTS Band IV (Main Antenna)

| UMTS1700<br>(Band IV) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 1312CH              | 1413CH       | 1513CH       |
| WCDMA                 | 12.2kbps RMC | <b>24.00</b> | <b>22.81</b>        | <b>22.85</b> | <b>22.82</b> |
|                       | 12.2kbps AMR | 24.00        | 22.83               | 22.85        | 22.81        |
| HSDPA                 | Subtest 1    | 23.00        | 21.80               | 21.91        | 21.81        |
|                       | Subtest 2    | 23.00        | 21.59               | 21.62        | 21.61        |
|                       | Subtest 3    | 22.50        | 21.12               | 21.20        | 21.16        |
|                       | Subtest 4    | 22.50        | 21.22               | 21.19        | 21.21        |
| HSUPA                 | Subtest 1    | 23.00        | 21.40               | 21.57        | 21.56        |
|                       | Subtest 2    | 20.00        | 18.53               | 18.58        | 18.77        |
|                       | Subtest 3    | 20.00        | 19.08               | 19.04        | 19.60        |
|                       | Subtest 4    | 20.00        | 18.81               | 18.76        | 19.20        |
|                       | Subtest 5    | 23.00        | 21.74               | 21.69        | 21.73        |
| DC-HSDPA              | Subtest 1    | 23.00        | 21.64               | 22.03        | 21.94        |
|                       | Subtest 2    | 23.00        | 21.45               | 21.44        | 21.47        |
|                       | Subtest 3    | 22.50        | 21.22               | 21.19        | 21.26        |
|                       | Subtest 4    | 22.50        | 21.21               | 21.20        | 21.25        |

Table 53: Conducted power measurement results of UMTS Band IV (Full power)

| UMTS1700<br>(Band IV) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 1312CH              | 1413CH       | 1513CH       |
| WCDMA                 | 12.2kbps RMC | <b>21.00</b> | <b>19.86</b>        | <b>19.94</b> | <b>19.88</b> |
|                       | 12.2kbps AMR | 21.00        | 19.85               | 19.96        | 19.89        |
| HSDPA                 | Subtest 1    | 20.00        | 18.82               | 18.93        | 18.85        |
|                       | Subtest 2    | 20.00        | 18.56               | 18.69        | 18.61        |
|                       | Subtest 3    | 19.50        | 18.00               | 18.13        | 18.05        |
|                       | Subtest 4    | 19.50        | 17.99               | 18.11        | 18.03        |
| HSUPA                 | Subtest 1    | 20.00        | 18.47               | 18.54        | 18.54        |
|                       | Subtest 2    | 17.00        | 15.80               | 15.80        | 15.61        |
|                       | Subtest 3    | 18.00        | 16.98               | 17.14        | 17.09        |
|                       | Subtest 4    | 17.00        | 15.86               | 16.24        | 16.23        |
|                       | Subtest 5    | 20.00        | 18.73               | 18.88        | 18.79        |
| DC-HSDPA              | Subtest 1    | 20.00        | 18.93               | 19.08        | 18.89        |
|                       | Subtest 2    | 20.00        | 18.39               | 18.59        | 18.65        |
|                       | Subtest 3    | 19.50        | 18.16               | 18.29        | 17.88        |
|                       | Subtest 4    | 19.50        | 18.15               | 18.23        | 17.96        |

Table 54: Conducted power measurement results of UMTS Band IV (Hotspot on)

| UMTS1700<br>(Band IV) |              | Tune-up | Average Power (dBm) |        |        |
|-----------------------|--------------|---------|---------------------|--------|--------|
|                       |              |         | 1312CH              | 1413CH | 1513CH |
| WCDMA                 | 12.2kbps RMC | 22.00   | 20.89               | 20.93  | 20.91  |
|                       | 12.2kbps AMR | 22.00   | 20.89               | 20.91  | 20.89  |
| HSDPA                 | Subtest 1    | 21.00   | 19.89               | 19.90  | 19.88  |
|                       | Subtest 2    | 21.00   | 19.69               | 19.68  | 19.66  |
|                       | Subtest 3    | 20.50   | 19.10               | 19.10  | 19.07  |
|                       | Subtest 4    | 20.50   | 19.09               | 19.07  | 19.05  |
| HSUPA                 | Subtest 1    | 21.00   | 20.72               | 20.42  | 20.88  |
|                       | Subtest 2    | 18.00   | 16.84               | 16.74  | 16.97  |
|                       | Subtest 3    | 19.00   | 17.69               | 17.85  | 17.65  |
|                       | Subtest 4    | 18.00   | 16.45               | 16.68  | 16.96  |
|                       | Subtest 5    | 21.00   | 19.34               | 19.08  | 19.48  |
| DC-HSDPA              | Subtest 1    | 21.00   | 20.00               | 20.07  | 19.75  |
|                       | Subtest 2    | 21.00   | 19.84               | 19.58  | 19.84  |
|                       | Subtest 3    | 20.50   | 19.16               | 19.03  | 19.13  |
|                       | Subtest 4    | 20.50   | 19.17               | 19.04  | 18.93  |

Table 55: Conducted power measurement results of UMTS Band IV (Proximity sensor on)

| UMTS1700<br>(Band IV) |              | Tune-up      | Average Power (dBm) |              |              |
|-----------------------|--------------|--------------|---------------------|--------------|--------------|
|                       |              |              | 1312CH              | 1413CH       | 1513CH       |
| WCDMA                 | 12.2kbps RMC | <b>18.00</b> | <b>17.52</b>        | <b>17.42</b> | <b>17.51</b> |
|                       | 12.2kbps AMR | 18.00        | 17.50               | 17.51        | 17.41        |
| HSDPA                 | Subtest 1    | 18.00        | 16.88               | 17.54        | 17.64        |
|                       | Subtest 2    | 18.00        | 16.63               | 17.74        | 16.67        |
|                       | Subtest 3    | 17.50        | 16.17               | 16.26        | 16.33        |
|                       | Subtest 4    | 17.00        | 16.44               | 15.83        | 15.95        |
| HSUPA                 | Subtest 1    | 18.50        | 17.75               | 18.04        | 17.95        |
|                       | Subtest 2    | 16.00        | 15.14               | 15.12        | 14.93        |
|                       | Subtest 3    | 17.00        | 16.49               | 16.65        | 16.82        |
|                       | Subtest 4    | 16.00        | 15.66               | 15.79        | 15.72        |
|                       | Subtest 5    | 18.50        | 18.47               | 18.34        | 18.22        |
| DC-HSDPA              | Subtest 1    | 18.00        | 16.52               | 17.49        | 17.59        |
|                       | Subtest 2    | 18.00        | 16.61               | 17.88        | 16.64        |
|                       | Subtest 3    | 17.50        | 16.10               | 16.17        | 16.15        |
|                       | Subtest 4    | 17.00        | 16.32               | 15.99        | 16.07        |

Table 56: Conducted power measurement results of UMTS Band IV (Proximity sensor on+hotspot on)

Note: 1) The conducted power of UMTS Band IV is measured with RMS detector.

2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).

3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the Second mode.

### 7.1.16 Conducted power measurements of UMTS Band V (Main Antenna)

| UMTS850<br>(Band V) |              | Tune-up      | Average Power (dBm) |              |              |
|---------------------|--------------|--------------|---------------------|--------------|--------------|
|                     |              |              | 4132CH              | 4182CH       | 4233CH       |
| WCDMA               | 12.2kbps RMC | <b>24.00</b> | <b>22.90</b>        | <b>22.89</b> | <b>22.92</b> |
|                     | 12.2kbps AMR | 24.00        | 22.93               | 22.80        | 22.89        |
| HSDPA               | Subtest 1    | 23.00        | 22.02               | 22.49        | 22.45        |
|                     | Subtest 2    | 23.00        | 21.82               | 22.26        | 22.18        |
|                     | Subtest 3    | 22.50        | 21.14               | 21.64        | 21.58        |
|                     | Subtest 4    | 22.50        | 21.14               | 21.60        | 21.56        |
| HSUPA               | Subtest 1    | 22.50        | 21.16               | 21.76        | 21.65        |
|                     | Subtest 2    | 20.00        | 18.89               | 19.34        | 19.36        |
|                     | Subtest 3    | 21.00        | 20.22               | 19.92        | 19.79        |
|                     | Subtest 4    | 21.00        | 19.29               | 19.83        | 19.72        |
|                     | Subtest 5    | 22.50        | 21.95               | 21.66        | 22.34        |
| DC-HSDPA            | Subtest 1    | 23.00        | 22.08               | 22.52        | 22.46        |
|                     | Subtest 2    | 23.00        | 21.82               | 22.25        | 22.05        |
|                     | Subtest 3    | 22.50        | 21.32               | 21.80        | 21.52        |
|                     | Subtest 4    | 22.50        | 21.32               | 21.68        | 21.42        |

Table 57: Conducted power measurement results of UMTS Band V

Note:

- 1) The conducted power of UMTS Band V is measured with RMS detector.
- 2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).
- 3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the Second mode.

### 7.1.17 Conducted power measurements of LTE Band II (Main Antenna)

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18607CH              | 18900CH | 19193CH |
| 1.4MHz      | QPSK       | 1       | 0         | 23.50   | 22.28                | 22.82   | 22.84   |
|             |            | 1       | 3         | 23.50   | 22.37                | 22.82   | 22.88   |
|             |            | 1       | 5         | 23.50   | 22.31                | 22.68   | 22.88   |
|             |            | 3       | 0         | 23.50   | 22.42                | 22.81   | 22.87   |
|             |            | 3       | 2         | 23.50   | 22.41                | 22.81   | 22.86   |
|             |            | 3       | 3         | 23.50   | 22.36                | 22.74   | 22.91   |
|             |            | 6       | 0         | 23.00   | 21.36                | 21.90   | 21.92   |
|             | 16QAM      | 1       | 0         | 23.00   | 21.38                | 22.22   | 21.99   |
|             |            | 1       | 3         | 23.00   | 21.38                | 22.25   | 21.99   |
|             |            | 1       | 5         | 23.00   | 21.35                | 22.15   | 21.99   |
|             |            | 3       | 0         | 23.00   | 21.44                | 21.98   | 21.92   |
|             |            | 3       | 2         | 23.00   | 21.43                | 22.00   | 21.89   |
|             |            | 3       | 3         | 23.00   | 21.40                | 21.94   | 21.95   |
|             |            | 6       | 0         | 22.00   | 20.50                | 20.79   | 21.01   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18615CH              | 18900CH | 19185CH |
| 3MHz        | QPSK       | 1       | 0         | 23.50   | 22.30                | 22.77   | 22.82   |
|             |            | 1       | 7         | 23.50   | 22.50                | 23.10   | 22.99   |
|             |            | 1       | 14        | 23.50   | 22.28                | 22.78   | 22.80   |
|             |            | 8       | 0         | 23.00   | 21.43                | 21.91   | 21.86   |
|             |            | 8       | 4         | 23.00   | 21.43                | 21.98   | 21.91   |
|             |            | 8       | 7         | 23.00   | 21.38                | 21.91   | 21.87   |
|             |            | 15      | 0         | 23.00   | 21.41                | 21.97   | 21.90   |
|             | 16QAM      | 1       | 0         | 23.00   | 21.29                | 21.81   | 21.85   |
|             |            | 1       | 7         | 23.00   | 21.45                | 22.04   | 22.00   |
|             |            | 1       | 14        | 23.00   | 21.30                | 21.74   | 21.83   |
|             |            | 8       | 0         | 22.00   | 20.43                | 20.83   | 20.76   |
|             |            | 8       | 4         | 22.00   | 20.44                | 20.84   | 20.79   |
|             |            | 8       | 7         | 22.00   | 20.39                | 20.72   | 20.83   |
|             |            | 15      | 0         | 22.00   | 20.38                | 20.83   | 20.78   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|-----------|------------|---------|-----------|---------|---------|---------|---------|
|           |            |         |           |         | 18625CH | 18900CH | 19175CH |
| 5MHz      | QPSK       | 1       | 0         | 23.50   | 22.49   | 22.89   | 22.84   |
|           |            | 1       | 13        | 23.50   | 22.68   | 23.04   | 23.13   |
|           |            | 1       | 24        | 23.50   | 22.41   | 22.61   | 22.76   |
|           |            | 12      | 0         | 23.00   | 21.66   | 21.99   | 22.09   |
|           |            | 12      | 6         | 23.00   | 21.69   | 22.08   | 22.25   |
|           |            | 12      | 13        | 23.00   | 21.57   | 21.91   | 22.08   |
|           |            | 25      | 0         | 23.00   | 21.57   | 21.95   | 22.14   |
|           | 16QAM      | 1       | 0         | 23.00   | 21.68   | 22.03   | 21.98   |
|           |            | 1       | 13        | 23.00   | 21.83   | 22.16   | 22.40   |
|           |            | 1       | 24        | 23.00   | 21.57   | 21.77   | 22.00   |
|           |            | 12      | 0         | 22.00   | 20.68   | 21.04   | 20.93   |
|           |            | 12      | 6         | 22.00   | 20.67   | 21.11   | 21.09   |
|           |            | 12      | 13        | 22.00   | 20.60   | 20.90   | 20.91   |
|           |            | 25      | 0         | 22.00   | 20.53   | 20.89   | 20.94   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|           |            |         |           |         | 18650CH | 18900CH | 19150CH |
| 10MHz     | QPSK       | 1       | 0         | 24.00   | 23.36   | 23.46   | 23.40   |
|           |            | 1       | 25        | 24.00   | 22.85   | 23.08   | 23.08   |
|           |            | 1       | 49        | 24.00   | 22.62   | 22.79   | 22.86   |
|           |            | 25      | 0         | 23.00   | 21.69   | 21.99   | 21.90   |
|           |            | 25      | 13        | 23.00   | 21.84   | 21.99   | 21.97   |
|           |            | 25      | 25        | 23.00   | 21.74   | 21.92   | 22.06   |
|           |            | 50      | 0         | 23.00   | 21.68   | 22.05   | 22.12   |
|           | 16QAM      | 1       | 0         | 23.00   | 22.34   | 22.64   | 22.52   |
|           |            | 1       | 25        | 23.00   | 22.05   | 22.24   | 21.97   |
|           |            | 1       | 49        | 23.00   | 21.87   | 21.96   | 21.81   |
|           |            | 25      | 0         | 22.00   | 20.57   | 21.00   | 20.87   |
|           |            | 25      | 13        | 22.00   | 20.71   | 20.95   | 20.95   |
|           |            | 25      | 25        | 22.00   | 20.61   | 20.88   | 20.91   |
|           |            | 50      | 0         | 22.00   | 20.57   | 20.96   | 20.96   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 18675CH      | 18900CH      | 19125CH      |
| 15MHz     | QPSK       | 1       | 0         | 23.50   | 22.21        | 22.68        | 22.82        |
|           |            | 1       | 38        | 23.50   | 22.87        | 23.09        | 23.01        |
|           |            | 1       | 74        | 23.50   | 22.43        | 22.57        | 22.59        |
|           |            | 36      | 0         | 23.00   | 21.61        | 21.98        | 21.99        |
|           |            | 36      | 18        | 23.00   | 21.83        | 22.11        | 21.94        |
|           |            | 36      | 39        | 23.00   | 21.70        | 21.92        | 21.79        |
|           |            | 75      | 0         | 23.00   | 21.71        | 21.87        | 21.96        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.40        | 21.82        | 21.79        |
|           |            | 1       | 38        | 23.00   | 22.08        | 22.15        | 21.97        |
|           |            | 1       | 74        | 23.00   | 21.62        | 21.66        | 21.60        |
|           |            | 36      | 0         | 22.00   | 20.58        | 21.01        | 20.90        |
|           |            | 36      | 18        | 22.00   | 20.80        | 21.09        | 20.93        |
|           |            | 36      | 39        | 22.00   | 20.67        | 20.89        | 20.77        |
|           |            | 75      | 0         | 22.00   | 20.60        | 20.81        | 20.96        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 18700CH      | 18900CH      | 19100CH      |
| 20MHz     | QPSK       | 1       | 0         | 23.50   | <b>22.23</b> | 21.55        | 22.30        |
|           |            | 1       | 50        | 23.50   | 22.11        | <b>22.67</b> | 22.09        |
|           |            | 1       | 99        | 23.50   | 21.57        | 22.23        | <b>22.32</b> |
|           |            | 50      | 0         | 23.00   | 21.59        | 21.88        | 21.92        |
|           |            | 50      | 25        | 23.00   | 21.69        | <b>22.07</b> | 21.98        |
|           |            | 50      | 50        | 23.00   | 21.60        | 21.88        | 21.83        |
|           |            | 100     | 0         | 23.00   | 21.61        | 21.80        | 21.86        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.67        | 21.82        | 22.06        |
|           |            | 1       | 50        | 23.00   | 22.41        | 22.39        | 22.35        |
|           |            | 1       | 99        | 23.00   | 21.63        | 21.88        | 21.93        |
|           |            | 50      | 0         | 22.00   | 20.49        | 20.83        | 20.89        |
|           |            | 50      | 25        | 22.00   | 20.66        | 21.04        | 20.97        |
|           |            | 50      | 50        | 22.00   | 20.56        | 20.79        | 20.83        |
|           |            | 100     | 0         | 22.00   | 20.58        | 20.70        | 20.85        |

Table 58: Conducted power measurement results of LTE Band II (Full power)

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18607CH              | 18900CH | 19193CH |
| 1.4MHz      | QPSK       | 1       | 0         | 22.00   | 20.38                | 20.89   | 20.87   |
|             |            | 1       | 3         | 22.00   | 20.43                | 20.88   | 20.93   |
|             |            | 1       | 5         | 22.00   | 20.32                | 20.72   | 20.87   |
|             |            | 3       | 0         | 22.00   | 20.37                | 20.90   | 20.90   |
|             |            | 3       | 2         | 22.00   | 20.34                | 20.89   | 20.90   |
|             |            | 3       | 3         | 22.00   | 20.35                | 20.82   | 20.91   |
|             |            | 6       | 0         | 21.00   | 19.48                | 19.95   | 20.00   |
|             | 16QAM      | 1       | 0         | 21.00   | 19.62                | 20.20   | 20.16   |
|             |            | 1       | 3         | 21.00   | 19.59                | 20.21   | 20.20   |
|             |            | 1       | 5         | 21.00   | 19.48                | 20.04   | 20.13   |
|             |            | 3       | 0         | 21.00   | 19.53                | 19.98   | 20.07   |
|             |            | 3       | 2         | 21.00   | 19.54                | 19.98   | 20.08   |
|             |            | 3       | 3         | 21.00   | 19.49                | 19.89   | 20.06   |
|             |            | 6       | 0         | 20.00   | 18.61                | 19.01   | 19.12   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18615CH              | 18900CH | 19185CH |
| 3MHz        | QPSK       | 1       | 0         | 22.00   | 20.33                | 20.81   | 20.80   |
|             |            | 1       | 7         | 22.00   | 20.48                | 20.99   | 21.03   |
|             |            | 1       | 14        | 22.00   | 20.22                | 20.68   | 20.82   |
|             |            | 8       | 0         | 21.00   | 19.50                | 19.98   | 19.93   |
|             |            | 8       | 4         | 21.00   | 19.51                | 19.95   | 19.98   |
|             |            | 8       | 7         | 21.00   | 19.44                | 19.87   | 19.93   |
|             |            | 15      | 0         | 21.00   | 19.47                | 19.93   | 19.97   |
|             | 16QAM      | 1       | 0         | 21.00   | 19.47                | 19.91   | 19.92   |
|             |            | 1       | 7         | 21.00   | 19.65                | 20.11   | 20.11   |
|             |            | 1       | 14        | 21.00   | 19.40                | 19.73   | 19.89   |
|             |            | 8       | 0         | 20.00   | 18.46                | 19.03   | 18.92   |
|             |            | 8       | 4         | 20.00   | 18.43                | 19.04   | 18.95   |
|             |            | 8       | 7         | 20.00   | 18.37                | 18.95   | 18.89   |
|             |            | 15      | 0         | 20.00   | 18.41                | 18.99   | 18.99   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|-----------|------------|---------|-----------|---------|---------|---------|---------|
|           |            |         |           |         | 18625CH | 18900CH | 19175CH |
| 5MHz      | QPSK       | 1       | 0         | 22.00   | 20.60   | 20.99   | 20.89   |
|           |            | 1       | 13        | 22.00   | 20.78   | 21.23   | 21.21   |
|           |            | 1       | 24        | 22.00   | 20.44   | 20.74   | 20.79   |
|           |            | 12      | 0         | 21.00   | 19.79   | 20.15   | 20.02   |
|           |            | 12      | 6         | 21.00   | 19.80   | 20.25   | 20.18   |
|           |            | 12      | 13        | 21.00   | 19.65   | 20.00   | 20.00   |
|           |            | 25      | 0         | 21.00   | 19.66   | 20.11   | 20.06   |
|           | 16QAM      | 1       | 0         | 21.00   | 19.83   | 20.50   | 20.23   |
|           |            | 1       | 13        | 21.00   | 19.97   | 20.65   | 20.55   |
|           |            | 1       | 24        | 21.00   | 19.65   | 20.11   | 20.13   |
|           |            | 12      | 0         | 20.00   | 18.73   | 19.25   | 19.01   |
|           |            | 12      | 6         | 20.00   | 18.74   | 19.34   | 19.19   |
|           |            | 12      | 13        | 20.00   | 18.59   | 19.11   | 19.04   |
|           |            | 25      | 0         | 20.00   | 18.60   | 19.18   | 19.07   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|           |            |         |           |         | 18650CH | 18900CH | 19150CH |
| 10MHz     | QPSK       | 1       | 0         | 22.00   | 21.28   | 21.68   | 21.68   |
|           |            | 1       | 25        | 22.00   | 20.97   | 21.28   | 21.15   |
|           |            | 1       | 49        | 22.00   | 20.68   | 20.89   | 20.89   |
|           |            | 25      | 0         | 21.00   | 19.77   | 20.16   | 20.05   |
|           |            | 25      | 13        | 21.00   | 19.90   | 20.16   | 20.06   |
|           |            | 25      | 25        | 21.00   | 19.73   | 20.01   | 20.00   |
|           |            | 50      | 0         | 21.00   | 19.69   | 20.15   | 20.13   |
|           | 16QAM      | 1       | 0         | 21.00   | 20.70   | 20.97   | 20.88   |
|           |            | 1       | 25        | 21.00   | 20.32   | 20.64   | 20.31   |
|           |            | 1       | 49        | 21.00   | 19.92   | 20.24   | 19.98   |
|           |            | 25      | 0         | 20.00   | 18.69   | 19.20   | 19.00   |
|           |            | 25      | 13        | 20.00   | 18.83   | 19.22   | 19.06   |
|           |            | 25      | 25        | 20.00   | 18.69   | 19.08   | 19.02   |
|           |            | 50      | 0         | 20.00   | 18.68   | 19.16   | 19.12   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 18675CH      | 18900CH      | 19125CH      |
| 15MHz     | QPSK       | 1       | 0         | 22.00   | 20.38        | 20.74        | 20.84        |
|           |            | 1       | 38        | 22.00   | 21.04        | 21.24        | 21.13        |
|           |            | 1       | 74        | 22.00   | 20.58        | 20.61        | 20.52        |
|           |            | 36      | 0         | 21.00   | 19.76        | 20.15        | 20.11        |
|           |            | 36      | 18        | 21.00   | 19.90        | 20.18        | 20.03        |
|           |            | 36      | 39        | 21.00   | 19.72        | 20.00        | 19.88        |
|           |            | 75      | 0         | 21.00   | 19.72        | 20.02        | 20.09        |
|           | 16QAM      | 1       | 0         | 21.00   | 19.64        | 20.08        | 19.95        |
|           |            | 1       | 38        | 21.00   | 20.31        | 20.50        | 20.24        |
|           |            | 1       | 74        | 21.00   | 19.81        | 19.96        | 19.74        |
|           |            | 36      | 0         | 20.00   | 18.73        | 19.22        | 19.08        |
|           |            | 36      | 18        | 20.00   | 18.89        | 19.21        | 19.08        |
|           |            | 36      | 39        | 20.00   | 18.75        | 19.03        | 18.94        |
|           |            | 75      | 0         | 20.00   | 18.68        | 19.02        | 19.15        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 18700CH      | 18900CH      | 19100CH      |
| 20MHz     | QPSK       | 1       | 0         | 22.00   | 20.62        | 20.77        | 21.12        |
|           |            | 1       | 50        | 22.00   | <b>21.45</b> | <b>21.31</b> | <b>21.60</b> |
|           |            | 1       | 99        | 22.00   | 20.59        | 20.97        | 20.98        |
|           |            | 50      | 0         | 21.00   | 19.59        | 20.00        | 19.99        |
|           |            | 50      | 25        | 21.00   | 19.77        | <b>20.15</b> | 20.08        |
|           |            | 50      | 50        | 21.00   | 19.67        | 19.95        | 19.88        |
|           |            | 100     | 0         | 21.00   | 19.70        | 19.92        | <b>19.95</b> |
|           | 16QAM      | 1       | 0         | 21.00   | 19.73        | 20.00        | 20.19        |
|           |            | 1       | 50        | 21.00   | 20.55        | 20.60        | 20.70        |
|           |            | 1       | 99        | 21.00   | 19.81        | 20.12        | 19.98        |
|           |            | 50      | 0         | 20.00   | 18.60        | 19.04        | 19.03        |
|           |            | 50      | 25        | 20.00   | 18.74        | 19.20        | 19.13        |
|           |            | 50      | 50        | 20.00   | 18.64        | 18.92        | 18.98        |
|           |            | 100     | 0         | 20.00   | 18.69        | 18.90        | 18.97        |

Table 59: Conducted power measurement results of LTE Band II (Proximity sensor on)

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18607CH              | 18900CH | 19193CH |
| 1.4MHz      | QPSK       | 1       | 0         | 19.70   | 18.04                | 18.58   | 18.62   |
|             |            | 1       | 3         | 19.70   | 18.03                | 18.65   | 18.67   |
|             |            | 1       | 5         | 19.70   | 17.96                | 18.50   | 18.60   |
|             |            | 3       | 0         | 19.70   | 18.09                | 18.62   | 18.58   |
|             |            | 3       | 2         | 19.70   | 18.07                | 18.63   | 18.54   |
|             |            | 3       | 3         | 19.70   | 18.02                | 18.56   | 18.54   |
|             |            | 6       | 0         | 19.70   | 18.03                | 18.60   | 18.52   |
|             | 16QAM      | 1       | 0         | 19.70   | 18.08                | 18.81   | 18.69   |
|             |            | 1       | 3         | 19.70   | 18.07                | 18.81   | 18.71   |
|             |            | 1       | 5         | 19.70   | 17.97                | 18.63   | 18.73   |
|             |            | 3       | 0         | 19.70   | 18.04                | 18.69   | 18.72   |
|             |            | 3       | 2         | 19.70   | 18.02                | 18.65   | 18.68   |
|             |            | 3       | 3         | 19.70   | 17.98                | 18.63   | 18.70   |
|             |            | 6       | 0         | 19.70   | 18.05                | 18.57   | 18.58   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18615CH              | 18900CH | 19185CH |
| 3MHz        | QPSK       | 1       | 0         | 19.70   | 17.93                | 18.48   | 18.51   |
|             |            | 1       | 7         | 19.70   | 18.07                | 18.74   | 18.70   |
|             |            | 1       | 14        | 19.70   | 17.79                | 18.37   | 18.40   |
|             |            | 8       | 0         | 19.70   | 18.03                | 18.56   | 18.56   |
|             |            | 8       | 4         | 19.70   | 18.01                | 18.59   | 18.59   |
|             |            | 8       | 7         | 19.70   | 17.94                | 18.50   | 18.47   |
|             |            | 15      | 0         | 19.70   | 17.99                | 18.57   | 18.57   |
|             | 16QAM      | 1       | 0         | 19.70   | 18.21                | 18.64   | 18.55   |
|             |            | 1       | 7         | 19.70   | 18.32                | 18.87   | 18.72   |
|             |            | 1       | 14        | 19.70   | 18.04                | 18.52   | 18.51   |
|             |            | 8       | 0         | 19.70   | 17.97                | 18.51   | 18.57   |
|             |            | 8       | 4         | 19.70   | 17.96                | 18.56   | 18.54   |
|             |            | 8       | 7         | 19.70   | 17.90                | 18.45   | 18.48   |
|             |            | 15      | 0         | 19.70   | 17.93                | 18.52   | 18.55   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|-----------|------------|---------|-----------|---------|---------|---------|---------|
|           |            |         |           |         | 18625CH | 18900CH | 19175CH |
| 5MHz      | QPSK       | 1       | 0         | 19.70   | 18.20   | 18.63   | 18.45   |
|           |            | 1       | 13        | 19.70   | 18.35   | 18.86   | 18.78   |
|           |            | 1       | 24        | 19.70   | 17.97   | 18.35   | 18.37   |
|           |            | 12      | 0         | 19.70   | 18.29   | 18.73   | 18.64   |
|           |            | 12      | 6         | 19.70   | 18.34   | 18.83   | 18.79   |
|           |            | 12      | 13        | 19.70   | 18.19   | 18.63   | 18.61   |
|           |            | 25      | 0         | 19.70   | 18.20   | 18.68   | 18.66   |
|           | 16QAM      | 1       | 0         | 19.70   | 18.52   | 19.03   | 18.70   |
|           |            | 1       | 13        | 19.70   | 18.68   | 19.18   | 19.03   |
|           |            | 1       | 24        | 19.70   | 18.29   | 18.75   | 18.70   |
|           |            | 12      | 0         | 19.70   | 18.32   | 18.76   | 18.57   |
|           |            | 12      | 6         | 19.70   | 18.30   | 18.89   | 18.73   |
|           |            | 12      | 13        | 19.70   | 18.20   | 18.67   | 18.54   |
|           |            | 25      | 0         | 19.70   | 18.11   | 18.67   | 18.65   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|           |            |         |           |         | 18650CH | 18900CH | 19150CH |
| 10MHz     | QPSK       | 1       | 0         | 19.70   | 18.84   | 19.31   | 19.28   |
|           |            | 1       | 25        | 19.70   | 18.55   | 18.90   | 18.76   |
|           |            | 1       | 49        | 19.70   | 18.19   | 18.51   | 18.41   |
|           |            | 25      | 0         | 19.70   | 18.28   | 18.72   | 18.60   |
|           |            | 25      | 13        | 19.70   | 18.40   | 18.73   | 18.63   |
|           |            | 25      | 25        | 19.70   | 18.26   | 18.61   | 18.58   |
|           |            | 50      | 0         | 19.70   | 18.22   | 18.75   | 18.65   |
|           | 16QAM      | 1       | 0         | 19.70   | 19.12   | 19.52   | 19.28   |
|           |            | 1       | 25        | 19.70   | 18.74   | 19.02   | 18.76   |
|           |            | 1       | 49        | 19.70   | 18.45   | 18.63   | 18.34   |
|           |            | 25      | 0         | 19.70   | 18.20   | 18.67   | 18.60   |
|           |            | 25      | 13        | 19.70   | 18.32   | 18.68   | 18.57   |
|           |            | 25      | 25        | 19.70   | 18.19   | 18.56   | 18.58   |
|           |            | 50      | 0         | 19.70   | 18.19   | 18.69   | 18.66   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 18675CH      | 18900CH      | 19125CH      |
| 15MHz     | QPSK       | 1       | 0         | 19.70   | 17.90        | 18.31        | 18.42        |
|           |            | 1       | 38        | 19.70   | 18.57        | 18.85        | 18.79        |
|           |            | 1       | 74        | 19.70   | 18.08        | 18.12        | 18.09        |
|           |            | 36      | 0         | 19.70   | 18.23        | 18.68        | 18.65        |
|           |            | 36      | 18        | 19.70   | 18.41        | 18.74        | 18.63        |
|           |            | 36      | 39        | 19.70   | 18.31        | 18.60        | 18.44        |
|           |            | 75      | 0         | 19.70   | 18.28        | 18.55        | 18.68        |
|           | 16QAM      | 1       | 0         | 19.70   | 18.16        | 18.61        | 18.57        |
|           |            | 1       | 38        | 19.70   | 18.79        | 19.18        | 18.84        |
|           |            | 1       | 74        | 19.70   | 18.42        | 18.43        | 18.12        |
|           |            | 36      | 0         | 19.70   | 18.14        | 18.65        | 18.65        |
|           |            | 36      | 18        | 19.70   | 18.33        | 18.71        | 18.57        |
|           |            | 36      | 39        | 19.70   | 18.23        | 18.57        | 18.38        |
|           |            | 75      | 0         | 19.70   | 18.21        | 18.50        | 18.65        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 18700CH      | 18900CH      | 19100CH      |
| 20MHz     | QPSK       | 1       | 0         | 19.70   | 17.82        | 18.17        | 18.33        |
|           |            | 1       | 50        | 19.70   | 18.68        | 18.84        | <b>18.85</b> |
|           |            | 1       | 99        | 19.70   | 18.04        | 18.19        | 18.02        |
|           |            | 50      | 0         | 19.70   | 18.15        | 18.52        | 18.57        |
|           |            | 50      | 25        | 19.70   | <b>18.35</b> | <b>18.76</b> | <b>18.67</b> |
|           |            | 50      | 50        | 19.70   | 18.21        | 18.53        | 18.45        |
|           |            | 100     | 0         | 19.70   | 18.26        | 18.44        | 18.52        |
|           | 16QAM      | 1       | 0         | 19.70   | 18.18        | 18.59        | 18.82        |
|           |            | 1       | 50        | 19.70   | 18.93        | 19.19        | 19.31        |
|           |            | 1       | 99        | 19.70   | 18.39        | 18.58        | 18.48        |
|           |            | 50      | 0         | 19.70   | 18.10        | 18.48        | 18.59        |
|           |            | 50      | 25        | 19.70   | 18.30        | 18.70        | 18.62        |
|           |            | 50      | 50        | 19.70   | 18.18        | 18.47        | 18.44        |
|           |            | 100     | 0         | 19.70   | 18.20        | 18.37        | 18.55        |

Table 60: Conducted power measurement results of LTE Band II (Hotspot on)

| LTE Band II |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18607CH              | 18900CH | 19193CH |
| 1.4MHz      | QPSK       | 1       | 0         | 17.80   | 16.21                | 16.70   | 16.72   |
|             |            | 1       | 3         | 17.80   | 16.26                | 16.77   | 16.75   |
|             |            | 1       | 5         | 17.80   | 16.09                | 16.59   | 16.67   |
|             |            | 3       | 0         | 17.80   | 16.21                | 16.72   | 16.66   |
|             |            | 3       | 2         | 17.80   | 16.20                | 16.74   | 16.70   |
|             |            | 3       | 3         | 17.80   | 16.14                | 16.66   | 16.71   |
|             |            | 6       | 0         | 17.80   | 16.15                | 16.76   | 16.70   |
|             | 16QAM      | 1       | 0         | 17.80   | 16.34                | 17.11   | 16.66   |
|             |            | 1       | 3         | 17.80   | 16.33                | 17.13   | 16.82   |
|             |            | 1       | 5         | 17.80   | 16.15                | 16.98   | 16.72   |
|             |            | 3       | 0         | 17.80   | 16.25                | 16.84   | 16.74   |
|             |            | 3       | 2         | 17.80   | 16.23                | 16.86   | 16.72   |
|             |            | 3       | 3         | 17.80   | 16.19                | 16.79   | 16.73   |
|             |            | 6       | 0         | 17.80   | 16.12                | 16.68   | 16.72   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 18615CH              | 18900CH | 19185CH |
| 3MHz        | QPSK       | 1       | 0         | 17.80   | 15.96                | 16.53   | 16.59   |
|             |            | 1       | 7         | 17.80   | 16.27                | 16.86   | 16.84   |
|             |            | 1       | 14        | 17.80   | 15.90                | 16.35   | 16.50   |
|             |            | 8       | 0         | 17.80   | 16.14                | 16.68   | 16.66   |
|             |            | 8       | 4         | 17.80   | 16.15                | 16.74   | 16.67   |
|             |            | 8       | 7         | 17.80   | 16.06                | 16.55   | 16.59   |
|             |            | 15      | 0         | 17.80   | 16.08                | 16.68   | 16.63   |
|             | 16QAM      | 1       | 0         | 17.80   | 16.27                | 16.52   | 16.76   |
|             |            | 1       | 7         | 17.80   | 16.51                | 16.77   | 17.01   |
|             |            | 1       | 14        | 17.80   | 16.14                | 16.35   | 16.68   |
|             |            | 8       | 0         | 17.80   | 16.16                | 16.69   | 16.68   |
|             |            | 8       | 4         | 17.80   | 16.18                | 16.67   | 16.66   |
|             |            | 8       | 7         | 17.80   | 16.09                | 16.57   | 16.59   |
|             |            | 15      | 0         | 17.80   | 16.06                | 16.58   | 16.58   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|-----------|------------|---------|-----------|---------|---------|---------|---------|
|           |            |         |           |         | 18625CH | 18900CH | 19175CH |
| 5MHz      | QPSK       | 1       | 0         | 17.80   | 16.35   | 16.61   | 16.55   |
|           |            | 1       | 13        | 17.80   | 16.52   | 16.87   | 16.84   |
|           |            | 1       | 24        | 17.80   | 16.07   | 16.36   | 16.44   |
|           |            | 12      | 0         | 17.80   | 16.42   | 16.74   | 16.78   |
|           |            | 12      | 6         | 17.80   | 16.44   | 16.86   | 16.86   |
|           |            | 12      | 13        | 17.80   | 16.34   | 16.66   | 16.66   |
|           |            | 25      | 0         | 17.80   | 16.36   | 16.75   | 16.73   |
|           | 16QAM      | 1       | 0         | 17.80   | 16.52   | 16.98   | 17.03   |
|           |            | 1       | 13        | 17.80   | 16.69   | 17.17   | 17.44   |
|           |            | 1       | 24        | 17.80   | 16.27   | 16.70   | 16.97   |
|           |            | 12      | 0         | 17.80   | 16.52   | 16.80   | 16.76   |
|           |            | 12      | 6         | 17.80   | 16.56   | 16.89   | 16.89   |
|           |            | 12      | 13        | 17.80   | 16.39   | 16.69   | 16.69   |
|           |            | 25      | 0         | 17.80   | 16.36   | 16.72   | 16.82   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|           |            |         |           |         | 18650CH | 18900CH | 19150CH |
| 10MHz     | QPSK       | 1       | 0         | 17.80   | 17.01   | 17.40   | 17.43   |
|           |            | 1       | 25        | 17.80   | 16.71   | 17.01   | 16.94   |
|           |            | 1       | 49        | 17.80   | 16.27   | 16.58   | 16.54   |
|           |            | 25      | 0         | 17.80   | 16.43   | 16.78   | 16.78   |
|           |            | 25      | 13        | 17.80   | 16.54   | 16.81   | 16.76   |
|           |            | 25      | 25        | 17.80   | 16.37   | 16.71   | 16.70   |
|           |            | 50      | 0         | 17.80   | 16.34   | 16.84   | 16.82   |
|           | 16QAM      | 1       | 0         | 17.80   | 17.34   | 17.80   | 17.60   |
|           |            | 1       | 25        | 17.80   | 16.98   | 17.28   | 17.20   |
|           |            | 1       | 49        | 17.80   | 16.60   | 16.87   | 16.64   |
|           |            | 25      | 0         | 17.80   | 16.38   | 16.81   | 16.73   |
|           |            | 25      | 13        | 17.80   | 16.54   | 16.78   | 16.76   |
|           |            | 25      | 25        | 17.80   | 16.42   | 16.68   | 16.70   |
|           |            | 50      | 0         | 17.80   | 16.41   | 16.78   | 16.78   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|---------|--------------|--------------|
|           |            |         |           |         | 18675CH | 18900CH      | 19125CH      |
| 15MHz     | QPSK       | 1       | 0         | 17.80   | 15.89   | 16.30        | 16.52        |
|           |            | 1       | 38        | 17.80   | 16.61   | 16.94        | 16.98        |
|           |            | 1       | 74        | 17.80   | 15.99   | 16.16        | 16.19        |
|           |            | 36      | 0         | 17.80   | 16.36   | 16.75        | 16.77        |
|           |            | 36      | 18        | 17.80   | 16.54   | 16.84        | 16.79        |
|           |            | 36      | 39        | 17.80   | 16.38   | 16.70        | 16.58        |
|           |            | 75      | 0         | 17.80   | 16.38   | 16.62        | 16.81        |
|           | 16QAM      | 1       | 0         | 17.80   | 16.17   | 16.57        | 16.61        |
|           |            | 1       | 38        | 17.80   | 16.90   | 17.21        | 17.04        |
|           |            | 1       | 74        | 17.80   | 16.38   | 16.43        | 16.27        |
|           |            | 36      | 0         | 17.80   | 16.32   | 16.72        | 16.71        |
|           |            | 36      | 18        | 17.80   | 16.56   | 16.80        | 16.72        |
|           |            | 36      | 39        | 17.80   | 16.41   | 16.67        | 16.51        |
|           |            | 75      | 0         | 17.80   | 16.31   | 16.57        | 16.76        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel      | Channel      |
|           |            |         |           |         | 18700CH | 18900CH      | 19100CH      |
| 20MHz     | QPSK       | 1       | 0         | 17.80   | 15.89   | 16.16        | 16.35        |
|           |            | 1       | 50        | 17.80   | 16.81   | 16.94        | <b>16.97</b> |
|           |            | 1       | 99        | 17.80   | 16.01   | 16.22        | 16.02        |
|           |            | 50      | 0         | 17.80   | 16.27   | 16.57        | 16.67        |
|           |            | 50      | 25        | 17.80   | 16.49   | <b>16.86</b> | 16.80        |
|           |            | 50      | 50        | 17.80   | 16.31   | 16.61        | 16.56        |
|           |            | 100     | 0         | 17.80   | 16.37   | 16.49        | 16.62        |
|           | 16QAM      | 1       | 0         | 17.80   | 16.09   | 16.62        | 16.73        |
|           |            | 1       | 50        | 17.80   | 16.96   | 17.41        | 17.29        |
|           |            | 1       | 99        | 17.80   | 16.24   | 16.68        | 16.36        |
|           |            | 50      | 0         | 17.80   | 16.24   | 16.53        | 16.62        |
|           |            | 50      | 25        | 17.80   | 16.51   | 16.82        | 16.75        |
|           |            | 50      | 50        | 17.80   | 16.33   | 16.56        | 16.51        |
|           |            | 100     | 0         | 17.80   | 16.35   | 16.43        | 16.57        |

Table 61: Conducted power measurement results of LTE Band II (Proximity sensor on+Hotspot on)

### 7.1.18 Conducted power measurements of LTE Band IV (Main Antenna)

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19957CH              | 20175CH | 20393CH |
| 1.4MHz      | QPSK       | 1       | 0         | 23.50   | 22.24                | 22.70   | 22.48   |
|             |            | 1       | 3         | 23.50   | 22.33                | 22.79   | 22.49   |
|             |            | 1       | 5         | 23.50   | 22.22                | 22.65   | 22.35   |
|             |            | 3       | 0         | 23.50   | 22.26                | 22.77   | 22.41   |
|             |            | 3       | 2         | 23.50   | 22.27                | 22.78   | 22.40   |
|             |            | 3       | 3         | 23.50   | 22.25                | 22.76   | 22.33   |
|             |            | 6       | 0         | 23.00   | 21.49                | 21.96   | 21.63   |
|             | 16QAM      | 1       | 0         | 23.00   | 21.50                | 22.10   | 21.74   |
|             |            | 1       | 3         | 23.00   | 21.56                | 22.16   | 21.78   |
|             |            | 1       | 5         | 23.00   | 21.52                | 22.02   | 21.63   |
|             |            | 3       | 0         | 23.00   | 21.56                | 21.98   | 21.70   |
|             |            | 3       | 2         | 23.00   | 21.58                | 21.99   | 21.69   |
|             |            | 3       | 3         | 23.00   | 21.54                | 21.93   | 21.65   |
|             |            | 6       | 0         | 22.00   | 20.62                | 20.92   | 20.81   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19965CH              | 20175CH | 20385CH |
| 3MHz        | QPSK       | 1       | 0         | 23.50   | 22.12                | 22.61   | 22.45   |
|             |            | 1       | 7         | 23.50   | 22.32                | 22.87   | 22.62   |
|             |            | 1       | 14        | 23.50   | 22.14                | 22.55   | 22.24   |
|             |            | 8       | 0         | 23.00   | 21.53                | 21.91   | 21.66   |
|             |            | 8       | 4         | 23.00   | 21.58                | 21.93   | 21.66   |
|             |            | 8       | 7         | 23.00   | 21.48                | 21.89   | 21.59   |
|             |            | 15      | 0         | 23.00   | 21.53                | 21.91   | 21.61   |
|             | 16QAM      | 1       | 0         | 23.00   | 21.50                | 21.87   | 21.68   |
|             |            | 1       | 7         | 23.00   | 21.80                | 22.07   | 21.82   |
|             |            | 1       | 14        | 23.00   | 21.59                | 21.80   | 21.46   |
|             |            | 8       | 0         | 22.00   | 20.59                | 20.97   | 20.84   |
|             |            | 8       | 4         | 22.00   | 20.64                | 21.00   | 20.81   |
|             |            | 8       | 7         | 22.00   | 20.60                | 21.11   | 20.74   |
|             |            | 15      | 0         | 22.00   | 20.69                | 20.90   | 20.74   |

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19975CH              | 20175CH | 20375CH |
| 5MHz        | QPSK       | 1       | 0         | 23.50   | 22.46                | 22.55   | 22.53   |
|             |            | 1       | 13        | 23.50   | 22.84                | 22.77   | 22.56   |
|             |            | 1       | 24        | 23.50   | 22.48                | 22.36   | 22.03   |
|             |            | 12      | 0         | 23.00   | 21.75                | 21.93   | 21.83   |
|             |            | 12      | 6         | 23.00   | 21.85                | 21.99   | 21.74   |
|             |            | 12      | 13        | 23.00   | 21.81                | 21.84   | 21.47   |
|             |            | 25      | 0         | 23.00   | 21.74                | 21.86   | 21.71   |
|             | 16QAM      | 1       | 0         | 23.00   | 21.74                | 21.92   | 21.89   |
|             |            | 1       | 13        | 23.00   | 22.09                | 22.17   | 21.98   |
|             |            | 1       | 24        | 23.00   | 21.74                | 21.77   | 21.37   |
|             |            | 12      | 0         | 22.00   | 20.94                | 20.86   | 20.96   |
|             |            | 12      | 6         | 22.00   | 21.03                | 20.99   | 20.91   |
|             |            | 12      | 13        | 22.00   | 20.71                | 20.83   | 20.65   |
|             |            | 25      | 0         | 22.00   | 20.90                | 20.77   | 20.89   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 20000CH              | 20175CH | 20350CH |
| 10MHz       | QPSK       | 1       | 0         | 23.50   | 22.72                | 22.89   | 23.13   |
|             |            | 1       | 25        | 23.50   | 22.82                | 22.85   | 22.77   |
|             |            | 1       | 49        | 23.50   | 22.87                | 23.05   | 22.42   |
|             |            | 25      | 0         | 23.00   | 21.81                | 21.86   | 21.97   |
|             |            | 25      | 13        | 23.00   | 21.87                | 21.88   | 21.82   |
|             |            | 25      | 25        | 23.00   | 21.84                | 21.84   | 21.59   |
|             |            | 50      | 0         | 23.00   | 21.88                | 21.80   | 21.76   |
|             | 16QAM      | 1       | 0         | 23.00   | 22.13                | 22.26   | 22.35   |
|             |            | 1       | 25        | 23.00   | 22.27                | 22.34   | 21.92   |
|             |            | 1       | 49        | 23.00   | 22.14                | 22.34   | 21.65   |
|             |            | 25      | 0         | 22.00   | 20.91                | 20.76   | 21.06   |
|             |            | 25      | 13        | 22.00   | 20.76                | 20.86   | 20.93   |
|             |            | 25      | 25        | 22.00   | 20.68                | 21.02   | 20.71   |
|             |            | 50      | 0         | 22.00   | 20.77                | 20.69   | 20.93   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 20025CH      | 20175CH      | 20325CH      |
| 15MHz     | QPSK       | 1       | 0         | 23.50   | 22.45        | 22.52        | 22.60        |
|           |            | 1       | 38        | 23.50   | 23.00        | 22.89        | 22.92        |
|           |            | 1       | 74        | 23.50   | 22.50        | 22.63        | 22.14        |
|           |            | 36      | 0         | 23.00   | 21.89        | 21.92        | 22.11        |
|           |            | 36      | 18        | 23.00   | 22.06        | 21.95        | 22.09        |
|           |            | 36      | 39        | 23.00   | 21.88        | 22.00        | 21.81        |
|           |            | 75      | 0         | 23.00   | 21.92        | 21.86        | 21.98        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.67        | 21.69        | 21.90        |
|           |            | 1       | 38        | 23.00   | 22.25        | 22.05        | 22.18        |
|           |            | 1       | 74        | 23.00   | 21.84        | 21.86        | 21.41        |
|           |            | 36      | 0         | 22.00   | 20.74        | 20.80        | 21.21        |
|           |            | 36      | 18        | 22.00   | 20.92        | 20.89        | 21.23        |
|           |            | 36      | 39        | 22.00   | 20.74        | 21.19        | 20.97        |
|           |            | 75      | 0         | 22.00   | 20.83        | 20.77        | 21.08        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 20050CH      | 20175CH      | 20300CH      |
| 20MHz     | QPSK       | 1       | 0         | 23.50   | 21.58        | 21.68        | 21.86        |
|           |            | 1       | 50        | 23.50   | <b>22.95</b> | <b>22.82</b> | <b>23.04</b> |
|           |            | 1       | 99        | 23.50   | 22.50        | 22.55        | 22.12        |
|           |            | 50      | 0         | 23.00   | 21.83        | 21.85        | 21.99        |
|           |            | 50      | 25        | 23.00   | 21.93        | 21.85        | <b>22.01</b> |
|           |            | 50      | 50        | 23.00   | 21.80        | 22.00        | 21.78        |
|           |            | 100     | 0         | 23.00   | 21.82        | 21.95        | 21.98        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.84        | 21.91        | 22.11        |
|           |            | 1       | 50        | 23.00   | 22.21        | 22.24        | 22.48        |
|           |            | 1       | 99        | 23.00   | 21.83        | 21.98        | 21.53        |
|           |            | 50      | 0         | 22.00   | 20.73        | 20.76        | 21.13        |
|           |            | 50      | 25        | 22.00   | 20.78        | 20.75        | 21.12        |
|           |            | 50      | 50        | 22.00   | 20.70        | 21.10        | 20.91        |
|           |            | 100     | 0         | 22.00   | 20.74        | 20.78        | 21.04        |

Table 62: Conducted power measurement results of LTE Band IV(Full power)

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19957CH              | 20175CH | 20393CH |
| 1.4MHz      | QPSK       | 1       | 0         | 21.50   | 20.61                | 21.00   | 20.89   |
|             |            | 1       | 3         | 21.50   | 20.72                | 21.04   | 20.91   |
|             |            | 1       | 5         | 21.50   | 20.59                | 20.96   | 20.77   |
|             |            | 3       | 0         | 21.50   | 20.68                | 21.02   | 20.86   |
|             |            | 3       | 2         | 21.50   | 20.70                | 21.03   | 20.84   |
|             |            | 3       | 3         | 21.50   | 20.65                | 21.01   | 20.78   |
|             |            | 6       | 0         | 21.00   | 19.69                | 20.26   | 20.12   |
|             | 16QAM      | 1       | 0         | 21.00   | 19.80                | 20.48   | 20.17   |
|             |            | 1       | 3         | 21.00   | 19.90                | 20.62   | 20.22   |
|             |            | 1       | 5         | 21.00   | 19.71                | 20.48   | 20.08   |
|             |            | 3       | 0         | 21.00   | 19.77                | 20.32   | 20.31   |
|             |            | 3       | 2         | 21.00   | 19.79                | 20.35   | 20.30   |
|             |            | 3       | 3         | 21.00   | 19.77                | 20.27   | 20.26   |
|             |            | 6       | 0         | 20.00   | 18.94                | 19.11   | 18.83   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19965CH              | 20175CH | 20385CH |
| 3MHz        | QPSK       | 1       | 0         | 21.50   | 20.54                | 20.90   | 20.84   |
|             |            | 1       | 7         | 21.50   | 20.74                | 21.13   | 20.99   |
|             |            | 1       | 14        | 21.50   | 20.50                | 20.94   | 20.66   |
|             |            | 8       | 0         | 21.00   | 19.70                | 20.23   | 20.16   |
|             |            | 8       | 4         | 21.00   | 19.68                | 20.28   | 20.14   |
|             |            | 8       | 7         | 21.00   | 19.64                | 20.23   | 20.06   |
|             |            | 15      | 0         | 21.00   | 19.64                | 20.25   | 20.08   |
|             | 16QAM      | 1       | 0         | 21.00   | 19.75                | 20.20   | 20.12   |
|             |            | 1       | 7         | 21.00   | 20.01                | 20.49   | 20.30   |
|             |            | 1       | 14        | 21.00   | 19.79                | 20.13   | 19.98   |
|             |            | 8       | 0         | 20.00   | 18.86                | 19.17   | 18.72   |
|             |            | 8       | 4         | 20.00   | 18.90                | 19.14   | 18.72   |
|             |            | 8       | 7         | 20.00   | 18.80                | 19.11   | 18.59   |
|             |            | 15      | 0         | 20.00   | 18.85                | 19.13   | 18.66   |

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19975CH              | 20175CH | 20375CH |
| 5MHz        | QPSK       | 1       | 0         | 21.50   | 20.56                | 20.64   | 21.00   |
|             |            | 1       | 13        | 21.50   | 20.87                | 20.98   | 21.08   |
|             |            | 1       | 24        | 21.50   | 20.50                | 20.56   | 20.50   |
|             |            | 12      | 0         | 21.00   | 19.87                | 20.12   | 20.08   |
|             |            | 12      | 6         | 21.00   | 19.99                | 20.21   | 20.09   |
|             |            | 12      | 13        | 21.00   | 19.88                | 20.07   | 19.79   |
|             |            | 25      | 0         | 21.00   | 19.88                | 20.07   | 20.00   |
|             | 16QAM      | 1       | 0         | 21.00   | 19.89                | 20.24   | 20.30   |
|             |            | 1       | 13        | 21.00   | 20.25                | 20.54   | 20.42   |
|             |            | 1       | 24        | 21.00   | 19.88                | 20.08   | 20.04   |
|             |            | 12      | 0         | 20.00   | 19.30                | 19.24   | 19.02   |
|             |            | 12      | 6         | 20.00   | 19.31                | 19.32   | 19.04   |
|             |            | 12      | 13        | 20.00   | 19.21                | 19.13   | 18.68   |
|             |            | 25      | 0         | 20.00   | 19.15                | 19.19   | 18.86   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 20000CH              | 20175CH | 20350CH |
| 10MHz       | QPSK       | 1       | 0         | 21.50   | 21.08                | 21.03   | 21.48   |
|             |            | 1       | 25        | 21.50   | 20.98                | 21.11   | 21.22   |
|             |            | 1       | 49        | 21.50   | 20.98                | 21.33   | 20.94   |
|             |            | 25      | 0         | 21.00   | 19.90                | 20.11   | 20.15   |
|             |            | 25      | 13        | 21.00   | 19.99                | 20.13   | 20.12   |
|             |            | 25      | 25        | 21.00   | 19.96                | 20.08   | 19.88   |
|             |            | 50      | 0         | 21.00   | 20.02                | 19.99   | 20.06   |
|             | 16QAM      | 1       | 0         | 21.00   | 20.32                | 20.55   | 20.89   |
|             |            | 1       | 25        | 21.00   | 20.40                | 20.66   | 20.37   |
|             |            | 1       | 49        | 21.00   | 20.32                | 20.67   | 20.36   |
|             |            | 25      | 0         | 20.00   | 19.21                | 19.15   | 19.13   |
|             |            | 25      | 13        | 20.00   | 19.26                | 19.19   | 19.08   |
|             |            | 25      | 25        | 20.00   | 19.16                | 19.11   | 18.84   |
|             |            | 50      | 0         | 20.00   | 19.24                | 19.02   | 18.97   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 20025CH | 20175CH | 20325CH      |
| 15MHz     | QPSK       | 1       | 0         | 21.50   | 20.44   | 20.69   | 21.09        |
|           |            | 1       | 38        | 21.50   | 20.96   | 21.04   | 21.25        |
|           |            | 1       | 74        | 21.50   | 20.57   | 20.97   | 20.60        |
|           |            | 36      | 0         | 21.00   | 20.02   | 20.14   | 20.26        |
|           |            | 36      | 18        | 21.00   | 20.13   | 20.13   | 20.29        |
|           |            | 36      | 39        | 21.00   | 20.06   | 20.26   | 20.07        |
|           |            | 75      | 0         | 21.00   | 20.05   | 20.11   | 20.14        |
|           | 16QAM      | 1       | 0         | 21.00   | 19.91   | 20.26   | 20.16        |
|           |            | 1       | 38        | 21.00   | 20.56   | 20.55   | 20.36        |
|           |            | 1       | 74        | 21.00   | 20.10   | 20.28   | 20.02        |
|           |            | 36      | 0         | 20.00   | 19.27   | 19.21   | 19.19        |
|           |            | 36      | 18        | 20.00   | 19.37   | 19.27   | 19.26        |
|           |            | 36      | 39        | 20.00   | 19.14   | 19.25   | 19.02        |
|           |            | 75      | 0         | 20.00   | 19.22   | 19.16   | 19.11        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 20050CH | 20175CH | 20300CH      |
| 20MHz     | QPSK       | 1       | 0         | 21.50   | 20.72   | 20.82   | 21.11        |
|           |            | 1       | 50        | 21.50   | 21.00   | 21.08   | <b>21.49</b> |
|           |            | 1       | 99        | 21.50   | 20.72   | 21.02   | 20.78        |
|           |            | 50      | 0         | 21.00   | 19.92   | 20.09   | 20.20        |
|           |            | 50      | 25        | 21.00   | 20.14   | 20.09   | <b>20.25</b> |
|           |            | 50      | 50        | 21.00   | 20.05   | 20.21   | 20.15        |
|           |            | 100     | 0         | 21.00   | 20.07   | 20.14   | 20.18        |
|           | 16QAM      | 1       | 0         | 21.00   | 20.08   | 20.13   | 20.44        |
|           |            | 1       | 50        | 21.00   | 20.56   | 20.45   | 20.67        |
|           |            | 1       | 99        | 21.00   | 20.17   | 20.36   | 20.41        |
|           |            | 50      | 0         | 20.00   | 19.16   | 19.15   | 19.26        |
|           |            | 50      | 25        | 20.00   | 19.22   | 19.11   | 19.26        |
|           |            | 50      | 50        | 20.00   | 19.07   | 19.21   | 19.07        |
|           |            | 100     | 0         | 20.00   | 19.21   | 19.22   | 19.20        |

Table 63: Conducted power measurement results of LTE Band IV (Proximity sensor on)

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19957CH              | 20175CH | 20393CH |
| 1.4MHz      | QPSK       | 1       | 0         | 19.50   | 18.50                | 18.80   | 18.44   |
|             |            | 1       | 3         | 19.50   | 18.57                | 18.94   | 18.49   |
|             |            | 1       | 5         | 19.50   | 18.46                | 18.84   | 18.35   |
|             |            | 3       | 0         | 19.50   | 18.55                | 18.88   | 18.40   |
|             |            | 3       | 2         | 19.50   | 18.56                | 18.92   | 18.41   |
|             |            | 3       | 3         | 19.50   | 18.52                | 18.84   | 18.35   |
|             |            | 6       | 0         | 19.50   | 18.50                | 18.80   | 18.38   |
|             | 16QAM      | 1       | 0         | 19.50   | 18.69                | 19.12   | 18.43   |
|             |            | 1       | 3         | 19.50   | 18.78                | 19.27   | 18.56   |
|             |            | 1       | 5         | 19.50   | 18.61                | 19.18   | 18.37   |
|             |            | 3       | 0         | 19.50   | 18.65                | 18.92   | 18.44   |
|             |            | 3       | 2         | 19.50   | 18.67                | 18.95   | 18.45   |
|             |            | 3       | 3         | 19.50   | 18.63                | 18.88   | 18.35   |
|             |            | 6       | 0         | 19.50   | 18.51                | 18.62   | 18.32   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19965CH              | 20175CH | 20385CH |
| 3MHz        | QPSK       | 1       | 0         | 19.50   | 18.39                | 18.72   | 18.35   |
|             |            | 1       | 7         | 19.50   | 18.61                | 18.98   | 18.56   |
|             |            | 1       | 14        | 19.50   | 18.28                | 18.60   | 18.19   |
|             |            | 8       | 0         | 19.50   | 18.52                | 18.79   | 18.40   |
|             |            | 8       | 4         | 19.50   | 18.56                | 18.84   | 18.43   |
|             |            | 8       | 7         | 19.50   | 18.45                | 18.80   | 18.36   |
|             |            | 15      | 0         | 19.50   | 18.51                | 18.79   | 18.38   |
|             | 16QAM      | 1       | 0         | 19.50   | 18.48                | 18.77   | 18.46   |
|             |            | 1       | 7         | 19.50   | 18.70                | 19.09   | 18.67   |
|             |            | 1       | 14        | 19.50   | 18.40                | 18.73   | 18.24   |
|             |            | 8       | 0         | 19.50   | 18.53                | 18.74   | 18.36   |
|             |            | 8       | 4         | 19.50   | 18.49                | 18.79   | 18.38   |
|             |            | 8       | 7         | 19.50   | 18.45                | 18.71   | 18.26   |
|             |            | 15      | 0         | 19.50   | 18.43                | 18.74   | 18.38   |

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19975CH              | 20175CH | 20375CH |
| 5MHz        | QPSK       | 1       | 0         | 19.50   | 18.77                | 18.63   | 18.61   |
|             |            | 1       | 13        | 19.50   | 19.04                | 18.97   | 18.71   |
|             |            | 1       | 24        | 19.50   | 18.61                | 18.52   | 18.06   |
|             |            | 12      | 0         | 19.50   | 18.86                | 18.84   | 18.69   |
|             |            | 12      | 6         | 19.50   | 18.93                | 18.93   | 18.70   |
|             |            | 12      | 13        | 19.50   | 18.84                | 18.79   | 18.40   |
|             |            | 25      | 0         | 19.50   | 18.81                | 18.85   | 18.60   |
|             | 16QAM      | 1       | 0         | 19.50   | 18.86                | 18.87   | 18.88   |
|             |            | 1       | 13        | 19.50   | 19.14                | 19.24   | 19.02   |
|             |            | 1       | 24        | 19.50   | 18.69                | 18.78   | 18.46   |
|             |            | 12      | 0         | 19.50   | 18.84                | 18.91   | 18.68   |
|             |            | 12      | 6         | 19.50   | 18.99                | 18.93   | 18.69   |
|             |            | 12      | 13        | 19.50   | 18.89                | 18.81   | 18.40   |
|             |            | 25      | 0         | 19.50   | 18.78                | 18.80   | 18.54   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 20000CH              | 20175CH | 20350CH |
| 10MHz       | QPSK       | 1       | 0         | 19.50   | 19.00                | 18.97   | 19.12   |
|             |            | 1       | 25        | 19.50   | 19.08                | 19.04   | 18.88   |
|             |            | 1       | 49        | 19.50   | 18.94                | 18.99   | 18.45   |
|             |            | 25      | 0         | 19.50   | 18.88                | 18.79   | 18.78   |
|             |            | 25      | 13        | 19.50   | 18.93                | 18.90   | 18.74   |
|             |            | 25      | 25        | 19.50   | 18.87                | 18.81   | 18.50   |
|             |            | 50      | 0         | 19.50   | 18.94                | 18.74   | 18.64   |
|             | 16QAM      | 1       | 0         | 19.50   | 19.27                | 19.15   | 19.14   |
|             |            | 1       | 25        | 19.50   | 19.28                | 19.27   | 18.98   |
|             |            | 1       | 49        | 19.50   | 19.18                | 19.30   | 18.61   |
|             |            | 25      | 0         | 19.50   | 18.80                | 18.77   | 18.75   |
|             |            | 25      | 13        | 19.50   | 18.85                | 18.82   | 18.66   |
|             |            | 25      | 25        | 19.50   | 18.74                | 18.74   | 18.45   |
|             |            | 50      | 0         | 19.50   | 18.81                | 18.67   | 18.56   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 20025CH | 20175CH | 20325CH      |
| 15MHz     | QPSK       | 1       | 0         | 19.50   | 18.59   | 18.66   | 18.77        |
|           |            | 1       | 38        | 19.50   | 19.03   | 19.06   | 18.97        |
|           |            | 1       | 74        | 19.50   | 18.51   | 18.81   | 18.25        |
|           |            | 36      | 0         | 19.50   | 18.91   | 18.83   | 18.95        |
|           |            | 36      | 18        | 19.50   | 19.04   | 18.91   | 18.92        |
|           |            | 36      | 39        | 19.50   | 18.84   | 18.92   | 18.72        |
|           |            | 75      | 0         | 19.50   | 18.95   | 18.87   | 18.82        |
|           | 16QAM      | 1       | 0         | 19.50   | 18.91   | 18.91   | 18.72        |
|           |            | 1       | 38        | 19.50   | 19.33   | 19.20   | 18.89        |
|           |            | 1       | 74        | 19.50   | 18.82   | 18.97   | 18.19        |
|           |            | 36      | 0         | 19.50   | 18.87   | 18.75   | 18.82        |
|           |            | 36      | 18        | 19.50   | 18.94   | 18.88   | 18.87        |
|           |            | 36      | 39        | 19.50   | 18.74   | 18.89   | 18.62        |
|           |            | 75      | 0         | 19.50   | 18.85   | 18.76   | 18.76        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 20050CH | 20175CH | 20300CH      |
| 20MHz     | QPSK       | 1       | 0         | 19.50   | 18.53   | 18.56   | 18.69        |
|           |            | 1       | 50        | 19.50   | 19.03   | 19.00   | <b>19.26</b> |
|           |            | 1       | 99        | 19.50   | 18.40   | 18.68   | 18.28        |
|           |            | 50      | 0         | 19.50   | 18.85   | 18.75   | <b>18.95</b> |
|           |            | 50      | 25        | 19.50   | 18.87   | 18.84   | 18.93        |
|           |            | 50      | 50        | 19.50   | 18.70   | 18.90   | 18.72        |
|           |            | 100     | 0         | 19.50   | 18.82   | 18.87   | 18.85        |
|           | 16QAM      | 1       | 0         | 19.50   | 18.91   | 18.73   | 18.86        |
|           |            | 1       | 50        | 19.50   | 19.29   | 19.16   | 19.34        |
|           |            | 1       | 99        | 19.50   | 18.66   | 18.79   | 18.41        |
|           |            | 50      | 0         | 19.50   | 18.85   | 18.67   | 18.83        |
|           |            | 50      | 25        | 19.50   | 18.80   | 18.74   | 18.88        |
|           |            | 50      | 50        | 19.50   | 18.71   | 18.82   | 18.62        |
|           |            | 100     | 0         | 19.50   | 18.75   | 18.77   | 18.81        |

Table 64: Conducted power measurement results of LTE Band IV (Hotspot on)

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19957CH              | 20175CH | 20393CH |
| 1.4MHz      | QPSK       | 1       | 0         | 18.00   | 16.51                | 17.23   | 16.99   |
|             |            | 1       | 3         | 18.00   | 16.58                | 17.29   | 16.99   |
|             |            | 1       | 5         | 18.00   | 16.47                | 17.17   | 16.85   |
|             |            | 3       | 0         | 18.00   | 16.54                | 17.24   | 16.91   |
|             |            | 3       | 2         | 18.00   | 16.57                | 17.28   | 16.91   |
|             |            | 3       | 3         | 18.00   | 16.53                | 17.25   | 16.92   |
|             |            | 6       | 0         | 18.00   | 16.52                | 17.23   | 16.94   |
|             | 16QAM      | 1       | 0         | 18.00   | 16.74                | 17.43   | 17.07   |
|             |            | 1       | 3         | 18.00   | 16.74                | 17.55   | 17.10   |
|             |            | 1       | 5         | 18.00   | 16.73                | 17.40   | 16.96   |
|             |            | 3       | 0         | 18.00   | 16.57                | 17.31   | 17.06   |
|             |            | 3       | 2         | 18.00   | 16.60                | 17.28   | 17.07   |
|             |            | 3       | 3         | 18.00   | 16.56                | 17.27   | 17.01   |
|             |            | 6       | 0         | 18.00   | 16.49                | 17.17   | 16.91   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19965CH              | 20175CH | 20385CH |
| 3MHz        | QPSK       | 1       | 0         | 18.00   | 16.29                | 17.08   | 16.95   |
|             |            | 1       | 7         | 18.00   | 16.68                | 17.36   | 17.11   |
|             |            | 1       | 14        | 18.00   | 16.35                | 16.97   | 16.77   |
|             |            | 8       | 0         | 18.00   | 16.57                | 17.17   | 17.02   |
|             |            | 8       | 4         | 18.00   | 16.62                | 17.21   | 16.93   |
|             |            | 8       | 7         | 18.00   | 16.56                | 17.17   | 16.86   |
|             |            | 15      | 0         | 18.00   | 16.56                | 17.16   | 16.87   |
|             | 16QAM      | 1       | 0         | 18.00   | 16.57                | 17.12   | 17.05   |
|             |            | 1       | 7         | 18.00   | 16.94                | 17.41   | 17.22   |
|             |            | 1       | 14        | 18.00   | 16.64                | 16.97   | 16.78   |
|             |            | 8       | 0         | 18.00   | 16.53                | 17.11   | 16.98   |
|             |            | 8       | 4         | 18.00   | 16.56                | 17.15   | 16.88   |
|             |            | 8       | 7         | 18.00   | 16.52                | 17.10   | 16.80   |
|             |            | 15      | 0         | 18.00   | 16.51                | 17.11   | 16.76   |

| LTE Band IV |            |         |           |         | Conducted Power(dBm) |         |         |
|-------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 19975CH              | 20175CH | 20375CH |
| 5MHz        | QPSK       | 1       | 0         | 18.00   | 16.56                | 16.75   | 16.79   |
|             |            | 1       | 13        | 18.00   | 16.91                | 17.07   | 16.84   |
|             |            | 1       | 24        | 18.00   | 16.59                | 16.58   | 16.31   |
|             |            | 12      | 0         | 18.00   | 16.81                | 16.98   | 16.89   |
|             |            | 12      | 6         | 18.00   | 16.96                | 17.01   | 16.85   |
|             |            | 12      | 13        | 18.00   | 16.84                | 16.86   | 16.61   |
|             |            | 25      | 0         | 18.00   | 16.77                | 16.92   | 16.80   |
|             | 16QAM      | 1       | 0         | 18.00   | 16.86                | 16.94   | 17.11   |
|             |            | 1       | 13        | 18.00   | 17.22                | 17.26   | 17.18   |
|             |            | 1       | 24        | 18.00   | 16.93                | 16.77   | 16.66   |
|             |            | 12      | 0         | 18.00   | 16.77                | 16.97   | 16.84   |
|             |            | 12      | 6         | 18.00   | 16.91                | 16.98   | 16.79   |
|             |            | 12      | 13        | 18.00   | 16.82                | 16.85   | 16.54   |
|             |            | 25      | 0         | 18.00   | 16.71                | 16.82   | 16.77   |
| Bandwidth   | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|             |            |         |           |         | 20000CH              | 20175CH | 20350CH |
| 10MHz       | QPSK       | 1       | 0         | 18.00   | 16.96                | 17.23   | 17.43   |
|             |            | 1       | 25        | 18.00   | 17.12                | 17.12   | 17.12   |
|             |            | 1       | 49        | 18.00   | 17.16                | 17.15   | 16.83   |
|             |            | 25      | 0         | 18.00   | 16.82                | 16.97   | 16.96   |
|             |            | 25      | 13        | 18.00   | 16.92                | 16.96   | 16.92   |
|             |            | 25      | 25        | 18.00   | 16.87                | 16.86   | 16.69   |
|             |            | 50      | 0         | 18.00   | 16.87                | 16.79   | 16.85   |
|             | 16QAM      | 1       | 0         | 18.00   | 17.27                | 17.43   | 17.52   |
|             |            | 1       | 25        | 18.00   | 17.30                | 17.34   | 17.20   |
|             |            | 1       | 49        | 18.00   | 17.42                | 17.35   | 16.97   |
|             |            | 25      | 0         | 18.00   | 16.67                | 16.91   | 16.93   |
|             |            | 25      | 13        | 18.00   | 16.78                | 16.85   | 16.89   |
|             |            | 25      | 25        | 18.00   | 16.73                | 16.75   | 16.65   |
|             |            | 50      | 0         | 18.00   | 16.73                | 16.64   | 16.79   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 20025CH | 20175CH | 20325CH      |
| 15MHz     | QPSK       | 1       | 0         | 18.00   | 16.49   | 16.89   | 16.87        |
|           |            | 1       | 38        | 18.00   | 17.16   | 17.09   | 17.14        |
|           |            | 1       | 74        | 18.00   | 16.76   | 16.77   | 16.43        |
|           |            | 36      | 0         | 18.00   | 16.84   | 17.05   | 17.05        |
|           |            | 36      | 18        | 18.00   | 17.00   | 16.96   | 17.08        |
|           |            | 36      | 39        | 18.00   | 16.98   | 17.03   | 16.87        |
|           |            | 75      | 0         | 18.00   | 16.90   | 16.92   | 16.92        |
|           | 16QAM      | 1       | 0         | 18.00   | 16.85   | 17.04   | 17.03        |
|           |            | 1       | 38        | 18.00   | 17.50   | 17.27   | 17.21        |
|           |            | 1       | 74        | 18.00   | 17.12   | 16.93   | 16.48        |
|           |            | 36      | 0         | 18.00   | 16.79   | 16.99   | 16.98        |
|           |            | 36      | 18        | 18.00   | 16.95   | 16.90   | 17.00        |
|           |            | 36      | 39        | 18.00   | 16.94   | 16.98   | 16.80        |
|           |            | 75      | 0         | 18.00   | 16.83   | 16.85   | 16.85        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 20050CH | 20175CH | 20300CH      |
| 20MHz     | QPSK       | 1       | 0         | 18.00   | 16.58   | 16.79   | 16.68        |
|           |            | 1       | 50        | 18.00   | 17.11   | 17.16   | <b>17.29</b> |
|           |            | 1       | 99        | 18.00   | 16.54   | 16.84   | 16.45        |
|           |            | 50      | 0         | 18.00   | 16.88   | 17.03   | 17.02        |
|           |            | 50      | 25        | 18.00   | 16.90   | 16.88   | <b>17.06</b> |
|           |            | 50      | 50        | 18.00   | 16.74   | 17.01   | 16.94        |
|           |            | 100     | 0         | 18.00   | 16.85   | 16.97   | 16.96        |
|           | 16QAM      | 1       | 0         | 18.00   | 16.79   | 17.07   | 16.90        |
|           |            | 1       | 50        | 18.00   | 17.37   | 17.38   | 17.56        |
|           |            | 1       | 99        | 18.00   | 16.72   | 17.06   | 16.81        |
|           |            | 50      | 0         | 18.00   | 16.79   | 16.98   | 16.93        |
|           |            | 50      | 25        | 18.00   | 16.87   | 16.84   | 16.96        |
|           |            | 50      | 50        | 18.00   | 16.71   | 16.96   | 16.81        |
|           |            | 100     | 0         | 18.00   | 16.83   | 16.93   | 16.86        |

Table 65: Conducted power measurement results of LTE Band IV (Proximity sensor on+hotspot on)

### 7.1.19 Conducted power measurements of LTE Band V(Main Antenna)

| LTE Band V |            |         |           |         | Conducted Power(dBm) |         |         |
|------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20407CH              | 20525CH | 20643CH |
| 1.4MHz     | QPSK       | 1       | 0         | 24.00   | 22.66                | 22.76   | 22.86   |
|            |            | 1       | 3         | 24.00   | 22.78                | 22.82   | 22.92   |
|            |            | 1       | 5         | 24.00   | 22.66                | 22.67   | 22.69   |
|            |            | 3       | 0         | 24.00   | 22.74                | 22.75   | 22.82   |
|            |            | 3       | 2         | 24.00   | 22.76                | 22.76   | 22.79   |
|            |            | 3       | 3         | 24.00   | 22.70                | 22.70   | 22.70   |
|            |            | 6       | 0         | 23.00   | 21.77                | 21.82   | 21.87   |
|            | 16QAM      | 1       | 0         | 23.00   | 21.77                | 22.05   | 22.06   |
|            |            | 1       | 3         | 23.00   | 21.91                | 22.15   | 22.16   |
|            |            | 1       | 5         | 23.00   | 21.76                | 21.99   | 21.94   |
|            |            | 3       | 0         | 23.00   | 21.80                | 21.92   | 21.98   |
|            |            | 3       | 2         | 23.00   | 21.85                | 21.96   | 21.97   |
|            |            | 3       | 3         | 23.00   | 21.80                | 21.89   | 21.92   |
|            |            | 6       | 0         | 22.00   | 20.82                | 20.84   | 21.02   |
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20415CH              | 20525CH | 20635CH |
| 3MHz       | QPSK       | 1       | 0         | 24.00   | 22.46                | 22.55   | 22.84   |
|            |            | 1       | 7         | 24.00   | 22.91                | 22.86   | 22.99   |
|            |            | 1       | 14        | 24.00   | 22.55                | 22.63   | 22.55   |
|            |            | 8       | 0         | 23.00   | 21.75                | 21.77   | 21.86   |
|            |            | 8       | 4         | 23.00   | 21.90                | 21.83   | 21.90   |
|            |            | 8       | 7         | 23.00   | 21.87                | 21.81   | 21.79   |
|            |            | 15      | 0         | 23.00   | 21.83                | 21.76   | 21.86   |
|            | 16QAM      | 1       | 0         | 23.00   | 21.63                | 21.73   | 21.92   |
|            |            | 1       | 7         | 23.00   | 22.07                | 22.03   | 22.11   |
|            |            | 1       | 14        | 23.00   | 21.72                | 21.71   | 21.70   |
|            |            | 8       | 0         | 22.00   | 20.77                | 20.86   | 20.95   |
|            |            | 8       | 4         | 22.00   | 20.88                | 20.93   | 20.99   |
|            |            | 8       | 7         | 22.00   | 20.85                | 20.91   | 20.88   |
|            |            | 15      | 0         | 22.00   | 20.77                | 20.81   | 20.89   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 20425CH      | 20525CH      | 20625CH      |
| 5MHz      | QPSK       | 1       | 0         | 24.00   | 22.51        | 22.43        | 22.87        |
|           |            | 1       | 13        | 24.00   | 22.92        | 22.78        | 22.96        |
|           |            | 1       | 24        | 24.00   | 22.44        | 22.56        | 22.36        |
|           |            | 12      | 0         | 23.00   | 21.85        | 21.74        | 22.05        |
|           |            | 12      | 6         | 23.00   | 21.99        | 21.83        | 22.03        |
|           |            | 12      | 13        | 23.00   | 21.73        | 21.76        | 21.72        |
|           |            | 25      | 0         | 23.00   | 21.79        | 21.78        | 21.86        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.72        | 21.80        | 22.27        |
|           |            | 1       | 13        | 23.00   | 22.20        | 22.18        | 22.36        |
|           |            | 1       | 24        | 23.00   | 21.64        | 21.86        | 21.79        |
|           |            | 12      | 0         | 22.00   | 20.86        | 20.83        | 21.10        |
|           |            | 12      | 6         | 22.00   | 21.03        | 20.90        | 21.07        |
|           |            | 12      | 13        | 22.00   | 20.71        | 20.83        | 20.79        |
|           |            | 25      | 0         | 22.00   | 20.72        | 20.81        | 20.91        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 20450CH      | 20525CH      | 20600CH      |
| 10MHz     | QPSK       | 1       | 0         | 24.00   | 22.33        | 22.26        | 22.64        |
|           |            | 1       | 25        | 24.00   | <b>22.88</b> | <b>22.80</b> | <b>23.12</b> |
|           |            | 1       | 49        | 24.00   | 22.19        | 22.65        | 22.24        |
|           |            | 25      | 0         | 23.00   | 21.72        | 21.62        | 21.95        |
|           |            | 25      | 13        | 23.00   | 21.79        | 21.80        | 22.08        |
|           |            | 25      | 25        | 23.00   | 21.60        | 21.73        | 21.73        |
|           |            | 50      | 0         | 23.00   | 21.63        | 21.72        | 21.89        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.53        | 21.69        | 21.78        |
|           |            | 1       | 25        | 23.00   | 22.08        | 22.17        | 22.32        |
|           |            | 1       | 49        | 23.00   | 21.52        | 21.92        | 21.47        |
|           |            | 25      | 0         | 22.00   | 20.69        | 20.63        | 20.94        |
|           |            | 25      | 13        | 22.00   | 20.77        | 20.82        | 21.09        |
|           |            | 25      | 25        | 22.00   | 20.59        | 20.73        | 20.76        |
|           |            | 50      | 0         | 22.00   | 20.62        | 20.75        | 20.87        |

Table 66: Conducted power measurement results of LTE Band V (Full power)

| LTE Band V |            |         |           |         | Conducted Power(dBm) |         |         |
|------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20407CH              | 20525CH | 20643CH |
| 1.4MHz     | QPSK       | 1       | 0         | 22.00   | 20.73                | 20.96   | 21.03   |
|            |            | 1       | 3         | 22.00   | 20.96                | 21.05   | 21.15   |
|            |            | 1       | 5         | 22.00   | 20.81                | 20.92   | 21.06   |
|            |            | 3       | 0         | 22.00   | 20.81                | 20.94   | 21.08   |
|            |            | 3       | 2         | 22.00   | 20.90                | 20.97   | 21.10   |
|            |            | 3       | 3         | 22.00   | 20.86                | 20.93   | 21.05   |
|            |            | 6       | 0         | 21.00   | 19.82                | 19.87   | 20.10   |
|            | 16QAM      | 1       | 0         | 21.00   | 19.77                | 20.31   | 20.16   |
|            |            | 1       | 3         | 21.00   | 19.99                | 20.45   | 20.29   |
|            |            | 1       | 5         | 21.00   | 19.88                | 20.28   | 20.14   |
|            |            | 3       | 0         | 21.00   | 19.77                | 20.07   | 20.22   |
|            |            | 3       | 2         | 21.00   | 19.86                | 20.09   | 20.24   |
|            |            | 3       | 3         | 21.00   | 19.83                | 20.04   | 20.23   |
|            |            | 6       | 0         | 20.00   | 18.81                | 18.89   | 19.05   |
| Bandwidth  | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|            |            |         |           |         | 20415CH              | 20525CH | 20635CH |
| 3MHz       | QPSK       | 1       | 0         | 22.00   | 20.45                | 20.70   | 20.96   |
|            |            | 1       | 7         | 22.00   | 21.00                | 21.05   | 21.22   |
|            |            | 1       | 14        | 22.00   | 20.71                | 20.69   | 20.78   |
|            |            | 8       | 0         | 21.00   | 19.83                | 19.78   | 19.97   |
|            |            | 8       | 4         | 21.00   | 19.95                | 19.86   | 20.09   |
|            |            | 8       | 7         | 21.00   | 19.95                | 19.82   | 19.96   |
|            |            | 15      | 0         | 21.00   | 19.89                | 19.77   | 20.03   |
|            | 16QAM      | 1       | 0         | 21.00   | 19.76                | 19.68   | 19.81   |
|            |            | 1       | 7         | 21.00   | 20.13                | 20.17   | 20.28   |
|            |            | 1       | 14        | 21.00   | 20.00                | 19.68   | 19.79   |
|            |            | 8       | 0         | 20.00   | 18.72                | 18.85   | 19.03   |
|            |            | 8       | 4         | 20.00   | 18.87                | 18.87   | 19.04   |
|            |            | 8       | 7         | 20.00   | 18.84                | 18.87   | 18.95   |
|            |            | 15      | 0         | 20.00   | 18.74                | 18.84   | 18.99   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|-----------|------------|---------|-----------|---------|---------|---------|--------------|
|           |            |         |           |         | 20425CH | 20525CH | 20625CH      |
| 5MHz      | QPSK       | 1       | 0         | 22.00   | 20.49   | 20.64   | 21.05        |
|           |            | 1       | 13        | 22.00   | 21.11   | 20.99   | 21.16        |
|           |            | 1       | 24        | 22.00   | 20.57   | 20.65   | 20.61        |
|           |            | 12      | 0         | 21.00   | 19.87   | 19.75   | 20.10        |
|           |            | 12      | 6         | 21.00   | 20.02   | 19.84   | 20.12        |
|           |            | 12      | 13        | 21.00   | 19.79   | 19.76   | 19.89        |
|           |            | 25      | 0         | 21.00   | 19.83   | 19.78   | 19.94        |
|           | 16QAM      | 1       | 0         | 21.00   | 19.77   | 19.96   | 20.24        |
|           |            | 1       | 13        | 21.00   | 20.32   | 20.32   | 20.42        |
|           |            | 1       | 24        | 21.00   | 19.73   | 19.95   | 19.95        |
|           |            | 12      | 0         | 20.00   | 18.78   | 18.84   | 19.11        |
|           |            | 12      | 6         | 20.00   | 18.98   | 18.93   | 19.11        |
|           |            | 12      | 13        | 20.00   | 18.76   | 18.83   | 18.85        |
|           |            | 25      | 0         | 20.00   | 18.72   | 18.82   | 18.95        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel      |
|           |            |         |           |         | 20450CH | 20525CH | 20600CH      |
| 10MHz     | QPSK       | 1       | 0         | 22.00   | 20.27   | 20.39   | 20.73        |
|           |            | 1       | 25        | 22.00   | 20.99   | 20.96   | <b>21.31</b> |
|           |            | 1       | 49        | 22.00   | 20.28   | 20.67   | 20.49        |
|           |            | 25      | 0         | 21.00   | 19.77   | 19.70   | 19.97        |
|           |            | 25      | 13        | 21.00   | 19.82   | 19.84   | <b>20.13</b> |
|           |            | 25      | 25        | 21.00   | 19.69   | 19.74   | 19.82        |
|           |            | 50      | 0         | 21.00   | 19.72   | 19.75   | 19.91        |
|           | 16QAM      | 1       | 0         | 21.00   | 19.71   | 19.85   | 19.81        |
|           |            | 1       | 25        | 21.00   | 20.27   | 20.21   | 20.35        |
|           |            | 1       | 49        | 21.00   | 19.63   | 19.95   | 19.50        |
|           |            | 25      | 0         | 20.00   | 18.72   | 18.72   | 18.98        |
|           |            | 25      | 13        | 20.00   | 18.78   | 18.85   | 19.10        |
|           |            | 25      | 25        | 20.00   | 18.56   | 18.76   | 18.82        |
|           |            | 50      | 0         | 20.00   | 18.58   | 18.74   | 18.90        |

Table 67: Conducted power measurement results of LTE Band V (Proximity sensor on)

### 7.1.20 Conducted power measurements of LTE Band VII (Main Antenna)

| LTE Band VII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20775CH              | 21100CH | 21425CH |
| 5MHz         | QPSK       | 1       | 0         | 23.00   | 21.47                | 21.81   | 21.41   |
|              |            | 1       | 13        | 23.00   | 21.56                | 21.69   | 21.23   |
|              |            | 1       | 24        | 23.00   | 21.57                | 21.72   | 21.02   |
|              |            | 12      | 0         | 22.00   | 20.52                | 20.72   | 20.43   |
|              |            | 12      | 6         | 22.00   | 20.70                | 20.77   | 20.49   |
|              |            | 12      | 13        | 22.00   | 20.65                | 20.56   | 20.30   |
|              |            | 25      | 0         | 22.00   | 20.56                | 20.58   | 20.36   |
|              | 16QAM      | 1       | 0         | 22.00   | 20.77                | 21.32   | 20.84   |
|              |            | 1       | 13        | 22.00   | 20.83                | 21.13   | 20.72   |
|              |            | 1       | 24        | 22.00   | 20.91                | 21.15   | 20.61   |
|              |            | 12      | 0         | 22.00   | 20.95                | 21.17   | 20.78   |
|              |            | 12      | 6         | 22.00   | 21.10                | 21.20   | 20.73   |
|              |            | 12      | 13        | 22.00   | 20.95                | 21.06   | 20.56   |
|              |            | 25      | 0         | 22.00   | 20.89                | 21.04   | 20.59   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20800CH              | 21100CH | 21400CH |
| 10MHz        | QPSK       | 1       | 0         | 23.00   | 21.43                | 21.67   | 21.47   |
|              |            | 1       | 25        | 23.00   | 21.74                | 21.70   | 21.24   |
|              |            | 1       | 49        | 23.00   | 21.73                | 21.74   | 21.07   |
|              |            | 25      | 0         | 22.00   | 20.63                | 20.64   | 20.36   |
|              |            | 25      | 13        | 22.00   | 20.81                | 20.70   | 20.39   |
|              |            | 25      | 25        | 22.00   | 20.78                | 20.62   | 20.29   |
|              |            | 50      | 0         | 22.00   | 20.86                | 20.53   | 20.34   |
|              | 16QAM      | 1       | 0         | 22.00   | 20.61                | 20.96   | 20.61   |
|              |            | 1       | 25        | 22.00   | 20.96                | 20.97   | 20.55   |
|              |            | 1       | 49        | 22.00   | 20.93                | 21.07   | 20.49   |
|              |            | 25      | 0         | 22.00   | 20.90                | 21.00   | 20.71   |
|              |            | 25      | 13        | 22.00   | 20.97                | 21.05   | 20.62   |
|              |            | 25      | 25        | 22.00   | 21.02                | 20.96   | 20.57   |
|              |            | 50      | 0         | 22.00   | 21.13                | 20.92   | 20.76   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 20825CH      | 21100CH      | 21375CH      |
| 15MHz     | QPSK       | 1       | 0         | 23.00   | 21.22        | 21.49        | 21.39        |
|           |            | 1       | 38        | 23.00   | 21.74        | 21.70        | 21.24        |
|           |            | 1       | 74        | 23.00   | 21.42        | 21.55        | 21.21        |
|           |            | 36      | 0         | 22.00   | 20.72        | 20.56        | 20.40        |
|           |            | 36      | 18        | 22.00   | 20.79        | 20.68        | 20.43        |
|           |            | 36      | 39        | 22.00   | 20.59        | 20.54        | 20.21        |
|           |            | 75      | 0         | 22.00   | 20.73        | 20.46        | 20.42        |
|           | 16QAM      | 1       | 0         | 22.00   | 20.50        | 20.89        | 20.68        |
|           |            | 1       | 38        | 22.00   | 21.03        | 21.08        | 20.65        |
|           |            | 1       | 74        | 22.00   | 20.69        | 21.01        | 20.43        |
|           |            | 36      | 0         | 22.00   | 21.06        | 20.92        | 20.71        |
|           |            | 36      | 18        | 22.00   | 21.10        | 21.06        | 20.73        |
|           |            | 36      | 39        | 22.00   | 20.97        | 20.98        | 20.58        |
|           |            | 75      | 0         | 22.00   | 20.98        | 20.87        | 20.78        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 20850CH      | 21100CH      | 21350CH      |
| 20MHz     | QPSK       | 1       | 0         | 23.00   | 21.39        | <b>21.62</b> | <b>21.67</b> |
|           |            | 1       | 50        | 23.00   | <b>21.62</b> | <b>21.75</b> | 21.35        |
|           |            | 1       | 99        | 23.00   | 21.53        | 21.68        | 21.02        |
|           |            | 50      | 0         | 22.00   | <b>20.77</b> | 20.48        | 20.59        |
|           |            | 50      | 25        | 22.00   | 20.61        | 20.66        | 20.56        |
|           |            | 50      | 50        | 22.00   | 20.54        | 20.65        | 20.33        |
|           |            | 100     | 0         | 22.00   | 20.66        | 20.48        | 20.53        |
|           | 16QAM      | 1       | 0         | 22.00   | 20.87        | 20.92        | 20.94        |
|           |            | 1       | 50        | 22.00   | 20.97        | 20.91        | 20.68        |
|           |            | 1       | 99        | 22.00   | 20.97        | 20.97        | 20.56        |
|           |            | 50      | 0         | 22.00   | 21.08        | 20.85        | 20.92        |
|           |            | 50      | 25        | 22.00   | 21.08        | 21.01        | 20.85        |
|           |            | 50      | 50        | 22.00   | 20.87        | 21.00        | 20.56        |
|           |            | 100     | 0         | 22.00   | 20.92        | 20.87        | 20.90        |

Table 68: Conducted power measurement results of LTE Band VII (Full power)

| LTE Band VII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20775CH              | 21100CH | 21425CH |
| 5MHz         | QPSK       | 1       | 0         | 21.00   | 19.93                | 20.06   | 19.90   |
|              |            | 1       | 13        | 21.00   | 19.83                | 19.87   | 19.68   |
|              |            | 1       | 24        | 21.00   | 20.00                | 19.81   | 19.72   |
|              |            | 12      | 0         | 20.00   | 18.49                | 18.48   | 18.34   |
|              |            | 12      | 6         | 20.00   | 18.61                | 18.59   | 18.37   |
|              |            | 12      | 13        | 20.00   | 18.41                | 18.40   | 18.15   |
|              |            | 25      | 0         | 20.00   | 18.48                | 18.41   | 18.26   |
|              | 16QAM      | 1       | 0         | 20.00   | 18.91                | 19.10   | 18.88   |
|              |            | 1       | 13        | 20.00   | 18.77                | 18.85   | 18.69   |
|              |            | 1       | 24        | 20.00   | 18.85                | 18.85   | 18.62   |
|              |            | 12      | 0         | 20.00   | 18.99                | 18.99   | 18.69   |
|              |            | 12      | 6         | 20.00   | 19.07                | 19.10   | 18.74   |
|              |            | 12      | 13        | 20.00   | 18.94                | 18.90   | 18.55   |
|              |            | 25      | 0         | 20.00   | 18.86                | 18.82   | 18.63   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20800CH              | 21100CH | 21400CH |
| 10MHz        | QPSK       | 1       | 0         | 21.00   | 19.83                | 19.97   | 19.85   |
|              |            | 1       | 25        | 21.00   | 19.92                | 19.87   | 19.68   |
|              |            | 1       | 49        | 21.00   | 20.07                | 19.91   | 19.77   |
|              |            | 25      | 0         | 20.00   | 18.46                | 18.39   | 18.18   |
|              |            | 25      | 13        | 20.00   | 18.59                | 18.46   | 18.28   |
|              |            | 25      | 25        | 20.00   | 18.59                | 18.37   | 18.19   |
|              |            | 50      | 0         | 20.00   | 18.66                | 18.35   | 18.30   |
|              | 16QAM      | 1       | 0         | 20.00   | 18.82                | 19.03   | 18.69   |
|              |            | 1       | 25        | 20.00   | 18.76                | 18.76   | 18.61   |
|              |            | 1       | 49        | 20.00   | 18.81                | 18.75   | 18.50   |
|              |            | 25      | 0         | 20.00   | 18.88                | 18.87   | 18.72   |
|              |            | 25      | 13        | 20.00   | 18.97                | 18.90   | 18.71   |
|              |            | 25      | 25        | 20.00   | 18.95                | 18.81   | 18.60   |
|              |            | 50      | 0         | 20.00   | 19.08                | 18.76   | 18.68   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|-----------|------------|---------|-----------|---------|---------|---------|---------|
|           |            |         |           |         | 20825CH | 21100CH | 21375CH |
| 15MHz     | QPSK       | 1       | 0         | 21.00   | 19.67   | 19.78   | 19.77   |
|           |            | 1       | 38        | 21.00   | 20.01   | 19.87   | 19.74   |
|           |            | 1       | 74        | 21.00   | 19.85   | 19.78   | 19.53   |
|           |            | 36      | 0         | 20.00   | 18.57   | 18.32   | 18.19   |
|           |            | 36      | 18        | 20.00   | 18.66   | 18.50   | 18.26   |
|           |            | 36      | 39        | 20.00   | 18.43   | 18.25   | 18.17   |
|           |            | 75      | 0         | 20.00   | 18.57   | 18.30   | 18.38   |
|           | 16QAM      | 1       | 0         | 20.00   | 18.62   | 18.69   | 18.47   |
|           |            | 1       | 38        | 20.00   | 18.89   | 18.79   | 18.49   |
|           |            | 1       | 74        | 20.00   | 18.64   | 18.65   | 18.34   |
|           |            | 36      | 0         | 20.00   | 19.03   | 18.77   | 18.72   |
|           |            | 36      | 18        | 20.00   | 19.01   | 18.93   | 18.74   |
|           |            | 36      | 39        | 20.00   | 18.85   | 18.75   | 18.59   |
|           |            | 75      | 0         | 20.00   | 18.99   | 18.72   | 18.77   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel | Channel | Channel |
|           |            |         |           |         | 20850CH | 21100CH | 21350CH |
| 20MHz     | QPSK       | 1       | 0         | 21.00   | 19.82   | 19.91   | 20.05   |
|           |            | 1       | 50        | 21.00   | 19.99   | 19.89   | 19.80   |
|           |            | 1       | 99        | 21.00   | 19.96   | 20.02   | 19.72   |
|           |            | 50      | 0         | 20.00   | 18.57   | 18.24   | 18.45   |
|           |            | 50      | 25        | 20.00   | 18.53   | 18.45   | 18.41   |
|           |            | 50      | 50        | 20.00   | 18.35   | 18.44   | 18.22   |
|           |            | 100     | 0         | 20.00   | 18.53   | 18.33   | 18.38   |
|           | 16QAM      | 1       | 0         | 20.00   | 18.99   | 18.86   | 19.07   |
|           |            | 1       | 50        | 20.00   | 19.02   | 18.85   | 18.84   |
|           |            | 1       | 99        | 20.00   | 18.90   | 18.97   | 18.80   |
|           |            | 50      | 0         | 20.00   | 19.03   | 18.70   | 18.91   |
|           |            | 50      | 25        | 20.00   | 18.90   | 18.87   | 18.89   |
|           |            | 50      | 50        | 20.00   | 18.77   | 18.88   | 18.66   |
|           |            | 100     | 0         | 20.00   | 18.99   | 18.74   | 18.80   |

Table 69: Conducted power measurement results of LTE Band VII (Proximity sensor on)

| LTE Band VII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20775CH              | 21100CH | 21425CH |
| 5MHz         | QPSK       | 1       | 0         | 18.00   | 17.09                | 17.15   | 16.83   |
|              |            | 1       | 13        | 18.00   | 17.05                | 16.93   | 16.59   |
|              |            | 1       | 24        | 18.00   | 17.11                | 16.94   | 16.47   |
|              |            | 12      | 0         | 18.00   | 16.87                | 16.75   | 16.59   |
|              |            | 12      | 6         | 18.00   | 16.96                | 16.89   | 16.58   |
|              |            | 12      | 13        | 18.00   | 16.78                | 16.73   | 16.35   |
|              |            | 25      | 0         | 18.00   | 16.80                | 16.74   | 16.47   |
|              | 16QAM      | 1       | 0         | 18.00   | 17.24                | 17.50   | 17.22   |
|              |            | 1       | 13        | 18.00   | 17.25                | 17.33   | 17.07   |
|              |            | 1       | 24        | 18.00   | 17.31                | 17.28   | 16.87   |
|              |            | 12      | 0         | 18.00   | 16.76                | 16.79   | 16.51   |
|              |            | 12      | 6         | 18.00   | 16.85                | 16.95   | 16.50   |
|              |            | 12      | 13        | 18.00   | 16.72                | 16.77   | 16.26   |
|              |            | 25      | 0         | 18.00   | 16.70                | 16.71   | 16.47   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20800CH              | 21100CH | 21400CH |
| 10MHz        | QPSK       | 1       | 0         | 18.00   | 16.90                | 17.15   | 16.86   |
|              |            | 1       | 25        | 18.00   | 17.08                | 17.00   | 16.63   |
|              |            | 1       | 49        | 18.00   | 17.32                | 17.08   | 16.57   |
|              |            | 25      | 0         | 18.00   | 16.74                | 16.68   | 16.45   |
|              |            | 25      | 13        | 18.00   | 16.93                | 16.82   | 16.54   |
|              |            | 25      | 25        | 18.00   | 17.00                | 16.74   | 16.43   |
|              |            | 50      | 0         | 18.00   | 17.01                | 16.70   | 16.51   |
|              | 16QAM      | 1       | 0         | 18.00   | 17.30                | 17.39   | 17.04   |
|              |            | 1       | 25        | 18.00   | 17.43                | 17.32   | 16.88   |
|              |            | 1       | 49        | 18.00   | 17.66                | 17.37   | 16.77   |
|              |            | 25      | 0         | 18.00   | 16.68                | 16.66   | 16.41   |
|              |            | 25      | 13        | 18.00   | 16.85                | 16.80   | 16.49   |
|              |            | 25      | 25        | 18.00   | 16.92                | 16.72   | 16.40   |
|              |            | 50      | 0         | 18.00   | 16.96                | 16.66   | 16.47   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|-----------|------------|---------|-----------|---------|--------------|---------|---------|
|           |            |         |           |         | 20825CH      | 21100CH | 21375CH |
| 15MHz     | QPSK       | 1       | 0         | 18.00   | 16.69        | 16.83   | 16.69   |
|           |            | 1       | 38        | 18.00   | 17.22        | 17.01   | 16.61   |
|           |            | 1       | 74        | 18.00   | 16.95        | 16.86   | 16.34   |
|           |            | 36      | 0         | 18.00   | 16.88        | 16.59   | 16.42   |
|           |            | 36      | 18        | 18.00   | 17.05        | 16.80   | 16.50   |
|           |            | 36      | 39        | 18.00   | 16.81        | 16.67   | 16.30   |
|           |            | 75      | 0         | 18.00   | 16.92        | 16.63   | 16.46   |
|           | 16QAM      | 1       | 0         | 18.00   | 17.19        | 17.11   | 17.10   |
|           |            | 1       | 38        | 18.00   | 17.61        | 17.33   | 16.95   |
|           |            | 1       | 74        | 18.00   | 17.35        | 17.13   | 16.68   |
|           |            | 36      | 0         | 18.00   | 16.91        | 16.64   | 16.48   |
|           |            | 36      | 18        | 18.00   | 17.07        | 16.83   | 16.52   |
|           |            | 36      | 39        | 18.00   | 16.83        | 16.71   | 16.34   |
|           |            | 75      | 0         | 18.00   | 16.93        | 16.64   | 16.53   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|           |            |         |           |         | 20850CH      | 21100CH | 21350CH |
| 20MHz     | QPSK       | 1       | 0         | 18.00   | 16.98        | 17.01   | 17.03   |
|           |            | 1       | 50        | 18.00   | <b>17.12</b> | 16.97   | 16.72   |
|           |            | 1       | 99        | 18.00   | 16.99        | 16.99   | 16.52   |
|           |            | 50      | 0         | 18.00   | 16.95        | 16.54   | 16.78   |
|           |            | 50      | 25        | 18.00   | <b>16.96</b> | 16.81   | 16.66   |
|           |            | 50      | 50        | 18.00   | 16.72        | 16.82   | 16.32   |
|           |            | 100     | 0         | 18.00   | 16.94        | 16.69   | 16.67   |
|           | 16QAM      | 1       | 0         | 18.00   | 17.48        | 17.55   | 17.44   |
|           |            | 1       | 50        | 18.00   | 17.57        | 17.46   | 17.21   |
|           |            | 1       | 99        | 18.00   | 17.41        | 17.55   | 16.93   |
|           |            | 50      | 0         | 18.00   | 16.96        | 16.54   | 16.80   |
|           |            | 50      | 25        | 18.00   | 16.97        | 16.80   | 16.69   |
|           |            | 50      | 50        | 18.00   | 16.73        | 16.82   | 16.35   |
|           |            | 100     | 0         | 18.00   | 16.96        | 16.68   | 16.59   |

Table 70: Conducted power measurement results of LTE Band VII (Hotspot on)

| LTE Band VII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20775CH              | 21100CH | 21425CH |
| 5MHz         | QPSK       | 1       | 0         | 16.00   | 15.10                | 15.33   | 15.09   |
|              |            | 1       | 13        | 16.00   | 15.26                | 15.07   | 14.86   |
|              |            | 1       | 24        | 16.00   | 15.26                | 15.14   | 14.77   |
|              |            | 12      | 0         | 16.00   | 14.91                | 14.92   | 14.77   |
|              |            | 12      | 6         | 16.00   | 15.09                | 15.06   | 14.76   |
|              |            | 12      | 13        | 16.00   | 14.94                | 14.84   | 14.54   |
|              |            | 25      | 0         | 16.00   | 14.95                | 14.83   | 14.66   |
|              | 16QAM      | 1       | 0         | 16.00   | 15.20                | 15.73   | 15.45   |
|              |            | 1       | 13        | 16.00   | 15.40                | 15.44   | 15.21   |
|              |            | 1       | 24        | 16.00   | 15.41                | 15.53   | 15.12   |
|              |            | 12      | 0         | 16.00   | 14.91                | 15.04   | 14.73   |
|              |            | 12      | 6         | 16.00   | 15.07                | 15.16   | 14.74   |
|              |            | 12      | 13        | 16.00   | 14.89                | 14.91   | 14.49   |
|              |            | 25      | 0         | 16.00   | 14.86                | 14.83   | 14.64   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 20800CH              | 21100CH | 21400CH |
| 10MHz        | QPSK       | 1       | 0         | 16.00   | 14.87                | 15.22   | 15.05   |
|              |            | 1       | 25        | 16.00   | 15.20                | 15.11   | 14.96   |
|              |            | 1       | 49        | 16.00   | 15.47                | 15.27   | 14.85   |
|              |            | 25      | 0         | 16.00   | 14.79                | 14.84   | 14.71   |
|              |            | 25      | 13        | 16.00   | 15.02                | 14.91   | 14.79   |
|              |            | 25      | 25        | 16.00   | 15.19                | 14.83   | 14.62   |
|              |            | 50      | 0         | 16.00   | 15.16                | 14.78   | 14.76   |
|              | 16QAM      | 1       | 0         | 16.00   | 15.15                | 15.46   | 15.09   |
|              |            | 1       | 25        | 16.00   | 15.59                | 15.37   | 15.05   |
|              |            | 1       | 49        | 16.00   | 15.72                | 15.60   | 14.90   |
|              |            | 25      | 0         | 16.00   | 14.79                | 14.86   | 14.67   |
|              |            | 25      | 13        | 16.00   | 15.03                | 14.93   | 14.74   |
|              |            | 25      | 25        | 16.00   | 15.12                | 14.84   | 14.57   |
|              |            | 50      | 0         | 16.00   | 15.08                | 14.76   | 14.70   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|-----------|------------|---------|-----------|---------|--------------|---------|---------|
|           |            |         |           |         | 20825CH      | 21100CH | 21375CH |
| 15MHz     | QPSK       | 1       | 0         | 16.00   | 14.62        | 14.90   | 14.89   |
|           |            | 1       | 38        | 16.00   | 15.39        | 15.11   | 14.90   |
|           |            | 1       | 74        | 16.00   | 14.99        | 14.96   | 14.57   |
|           |            | 36      | 0         | 16.00   | 14.93        | 14.76   | 14.72   |
|           |            | 36      | 18        | 16.00   | 15.23        | 14.97   | 14.75   |
|           |            | 36      | 39        | 16.00   | 15.02        | 14.85   | 14.59   |
|           |            | 75      | 0         | 16.00   | 15.08        | 14.73   | 14.76   |
|           | 16QAM      | 1       | 0         | 16.00   | 15.01        | 15.25   | 15.19   |
|           |            | 1       | 38        | 16.00   | 15.83        | 15.44   | 15.17   |
|           |            | 1       | 74        | 16.00   | 15.45        | 15.36   | 14.81   |
|           |            | 36      | 0         | 16.00   | 14.96        | 14.74   | 14.68   |
|           |            | 36      | 18        | 16.00   | 15.19        | 14.95   | 14.72   |
|           |            | 36      | 39        | 16.00   | 14.98        | 14.82   | 14.56   |
|           |            | 75      | 0         | 16.00   | 15.05        | 14.67   | 14.71   |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel | Channel |
|           |            |         |           |         | 20850CH      | 21100CH | 21350CH |
| 20MHz     | QPSK       | 1       | 0         | 16.00   | 14.91        | 15.15   | 15.23   |
|           |            | 1       | 50        | 16.00   | <b>15.30</b> | 15.09   | 14.93   |
|           |            | 1       | 99        | 16.00   | 15.05        | 15.21   | 14.77   |
|           |            | 50      | 0         | 16.00   | 15.10        | 14.72   | 15.02   |
|           |            | 50      | 25        | 16.00   | <b>15.17</b> | 14.91   | 14.92   |
|           |            | 50      | 50        | 16.00   | 14.93        | 14.93   | 14.62   |
|           |            | 100     | 0         | 16.00   | 15.11        | 14.78   | 14.90   |
|           | 16QAM      | 1       | 0         | 16.00   | 15.30        | 15.68   | 15.82   |
|           |            | 1       | 50        | 16.00   | 15.70        | 15.49   | 15.51   |
|           |            | 1       | 99        | 16.00   | 15.45        | 15.66   | 15.27   |
|           |            | 50      | 0         | 16.00   | 15.05        | 14.68   | 15.00   |
|           |            | 50      | 25        | 16.00   | 15.12        | 14.86   | 14.90   |
|           |            | 50      | 50        | 16.00   | 14.88        | 14.90   | 14.60   |
|           |            | 100     | 0         | 16.00   | 15.09        | 14.73   | 14.84   |

Table 71: Conducted power measurement results of LTE Band VII (Proximity sensor on+Hotspot on)

### 7.1.21 Conducted power measurements of LTE Band XII (Main Antenna)

| LTE Band XII |            |         |           |         | Conducted Power(dBm) |         |         |
|--------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23017CH              | 23095CH | 23173CH |
| 1.4MHz       | QPSK       | 1       | 0         | 24.00   | 22.68                | 22.89   | 22.78   |
|              |            | 1       | 3         | 24.00   | 22.93                | 22.99   | 22.86   |
|              |            | 1       | 5         | 24.00   | 22.90                | 22.90   | 22.79   |
|              |            | 3       | 0         | 24.00   | 22.73                | 22.85   | 22.78   |
|              |            | 3       | 2         | 24.00   | 22.83                | 22.91   | 22.79   |
|              |            | 3       | 3         | 24.00   | 22.86                | 22.87   | 22.78   |
|              |            | 6       | 0         | 23.00   | 21.92                | 22.02   | 21.95   |
|              | 16QAM      | 1       | 0         | 23.00   | 21.89                | 22.12   | 21.86   |
|              |            | 1       | 3         | 23.00   | 22.11                | 22.20   | 21.99   |
|              |            | 1       | 5         | 23.00   | 22.13                | 22.16   | 21.93   |
|              |            | 3       | 0         | 23.00   | 21.83                | 21.99   | 21.95   |
|              |            | 3       | 2         | 23.00   | 21.93                | 22.04   | 21.96   |
|              |            | 3       | 3         | 23.00   | 21.93                | 22.01   | 21.97   |
|              |            | 6       | 0         | 22.00   | 20.92                | 20.96   | 20.86   |
| Bandwidth    | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|              |            |         |           |         | 23025CH              | 23095CH | 23165CH |
| 3MHz         | QPSK       | 1       | 0         | 24.00   | 22.49                | 22.66   | 22.91   |
|              |            | 1       | 7         | 24.00   | 23.02                | 23.00   | 23.02   |
|              |            | 1       | 14        | 24.00   | 22.86                | 22.70   | 22.60   |
|              |            | 8       | 0         | 23.00   | 21.89                | 21.92   | 22.01   |
|              |            | 8       | 4         | 23.00   | 22.06                | 22.02   | 22.01   |
|              |            | 8       | 7         | 23.00   | 21.93                | 21.91   | 21.90   |
|              |            | 15      | 0         | 23.00   | 21.88                | 21.92   | 21.99   |
|              | 16QAM      | 1       | 0         | 23.00   | 21.58                | 21.73   | 21.80   |
|              |            | 1       | 7         | 23.00   | 22.21                | 22.10   | 22.01   |
|              |            | 1       | 14        | 23.00   | 21.91                | 21.78   | 21.58   |
|              |            | 8       | 0         | 22.00   | 20.87                | 20.83   | 20.87   |
|              |            | 8       | 4         | 22.00   | 21.04                | 21.00   | 20.88   |
|              |            | 8       | 7         | 22.00   | 20.83                | 20.81   | 20.78   |
|              |            | 15      | 0         | 22.00   | 20.78                | 20.86   | 20.84   |

| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|-----------|------------|---------|-----------|---------|--------------|--------------|--------------|
|           |            |         |           |         | 23035CH      | 23095CH      | 23155CH      |
| 5MHz      | QPSK       | 1       | 0         | 24.00   | 22.45        | 22.50        | 22.74        |
|           |            | 1       | 13        | 24.00   | 23.15        | 22.83        | 22.93        |
|           |            | 1       | 24        | 24.00   | 22.56        | 22.50        | 22.40        |
|           |            | 12      | 0         | 23.00   | 21.87        | 21.79        | 22.02        |
|           |            | 12      | 6         | 23.00   | 22.08        | 21.91        | 22.03        |
|           |            | 12      | 13        | 23.00   | 21.79        | 21.81        | 21.80        |
|           |            | 25      | 0         | 23.00   | 21.82        | 21.83        | 21.92        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.54        | 21.85        | 22.11        |
|           |            | 1       | 13        | 23.00   | 22.15        | 22.23        | 22.27        |
|           |            | 1       | 24        | 23.00   | 21.54        | 21.89        | 21.76        |
|           |            | 12      | 0         | 22.00   | 20.79        | 20.83        | 20.96        |
|           |            | 12      | 6         | 22.00   | 20.97        | 20.96        | 20.98        |
|           |            | 12      | 13        | 22.00   | 20.73        | 20.89        | 20.75        |
|           |            | 25      | 0         | 22.00   | 20.75        | 20.90        | 20.87        |
| Bandwidth | Modulation | RB size | RB offset | Tune-up | Channel      | Channel      | Channel      |
|           |            |         |           |         | 23060CH      | 23095CH      | 23130CH      |
| 10MHz     | QPSK       | 1       | 0         | 24.00   | 22.38        | 22.51        | 22.44        |
|           |            | 1       | 25        | 24.00   | <b>22.84</b> | <b>22.88</b> | <b>23.05</b> |
|           |            | 1       | 49        | 24.00   | 22.29        | 22.33        | 22.15        |
|           |            | 25      | 0         | 23.00   | 21.76        | 21.73        | 21.80        |
|           |            | 25      | 13        | 23.00   | 21.80        | 21.84        | <b>21.95</b> |
|           |            | 25      | 25        | 23.00   | 21.59        | 21.68        | 21.68        |
|           |            | 50      | 0         | 23.00   | 21.67        | 21.67        | 21.78        |
|           | 16QAM      | 1       | 0         | 23.00   | 21.44        | 21.56        | 21.69        |
|           |            | 1       | 25        | 23.00   | 21.97        | 22.10        | 22.22        |
|           |            | 1       | 49        | 23.00   | 21.46        | 21.50        | 21.41        |
|           |            | 25      | 0         | 22.00   | 20.69        | 20.74        | 20.74        |
|           |            | 25      | 13        | 22.00   | 20.73        | 20.80        | 20.88        |
|           |            | 25      | 25        | 22.00   | 20.53        | 20.62        | 20.60        |
|           |            | 50      | 0         | 22.00   | 20.59        | 20.56        | 20.69        |

Table 72: Conducted power measurement results of LTE Band XII

### 7.1.22 Conducted power measurements of LTE Band XVII (Main Antenna)

| LTE Band XVII |            |         |           |         | Conducted Power(dBm) |         |         |
|---------------|------------|---------|-----------|---------|----------------------|---------|---------|
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23755CH              | 23790CH | 23825CH |
| 5MHz          | QPSK       | 1       | 0         | 24.00   | 22.52                | 22.75   | 22.85   |
|               |            | 1       | 13        | 24.00   | 22.92                | 23.07   | 23.03   |
|               |            | 1       | 24        | 24.00   | 22.69                | 22.71   | 22.45   |
|               |            | 12      | 0         | 23.00   | 21.88                | 22.03   | 22.09   |
|               |            | 12      | 6         | 23.00   | 22.02                | 22.19   | 22.14   |
|               |            | 12      | 13        | 23.00   | 21.97                | 21.99   | 21.97   |
|               |            | 25      | 0         | 23.00   | 21.98                | 22.08   | 22.07   |
|               | 16QAM      | 1       | 0         | 23.00   | 21.77                | 21.92   | 22.19   |
|               |            | 1       | 13        | 23.00   | 22.28                | 22.28   | 22.42   |
|               |            | 1       | 24        | 23.00   | 21.89                | 21.88   | 21.93   |
|               |            | 12      | 0         | 22.00   | 20.95                | 21.13   | 21.09   |
|               |            | 12      | 6         | 22.00   | 21.12                | 21.24   | 21.12   |
|               |            | 12      | 13        | 22.00   | 20.91                | 20.99   | 20.89   |
|               |            | 25      | 0         | 22.00   | 21.01                | 21.03   | 21.09   |
| Bandwidth     | Modulation | RB size | RB offset | Tune-up | Channel              | Channel | Channel |
|               |            |         |           |         | 23780CH              | 23790CH | 23800CH |
| 10MHz         | QPSK       | 1       | 0         | 24.00   | 22.43                | 22.48   | 22.59   |
|               |            | 1       | 25        | 24.00   | 23.19                | 23.09   | 23.12   |
|               |            | 1       | 49        | 24.00   | 22.59                | 22.41   | 22.34   |
|               |            | 25      | 0         | 23.00   | 21.84                | 21.87   | 21.93   |
|               |            | 25      | 13        | 23.00   | 22.11                | 22.10   | 22.12   |
|               |            | 25      | 25        | 23.00   | 21.83                | 21.84   | 21.84   |
|               |            | 50      | 0         | 23.00   | 21.84                | 21.89   | 21.87   |
|               | 16QAM      | 1       | 0         | 23.00   | 21.71                | 21.70   | 21.64   |
|               |            | 1       | 25        | 23.00   | 22.35                | 22.38   | 22.11   |
|               |            | 1       | 49        | 23.00   | 21.77                | 21.58   | 21.33   |
|               |            | 25      | 0         | 22.00   | 20.78                | 20.85   | 20.89   |
|               |            | 25      | 13        | 22.00   | 21.01                | 21.12   | 21.01   |
|               |            | 25      | 25        | 22.00   | 20.79                | 20.78   | 20.75   |
|               |            | 50      | 0         | 22.00   | 20.75                | 20.80   | 20.88   |

Table 73: Conducted power measurement results of LTE Band XVII

### 7.1.23 Conducted power measurements of WiFi 2.4G

The output power of WiFi antenna is as following:

| Mode        | Channel | Frequency (MHz) | Data Rate (Mbps) | Tune-up | Average Power (dBm) | SAR Test (Yes/No) |
|-------------|---------|-----------------|------------------|---------|---------------------|-------------------|
| 802.11b     | 1       | 2412            | 1                | 16.5    | <b>14.82</b>        | Yes               |
|             | 6       | 2437            |                  | 16.5    | 14.81               | Yes               |
|             | 11      | 2462            |                  | 16.5    | 14.77               | Yes               |
| 802.11g     | 1       | 2412            | 6                | 17.0    | 15.66               | No                |
|             | 6       | 2437            |                  | 17.0    | 15.49               | No                |
|             | 10      | 2457            |                  | 17.0    | 15.21               | No                |
|             | 11      | 2462            |                  | 15.5    | 13.51               | No                |
| 802.11n-20M | 1       | 2412            | 6.5              | 17.0    | 15.89               | No                |
|             | 6       | 2437            |                  | 17.0    | 15.76               | No                |
|             | 10      | 2457            |                  | 17.0    | 15.16               | No                |
|             | 11      | 2462            |                  | 14.5    | 12.60               | No                |
| 802.11n-40M | 3       | 2422            | 13.5             | 14.5    | 12.53               | No                |
|             | 6       | 2437            |                  | 14.5    | 12.55               | No                |
|             | 9       | 2452            |                  | 14.5    | 12.58               | No                |

Table 74: Conducted power measurement results of WiFi 2.4G(Full power level).

Note: 1) The Average conducted power of WiFi is measured with RMS detector.

| Mode        | Channel | Frequency (MHz) | Data Rate (Mbps) | Tune-up | Average Power (dBm) | SAR Test (Yes/No) |
|-------------|---------|-----------------|------------------|---------|---------------------|-------------------|
| 802.11b     | 1       | 2412            | 1                | 11.0    | <b>10.40</b>        | Yes               |
|             | 6       | 2437            |                  | 11.0    | <b>10.39</b>        | Yes               |
|             | 11      | 2462            |                  | 11.0    | <b>10.10</b>        | Yes               |
| 802.11g     | 1       | 2412            | 6                | 11.0    | 10.34               | No                |
|             | 6       | 2437            |                  | 11.0    | 10.35               | No                |
|             | 11      | 2462            |                  | 11.0    | 10.05               | No                |
| 802.11n-20M | 1       | 2412            | 6.5              | 11.0    | 10.51               | No                |
|             | 6       | 2437            |                  | 11.0    | 10.54               | No                |
|             | 11      | 2462            |                  | 11.0    | 10.23               | No                |
| 802.11n-40M | 3       | 2422            | 13.5             | 11.0    | 10.17               | No                |
|             | 6       | 2437            |                  | 11.0    | 10.10               | No                |
|             | 9       | 2452            |                  | 11.0    | 9.27                | No                |

Table 75: Conducted power measurement results of WiFi 2.4G (infrared proximity sensor on, reduced power level).

Note: 1) The Average conducted power of WiFi is measured with RMS detector.

### 7.1.24 Conducted power measurements of BT

The output power of BT antenna is as following:

| BT 2450 | Tune-up | Average Conducted Power (dBm) |             |             |
|---------|---------|-------------------------------|-------------|-------------|
|         |         | 0CH                           | 39CH        | 78CH        |
| DH5     | 8.0     | <b>6.05</b>                   | <b>7.45</b> | <b>7.65</b> |
| 2DH5    | 8.0     | 4.10                          | 5.21        | 5.51        |
| 3DH5    | 8.0     | 4.04                          | 5.25        | 5.58        |

| BT 2450 | Tune-up | Average Conducted Power (dBm) |      |      |
|---------|---------|-------------------------------|------|------|
|         |         | 0CH                           | 19CH | 39CH |
| BT BLE  | 4.0     | 1.10                          | 2.25 | 2.51 |

Table 76: Conducted power measurement results of BT.

Note:

- 1) The conducted power of BT is measured with RMS detector.
- 2) The bolded mode was selected for SAR testing.



Figure: Bluetooth Transmission Plot

So the bluetooth duty cycle is calculated as below:

$$Dutycycle = pulse \frac{width}{period} * 100\% = \frac{2.887ms}{3.7565ms} * 100\% = 76.9\%$$

## 7.2 SAR measurement Results

### General Notes:

- 1) Per KDB447498 D01, all SAR measurement results are scaled to the maximum tune-up tolerance limit to demonstrate SAR compliance.
- 2) Per KDB447498 D01, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- $\leq 0.8\text{W/kg}$  for 1-g or  $2.0\text{W/kg}$  for 10-g respectively, when the transmission band is  $\leq 100\text{MHz}$ .
- $\leq 0.6\text{ W/kg}$  or  $1.5\text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz.
- $\leq 0.4\text{ W/kg}$  or  $1.0\text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\geq 200\text{ MHz}$ .

When the maximum output power variation across the required test channels is  $> \frac{1}{2}\text{ dB}$ , instead of the middle channel, the highest output power channel must be used.

- 3) Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8\text{W/kg}$ ; if the deviation among the repeated measurement is  $\leq 20\%$ , and the measured SAR  $< 1.45\text{W/Kg}$ , only one repeated measurement is required.
- 4) Per KDB941225 D06, the DUT Dimension is bigger than 9 cm x 5 cm, so 10mm is chosen as the test separation distance for Hotspot mode. When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.
- 5) Per KDB648474 D04, SAR is evaluated without a headset connected to the device. When the standalone reported body-worn SAR is  $\leq 1.2\text{ W/kg}$ , no additional SAR evaluations using a headset are required.
- 6) Per KDB865664 D02, SAR plot is only required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination; Plots are also required when the measured SAR is  $> 1.5\text{ W/kg}$ , or  $> 7.0\text{ W/kg}$  for occupational exposure. The published RF exposure KDB procedures may require additional plots; for example, to support SAR to peak location separation ratio test exclusion and/or volume scan post-processing(Refer to appendix B for details).
- 7) Per KDB 648474D04, for handsets with additional batteries, the highest reported SAR for each wireless technology, frequency band, operating mode and applicable exposure condition (head, body-worn accessory, hotspot mode, etc.) must be repeated with the specific accessory attached. In addition, for test cases where the measured SAR for a handset is greater than  $1.2\text{ W/kg}$ , these tests should also be repeated with the additional batteries.

### GSM Notes:

- 1) Per KDB941225 D01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.
- 2) Per KDB648474 D04, the device does not support DTM function. Body-worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.

#### UMTS Notes:

1) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the Second mode.

#### LTE Notes:

1) The LTE test configurations are determined according to KDB941225 D05 SAR for LTE Devices. The general test procedures used for SAR testing can be found in Section 6.5.

2) A-MPR was disabled for all SAR test by setting NS\_01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI)

#### WiFi Notes:

Per KDB248227D01:

1) When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test position is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is  $\leq 0.8$  W/kg or all test position are measured. For all positions/configurations tested using the initial test position and subsequent test positions, when the *reported* SAR is  $> 0.8$  W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the *reported* SAR is  $\leq 1.2$  W/kg or all required channels are tested..

2) The highest SAR measured for the initial test position or initial test configuration should be used to determine SAR test exclusion according to the sum of 1-g SAR and SAR peak to location ratio provisions in KDB 447498. In addition, a test lab may also choose to perform standalone SAR measurements for test positions and 802.11 configurations that are not required by the initial test position or initial test configuration procedures and apply the results to determine simultaneous transmission SAR test exclusion, according to sum of 1-g and SAR peak to location ratio requirements to reduce the number of simultaneous transmission SAR measurements.

3) The device not supports VoWiFi function. Head SAR for Wi-Fi antenna is evaluated at reduced power levels according to the real usage scenarios.

## 7.2.1 SAR measurement Result of GSM850 (Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 190/836.6           | GSM       | 0.271            | 0.152 | 0.03             | 29.34                 | 30.50               | 0.354                   | Battery1#             | /         |
| Left tilt             | 190/836.6           | GSM       | 0.238            | 0.129 | -0.06            | 29.34                 | 30.50               | 0.311                   | Battery1#             | /         |
| Right touch           | 190/836.6           | GSM       | 0.695            | 0.357 | -0.08            | 29.34                 | 30.50               | 0.908                   | Battery1#             | /         |
| Right tilt            | 190/836.6           | GSM       | 0.587            | 0.284 | -0.04            | 29.34                 | 30.50               | 0.767                   | Battery1#             | /         |
| Right touch           | 190/836.6           | GSM       | 0.666            | 0.345 | -0.08            | 29.34                 | 30.50               | 0.870                   | SIM2                  | /         |
| Right touch           | 190/836.6           | GSM       | 0.726            | 0.365 | -0.04            | 29.34                 | 30.50               | 0.948                   | Battery 2#            | /         |
| Right touch           | 190/836.6           | GSM       | 0.705            | 0.361 | -0.04            | 29.34                 | 30.50               | 0.921                   | Battery 3#            | /         |
| Right touch           | 128/824.2           | GSM       | 0.772            | 0.397 | -0.03            | 29.37                 | 30.50               | 1.001                   | Battery 2#            | Yes       |
| Right touch           | 251/848.8           | GSM       | 0.630            | 0.323 | -0.08            | 29.28                 | 30.50               | 0.834                   | Battery 2#            | /         |

Table 77: Head SAR test results of GSM850

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 190/836.6           | GSM       | 0.236            | 0.175 | -0.04            | 32.40                 | 33.50               | 0.304                   | Battery1#             | /         |
| Back Side                       | 190/836.6           | GSM       | 0.353            | 0.254 | -0.06            | 32.40                 | 33.50               | 0.455                   | Battery1#             | /         |
| Back Side                       | 190/836.6           | GSM       | 0.334            | 0.196 | -0.13            | 32.40                 | 33.50               | 0.430                   | SIM2                  | /         |
| Back Side                       | 190/836.6           | GSM       | 0.369            | 0.259 | -0.03            | 32.40                 | 33.50               | 0.475                   | Battery 2#            | Yes       |
| Back Side                       | 190/836.6           | GSM       | 0.288            | 0.192 | -0.10            | 32.40                 | 33.50               | 0.371                   | Battery 3#            | /         |

Table 78: Body-Worn SAR test results of GSM850

| Test Position of Hotspot 10mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 190/836.6           | GPRS 2TS  | 0.105            | 0.061 | 0.09             | 25.30                 | 26.50               | 0.138                   | Battery1#             | /         |
| Back Side                     | 190/836.6           | GPRS 2TS  | 0.184            | 0.103 | -0.02            | 25.30                 | 26.50               | 0.243                   | Battery1#             | /         |
| Left Side                     | 190/836.6           | GPRS 2TS  | 0.112            | 0.074 | -0.05            | 25.30                 | 26.50               | 0.148                   | Battery1#             | /         |
| Top Side                      | 190/836.6           | GPRS 2TS  | 0.087            | 0.042 | -0.07            | 25.30                 | 26.50               | 0.115                   | Battery1#             | /         |
| Back Side                     | 190/836.6           | GPRS 2TS  | 0.192            | 0.107 | -0.12            | 25.30                 | 26.50               | 0.253                   | SIM2                  | /         |
| Back Side                     | 190/836.6           | GPRS 2TS  | 0.234            | 0.127 | -0.12            | 25.30                 | 26.50               | 0.308                   | Battery 2#            | Yes       |
| Back Side                     | 190/836.6           | GPRS 2TS  | 0.208            | 0.126 | 0.03             | 25.30                 | 26.50               | 0.274                   | Battery 3#            | /         |

Table 79: Hotspot SAR test results of GSM850

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 190/836.6           | GPRS 2TS  | 0.105            | 0.061 | 0.09             | 25.30                 | 31.50               | 0.438                   | Battery1#             | Yes                                 |
| Back Side                | 190/836.6           | GPRS 2TS  | 0.184            | 0.103 | -0.02            | 25.30                 | 31.50               | 0.767                   | Battery1#             | Yes                                 |
| Left Side                | 190/836.6           | GPRS 2TS  | 0.112            | 0.074 | -0.05            | 25.30                 | 31.50               | 0.467                   | Battery1#             | Yes                                 |
| Top Side                 | 190/836.6           | GPRS 2TS  | 0.087            | 0.042 | -0.07            | 25.30                 | 31.50               | 0.364                   | Battery1#             | Yes                                 |
| Back Side                | 190/836.6           | GPRS 2TS  | 0.192            | 0.107 | -0.12            | 25.30                 | 31.50               | 0.800                   | SIM2                  | Yes                                 |
| Back Side                | 190/836.6           | GPRS 2TS  | 0.234            | 0.127 | -0.12            | 25.30                 | 31.50               | 0.975                   | Battery 2#            | Yes                                 |
| Back Side                | 190/836.6           | GPRS 2TS  | 0.208            | 0.126 | 0.03             | 25.30                 | 31.50               | 0.867                   | Battery 3#            | Yes                                 |

Table 80: Product Specific 10-g SAR test reduction evaluation of GSM850

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.2 SAR measurement Result of GSM1900 (Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 661/1880            | GSM       | 0.100            | 0.063 | 0.06             | 26.31                 | 28.00               | 0.148                   | Battery1#             | /         |
| Left tilt             | 661/1880            | GSM       | 0.093            | 0.050 | 0.10             | 26.31                 | 28.00               | 0.137                   | Battery1#             | /         |
| Right touch           | 661/1880            | GSM       | 0.300            | 0.171 | 0.01             | 26.31                 | 28.00               | 0.443                   | Battery1#             | Yes       |
| Right tilt            | 661/1880            | GSM       | 0.183            | 0.101 | 0.11             | 26.31                 | 28.00               | 0.270                   | Battery1#             | /         |
| Right touch           | 661/1880            | GSM       | 0.246            | 0.141 | 0.10             | 26.31                 | 28.00               | 0.363                   | SIM2                  | /         |
| Right touch           | 661/1880            | GSM       | 0.262            | 0.151 | 0.17             | 26.46                 | 28.00               | 0.374                   | Battery 2#            | /         |
| Right touch           | 661/1880            | GSM       | 0.148            | 0.084 | 0.13             | 26.46                 | 28.00               | 0.211                   | Battery 3#            | /         |
| Right touch           | 512/1850.2          | GSM       | 0.298            | 0.169 | 0.13             | 26.46                 | 28.00               | 0.425                   | Battery1#             | /         |
| Right touch           | 810/1909.8          | GSM       | 0.265            | 0.151 | 0.02             | 26.37                 | 28.00               | 0.386                   | Battery1#             | /         |

Table 81: Head SAR test results of GSM1900

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 661/1880            | GSM       | 0.017            | 0.010 | -0.12            | 28.44                 | 30.00               | 0.024                   | Battery1#             | /         |
| Back Side                       | 661/1880            | GSM       | 0.031            | 0.017 | -0.19            | 28.44                 | 30.00               | 0.044                   | Battery1#             | /         |
| Back Side                       | 661/1880            | GSM       | 0.031            | 0.017 | 0.03             | 28.44                 | 30.00               | 0.045                   | Battery 2#            | /         |
| Back Side                       | 661/1880            | GSM       | 0.032            | 0.018 | -0.15            | 28.44                 | 30.00               | 0.045                   | Battery 3#            | Yes       |
| Back Side                       | 661/1880            | GSM       | 0.030            | 0.017 | -0.18            | 28.44                 | 30.00               | 0.043                   | SIM2                  | /         |

Table 82: Body-Worn SAR test results of GSM1900

| Test Position of Hotspot 10mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 661/1880            | GPRS 2TS  | 0.015            | 0.008 | -0.18            | 21.31                 | 23.00               | 0.022                   | Battery1#             | /         |
| Back Side                     | 661/1880            | GPRS 2TS  | 0.026            | 0.013 | 0.16             | 21.31                 | 23.00               | 0.039                   | Battery1#             | /         |
| Left Side                     | 661/1880            | GPRS 2TS  | 0.017            | 0.009 | -0.15            | 21.31                 | 23.00               | 0.025                   | Battery1#             | /         |
| Top Side                      | 661/1880            | GPRS 2TS  | 0.027            | 0.014 | -0.13            | 21.31                 | 23.00               | 0.040                   | Battery1#             | /         |
| Top Side                      | 661/1880            | GPRS 2TS  | 0.029            | 0.015 | -0.17            | 21.31                 | 23.00               | 0.042                   | Battery 2#            | Yes       |
| Top Side                      | 661/1880            | GPRS 2TS  | 0.028            | 0.015 | 0.11             | 21.31                 | 23.00               | 0.041                   | Battery 3#            | /         |
| Top Side                      | 661/1880            | GPRS 2TS  | 0.027            | 0.014 | 0.11             | 21.31                 | 23.00               | 0.040                   | SIM2                  | /         |

Table 83: Hotspot SAR test results of GSM1900

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 661/1880            | GPRS 2TS  | 0.015            | 0.008 | -0.18            | 21.31                 | 28.00               | 0.069                   | Battery1#             | Yes                                 |
| Back Side                | 661/1880            | GPRS 2TS  | 0.026            | 0.013 | 0.16             | 21.31                 | 28.00               | 0.122                   | Battery1#             | Yes                                 |
| Left Side                | 661/1880            | GPRS 2TS  | 0.017            | 0.009 | -0.15            | 21.31                 | 28.00               | 0.079                   | Battery1#             | Yes                                 |
| Top Side                 | 661/1880            | GPRS 2TS  | 0.027            | 0.014 | -0.13            | 21.31                 | 28.00               | 0.125                   | Battery1#             | Yes                                 |
| Top Side                 | 661/1880            | GPRS 2TS  | 0.029            | 0.015 | -0.17            | 21.31                 | 28.00               | 0.133                   | Battery 2#            | Yes                                 |
| Top Side                 | 661/1880            | GPRS 2TS  | 0.028            | 0.015 | 0.11             | 21.31                 | 28.00               | 0.131                   | Battery 3#            | Yes                                 |
| Top Side                 | 661/1880            | GPRS 2TS  | 0.027            | 0.014 | 0.11             | 21.31                 | 28.00               | 0.127                   | SIM2                  | Yes                                 |

Table 84: Product Specific 10-g SAR test reduction evaluation of GSM1900

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

### 7.2.3 SAR measurement Result of UMTS Band II(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 9400/1880           | RMC       | 0.107            | 0.065 | 0.00             | 18.77                 | 20.00               | 0.142                   | Battery1#             | /         |
| Left tilt             | 9400/1880           | RMC       | 0.096            | 0.056 | 0.01             | 18.77                 | 20.00               | 0.127                   | Battery1#             | /         |
| Right touch           | 9400/1880           | RMC       | 0.275            | 0.159 | -0.12            | 18.77                 | 20.00               | 0.365                   | Battery1#             | /         |
| Right tilt            | 9400/1880           | RMC       | 0.223            | 0.121 | -0.07            | 18.77                 | 20.00               | 0.296                   | Battery1#             | /         |
| Right touch           | 9400/1880           | RMC       | 0.288            | 0.165 | -0.02            | 18.77                 | 20.00               | 0.382                   | SIM2                  | /         |
| Right touch           | 9400/1880           | RMC       | 0.518            | 0.299 | -0.04            | 18.77                 | 20.00               | 0.688                   | Battery 2#            | /         |
| Right touch           | 9400/1880           | RMC       | 0.545            | 0.314 | -0.05            | 18.77                 | 20.00               | 0.723                   | Battery 3#            | /         |
| Right touch           | 9262/1852.4         | RMC       | 0.486            | 0.286 | -0.05            | 18.63                 | 20.00               | 0.666                   | Battery 3#            | /         |
| Right touch           | 9538/1907.6         | RMC       | 0.623            | 0.359 | -0.10            | 18.87                 | 20.00               | 0.808                   | Battery 3#            | Yes       |

Table 85: Head SAR test results of UMTS Band II

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 9400/1880           | RMC       | 0.034            | 0.021 | -0.11            | 21.80                 | 23.00               | 0.044                   | Battery1#             | /         |
| Back Side                       | 9400/1880           | RMC       | 0.061            | 0.034 | -0.18            | 21.80                 | 23.00               | 0.081                   | Battery1#             | /         |
| Back Side                       | 9400/1880           | RMC       | 0.067            | 0.037 | -0.19            | 21.80                 | 23.00               | 0.088                   | Battery 2#            | Yes       |
| Back Side                       | 9400/1880           | RMC       | 0.061            | 0.033 | -0.16            | 21.80                 | 23.00               | 0.080                   | Battery 3#            | /         |
| Back Side                       | 9400/1880           | RMC       | 0.060            | 0.033 | -0.15            | 21.80                 | 23.00               | 0.079                   | SIM2                  | /         |

Table 86: Body-Worn SAR test results of UMTS Band II

| Test Position of Hotspot 10mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 9400/1880           | RMC       | 0.034            | 0.018 | 0.15             | 15.75                 | 17.00               | 0.045                   | Battery1#             | /         |
| Back Side                     | 9400/1880           | RMC       | 0.071            | 0.036 | 0.03             | 15.75                 | 17.00               | 0.095                   | Battery1#             | Yes       |
| Left Side                     | 9400/1880           | RMC       | 0.044            | 0.026 | 0.16             | 15.75                 | 17.00               | 0.059                   | Battery1#             | /         |
| Top Side                      | 9400/1880           | RMC       | 0.054            | 0.028 | -0.01            | 15.75                 | 17.00               | 0.072                   | Battery1#             | /         |
| Back Side                     | 9400/1880           | RMC       | 0.066            | 0.034 | -0.17            | 15.75                 | 17.00               | 0.088                   | Battery 2#            | /         |
| Back Side                     | 9400/1880           | RMC       | 0.063            | 0.032 | -0.18            | 15.75                 | 17.00               | 0.084                   | Battery 3#            | /         |
| Back Side                     | 9400/1880           | RMC       | 0.063            | 0.031 | 0.16             | 15.75                 | 17.00               | 0.083                   | Battery1#             | /         |

Table 87: Hotspot SAR test results of UMTS Band II

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 9400/1880           | RMC       | 0.034            | 0.018 | 0.15             | 15.75                 | 23.00               | 0.181                   | Battery1#             | Yes                                 |
| Back Side                | 9400/1880           | RMC       | 0.071            | 0.036 | 0.03             | 15.75                 | 23.00               | 0.379                   | Battery1#             | Yes                                 |
| Left Side                | 9400/1880           | RMC       | 0.044            | 0.026 | 0.16             | 15.75                 | 23.00               | 0.236                   | Battery1#             | Yes                                 |
| Top Side                 | 9400/1880           | RMC       | 0.054            | 0.028 | -0.01            | 15.75                 | 23.00               | 0.286                   | Battery1#             | Yes                                 |
| Back Side                | 9400/1880           | RMC       | 0.066            | 0.034 | -0.17            | 15.75                 | 23.00               | 0.352                   | Battery 2#            | Yes                                 |
| Back Side                | 9400/1880           | RMC       | 0.063            | 0.032 | -0.18            | 15.75                 | 23.00               | 0.334                   | Battery 3#            | Yes                                 |
| Back Side                | 9400/1880           | RMC       | 0.063            | 0.031 | 0.16             | 15.75                 | 23.00               | 0.332                   | Battery1#             | Yes                                 |

Table 88: Product Specific 10-g SAR test reduction evaluation of UMTS Band II

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.4 SAR measurement Result of UMTS Band IV(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 1413/1732.6         | RMC       | 0.310            | 0.195 | -0.01            | 19.92                 | 21.00               | 0.398                   | Battery1#             | /         |
| Left tilt             | 1413/1732.6         | RMC       | 0.322            | 0.179 | -0.02            | 19.92                 | 21.00               | 0.413                   | Battery1#             | /         |
| Right touch           | 1413/1732.6         | RMC       | 0.683            | 0.386 | -0.05            | 19.92                 | 21.00               | 0.876                   | Battery1#             | /         |
| Right tilt            | 1413/1732.6         | RMC       | 0.536            | 0.269 | 0.00             | 19.92                 | 21.00               | 0.687                   | Battery1#             | /         |
| Right touch           | 1413/1732.6         | RMC       | 0.770            | 0.422 | -0.03            | 19.92                 | 21.00               | 0.987                   | SIM2                  | /         |
| Right touch           | 1413/1732.6         | RMC       | 0.868            | 0.467 | 0.07             | 19.92                 | 21.00               | 1.113                   | Battery 2#            | Yes       |
| Right touch-Repeated  | 1413/1732.6         | RMC       | 0.731            | 0.412 | -0.02            | 19.92                 | 21.00               | 0.937                   | Battery 2#            | /         |
| Right touch           | 1413/1732.6         | RMC       | 0.774            | 0.427 | -0.03            | 19.92                 | 21.00               | 0.993                   | Battery 3#            | /         |
| Right touch           | 1312/1712.4         | RMC       | 0.791            | 0.434 | 0.03             | 19.95                 | 21.00               | 1.007                   | Battery 2#            | /         |
| Right touch           | 1513/1752.6         | RMC       | 0.758            | 0.421 | 0.03             | 19.96                 | 21.00               | 0.963                   | Battery 2#            | /         |

Table 89: Head SAR test results of UMTS Band IV

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 1413/1732.6         | RMC       | 0.085            | 0.057 | -0.15            | 21.95                 | 23.00               | 0.108                   | Battery1#             | /         |
| Back Side                       | 1413/1732.6         | RMC       | 0.153            | 0.084 | -0.13            | 21.95                 | 23.00               | 0.195                   | Battery1#             | Yes       |
| Back Side                       | 1413/1732.6         | RMC       | 0.148            | 0.082 | -0.13            | 21.95                 | 23.00               | 0.188                   | SIM2                  | /         |
| Back Side                       | 1413/1732.6         | RMC       | 0.105            | 0.058 | -0.12            | 21.95                 | 23.00               | 0.134                   | Battery 2#            | /         |
| Back Side                       | 1413/1732.6         | RMC       | 0.096            | 0.053 | -0.13            | 21.95                 | 23.00               | 0.122                   | Battery 3#            | /         |

Table 90: Body-Worn SAR test results of UMTS Band IV

| Test Position of Hotspot 10mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 1413/1732.6         | RMC       | 0.078            | 0.042 | -0.06            | 17.90                 | 19.00               | 0.101                   | Battery1#             | /         |
| Back Side                     | 1413/1732.6         | RMC       | 0.139            | 0.072 | 0.08             | 17.90                 | 19.00               | 0.179                   | Battery1#             | /         |
| Left Side                     | 1413/1732.6         | RMC       | 0.094            | 0.056 | -0.17            | 17.90                 | 19.00               | 0.121                   | Battery1#             | /         |
| Right Side                    | 1413/1732.6         | RMC       | 0.018            | 0.009 | -0.14            | 17.90                 | 19.00               | 0.023                   | Battery1#             | /         |
| Top Side                      | 1413/1732.6         | RMC       | 0.229            | 0.121 | 0.03             | 17.90                 | 19.00               | 0.295                   | Battery1#             | Yes       |
| Top Side                      | 1413/1732.6         | RMC       | 0.139            | 0.073 | -0.19            | 17.90                 | 19.00               | 0.179                   | SIM2                  | /         |
| Top Side                      | 1413/1732.6         | RMC       | 0.153            | 0.081 | 0.18             | 17.90                 | 19.00               | 0.197                   | Battery 2#            | /         |
| Top Side                      | 1413/1732.6         | RMC       | 0.147            | 0.077 | 0.11             | 17.90                 | 19.00               | 0.189                   | Battery 3#            | /         |

Table 91: Hotspot SAR test results of UMTS Band IV

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 1413/1732.6         | RMC       | 0.078            | 0.042 | -0.06            | 17.90                 | 23.00               | 0.253                   | Battery1#             | Yes                                 |
| Back Side                | 1413/1732.6         | RMC       | 0.139            | 0.072 | 0.08             | 17.90                 | 23.00               | 0.450                   | Battery1#             | Yes                                 |
| Left Side                | 1413/1732.6         | RMC       | 0.094            | 0.056 | -0.17            | 17.90                 | 23.00               | 0.303                   | Battery1#             | Yes                                 |
| Right Side               | 1413/1732.6         | RMC       | 0.018            | 0.009 | -0.14            | 17.90                 | 23.00               | 0.057                   | Battery1#             | Yes                                 |
| Top Side                 | 1413/1732.6         | RMC       | 0.229            | 0.121 | 0.03             | 17.90                 | 23.00               | 0.741                   | Battery1#             | Yes                                 |
| Top Side                 | 1413/1732.6         | RMC       | 0.139            | 0.073 | -0.19            | 17.90                 | 23.00               | 0.450                   | SIM2                  | Yes                                 |
| Top Side                 | 1413/1732.6         | RMC       | 0.153            | 0.081 | 0.18             | 17.90                 | 23.00               | 0.495                   | Battery 2#            | Yes                                 |
| Top Side                 | 1413/1732.6         | RMC       | 0.147            | 0.077 | 0.11             | 17.90                 | 23.00               | 0.476                   | Battery 3#            | Yes                                 |

Table 92: Product Specific 10-g SAR test reduction evaluation of UMTS Band IV

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.5 SAR measurement Result of UMTS Band V(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 4182/836.4          | RMC       | 0.336            | 0.190 | 0.11             | 19.34                 | 20.50               | 0.439                   | Battery1#             | /         |
| Left tilt             | 4182/836.4          | RMC       | 0.333            | 0.204 | -0.18            | 19.34                 | 20.50               | 0.435                   | Battery1#             | /         |
| Right touch           | 4182/836.4          | RMC       | 0.563            | 0.287 | -0.19            | 19.34                 | 20.50               | 0.735                   | Battery1#             | /         |
| Right tilt            | 4182/836.4          | RMC       | 0.544            | 0.316 | -0.16            | 19.34                 | 20.50               | 0.711                   | Battery1#             | /         |
| Right touch           | 4182/836.4          | RMC       | 0.607            | 0.308 | -0.02            | 19.34                 | 20.50               | 0.793                   | SIM2                  | /         |
| Right touch           | 4182/836.4          | RMC       | 0.550            | 0.278 | -0.02            | 19.34                 | 20.50               | 0.718                   | Battery 2#            | /         |
| Right touch           | 4182/836.4          | RMC       | 0.632            | 0.319 | -0.07            | 19.34                 | 20.50               | 0.826                   | Battery 3#            | /         |
| Right touch           | 4132/826.4          | RMC       | 0.653            | 0.330 | 0.18             | 19.33                 | 20.50               | 0.855                   | Battery 3#            | Yes       |
| Right touch           | 4233/846.6          | RMC       | 0.592            | 0.300 | -0.01            | 19.38                 | 20.50               | 0.766                   | Battery 3#            | /         |

Table 93: Head SAR test results of UMTS Band V

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 4182/836.4          | RMC       | 0.185            | 0.112 | -0.19            | 22.87                 | 24.00               | 0.240                   | Battery1#             | /         |
| Back Side                       | 4182/836.4          | RMC       | 0.287            | 0.171 | 0.03             | 22.87                 | 24.00               | 0.372                   | Battery1#             | /         |
| Back Side                       | 4182/836.4          | RMC       | 0.279            | 0.175 | -0.01            | 22.87                 | 24.00               | 0.362                   | SIM2                  | /         |
| Back Side                       | 4182/836.4          | RMC       | 0.315            | 0.184 | -0.05            | 22.87                 | 24.00               | 0.409                   | Battery 2#            | Yes       |
| Back Side                       | 4182/836.4          | RMC       | 0.254            | 0.162 | -0.09            | 22.87                 | 24.00               | 0.329                   | Battery 3#            | /         |

Table 94: Body-Worn SAR test results of UMTS Band V

| Test Position of Hotspot 10mm | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 4182/836.4          | RMC       | 0.091            | 0.053 | -0.18            | 16.85                 | 18.00               | 0.119                   | Battery1#             | /         |
| Back Side                     | 4182/836.4          | RMC       | 0.194            | 0.106 | -0.17            | 16.85                 | 18.00               | 0.253                   | Battery1#             | Yes       |
| Left Side                     | 4182/836.4          | RMC       | 0.083            | 0.055 | -0.09            | 16.85                 | 18.00               | 0.108                   | Battery1#             | /         |
| Top Side                      | 4182/836.4          | RMC       | 0.070            | 0.034 | -0.12            | 16.85                 | 18.00               | 0.091                   | Battery1#             | /         |
| Back Side                     | 4182/836.4          | RMC       | 0.160            | 0.103 | -0.12            | 16.85                 | 18.00               | 0.209                   | SIM2                  | /         |
| Back Side                     | 4182/836.4          | RMC       | 0.161            | 0.100 | -0.16            | 16.85                 | 18.00               | 0.210                   | Battery 2#            | /         |
| Back Side                     | 4182/836.4          | RMC       | 0.171            | 0.093 | -0.14            | 16.85                 | 18.00               | 0.223                   | Battery 3#            | /         |

Table 95: Hotspot SAR test results of UMTS Band V

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 4182/836.4          | RMC       | 0.091            | 0.053 | -0.18            | 16.85                 | 24.00               | 0.474                   | Battery1#             | Yes                                 |
| Back Side                | 4182/836.4          | RMC       | 0.194            | 0.106 | -0.17            | 16.85                 | 24.00               | 1.006                   | Battery1#             | Yes                                 |
| Left Side                | 4182/836.4          | RMC       | 0.083            | 0.055 | -0.09            | 16.85                 | 24.00               | 0.431                   | Battery1#             | Yes                                 |
| Top Side                 | 4182/836.4          | RMC       | 0.070            | 0.034 | -0.12            | 16.85                 | 24.00               | 0.362                   | Battery1#             | Yes                                 |
| Back Side                | 4182/836.4          | RMC       | 0.160            | 0.103 | -0.12            | 16.85                 | 24.00               | 0.830                   | SIM2                  | Yes                                 |
| Back Side                | 4182/836.4          | RMC       | 0.161            | 0.100 | -0.16            | 16.85                 | 24.00               | 0.835                   | Battery 2#            | Yes                                 |
| Back Side                | 4182/836.4          | RMC       | 0.171            | 0.093 | -0.14            | 16.85                 | 24.00               | 0.887                   | Battery 3#            | Yes                                 |

Table 96: Product Specific 10-g SAR test reduction evaluation of UMTS Band V

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.6 SAR measurement Result of LTE Band II(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 18700/1860          | 20M QPSK 1RB#50   | 0.253            | 0.158 | -0.13            | 18.93                 | 19.00               | 0.257                   | Battery1#             | /         |
| Left tilt             | 18700/1860          | 20M QPSK 1RB#50   | 0.208            | 0.113 | -0.01            | 18.93                 | 19.00               | 0.211                   | Battery1#             | /         |
| Right touch           | 18700/1860          | 20M QPSK 1RB#50   | 0.535            | 0.318 | 0.03             | 18.93                 | 19.00               | 0.544                   | Battery1#             | /         |
| Right tilt            | 18700/1860          | 20M QPSK 1RB#50   | 0.378            | 0.210 | 0.03             | 18.93                 | 19.00               | 0.384                   | Battery1#             | /         |
| Left touch            | 19100/1900          | 20M QPSK 50%RB#0  | 0.231            | 0.144 | 0.00             | 18.58                 | 19.00               | 0.254                   | Battery1#             | /         |
| Left tilt             | 19100/1900          | 20M QPSK 50%RB#0  | 0.186            | 0.107 | -0.08            | 18.58                 | 19.00               | 0.205                   | Battery1#             | /         |
| Right touch           | 19100/1900          | 20M QPSK 50%RB#0  | 0.609            | 0.349 | 0.11             | 18.58                 | 19.00               | 0.671                   | Battery1#             | Yes       |
| Right tilt            | 19100/1900          | 20M QPSK 50%RB#0  | 0.359            | 0.203 | 0.04             | 18.58                 | 19.00               | 0.395                   | Battery1#             | /         |
| Right touch           | 19100/1900          | 20M QPSK 50%RB#0  | 0.507            | 0.300 | 0.13             | 18.58                 | 19.00               | 0.558                   | SIM2                  | /         |
| Right touch           | 19100/1900          | 20M QPSK 50%RB#0  | 0.428            | 0.249 | 0.00             | 18.58                 | 19.00               | 0.471                   | Battery 2#            | /         |
| Right touch           | 19100/1900          | 20M QPSK 50%RB#0  | 0.417            | 0.242 | 0.00             | 18.58                 | 19.00               | 0.459                   | Battery 3#            | /         |
| Right touch           | 18700/1860          | 20M QPSK 50%RB#25 | 0.584            | 0.334 | 0.03             | 18.52                 | 19.00               | 0.652                   | Battery1#             | /         |
| Right touch           | 18900/1880          | 20M QPSK 50%RB#50 | 0.583            | 0.339 | -0.04            | 18.17                 | 19.00               | 0.706                   | Battery1#             | /         |

Table 97: Head SAR test results of LTE Band II

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 18700/1860          | 20M QPSK 1RB#50   | 0.088            | 0.051 | 0.01             | 22.39                 | 23.00               | 0.102                   | Battery1#             | /         |
| Back Side                       | 18700/1860          | 20M QPSK 1RB#50   | 0.181            | 0.100 | 0.02             | 22.39                 | 23.00               | 0.208                   | Battery1#             | Yes       |
| Front Side                      | 18700/1860          | 20M QPSK 50%RB#25 | 0.072            | 0.041 | 0.04             | 21.92                 | 22.50               | 0.083                   | Battery1#             | /         |
| Back Side                       | 18700/1860          | 20M QPSK 50%RB#25 | 0.119            | 0.065 | -0.05            | 21.92                 | 22.50               | 0.136                   | Battery1#             | /         |
| Back Side                       | 18700/1860          | 20M QPSK 1RB#50   | 0.154            | 0.084 | -0.14            | 22.39                 | 23.00               | 0.177                   | Battery 2#            | /         |
| Back Side                       | 18700/1860          | 20M QPSK 1RB#50   | 0.153            | 0.083 | 0.01             | 22.39                 | 23.00               | 0.176                   | Battery 3#            | /         |
| Back Side                       | 18700/1860          | 20M QPSK 1RB#50   | 0.149            | 0.081 | -0.05            | 22.39                 | 23.00               | 0.171                   | SIM2                  | /         |

Table 98: Body-Worn SAR test results of LTE Band II

| Test Position of Hotspot 10mm | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 18700/1860               | 20M QPSK 1RB#50   | 0.045            | 0.025 | -0.01            | 16.66                 | 16.70               | 0.045                   | Battery1#             | /         |
| Back Side                     | 18700/1860               | 20M QPSK 1RB#50   | 0.091            | 0.046 | 0.16             | 16.66                 | 16.70               | 0.091                   | Battery1#             | /         |
| Left Side                     | 18700/1860               | 20M QPSK 1RB#50   | 0.059            | 0.035 | 0.18             | 16.66                 | 16.70               | 0.060                   | Battery1#             | /         |
| Top Side                      | 18700/1860               | 20M QPSK 1RB#50   | 0.065            | 0.033 | -0.13            | 16.66                 | 16.70               | 0.065                   | Battery1#             | /         |
| Front Side                    | 18700/1860               | 20M QPSK 50%RB#25 | 0.036            | 0.021 | -0.03            | 16.19                 | 16.70               | 0.041                   | Battery1#             | /         |
| Back Side                     | 18700/1860               | 20M QPSK 50%RB#25 | 0.071            | 0.036 | -0.15            | 16.19                 | 16.70               | 0.080                   | Battery1#             | /         |
| Left Side                     | 18700/1860               | 20M QPSK 50%RB#25 | 0.055            | 0.032 | 0.00             | 16.19                 | 16.70               | 0.061                   | Battery1#             | /         |
| Top Side                      | 18700/1860               | 20M QPSK 50%RB#25 | 0.062            | 0.032 | -0.10            | 16.19                 | 16.70               | 0.070                   | Battery1#             | /         |
| Back Side                     | 18700/1860               | 20M QPSK 1RB#50   | 0.084            | 0.043 | -0.17            | 16.66                 | 16.70               | 0.085                   | Battery 2#            | /         |
| Back Side                     | 18700/1860               | 20M QPSK 1RB#50   | 0.101            | 0.051 | -0.01            | 16.66                 | 16.70               | 0.102                   | Battery 3#            | Yes       |
| Back Side                     | 18700/1860               | 20M QPSK 1RB#50   | 0.086            | 0.043 | -0.09            | 16.66                 | 16.70               | 0.086                   | SIM2                  | /         |

Table 99: Hotspot SAR test results of LTE Band II

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 18700/1860               | 20M QPSK 1RB#50   | 0.045            | 0.025 | -0.01            | 16.66                 | 23.00               | 0.192                   | Battery1#             | Yes                                 |
| Back Side                | 18700/1860               | 20M QPSK 1RB#50   | 0.091            | 0.046 | 0.16             | 16.66                 | 23.00               | 0.390                   | Battery1#             | Yes                                 |
| Left Side                | 18700/1860               | 20M QPSK 1RB#50   | 0.059            | 0.035 | 0.18             | 16.66                 | 23.00               | 0.254                   | Battery1#             | Yes                                 |
| Top Side                 | 18700/1860               | 20M QPSK 1RB#50   | 0.065            | 0.033 | -0.13            | 16.66                 | 23.00               | 0.279                   | Battery1#             | Yes                                 |
| Front Side               | 18700/1860               | 20M QPSK 50%RB#25 | 0.036            | 0.021 | -0.03            | 16.19                 | 22.50               | 0.155                   | Battery1#             | Yes                                 |
| Back Side                | 18700/1860               | 20M QPSK 50%RB#25 | 0.071            | 0.036 | -0.15            | 16.19                 | 22.50               | 0.304                   | Battery1#             | Yes                                 |
| Left Side                | 18700/1860               | 20M QPSK 50%RB#25 | 0.055            | 0.032 | 0.00             | 16.19                 | 22.50               | 0.233                   | Battery1#             | Yes                                 |
| Top Side                 | 18700/1860               | 20M QPSK 50%RB#25 | 0.062            | 0.032 | -0.10            | 16.19                 | 22.50               | 0.264                   | Battery1#             | Yes                                 |
| Back Side                | 18700/1860               | 20M QPSK 1RB#50   | 0.084            | 0.043 | -0.17            | 16.66                 | 23.00               | 0.362                   | Battery 2#            | Yes                                 |
| Back Side                | 18700/1860               | 20M QPSK 1RB#50   | 0.101            | 0.051 | -0.01            | 16.66                 | 23.00               | 0.435                   | Battery 3#            | Yes                                 |
| Back Side                | 18700/1860               | 20M QPSK 1RB#50   | 0.086            | 0.043 | -0.09            | 16.66                 | 23.00               | 0.368                   | SIM2                  | Yes                                 |

Table 100: Product Specific 10-g SAR test reduction evaluation of LTE Band II

---

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.7 SAR measurement Result of LTE Band IV(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 20050/1720          | 20M QPSK 1RB#50   | 0.402            | 0.257 | -0.07            | 20.57                 | 21.00               | 0.444                   | Battery1#             | /         |
| Left tilt             | 20050/1720          | 20M QPSK 1RB#50   | 0.400            | 0.213 | -0.13            | 20.57                 | 21.00               | 0.442                   | Battery1#             | /         |
| Right touch           | 20050/1720          | 20M QPSK 1RB#50   | 0.752            | 0.436 | 0.17             | 20.57                 | 21.00               | 0.830                   | Battery1#             | /         |
| Right touch           | 20175/1732.5        | 20M QPSK 1RB#0    | 0.690            | 0.401 | 0.01             | 20.40                 | 21.00               | 0.792                   | Battery1#             | /         |
| Right touch           | 20300/1745          | 20M QPSK 1RB#50   | 0.740            | 0.430 | 0.01             | 20.48                 | 21.00               | 0.834                   | Battery1#             | /         |
| Right tilt            | 20050/1720          | 20M QPSK 1RB#50   | 0.691            | 0.340 | 0.13             | 20.57                 | 21.00               | 0.763                   | Battery1#             | /         |
| Left touch            | 20300/1745          | 20M QPSK 50%RB#50 | 0.380            | 0.237 | -0.03            | 20.39                 | 21.00               | 0.437                   | Battery1#             | /         |
| Left tilt             | 20300/1745          | 20M QPSK 50%RB#50 | 0.378            | 0.217 | -0.02            | 20.39                 | 21.00               | 0.435                   | Battery1#             | /         |
| Right touch           | 20300/1745          | 20M QPSK 50%RB#50 | 0.759            | 0.442 | 0.01             | 20.39                 | 21.00               | 0.873                   | Battery1#             | /         |
| Right touch           | 20050/1720          | 20M QPSK 50%RB#25 | 0.684            | 0.388 | -0.04            | 20.33                 | 21.00               | 0.798                   | Battery1#             | /         |
| Right touch           | 20175/1732.5        | 20M QPSK 50%RB#0  | 0.651            | 0.373 | 0.00             | 20.21                 | 21.00               | 0.781                   | Battery1#             | /         |
| Right tilt            | 20300/1745          | 20M QPSK 50%RB#50 | 0.670            | 0.334 | -0.04            | 20.39                 | 21.00               | 0.771                   | Battery1#             | /         |
| Right touch           | 20300/1745          | 20M QPSK 100%RB#0 | 0.696            | 0.403 | -0.08            | 20.29                 | 21.00               | 0.820                   | Battery1#             | /         |
| Right touch           | 20300/1745          | 20M QPSK 50%RB#50 | 0.825            | 0.471 | -0.19            | 20.39                 | 21.00               | 0.949                   | Battery 2#            | Yes       |
| Right touch-repeated  | 20300/1745          | 20M QPSK 50%RB#50 | 0.757            | 0.438 | -0.07            | 20.39                 | 21.00               | 0.871                   | Battery 2#            | /         |
| Right touch           | 20300/1745          | 20M QPSK 50%RB#50 | 0.803            | 0.463 | -0.02            | 20.39                 | 21.00               | 0.924                   | Battery 3#            | /         |
| Right touch           | 20300/1745          | 20M QPSK 50%RB#50 | 0.671            | 0.396 | 0.18             | 20.39                 | 21.00               | 0.772                   | SIM2                  | /         |

Table 101: Head SAR test results of LTE Band IV

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 20050/1720          | 20M QPSK 1RB#50   | 0.143            | 0.083 | -0.05            | 22.94                 | 23.00               | 0.145                   | Battery1#             | /         |
| Back Side                       | 20050/1720          | 20M QPSK 1RB#50   | 0.232            | 0.128 | -0.11            | 22.94                 | 23.00               | 0.235                   | Battery1#             | /         |
| Front Side                      | 20050/1720          | 20M QPSK 50%RB#25 | 0.108            | 0.068 | 0.07             | 21.88                 | 22.50               | 0.125                   | Battery1#             | /         |
| Back Side                       | 20050/1720          | 20M QPSK 50%RB#25 | 0.180            | 0.098 | -0.06            | 21.88                 | 22.50               | 0.208                   | Battery1#             | /         |
| Back Side                       | 20050/1720          | 20M QPSK 1RB#50   | 0.236            | 0.130 | -0.10            | 22.94                 | 23.00               | 0.239                   | SIM2                  | /         |
| Back Side                       | 20050/1720          | 20M QPSK 1RB#50   | 0.241            | 0.130 | -0.11            | 22.94                 | 23.00               | 0.244                   | Battery 2#            | Yes       |
| Back Side                       | 20050/1720          | 20M QPSK 1RB#50   | 0.134            | 0.073 | -0.11            | 22.94                 | 23.00               | 0.136                   | Battery 3#            | /         |

Table 102: Body-Worn SAR test results of LTE Band IV

| Test Position of Hotspot 10mm | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 20050/1720               | 20M QPSK 1RB#50   | 0.085            | 0.045 | -0.03            | 17.49                 | 18.00               | 0.096                   | Battery1#             | /         |
| Back Side                     | 20050/1720               | 20M QPSK 1RB#50   | 0.156            | 0.078 | -0.16            | 17.49                 | 18.00               | 0.175                   | Battery1#             | /         |
| Left Side                     | 20050/1720               | 20M QPSK 1RB#50   | 0.068            | 0.039 | -0.01            | 17.49                 | 18.00               | 0.077                   | Battery1#             | /         |
| Top Side                      | 20050/1720               | 20M QPSK 1RB#50   | 0.129            | 0.068 | 0.15             | 17.49                 | 18.00               | 0.145                   | Battery1#             | /         |
| Front Side                    | 20050/1720               | 20M QPSK 50%RB#25 | 0.079            | 0.044 | 0.03             | 17.31                 | 18.00               | 0.093                   | Battery1#             | /         |
| Back Side                     | 20050/1720               | 20M QPSK 50%RB#25 | 0.149            | 0.075 | -0.13            | 17.31                 | 18.00               | 0.175                   | Battery1#             | /         |
| Left Side                     | 20050/1720               | 20M QPSK 50%RB#25 | 0.065            | 0.037 | 0.00             | 17.31                 | 18.00               | 0.076                   | Battery1#             | /         |
| Top Side                      | 20050/1720               | 20M QPSK 50%RB#25 | 0.125            | 0.063 | 0.12             | 17.31                 | 18.00               | 0.147                   | Battery1#             | /         |
| Back Side                     | 20050/1720               | 20M QPSK 1RB#50   | 0.149            | 0.076 | -0.14            | 17.49                 | 18.00               | 0.168                   | SIM2                  | /         |
| Back Side                     | 20050/1720               | 20M QPSK 1RB#50   | 0.160            | 0.080 | -0.07            | 17.49                 | 18.00               | 0.180                   | Battery 2#            | Yes       |
| Back Side                     | 20050/1720               | 20M QPSK 1RB#50   | 0.149            | 0.075 | -0.03            | 17.49                 | 18.00               | 0.168                   | Battery 3#            | /         |

Table 103: Hotspot SAR test results of LTE Band IV

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 20050/1720               | 20M QPSK 1RB#50   | 0.085            | 0.045 | -0.03            | 17.49                 | 23.00               | 0.303                   | Battery1#             | Yes                                 |
| Back Side                | 20050/1720               | 20M QPSK 1RB#50   | 0.156            | 0.078 | -0.16            | 17.49                 | 23.00               | 0.555                   | Battery1#             | Yes                                 |
| Left Side                | 20050/1720               | 20M QPSK 1RB#50   | 0.068            | 0.039 | -0.01            | 17.49                 | 23.00               | 0.243                   | Battery1#             | Yes                                 |
| Top Side                 | 20050/1720               | 20M QPSK 1RB#50   | 0.129            | 0.068 | 0.15             | 17.49                 | 23.00               | 0.459                   | Battery1#             | Yes                                 |
| Front Side               | 20050/1720               | 20M QPSK 50%RB#25 | 0.079            | 0.044 | 0.03             | 17.31                 | 22.50               | 0.262                   | Battery1#             | Yes                                 |
| Back Side                | 20050/1720               | 20M QPSK 50%RB#25 | 0.149            | 0.075 | -0.13            | 17.31                 | 22.50               | 0.492                   | Battery1#             | Yes                                 |
| Left Side                | 20050/1720               | 20M QPSK 50%RB#25 | 0.065            | 0.037 | 0.00             | 17.31                 | 22.50               | 0.215                   | Battery1#             | Yes                                 |
| Top Side                 | 20050/1720               | 20M QPSK 50%RB#25 | 0.125            | 0.063 | 0.12             | 17.31                 | 22.50               | 0.413                   | Battery1#             | Yes                                 |
| Back Side                | 20050/1720               | 20M QPSK 1RB#50   | 0.149            | 0.076 | -0.14            | 17.49                 | 23.00               | 0.530                   | SIM2                  | Yes                                 |
| Back Side                | 20050/1720               | 20M QPSK 1RB#50   | 0.160            | 0.080 | -0.07            | 17.49                 | 23.00               | 0.569                   | Battery 2#            | Yes                                 |
| Back Side                | 20050/1720               | 20M QPSK 1RB#50   | 0.149            | 0.075 | -0.03            | 17.49                 | 23.00               | 0.530                   | Battery 3#            | Yes                                 |

Table 104: Product Specific 10-g SAR test reduction evaluation of LTE Band IV

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.8 SAR measurement Result of LTE Band V(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 20600/844           | 10M QPSK 1RB#25   | 0.356            | 0.198 | 0.17             | 19.62                 | 20.50               | 0.436                   | Battery1#             | /         |
| Left tilt             | 20600/844           | 10M QPSK 1RB#25   | 0.351            | 0.215 | -0.13            | 19.62                 | 20.50               | 0.430                   | Battery1#             | /         |
| Right touch           | 20600/844           | 10M QPSK 1RB#25   | 0.562            | 0.286 | 0.03             | 19.62                 | 20.50               | 0.688                   | Battery1#             | /         |
| Right tilt            | 20600/844           | 10M QPSK 1RB#25   | 0.459            | 0.218 | -0.10            | 19.62                 | 20.50               | 0.562                   | Battery1#             | /         |
| Left touch            | 20600/844           | 10M QPSK 50%RB#13 | 0.351            | 0.194 | 0.19             | 19.47                 | 20.50               | 0.445                   | Battery1#             | /         |
| Left tilt             | 20600/844           | 10M QPSK 50%RB#13 | 0.350            | 0.215 | -0.19            | 19.47                 | 20.50               | 0.444                   | Battery1#             | /         |
| Right touch           | 20600/844           | 10M QPSK 50%RB#13 | 0.556            | 0.282 | 0.00             | 19.47                 | 20.50               | 0.705                   | Battery1#             | /         |
| Right tilt            | 20600/844           | 10M QPSK 50%RB#13 | 0.548            | 0.332 | -0.13            | 19.47                 | 20.50               | 0.695                   | Battery1#             | /         |
| Right touch           | 20600/844           | 10M QPSK 50%RB#13 | 0.569            | 0.287 | -0.03            | 19.47                 | 20.50               | 0.721                   | SIM2                  | /         |
| Right touch           | 20600/844           | 10M QPSK 50%RB#13 | 0.576            | 0.291 | 0.02             | 19.47                 | 20.50               | 0.730                   | Battery 2#            | /         |
| Right touch           | 20600/844           | 10M QPSK 50%RB#13 | 0.533            | 0.273 | 0.05             | 19.47                 | 20.50               | 0.676                   | Battery 3#            | /         |
| Right touch           | 20450/829           | 10M QPSK 50%RB#13 | 0.630            | 0.320 | -0.12            | 19.22                 | 20.50               | 0.846                   | Battery 2#            | /         |
| Right touch           | 20525/836.5         | 10M QPSK 50%RB#13 | 0.713            | 0.363 | -0.01            | 19.18                 | 20.50               | 0.966                   | Battery 2#            | Yes       |
| Right touch           | 20600/844           | 10M QPSK 100%RB#0 | 0.632            | 0.379 | -0.17            | 19.30                 | 20.50               | 0.833                   | Battery 2#            | /         |

Table 105: Head SAR test results of LTE Band V

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 20600/844           | 10M QPSK 1RB#25   | 0.074            | 0.044 | -0.07            | 22.99                 | 24.00               | 0.093                   | Battery1#             | /         |
| Back Side                       | 20600/844           | 10M QPSK 1RB#25   | 0.150            | 0.086 | -0.15            | 22.99                 | 24.00               | 0.189                   | Battery1#             | /         |
| Front Side                      | 20600/844           | 10M QPSK 50%RB#13 | 0.072            | 0.044 | -0.09            | 21.92                 | 23.00               | 0.092                   | Battery1#             | /         |
| Back Side                       | 20600/844           | 10M QPSK 50%RB#13 | 0.146            | 0.084 | -0.16            | 21.92                 | 23.00               | 0.187                   | Battery1#             | /         |
| Back Side                       | 20600/844           | 10M QPSK 1RB#25   | 0.135            | 0.078 | -0.13            | 22.99                 | 24.00               | 0.170                   | SIM2                  |           |
| Back Side                       | 20600/844           | 10M QPSK 1RB#25   | 0.150            | 0.086 | -0.11            | 22.99                 | 24.00               | 0.189                   | Battery 2#            | /         |
| Back Side                       | 20600/844           | 10M QPSK 1RB#25   | 0.312            | 0.181 | -0.09            | 22.99                 | 24.00               | 0.394                   | Battery 3#            | Yes       |

Table 106: Body-Worn SAR test results of LTE Band V

| Test Position of Hotspot 10mm | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 20600/844                | 10M QPSK 1RB#25   | 0.076            | 0.044 | -0.13            | 16.75                 | 17.50               | 0.090                   | Battery1#             | /         |
| Back Side                     | 20600/844                | 10M QPSK 1RB#25   | 0.155            | 0.085 | -0.13            | 16.75                 | 17.50               | 0.184                   | Battery1#             | /         |
| Left Side                     | 20600/844                | 10M QPSK 1RB#25   | 0.066            | 0.043 | -0.04            | 16.75                 | 17.50               | 0.078                   | Battery1#             | /         |
| Top Side                      | 20600/844                | 10M QPSK 1RB#25   | 0.059            | 0.028 | -0.06            | 16.75                 | 17.50               | 0.070                   | Battery1#             | /         |
| Front Side                    | 20600/844                | 10M QPSK 50%RB#13 | 0.072            | 0.042 | 0.07             | 16.58                 | 17.50               | 0.089                   | Battery1#             | /         |
| Back Side                     | 20600/844                | 10M QPSK 50%RB#13 | 0.149            | 0.082 | -0.15            | 16.58                 | 17.50               | 0.184                   | Battery1#             | /         |
| Left Side                     | 20600/844                | 10M QPSK 50%RB#13 | 0.064            | 0.042 | -0.17            | 16.58                 | 17.50               | 0.079                   | Battery1#             | /         |
| Top Side                      | 20600/844                | 10M QPSK 50%RB#13 | 0.058            | 0.028 | -0.01            | 16.58                 | 17.50               | 0.072                   | Battery1#             | /         |
| Back Side                     | 20600/844                | 10M QPSK 1RB#25   | 0.169            | 0.091 | -0.19            | 16.75                 | 17.50               | 0.201                   | SIM2                  | /         |
| Back Side                     | 20600/844                | 10M QPSK 1RB#25   | 0.162            | 0.089 | -0.03            | 16.75                 | 17.50               | 0.193                   | Battery 2#            | /         |
| Back Side                     | 20600/844                | 10M QPSK 1RB#25   | 0.185            | 0.099 | -0.07            | 16.75                 | 17.50               | 0.220                   | Battery 3#            | Yes       |

Table 107: Hotspot SAR test results of LTE Band V

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 20600/844                | 10M QPSK 1RB#25   | 0.076            | 0.044 | -0.13            | 16.75                 | 24.00               | 0.404                   | Battery1#             | Yes                                 |
| Back Side                | 20600/844                | 10M QPSK 1RB#25   | 0.155            | 0.085 | -0.13            | 16.75                 | 24.00               | 0.823                   | Battery1#             | Yes                                 |
| Left Side                | 20600/844                | 10M QPSK 1RB#25   | 0.066            | 0.043 | -0.04            | 16.75                 | 24.00               | 0.349                   | Battery1#             | Yes                                 |
| Top Side                 | 20600/844                | 10M QPSK 1RB#25   | 0.059            | 0.028 | -0.06            | 16.75                 | 24.00               | 0.311                   | Battery1#             | Yes                                 |
| Front Side               | 20600/844                | 10M QPSK 50%RB#13 | 0.072            | 0.042 | 0.07             | 16.58                 | 23.00               | 0.317                   | Battery1#             | Yes                                 |
| Back Side                | 20600/844                | 10M QPSK 50%RB#13 | 0.149            | 0.082 | -0.15            | 16.58                 | 23.00               | 0.653                   | Battery1#             | Yes                                 |
| Left Side                | 20600/844                | 10M QPSK 50%RB#13 | 0.064            | 0.042 | -0.17            | 16.58                 | 23.00               | 0.281                   | Battery1#             | Yes                                 |
| Top Side                 | 20600/844                | 10M QPSK 50%RB#13 | 0.058            | 0.028 | -0.01            | 16.58                 | 23.00               | 0.256                   | Battery1#             | Yes                                 |
| Back Side                | 20600/844                | 10M QPSK 1RB#25   | 0.169            | 0.091 | -0.19            | 16.75                 | 24.00               | 0.897                   | SIM2                  | Yes                                 |
| Back Side                | 20600/844                | 10M QPSK 1RB#25   | 0.162            | 0.089 | -0.03            | 16.75                 | 24.00               | 0.860                   | Battery 2#            | Yes                                 |
| Back Side                | 20600/844                | 10M QPSK 1RB#25   | 0.185            | 0.100 | -0.07            | 16.75                 | 24.00               | 0.982                   | Battery 3#            | Yes                                 |

Table 108: Product Specific 10-g SAR test reduction evaluation of LTE Band V

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.9 SAR measurement Result of LTE Band VII(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 21100/2535          | 20M QPSK 1RB#50   | 0.185            | 0.090 | 0.06             | 15.48                 | 16.00               | 0.209                   | Battery1#             | /         |
| Left tilt             | 21100/2535          | 20M QPSK 1RB#50   | 0.137            | 0.064 | 0.18             | 15.48                 | 16.00               | 0.154                   | Battery1#             | /         |
| Right touch           | 21100/2535          | 20M QPSK 1RB#50   | 0.721            | 0.317 | 0.14             | 15.48                 | 16.00               | 0.813                   | Battery1#             | Yes       |
| Right touch           | 20850/2510          | 20M QPSK 1RB#0    | 0.708            | 0.303 | 0.17             | 15.32                 | 16.00               | 0.828                   | Battery1#             | /         |
| Right touch           | 21350/2560          | 20M QPSK 1RB#99   | 0.663            | 0.314 | 0.19             | 15.13                 | 16.00               | 0.810                   | Battery1#             | /         |
| Right tilt            | 21100/2535          | 20M QPSK 1RB#50   | 0.448            | 0.190 | 0.07             | 15.48                 | 16.00               | 0.505                   | Battery1#             | /         |
| Left touch            | 21100/2535          | 20M QPSK 50%RB#25 | 0.167            | 0.086 | -0.19            | 15.23                 | 16.00               | 0.199                   | Battery1#             | /         |
| Left tilt             | 21100/2535          | 20M QPSK 50%RB#25 | 0.136            | 0.069 | 0.16             | 15.23                 | 16.00               | 0.162                   | Battery1#             | /         |
| Right touch           | 21100/2535          | 20M QPSK 50%RB#25 | 0.696            | 0.304 | 0.07             | 15.23                 | 16.00               | 0.831                   | Battery1#             | /         |
| Right touch           | 20850/2510          | 20M QPSK 50%RB#0  | 0.682            | 0.298 | 0.07             | 15.02                 | 16.00               | 0.855                   | Battery1#             | /         |
| Right touch           | 21350/2560          | 20M QPSK 50%RB#50 | 0.696            | 0.304 | 0.17             | 14.67                 | 16.00               | 0.945                   | Battery1#             | /         |
| Right tilt            | 21100/2535          | 20M QPSK 50%RB#25 | 0.432            | 0.184 | -0.16            | 15.23                 | 16.00               | 0.516                   | Battery1#             | /         |
| Right touch           | 21100/2535          | 20M QPSK 100%RB#0 | 0.603            | 0.265 | -0.06            | 14.98                 | 16.00               | 0.763                   | Battery1#             | /         |
| Right touch           | 21350/2560          | 20M QPSK 50%RB#50 | 0.611            | 0.268 | 0.14             | 14.67                 | 16.00               | 0.830                   | Battery 2#            | /         |
| Right touch           | 21350/2560          | 20M QPSK 50%RB#50 | 0.614            | 0.268 | -0.17            | 14.67                 | 16.00               | 0.834                   | Battery 3#            | /         |
| Right touch           | 21350/2560          | 20M QPSK 50%RB#50 | 0.578            | 0.258 | 0.04             | 14.67                 | 16.00               | 0.785                   | SIM2                  | /         |

Table 109: Head SAR test results of LTE Band VII

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 21100/2535          | 20M QPSK 1RB#50   | 0.161            | 0.089 | 0.08             | 22.04                 | 22.50               | 0.179                   | Battery1#             | /         |
| Back Side                       | 21100/2535          | 20M QPSK 1RB#50   | 0.191            | 0.102 | -0.10            | 22.04                 | 22.50               | 0.212                   | Battery1#             | Yes       |
| Front Side                      | 21100/2535          | 20M QPSK 50%RB#25 | 0.125            | 0.066 | -0.19            | 20.87                 | 21.50               | 0.145                   | Battery1#             | /         |
| Back Side                       | 21100/2535          | 20M QPSK 50%RB#25 | 0.144            | 0.076 | -0.17            | 20.87                 | 21.50               | 0.166                   | Battery1#             | /         |
| Back Side                       | 21100/2535          | 20M QPSK 1RB#50   | 0.169            | 0.090 | -0.16            | 22.04                 | 22.50               | 0.188                   | Battery 2#            | /         |
| Back Side                       | 21100/2535          | 20M QPSK 1RB#50   | 0.182            | 0.096 | -0.19            | 22.04                 | 22.50               | 0.202                   | Battery 3#            | /         |
| Back Side                       | 21100/2535          | 20M QPSK 1RB#50   | 0.182            | 0.097 | -0.07            | 22.04                 | 22.50               | 0.202                   | SIM2                  | /         |

Table 110: Body-Worn SAR test results of LTE Band VII

| Test Position of Hotspot 10mm | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 21100/2535               | 20M QPSK 1RB#50   | 0.045            | 0.023 | 0.16             | 13.49                 | 14.20               | 0.053                   | Battery1#             | /         |
| Back Side                     | 21100/2535               | 20M QPSK 1RB#50   | 0.069            | 0.035 | -0.16            | 13.49                 | 14.20               | 0.081                   | Battery1#             | /         |
| Left Side                     | 21100/2535               | 20M QPSK 1RB#50   | 0.026            | 0.139 | 0.16             | 13.49                 | 14.20               | 0.030                   | Battery1#             | /         |
| Top Side                      | 21100/2535               | 20M QPSK 1RB#50   | 0.028            | 0.012 | -0.03            | 13.49                 | 14.20               | 0.033                   | Battery1#             | /         |
| Front Side                    | 21100/2535               | 20M QPSK 50%RB#25 | 0.044            | 0.021 | -0.18            | 13.27                 | 14.20               | 0.054                   | Battery1#             | /         |
| Back Side                     | 21100/2535               | 20M QPSK 50%RB#25 | 0.065            | 0.033 | -0.05            | 13.27                 | 14.20               | 0.080                   | Battery1#             | /         |
| Left Side                     | 21100/2535               | 20M QPSK 50%RB#25 | 0.025            | 0.014 | -0.11            | 13.27                 | 14.20               | 0.031                   | Battery1#             | /         |
| Top Side                      | 21100/2535               | 20M QPSK 50%RB#25 | 0.026            | 0.011 | 0.16             | 13.27                 | 14.20               | 0.032                   | Battery1#             | /         |
| Back Side                     | 21100/2535               | 20M QPSK 1RB#50   | 0.071            | 0.034 | -0.16            | 13.49                 | 14.20               | 0.083                   | SIM2                  | /         |
| Back Side                     | 21100/2535               | 20M QPSK 1RB#50   | 0.079            | 0.038 | -0.19            | 13.49                 | 14.20               | 0.093                   | Battery 2#            | Yes       |
| Back Side                     | 21100/2535               | 20M QPSK 1RB#50   | 0.066            | 0.032 | -0.02            | 13.49                 | 14.20               | 0.078                   | Battery 3#            | /         |

Table 111: Hotspot SAR test results of LTE Band VII

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 21100/2535               | 20M QPSK 1RB#50   | 0.045            | 0.023 | 0.16             | 13.49                 | 22.50               | 0.357                   | Battery1#             | Yes                                 |
| Back Side                | 21100/2535               | 20M QPSK 1RB#50   | 0.069            | 0.035 | -0.16            | 13.49                 | 22.50               | 0.549                   | Battery1#             | Yes                                 |
| Left Side                | 21100/2535               | 20M QPSK 1RB#50   | 0.026            | 0.139 | 0.16             | 13.49                 | 22.50               | 0.205                   | Battery1#             | Yes                                 |
| Top Side                 | 21100/2535               | 20M QPSK 1RB#50   | 0.028            | 0.012 | -0.03            | 13.49                 | 22.50               | 0.224                   | Battery1#             | Yes                                 |
| Front Side               | 21100/2535               | 20M QPSK 50%RB#25 | 0.044            | 0.021 | -0.18            | 13.27                 | 21.50               | 0.290                   | Battery1#             | Yes                                 |
| Back Side                | 21100/2535               | 20M QPSK 50%RB#25 | 0.065            | 0.033 | -0.05            | 13.27                 | 21.50               | 0.430                   | Battery1#             | Yes                                 |
| Left Side                | 21100/2535               | 20M QPSK 50%RB#25 | 0.025            | 0.014 | -0.11            | 13.27                 | 21.50               | 0.166                   | Battery1#             | Yes                                 |
| Top Side                 | 21100/2535               | 20M QPSK 50%RB#25 | 0.026            | 0.011 | 0.16             | 13.27                 | 21.50               | 0.173                   | Battery1#             | Yes                                 |
| Back Side                | 21100/2535               | 20M QPSK 1RB#50   | 0.071            | 0.034 | -0.16            | 13.49                 | 22.50               | 0.563                   | SIM2                  | Yes                                 |
| Back Side                | 21100/2535               | 20M QPSK 1RB#50   | 0.079            | 0.038 | -0.19            | 13.49                 | 22.50               | 0.630                   | Battery 2#            | Yes                                 |
| Back Side                | 21100/2535               | 20M QPSK 1RB#50   | 0.066            | 0.032 | -0.02            | 13.49                 | 22.50               | 0.527                   | Battery 3#            | Yes                                 |

Table 112: Product Specific 10-g SAR test reduction evaluation of LTE Band VII

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

### 7.2.10 SAR measurement Result of LTE Band XII(Second Antenna)

| Test Position of Head | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | 23130/711           | 10M QPSK 1RB#25   | 0.461            | 0.261 | 0.08             | 20.87                 | 21.50               | 0.533                   | Battery1#             | /         |
| Left tilt             | 23130/711           | 10M QPSK 1RB#25   | 0.457            | 0.302 | -0.02            | 20.87                 | 21.50               | 0.528                   | Battery1#             | /         |
| Right touch           | 23130/711           | 10M QPSK 1RB#25   | 0.839            | 0.432 | -0.08            | 20.87                 | 21.50               | 0.970                   | Battery1#             | /         |
| Right touch-Repeated  | 23130/711           | 10M QPSK 1RB#25   | 0.820            | 0.411 | -0.03            | 20.87                 | 21.50               | 0.948                   | Battery1#             | /         |
| Right touch           | 23060/704           | 10M QPSK 1RB#25   | 0.765            | 0.396 | 0.07             | 20.30                 | 21.50               | 1.008                   | Battery1#             | Yes       |
| Right touch           | 23095/707.5         | 10M QPSK 1RB#25   | 0.804            | 0.417 | -0.11            | 20.77                 | 21.50               | 0.951                   | Battery1#             | /         |
| Right tilt            | 23130/711           | 10M QPSK 1RB#25   | 0.658            | 0.386 | -0.17            | 20.87                 | 21.50               | 0.761                   | Battery1#             | /         |
| Left touch            | 23130/711           | 10M QPSK 50%RB#13 | 0.645            | 0.367 | -0.04            | 20.55                 | 21.50               | 0.803                   | Battery1#             | /         |
| Left touch            | 23060/704           | 10M QPSK 50%RB#13 | 0.446            | 0.301 | -0.18            | 20.14                 | 21.50               | 0.610                   | Battery1#             | /         |
| Left touch            | 23095/707.5         | 10M QPSK 50%RB#13 | 0.488            | 0.331 | -0.16            | 20.49                 | 21.50               | 0.616                   | Battery1#             | /         |
| Left tilt             | 23130/711           | 10M QPSK 50%RB#13 | 0.412            | 0.274 | -0.04            | 20.55                 | 21.50               | 0.513                   | Battery1#             | /         |
| Right touch           | 23130/711           | 10M QPSK 50%RB#13 | 0.748            | 0.389 | -0.07            | 20.55                 | 21.50               | 0.931                   | Battery1#             | /         |
| Right touch           | 23060/704           | 10M QPSK 50%RB#13 | 0.582            | 0.296 | -0.05            | 20.14                 | 21.50               | 0.796                   | Battery1#             |           |
| Right touch           | 23095/707.5         | 10M QPSK 50%RB#13 | 0.676            | 0.345 | -0.04            | 20.49                 | 21.50               | 0.853                   | Battery1#             |           |
| Right tilt            | 23130/711           | 10M QPSK 50%RB#13 | 0.634            | 0.371 | -0.11            | 20.55                 | 21.50               | 0.789                   | Battery1#             | /         |
| Right touch           | 23130/711           | 10M QPSK 100%RB#0 | 0.728            | 0.372 | 0.02             | 20.30                 | 21.50               | 0.960                   | Battery1#             | /         |
| Right touch           | 23060/704           | 10M QPSK 1RB#25   | 0.754            | 0.383 | -0.16            | 20.30                 | 21.50               | 0.994                   | SIM2                  | /         |
| Right touch           | 23060/704           | 10M QPSK 1RB#25   | 0.748            | 0.381 | -0.15            | 20.30                 | 21.50               | 0.986                   | Battery 2#            | /         |
| Right touch           | 23060/704           | 10M QPSK 1RB#25   | 0.731            | 0.376 | -0.13            | 20.30                 | 21.50               | 0.964                   | Battery 3#            | /         |

Table 113: Head SAR test results of LTE Band XII

| Test Position of Body-Worn 15mm | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|---------------------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                 |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                      | 23130/711           | 10M QPSK 1RB#25   | 0.089            | 0.065 | -0.08            | 23.09                 | 24.00               | 0.109                   | Battery1#             | /         |
| Back Side                       | 23130/711           | 10M QPSK 1RB#25   | 0.308            | 0.183 | -0.14            | 23.09                 | 24.00               | 0.380                   | Battery1#             | Yes       |
| Front Side                      | 23130/711           | 10M QPSK 50%RB#13 | 0.124            | 0.076 | -0.06            | 22.04                 | 23.00               | 0.155                   | Battery1#             | /         |
| Back Side                       | 23130/711           | 10M QPSK 50%RB#13 | 0.247            | 0.147 | -0.10            | 22.04                 | 23.00               | 0.308                   | Battery1#             | /         |
| Back Side                       | 23130/711           | 10M QPSK 1RB#25   | 0.179            | 0.106 | -0.12            | 23.09                 | 24.00               | 0.221                   | Battery 2#            | /         |
| Back Side                       | 23130/711           | 10M QPSK 1RB#25   | 0.243            | 0.143 | -0.14            | 23.09                 | 24.00               | 0.300                   | Battery 3#            | /         |
| Back Side                       | 23130/711           | 10M QPSK 1RB#25   | 0.174            | 0.102 | -0.12            | 23.09                 | 24.00               | 0.215                   | SIM2                  | /         |

Table 114: Body-Worn SAR test results of LTE Band XII

| Test Position of Hotspot 10mm | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-------------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                               |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                    | 23130/711                | 10M QPSK 1RB#25   | 0.097            | 0.056 | -0.10            | 17.51                 | 18.00               | 0.109                   | Battery1#             | /         |
| Back Side                     | 23130/711                | 10M QPSK 1RB#25   | 0.165            | 0.091 | -0.12            | 17.51                 | 18.00               | 0.185                   | Battery1#             | /         |
| Left Side                     | 23130/711                | 10M QPSK 1RB#25   | 0.091            | 0.062 | -0.18            | 17.51                 | 18.00               | 0.102                   | Battery1#             | /         |
| Top Side                      | 23130/711                | 10M QPSK 1RB#25   | 0.160            | 0.074 | -0.09            | 17.51                 | 18.00               | 0.179                   | Battery1#             | /         |
| Front Side                    | 23130/711                | 10M QPSK 50%RB#13 | 0.075            | 0.046 | -0.09            | 17.23                 | 18.00               | 0.090                   | Battery1#             | /         |
| Back Side                     | 23130/711                | 10M QPSK 50%RB#13 | 0.159            | 0.088 | -0.19            | 17.23                 | 18.00               | 0.190                   | Battery1#             | /         |
| Left Side                     | 23130/711                | 10M QPSK 50%RB#13 | 0.089            | 0.061 | -0.18            | 17.23                 | 18.00               | 0.106                   | Battery1#             | /         |
| Top Side                      | 23130/711                | 10M QPSK 50%RB#13 | 0.153            | 0.071 | -0.07            | 17.23                 | 18.00               | 0.183                   | Battery1#             | /         |
| Back Side                     | 23130/711                | 10M QPSK 50%RB#13 | 0.171            | 0.093 | -0.04            | 17.23                 | 18.00               | 0.204                   | Battery 2#            | /         |
| Back Side                     | 23130/711                | 10M QPSK 50%RB#13 | 0.180            | 0.098 | -0.19            | 17.23                 | 18.00               | 0.215                   | Battery 3#            | Yes       |
| Back Side                     | 23130/711                | 10M QPSK 50%RB#13 | 0.175            | 0.096 | -0.19            | 17.23                 | 18.00               | 0.209                   | SIM2                  | /         |

Table 115: Hotspot SAR test results of LTE Band XII

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 23130/711                | 10M QPSK 1RB#25   | 0.097            | 0.056 | -0.10            | 17.51                 | 24.00               | 0.433                   | Battery1#             | Yes                                 |
| Back Side                | 23130/711                | 10M QPSK 1RB#25   | 0.165            | 0.091 | -0.12            | 17.51                 | 24.00               | 0.735                   | Battery1#             | Yes                                 |
| Left Side                | 23130/711                | 10M QPSK 1RB#25   | 0.091            | 0.062 | -0.18            | 17.51                 | 24.00               | 0.406                   | Battery1#             | Yes                                 |
| Top Side                 | 23130/711                | 10M QPSK 1RB#25   | 0.160            | 0.074 | -0.09            | 17.51                 | 24.00               | 0.713                   | Battery1#             | Yes                                 |
| Front Side               | 23130/711                | 10M QPSK 50%RB#13 | 0.075            | 0.046 | -0.09            | 17.23                 | 23.00               | 0.284                   | Battery1#             | Yes                                 |
| Back Side                | 23130/711                | 10M QPSK 50%RB#13 | 0.159            | 0.088 | -0.19            | 17.23                 | 23.00               | 0.600                   | Battery1#             | Yes                                 |
| Left Side                | 23130/711                | 10M QPSK 50%RB#13 | 0.089            | 0.061 | -0.18            | 17.23                 | 23.00               | 0.336                   | Battery1#             | Yes                                 |
| Top Side                 | 23130/711                | 10M QPSK 50%RB#13 | 0.153            | 0.071 | -0.07            | 17.23                 | 23.00               | 0.578                   | Battery1#             | Yes                                 |
| Back Side                | 23130/711                | 10M QPSK 50%RB#13 | 0.171            | 0.093 | -0.04            | 17.23                 | 23.00               | 0.646                   | Battery 2#            | Yes                                 |
| Back Side                | 23130/711                | 10M QPSK 50%RB#13 | 0.180            | 0.098 | -0.19            | 17.23                 | 23.00               | 0.680                   | Battery 3#            | Yes                                 |
| Back Side                | 23130/711                | 10M QPSK 50%RB#13 | 0.175            | 0.096 | -0.19            | 17.23                 | 23.00               | 0.661                   | SIM2                  | Yes                                 |

Table 116: Product Specific 10-g SAR test reduction evaluation of LTE Band XII

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

### 7.2.11 SAR measurement Result of LTE Band XVII(Second Antenna)

SAR for LTE Band 17 (Frequency range:704-716 MHz) is covered by LTE Band 12 (Frequency range:699-716 MHz) due to similar frequency range,same maximum tune up limit and same channel bandwidth.

## 7.2.12 SAR measurement Result of GSM850(Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | /                | 190/836.6           | GSM       | 0.136            | 0.107 | 0.02             | 32.57                 | 33.50               | 0.168                   | Battery1#             | /         |
| Left tilt             | /     | /                | 190/836.6           | GSM       | 0.105            | 0.072 | -0.07            | 32.57                 | 33.50               | 0.130                   | Battery1#             | /         |
| Right touch           | /     | /                | 190/836.6           | GSM       | 0.168            | 0.129 | 0.10             | 32.57                 | 33.50               | 0.208                   | Battery1#             | /         |
| Right tilt            | /     | /                | 190/836.6           | GSM       | 0.104            | 0.073 | 0.01             | 32.57                 | 33.50               | 0.129                   | Battery1#             | /         |
| Right touch           | /     | /                | 190/836.6           | GSM       | 0.159            | 0.110 | 0.03             | 32.57                 | 33.50               | 0.197                   | SIM2                  | /         |
| Right touch           | /     | /                | 190/836.6           | GSM       | 0.134            | 0.092 | 0.13             | 32.57                 | 33.50               | 0.166                   | Battery 2#            | /         |
| Right touch           | /     | /                | 190/836.6           | GSM       | 0.138            | 0.096 | 0.01             | 32.57                 | 33.50               | 0.171                   | Battery 3#            | /         |
| Right touch           | /     | /                | 128/824.2           | GSM       | 0.192            | 0.150 | 0.08             | 32.58                 | 33.50               | 0.237                   | Battery1#             | Yes       |
| Right touch           | /     | /                | 251/848.8           | GSM       | 0.126            | 0.088 | 0.06             | 32.57                 | 33.50               | 0.156                   | Battery1#             | /         |

Table 117: Head SAR test results of GSM850

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | /                | 190/836.6           | GSM       | 0.209            | 0.163 | -0.09            | 32.57                 | 33.50               | 0.259                   | Battery1#             | /         |
| Back Side                  | 15mm  | /                | 190/836.6           | GSM       | 0.352            | 0.277 | -0.01            | 32.57                 | 33.50               | 0.436                   | Battery1#             | /         |
| Back Side                  | 15mm  | /                | 190/836.6           | GSM       | 0.348            | 0.272 | -0.02            | 32.57                 | 33.50               | 0.431                   | SIM2                  | /         |
| Back Side                  | 15mm  | /                | 190/836.6           | GSM       | 0.355            | 0.276 | -0.02            | 32.57                 | 33.50               | 0.440                   | Battery 2#            | /         |
| Back Side                  | 15mm  | /                | 190/836.6           | GSM       | 0.367            | 0.284 | 0.00             | 32.57                 | 33.50               | 0.455                   | Battery 3#            | Yes       |

Table 118: Body-Worn SAR test results of GSM850

| Test Position of Hotspot | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                          |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side               | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.178            | 0.138 | -0.03            | 30.44                 | 31.50               | 0.227                   | Battery1#             | Yes                                 |
| Back Side                | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.339            | 0.266 | -0.03            | 30.44                 | 31.50               | 0.433                   | Battery1#             | Yes                                 |
| Left Side                | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.276            | 0.181 | 0.03             | 30.44                 | 31.50               | 0.352                   | Battery1#             | Yes                                 |
| Right Side               | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.460            | 0.316 | -0.14            | 30.44                 | 31.50               | 0.587                   | Battery1#             | Yes                                 |
| Bottom Side              | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.111            | 0.059 | 0.10             | 30.44                 | 31.50               | 0.142                   | Battery1#             | Yes                                 |
| Right Side               | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.393            | 0.259 | -0.09            | 30.44                 | 31.50               | 0.502                   | SIM2                  | Yes                                 |
| Right Side               | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.395            | 0.262 | -0.12            | 30.44                 | 31.50               | 0.504                   | Battery 2#            | Yes                                 |
| Right Side               | 10mm  | /                | 190/836.6           | GPRS 2TS  | 0.414            | 0.275 | -0.19            | 30.44                 | 31.50               | 0.528                   | Battery 3#            | Yes                                 |

Table 119: Hotspot SAR test results of GSM850

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

### 7.2.13 SAR measurement Result of GSM1900(Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | State2           | 661/1880            | GSM       | 0.062            | 0.040 | 0.06             | 28.87                 | 30.00               | 0.080                   | Battery1#             | /         |
| Left touch            | /     | State1           | 661/1880            | GSM       | 0.098            | 0.062 | -0.03            | 28.87                 | 30.00               | 0.127                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 661/1880            | GSM       | 0.068            | 0.039 | 0.01             | 28.87                 | 30.00               | 0.088                   | Battery1#             | /         |
| Right touch           | /     | State1           | 661/1880            | GSM       | 0.065            | 0.041 | 0.01             | 28.87                 | 30.00               | 0.084                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 661/1880            | GSM       | 0.053            | 0.029 | 0.00             | 28.87                 | 30.00               | 0.069                   | Battery1#             | /         |
| Left touch            | /     | State1           | 661/1880            | GSM       | 0.126            | 0.080 | -0.16            | 28.87                 | 30.00               | 0.163                   | SIM2                  | /         |
| Left touch            | /     | State1           | 661/1880            | GSM       | 0.148            | 0.094 | -0.05            | 28.87                 | 30.00               | 0.192                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 661/1880            | GSM       | 0.151            | 0.097 | -0.13            | 28.87                 | 30.00               | 0.196                   | Battery 3#            | Yes       |
| Left touch            | /     | State2           | 661/1880            | GSM       | 0.054            | 0.032 | 0.13             | 28.87                 | 30.00               | 0.070                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 512/1850.2          | GSM       | 0.043            | 0.025 | 0.12             | 29.21                 | 30.00               | 0.052                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 810/1909.8          | GSM       | 0.103            | 0.063 | 0.05             | 28.57                 | 30.00               | 0.143                   | Battery 3#            | /         |

Table 120: Head SAR test results of GSM1900

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | State2           | 661/1880            | GSM       | 0.134            | 0.078 | 0.05             | 28.87                 | 30.00               | 0.174                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 661/1880            | GSM       | 0.201            | 0.117 | 0.06             | 28.87                 | 30.00               | 0.261                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 661/1880            | GSM       | 0.342            | 0.189 | -0.03            | 28.87                 | 30.00               | 0.444                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 661/1880            | GSM       | 0.339            | 0.185 | -0.03            | 28.87                 | 30.00               | 0.440                   | Battery 2#            | /         |
| Back Side                  | 15mm  | State1           | 661/1880            | GSM       | 0.382            | 0.208 | -0.14            | 28.87                 | 30.00               | 0.496                   | Battery 3#            | Yes       |
| Back Side                  | 15mm  | State2           | 661/1880            | GSM       | 0.230            | 0.132 | -0.08            | 28.87                 | 30.00               | 0.298                   | Battery 3#            | /         |
| Back Side                  | 15mm  | State1           | 661/1880            | GSM       | 0.306            | 0.168 | -0.03            | 28.87                 | 30.00               | 0.397                   | SIM2                  | /         |

Table 121: Body-Worn SAR test results of GSM1900

| Test Position of Hotspot                         | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                                       | 10mm  | State2           | 661/1880            | GPRS 2TS  | 0.189            | 0.103 | 0.12             | 24.77                 | 26.00               | 0.251                   | Battery1#             | /         |
| Front Side                                       | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.351            | 0.193 | 0.14             | 24.77                 | 26.00               | 0.466                   | Battery1#             | /         |
| Back Side                                        | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.385            | 0.199 | 0.12             | 24.77                 | 26.00               | 0.511                   | Battery1#             | /         |
| Left Side                                        | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.091            | 0.054 | -0.07            | 26.74                 | 28.00               | 0.122                   | Battery1#             | /         |
| Right Side                                       | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.097            | 0.056 | 0.18             | 26.74                 | 28.00               | 0.129                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.713            | 0.376 | 0.06             | 24.77                 | 26.00               | 0.946                   | Battery1#             | Yes       |
| Bottom Side                                      | 10mm  | State2           | 661/1880            | GPRS 2TS  | 0.391            | 0.204 | -0.05            | 24.77                 | 26.00               | 0.519                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 512/1850.2          | GPRS 2TS  | 0.353            | 0.184 | 0.07             | 25.00                 | 26.00               | 0.444                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 810/1909.8          | GPRS 2TS  | 0.642            | 0.337 | 0.06             | 24.71                 | 26.00               | 0.864                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.441            | 0.232 | -0.02            | 24.77                 | 26.00               | 0.585                   | Battery 2#            | /         |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.436            | 0.230 | -0.13            | 24.77                 | 26.00               | 0.579                   | Battery 3#            | /         |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.427            | 0.223 | 0.15             | 24.77                 | 26.00               | 0.567                   | SIM2                  | /         |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                         |                       |           |
| Front Side                                       | 11mm  | State1           | 661/1880            | GPRS 2TS  | 0.291            | 0.165 | 0.19             | 26.74                 | 28.00               | 0.389                   | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 661/1880            | GPRS 2TS  | 0.458            | 0.246 | -0.10            | 26.74                 | 28.00               | 0.612                   | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 661/1880            | GPRS 2TS  | 0.539            | 0.293 | 0.05             | 26.74                 | 28.00               | 0.720                   | Battery1#             | /         |

Table 122: Hotspot SAR test results of GSM1900

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot                         | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 10mm  | State2           | 661/1880            | GPRS 2TS  | 0.189            | 0.103 | 0.12             | 24.77                 | 28.00               | 0.398                   | Battery1#             | Yes                                 |
| Front Side                                       | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.351            | 0.193 | 0.14             | 24.77                 | 28.00               | 0.738                   | Battery1#             | Yes                                 |
| Back Side                                        | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.385            | 0.199 | 0.12             | 24.77                 | 28.00               | 0.810                   | Battery1#             | Yes                                 |
| Left Side                                        | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.091            | 0.054 | -0.07            | 26.74                 | 28.00               | 0.122                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.097            | 0.056 | 0.18             | 26.74                 | 28.00               | 0.129                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.713            | 0.376 | 0.06             | 24.77                 | 28.00               | 1.500                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State2           | 661/1880            | GPRS 2TS  | 0.391            | 0.204 | -0.05            | 24.77                 | 28.00               | 0.823                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 512/1850.2          | GPRS 2TS  | 0.353            | 0.184 | 0.07             | 25.00                 | 28.00               | 0.704                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 810/1909.8          | GPRS 2TS  | 0.642            | 0.337 | 0.06             | 24.71                 | 28.00               | 1.369                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.441            | 0.232 | -0.02            | 24.77                 | 28.00               | 0.928                   | Battery 2#            | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.436            | 0.230 | -0.13            | 24.77                 | 28.00               | 0.917                   | Battery 3#            | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 661/1880            | GPRS 2TS  | 0.427            | 0.223 | 0.15             | 24.77                 | 28.00               | 0.898                   | SIM2                  | Yes                                 |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 11mm  | State1           | 661/1880            | GPRS 2TS  | 0.291            | 0.165 | 0.19             | 26.74                 | 28.00               | 0.389                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | State1           | 661/1880            | GPRS 2TS  | 0.458            | 0.246 | -0.10            | 26.74                 | 28.00               | 0.612                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | State1           | 661/1880            | GPRS 2TS  | 0.539            | 0.293 | 0.05             | 26.74                 | 28.00               | 0.720                   | Battery1#             | Yes                                 |

Table 123: Product Specific 10-g SAR test reduction evaluation of GSM1900

Note : According to the table above , only **Bottom Side** Product Specific 10-g SAR test is required for this frequency band:

| Product Specific 10-g SAR                        | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 10-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|--------------------------|-----------------------|-----------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                          |                       |           |
| Bottom Side                                      | 0mm   | State2           | 661/1880            | GPRS 2TS  | 0.343            | 0.178 | -0.13            | 24.77                 | 26.00               | 0.236                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 661/1880            | GPRS 2TS  | 0.354            | 0.181 | -0.08            | 24.77                 | 26.00               | 0.240                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 661/1880            | GPRS 2TS  | 0.418            | 0.194 | 0.12             | 24.77                 | 26.00               | 0.258                    | Battery 2#            | /         |
| Bottom Side                                      | 0mm   | State1           | 661/1880            | GPRS 2TS  | 0.430            | 0.196 | -0.13            | 24.77                 | 26.00               | 0.260                    | Battery 3#            | Yes       |
| Bottom Side                                      | 0mm   | State1           | 661/1880            | GPRS 2TS  | 0.354            | 0.165 | 0.12             | 24.77                 | 26.00               | 0.219                    | SIM2                  | /         |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                          |                       |           |
| Bottom Side                                      | 12mm  | State1           | 661/1880            | GPRS 2TS  | 0.076            | 0.041 | -0.15            | 26.74                 | 28.00               | 0.055                    | Battery3#             | /         |

Table 124: Product Specific 10-g SAR results of GSM1900

## 7.2.14 SAR measurement Result of UMTS Band II(Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | State2           | 9400/1880           | RMC       | 0.168            | 0.110 | 0.13             | 22.91                 | 24.00               | 0.216                   | Battery1#             | /         |
| Left touch            | /     | State1           | 9400/1880           | RMC       | 0.234            | 0.152 | -0.02            | 22.91                 | 24.00               | 0.301                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 9400/1880           | RMC       | 0.137            | 0.084 | 0.03             | 22.91                 | 24.00               | 0.176                   | Battery1#             | /         |
| Right touch           | /     | State1           | 9400/1880           | RMC       | 0.168            | 0.108 | -0.13            | 22.91                 | 24.00               | 0.216                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 9400/1880           | RMC       | 0.127            | 0.073 | -0.07            | 22.91                 | 24.00               | 0.163                   | Battery1#             | /         |
| Left touch            | /     | State1           | 9400/1880           | RMC       | 0.232            | 0.149 | -0.18            | 22.91                 | 24.00               | 0.298                   | SIM2                  | /         |
| Left touch            | /     | State1           | 9400/1880           | RMC       | 0.251            | 0.163 | 0.15             | 22.91                 | 24.00               | 0.323                   | Battery 2#            | Yes       |
| Left touch            | /     | State2           | 9400/1880           | RMC       | 0.134            | 0.087 | -0.17            | 22.91                 | 24.00               | 0.172                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 9400/1880           | RMC       | 0.242            | 0.143 | -0.09            | 22.91                 | 24.00               | 0.311                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 9262/1852.4         | RMC       | 0.173            | 0.113 | 0.07             | 22.92                 | 24.00               | 0.222                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 9538/1907.6         | RMC       | 0.246            | 0.158 | 0.07             | 23.01                 | 24.00               | 0.309                   | Battery 2#            | /         |

Table 125: Head SAR test results of UMTS Band II

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | State2           | 9400/1880           | RMC       | 0.331            | 0.188 | -0.18            | 22.91                 | 24.00               | 0.425                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 9400/1880           | RMC       | 0.494            | 0.281 | 0.15             | 22.91                 | 24.00               | 0.635                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 9400/1880           | RMC       | 0.833            | 0.453 | -0.03            | 22.91                 | 24.00               | 1.071                   | Battery1#             | /         |
| Back Side-Repeated         | 15mm  | State1           | 9400/1880           | RMC       | 0.864            | 0.477 | -0.12            | 22.91                 | 24.00               | 1.110                   | Battery1#             | Yes       |
| Back Side                  | 15mm  | State1           | 9400/1880           | RMC       | 0.766            | 0.418 | -0.02            | 22.91                 | 24.00               | 0.985                   | SIM2                  | /         |
| Back Side                  | 15mm  | State1           | 9262/1852.4         | RMC       | 0.591            | 0.325 | 0.00             | 22.92                 | 24.00               | 0.758                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 9538/1907.6         | RMC       | 0.607            | 0.340 | 0.04             | 23.01                 | 24.00               | 0.762                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 9400/1880           | RMC       | 0.761            | 0.420 | 0.13             | 22.91                 | 24.00               | 0.978                   | Battery 2#            | /         |
| Back Side                  | 15mm  | State1           | 9400/1880           | RMC       | 0.748            | 0.414 | -0.07            | 22.91                 | 24.00               | 0.961                   | Battery 3#            | /         |
| Back Side                  | 15mm  | State2           | 9400/1880           | RMC       | 0.267            | 0.151 | -0.17            | 22.91                 | 24.00               | 0.343                   | Battery1#             | /         |

Table 126: Body-Worn SAR test results of UMTS Band II

| Test Position of Hotspot                                     | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                                              |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 10mm  | State2           | 9400/1880           | RMC       | 0.214            | 0.114 | 0.08             | 17.92                 | 19.00               | 0.274                   | Battery1#             | /         |
| Front Side                                                   | 10mm  | State1           | 9400/1880           | RMC       | 0.313            | 0.170 | -0.03            | 17.92                 | 19.00               | 0.401                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 9400/1880           | RMC       | 0.561            | 0.285 | -0.10            | 17.92                 | 19.00               | 0.719                   | Battery1#             | /         |
| Left Side                                                    | 10mm  | State1           | 9400/1880           | RMC       | 0.190            | 0.106 | 0.11             | 19.97                 | 21.00               | 0.241                   | Battery1#             | /         |
| Right Side                                                   | 10mm  | State1           | 9400/1880           | RMC       | 0.121            | 0.068 | 0.08             | 19.97                 | 21.00               | 0.153                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 9400/1880           | RMC       | 0.694            | 0.364 | 0.16             | 17.92                 | 19.00               | 0.890                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 9262/1852.4         | RMC       | 0.622            | 0.325 | 0.13             | 17.92                 | 19.00               | 0.798                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 9538/1907.6         | RMC       | 0.540            | 0.283 | 0.11             | 18.07                 | 19.00               | 0.669                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 9400/1880           | RMC       | 0.711            | 0.372 | 0.12             | 17.92                 | 19.00               | 0.912                   | SIM2                  | /         |
| Bottom Side                                                  | 10mm  | State1           | 9400/1880           | RMC       | 0.736            | 0.381 | 0.19             | 17.92                 | 19.00               | 0.944                   | Battery 2#            | /         |
| Bottom Side                                                  | 10mm  | State2           | 9400/1880           | RMC       | 0.471            | 0.247 | 0.19             | 17.92                 | 19.00               | 0.604                   | Battery 2#            | /         |
| Bottom Side                                                  | 10mm  | State1           | 9400/1880           | RMC       | 0.676            | 0.355 | 0.12             | 17.92                 | 19.00               | 0.867                   | Battery 3#            | /         |
| Additional Body SAR test results with sensor off(hotspot on) |       |                  |                     |           |                  |       |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 11mm  | State1           | 9400/1880           | RMC       | 0.454            | 0.245 | -0.04            | 19.97                 | 21.00               | 0.576                   | Battery1#             | /         |
| Back Side                                                    | 13mm  | State1           | 9400/1880           | RMC       | 0.601            | 0.316 | -0.03            | 19.97                 | 21.00               | 0.762                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 9400/1880           | RMC       | 0.814            | 0.442 | 0.18             | 19.97                 | 21.00               | 1.032                   | Battery1#             | Yes       |
| Bottom Side-repeated                                         | 12mm  | State1           | 9538/1907.6         | RMC       | 0.786            | 0.431 | 0.17             | 20.13                 | 21.00               | 0.960                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 9262/1852.4         | RMC       | 0.774            | 0.425 | 0.12             | 20.01                 | 21.00               | 0.972                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 9538/1907.6         | RMC       | 0.561            | 0.308 | 0.18             | 20.13                 | 21.00               | 0.685                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State2           | 9400/1880           | RMC       | 0.453            | 0.242 | 0.11             | 19.97                 | 21.00               | 0.574                   | Battery1#             | /         |

Table 127: Hotspot SAR test results of UMTS Band II

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot                         | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 10mm  | State2           | 9400/1880           | RMC       | 0.214            | 0.114 | 0.08             | 17.92                 | 24.00               | 0.868                   | Battery1#             | Yes                                 |
| Front Side                                       | 10mm  | State1           | 9400/1880           | RMC       | 0.313            | 0.170 | -0.03            | 17.92                 | 24.00               | 1.269                   | Battery1#             | No                                  |
| Back Side                                        | 10mm  | State1           | 9400/1880           | RMC       | 0.561            | 0.285 | -0.10            | 17.92                 | 24.00               | 2.275                   | Battery1#             | No                                  |
| Left Side                                        | 10mm  | State1           | 9400/1880           | RMC       | 0.190            | 0.106 | 0.11             | 19.97                 | 24.00               | 0.481                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | State1           | 9400/1880           | RMC       | 0.121            | 0.068 | 0.08             | 19.97                 | 24.00               | 0.306                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 9400/1880           | RMC       | 0.694            | 0.364 | 0.16             | 17.92                 | 24.00               | 2.814                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State1           | 9262/1852.4         | RMC       | 0.622            | 0.325 | 0.13             | 17.92                 | 24.00               | 2.522                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State1           | 9538/1907.6         | RMC       | 0.540            | 0.283 | 0.11             | 18.07                 | 24.00               | 2.115                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State1           | 9400/1880           | RMC       | 0.711            | 0.372 | 0.12             | 17.92                 | 24.00               | 2.883                   | SIM2                  | No                                  |
| Bottom Side                                      | 10mm  | State1           | 9400/1880           | RMC       | 0.736            | 0.381 | 0.19             | 17.92                 | 24.00               | 2.985                   | Battery 2#            | No                                  |
| Bottom Side                                      | 10mm  | State2           | 9400/1880           | RMC       | 0.471            | 0.247 | 0.19             | 17.92                 | 24.00               | 1.910                   | Battery 2#            | No                                  |
| Bottom Side                                      | 10mm  | State1           | 9400/1880           | RMC       | 0.676            | 0.355 | 0.12             | 17.92                 | 24.00               | 2.741                   | Battery 3#            | No                                  |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 11mm  | State1           | 9400/1880           | RMC       | 0.454            | 0.245 | -0.04            | 19.97                 | 24.00               | 1.148                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | State1           | 9400/1880           | RMC       | 0.601            | 0.316 | -0.03            | 19.97                 | 24.00               | 1.520                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 9400/1880           | RMC       | 0.814            | 0.442 | 0.18             | 19.97                 | 24.00               | 2.059                   | Battery1#             | No                                  |
| Bottom Side-repeated                             | 12mm  | State1           | 9538/1907.6         | RMC       | 0.786            | 0.431 | 0.17             | 20.13                 | 24.00               | 1.916                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 9262/1852.4         | RMC       | 0.774            | 0.425 | 0.12             | 20.01                 | 24.00               | 1.940                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 9538/1907.6         | RMC       | 0.561            | 0.308 | 0.18             | 20.13                 | 24.00               | 1.368                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State2           | 9400/1880           | RMC       | 0.453            | 0.242 | 0.11             | 19.97                 | 24.00               | 1.146                   | Battery1#             | Yes                                 |

Table 128: Product Specific 10-g SAR test reduction evaluation of UMTS Band II

Note : According to the table above , **Front side**、**Bottom Side** and **Back side** Product Specific 10-g SAR test is required for this frequency band:

| Product Specific 10-g SAR                        | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 10-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|--------------------------|-----------------------|-----------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                          |                       |           |
| Bottom Side                                      | 0mm   | State2           | 9400/1880           | RMC       | 0.617            | 0.295 | 0.14             | 20.97                 | 22.00               | 0.374                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 9400/1880           | RMC       | 0.676            | 0.349 | -0.13            | 20.97                 | 22.00               | 0.442                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 9400/1880           | RMC       | 1.520            | 0.875 | 0.11             | 20.97                 | 22.00               | 1.109                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 9400/1880           | RMC       | 2.660            | 1.130 | 0.16             | 20.97                 | 22.00               | 1.432                    | Battery1#             | Yes       |
| Back Side                                        | 0mm   | State1           | 9400/1880           | RMC       | 2.450            | 1.100 | 0.04             | 20.97                 | 22.00               | 1.394                    | SIM2                  | /         |
| Back Side                                        | 0mm   | State1           | 9400/1880           | RMC       | 2.010            | 0.899 | 0.17             | 20.97                 | 22.00               | 1.140                    | Battery 2#            | /         |
| Back Side                                        | 0mm   | State1           | 9400/1880           | RMC       | 1.930            | 0.841 | 0.19             | 20.97                 | 22.00               | 1.066                    | Battery 3#            | /         |
| Back Side                                        | 0mm   | State2           | 9400/1880           | RMC       | 2.550            | 1.100 | 0.13             | 20.97                 | 22.00               | 1.394                    | Battery1#             | /         |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                          |                       |           |
| Front Side                                       | 11mm  | State1           | 9400/1880           | RMC       | 0.812            | 0.429 | 0.03             | 22.91                 | 24.00               | 0.551                    | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 9400/1880           | RMC       | 1.130            | 0.593 | 0.01             | 22.91                 | 24.00               | 0.762                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 9400/1880           | RMC       | 1.720            | 0.934 | 0.15             | 22.91                 | 24.00               | 1.200                    | Battery1#             | /         |

Table 129: Product Specific 10-g SAR results of UMTS Band II

## 7.2.15 SAR measurement Result of UMTS Band IV(Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | State2           | 1413/1732.6         | RMC       | 0.249            | 0.157 | -0.17            | 22.85                 | 24.00               | 0.324                   | Battery1#             | /         |
| Left touch            | /     | State1           | 1413/1732.6         | RMC       | 0.420            | 0.267 | 0.00             | 22.85                 | 24.00               | 0.547                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 1413/1732.6         | RMC       | 0.138            | 0.083 | -0.02            | 22.85                 | 24.00               | 0.180                   | Battery1#             | /         |
| Right touch           | /     | State1           | 1413/1732.6         | RMC       | 0.179            | 0.118 | 0.19             | 22.85                 | 24.00               | 0.233                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 1413/1732.6         | RMC       | 0.117            | 0.067 | -0.01            | 22.85                 | 24.00               | 0.152                   | Battery1#             | /         |
| Left touch            | /     | State1           | 1413/1732.6         | RMC       | 0.393            | 0.253 | 0.10             | 22.85                 | 24.00               | 0.512                   | SIM2                  | /         |
| Left touch            | /     | State1           | 1413/1732.6         | RMC       | 0.347            | 0.222 | -0.01            | 22.85                 | 24.00               | 0.452                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 1413/1732.6         | RMC       | 0.372            | 0.238 | -0.05            | 22.85                 | 24.00               | 0.485                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 1312/1712.4         | RMC       | 0.296            | 0.190 | -0.10            | 22.81                 | 24.00               | 0.389                   | Battery1#             | /         |
| Left touch            | /     | State1           | 1513/1752.6         | RMC       | 0.427            | 0.274 | -0.06            | 22.82                 | 24.00               | 0.560                   | Battery1#             | Yes       |
| Left touch            | /     | State2           | 1513/1752.6         | RMC       | 0.296            | 0.173 | 0.11             | 22.82                 | 24.00               | 0.388                   | Battery1#             | /         |

Table 130: Head SAR test results of UMTS Band IV

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | State2           | 1413/1732.6         | RMC       | 0.287            | 0.167 | -0.11            | 22.85                 | 24.00               | 0.374                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 1413/1732.6         | RMC       | 0.403            | 0.236 | -0.11            | 22.85                 | 24.00               | 0.525                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 1413/1732.6         | RMC       | 0.656            | 0.377 | 0.02             | 22.85                 | 24.00               | 0.855                   | Battery1#             | /         |
| Back Side                  | 15mm  | State2           | 1413/1732.6         | RMC       | 0.419            | 0.240 | -0.06            | 22.85                 | 24.00               | 0.546                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 1312/1712.4         | RMC       | 0.547            | 0.305 | -0.18            | 22.81                 | 24.00               | 0.719                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 1513/1752.6         | RMC       | 0.656            | 0.377 | -0.19            | 22.82                 | 24.00               | 0.861                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 1413/1732.6         | RMC       | 0.452            | 0.264 | -0.18            | 22.85                 | 24.00               | 0.589                   | SIM2                  | /         |
| Back Side                  | 15mm  | State1           | 1413/1732.6         | RMC       | 0.659            | 0.379 | -0.17            | 22.85                 | 24.00               | 0.859                   | Battery 2#            | /         |
| Back Side                  | 15mm  | State1           | 1413/1732.6         | RMC       | 0.660            | 0.376 | 0.07             | 22.85                 | 24.00               | 0.860                   | Battery 3#            | Yes       |
| Back Side                  | 15mm  | State1           | 1413/1732.6         | RMC       | 0.626            | 0.364 | -0.16            | 22.85                 | 24.00               | 0.816                   | Battery 3#            | /         |

Table 131: Body-Worn SAR test results of UMTS Band IV

| Test Position of Hotspot                         | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                                       | 10mm  | State1           | 1413/1732.6         | RMC       | 0.425            | 0.234 | 0.00             | 17.42                 | 18.00               | 0.486                   | Battery1#             | /         |
| Front Side                                       | 10mm  | State2           | 1413/1732.6         | RMC       | 0.289            | 0.158 | -0.16            | 17.42                 | 18.00               | 0.330                   | Battery1#             | /         |
| Back Side                                        | 10mm  | State1           | 1413/1732.6         | RMC       | 0.525            | 0.287 | 0.08             | 17.42                 | 18.00               | 0.600                   | Battery1#             | /         |
| Left Side                                        | 10mm  | State1           | 1413/1732.6         | RMC       | 0.171            | 0.102 | -0.12            | 19.94                 | 21.00               | 0.218                   | Battery1#             | /         |
| Right Side                                       | 10mm  | State1           | 1413/1732.6         | RMC       | 0.044            | 0.024 | -0.13            | 19.94                 | 21.00               | 0.056                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 1.090            | 0.594 | -0.03            | 17.42                 | 18.00               | 1.246                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 1312/1712.4         | RMC       | 0.634            | 0.345 | 0.08             | 17.52                 | 18.00               | 0.708                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 1513/1752.6         | RMC       | 0.708            | 0.384 | 0.07             | 17.51                 | 18.00               | 0.793                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 1.070            | 0.582 | 0.05             | 17.42                 | 18.00               | 1.223                   | Battery 2#            | /         |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 1.110            | 0.607 | -0.06            | 17.42                 | 18.00               | 1.269                   | Battery 3#            | Yes       |
| Bottom Side-Repeated                             | 10mm  | State1           | 1413/1732.6         | RMC       | 1.080            | 0.593 | -0.13            | 17.42                 | 18.00               | 1.234                   | Battery 3#            | /         |
| Bottom Side-holder perturbation verification     | 10mm  | State1           | 1413/1732.6         | RMC       | 0.967            | 0.528 | 0.02             | 17.42                 | 18.00               | 1.105                   | Battery 3#            | /         |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 0.982            | 0.536 | 0.02             | 17.42                 | 18.00               | 1.122                   | SIM2                  | /         |
| Bottom Side                                      | 10mm  | State2           | 1413/1732.6         | RMC       | 0.676            | 0.368 | -0.05            | 17.42                 | 18.00               | 0.773                   | Battery 3#            | /         |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                         |                       |           |
| Front Side                                       | 11mm  | State1           | 1413/1732.6         | RMC       | 0.513            | 0.289 | 0.04             | 19.94                 | 21.00               | 0.655                   | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 1413/1732.6         | RMC       | 0.344            | 0.200 | -0.12            | 19.94                 | 21.00               | 0.439                   | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 1413/1732.6         | RMC       | 0.873            | 0.490 | -0.05            | 19.94                 | 21.00               | 1.114                   | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 1312/1712.4         | RMC       | 0.778            | 0.437 | -0.13            | 19.86                 | 21.00               | 1.012                   | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 1513/1752.6         | RMC       | 0.855            | 0.479 | -0.14            | 19.88                 | 21.00               | 1.107                   | Battery1#             | /         |

Table 132: Hotspot SAR test results of UMTS Band IV

Note: According to 201610 FCC TCB workshop RF exposure slides, when the highest reported SAR of an antenna is > 1.2 W/kg, holder perturbation verification is required for each antenna, using the highest SAR configuration among all applicable frequency bands.

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot                         | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 10mm  | State1           | 1413/1732.6         | RMC       | 0.425            | 0.234 | 0.00             | 17.42                 | 24.00               | 1.934                   | Battery1#             | No                                  |
| Front Side                                       | 10mm  | State2           | 1413/1732.6         | RMC       | 0.289            | 0.158 | -0.16            | 17.42                 | 24.00               | 1.315                   | Battery1#             | No                                  |
| Back Side                                        | 10mm  | State1           | 1413/1732.6         | RMC       | 0.525            | 0.287 | 0.08             | 17.42                 | 24.00               | 2.389                   | Battery1#             | No                                  |
| Left Side                                        | 10mm  | State1           | 1413/1732.6         | RMC       | 0.171            | 0.102 | -0.12            | 19.94                 | 24.00               | 0.436                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | State1           | 1413/1732.6         | RMC       | 0.044            | 0.024 | -0.13            | 19.94                 | 24.00               | 0.112                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 1.090            | 0.594 | -0.03            | 17.42                 | 24.00               | 4.959                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State1           | 1312/1712.4         | RMC       | 0.634            | 0.345 | 0.08             | 17.52                 | 24.00               | 2.819                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State1           | 1513/1752.6         | RMC       | 0.708            | 0.384 | 0.07             | 17.51                 | 24.00               | 3.155                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 1.070            | 0.582 | 0.05             | 17.42                 | 24.00               | 4.868                   | Battery 2#            | No                                  |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 1.110            | 0.607 | -0.06            | 17.42                 | 24.00               | 5.050                   | Battery 3#            | No                                  |
| Bottom Side- Repeated                            | 10mm  | State1           | 1413/1732.6         | RMC       | 1.080            | 0.593 | -0.13            | 17.42                 | 24.00               | 4.914                   | Battery 3#            | No                                  |
| Bottom Side- holder perturbation verification    | 10mm  | State1           | 1413/1732.6         | RMC       | 0.967            | 0.528 | 0.02             | 17.42                 | 24.00               | 4.400                   | Battery 3#            | No                                  |
| Bottom Side                                      | 10mm  | State1           | 1413/1732.6         | RMC       | 0.982            | 0.536 | 0.02             | 17.42                 | 24.00               | 4.468                   | SIM2                  | No                                  |
| Bottom Side                                      | 10mm  | State2           | 1413/1732.6         | RMC       | 0.676            | 0.368 | -0.05            | 17.42                 | 24.00               | 3.076                   | Battery 3#            | No                                  |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 11mm  | State1           | 1413/1732.6         | RMC       | 0.513            | 0.289 | 0.04             | 19.94                 | 24.00               | 1.307                   | Battery1#             | No                                  |
| Back Side                                        | 13mm  | State1           | 1413/1732.6         | RMC       | 0.344            | 0.200 | -0.12            | 19.94                 | 24.00               | 0.876                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | State1           | 1413/1732.6         | RMC       | 0.873            | 0.490 | -0.05            | 19.94                 | 24.00               | 2.223                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 1312/1712.4         | RMC       | 0.778            | 0.437 | -0.13            | 19.86                 | 24.00               | 2.018                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 1513/1752.6         | RMC       | 0.855            | 0.479 | -0.14            | 19.88                 | 24.00               | 2.208                   | Battery1#             | No                                  |

Table 133: Product Specific 10-g SAR test reduction evaluation of UMTS Band IV

Note : According to the table above , **Front side**、**Bottom Side** and **Back side** Product Specific 10-g SAR test is required for this frequency band:

| Product Specific 10-g SAR                        | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 10-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|--------------------------|-----------------------|-----------|
|                                                  |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                          |                       |           |
| Front Side                                       | 0mm   | State2           | 1413/1732.6         | RMC       | 3.300            | 1.470 | 0.01             | 20.93                 | 22.00               | 1.881                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 1413/1732.6         | RMC       | 3.850            | 1.700 | 0.14             | 20.93                 | 22.00               | 2.175                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 1312/1712.4         | RMC       | 4.070            | 1.760 | -0.08            | 20.89                 | 22.00               | 2.273                    | Battery1#             | Yes       |
| Front Side                                       | 0mm   | State2           | 1312/1712.4         | RMC       | 2.730            | 1.240 | -0.11            | 20.93                 | 22.00               | 1.586                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 1513/1752.6         | RMC       | 3.530            | 1.510 | -0.01            | 20.91                 | 22.00               | 1.941                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 1413/1732.6         | RMC       | 3.430            | 1.450 | 0.19             | 20.93                 | 22.00               | 1.855                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 1413/1732.6         | RMC       | 1.230            | 0.505 | -0.14            | 20.93                 | 22.00               | 0.646                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 1312/1712.4         | RMC       | 3.890            | 1.690 | 0.18             | 20.89                 | 22.00               | 2.182                    | Battery 2#            | /         |
| Front Side                                       | 0mm   | State1           | 1312/1712.4         | RMC       | 3.800            | 1.680 | -0.10            | 20.89                 | 22.00               | 2.169                    | Battery 3#            | /         |
| Front Side                                       | 0mm   | State1           | 1312/1712.4         | RMC       | 4.050            | 1.760 | 0.03             | 20.89                 | 22.00               | 2.273                    | SIM2                  | /         |
| Additional Body SAR test results with sensor off |       |                  |                     |           |                  |       |                  |                       |                     |                          |                       |           |
| Front Side                                       | 10mm  | State1           | 1413/1732.6         | RMC       | 0.960            | 0.546 | -0.19            | 22.85                 | 24.00               | 1.251                    | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 1413/1732.6         | RMC       | 1.050            | 0.601 | -0.16            | 22.85                 | 24.00               | 1.368                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 1413/1732.6         | RMC       | 1.690            | 0.959 | -0.11            | 22.85                 | 24.00               | 2.202                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 1312/1712.4         | RMC       | 1.660            | 0.943 | -0.01            | 22.81                 | 24.00               | 2.183                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 1513/1752.6         | RMC       | 1.720            | 0.974 | -0.11            | 22.82                 | 24.00               | 2.257                    | Battery1#             | /         |

Table 134: Product Specific 10-g SAR results of UMTS Band IV

## 7.2.16 SAR measurement Result of UMTS Band V(Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | /                | 4182/836.4          | RMC       | 0.159            | 0.122 | 0.01             | 22.89                 | 24.00               | 0.205                   | Battery1#             | /         |
| Left tilt             | /     | /                | 4182/836.4          | RMC       | 0.135            | 0.094 | -0.17            | 22.89                 | 24.00               | 0.174                   | Battery1#             | /         |
| Right touch           | /     | /                | 4182/836.4          | RMC       | 0.198            | 0.152 | 0.05             | 22.89                 | 24.00               | 0.256                   | Battery1#             | /         |
| Right tilt            | /     | /                | 4182/836.4          | RMC       | 0.130            | 0.091 | -0.09            | 22.89                 | 24.00               | 0.168                   | Battery1#             | /         |
| Right touch           | /     | /                | 4182/836.4          | RMC       | 0.196            | 0.150 | 0.03             | 22.89                 | 24.00               | 0.253                   | SIM2                  | /         |
| Right touch           | /     | /                | 4182/836.4          | RMC       | 0.217            | 0.167 | -0.01            | 22.89                 | 24.00               | 0.280                   | Battery 2#            | /         |
| Right touch           | /     | /                | 4182/836.4          | RMC       | 0.225            | 0.217 | -0.06            | 22.89                 | 24.00               | 0.291                   | Battery 3#            | /         |
| Right touch           | /     | /                | 4132/826.4          | RMC       | 0.215            | 0.165 | -0.03            | 22.90                 | 24.00               | 0.277                   | Battery 3#            | /         |
| Right touch           | /     | /                | 4233/846.6          | RMC       | 0.227            | 0.172 | -0.06            | 22.92                 | 24.00               | 0.291                   | Battery 3#            | Yes       |

Table 135: Head SAR test results of UMTS Band V

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | /                | 4182/836.4          | RMC       | 0.204            | 0.159 | -0.03            | 22.89                 | 24.00               | 0.263                   | Battery1#             | /         |
| Back Side                  | 15mm  | /                | 4182/836.4          | RMC       | 0.354            | 0.276 | -0.03            | 22.89                 | 24.00               | 0.457                   | Battery1#             | /         |
| Back Side                  | 15mm  | /                | 4182/836.4          | RMC       | 0.380            | 0.296 | -0.06            | 22.89                 | 24.00               | 0.491                   | SIM2                  | /         |
| Back Side                  | 15mm  | /                | 4182/836.4          | RMC       | 0.381            | 0.294 | -0.04            | 22.89                 | 24.00               | 0.492                   | Battery 2#            | Yes       |
| Back Side                  | 15mm  | /                | 4182/836.4          | RMC       | 0.374            | 0.292 | -0.04            | 22.89                 | 24.00               | 0.483                   | Battery 3#            | /         |

Table 136: Body-Worn SAR test results of UMTS Band V

| Test Position of Hotspot | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------|-------|------------------|---------------------|-----------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                          |       |                  |                     |           | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side               | 10mm  | /                | 4182/836.4          | RMC       | 0.206            | 0.159 | -0.08            | 22.89                 | 24.00               | 0.266                   | Battery1#             | /         |
| Back Side                | 10mm  | /                | 4182/836.4          | RMC       | 0.374            | 0.292 | -0.06            | 22.89                 | 24.00               | 0.483                   | Battery1#             | /         |
| Left Side                | 10mm  | /                | 4182/836.4          | RMC       | 0.285            | 0.196 | -0.04            | 22.89                 | 24.00               | 0.368                   | Battery1#             | /         |
| Right Side               | 10mm  | /                | 4182/836.4          | RMC       | 0.506            | 0.349 | -0.07            | 22.89                 | 24.00               | 0.653                   | Battery1#             | Yes       |
| Bottom Side              | 10mm  | /                | 4182/836.4          | RMC       | 0.143            | 0.074 | -0.08            | 22.89                 | 24.00               | 0.185                   | Battery1#             | /         |
| Right Side               | 10mm  | /                | 4182/836.4          | RMC       | 0.492            | 0.338 | -0.19            | 22.89                 | 24.00               | 0.635                   | SIM2                  | /         |
| Right Side               | 10mm  | /                | 4182/836.4          | RMC       | 0.478            | 0.329 | -0.11            | 22.89                 | 24.00               | 0.617                   | Battery 2#            | /         |
| Right Side               | 10mm  | /                | 4182/836.4          | RMC       | 0.480            | 0.332 | -0.13            | 22.89                 | 24.00               | 0.620                   | Battery 3#            | /         |

Table 137: Hotspot SAR test results of UMTS Band V

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.17 SAR measurement Result of LTE Band II (Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | State2           | 18900/1880          | 20M QPSK 1RB#50   | 0.171            | 0.112 | -0.16            | 22.67                 | 23.50               | 0.207                   | Battery1#             | /         |
| Left touch            | /     | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.256            | 0.166 | -0.16            | 22.67                 | 23.50               | 0.310                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.191            | 0.117 | -0.06            | 22.67                 | 23.50               | 0.231                   | Battery1#             | /         |
| Right touch           | /     | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.185            | 0.121 | -0.19            | 22.67                 | 23.50               | 0.224                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.155            | 0.088 | 0.04             | 22.67                 | 23.50               | 0.188                   | Battery1#             | /         |
| Left touch            | /     | State1           | 18900/1880          | 20M QPSK 50%RB#25 | 0.195            | 0.113 | 0.01             | 22.07                 | 23.00               | 0.242                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 18900/1880          | 20M QPSK 50%RB#25 | 0.152            | 0.093 | -0.05            | 22.07                 | 23.00               | 0.188                   | Battery1#             | /         |
| Right touch           | /     | State1           | 18900/1880          | 20M QPSK 50%RB#25 | 0.142            | 0.083 | 0.01             | 22.07                 | 23.00               | 0.176                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 18900/1880          | 20M QPSK 50%RB#25 | 0.119            | 0.064 | 0.04             | 22.07                 | 23.00               | 0.147                   | Battery1#             | /         |
| Left touch            | /     | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.238            | 0.155 | 0.09             | 22.67                 | 23.50               | 0.288                   | SIM2                  | /         |
| Left touch            | /     | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.258            | 0.169 | -0.11            | 22.67                 | 23.50               | 0.312                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.265            | 0.174 | -0.07            | 22.67                 | 23.50               | 0.321                   | Battery 3#            | Yes       |
| Left touch            | /     | State2           | 18900/1880          | 20M QPSK 1RB#50   | 0.188            | 0.119 | -0.15            | 22.67                 | 23.50               | 0.228                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 18700/1860          | 20M QPSK 1RB#0    | 0.171            | 0.112 | -0.16            | 22.23                 | 23.50               | 0.229                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 19100/1900          | 20M QPSK 1RB#99   | 0.218            | 0.141 | -0.01            | 22.32                 | 23.50               | 0.286                   | Battery 3#            | /         |

Table 138: Head SAR test results of LTE Band II

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | State2           | 18900/1880          | 20M QPSK 1RB#50   | 0.561            | 0.307 | 0.06             | 22.67                 | 23.50               | 0.679                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.607            | 0.351 | -0.17            | 22.67                 | 23.50               | 0.735                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.866            | 0.475 | -0.06            | 22.67                 | 23.50               | 1.048                   | Battery1#             | Yes       |
| Back Side                  | 15mm  | State2           | 18900/1880          | 20M QPSK 1RB#50   | 0.763            | 0.421 | -0.04            | 22.67                 | 23.50               | 0.924                   | Battery1#             | /         |
| Back Side-repeated         | 15mm  | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.794            | 0.435 | -0.02            | 22.67                 | 23.50               | 0.961                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 18700/1860          | 20M QPSK 1RB#0    | 0.628            | 0.341 | -0.18            | 22.23                 | 23.50               | 0.841                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 19100/1900          | 20M QPSK 1RB#99   | 0.717            | 0.397 | -0.12            | 22.32                 | 23.50               | 0.941                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 18900/1880          | 20M QPSK 50%RB#25 | 0.473            | 0.273 | 0.11             | 22.07                 | 23.00               | 0.586                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 18900/1880          | 20M QPSK 50%RB#25 | 0.465            | 0.258 | -0.16            | 22.07                 | 23.00               | 0.576                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 19100/1900          | 20M QPSK 100%RB#0 | 0.554            | 0.307 | -0.02            | 21.86                 | 23.00               | 0.720                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.639            | 0.348 | 0.01             | 22.67                 | 23.50               | 0.774                   | Battery 2#            | /         |
| Back Side                  | 15mm  | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.624            | 0.316 | 0.08             | 22.67                 | 23.50               | 0.755                   | Battery 3#            | /         |
| Back Side                  | 15mm  | State1           | 18900/1880          | 20M QPSK 1RB#50   | 0.638            | 0.357 | -0.14            | 22.67                 | 23.50               | 0.772                   | SIM2                  | /         |

Table 139: Body-Worn SAR test results of LTE Band II

| Test Position of Hotspot                                     | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                                              |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 10mm  | State2           | 19100/1900               | 20M QPSK 1RB#50   | 0.285            | 0.154 | -0.12            | 16.97                 | 17.80               | 0.345                   | Battery1#             | /         |
| Front Side                                                   | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.383            | 0.207 | -0.04            | 16.97                 | 17.80               | 0.464                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.405            | 0.207 | -0.02            | 16.97                 | 17.80               | 0.490                   | Battery1#             | /         |
| Left Side                                                    | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.129            | 0.074 | -0.11            | 18.85                 | 19.70               | 0.157                   | Battery1#             | /         |
| Right Side                                                   | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.096            | 0.055 | -0.06            | 18.85                 | 19.70               | 0.116                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.505            | 0.265 | 0.11             | 16.97                 | 17.80               | 0.611                   | Battery1#             | /         |
| Front Side                                                   | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.415            | 0.222 | -0.13            | 16.86                 | 17.80               | 0.515                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.442            | 0.225 | -0.19            | 16.86                 | 17.80               | 0.549                   | Battery1#             | /         |
| Left Side                                                    | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.129            | 0.073 | -0.03            | 18.76                 | 19.70               | 0.160                   | Battery1#             | /         |
| Right Side                                                   | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.098            | 0.056 | -0.18            | 18.76                 | 19.70               | 0.121                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.561            | 0.293 | 0.17             | 16.86                 | 17.80               | 0.697                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.558            | 0.292 | -0.15            | 16.86                 | 17.80               | 0.693                   | SIM2                  | /         |
| Bottom Side                                                  | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.572            | 0.299 | -0.15            | 16.86                 | 17.80               | 0.710                   | Battery 2#            | /         |
| Bottom Side                                                  | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.530            | 0.280 | 0.16             | 16.86                 | 17.80               | 0.658                   | Battery 3#            | /         |
| Bottom Side                                                  | 10mm  | State2           | 18900/1880               | 20M QPSK 50%RB#25 | 0.408            | 0.214 | 0.02             | 16.86                 | 17.80               | 0.507                   | Battery 2#            | /         |
| Additional Body SAR test results with sensor off(hotspot on) |       |                  |                          |                   |                  |       |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 11mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.318            | 0.174 | 0.14             | 18.85                 | 19.70               | 0.387                   | Battery1#             | /         |
| Back Side                                                    | 13mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.361            | 0.192 | -0.12            | 18.85                 | 19.70               | 0.439                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.521            | 0.282 | 0.04             | 18.85                 | 19.70               | 0.634                   | Battery1#             | /         |
| Front Side                                                   | 11mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.373            | 0.206 | -0.06            | 18.76                 | 19.70               | 0.463                   | Battery1#             | /         |
| Back Side                                                    | 13mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.440            | 0.239 | 0.04             | 18.76                 | 19.70               | 0.546                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.646            | 0.359 | 0.08             | 18.76                 | 19.70               | 0.802                   | Battery1#             | Yes       |
| Bottom Side                                                  | 12mm  | State2           | 18900/1880               | 20M QPSK 50%RB#25 | 0.594            | 0.322 | 0.10             | 18.76                 | 19.70               | 0.738                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 18700/1860               | 20M QPSK 50%RB#25 | 0.418            | 0.220 | 0.10             | 18.35                 | 19.70               | 0.570                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 19100/1900               | 20M QPSK 50%RB#25 | 0.584            | 0.316 | 0.07             | 18.67                 | 19.70               | 0.740                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 19100/1900               | 20M QPSK 100%RB#0 | 0.535            | 0.280 | 0.08             | 18.52                 | 19.70               | 0.702                   | Battery1#             | /         |

Table 140: Hotspot SAR test results of LTE Band II

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot                         | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                                                  |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 10mm  | State2           | 19100/1900               | 20M QPSK 1RB#50   | 0.285            | 0.154 | -0.12            | 16.97                 | 23.50               | 1.282                   | Front Side            | No                                  |
| Front Side                                       | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.383            | 0.207 | -0.04            | 16.97                 | 23.50               | 1.723                   | Front Side            | No                                  |
| Back Side                                        | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.405            | 0.207 | -0.02            | 16.97                 | 23.50               | 1.822                   | Back Side             | No                                  |
| Left Side                                        | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.129            | 0.074 | -0.11            | 18.85                 | 23.50               | 0.376                   | Left Side             | Yes                                 |
| Right Side                                       | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.096            | 0.055 | -0.06            | 18.85                 | 23.50               | 0.279                   | Right Side            | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.505            | 0.265 | 0.11             | 16.97                 | 23.50               | 2.271                   | Bottom Side           | No                                  |
| Front Side                                       | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.415            | 0.222 | -0.13            | 16.86                 | 23.00               | 1.706                   | Battery1#             | No                                  |
| Back Side                                        | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.442            | 0.225 | -0.19            | 16.86                 | 23.00               | 1.817                   | Battery1#             | No                                  |
| Left Side                                        | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.129            | 0.073 | -0.03            | 18.76                 | 23.00               | 0.342                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.098            | 0.056 | -0.18            | 18.76                 | 23.00               | 0.259                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.561            | 0.293 | 0.17             | 16.86                 | 23.00               | 2.307                   | Battery1#             | No                                  |
| Bottom Side                                      | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.558            | 0.292 | -0.15            | 16.86                 | 23.00               | 2.294                   | SIM2                  | No                                  |
| Bottom Side                                      | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.572            | 0.299 | -0.15            | 16.86                 | 23.00               | 2.352                   | Battery 2#            | No                                  |
| Bottom Side                                      | 10mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.530            | 0.280 | 0.16             | 16.86                 | 23.00               | 2.179                   | Battery 3#            | No                                  |
| Bottom Side                                      | 10mm  | State2           | 18900/1880               | 20M QPSK 50%RB#25 | 0.408            | 0.214 | 0.02             | 16.86                 | 23.00               | 1.677                   | Battery 2#            | No                                  |
| Additional Body SAR test results with sensor off |       |                  |                          |                   |                  |       |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 11mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.318            | 0.174 | 0.14             | 18.85                 | 23.50               | 0.928                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.361            | 0.192 | -0.12            | 18.85                 | 23.50               | 1.053                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.521            | 0.282 | 0.04             | 18.85                 | 23.50               | 1.520                   | Battery1#             | No                                  |
| Front Side                                       | 11mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.373            | 0.206 | -0.06            | 18.76                 | 23.00               | 0.990                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.440            | 0.239 | 0.04             | 18.76                 | 23.00               | 1.168                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.646            | 0.359 | 0.08             | 18.76                 | 23.00               | 1.715                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State2           | 18900/1880               | 20M QPSK 50%RB#25 | 0.594            | 0.322 | 0.10             | 18.76                 | 23.00               | 1.577                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 18700/1860               | 20M QPSK 50%RB#25 | 0.418            | 0.220 | 0.10             | 18.35                 | 23.00               | 1.219                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 19100/1900               | 20M QPSK 50%RB#25 | 0.584            | 0.316 | 0.07             | 18.67                 | 23.00               | 1.583                   | Battery1#             | No                                  |
| Bottom Side                                      | 12mm  | State1           | 19100/1900               | 20M QPSK 100%RB#0 | 0.535            | 0.280 | 0.08             | 18.52                 | 23.00               | 1.501                   | Battery1#             | No                                  |

Table 141: Product Specific 10-g SAR test reduction evaluation of LTE Band II

Note : According to the table above ,**Front side**、**Bottom Side** and **Back side** Product Specific 10-g SAR test is required for this frequency band:

| Product Specific 10-g SAR                        | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 10-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|--------------------------|-----------------------|-----------|
|                                                  |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                          |                       |           |
| Front Side                                       | 0mm   | State2           | 19100/1900               | 20M QPSK 1RB#50   | 2.680            | 1.260 | 0.12             | 21.60                 | 22.00               | 1.382                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 19100/1900               | 20M QPSK 1RB#50   | 2.950            | 1.390 | 0.14             | 21.60                 | 22.00               | 1.524                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 19100/1900               | 20M QPSK 1RB#50   | 3.470            | 1.510 | -0.10            | 21.60                 | 22.00               | 1.656                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State2           | 19100/1900               | 20M QPSK 1RB#50   | 4.480            | 1.950 | 0.18             | 21.60                 | 22.00               | 2.138                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State2           | 18700/1860               | 20M QPSK 1RB#50   | 4.420            | 2.110 | 0.17             | 21.45                 | 22.00               | 2.395                    | Battery1#             | Yes       |
| Back Side-Repeated                               | 0mm   | State2           | 18700/1860               | 20M QPSK 1RB#50   | 4.080            | 1.860 | 0.11             | 21.45                 | 22.00               | 2.111                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State2           | 18900/1880               | 20M QPSK 1RB#50   | 3.020            | 1.430 | 0.11             | 21.31                 | 22.00               | 1.676                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.785            | 0.412 | -0.09            | 21.60                 | 22.00               | 0.452                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 1.940            | 0.926 | -0.13            | 20.15                 | 21.00               | 1.126                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 2.060            | 0.971 | -0.03            | 20.15                 | 21.00               | 1.181                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.467            | 0.245 | -0.07            | 20.15                 | 21.00               | 0.298                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State2           | 19100/1900               | 20M QPSK 100%RB#0 | 3.020            | 1.420 | 0.17             | 19.95                 | 21.00               | 1.808                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 19100/1900               | 20M QPSK 1RB#50   | 3.320            | 1.500 | -0.09            | 21.60                 | 22.00               | 1.645                    | SIM2                  | /         |
| Back Side                                        | 0mm   | State1           | 19100/1900               | 20M QPSK 1RB#50   | 3.230            | 1.400 | 0.06             | 21.60                 | 22.00               | 1.535                    | Battery 2#            | /         |
| Back Side                                        | 0mm   | State1           | 19100/1900               | 20M QPSK 1RB#50   | 3.200            | 1.400 | 0.04             | 21.60                 | 22.00               | 1.535                    | Battery 3#            | /         |
| Additional Body SAR test results with sensor off |       |                  |                          |                   |                  |       |                  |                       |                     |                          |                       |           |
| Front Side                                       | 11mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 0.936            | 0.497 | -0.03            | 22.67                 | 23.50               | 0.602                    | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 1.170            | 0.588 | -0.08            | 22.67                 | 23.50               | 0.712                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 19100/1900               | 20M QPSK 1RB#50   | 1.610            | 0.873 | 0.17             | 22.67                 | 23.50               | 1.057                    | Battery1#             | /         |
| Front Side                                       | 11mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.800            | 0.446 | -0.03            | 22.07                 | 23.00               | 0.553                    | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 0.991            | 0.491 | -0.03            | 22.07                 | 23.00               | 0.608                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 18900/1880               | 20M QPSK 50%RB#25 | 1.270            | 0.657 | 0.11             | 22.07                 | 23.00               | 0.814                    | Battery1#             | /         |

Table 142: Product Specific 10-g SAR results of LTE Band II

## 7.2.18 SAR measurement Result of LTE Band IV(Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | State2           | 20300/1745          | 20M QPSK 1RB#50   | 0.210            | 0.133 | -0.15            | 23.04                 | 23.50               | 0.233                   | Battery1#             | /         |
| Left touch            | /     | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.453            | 0.287 | -0.04            | 23.04                 | 23.50               | 0.504                   | Battery1#             | Yes       |
| Left tilt             | /     | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.125            | 0.076 | 0.01             | 23.04                 | 23.50               | 0.139                   | Battery1#             | /         |
| Right touch           | /     | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.176            | 0.118 | 0.10             | 23.04                 | 23.50               | 0.196                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.117            | 0.065 | 0.03             | 23.04                 | 23.50               | 0.130                   | Battery1#             | /         |
| Left touch            | /     | State1           | 20300/1745          | 20M QPSK 50%RB#25 | 0.355            | 0.224 | 0.19             | 22.01                 | 23.00               | 0.446                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 20300/1745          | 20M QPSK 50%RB#25 | 0.105            | 0.069 | -0.09            | 22.01                 | 23.00               | 0.132                   | Battery1#             | /         |
| Right touch           | /     | State1           | 20300/1745          | 20M QPSK 50%RB#25 | 0.133            | 0.081 | 0.17             | 22.01                 | 23.00               | 0.167                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 20300/1745          | 20M QPSK 50%RB#25 | 0.092            | 0.051 | 0.05             | 22.01                 | 23.00               | 0.116                   | Battery1#             | /         |
| Left touch            | /     | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.386            | 0.247 | -0.14            | 23.04                 | 23.50               | 0.429                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.390            | 0.250 | 0.16             | 23.04                 | 23.50               | 0.434                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.396            | 0.252 | 0.12             | 23.04                 | 23.50               | 0.440                   | SIM2                  | /         |
| Left touch            | /     | State1           | 20050/1720          | 20M QPSK 1RB#50   | 0.302            | 0.183 | -0.12            | 22.95                 | 23.50               | 0.343                   | Battery1#             | /         |
| Left touch            | /     | State1           | 20175/1732.5        | 20M QPSK 1RB#50   | 0.276            | 0.167 | 0.13             | 22.82                 | 23.50               | 0.323                   | Battery1#             | /         |

Table 143: Head SAR test results of LTE Band IV

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | State2           | 20300/1745          | 20M QPSK 1RB#50   | 0.168            | 0.097 | -0.11            | 23.04                 | 23.50               | 0.187                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.452            | 0.269 | -0.11            | 23.04                 | 23.50               | 0.503                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.761            | 0.436 | 0.17             | 23.04                 | 23.50               | 0.846                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 20300/1745          | 20M QPSK 50%RB#25 | 0.444            | 0.262 | -0.15            | 22.01                 | 23.00               | 0.558                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 20300/1745          | 20M QPSK 50%RB#25 | 0.522            | 0.302 | -0.16            | 22.01                 | 23.00               | 0.656                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.507            | 0.296 | -0.11            | 23.04                 | 23.50               | 0.564                   | Battery 2#            | /         |
| Back Side                  | 15mm  | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.789            | 0.460 | -0.12            | 23.04                 | 23.50               | 0.877                   | Battery 3#            | Yes       |
| Back Side                  | 15mm  | State1           | 20050/1720          | 20M QPSK 1RB#50   | 0.489            | 0.284 | -0.11            | 22.95                 | 23.50               | 0.555                   | Battery 3#            | /         |
| Back Side                  | 15mm  | State1           | 20175/1732.5        | 20M QPSK 1RB#50   | 0.400            | 0.231 | -0.17            | 22.82                 | 23.50               | 0.468                   | Battery 3#            | /         |
| Back Side                  | 15mm  | State1           | 20300/1745          | 20M QPSK 100%RB#0 | 0.495            | 0.289 | 0.11             | 21.98                 | 23.00               | 0.626                   | Battery3#             | /         |
| Back Side                  | 15mm  | State1           | 20300/1745          | 20M QPSK 1RB#50   | 0.704            | 0.408 | -0.05            | 23.04                 | 23.50               | 0.783                   | SIM2                  | /         |
| Back Side                  | 15mm  | State2           | 20300/1745          | 20M QPSK 1RB#50   | 0.192            | 0.108 | -0.10            | 23.04                 | 23.50               | 0.213                   | Battery 3#            | /         |

Table 144: Body-Worn SAR test results of LTE Band IV

| Test Position of Hotspot                                     | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                                              |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 10mm  | State2           | 20300/1745               | 20M QPSK 1RB#50   | 0.279            | 0.155 | -0.07            | 17.29                 | 18.00               | 0.329                   | Battery1#             | /         |
| Front Side                                                   | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.428            | 0.235 | 0.11             | 17.29                 | 18.00               | 0.504                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.530            | 0.279 | -0.13            | 17.29                 | 18.00               | 0.624                   | Battery1#             | /         |
| Left Side                                                    | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.150            | 0.092 | -0.14            | 19.26                 | 19.50               | 0.159                   | Battery1#             | /         |
| Right Side                                                   | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.036            | 0.020 | -0.10            | 19.26                 | 19.50               | 0.038                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.651            | 0.355 | -0.04            | 17.29                 | 18.00               | 0.767                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State2           | 20300/1745               | 20M QPSK 1RB#50   | 0.359            | 0.190 | 0.09             | 17.29                 | 18.00               | 0.423                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 20050/1720               | 20M QPSK 1RB#50   | 0.551            | 0.293 | 0.15             | 17.11                 | 18.00               | 0.676                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 20175/1732.5             | 20M QPSK 1RB#50   | 0.525            | 0.279 | 0.19             | 17.16                 | 18.00               | 0.637                   | Battery1#             | /         |
| Front Side                                                   | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 0.399            | 0.220 | -0.15            | 17.06                 | 18.00               | 0.495                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 0.470            | 0.248 | -0.07            | 17.06                 | 18.00               | 0.584                   | Battery1#             | /         |
| Left Side                                                    | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.139            | 0.085 | -0.03            | 18.95                 | 19.50               | 0.158                   | Battery1#             | /         |
| Right Side                                                   | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.037            | 0.021 | -0.06            | 18.95                 | 19.50               | 0.041                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 0.615            | 0.335 | -0.08            | 17.06                 | 18.00               | 0.764                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.557            | 0.295 | 0.12             | 17.29                 | 18.00               | 0.656                   | SIM2                  | /         |
| Bottom Side                                                  | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.585            | 0.309 | 0.03             | 17.29                 | 18.00               | 0.689                   | Battery 2#            | /         |
| Bottom Side                                                  | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.592            | 0.312 | 0.08             | 17.29                 | 18.00               | 0.697                   | Battery 3#            | /         |
| Additional Body SAR test results with sensor off(hotspot on) |       |                  |                          |                   |                  |       |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 11mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.411            | 0.232 | -0.05            | 19.26                 | 19.50               | 0.434                   | Battery1#             | /         |
| Back Side                                                    | 13mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.449            | 0.250 | -0.12            | 19.26                 | 19.50               | 0.475                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.747            | 0.419 | 0.12             | 19.26                 | 19.50               | 0.789                   | Battery1#             | Yes       |
| Bottom Side                                                  | 12mm  | State2           | 20300/1745               | 20M QPSK 1RB#50   | 0.320            | 0.166 | 0.17             | 19.26                 | 19.50               | 0.338                   | Battery1#             | /         |
| Front Side                                                   | 11mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.379            | 0.214 | 0.14             | 18.95                 | 19.50               | 0.430                   | Battery1#             | /         |
| Back Side                                                    | 13mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.422            | 0.234 | -0.07            | 18.95                 | 19.50               | 0.479                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.680            | 0.381 | 0.08             | 18.95                 | 19.50               | 0.772                   | Battery1#             | /         |

Table 145: Hotspot SAR test results of LTE Band IV

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot         | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|----------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                                  |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side                       | 10mm  | State2           | 20300/1745               | 20M QPSK 1RB#50   | 0.279            | 0.155 | -0.07            | 17.29                 | 23.50               | 1.166                   | Battery1#             | Yes                                 |
| Front Side                       | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.428            | 0.235 | 0.11             | 17.29                 | 23.50               | 1.788                   | Battery1#             | No                                  |
| Back Side                        | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.530            | 0.279 | -0.13            | 17.29                 | 23.50               | 2.215                   | Battery1#             | No                                  |
| Left Side                        | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.150            | 0.092 | -0.14            | 19.26                 | 23.50               | 0.398                   | Battery1#             | Yes                                 |
| Right Side                       | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.036            | 0.020 | -0.10            | 19.26                 | 23.50               | 0.095                   | Battery1#             | Yes                                 |
| Bottom Side                      | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.651            | 0.355 | -0.04            | 17.29                 | 23.50               | 2.720                   | Battery1#             | No                                  |
| Bottom Side                      | 10mm  | State2           | 20300/1745               | 20M QPSK 1RB#50   | 0.359            | 0.190 | 0.09             | 17.29                 | 23.50               | 1.500                   | Battery1#             | No                                  |
| Bottom Side                      | 10mm  | State1           | 20050/1720               | 20M QPSK 1RB#50   | 0.551            | 0.293 | 0.15             | 17.11                 | 23.50               | 2.400                   | Battery1#             | No                                  |
| Bottom Side                      | 10mm  | State1           | 20175/1732.5             | 20M QPSK 1RB#50   | 0.525            | 0.279 | 0.19             | 17.16                 | 23.50               | 2.260                   | Battery1#             | No                                  |
| Front Side                       | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 0.399            | 0.220 | -0.15            | 17.06                 | 23.00               | 1.567                   | Battery1#             | No                                  |
| Back Side                        | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 0.470            | 0.248 | -0.07            | 17.06                 | 23.00               | 1.845                   | Battery1#             | No                                  |
| Left Side                        | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.139            | 0.085 | -0.03            | 18.95                 | 23.00               | 0.353                   | Battery1#             | Yes                                 |
| Right Side                       | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.037            | 0.021 | -0.06            | 18.95                 | 23.00               | 0.093                   | Battery1#             | Yes                                 |
| Bottom Side                      | 10mm  | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 0.615            | 0.335 | -0.08            | 17.06                 | 23.00               | 2.415                   | Battery1#             | No                                  |
| Bottom Side                      | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.557            | 0.295 | 0.12             | 17.29                 | 23.00               | 2.074                   | SIM2                  | No                                  |
| Bottom Side                      | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.585            | 0.309 | 0.03             | 17.29                 | 23.00               | 2.178                   | Battery 2#            | No                                  |
| Bottom Side                      | 10mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.592            | 0.312 | 0.08             | 17.29                 | 23.00               | 2.205                   | Battery 3#            | No                                  |
| Additional Body SAR test results |       |                  |                          |                   |                  |       |                  |                       |                     |                         |                       |                                     |
| Front Side                       | 11mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.411            | 0.232 | -0.05            | 19.26                 | 23.50               | 1.091                   | Battery1#             | Yes                                 |
| Back Side                        | 13mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.449            | 0.250 | -0.12            | 19.26                 | 23.50               | 1.192                   | Battery1#             | Yes                                 |
| Bottom Side                      | 12mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.747            | 0.419 | 0.12             | 19.26                 | 23.50               | 1.983                   | Battery1#             | No                                  |
| Bottom Side                      | 12mm  | State2           | 20300/1745               | 20M QPSK 1RB#50   | 0.320            | 0.166 | 0.17             | 19.26                 | 23.50               | 0.849                   | Battery1#             | Yes                                 |
| Front Side                       | 11mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.379            | 0.214 | 0.14             | 18.95                 | 23.00               | 0.963                   | Battery1#             | Yes                                 |
| Back Side                        | 13mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.422            | 0.234 | -0.07            | 18.95                 | 23.00               | 1.072                   | Battery1#             | Yes                                 |
| Bottom Side                      | 12mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.680            | 0.381 | 0.08             | 18.95                 | 23.00               | 1.728                   | Battery1#             | No                                  |

Table 146: Product Specific 10-g SAR test reduction evaluation of LTE Band IV

Note : According to the table above , only **Bottom Side** and **Back side** Product Specific 10-g SAR test is required for this frequency band:

| Product Specific 10-g SAR                        | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 10-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|--------------------------|-----------------------|-----------|
|                                                  |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                          |                       |           |
| Back Side                                        | 0mm   | State2           | 20300/1745               | 20M QPSK 1RB#50   | 2.470            | 1.060 | 0.15             | 21.49                 | 21.50               | 1.062                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 20300/1745               | 20M QPSK 1RB#50   | 4.680            | 1.960 | -0.16            | 21.49                 | 21.50               | 1.965                    | Battery1#             | Yes       |
| Front Side                                       | 0mm   | State1           | 20300/1745               | 20M QPSK 1RB#50   | 2.020            | 0.916 | 0.01             | 21.49                 | 21.50               | 0.918                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 20300/1745               | 20M QPSK 1RB#50   | 0.769            | 0.396 | -0.06            | 21.49                 | 21.50               | 0.397                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 3.330            | 1.380 | 0.10             | 20.25                 | 21.00               | 1.640                    | Battery1#             | /         |
| Front Side                                       | 0mm   | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 2.000            | 0.901 | 0.17             | 20.25                 | 21.00               | 1.071                    | Battery1#             | /         |
| Bottom Side                                      | 0mm   | State1           | 20300/1745               | 20M QPSK 50%RB#25 | 0.616            | 0.318 | -0.07            | 20.25                 | 21.00               | 0.378                    | Battery1#             | /         |
| Back Side                                        | 0mm   | State1           | 20300/1745               | 20M QPSK 1RB#50   | 3.530            | 1.510 | 0.16             | 21.49                 | 21.50               | 1.513                    | SIM2                  | /         |
| Back Side                                        | 0mm   | State1           | 20300/1745               | 20M QPSK 1RB#50   | 4.380            | 1.830 | 0.03             | 21.49                 | 21.50               | 1.834                    | Battery 2#            | /         |
| Back Side                                        | 0mm   | State1           | 20300/1745               | 20M QPSK 1RB#50   | 3.890            | 1.650 | 0.08             | 21.49                 | 21.50               | 1.654                    | Battery 3#            | /         |
| Additional Body SAR test results with sensor off |       |                  |                          |                   |                  |       |                  |                       |                     |                          |                       |           |
| Front Side                                       | 11mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 1.000            | 0.556 | 0.13             | 23.04                 | 23.50               | 0.618                    | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 1.120            | 0.628 | -0.03            | 23.04                 | 23.50               | 0.698                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 20300/1745               | 20M QPSK 1RB#50   | 1.750            | 0.975 | 0.18             | 23.04                 | 23.50               | 1.084                    | Battery1#             | /         |
| Front Side                                       | 11mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 0.811            | 0.447 | 0.15             | 22.01                 | 23.00               | 0.561                    | Battery1#             | /         |
| Back Side                                        | 13mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 1.040            | 0.577 | -0.04            | 22.01                 | 23.00               | 0.725                    | Battery1#             | /         |
| Bottom Side                                      | 12mm  | State1           | 20300/1745               | 20M QPSK 50%RB#0  | 1.420            | 0.794 | 0.16             | 22.01                 | 23.00               | 0.997                    | Battery1#             | /         |

Table 147: Product Specific 10-g SAR results of LTE Band IV

### 7.2.19 SAR measurement Result of LTE Band V(Main Antenna)

| Test Position of Head | Dist. | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | 20600/844           | 10M QPSK 1RB#25   | 0.172            | 0.131 | -0.12            | 23.12                 | 24.00               | 0.211                   | Battery1#             | /         |
| Left tilt             | /     | 20600/844           | 10M QPSK 1RB#25   | 0.143            | 0.109 | 0.14             | 23.12                 | 24.00               | 0.175                   | Battery1#             | /         |
| Right touch           | /     | 20600/844           | 10M QPSK 1RB#25   | 0.214            | 0.163 | -0.04            | 23.12                 | 24.00               | 0.262                   | Battery1#             | /         |
| Right tilt            | /     | 20600/844           | 10M QPSK 1RB#25   | 0.125            | 0.087 | -0.06            | 23.12                 | 24.00               | 0.153                   | Battery1#             | /         |
| Left touch            | /     | 20600/844           | 10M QPSK 50%RB#13 | 0.131            | 0.100 | -0.11            | 22.08                 | 23.00               | 0.162                   | Battery1#             | /         |
| Left tilt             | /     | 20600/844           | 10M QPSK 50%RB#13 | 0.101            | 0.070 | 0.00             | 22.08                 | 23.00               | 0.125                   | Battery1#             | /         |
| Right touch           | /     | 20600/844           | 10M QPSK 50%RB#13 | 0.167            | 0.128 | 0.02             | 22.08                 | 23.00               | 0.206                   | Battery1#             | /         |
| Right tilt            | /     | 20600/844           | 10M QPSK 50%RB#13 | 0.077            | 0.054 | 0.01             | 22.08                 | 23.00               | 0.095                   | Battery1#             | /         |
| Right touch           | /     | 20600/844           | 10M QPSK 1RB#25   | 0.200            | 0.154 | 0.01             | 23.12                 | 24.00               | 0.245                   | SIM2                  | /         |
| Right touch           | /     | 20600/844           | 10M QPSK 1RB#25   | 0.220            | 0.165 | 0.04             | 23.12                 | 24.00               | 0.269                   | Battery 2#            | /         |
| Right touch           | /     | 20600/844           | 10M QPSK 1RB#25   | 0.190            | 0.130 | -0.18            | 23.12                 | 24.00               | 0.233                   | Battery 3#            | /         |
| Right touch           | /     | 20450/829           | 10M QPSK 1RB#25   | 0.225            | 0.171 | -0.04            | 22.88                 | 24.00               | 0.291                   | Battery 2#            | Yes       |
| Right touch           | /     | 20525/836.5         | 10M QPSK 1RB#25   | 0.188            | 0.128 | -0.03            | 22.80                 | 24.00               | 0.248                   | Battery 2#            | /         |

Table 148: Head SAR test results of LTE Band V

| Test Position of Body-Worn | Dist. | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | 20600/844           | 10M QPSK 1RB#25   | 0.104            | 0.080 | -0.06            | 23.12                 | 24.00               | 0.127                   | Battery1#             | /         |
| Back Side                  | 15mm  | 20600/844           | 10M QPSK 1RB#25   | 0.304            | 0.216 | -0.05            | 23.12                 | 24.00               | 0.372                   | Battery1#             | /         |
| Front Side                 | 15mm  | 20600/844           | 10M QPSK 50%RB#13 | 0.080            | 0.056 | -0.03            | 22.08                 | 23.00               | 0.098                   | Battery1#             | /         |
| Back Side                  | 15mm  | 20600/844           | 10M QPSK 50%RB#13 | 0.164            | 0.127 | 0.01             | 22.08                 | 23.00               | 0.203                   | Battery1#             | /         |
| Back Side                  | 15mm  | 20600/844           | 10M QPSK 1RB#25   | 0.314            | 0.241 | -0.03            | 23.12                 | 24.00               | 0.385                   | SIM2                  | /         |
| Back Side                  | 15mm  | 20600/844           | 10M QPSK 1RB#25   | 0.344            | 0.266 | -0.04            | 23.12                 | 24.00               | 0.421                   | Battery 2#            | Yes       |
| Back Side                  | 15mm  | 20600/844           | 10M QPSK 1RB#25   | 0.305            | 0.219 | 0.17             | 23.12                 | 24.00               | 0.374                   | Battery 3#            | /         |

Table 149: Body-Worn SAR test results of LTE Band V

| Test Position of Hotspot                         | Dist. | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------|-------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                                  |       |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.197            | 0.151 | -0.05            | 21.31                 | 22.00               | 0.231                   | Battery1#             | /         |
| Back Side                                        | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.246            | 0.188 | 0.14             | 21.31                 | 22.00               | 0.288                   | Battery1#             | /         |
| Left Side                                        | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.241            | 0.166 | -0.07            | 23.12                 | 24.00               | 0.295                   | Battery1#             | /         |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.427            | 0.294 | -0.14            | 23.12                 | 24.00               | 0.523                   | Battery1#             | Yes       |
| Bottom Side                                      | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.090            | 0.046 | 0.12             | 21.31                 | 22.00               | 0.105                   | Battery1#             | /         |
| Front Side                                       | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.156            | 0.120 | -0.06            | 20.13                 | 21.00               | 0.191                   | Battery1#             | /         |
| Back Side                                        | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.185            | 0.143 | -0.15            | 20.13                 | 21.00               | 0.226                   | Battery1#             | /         |
| Left Side                                        | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.192            | 0.132 | -0.02            | 22.08                 | 23.00               | 0.237                   | Battery1#             | /         |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.356            | 0.247 | -0.14            | 22.08                 | 23.00               | 0.440                   | Battery1#             | /         |
| Bottom Side                                      | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.068            | 0.035 | 0.06             | 20.13                 | 21.00               | 0.083                   | Battery1#             | /         |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.215            | 0.148 | -0.14            | 23.12                 | 24.00               | 0.263                   | Battery 2#            | /         |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.224            | 0.154 | -0.09            | 23.12                 | 24.00               | 0.274                   | Battery 3#            | /         |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.399            | 0.268 | 0.17             | 23.12                 | 24.00               | 0.489                   | SIM2                  | /         |
| Additional Body SAR test results with sensor off |       |                          |                   |                  |       |                  |                       |                     |                         |                       |           |
| Front Side                                       | 11mm  | 20600/844                | 10M QPSK 1RB#25   | 0.187            | 0.146 | -0.17            | 23.12                 | 24.00               | 0.229                   | Battery1#             | /         |
| Back Side                                        | 13mm  | 20600/844                | 10M QPSK 1RB#25   | 0.383            | 0.299 | 0.00             | 23.12                 | 24.00               | 0.469                   | Battery1#             | /         |
| Bottom Side                                      | 12mm  | 20600/844                | 10M QPSK 1RB#25   | 0.099            | 0.053 | 0.12             | 23.12                 | 24.00               | 0.121                   | Battery1#             | /         |
| Front Side                                       | 11mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.150            | 0.118 | 0.12             | 22.08                 | 23.00               | 0.185                   | Battery1#             | /         |
| Back Side                                        | 13mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.277            | 0.219 | -0.02            | 22.08                 | 23.00               | 0.342                   | Battery1#             | /         |
| Bottom Side                                      | 12mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.077            | 0.041 | 0.02             | 22.08                 | 23.00               | 0.095                   | Battery1#             | /         |

Table 150: Hotspot SAR test results of LTE Band V

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot                         | Dist. | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------------------------------|-------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                                                  |       |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.197            | 0.151 | -0.05            | 21.31                 | 24.00               | 0.366                   | Battery1#             | Yes                                 |
| Back Side                                        | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.246            | 0.188 | 0.14             | 21.31                 | 24.00               | 0.457                   | Battery1#             | Yes                                 |
| Left Side                                        | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.241            | 0.166 | -0.07            | 23.12                 | 24.00               | 0.295                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.427            | 0.294 | -0.14            | 23.12                 | 24.00               | 0.523                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.090            | 0.046 | 0.12             | 21.31                 | 24.00               | 0.167                   | Battery1#             | Yes                                 |
| Front Side                                       | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.156            | 0.120 | -0.06            | 20.13                 | 23.00               | 0.302                   | Battery1#             | Yes                                 |
| Back Side                                        | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.185            | 0.143 | -0.15            | 20.13                 | 23.00               | 0.358                   | Battery1#             | Yes                                 |
| Left Side                                        | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.192            | 0.132 | -0.02            | 22.08                 | 23.00               | 0.237                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.356            | 0.247 | -0.14            | 22.08                 | 23.00               | 0.440                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.068            | 0.035 | 0.06             | 20.13                 | 23.00               | 0.132                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.215            | 0.148 | -0.14            | 21.31                 | 24.00               | 0.263                   | Battery 2#            | Yes                                 |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.224            | 0.154 | -0.09            | 21.31                 | 24.00               | 0.274                   | Battery 3#            | Yes                                 |
| Right Side                                       | 10mm  | 20600/844                | 10M QPSK 1RB#25   | 0.399            | 0.268 | 0.17             | 21.31                 | 24.00               | 0.489                   | SIM2                  | Yes                                 |
| Additional Body SAR test results with sensor off |       |                          |                   |                  |       |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 11mm  | 20600/844                | 10M QPSK 1RB#25   | 0.187            | 0.146 | -0.17            | 23.12                 | 24.00               | 0.229                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | 20600/844                | 10M QPSK 1RB#25   | 0.383            | 0.299 | 0.00             | 23.12                 | 24.00               | 0.469                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | 20600/844                | 10M QPSK 1RB#25   | 0.099            | 0.053 | 0.12             | 23.12                 | 24.00               | 0.121                   | Battery1#             | Yes                                 |
| Front Side                                       | 11mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.150            | 0.118 | 0.12             | 23.12                 | 23.00               | 0.185                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.277            | 0.219 | -0.02            | 23.12                 | 23.00               | 0.342                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | 20600/844                | 10M QPSK 50%RB#13 | 0.077            | 0.041 | 0.02             | 23.12                 | 23.00               | 0.095                   | Battery1#             | Yes                                 |

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.20 SAR measurement Result of LTE Band VII(Main Antenna)

| Test Position of Head | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode        | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|------------------|---------------------|------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                  |                     |                  | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | State2           | 21100/2535          | 20M QPSK 1RB#50  | 0.081            | 0.044 | -0.13            | 21.75                 | 23.00               | 0.109                   | Battery1#             | /         |
| Left touch            | /     | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.210            | 0.118 | -0.18            | 21.75                 | 23.00               | 0.280                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.072            | 0.035 | 0.08             | 21.75                 | 23.00               | 0.096                   | Battery1#             | /         |
| Right touch           | /     | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.124            | 0.073 | -0.03            | 21.75                 | 23.00               | 0.165                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.121            | 0.067 | 0.18             | 21.75                 | 23.00               | 0.161                   | Battery1#             | /         |
| Left touch            | /     | State1           | 20850/2510          | 20M QPSK 50%RB#0 | 0.167            | 0.094 | 0.15             | 20.77                 | 22.00               | 0.222                   | Battery1#             | /         |
| Left tilt             | /     | State1           | 20850/2510          | 20M QPSK 50%RB#0 | 0.053            | 0.025 | 0.12             | 20.77                 | 22.00               | 0.070                   | Battery1#             | /         |
| Right touch           | /     | State1           | 20850/2510          | 20M QPSK 50%RB#0 | 0.098            | 0.058 | 0.03             | 20.77                 | 22.00               | 0.130                   | Battery1#             | /         |
| Right tilt            | /     | State1           | 20850/2510          | 20M QPSK 50%RB#0 | 0.094            | 0.053 | 0.10             | 20.77                 | 22.00               | 0.125                   | Battery1#             | /         |
| Left touch            | /     | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.357            | 0.198 | 0.02             | 21.75                 | 23.00               | 0.476                   | SIM2                  | /         |
| Left touch            | /     | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.382            | 0.210 | 0.10             | 21.75                 | 23.00               | 0.509                   | Battery 2#            | Yes       |
| Left touch            | /     | State2           | 21100/2535          | 20M QPSK 1RB#50  | 0.089            | 0.048 | 0.00             | 21.75                 | 23.00               | 0.118                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.343            | 0.190 | 0.18             | 21.75                 | 23.00               | 0.457                   | Battery 3#            | /         |
| Left touch            | /     | State1           | 20850/2510          | 20M QPSK 1RB#50  | 0.317            | 0.165 | 0.19             | 21.62                 | 23.00               | 0.436                   | Battery 2#            | /         |
| Left touch            | /     | State1           | 21350/2560          | 20M QPSK 1RB#0   | 0.320            | 0.165 | -0.07            | 21.67                 | 23.00               | 0.435                   | Battery 2#            | /         |

Table 151: Head SAR test results of LTE Band VII

| Test Position of Body-Worn | Dist. | Ant Tuning State | Channel /Freq.(MHz) | Test Mode        | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|------------------|---------------------|------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                  |                     |                  | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | State2           | 21100/2535          | 20M QPSK 1RB#50  | 0.117            | 0.058 | -0.13            | 21.75                 | 23.00               | 0.156                   | Battery1#             | /         |
| Front Side                 | 15mm  | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.188            | 0.108 | 0.09             | 21.75                 | 23.00               | 0.251                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.220            | 0.122 | -0.17            | 21.75                 | 23.00               | 0.293                   | Battery1#             | Yes       |
| Front Side                 | 15mm  | State1           | 20850/2510          | 20M QPSK 50%RB#0 | 0.169            | 0.097 | 0.19             | 20.77                 | 22.00               | 0.224                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 20850/2510          | 20M QPSK 50%RB#0 | 0.190            | 0.108 | -0.01            | 20.77                 | 22.00               | 0.252                   | Battery1#             | /         |
| Back Side                  | 15mm  | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.122            | 0.068 | -0.06            | 21.75                 | 23.00               | 0.163                   | Battery 2#            | /         |
| Back Side                  | 15mm  | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.212            | 0.119 | 0.13             | 21.75                 | 23.00               | 0.283                   | Battery 3#            | /         |
| Back Side                  | 15mm  | State1           | 21100/2535          | 20M QPSK 1RB#50  | 0.162            | 0.091 | -0.13            | 21.75                 | 23.00               | 0.216                   | SIM2                  | /         |
| Back Side                  | 15mm  | State2           | 21100/2535          | 20M QPSK 1RB#50  | 0.071            | 0.038 | 0.19             | 21.75                 | 23.00               | 0.095                   | Battery1#             | /         |

Table 152: Body-Worn SAR test results of LTE Band VII

| Test Position of Hotspot                                     | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------------------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                                                              |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 10mm  | State2           | 20850/2510               | 20M QPSK 1RB#50   | 0.073            | 0.034 | 0.09             | 15.30                 | 16.00               | 0.086                   | Battery1#             | /         |
| Front Side                                                   | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.097            | 0.054 | 0.11             | 15.30                 | 16.00               | 0.113                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State2           | 20850/2510               | 20M QPSK 1RB#50   | 0.137            | 0.075 | 0.14             | 15.30                 | 16.00               | 0.161                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.162            | 0.072 | 0.08             | 15.30                 | 16.00               | 0.190                   | Battery1#             | Yes       |
| Left Side                                                    | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.122            | 0.065 | 0.06             | 17.12                 | 18.00               | 0.149                   | Battery1#             | /         |
| Right Side                                                   | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.009            | 0.004 | -0.02            | 17.12                 | 18.00               | 0.011                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.051            | 0.024 | -0.03            | 15.30                 | 16.00               | 0.059                   | Battery1#             | /         |
| Front Side                                                   | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.097            | 0.053 | -0.03            | 15.17                 | 16.00               | 0.118                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.131            | 0.073 | 0.03             | 15.17                 | 16.00               | 0.159                   | Battery1#             | /         |
| Left Side                                                    | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.120            | 0.064 | 0.07             | 16.96                 | 18.00               | 0.152                   | Battery1#             | /         |
| Right Side                                                   | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.007            | 0.003 | -0.11            | 16.96                 | 18.00               | 0.009                   | Battery1#             | /         |
| Bottom Side                                                  | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.048            | 0.023 | 0.04             | 15.17                 | 16.00               | 0.058                   | Battery1#             | /         |
| Back Side                                                    | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.098            | 0.055 | -0.03            | 15.30                 | 16.00               | 0.116                   | Battery 2#            | /         |
| Back Side                                                    | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.122            | 0.067 | -0.16            | 15.30                 | 16.00               | 0.143                   | Battery 3#            | /         |
| Back Side                                                    | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.113            | 0.064 | -0.19            | 15.30                 | 16.00               | 0.133                   | SIM2                  | /         |
| Additional Body SAR test results with sensor off(hotspot on) |       |                  |                          |                   |                  |       |                  |                       |                     |                         |                       |           |
| Front Side                                                   | 11mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.151            | 0.084 | 0.06             | 17.12                 | 18.00               | 0.185                   | Battery1#             | /         |
| Back Side                                                    | 13mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.143            | 0.079 | -0.17            | 17.12                 | 18.00               | 0.175                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.061            | 0.031 | -0.16            | 17.12                 | 18.00               | 0.075                   | Battery1#             | /         |
| Front Side                                                   | 11mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.148            | 0.082 | 0.16             | 16.96                 | 18.00               | 0.188                   | Battery1#             | /         |
| Back Side                                                    | 13mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.130            | 0.072 | -0.09            | 16.96                 | 18.00               | 0.165                   | Battery1#             | /         |
| Bottom Side                                                  | 12mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.059            | 0.029 | -0.07            | 16.96                 | 18.00               | 0.075                   | Battery1#             | /         |

Table 153: Hotspot SAR test results of LTE Band VII

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

| Test Position of Hotspot                         | Dist. | Ant Tuning State | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | Product Specific 10-g SAR Exclusion |
|--------------------------------------------------|-------|------------------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-------------------------------------|
|                                                  |       |                  |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 10mm  | State2           | 20850/2510               | 20M QPSK 1RB#50   | 0.073            | 0.034 | 0.09             | 15.30                 | 23.00               | 0.432                   | Battery1#             | Yes                                 |
| Front Side                                       | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.097            | 0.054 | 0.11             | 15.30                 | 23.00               | 0.568                   | Battery1#             | Yes                                 |
| Back Side                                        | 10mm  | State2           | 20850/2510               | 20M QPSK 1RB#50   | 0.137            | 0.075 | 0.14             | 15.30                 | 23.00               | 0.807                   | Battery1#             | Yes                                 |
| Back Side                                        | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.162            | 0.072 | 0.08             | 15.30                 | 23.00               | 0.954                   | Battery1#             | Yes                                 |
| Left Side                                        | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.122            | 0.065 | 0.06             | 17.12                 | 23.00               | 0.472                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.009            | 0.004 | -0.02            | 17.12                 | 23.00               | 0.035                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.051            | 0.024 | -0.03            | 15.30                 | 23.00               | 0.297                   | Battery1#             | Yes                                 |
| Front Side                                       | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.097            | 0.053 | -0.03            | 15.17                 | 22.00               | 0.468                   | Battery1#             | Yes                                 |
| Back Side                                        | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.131            | 0.073 | 0.03             | 15.17                 | 22.00               | 0.631                   | Battery1#             | Yes                                 |
| Left Side                                        | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.120            | 0.064 | 0.07             | 16.96                 | 22.00               | 0.383                   | Battery1#             | Yes                                 |
| Right Side                                       | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.007            | 0.003 | -0.11            | 16.96                 | 22.00               | 0.022                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 10mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.048            | 0.023 | 0.04             | 15.17                 | 22.00               | 0.230                   | Battery1#             | Yes                                 |
| Back Side                                        | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.098            | 0.055 | -0.03            | 15.30                 | 23.00               | 0.579                   | Battery 2#            | Yes                                 |
| Back Side                                        | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.122            | 0.067 | -0.16            | 15.30                 | 23.00               | 0.718                   | Battery 3#            | Yes                                 |
| Back Side                                        | 10mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.113            | 0.064 | -0.19            | 15.30                 | 23.00               | 0.665                   | SIM2                  | Yes                                 |
| Additional Body SAR test results with sensor off |       |                  |                          |                   |                  |       |                  |                       |                     |                         |                       |                                     |
| Front Side                                       | 11mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.151            | 0.084 | 0.06             | 17.12                 | 23.00               | 0.585                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.143            | 0.079 | -0.17            | 17.12                 | 23.00               | 0.554                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | State1           | 20850/2510               | 20M QPSK 1RB#50   | 0.061            | 0.031 | -0.16            | 17.12                 | 23.00               | 0.236                   | Battery1#             | Yes                                 |
| Front Side                                       | 11mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.148            | 0.082 | 0.16             | 16.96                 | 22.00               | 0.472                   | Battery1#             | Yes                                 |
| Back Side                                        | 13mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.130            | 0.072 | -0.09            | 16.96                 | 22.00               | 0.415                   | Battery1#             | Yes                                 |
| Bottom Side                                      | 12mm  | State1           | 20850/2510               | 20M QPSK 50%RB#25 | 0.059            | 0.029 | -0.07            | 16.96                 | 22.00               | 0.188                   | Battery1#             | Yes                                 |

Table 154: Product Specific 10-g SAR test reduction evaluation LTE Band VII

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.21 SAR measurement Result of LTE Band XII(Main Antenna)

| Test Position of Head | Dist. | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|-------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                       |       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Left touch            | /     | 23130/711           | 10M QPSK 1RB#25   | 0.210            | 0.166 | -0.01            | 23.05                 | 24.00               | 0.261                   | Battery1#             | /         |
| Left tilt             | /     | 23130/711           | 10M QPSK 1RB#25   | 0.109            | 0.077 | -0.01            | 23.05                 | 24.00               | 0.136                   | Battery1#             | /         |
| Right touch           | /     | 23130/711           | 10M QPSK 1RB#25   | 0.233            | 0.183 | 0.02             | 23.05                 | 24.00               | 0.290                   | Battery1#             | /         |
| Right tilt            | /     | 23130/711           | 10M QPSK 1RB#25   | 0.109            | 0.078 | -0.03            | 23.05                 | 24.00               | 0.136                   | Battery1#             | /         |
| Left touch            | /     | 23130/711           | 10M QPSK 50%RB#13 | 0.152            | 0.122 | -0.08            | 21.95                 | 23.00               | 0.194                   | Battery1#             | /         |
| Left tilt             | /     | 23130/711           | 10M QPSK 50%RB#13 | 0.092            | 0.072 | 0.08             | 21.95                 | 23.00               | 0.117                   | Battery1#             | /         |
| Right touch           | /     | 23130/711           | 10M QPSK 50%RB#13 | 0.183            | 0.144 | -0.15            | 21.95                 | 23.00               | 0.233                   | Battery1#             | /         |
| Right tilt            | /     | 23130/711           | 10M QPSK 50%RB#13 | 0.088            | 0.063 | -0.10            | 21.95                 | 23.00               | 0.112                   | Battery1#             | /         |
| Right touch           | /     | 23130/711           | 10M QPSK 1RB#25   | 0.234            | 0.184 | -0.10            | 23.05                 | 24.00               | 0.291                   | SIM2                  | /         |
| Right touch           | /     | 23130/711           | 10M QPSK 1RB#25   | 0.234            | 0.185 | -0.02            | 23.05                 | 24.00               | 0.291                   | Battery 2#            | /         |
| Right touch           | /     | 23130/711           | 10M QPSK 1RB#25   | 0.226            | 0.178 | -0.14            | 23.05                 | 24.00               | 0.281                   | Battery 3#            | /         |
| Right touch           | /     | 23060/704           | 10M QPSK 1RB#25   | 0.231            | 0.181 | -0.19            | 22.84                 | 24.00               | 0.302                   | Battery 2#            | /         |
| Right touch           | /     | 23095/707.5         | 10M QPSK 1RB#25   | 0.250            | 0.196 | -0.12            | 22.88                 | 24.00               | 0.324                   | Battery 2#            | Yes       |

Table 155: Head SAR test results of LTE Band XII

| Test Position of Body-Worn | Dist. | Channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|----------------------------|-------|---------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                            |       |                     |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side                 | 15mm  | 23130/711           | 10M QPSK 1RB#25   | 0.224            | 0.177 | -0.04            | 23.05                 | 24.00               | 0.279                   | Battery1#             | /         |
| Back Side                  | 15mm  | 23130/711           | 10M QPSK 1RB#25   | 0.299            | 0.231 | -0.03            | 23.05                 | 24.00               | 0.372                   | Battery1#             | /         |
| Front Side                 | 15mm  | 23130/711           | 10M QPSK 50%RB#13 | 0.176            | 0.140 | -0.04            | 21.95                 | 23.00               | 0.224                   | Battery1#             | /         |
| Back Side                  | 15mm  | 23130/711           | 10M QPSK 50%RB#13 | 0.238            | 0.158 | -0.03            | 21.95                 | 23.00               | 0.303                   | Battery1#             | /         |
| Back Side                  | 15mm  | 23130/711           | 10M QPSK 1RB#25   | 0.288            | 0.225 | -0.06            | 23.05                 | 24.00               | 0.358                   | SIM2                  | /         |
| Back Side                  | 15mm  | 23130/711           | 10M QPSK 1RB#25   | 0.265            | 0.202 | -0.04            | 23.05                 | 24.00               | 0.330                   | Battery 2#            | /         |
| Back Side                  | 15mm  | 23130/711           | 10M QPSK 1RB#25   | 0.301            | 0.232 | -0.03            | 23.05                 | 24.00               | 0.375                   | Battery 3#            | Yes       |

Table 156: Body-Worn SAR test results of LTE Band XII

| Test Position of Hotspot | Dist. | Test channel /Freq.(MHz) | Test Mode         | SAR Value (W/kg) |       | Power Drift (dB) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported 1-g SAR (W/kg) | Accessory Information | SAR Plot. |
|--------------------------|-------|--------------------------|-------------------|------------------|-------|------------------|-----------------------|---------------------|-------------------------|-----------------------|-----------|
|                          |       |                          |                   | 1-g              | 10-g  |                  |                       |                     |                         |                       |           |
| Front Side               | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.237            | 0.190 | 0.04             | 23.05                 | 24.00               | 0.295                   | Battery1#             | /         |
| Back Side                | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.332            | 0.249 | -0.04            | 23.05                 | 24.00               | 0.413                   | Battery1#             | /         |
| Left Side                | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.181            | 0.123 | -0.13            | 23.05                 | 24.00               | 0.225                   | Battery1#             | /         |
| Right Side               | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.299            | 0.205 | -0.10            | 23.05                 | 24.00               | 0.372                   | Battery1#             | /         |
| Bottom Side              | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.099            | 0.053 | 0.01             | 23.05                 | 24.00               | 0.123                   | Battery1#             | /         |
| Front Side               | 10mm  | 23130/711                | 10M QPSK 50%RB#13 | 0.177            | 0.128 | 0.02             | 21.95                 | 23.00               | 0.225                   | Battery1#             | /         |
| Back Side                | 10mm  | 23130/711                | 10M QPSK 50%RB#13 | 0.253            | 0.180 | -0.08            | 21.95                 | 23.00               | 0.322                   | Battery1#             | /         |
| Left Side                | 10mm  | 23130/711                | 10M QPSK 50%RB#13 | 0.144            | 0.098 | -0.13            | 21.95                 | 23.00               | 0.183                   | Battery1#             | /         |
| Right Side               | 10mm  | 23130/711                | 10M QPSK 50%RB#13 | 0.240            | 0.164 | -0.08            | 21.95                 | 23.00               | 0.306                   | Battery1#             | /         |
| Bottom Side              | 10mm  | 23130/711                | 10M QPSK 50%RB#13 | 0.080            | 0.042 | 0.05             | 21.95                 | 23.00               | 0.101                   | Battery1#             | /         |
| Back Side                | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.352            | 0.265 | -0.08            | 23.05                 | 24.00               | 0.438                   | SIM2                  | /         |
| Back Side                | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.334            | 0.252 | -0.06            | 23.05                 | 24.00               | 0.416                   | Battery 2#            | /         |
| Back Side                | 10mm  | 23130/711                | 10M QPSK 1RB#25   | 0.364            | 0.274 | -0.06            | 23.05                 | 24.00               | 0.453                   | Battery 3#            | Yes       |

Table 157: Hotspot SAR test results of LTE Band XII

Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

## 7.2.22 SAR measurement Result of LTE Band XVII(Main Antenna)

SAR for LTE Band 17 (Frequency range:704-716 MHz) is covered by LTE Band 12 (Frequency range:699-716 MHz) due to similar frequency range,same maximum tune up limit and same channel bandwidth.

## 7.2.23 SAR measurement Result of WiFi 2.4G

| Test Position of Head | Test channel /Freq.(MHz) | Test Mode | Area Scan 1-g SAR (W/kg) | SAR Value (W/kg) |       | Power Drift (dB) | Actual duty factor | Scaled 1-g SAR (W/kg) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported SAR1-g (W/kg) | Accessory Information | SAR Plot. |
|-----------------------|--------------------------|-----------|--------------------------|------------------|-------|------------------|--------------------|-----------------------|-----------------------|---------------------|------------------------|-----------------------|-----------|
|                       |                          |           |                          | 1-g              | 10-g  |                  |                    |                       |                       |                     |                        |                       |           |
| Left touch            | 1/2412                   | 802.11b   | 0.254                    | 0.263            | 0.127 | 0.14             | 99.33%             | 0.265                 | 10.40                 | 11.00               | 0.304                  | Battery1#             | /         |
| Left tilt             | 1/2412                   | 802.11b   | 0.205                    | /                | /     | -0.06            | 99.33%             | /                     | 10.40                 | 11.00               | /                      | Battery1#             | /         |
| Right touch           | 1/2412                   | 802.11b   | 0.116                    | /                | /     | 0.13             | 99.33%             | /                     | 10.40                 | 11.00               | /                      | Battery1#             | /         |
| Right tilt            | 1/2412                   | 802.11b   | 0.122                    | /                | /     | 0.15             | 99.33%             | /                     | 10.40                 | 11.00               | /                      | Battery1#             | /         |
| Left touch            | 1/2412                   | 802.11b   | 0.253                    | 0.270            | 0.134 | 0.18             | 99.33%             | 0.272                 | 10.40                 | 11.00               | 0.312                  | Battery 2#            | /         |
| Left touch            | 1/2412                   | 802.11b   | 0.282                    | 0.278            | 0.135 | -0.02            | 99.33%             | 0.280                 | 10.40                 | 11.00               | 0.321                  | Battery 3#            | Yes       |
| Left touch            | 6/2437                   | 802.11b   | 0.256                    | 0.252            | 0.122 | 0.00             | 99.33%             | 0.254                 | 10.39                 | 11.00               | 0.292                  | Battery 3#            | /         |
| Left touch            | 11/2462                  | 802.11b   | 0.237                    | 0.234            | 0.112 | 0.01             | 99.33%             | 0.236                 | 10.10                 | 11.00               | 0.290                  | Battery 3#            | /         |

Table 158: Head SAR test results of WiFi 2.4G

| Mode        | Tune-up (dBm) | Tune-up (mW) | Highest Reported SAR(W/kg) | Adjusted SAR (W/kg) | SAR test |
|-------------|---------------|--------------|----------------------------|---------------------|----------|
| 802.11b     | 11.00         | 12.59        | 0.321                      | /                   | Yes      |
| 802.11g     | 11.00         | 12.59        | /                          | 0.321               | No       |
| 802.11n 20M | 11.00         | 12.59        | /                          | 0.321               | No       |
| 802.11n 40M | 11.00         | 12.59        | /                          | 0.321               | No       |

Note: Per KDB248227D01, for Head SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. The highest *reported* SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is < 1.2 W/kg, so SAR for 802.11g/n is not required.

| Test Position of Body-Worn with 15mm | Test channel /Freq.(MHz) | Test Mode | Area Scan 1-g SAR (W/kg) | SAR Value (W/kg) |       | Power Drift (dB) | Actual duty factor | Scaled 1-g SAR (W/kg) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported SAR1-g (W/kg) | SAR Plot. |
|--------------------------------------|--------------------------|-----------|--------------------------|------------------|-------|------------------|--------------------|-----------------------|-----------------------|---------------------|------------------------|-----------|
|                                      |                          |           |                          | 1-g              | 10-g  |                  |                    |                       |                       |                     |                        |           |
| Front Side                           | 1/2412                   | 802.11b   | 0.034                    | /                | /     | -0.01            | 99.33%             | /                     | 14.82                 | 16.50               | /                      | /         |
| Back Side                            | 1/2412                   | 802.11b   | 0.045                    | 0.046            | 0.025 | -0.12            | 99.33%             | 0.046                 | 14.82                 | 16.50               | 0.068                  | /         |
| Back Side                            | 1/2412                   | 802.11b   | 0.050                    | 0.052            | 0.028 | 0.13             | 99.33%             | 0.052                 | 14.82                 | 16.50               | 0.076                  | Yes       |
| Back Side                            | 1/2412                   | 802.11b   | 0.046                    | 0.046            | 0.024 | 0.11             | 99.33%             | 0.047                 | 14.82                 | 16.50               | 0.069                  | /         |

Table 159: Body-Worn SAR test results of WiFi 2.4G

| Mode        | Tune-up (dBm) | Tune-up (mW) | Highest Reported SAR(W/kg) | Adjusted SAR (W/kg) | SAR test |
|-------------|---------------|--------------|----------------------------|---------------------|----------|
| 802.11b     | 16.50         | 44.67        | 0.076                      | /                   | Yes      |
| 802.11g     | 17.00         | 50.12        | /                          | 0.085               | No       |
| 802.11n 20M | 17.00         | 50.12        | /                          | 0.085               | No       |
| 802.11n 40M | 17.00         | 50.12        | /                          | 0.085               | No       |

Note: Per KDB248227D01, for Body-worn SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. The highest *reported* SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is < 1.2 W/kg, so SAR for 802.11g/n is not required.

| Test Position of Hotspot with 10mm | Test channel /Freq.(MHz) | Test Mode | Area Scan 1-g SAR (W/kg) | SAR Value (W/kg) |       | Power Drift (dB) | Actual duty factor | Scaled 1-g SAR (W/kg) | Conducted Power (dBm) | Tune-up Power (dBm) | Reported SAR1-g (W/kg) | Actual duty factor | SAR Plot. |
|------------------------------------|--------------------------|-----------|--------------------------|------------------|-------|------------------|--------------------|-----------------------|-----------------------|---------------------|------------------------|--------------------|-----------|
|                                    |                          |           |                          | 1-g              | 10-g  |                  |                    |                       |                       |                     |                        |                    |           |
| Front Side                         | 1/2412                   | 802.11b   | 0.086                    | /                | /     | 0.00             | 99.33%             | 0.092                 | /                     | 16.50               | /                      | Battery1#          | /         |
| Back Side                          | 1/2412                   | 802.11b   | 0.103                    | 0.109            | 0.056 | 0.19             | 99.33%             | 0.110                 | 14.82                 | 16.50               | 0.162                  | Battery1#          | /         |
| Right Side                         | 1/2412                   | 802.11b   | 0.101                    | /                | /     | -0.11            | 99.33%             | 0.101                 | /                     | 16.50               | /                      | Battery1#          | /         |
| Top Side                           | 1/2412                   | 802.11b   | 0.045                    | /                | /     | 0.07             | 99.33%             | 0.052                 | /                     | 16.50               | /                      | Battery1#          | /         |
| Back Side                          | 1/2412                   | 802.11b   | 0.116                    | 0.124            | 0.063 | 0.03             | 99.33%             | 0.125                 | 14.82                 | 16.50               | 0.184                  | Battery 2#         | Yes       |
| Back Side                          | 1/2412                   | 802.11b   | 0.089                    | 0.095            | 0.048 | -0.04            | 99.33%             | 0.095                 | 14.82                 | 16.50               | 0.140                  | Battery 3#         | /         |

Table 160: Hotspot SAR test results of WiFi 2.4G

| Mode        | Tune-up (dBm) | Tune-up (mW) | Highest Reported SAR(W/kg) | Adjusted SAR (W/kg) | SAR test |
|-------------|---------------|--------------|----------------------------|---------------------|----------|
| 802.11b     | 16.50         | 44.67        | 0.184                      | /                   | Yes      |
| 802.11g     | 17.00         | 50.12        | /                          | 0.206               | No       |
| 802.11n 20M | 17.00         | 50.12        | /                          | 0.206               | No       |
| 802.11n 40M | 17.00         | 50.12        | /                          | 0.206               | No       |

Table 161: Hotspot SAR test results of WiFi 2.4G


Note:

- 1) Per KDB248227D01, for Hotspot SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. The highest *reported* SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is < 1.2 W/kg, so SAR for 802.11g/n is not required.
- 2) Note: Per KDB 648474 D04, product specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

### 7.3 Multiple Transmitter Evaluation

The following tables list information which is relevant for the decision if a simultaneous transmit evaluation is necessary according to FCC KDB 447498D01 General RF Exposure Guidance v06.

The location of the antennas inside the device is shown as below picture:



Note:

- 1) Per KDB 648474 D04, because the diagonal distance of this device is  $> 160\text{mm}$ , it is considered a "Phablet" device.
- 2) The device has two 2G/3G/4G Tx antennas (Main Antenna and Second Antenna). It can transmit from either Main Antenna or Second Antenna, but they can not transmit simultaneously.

| Mode        | Exposure Condition                 | Front Side | Back Side | Left Side | Right Side | Top Side | Bottom Side |
|-------------|------------------------------------|------------|-----------|-----------|------------|----------|-------------|
| Main ant    | Hotspot/ product specific 10-g SAR | Yes        | Yes       | Yes       | Yes        | No       | Yes         |
| Second ant  | Hotspot/ product specific 10-g SAR | Yes        | Yes       | Yes       | No         | Yes      | No          |
| WiFi Ant/BT | Hotspot/ product specific 10-g SAR | Yes        | Yes       | No        | Yes        | Yes      | No          |

Table 162: Sides for Hotspot// product specific 10-g SAR testing

Note:

- 1) Per KDB 941225 D06 and KDB 648474 D04, particular DUT edges were not required to be evaluated for Hotspot SAR if the antenna-to-edge distance is greater than 2.5cm;
- 2) Per KDB 648474 D04, when hotspot mode applies, product specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR  $> 1.2\text{ W/kg}$ ;

### 7.3.1 Stand-alone SAR test exclusion

Per FCC KDB 447498D01v06, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

| Mode | Position                        | $P_{\text{max}}$<br>(dBm)* | $P_{\text{max}}$<br>(mW) | Distance<br>(mm) | f<br>(GHz) | Calculation<br>Result | SAR<br>Exclusion<br>threshold | SAR test<br>exclusion |
|------|---------------------------------|----------------------------|--------------------------|------------------|------------|-----------------------|-------------------------------|-----------------------|
| BT   | Head                            | 8.00                       | 6.31                     | 5                | 2.480      | 1.99                  | 3.00                          | Yes                   |
| BT   | Body-<br>Worn                   | 8.00                       | 6.31                     | 15               | 2.480      | 0.66                  | 3.00                          | Yes                   |
| BT   | product<br>specific<br>10-g SAR | 8.00                       | 6.31                     | 5                | 2.480      | 1.99                  | 7.50                          | Yes                   |

Table 163: Standalone SAR test exclusion for BT

Note:

1)\* - maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$  for test separation distances  $\leq 50$  mm, where  $x = 7.5$  for 1-g SAR and  $x = 18.75$  for 10-g SAR.

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

| Mode | Position                     | $P_{\text{max}}$<br>(dBm)* | $P_{\text{max}}$<br>(mW) | Distance<br>(mm) | f<br>(GHz) | X     | Estimated<br>SAR (W/kg)* |
|------|------------------------------|----------------------------|--------------------------|------------------|------------|-------|--------------------------|
| BT   | Head                         | 8.00                       | 6.31                     | 5                | 2.480      | 7.50  | 0.265                    |
| BT   | Body-worn                    | 8.00                       | 6.31                     | 15               | 2.480      | 7.50  | 0.088                    |
| BT   | product specific<br>10-g SAR | 8.00                       | 6.31                     | 5                | 2.480      | 18.75 | 0.106                    |

Table 164: Estimated SAR calculation for BT

Note:

1) \* - maximum possible output power declared by manufacturer

2) Held to ear configurations are not applicable to Bluetooth and therefore were not considered for simultaneous transmission.

### 7.3.2 Simultaneous Transmission Possibilities

The Simultaneous Transmission Possibilities of this device are as below:

| NO. | Simultaneous Tx Combination   | Head | Body-worn | Hotspot (10mm) | Product Specific 10-g (0mm) |
|-----|-------------------------------|------|-----------|----------------|-----------------------------|
| 1   | GSM Voice(Main ant) + BT      | Yes  | Yes       | NA             | Yes                         |
| 2   | GSM DATA(Main ant) + BT       | N/A  | Yes       | NA             | Yes                         |
| 3   | GSM Voice(Second ant) + BT    | Yes  | Yes       | NA             | Yes                         |
| 4   | GSM DATA(Second ant)+ BT      | N/A  | Yes       | NA             | Yes                         |
| 5   | GSM Voice(Main ant) + WiFi    | Yes  | Yes       | NA             | Yes                         |
| 6   | GSM DATA(Main ant) + WiFi     | N/A  | Yes       | Yes            | Yes                         |
| 7   | GSM Voice(Second ant) + WiFi  | Yes  | Yes       | NA             | Yes                         |
| 8   | GSM DATA(Second ant) + WiFi   | N/A  | Yes       | Yes            | Yes                         |
| 9   | UMTS Voice(Main ant) + BT     | Yes  | Yes       | NA             | Yes                         |
| 10  | UMTS Data(Main ant) + BT      | N/A  | Yes       | NA             | Yes                         |
| 11  | UMTS Voice(Second ant) + BT   | Yes  | Yes       | NA             | Yes                         |
| 12  | UMTS Data(Second ant) + BT    | N/A  | Yes       | NA             | Yes                         |
| 13  | UMTS Voice(Main ant) + WiFi   | Yes  | Yes       | NA             | Yes                         |
| 14  | UMTS Data (Main ant) + WiFi   | Yes* | Yes       | Yes            | Yes                         |
| 15  | UMTS Voice (Second ant)+ WiFi | Yes  | Yes       | NA             | Yes                         |
| 16  | UMTS Data (Second ant)+ WiFi  | Yes* | Yes       | Yes            | Yes                         |
| 17  | LTE(Main ant) + WiFi          | Yes* | Yes*      | Yes            | Yes                         |
| 18  | LTE(Main ant) + BT            | Yes* | Yes*      | NA             | Yes                         |
| 19  | LTE (Second ant)+ WiFi        | Yes* | Yes*      | Yes            | Yes                         |
| 20  | LTE (Second ant) + BT         | Yes* | Yes*      | NA             | Yes                         |

Table 165: Simultaneous Transmission Possibilities

Note:

- 1) Wi-Fi and Bluetooth share the same Tx antenna and can't transmit simultaneously.
- 2) The device does not support DTM function.
- 3) \* VoLTE or pre-installed VOIP applications are considered.
- 4) The Main Antenna and Second Antenna can't transmit simultaneously.
- 5) The device not supports VoWiFi function.

### 7.3.3 SAR Summation Scenario

| Test Position            |             | Main antenna SAR <sub>Max</sub> |         |                 |                 |                |                |                |               |                 |                 | WiFi/BT antenna SAR <sub>Max</sub> |       | ΣSAR<br>(1.6W/kg Limit for 1g and<br>4.0W/kg Limit for Product<br>Specific 10-g SAR ) | SPLSR | Volume<br>scan |
|--------------------------|-------------|---------------------------------|---------|-----------------|-----------------|----------------|----------------|----------------|---------------|-----------------|-----------------|------------------------------------|-------|---------------------------------------------------------------------------------------|-------|----------------|
|                          |             | GSM850                          | GSM1900 | UMTS<br>Band II | UMTS<br>Band IV | UMTS<br>Band V | LTE<br>Band II | LTE<br>Band IV | LTE<br>Band V | LTE<br>Band VII | LTE<br>Band XII | WiFi 2.4G                          | BT    |                                                                                       |       |                |
| Head                     | Left touch  | 0.168                           | 0.196   | 0.323           | 0.560           | 0.205          | 0.321          | 0.504          | 0.211         | 0.509           | 0.261           | 0.321                              | 0.265 | 0.881                                                                                 | N/A   | N/A            |
|                          | Left tilt   | 0.130                           | 0.088   | 0.176           | 0.180           | 0.174          | 0.231          | 0.139          | 0.175         | 0.096           | 0.136           | 0.321                              | 0.265 | 0.552                                                                                 | N/A   | N/A            |
|                          | Right touch | 0.237                           | 0.084   | 0.216           | 0.233           | 0.291          | 0.224          | 0.196          | 0.291         | 0.165           | 0.324           | 0.321                              | 0.265 | 0.645                                                                                 | N/A   | N/A            |
| Body-worn                | Right tilt  | 0.129                           | 0.069   | 0.163           | 0.152           | 0.168          | 0.188          | 0.130          | 0.153         | 0.161           | 0.136           | 0.321                              | 0.265 | 0.509                                                                                 | N/A   | N/A            |
|                          | Front side  | 0.259                           | 0.261   | 0.635           | 0.525           | 0.263          | 0.735          | 0.558          | 0.127         | 0.251           | 0.279           | 0.066                              | 0.088 | 0.823                                                                                 | N/A   | N/A            |
|                          | Back side   | 0.455                           | 0.496   | 1.110           | 0.861           | 0.492          | 1.048          | 0.877          | 0.421         | 0.293           | 0.375           | 0.066                              | 0.088 | 1.198                                                                                 | N/A   | N/A            |
| Hotspot                  | Front side  | 0.227                           | 0.466   | 0.576           | 0.655           | 0.266          | 0.515          | 0.504          | 0.231         | 0.188           | 0.295           | 0.184                              | /     | 0.839                                                                                 | N/A   | N/A            |
|                          | Back side   | 0.433                           | 0.612   | 0.762           | 0.600           | 0.483          | 0.549          | 0.624          | 0.469         | 0.190           | 0.453           | 0.184                              | /     | 0.946                                                                                 | N/A   | N/A            |
|                          | Left side   | 0.352                           | 0.121   | 0.241           | 0.218           | 0.368          | 0.160          | 0.159          | 0.295         | 0.152           | 0.225           | /                                  | /     | 0.368                                                                                 | N/A   | N/A            |
|                          | Right side  | 0.587                           | 0.128   | 0.153           | 0.056           | 0.653          | 0.121          | 0.041          | 0.523         | 0.011           | 0.372           | 0.184                              | /     | 0.837                                                                                 | N/A   | N/A            |
|                          | Top side    | /                               | /       | /               | /               | /              | /              | /              | /             | /               | /               | 0.184                              | /     | 0.184                                                                                 | N/A   | N/A            |
| Product<br>Specific 10-g | Bottom side | 0.142                           | 0.946   | 1.032           | 1.269           | 0.185          | 0.802          | 0.789          | 0.121         | 0.075           | 0.123           | /                                  | /     | 1.269                                                                                 | N/A   | N/A            |
|                          | Front side  | /                               | /       | 1.109           | 2.273           | /              | 1.524          | 1.071          | /             | /               | /               | /                                  | 0.106 | 2.379                                                                                 | N/A   | N/A            |
|                          | Back side   | /                               | /       | 1.432           | 1.855           | /              | 2.395          | 1.965          | /             | /               | /               | /                                  | 0.106 | 2.501                                                                                 | N/A   | N/A            |
|                          | Left side   | /                               | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | /     | 0.000                                                                                 | N/A   | N/A            |
|                          | Right side  | /                               | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | 0.106 | 0.106                                                                                 | N/A   | N/A            |
|                          | Top side    | /                               | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | 0.106 | 0.106                                                                                 | N/A   | N/A            |
|                          | Bottom side | /                               | 0.260   | 1.200           | 2.257           | /              | 0.942          | 1.084          | /             | /               | /               | /                                  | 0.106 | 2.363                                                                                 | N/A   | N/A            |

Table 166: SAR Simultaneous Tx Combination of Main antenna and WiFi/BT antenna.

| Test Position            |             | Second antenna SAR <sub>Max</sub> |         |                 |                 |                |                |                |               |                 |                 | WiFi/BT antenna SAR <sub>Max</sub> |       | ΣSAR<br>(1.6W/kg Limit for 1g and<br>4.0W/kg Limit for Product<br>Specific 10-g SAR ) | SPLSR | Volume<br>scan |
|--------------------------|-------------|-----------------------------------|---------|-----------------|-----------------|----------------|----------------|----------------|---------------|-----------------|-----------------|------------------------------------|-------|---------------------------------------------------------------------------------------|-------|----------------|
|                          |             | GSM850                            | GSM1900 | UMTS<br>Band II | UMTS<br>Band IV | UMTS<br>Band V | LTE<br>Band II | LTE<br>Band IV | LTE<br>Band V | LTE<br>Band VII | LTE<br>Band XII | WiFi 2.4G                          | BT    |                                                                                       |       |                |
| Head                     | Left touch  | 0.354                             | 0.148   | 0.142           | 0.398           | 0.439          | 0.257          | 0.444          | 0.445         | 0.209           | 0.803           | 0.321                              | 0.265 | 1.124                                                                                 | N/A   | N/A            |
|                          | Left tilt   | 0.311                             | 0.137   | 0.127           | 0.413           | 0.435          | 0.211          | 0.442          | 0.444         | 0.162           | 0.528           | 0.321                              | 0.265 | 0.849                                                                                 | N/A   | N/A            |
|                          | Right touch | 1.001                             | 0.443   | 0.808           | 1.113           | 0.855          | 0.706          | 0.949          | 0.966         | 0.945           | 1.008           | 0.321                              | 0.265 | 1.434                                                                                 | N/A   | N/A            |
| Body-worn                | Right tilt  | 0.767                             | 0.270   | 0.296           | 0.687           | 0.711          | 0.395          | 0.771          | 0.695         | 0.516           | 0.789           | 0.321                              | 0.265 | 1.110                                                                                 | N/A   | N/A            |
|                          | Front side  | 0.304                             | 0.024   | 0.044           | 0.108           | 0.240          | 0.102          | 0.145          | 0.093         | 0.179           | 0.155           | 0.066                              | 0.088 | 0.392                                                                                 | N/A   | N/A            |
|                          | Back side   | 0.475                             | 0.045   | 0.088           | 0.195           | 0.409          | 0.208          | 0.244          | 0.394         | 0.212           | 0.380           | 0.066                              | 0.088 | 0.563                                                                                 | N/A   | N/A            |
| Hotspot                  | Front side  | 0.138                             | 0.022   | 0.045           | 0.101           | 0.119          | 0.045          | 0.096          | 0.090         | 0.054           | 0.109           | 0.184                              | /     | 0.322                                                                                 | N/A   | N/A            |
|                          | Back side   | 0.308                             | 0.039   | 0.095           | 0.179           | 0.253          | 0.102          | 0.180          | 0.220         | 0.093           | 0.215           | 0.184                              | /     | 0.492                                                                                 | N/A   | N/A            |
|                          | Left side   | 0.148                             | 0.025   | 0.059           | 0.121           | 0.108          | 0.061          | 0.077          | 0.079         | 0.031           | 0.106           | /                                  | /     | 0.148                                                                                 | N/A   | N/A            |
|                          | Right side  | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | 0.184                              | /     | 0.184                                                                                 | N/A   | N/A            |
|                          | Top side    | 0.115                             | 0.042   | 0.072           | 0.295           | 0.091          | 0.070          | 0.147          | 0.072         | 0.033           | 0.183           | 0.184                              | /     | 0.479                                                                                 | N/A   | N/A            |
| Product<br>Specific 10-g | Bottom side | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | /     | 0.000                                                                                 | N/A   | N/A            |
|                          | Front side  | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | 0.106 | 0.106                                                                                 | N/A   | N/A            |
|                          | Back side   | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | 0.106 | 0.106                                                                                 | N/A   | N/A            |
|                          | Left side   | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | /     | 0.000                                                                                 | N/A   | N/A            |
|                          | Right side  | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | 0.106 | 0.106                                                                                 | N/A   | N/A            |
|                          | Top side    | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | 0.106 | 0.106                                                                                 | N/A   | N/A            |
|                          | Bottom side | /                                 | /       | /               | /               | /              | /              | /              | /             | /               | /               | /                                  | 0.106 | 0.106                                                                                 | N/A   | N/A            |

Table 167: SAR Simultaneous Tx Combination of Second antenna and WiFi/BT antenna.

### 7.3.4 Simultaneous Transmission Conclusion

The above numeral summed SAR results is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore simultaneous transmission SAR with Volume Scans is not required per KDB 447498 D01v06.

#### **Appendix A. System Check Plots**

**(Pls See Appendix No.: SYBH(Z-SAR)005102017-2A, total: 26 pages)**

#### **Appendix B. SAR Measurement Plots**

**(Pls See Appendix No.: SYBH(Z-SAR)005102017-2B, total: 72 pages)**

#### **Appendix C. Calibration Certificate**

**(Pls See Appendix No.: SYBH(Z-SAR)005102017-2C, total: 101 pages)**

#### **Appendix D. Photo documentation**

**(Pls See Appendix No.: SYBH(Z-SAR)005102017-2D, total: 7 pages)**

---

## **End**