



Appendix B. SAR Measurement Plots

Table of contents
GSM850 Head
GSM850 Body
GSM1900 Head
GSM1900 Body
LTE Band VII Head
LTE Band VII Body
WiFi 2.4G Head
WiFi 2.4G Body
Volume Scan

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM850 251CH Left touch**DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 849$ MHz; $\sigma = 0.937$ S/m; $\epsilon_r = 41.95$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(8.77, 8.77, 8.77); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.635 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.553 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.707 W/kg

SAR(1 g) = 0.580 W/kg; SAR(10 g) = 0.444 W/kg

Maximum value of SAR (measured) = 0.637 W/kg



0 dB = 0.637 W/kg = -1.96 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM850 190CH Right touch

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.925$ S/m; $\epsilon_r = 42.116$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(8.77, 8.77, 8.77); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.536 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.509 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.595 W/kg

SAR(1 g) = 0.501 W/kg; SAR(10 g) = 0.389 W/kg

Maximum value of SAR (measured) = 0.538 W/kg



0 dB = 0.538 W/kg = -2.69 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM850 190CH Back Side 15mm with Battery 2

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.977$ S/m; $\epsilon_r = 52.969$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(8.82, 8.82, 8.82); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.626 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 24.97 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.733 W/kg

SAR(1 g) = 0.587 W/kg; SAR(10 g) = 0.449 W/kg

Maximum value of SAR (measured) = 0.644 W/kg



0 dB = 0.644 W/kg = -1.91 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM850 GPRS 2TS 251CH Back Side 10mm with Battery 2**DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-2TS (0); Frequency: 848.8 MHz; Duty Cycle: 1:4.10015

Medium parameters used: $f = 849$ MHz; $\sigma = 0.997$ S/m; $\epsilon_r = 52.834$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(8.82, 8.82, 8.82); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.22 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 34.49 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.866 W/kg

Maximum value of SAR (measured) = 1.23 W/kg



0 dB = 1.23 W/kg = 0.91 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM1900 810CH Right touch

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.432$ S/m; $\epsilon_r = 38.537$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ⌄ Probe: EX3DV4 - SN3744; ConvF(7.54, 7.54, 7.54); Calibrated: 2015-7-24;
- ⌄ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ⌄ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ⌄ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ⌄ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.431 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.974 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.573 W/kg

SAR(1 g) = 0.365 W/kg; SAR(10 g) = 0.223 W/kg

Maximum value of SAR (measured) = 0.424 W/kg



0 dB = 0.424 W/kg = -3.72 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM1900 661CH Front Side 15mm with Battery 2

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.484$ S/m; $\epsilon_r = 51.142$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(7.24, 7.24, 7.24); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.162 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.884 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.227 W/kg

SAR(1 g) = 0.150 W/kg; SAR(10 g) = 0.096 W/kg

Maximum value of SAR (measured) = 0.174 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.884 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.211 W/kg

SAR(1 g) = 0.141 W/kg; SAR(10 g) = 0.091 W/kg

Maximum value of SAR (measured) = 0.164 W/kg



0 dB = 0.164 W/kg = -7.85 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM1900 GPRS 2TS 810CH Back Side 10mm**DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-2TS (0); Frequency: 1909.8 MHz; Duty Cycle: 1:4.10015

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.526$ S/m; $\epsilon_r = 51.129$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(7.24, 7.24, 7.24); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.823 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.256 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.706 W/kg; SAR(10 g) = 0.346 W/kg

Maximum value of SAR (measured) = 0.916 W/kg



0 dB = 0.916 W/kg = -0.38 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 LTE Band VII 20M QPSK 1RB 50 offset 20850CH Left touch**DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2510 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2510$ MHz; $\sigma = 1.883$ S/m; $\epsilon_r = 38.894$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(6.68, 6.68, 6.68); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x15x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.134 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.329 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.207 W/kg

SAR(1 g) = 0.113 W/kg; SAR(10 g) = 0.061 W/kg

Maximum value of SAR (measured) = 0.139 W/kg



0 dB = 0.139 W/kg = -8.57 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 LTE Band VII 20M QPSK 1RB 99 offset 21350CH Back Side 15mm

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 2.141$ S/m; $\epsilon_r = 50.879$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(6.65, 6.65, 6.65); Calibrated: 2015-7-24;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn852; Calibrated: 2015-4-27

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x15x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.400 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.922 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.621 W/kg

SAR(1 g) = 0.343 W/kg; SAR(10 g) = 0.185 W/kg

Maximum value of SAR (measured) = 0.427 W/kg



0 dB = 0.427 W/kg = -3.70 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 LTE Band VII 20M QPSK 1RB 99 offset 21350CH Bottom Side 10mm-Repeated

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 2.141$ S/m; $\epsilon_r = 50.879$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3744; ConvF(6.65, 6.65, 6.65); Calibrated: 2015-7-24;

Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$

Electronics: DAE4 Sn852; Calibrated: 2015-4-27

Phantom: SAM4; Type: SAM; Serial: TP-1620

DASY52 52.8.8(1222);

Configuration/Body/Area Scan (6x11x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.05 W/kg



Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 15.61 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 0.889 W/kg; SAR(10 g) = 0.426 W/kg

Maximum value of SAR (measured) = 1.16 W/kg



0 dB = 1.16 W/kg = 0.64 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 wifi 2.4g 802.11b 11CH Right touch

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2462 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.817$ S/m; $\epsilon_r = 37.662$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ⌘ Probe: EX3DV4 - SN3744; ConvF(6.84, 6.84, 6.84); Calibrated: 2015-7-24;
- ⌘ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ⌘ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ⌘ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ⌘ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x15x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.04 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.66 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 2.24 W/kg

SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.448 W/kg

Maximum value of SAR (measured) = 1.38 W/kg



0 dB = 1.38 W/kg = 1.40 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 wifi 2.4g 802.11b 11CH Back Side 15mm**DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.995$ S/m; $\epsilon_r = 51.12$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(6.77, 6.77, 6.77); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x15x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.0857 W/kg



Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.981 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.366 W/kg

SAR(1 g) = 0.068 W/kg; SAR(10 g) = 0.025 W/kg

Maximum value of SAR (measured) = 0.0844 W/kg



0 dB = 0.0844 W/kg = -10.73 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 wifi 2.4g 802.11b 11CH Back Side 10mm**DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.995$ S/m; $\epsilon_r = 51.12$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(6.77, 6.77, 6.77); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x15x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.197 W/kg



Configuration/Body/Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.193 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.392 W/kg

SAR(1 g) = 0.163 W/kg; SAR(10 g) = 0.061 W/kg

Maximum value of SAR (measured) = 0.214 W/kg



0 dB = 0.214 W/kg = -6.69 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 GSM850 190CH Right touch-Volume Scan

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.899$ S/m; $\epsilon_r = 40.322$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(8.77, 8.77, 8.77); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Head/Volume Scan (22x35x7): Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 7.847 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.563 W/kg

SAR(1 g) = 0.465 W/kg; SAR(10 g) = 0.359 W/kg

Total Absorbed Power = 0.0535 W

Maximum value of SAR (measured) = 0.508 W/kg



0 dB = 0.508 W/kg = -2.94 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

HUAWEI CUN-L01 WiFi 2.4G 11b 11CH Right touch-Volume Scan

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.871$ S/m; $\epsilon_r = 38.821$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(6.84, 6.84, 6.84); Calibrated: 2015-7-24;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 31.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2015-4-27
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Head/Volume Scan (22x35x7): Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm



Reference Value = 11.13 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 2.04 W/kg

SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.452 W/kg

Total Absorbed Power = 0.0152 W

Maximum value of SAR (measured) = 1.32 W/kg



0 dB = 1.32 W/kg = 1.21 dBW/kg

Multi-Band Average SAR

Multi-Band Configurations:

DASY Configuration for Configuration/Head/Volume Scan:

Date/Time: 2016-3-26

Test Laboratory: HUAWEI SAR/HAC Lab

File Name: [HUAWEI CUN-L01 GSM850 190CH Right touch-Volume Scan.da53:0](#)

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium: HSL835 Medium parameters used: $f = 837$ MHz; $\sigma = 0.899$ S/m; $\epsilon_r = 40.322$; $\rho = 1000$ kg/m³

Phantom section: Right Section

- ε Probe: EX3DV4 - SN3744; ConvF(8.77, 8.77, 8.77); Calibrated: 2015-7-24;
 - ε Sensor-Surface: 3mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn852; Calibrated: 2015-4-27
 - ε Phantom: SAM3; Type: SAM; Serial: TP-1597
 - ε Measurement SW: DASY52, Version 52.8 (8)
-

DASY Configuration for Configuration/Head/Volume Scan:

Date/Time: 2016-3-25

Test Laboratory: HUAWEI SAR/HAC Lab

File Name: [HUAWEI CUN-L01 WiFi 2.4G 11b 11CH Right touch-Volume Scan.da53:0](#)

DUT: HUAWEI CUN-L01 CUN-L01; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL2450 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.871$ S/m; $\epsilon_r = 38.821$; $\rho = 1000$ kg/m³

Phantom section: Right Section

- ε Probe: EX3DV4 - SN3744; ConvF(6.84, 6.84, 6.84); Calibrated: 2015-7-24;
 - ε Sensor-Surface: 3mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn852; Calibrated: 2015-4-27
 - ε Phantom: SAM3; Type: SAM; Serial: TP-1597
 - ε Measurement SW: DASY52, Version 52.8 (8)
-

Multi Band Result:

SAR(1 g) = 1.4 W/kg; SAR(10 g) = 0.669 W/kg

Maximum value of SAR (interpolated) = 2.63 W/kg

