



SAR TEST REPORT

Product Name	Smart Phone
Model Name	HUAWEI GRA-L09
FCC ID	QISGRA-L09
Applicant	Huawei Technologies Co., Ltd.
Manufacturer	Huawei Technologies Co., Ltd.
Date of issue	April 3, 2015

TA Technology (Shanghai) Co., Ltd.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 2 of 370

GENERAL SUMMARY

Reference Standard(s)	FCC 47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices ANSI C95.1- 1992: Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.(IEEE Std C95.1-1991) IEEE Std 1528™-2003: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques. IEEE Std 1528a-2005: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques. KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r03: SAR Measurement Requirements for 100 MHz to 6 GHz KDB 447498 D01 Mobile Portable RF Exposure v05r02: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies KDB 648474 D04 Handset SAR v01r02: SAR Evaluation Considerations for Wireless Handsets. KDB 941225 D01 SAR test for 3G devices v03: SAR Measurement Procedures CDMA 20001x RTT, 1x Ev-Do, WCDMA, HSDPA/HSPA KDB 941225 D05 SAR for LTE Devices v02r03 SAR Test Considerations for LTE Handsets and Data Modems KDB 941225 D06 Hotspot Mode SAR v02: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities KDB 248227 D01 SAR meas for 802 11 a b g v01r02: SAR Measurement Procedures for 802.11a/b/g Transmitters.
Conclusion	This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 7 of this test report are below limits specified in the relevant standards for the tested bands only. General Judgment: Pass
Comment	The test result only responds to the measured sample.

Approved by Kai Xu
Kai Xu
Director

Revised by Jiang peng Lan
Jiangpeng Lan
SAR Manager

Performed by Liang Ye
Liang Ye
SAR Engineer

TABLE OF CONTENT

1. General Information	6
1.1. Notes of the Test Report.....	6
1.2. Testing Laboratory	6
1.3. Applicant Information	7
1.4. Manufacturer Information.....	7
1.5. Information of EUT	8
1.6. EUT Antenna Locations	10
1.7. The Maximum Reported SAR _{1g}	12
1.8. Test Date	14
2. SAR Measurements System Configuration	15
2.1. SAR Measurement Set-up	15
2.2. DASY5 E-field Probe System	16
2.2.1. EX3DV4 Probe Specification	16
2.2.2. E-field Probe Calibration	17
2.3. Other Test Equipment	17
2.3.1. Device Holder for Transmitters	17
2.3.2. Phantom	18
2.4. Scanning Procedure	18
2.5. Data Storage and Evaluation	20
2.5.1. Data Storage.....	20
2.5.2. Data Evaluation by SEMCAD	20
3. Laboratory Environment.....	22
4. Tissue-equivalent Liquid	23
4.1. Tissue-equivalent Liquid Ingredients.....	23
4.2. Tissue-equivalent Liquid Properties	26
5. System Check.....	27
5.1. Description of System Check.....	27
5.2. System Check Results.....	29
6. Operational Conditions during Test	31
6.1. General Description of Test Procedures	31
6.2. Test Positions.....	31
6.2.1. Against Phantom Head	31
6.2.2. Body Worn Configuration.....	31
6.3. Measurement Variability.....	33
6.4. Power Reduction.....	34
6.5. Test Configuration	55
6.5.1. GSM Test Configuration.....	55
6.5.2. UMTS Test Configuration	56
6.5.3. HSUPA Test Configuration	57
6.5.4. LTE Test Configuration.....	60
6.5.5. WiFi Test Configuration.....	62

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 4 of 370

7.	Test Results	63
7.1.	Conducted Power Results	63
7.2.	Standalone SAR Test Exclusion Considerations	128
7.3.	SAR Test Results	129
7.3.1.	GSM 850 (Antenna 1)	129
7.3.2.	GSM 1900 (Antenna 1)	131
7.3.3.	UMTS Band II (Antenna 1)	133
7.3.4.	UMTS Band IV (Antenna 1)	134
7.3.5.	UMTS Band V (Antenna 1)	136
7.3.6.	LTE Band 2 (Antenna 1)	137
7.3.7.	LTE Band 4 (Antenna 1)	139
7.3.8.	LTE Band 5 (Antenna 1)	141
7.3.9.	LTE Band 7 (Antenna 1)	143
7.3.10.	LTE Band 12 (Antenna 1)	145
7.3.11.	LTE Band 17 (Antenna 1)	147
7.3.12.	LTE Band 25 (Antenna 1)	149
7.3.13.	LTE Band 26 (Antenna 1)	151
7.3.14.	GSM 850 (Antenna 2)	153
7.3.15.	GSM 1900 (Antenna 2)	154
7.3.16.	UMTS Band II (Antenna 2)	156
7.3.17.	UMTS Band IV (Antenna 2)	158
7.3.18.	UMTS Band V (Antenna 2)	160
7.3.19.	LTE Band 2 (Antenna 2)	161
7.3.20.	LTE Band 4 (Antenna 2)	163
7.3.21.	LTE Band 5 (Antenna 2)	165
7.3.22.	LTE Band 7 (Antenna 2)	167
7.3.23.	LTE Band 12 (Antenna 2)	169
7.3.24.	LTE Band 17 (Antenna 2)	171
7.3.25.	LTE Band 25 (Antenna 2)	173
7.3.26.	LTE Band 26 (Antenna 2)	176
7.3.27.	WiFi	178
7.4.	Simultaneous Transmission Conditions	179
8.	700MHz to 3GHz Measurement Uncertainty	186
9.	Main Test Instruments	188
ANNEX A:	Test Layout	189
ANNEX B:	System Check Results	196
ANNEX C:	Highest Graph Results	216
ANNEX D:	Probe Calibration Certificate	298
ANNEX E:	D750V3 Dipole Calibration Certificate	309
ANNEX F:	D835V2 Dipole Calibration Certificate	317
ANNEX G:	D1750V2 Dipole Calibration Certificate	325
ANNEX H:	D1900V2 Dipole Calibration Certificate	333
ANNEX I:	D2450V2 Dipole Calibration Certificate	341
ANNEX J:	D2600V2 Dipole Calibration Certificate	349

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 5 of 370

ANNEX K: DAE4 Calibration Certificate	357
ANNEX L: The EUT Appearances and Test Configuration	362

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 6 of 370

1. General Information

1.1. Notes of the Test Report

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L2264.

TA Technology (Shanghai) Co., Ltd. guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at TA Technology (Shanghai) Co., Ltd. at the time of execution of the test.

TA Technology (Shanghai) Co., Ltd. is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. The sample under test was selected by the Client. This report only refers to the item that has undergone the test.

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of **TA Technology (Shanghai) Co., Ltd.**

If the electronic report is inconsistent with the printed one, it should be subject to the latter.

1.2. Testing Laboratory

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 7 of 370

1.3. Applicant Information

Company: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District
Shenzhen
518129
P.R.China

1.4. Manufacturer Information

Company: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District
Shenzhen
518129
P.R.China

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 8 of 370

1.5. Information of EUT

General Information

Device Type:	Portable Device	
Exposure Category:	Uncontrolled Environment / General Population	
State of Sample:	Prototype Unit	
Product IMEI:	8666950200148817	
Hardware Version:	HL2UGRACEM	
Software Version:	GRA-L09V100R1001C900B022	
Antenna Type:	Internal Antenna	
Device Operating Configurations :		
Test Mode(s):	GSM 850/GSM 1900; UMTS Band II/UMTS Band IV/UMTS Band V; LTE FDD Band 2/4/5/7/12/17/25/26; 802.11b/g/n HT20/HT40; Bluetooth/Bluetooth 4.1;	
Test Modulation:	(GSM)GMSK; (UMTS)QPSK, (LTE) QPSK, 16QAM; (WiFi)CCK	
Device Class:	B	
HSDPA UE Category:	10	
HSUPA UE Category:	6	
DC-HSDPA UE Category:	24	
HSPA+ UE Downlink Category:	14	
LTE UE Category:	4	
GPRS Multislot Class(12):	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
EGPRS Multislot Class(12):	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
Operating Frequency Range(s):	Mode	Tx (MHz)
	GSM 850	824 - 849
	GSM 1900	1850-1910
	UMTS Band II	1850-1910
	UMTS Band IV	1710–1755
	UMTS Band V	824 - 849
	LTE FDD 2	1850-1910
	LTE FDD 4	1710–1755

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 9 of 370

	LTE FDD 5	824 - 849
	LTE FDD 7	2500-2570
	LTE FDD 12	699-716
	LTE FDD 17	704-716
	LTE FDD 25	1850-1915
	LTE FDD 26	814-849
	Bluetooth/ Bluetooth 4.1	2400-2483.5
	WiFi	2400-2483.5
Power Class:	GSM 850: 4	
	GSM 1900: 1	
	UMTS Band II/IV/V: 3	
	LTE FDD 2/4/5/7/12/17/25/26: 3	
Power Level	GSM 850: level 5	
	GSM 1900: level 0	
	UMTS Band II/IV/V: all up bits	
	LTE FDD 2/4/5/7/12/17/25/26: max power	

Auxiliary Equipment Details

Name	Model	Manufacturer	SN
Battery 1	HB3447A9EBW	Huawei Technologies Co., Ltd.	/
Battery 2	HB3447A9EBW	Huawei Technologies Co., Ltd.	/


TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 10 of 370

1.6. EUT Antenna Locations



Note:

The device has NFC operation. The NFC antenna is integrated onto the Battery cover. The SAR tests were performed with the Battery cover. Phones with built-in NFC functions do not require separate SAR testing and can generally be tested according to the SAR measurement procedures normally required for the phone. Influences of the hardware introduced by the built-in NFC functions are inherently considered through testing of the other transmitters that require SAR.

Exact antenna separation distance are shown in the table

Antenna	Left side to edge (mm)	Right side to edge (mm)	Top side to edge (mm)	Bottom side to edge (mm)
Main Antenna (Antenna 2)	0	0	133.5	0
Diversity Antenna (Antenna 1)	0	33.3	0	141.1
WIFI/BT Antenna	47.1	0	0	141.1

Page 11 of 370

	Mode	Back Side	Front Side	Left Edge	Right Edge	Top Edge	Bottom Edge
Antenna 1	GSM 850	Yes	Yes	Yes	Yes	Yes	N/A
	GSM 1900	Yes	Yes	Yes	Yes	Yes	N/A
	UMTS Band II	Yes	Yes	Yes	Yes	Yes	N/A
	UMTS Band IV	Yes	Yes	Yes	Yes	Yes	N/A
	UMTS Band V	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 2	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 4	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 5	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 7	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 12	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 17	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 25	Yes	Yes	Yes	Yes	Yes	N/A
	LTE FDD 26	Yes	Yes	Yes	Yes	Yes	N/A
Antenna 2	GSM 850	Yes	Yes	Yes	Yes	N/A	Yes
	GSM 1900	Yes	Yes	Yes	Yes	N/A	Yes
	UMTS Band II	Yes	Yes	Yes	Yes	N/A	Yes
	UMTS Band IV	Yes	Yes	Yes	Yes	N/A	Yes
	UMTS Band V	Yes	Yes	Yes	Yes	N/A	Yes
	LTE FDD 2	Yes	Yes	Yes	Yes	N/A	Yes
	LTE FDD 4	Yes	Yes	Yes	Yes	N/A	Yes
	LTE FDD 5	Yes	Yes	Yes	Yes	N/A	Yes
	LTE FDD 7	Yes	Yes	Yes	Yes	N/A	Yes
	LTE FDD 12	Yes	Yes	Yes	Yes	N/A	Yes
	LTE FDD 17	Yes	Yes	Yes	Yes	N/A	Yes
	LTE FDD 25	Yes	Yes	Yes	Yes	N/A	Yes
LTE FDD 26	Yes	Yes	Yes	Yes	N/A	Yes	
WiFi		Yes	Yes	N/A	Yes	Yes	N/A
Note: When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.							

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 12 of 370

1.7. The Maximum Reported SAR_{1g}

Head SAR Configuration

Antenna	Mode	Test Position	Channel /Frequency(MHz)	Limit SAR _{1g} 1.6 W/kg	
				Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
Antenna 1	GSM 850	Right Cheek	128/824.2	1.030	1.282
	GSM 1900	Right Cheek	810/1909.8	0.966	1.148
	UMTS Band II	Right Cheek	9400/1880	0.494	0.609
	UMTS Band IV	Right Cheek	1413/1732.6	0.967	1.168
	UMTS Band V	Left Tilt	4183/836.6	0.645	0.842
	LTE Band 2	Right Cheek	19100/1900	1.090	1.407
	LTE Band 4	Right Cheek	20300/1745	0.937	1.261
	LTE Band 5	Right Cheek	20450/829	0.817	0.938
	LTE Band 7	Right Cheek	21350/2560	0.971	1.347
	LTE Band 12	Right Cheek	23060/704	0.616	0.913
	LTE Band 17	Right Cheek	23790/710	0.519	0.667
	LTE Band 25	Right Cheek	26590/1905	0.875	0.944
	LTE Band 26	Left Tilt	26965/841.5	0.857	0.916
Antenna 2	GSM 850	Right Cheek	190/836.6	0.234	0.281
	GSM 1900	Left Cheek	661/1880	0.364	0.520
	UMTS Band II	Left Cheek	9400/1880	0.551	0.683
	UMTS Band IV	Left Cheek	1413/1732.6	0.788	0.961
	UMTS Band V	Right Cheek	4183/836.6	0.262	0.346
	LTE Band 2	Left Cheek	19100/1900	0.538	0.641
	LTE Band 4	Left Cheek	20175/1732.5	0.636	0.836
	LTE Band 5	Right Cheek	20600/844	0.261	0.294
	LTE Band 7	Left Cheek	21350/2560	0.577	0.769
	LTE Band 12	Right Cheek	23095/707.5	0.046	0.059
	LTE Band 17	Right Cheek	23790/710	0.054	0.067
	LTE Band 25	Left Cheek	26590/1905	0.752	0.817
	LTE Band 26	Right Cheek	26865/831.5	0.207	0.211
WiFi(802.11b)		Left Tilt	1/2412	0.780	0.942

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 13 of 370

Body Worn Configuration

Antenna	Mode	Test Position	Channel /Frequency(MHz)	Limit SAR _{1g} 1.6 W/kg	
				Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
Antenna 1	GSM 850	Front Side	190/836.6	0.096	0.114
	GSM 1900	Front Side	661/1880	0.065	0.091
	UMTS Band II	Back Side	9400/1880	0.078	0.096
	UMTS Band IV	Back Side	1413/1732.6	0.064	0.078
	UMTS Band V	Back Side	4183/836.6	0.056	0.072
	LTE Band 2	Back Side	19100/1900	0.062	0.078
	LTE Band 4	Back Side	20175/1732.5	0.058	0.076
	LTE Band 5	Front Side	20600/844	0.048	0.054
	LTE Band 7	Front Side	21350/2560	0.057	0.076
	LTE Band 12	Back Side	23095/707.5	0.029	0.037
	LTE Band 17	Front Side	23790/710	0.078	0.100
	LTE Band 25	Front Side	26590/1905	0.070	0.076
	LTE Band 26	Front Side	26865/831.5	0.157	0.179
Antenna 2	GSM 850	Back Side	190/836.6	0.340	0.409
	GSM 1900	Back Side	810/1909.8	1.030	1.233
	UMTS Band II	Back Side	9262/1852.4	0.759	1.017
	UMTS Band IV	Back Side	1413/1732.6	0.446	0.544
	UMTS Band V	Back Side	4183/836.6	0.128	0.169
	LTE Band 2	Back Side	19100/1900	0.793	1.005
	LTE Band 4	Back Side	20175/1732.5	0.416	0.547
	LTE Band 5	Back Side	20600/844	0.138	0.156
	LTE Band 7	Front Side	21350/2560	0.326	0.435
	LTE Band 12	Back Side	23095/707.5	0.069	0.088
	LTE Band 17	Back Side	23790/710	0.053	0.066
	LTE Band 25	Back Side	26590/1905	0.415	0.451
	LTE Band 26	Back Side	26865/831.5	0.126	0.128
WiFi(802.11b)		Back Side	1/2412	0.078	0.094

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 14 of 370

Hotspot Configuration

Antenna	Mode	Test Position	Channel /Frequency(MHz)	Limit SAR _{1g} 1.6 W/kg	
				Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
Antenna 1	GSM 850	Front Side	190/836.6	0.211	0.217
	GSM 1900	Left Edge	661/1880	0.200	0.237
	UMTS Band II	Left Edge	9400/1880	0.178	0.219
	UMTS Band IV	Left Edge	1413/1732.6	0.198	0.239
	UMTS Band V	Top Edge	4183/836.6	0.165	0.216
	LTE Band 2	Left Edge	19100/1900	0.186	0.234
	LTE Band 4	Left Edge	20175/1732.5	0.153	0.200
	LTE Band 5	Top Edge	20600/844	0.177	0.198
	LTE Band 7	Left Edge	20850/2510	0.221	0.280
	LTE Band 12	Back Side	23095/707.5	0.053	0.068
	LTE Band 17	Back Side	23790/710	0.164	0.211
	LTE Band 25	Left Edge	26590/1905	0.176	0.190
	LTE Band 26	Front Side	26865/831.5	0.310	0.314
Antenna 2	GSM 850	Back Side	190/836.6	0.415	0.431
	GSM 1900	Back Side	810/1909.8	1.200	1.257
	UMTS Band II	Bottom Edge	9262/1852.4	0.949	1.423
	UMTS Band IV	Bottom Edge	1513/1752.6	1.100	1.360
	UMTS Band V	Back Side	4183/836.6	0.281	0.370
	LTE Band 2	Back Side	19100/1900	0.711	0.901
	LTE Band 4	Back Side	20175/1732.5	0.654	0.866
	LTE Band 5	Back Side	20600/844	0.316	0.356
	LTE Band 7	Front Side	21350/2560	0.399	0.479
	LTE Band 12	Back Side	23095/707.5	0.114	0.147
	LTE Band 17	Right Edge	23790/710	0.106	0.137
	LTE Band 25	Back Side	26590/1905	1.050	1.280
	LTE Band 26	Back Side	26865/831.5	0.249	0.281
WiFi(802.11b)		Back Side	1/2412	0.152	0.184

1.8. Test Date

The test performed from March 9, 2015 to March 30, 2015.

2. SAR Measurements System Configuration

2.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- A unit to operate the optical surface detector which is connected to the EOC.
- The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
- The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003
- DASY5 software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- System validation dipoles allowing to validate the proper functioning of the system.




Figure 1 SAR Lab Test Measurement Set-up

2.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4(manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

2.2.1. EX3DV4 Probe Specification

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



Figure 2.EX3DV4 E-field Probe



Figure 3. EX3DV4 E-field probe

2.2.2. E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),
 C = Heat capacity of tissue (brain or muscle),
 ΔT = Temperature increase due to RF exposure.
Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:
 σ = Simulated tissue conductivity,
 ρ = Tissue density (kg/m^3).

2.3. Other Test Equipment

2.3.1. Device Holder for Transmitters

The DASY device holder is designed to cope with the different positions given in the standard.

It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Figure 4 Device Holder

2.3.2. Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden Figure. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness	2±0.1 mm
Filling Volume	Approx. 20 liters
Dimensions	810 x 1000 x 500 mm (H x L x W) Available Special



Figure 5 Generic Twin Phantom

2.4. Scanning Procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

- The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. $\pm 5\%$.
- The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)
- Area Scan
The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 19 of 370

spacing is set according to FCC KDB Publication 865664. During scan the distance of the probe to the phantom remains unchanged.

After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

- Zoom Scan

After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm.

- Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation.

- A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

Table 1: Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01

Frequency	Maximum Area Scan Resolution (mm) (Δx_{area} , Δy_{area})	Maximum Zoom Scan Resolution (mm) (Δx_{zoom} , Δy_{zoom})	Maximum Zoom Scan Spatial Resolution (mm) $\Delta z_{\text{zoom}}(n)$	Minimum Zoom Scan Volume (mm) (x,y,z)
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≥ 22

2.5. Data Storage and Evaluation

2.5.1. Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “.DAE4”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

2.5.2. Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Norm _i , a _{i0} , a _{i1} , a _{i2}
	- Conversion factor	ConvF _i
	- Diode compression point	Dcp _i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	
	- Density	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 21 of 370

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c f / d c p_i$$

With V_i = compensated signal of channel i (i = x, y, z)

U_i = input signal of channel i (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp_i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: $E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$

H-field probes: $H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1} f + a_{i2} f^2) / f$

With V_i = compensated signal of channel i (i = x, y, z)

$Norm_i$ = sensor sensitivity of channel i (i = x, y, z)
[mV/(V/m)²] for E-field Probes

$ConvF$ = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot})^2 \cdot \sigma / (\rho \cdot 1000)$$

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 22 of 370

with **SAR** = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with **P_{pwe}** = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

3. Laboratory Environment

Table 2: The Requirements of the Ambient Conditions

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards.	
Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 23 of 370

4. Tissue-equivalent Liquid

4.1. Tissue-equivalent Liquid Ingredients

The liquid is consisted of water, salt, Glycol, Sugar, Preventol and Cellulose. The liquid has previously been proven to be suited for worst-case. The table 3 and table 4 show the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB 865664 D01.

Table 3: Composition of the Head Tissue Equivalent Matter

MIXTURE%	FREQUENCY(Brain) 750MHz
Water	41.448
Sugar	56
Salt	1.452
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	f=750MHz $\epsilon=41.9$ $\sigma=0.89$

MIXTURE%	FREQUENCY(Brain) 835MHz
Water	41.45
Sugar	56
Salt	1.45
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	f=835MHz $\epsilon=41.5$ $\sigma=0.9$

MIXTURE%	FREQUENCY(Brain) 1750MHz
Water	55.24
Glycol	44.45
Salt	0.31
Dielectric Parameters Target Value	f=1750MHz $\epsilon=40.1$ $\sigma=1.37$

MIXTURE%	FREQUENCY(Brain) 1900MHz
Water	55.242
Glycol monobutyl	44.452
Salt	0.306
Dielectric Parameters Target Value	f=1900MHz $\epsilon=40.0$ $\sigma=1.40$

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 24 of 370

MIXTURE%	FREQUENCY(Brain) 2450MHz
Water	62.7
Glycol	36.8
Salt	0.5
Dielectric Parameters Target Value	f=2450MHz $\epsilon=39.2$ $\sigma=1.80$

MIXTURE%	FREQUENCY(Brain) 2600MHz
Water	55.242
Glycol	44.452
Salt	0.306
Dielectric Parameters Target Value	f=2600MHz $\epsilon=39.0$ $\sigma=1.96$

Table 4: Composition of the Body Tissue Equivalent Matter

MIXTURE%	FREQUENCY(Body) 750MHz
Water	52.49
Sugar	45
Salt	1.41
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	f=750MHz $\epsilon=55.5$ $\sigma=0.96$

MIXTURE%	FREQUENCY(Body) 835MHz
Water	52.5
Sugar	45
Salt	1.4
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	f=835MHz $\epsilon=55.2$ $\sigma=0.97$

MIXTURE%	FREQUENCY(Body) 1750MHz
Water	69.91
Glycol	29.97
Salt	0.12
Dielectric Parameters Target Value	f=1750MHz $\epsilon=53.4$ $\sigma=1.49$

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 25 of 370

MIXTURE%	FREQUENCY (Body) 1900MHz
Water	69.91
Glycol monobutyl	29.96
Salt	0.13
Dielectric Parameters Target Value	f=1900MHz $\epsilon=53.3$ $\sigma=1.52$

MIXTURE%	FREQUENCY(Body) 2450MHz
Water	73.2
Glycol	26.7
Salt	0.1
Dielectric Parameters Target Value	f=2450MHz $\epsilon=52.7$ $\sigma=1.95$

MIXTURE%	FREQUENCY (Body) 2600MHz
Water	72.6
Glycol monobutyl	27.3
Salt	0.1
Dielectric Parameters Target Value	f=2600MHz $\epsilon=52.5$ $\sigma=2.16$

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 26 of 370

4.2. Tissue-equivalent Liquid Properties

Table 5: Dielectric Performance of Tissue Simulating Liquid

Frequency	Test Date	Temp ℃	Measured Dielectric Parameters		Target Dielectric Parameters		Limit (Within ±5%)	
			ϵ_r	$\sigma(\text{s/m})$	ϵ_r	$\sigma(\text{s/m})$	Dev $\epsilon_r(\%)$	Dev $\sigma(\%)$
750MHz (head)	2015-3-15	21.5	42.0	0.91	41.9	0.89	0.24	2.25
835MHz (head)	2015-3-11	21.5	41.4	0.93	41.5	0.90	-0.24	3.33
	2015-3-28	21.5	41.5	0.91	41.5	0.90	0.00	1.11
1750MHz (head)	2015-3-12	21.5	39.7	1.32	40.1	1.37	-1.00	-3.65
1900MHz (head)	2015-3-17	21.5	39.6	1.43	40.0	1.40	-1.00	2.14
	2015-3-27	21.5	39.7	1.40	40.0	1.40	-0.75	0.00
2450MHz (head)	2015-3-25	21.5	38.6	1.81	39.2	1.80	-1.53	0.56
2600MHz (head)	2015-3-9	21.5	38.6	1.98	39.0	1.96	-1.03	1.02
750MHz (body)	2015-3-13	21.5	54.3	0.97	55.5	0.96	-2.16	1.04
	2015-3-14	21.5	54.5	0.96	55.5	0.96	-1.80	0.00
835MHz (body)	2015-3-10	21.5	55.9	0.99	55.2	0.97	1.27	2.06
	2015-3-18	21.5	56.1	0.97	55.2	0.97	1.63	0.00
	2015-3-19	21.5	56.2	0.97	55.2	0.97	1.81	0.00
1750MHz (body)	2015-3-23	21.5	52.9	1.47	53.4	1.49	-0.94	-1.34
	2015-3-30	21.5	53.1	1.45	53.4	1.49	-0.56	-2.68
1900MHz (body)	2015-3-24	21.5	52.5	1.52	53.3	1.52	-1.50	0.00
	2015-3-21	21.5	52.5	1.51	53.3	1.52	-1.50	-0.66
	2015-3-26	21.5	52.7	1.49	53.3	1.52	-1.13	-1.97
2450MHz (body)	2015-3-25	21.5	52.1	1.99	52.7	1.95	-1.14	2.05
2600MHz (body)	2015-3-9	21.5	52.3	2.20	52.5	2.16	-0.38	1.85

5. System Check

5.1. Description of System Check

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulates were measured every day using the dielectric probe kit and the network analyzer. A system check measurement was made following the determination of the dielectric parameters of the simulates, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system check results (dielectric parameters and SAR values) are given in the table 6 and table 7.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.




Figure 6 System Check Set-up

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 28 of 370

Justification for Extended SAR Dipole Calibrations

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (< -20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB 865664 D01:

Dipole D1750V2 SN: 1033				
Head Liquid				
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)	$\Delta\Omega$
1/26/2014	-41.9	/	50.5	/
1/25/2015	-40.6	3.1%	52.4	1.9 Ω
Body Liquid				
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)	$\Delta\Omega$
1/26/2014	-24.3	/	45.8	/
1/25/2015	-23.5	3.3%	48.5	2.7 Ω

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 29 of 370

5.2. System Check Results

Table 6: System Check in Head Tissue Simulating Liquid

Frequency	Test Date	Dielectric Parameters		250mW Measured SAR _{1g}	1W Normalized SAR _{1g}	1W Target SAR _{1g}	Limit (±10% Deviation)
		ε _r	σ(s/m)	(W/kg)			
750MHz	2015-3-15	42.0	0.91	2.13	8.52	8.31	2.53
835MHz	2015-3-11	41.4	0.93	2.44	9.76	9.54	2.31
	2015-3-28	41.5	0.91	2.46	9.84	9.54	3.14
1750MHz	2015-3-12	39.7	1.32	8.95	35.80	37.20	-3.76
1900MHz	2015-3-17	39.6	1.43	9.48	37.92	39.20	-3.27
	2015-3-27	39.7	1.40	9.59	38.36	39.20	-2.14
2450MHz	2015-3-25	38.6	1.81	13.70	54.80	52.50	4.38
2600MHz	2015-3-9	38.6	1.98	13.90	55.60	56.90	-2.28
Note: 1. The graph results see ANNEX B. 2. Target Values used derive from the calibration certificate							

Table 7: System Check in Body Tissue Simulating Liquid

Frequency	Test Date	Dielectric Parameters		250mW Measured SAR _{1g}	1W Normalized SAR _{1g}	1W Target SAR _{1g}	Limit (±10% Deviation)
		ε _r	σ(s/m)	(W/kg)			
750MHz	2015-3-13	54.3	0.97	2.22	8.88	8.75	1.49
	2015-3-14	54.5	0.96	2.17	8.68	8.75	-0.80
835MHz	2015-3-10	55.9	0.99	2.41	9.64	9.54	1.05
	2015-3-18	56.1	0.97	2.46	9.84	9.54	3.14
	2015-3-19	56.2	0.97	2.49	9.96	9.54	4.40
1750MHz	2015-3-23	52.9	1.47	9.24	36.96	38.80	-4.74
	2015-3-30	53.1	1.45	9.27	37.08	38.80	-4.43
1900MHz	2015-3-24	52.5	1.52	9.93	39.72	40.00	-0.70
	2015-3-21	52.5	1.51	9.82	39.28	40.00	-1.80
	2015-3-26	52.7	1.49	9.83	39.32	40.00	-1.70

TA Technology (Shanghai) Co., Ltd. Test Report

Report No.: RHA1502-0012SAR02R1

Page 30 of 370

2450MHz	2015-3-25	52.1	1.99	12.50	50.00	52.40	-4.58
2600MHz	2015-3-9	52.3	2.20	13.50	54.00	56.40	-4.26
Note: 1. The graph results see ANNEX B. 2. Target Values used derive from the calibration certificate							

6. Operational Conditions during Test

6.1. General Description of Test Procedures

A communication link is set up with a System Simulator (SS) by air link, and a call is established. The EUT is commanded to operate at maximum transmitting power.

Connection to the EUT is established via air interface with CMW 500, and the EUT is set to maximum output power by CMW 500. The EUT battery must be fully charged and checked periodically during the test to as certain uniform power output. The antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the EUT. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the EUT by at least 30 dB.

6.2. Test Positions

6.2.1. Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

6.2.2. Body Worn Configuration

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations.

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. Per FCC KDB Publication 648474 D04, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 32 of 370

multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.3. Measurement Variability

Per FCC KDB Publication 865664 D01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 34 of 370

6.4. Power Reduction

Antenna 1

Config.	Mode	GSM 850	GSM 1900	UMT S B2	UMT S B4	UMT S B5	LTE B2	LTE B4	LTE B5	LTE B7	LTE B25	LTE B26	LTE B12	LTE B17
Power Reduction (dB)	WiFi off	0	0	0	0	0	0	0	0	0	0	0	0	0
	WiFi on	2.5	1	4	3	3.5	4.5	3	4.5	5.5	5	4.5	4.5	4.5

Antenna 2

Config.	Mode	GSM 850	GSM 1900	UMT S B2	UMT S B4	UMT S B5	LTE B2	LTE B4	LTE B5	LTE B7	LTE B25	LTE B26	LTE B12	LTE B17
Power Reduction (dB)	Hotspot off	0	0	0	0	0	0	0	0	0	0	0	0	0
	Hotspot on	0	1	2.5	1.5	0	4.5	1	0	0.5	4	0	0	0

Note: The device uses a single fixed level of power reduction through static table look-up for SAR compliance and it is triggered by a single event or operation:

- 1) A fixed level power reduction is applied for some frequency bands when hotspot mode becomes active. When the hotspot is disabled, the power value will be recovered.
- 2) A fixed level power reduction is applied for some frequency bands when simultaneously transmitting with WiFi antenna. The standalone SAR compliance still uses the standalone SAR results tested at the maximum output power level without any power reduction.

Tune up

Antenna 1(Wi-Fi off)

GSM/GPRS850 (GMSK) :

1TXslot:32.5 dBm [-1dB~~+0.8dB]

2TXslot:29.5 dBm [-2.0dB~~+1.0dB]

3TXslot:28 dBm [-2.0dB~~+1.0dB]

4TXslot:26.5 dBm [-2.0dB~~+1.0dB]

EDGE850 (8PSK) :

1TXslot: 26.5 dBm [-2dB~~+1.0dB]

2TXslot: 24.5 dBm [-2.0dB~~+1dB]

3TXslot: 22.5 dBm [-2.5dB~~+1.0dB]

4TXslot: 20.5 dBm [-2.5dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 35 of 370

EDGE850 (GMSK) :

1TXslot:32.5 dBm [-1dB~~+1dB]

2TXslot:29.5 dBm [-2dB~~+1dB]

3TXslot:28 dBm [-2dB~~+1dB]

4TXslot:26.5 dBm [-2dB~~+1dB]

PCS/GPRS1900 (GMSK) :

1TXslot:29.5 dBm [-1dB~~+1dB]

2TXslot:26.5 dBm [-2dB~~+1.0dB]

3TXslot:25 dBm [-2dB~~+1dB]

4TXslot:23.5 dBm [-2dB~~+1.0dB]

EDGE1900 (8PSK) :

1TXslot: 25.5 dBm [-2.0dB~~+1dB]

2TXslot: 23.5 dBm [-2.0dB~~+1dB]

3TXslot:21.5 dBm [-2.5dB~~+1dB]

4TXslot: 19.5 dBm [-2.5dB~~+1dB]

EDGE1900 (GMSK) :

1TXslot:29.5 dBm [-1dB~~+1dB]

2TXslot:26.5 dBm [-2dB~~+1.0dB]

3TXslot:25 dBm [-2dB~~+1dB]

4TXslot:23.5 dBm [-2dB~~+1.0dB]

WCDMA Band II

Output power of range:

WCDMA: 23 dBm [-1dB~~+1dB]

HSDPA:

case1: 22.5dBm [-2dB~~+1dB]

case2: 21 dBm [-2dB~~+1dB]

case3: 20.5 dBm [-2dB~~+1dB]

case4: 20.5 dBm [-2dB~~+1dB]

HSUPA:

case1:20.5dBm [-2dB~~+1dB]

case2:19 dBm [-2dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 36 of 370

case3:21.5 dBm [-2dB~~+1dB]

case4:19 dBm [-2dB~~+1dB]

case5: 22dBm [-2dB~~+1dB]

WCDMA Band IV

Output power of range:

WCDMA: 23.5 dBm [-1dB~~+1dB]

HSDPA:

case1: 22.5dBm [-2dB~~+1dB]

case2: 21 dBm [-2dB~~+1dB]

case3: 21.5 dBm [-2dB~~+1dB]

case4: 21.5 dBm [-2dB~~+1dB]

HSUPA:

case1:20.5dBm [-2dB~~+1dB]

case2:19 dBm [-2dB~~+1dB]

case3:21.5 dBm [-2dB~~+1dB]

case4:19 dBm [-2dB~~+1dB]

case5: 22dBm [-2dB~~+1dB]

WCDMA Band V

Output power of range:

WCDMA: 23.5 dBm [-1dB~~+1dB]

HSDPA:

case1: 22.5dBm [-2dB~~+1dB]

case2: 22 dBm [-2dB~~+1dB]

case3: 21.5 dBm [-2dB~~+1dB]

case4: 21.5 dBm [-2dB~~+1dB]

HSUPA:

case1:21dBm [-2dB~~+1dB]

case2:20 dBm [-2dB~~+1dB]

case3:21.5 dBm [-2dB~~+1dB]

case4:20 dBm [-2dB~~+1dB]

case5: 22dBm [-2dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 37 of 370

LTE Band II

LTE_B2	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	22.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	22.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	21.5+1/-2.5 dB
16 QAM	1	1	1	1	1	1	21.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	21.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	20.5+1/-2.5 dB

LTE Band 4

Output power of range:

LTE_B4	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	22.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	22.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	21.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	21.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	20.5+1/-2.5 dB

LTE Band 5

LTE_B5	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 7

LTE_B7	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
			5 MHz	10 MHz	15 MHz	20 MHz	
QPSK			1	1	1	1	23+1/-2.5 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 38 of 370

QPSK			≤ 8	≤ 12	≤ 16	≤ 18	23+1/-2.5 dB
QPSK			> 8	> 12	> 16	> 18	22+1/-2.5 dB
16 QAM			1	1	1	1	22+1/-2.5 dB
16 QAM			≤ 8	≤ 12	≤ 16	≤ 18	22+1/-2.5 dB
16 QAM			> 8	> 12	> 16	> 18	21+1/-2.5 dB

LTE Band 12

LTE_B12	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 17

LTE_B17	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 25

LTE_B25	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	22.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	22.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	21.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	21.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	20.5+1/-2.5 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 39 of 370

LTE Band 26

LTE_B26	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz		
QPSK	1	1	1	1	1		23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16		22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16		21+1/-2.5 dB

Antenna 1(Wi-Fi on)

GSM/GPRS850 (GMSK) :

1TXslot:30 dBm [-1dB~~+0.8dB]

2TXslot:27 dBm [-2.0dB~~+1.0dB]

3TXslot:25.5 dBm [-2.0dB~~+1.0dB]

4TXslot:24 dBm [-2.0dB~~+1.0dB]

EDGE850 (8PSK) :

1TXslot: 24 dBm [-2dB~~+1.0dB]

2TXslot: 22 dBm [-2.0dB~~+1dB]

3TXslot: 20 dBm [-2.5dB~~+1.0dB]

4TXslot: 18 dBm [-2.5dB~~+1dB]

EDGE850 (GMSK) :

1TXslot:30 dBm [-1dB~~+1dB]

2TXslot:27 dBm [-2dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 40 of 370

3TXslot:25.5 dBm [-2dB~~+1dB]

4TXslot:24 dBm [-2dB~~+1dB]

PCS/GPRS1900 (GMSK) :

1TXslot:28.5 dBm [-1dB~~+1dB]

2TXslot:25.5 dBm [-2dB~~+1dB]

3TXslot:24.5 dBm [-2dB~~+1dB]

4TXslot:22.5 dBm [-2dB~~+1dB]

EDGE1900 (8PSK) :

1TXslot: 24.5 dBm [-2.0dB~~+1dB]

2TXslot: 22.5 dBm [-2.0dB~~+1dB]

3TXslot:20.5 dBm [-2.5dB~~+1dB]

4TXslot: 18.5 dBm [-2.5dB~~+1dB]

EDGE1900 (GMSK) :

1TXslot:28.5 dBm [-1dB~~+1dB]

2TXslot:25.5 dBm [-2dB~~+1.0dB]

3TXslot:24 dBm [-2dB~~+1dB]

4TXslot:22.5 dBm [-2dB~~+1.0dB]

WCDMA Band II

WCDMA: 19 dBm [-1dB~~+1dB]

HSDPA:

case1: 18.5dBm [-2dB~~+1dB]

case2: 17 dBm [-2dB~~+1dB]

case3: 16.5 dBm [-2dB~~+1dB]

case4: 16.5 dBm [-2dB~~+1dB]

HSUPA:

case1:16.5dBm [-2dB~~+1dB]

case2:15 dBm [-2dB~~+1dB]

case3:17.5 dBm [-2dB~~+1dB]

case4:15 dBm [-2dB~~+1dB]

case5: 18 dBm [-2dB~~+1dB]

WCDMA Band IV

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 41 of 370

WCDMA: 20.5 dBm [-1dB~~+1dB]

HSDPA:

case1: 19.5dBm [-2dB~~+1dB]

case2: 18 dBm [-2dB~~+1dB]

case3: 18.5 dBm [-2dB~~+1dB]

case4: 18.5 dBm [-2dB~~+1dB]

HSUPA:

case1:17.5dBm [-2dB~~+1dB]

case2:16 dBm [-2dB~~+1dB]

case3:19.5 dBm [-2dB~~+1dB]

case4:16 dBm [-2dB~~+1dB]

case5: 19 dBm [-2dB~~+1dB]

WCDMA Band V

WCDMA: 20 dBm [-1dB~~+1dB]

HSDPA:

case1: 19 dBm [-2dB~~+1dB]

case2: 18.5 dBm [-2dB~~+1dB]

case3: 18 dBm [-2dB~~+1dB]

case4: 18 dBm [-2dB~~+1dB]

HSUPA:

case1:17.5 dBm [-2dB~~+1dB]

case2:16.5 dBm [-2dB~~+1dB]

case3:18 dBm [-2dB~~+1dB]

case4:16.5 dBm [-2dB~~+1dB]

case5: 18.5 dBm [-2dB~~+1dB]

LTE Band 2

LTE_B2	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	18+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	18+1/-2.5 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 42 of 370

QPSK	> 5	> 4	> 8	> 12	> 16	> 18	17+1/-2.5 dB
16 QAM	1	1	1	1	1	1	17+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	17+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	16+1/-2.5 dB

LTE Band 4

LTE_B4	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	19.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	19.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	18.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	18.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	17.5+1/-2.5 dB

LTE Band 5

LTE_B5	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			18.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			18.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			17.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			17.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			16.5+1/-2.5 dB

LTE Band 7

LTE_B7	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
			5 MHz	10 MHz	15 MHz	20 MHz	
QPSK			1	1	1	1	17.5+1/-2.5 dB
QPSK			≤ 8	≤ 12	≤ 16	≤ 18	17.5+1/-2.5 dB
QPSK			> 8	> 12	> 16	> 18	16.5+1/-2.5 dB
16 QAM			1	1	1	1	16.5+1/-2.5 dB
16 QAM			≤ 8	≤ 12	≤ 16	≤ 18	16.5+1/-2.5 dB
16 QAM			> 8	> 12	> 16	> 18	15.5+1/-2.5 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 43 of 370

LTE Band 12

LTE_B12	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			18.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			18.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			17.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			17.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			16.5+1/-2.5 dB

LTE Band 17

LTE_B17	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			18.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			18.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			17.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			17.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			16.5+1/-2.5 dB

LTE Band 25

LTE_B25	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	17.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	17.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	16.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	16.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	15.5+1/-2.5 dB

LTE Band 26

LTE_B26	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4	3	5	10	15		

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 44 of 370

	MHz	MHz	MHz	MHz	MHz		
QPSK	1	1	1	1	1		18.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		18.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16		17.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		17.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16		16.5+1/-2.5 dB

Antenna 2(Hotspot off)

GSM/GPRS850 (GMSK) :

1TXslot:32.5 dBm [-1dB~~+0.8dB]

2TXslot:29.5 dBm [-2.0dB~~+1.0dB]

3TXslot:28 dBm [-2.0dB~~+1.0dB]

4TXslot:26.5 dBm [-2.0dB~~+1.0dB]

EDGE850 (8PSK) :

1TXslot: 26.5 dBm [-2dB~~+1.0dB]

2TXslot: 24.5 dBm [-2.0dB~~+1dB]

3TXslot: 22.5 dBm [-2.5dB~~+1.0dB]

4TXslot: 20.5 dBm [-2.5dB~~+1dB]

EDGE850 (GMSK) :

1TXslot:32.5 dBm [-1dB~~+1dB]

2TXslot:29.5 dBm [-2dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 45 of 370

3TXslot:28 dBm [-2dB~~+1dB]

4TXslot:26.5 dBm [-2dB~~+1dB]

PCS/GPRS1900 (GMSK) :

1TXslot:29.5 dBm [-1dB~~+1dB]

2TXslot:26.5 dBm [-2dB~~+1.0dB]

3TXslot:25 dBm [-2dB~~+1dB]

4TXslot:23.5 dBm [-2dB~~+1.0dB]

EDGE1900 (8PSK) :

1TXslot: 25.5 dBm [-2.0dB~~+1dB]

2TXslot: 23.5 dBm [-2.0dB~~+1dB]

3TXslot:21.5 dBm [-2.5dB~~+1dB]

4TXslot: 19.5 dBm [-2.5dB~~+1dB]

EDGE1900 (GMSK) :

1TXslot:29.5 dBm [-1dB~~+1dB]

2TXslot:26.5 dBm [-2dB~~+1.0dB]

3TXslot:25 dBm [-2dB~~+1dB]

4TXslot:23.5 dBm [-2dB~~+1.0dB]

WCDMA Band II

WCDMA: 23 dBm [-1dB~~+1dB]

HSDPA:

case1: 22.5dBm [-2dB~~+1dB]

case2: 21 dBm [-2dB~~+1dB]

case3: 20.5 dBm [-2dB~~+1dB]

case4: 20.5 dBm [-2dB~~+1dB]

HSUPA:

case1:20.5dBm [-2dB~~+1dB]

case2:19 dBm [-2dB~~+1dB]

case3:21.5 dBm [-2dB~~+1dB]

case4:19 dBm [-2dB~~+1dB]

case5: 22dBm [-2dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 46 of 370

WCDMA Band IV

WCDMA: 23.5 dBm [-1dB~~+1dB]

HSDPA:

case1: 22.5dBm [-2dB~~+1dB]

case2: 21 dBm [-2dB~~+1dB]

case3: 21.5 dBm [-2dB~~+1dB]

case4: 21.5 dBm [-2dB~~+1dB]

HSUPA:

case1:20.5dBm [-2dB~~+1dB]

case2:19 dBm [-2dB~~+1dB]

case3:21.5 dBm [-2dB~~+1dB]

case4:19 dBm [-2dB~~+1dB]

case5: 22dBm [-2dB~~+1dB]

WCDMA Band V

WCDMA: 23.5 dBm [-1dB~~+1dB]

HSDPA:

case1: 22.5dBm [-2dB~~+1dB]

case2: 22 dBm [-2dB~~+1dB]

case3: 21.5 dBm [-2dB~~+1dB]

case4: 21.5 dBm [-2dB~~+1dB]

HSUPA:

case1:21dBm [-2dB~~+1dB]

case2:20 dBm [-2dB~~+1dB]

case3:21.5 dBm [-2dB~~+1dB]

case4:20 dBm [-2dB~~+1dB]

case5: 22dBm [-2dB~~+1dB]

LTE Band 2

LTE_B2	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 47 of 370

QPSK	1	1	1	1	1	1	22.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	22.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	21.5+1/-2.5 dB
16 QAM	1	1	1	1	1	1	21.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	21.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	20.5+1/-2.5 dB

LTE Band 4

LTE_B4	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	22.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	22.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	21.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	21.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	20.5+1/-2.5 dB

LTE Band 5

LTE_B5	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 7

LTE_B7	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
			5 MHz	10 MHz	15 MHz	20 MHz	
QPSK			1	1	1	1	23+1/-2.5 dB
QPSK			≤ 8	≤ 12	≤ 16	≤ 18	23+1/-2.5 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 48 of 370

QPSK			> 8	> 12	> 16	> 18	22+1/-2.5 dB
16 QAM			1	1	1	1	22+1/-2.5 dB
16 QAM			≤ 8	≤ 12	≤ 16	≤ 18	22+1/-2.5 dB
16 QAM			> 8	> 12	> 16	> 18	21+1/-2.5 dB

LTE Band 12

LTE_B12	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 17

LTE_B17	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 25

LTE_B25	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	22.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	22.5+1/-2.5 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 49 of 370

QPSK	> 5	> 4	> 8	> 12	> 16	> 18	21.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	21.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	20.5+1/-2.5 dB

LTE Band 26

LTE_B26	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz		
QPSK	1	1	1	1	1		23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16		22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16		21+1/-2.5 dB

Bluetooth

BT Average Power: ≤10dBm

WiFi

WiFi Average Power:

802.11b: 15dBm [-1.5dB~~+1.0dB]

802.11g: 14dBm [-1.5dB~~+1.0dB]

802.11n: 12dBm[-1.5dB~~+1.0dB]

Antenna 2(Hotspot on)

GSM/GPRS850 (GMSK) :

1TXslot:32.5 dBm [-1dB~~+0.8dB]

2TXslot:29.5 dBm [-2.0dB~~+1.0dB]

3TXslot:28 dBm [-2.0dB~~+1.0dB]

4TXslot:26.5 dBm [-2.0dB~~+1.0dB]

EDGE850 (8PSK) :

1TXslot: 26.5 dBm [-2dB~~+1.0dB]

2TXslot: 24.5 dBm [-2.0dB~~+1dB]

3TXslot: 22.5 dBm [-2.5dB~~+1.0dB]

4TXslot: 20.5 dBm [-2.5dB~~+1dB]

EDGE850 (GMSK) :

1TXslot:32.5 dBm [-1dB~~+1dB]

2TXslot:29.5 dBm [-2dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 50 of 370

3TXslot:28 dBm [-2dB~~+1dB]

4TXslot:26.5 dBm [-2dB~~+1dB]

PCS/GPRS1900 (GMSK) :

1TXslot:28.5 dBm [-1dB~~+1dB]

2TXslot:25.5 dBm [-2dB~~+1dB]

3TXslot:24.5 dBm [-2dB~~+1dB]

4TXslot:22.5 dBm [-2dB~~+1dB]

EDGE1900 (8PSK) :

1TXslot: 24.5 dBm [-2.0dB~~+1dB]

2TXslot: 22.5 dBm [-2.0dB~~+1dB]

3TXslot:20.5 dBm [-2.5dB~~+1dB]

4TXslot: 18.5 dBm [-2.5dB~~+1dB]

EDGE1900 (GMSK) :

1TXslot:28.5 dBm [-1dB~~+1dB]

2TXslot:25.5 dBm [-2dB~~+1.0dB]

3TXslot:24 dBm [-2dB~~+1dB]

4TXslot:22.5 dBm [-2dB~~+1.0dB]

WCDMA Band II

WCDMA: 21 dBm [-1dB~~+1dB]

HSDPA:

case1: 20dBm [-2dB~~+1dB]

case2: 18.5 dBm [-2dB~~+1dB]

case3: 18 dBm [-2dB~~+1dB]

case4: 18 dBm [-2dB~~+1dB]

HSUPA:

case1:18dBm [-2dB~~+1dB]

case2:16.5 dBm [-2dB~~+1dB]

case3:19 dBm [-2dB~~+1dB]

case4:16.5 dBm [-2dB~~+1dB]

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 51 of 370

case5: 19.5dBm [-2dB~~+1dB]

WCDMA Band IV

WCDMA: 22 dBm [-1dB~~+1dB]

HSDPA:

case1: 21dBm [-2dB~~+1dB]

case2: 19.5 dBm [-2dB~~+1dB]

case3: 20 dBm [-2dB~~+1dB]

case4: 20 dBm [-2dB~~+1dB]

HSUPA:

case1:19dBm [-2dB~~+1dB]

case2:17.5 dBm [-2dB~~+1dB]

case3:20 dBm [-2dB~~+1dB]

case4:17.5 dBm [-2dB~~+1dB]

case5: 20.5dBm [-2dB~~+1dB]

WCDMA Band V

WCDMA: 23.5 dBm [-1dB~~+1dB]

HSDPA:

case1: 22.5dBm [-2dB~~+1dB]

case2: 22 dBm [-2dB~~+1dB]

case3: 21.5 dBm [-2dB~~+1dB]

case4: 21.5 dBm [-2dB~~+1dB]

HSUPA:

case1:21dBm [-2dB~~+1dB]

case2:20 dBm [-2dB~~+1dB]

case3:21.5 dBm [-2dB~~+1dB]

case4:20 dBm [-2dB~~+1dB]

case5: 22dBm [-2dB~~+1dB]

LTE Band 2

LTE_B2	Channel bandwidth / Transmission bandwidth	Power (dBm)
--------	--	-------------

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 52 of 370

	configuration [RB]						
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	18+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	18+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	17+1/-2.5 dB
16 QAM	1	1	1	1	1	1	17+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	17+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	16+1/-2.5 dB

LTE Band 4

LTE_B4	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	21.5+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	21.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	20.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	20.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	19.5+1/-2.5 dB

LTE Band 5

LTE_B5	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 7

LTE_B7	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
			5	10	15	20	

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 53 of 370

			MHz	MHz	MHz	MHz	
QPSK			1	1	1	1	22+1/-2.5 dB
QPSK			≤ 8	≤ 12	≤ 16	≤ 18	22+1/-2.5 dB
QPSK			> 8	> 12	> 16	> 18	21+1/-2.5 dB
16 QAM			1	1	1	1	21+1/-2.5 dB
16 QAM			≤ 8	≤ 12	≤ 16	≤ 18	21+1/-2.5 dB
16 QAM			> 8	> 12	> 16	> 18	20+1/-2.5 dB

LTE Band 12

LTE_B12	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 17

LTE_B17	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz			
QPSK	1	1	1	1			23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12			23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12			22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12			22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12			21+1/-2.5 dB

LTE Band 25

LTE_B25	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	1	1	1	1	1	1	18.5+1/-2.5 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 54 of 370

QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	18.5+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	17.5+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	17.5+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	16.5+1/-2.5 dB

LTE Band 26

LTE_B26	Channel bandwidth / Transmission bandwidth configuration [RB]						Power (dBm)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz		
QPSK	1	1	1	1	1		23+1/-2.5 dB
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		23+1/-2.5 dB
QPSK	> 5	> 4	> 8	> 12	> 16		22+1/-2.5 dB
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16		22+1/-2.5 dB
16 QAM	> 5	> 4	> 8	> 12	> 16		21+1/-2.5 dB

Bluetooth

BT Average Power: ≤10dBm

WiFi

WiFi Average Power:

802.11b: 15dBm [-1.5dB~~+1.0dB]

802.11g: 14dBm [-1.5dB~~+1.0dB]

802.11n: 12dBm[-1.5dB~~+1.0dB]

6.5. Test Configuration

6.5.1. GSM Test Configuration

SAR tests for GSM 850 and GSM 1900, a communication link is set up with a System Simulator (SS) by air link. Using E5515C the power level is set to “5” for GSM 850, set to “0” for GSM 1900. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5. the EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

Output power of reductions:

Table 8: The allowed power reduction in the multi-slot configuration

Number of timeslots in uplink assignment	Permissible nominal reduction of maximum output power,(dB)
1	0
2	0 to 3,0
3	1,8 to 4,8
4	3,0 to 6,0

6.5.2. UMTS Test Configuration

6.5.2.1. 3G SAR Test Reduction Procedure

In the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.³ This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as “otherwise” in the applicable procedures; SAR measurement is required for the secondary mode.

6.5.2.2. Output power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1’s” for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are required in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

6.5.2.3. Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

6.5.2.4. Body-Worn Accessory SAR

SAR for body-worn accessory configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When more than 2 DPDCHn are supported by the handset, it may be necessary to configure additional DPDCHn using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

6.5.2.5. Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn accessory configurations with

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 57 of 370

12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices” section of this document, for the highest reported SAR body-worn accessory exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

HSDPA should be configured according to the UE category of a test device. The number of HSDSCH/ HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors(β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) should be set according to values indicated in the Table below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Table 9: Subtests for UMTS Release 5 HSDPA

Sub-set	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (note 1, note 2)	CM(dB) (note 3)	MPR(dB)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (note 4)	15/15 (note 4)	64	12/15 (note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 8$ $\beta_{hs} = \beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$ Note2: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. Note3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC (TFC1,TF1) to $\beta_c=11/15$ and $\beta_d=15/15$.							

6.5.3. HSUPA Test Configuration

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn accessory configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices” section of this document, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn accessory measurements is tested for next to the ear head exposure.

Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in Table 2 and other applicable procedures described in the ‘WCDMA Handset’ and ‘Release 5 HSDPA Data Devices’ sections of this document

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 58 of 370

Table 10: Sub-Test 5 Setup for Release 6 HSUPA

Sub-set	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (2) (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Figure 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Table 11: HSUPA UE category

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E- DCH TTI (ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	2	2 SF2 & 2 SF4	11484	5.76
	4	4	10		20000	2.00
7 (No DPDCH)	4	8	2	2 SF2 & 2 SF4	22996	?
	4	4	10		20000	?

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4.
 UE Categories 1 to 6 supports QPSK only. UE Category 7 supports QPSK and 16QAM.
 (TS25.306-7.3.0)

6.5.3.1. HSPA, HSPA+ and DC-HSDPA Test Configuration

measurement is required for HSPA, HSPA+ or DC-HSDPA, a KDB inquiry is required to confirm that the wireless mode configurations in the test setup have remained stable throughout the SAR measurements.³⁵ Without prior KDB confirmation to determine the SAR results are acceptable, a PBA is required for TCB approval.

SAR test exclusion for HSPA, HSPA+ and DC-HSDPA is determined according to the following:

1) The HSPA procedures are applied to configure 3GPP Rel. 6 HSPA devices in the required sub-test mode(s) to determine SAR test exclusion.

2) SAR is required for Rel. 7 HSPA+ when SAR is required for Rel. 6 HSPA; otherwise, the 3G SAR test reduction procedure is applied to (uplink) HSPA+ with 12.2 kbps RMC as the primary mode.³⁶ Power is measured for HSPA+ that supports uplink 16 QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.

3) SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

4) Regardless of whether a PBA is required, the following information must be verified and included in the SAR report for devices supporting HSPA, HSPA+ or DC-HSDPA: a) The output power measurement results and applicable release version(s) of 3GPP TS 34.121.

i) Power measurement difficulties due to test equipment setup or availability must be resolved between the grantee and its test lab.

b) The power measurement results are in agreement with the individual device implementation and specifications. When Enhanced MPR (E-MPR) applies, the normal MPR targets may be modified according to the Cubic Metric (CM) measured by the device, which must be taken into consideration.

c) The UE category, operating parameters, such as the β and Δ values used to configure the device for testing, power setback procedures described in 3GPP TS 34.121 for the power measurements, and HSPA/HSPA+ channel conditions (active and stable) for the entire duration of the measurement according to the required E-TFCI and AG index values.

5) When SAR measurement is required, the test configurations, procedures and power measurement results must be clearly described to confirm that the required test parameters are used, including E-TFCI and AG index stability and output power conditions.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 60 of 370

Table 12: HS-DSCH UE category

Table 5.1a: FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes received	Minimum inter-TTI interval	Maximum number of bits of an HS-DSCH transport block received within an HS-DSCH TTI NOTE 1	Total number of soft channel bits	Supported modulations without MIMO operation or dual cell operation	Supported modulations with MIMO operation and without dual cell operation	Supported modulations with dual cell operation
Category 1	5	3	7298	19200	QPSK, 16QAM	Not applicable (MIMO not supported)	Not applicable (dual cell operation not supported)
Category 2	5	3	7298	28800			
Category 3	5	2	7298	28800			
Category 4	5	2	7298	38400			
Category 5	5	1	7298	57600			
Category 6	5	1	7298	67200			
Category 7	10	1	14411	115200			
Category 8	10	1	14411	134400			
Category 9	15	1	20251	172800			
Category 10	15	1	27952	172800			
Category 11	5	2	3630	14400	QPSK		
Category 12	5	1	3630	28800			
Category 13	15	1	35280	259200	QPSK, 16QAM, 64QAM		
Category 14	15	1	42192	259200			
Category 15	15	1	23370	345600	QPSK, 16QAM		
Category 16	15	1	27952	345600	QPSK, 16QAM		
Category 17 NOTE 2	15	1	35280	259200	QPSK, 16QAM, 64QAM	–	
			23370	345600	–	QPSK, 16QAM	
Category 18 NOTE 3	15	1	42192	259200	QPSK, 16QAM, 64QAM	–	
			27952	345600	–	QPSK, 16QAM	
Category 19	15	1	35280	518400	QPSK, 16QAM, 64QAM		
Category 20	15	1	42192	518400	QPSK, 16QAM, 64QAM		
Category 21	15	1	23370	345600	-	-	QPSK, 16QAM
Category 22	15	1	27952	345600			QPSK, 16QAM, 64QAM
Category 23	15	1	35280	518400			
Category 24	15	1	42192	518400			

6.5.4. LTE Test Configuration

LTE modes were tested according to FCC KDB 941225 D05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI (transmit time interval) supported by the device in each LTE configuration.

A) Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

B)MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

C)A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

D) Largest channel bandwidth standalone SAR test requirements

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

4) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

E) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the *reported* SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

6.5.5. WiFi Test Configuration

For WLAN SAR testing, WLAN engineering testing software installed on the DUT can provide continuous transmitting RF signal. The Tx power is set to 15 for 802.11 b mode by software. This RF signal utilized in SAR measurement has almost 100% duty cycle and its crest factor is 1.

For the 802.11b/g/n SAR tests, a communication link is set up with the test mode software for WiFi mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest data rate. Testing at higher data rates is not required when the maximum average output power is less than 0.25dB higher than those measured at the lowest data rate.

802.11b/g/n operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g/n modes are tested on the maximum average output channel; SAR is not required for 802.11g/n channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 63 of 370

7. Test Results

7.1. Conducted Power Results

Table 13: Conducted Power Measurement Results
Antenna 1

GSM 850 (WiFi Off)		Burst Conducted Power(dBm)			/	Average power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8		128/824.2	190/836.6	251/848.8
GSM		32.35	32.52	32.43	-9.03dB	23.32	23.49	23.40
GPRS (GMSK)	1Txslot	32.32	32.44	32.37	-9.03dB	23.29	23.41	23.34
	2Txslots	30.24	30.37	30.29	-6.02dB	24.22	24.35	24.27
	3Txslots	28.25	28.36	28.33	-4.26dB	23.99	24.10	24.07
	4Txslots	26.21	26.39	26.26	-3.01dB	23.20	23.38	23.25
EGPRS (GMSK)	1Txslot	32.29	32.52	32.40	-9.03dB	23.26	23.49	23.37
	2Txslots	30.22	30.44	30.30	-6.02dB	24.20	24.42	24.28
	3Txslots	28.04	28.16	28.25	-4.26dB	23.78	23.90	23.99
	4Txslots	26.74	26.87	26.99	-3.01dB	23.73	23.86	23.98
EGPRS (8PSK)	1Txslot	26.28	26.50	26.37	-9.03dB	17.25	17.47	17.34
	2Txslots	23.84	23.99	24.53	-6.02dB	17.82	17.97	18.51
	3Txslots	22.08	22.19	22.41	-4.26dB	17.82	17.93	18.15
	4Txslots	20.72	20.77	20.60	-3.01dB	17.71	17.76	17.59
GSM 850 (WiFi On)		Burst Conducted Power(dBm)			/	Average power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8		128/824.2	190/836.6	251/848.8
GSM		30.15	30.62	30.23	-9.03dB	21.12	21.59	21.20
GPRS (GMSK)	1Txslot	30.13	30.25	30.17	-9.03dB	21.10	21.22	21.14
	2Txslots	27.74	27.87	27.79	-6.02dB	21.72	21.85	21.77
	3Txslots	25.75	25.86	25.83	-4.26dB	21.49	21.60	21.57
	4Txslots	24.21	24.39	24.26	-3.01dB	23.20	23.38	23.25
EGPRS (GMSK)	1Txslot	30.09	30.31	30.18	-9.03dB	21.06	21.28	21.15
	2Txslots	27.62	27.84	27.70	-6.02dB	21.60	21.82	21.68
	3Txslots	25.84	25.96	25.93	-4.26dB	21.58	21.70	21.67
	4Txslots	24.54	24.67	24.67	-3.01dB	21.53	21.66	21.66
EGPRS (8PSK)	1Txslot	24.08	24.30	24.17	-9.03dB	15.05	15.27	15.14
	2Txslots	21.64	21.79	22.33	-6.02dB	15.62	15.77	16.31
	3Txslots	19.88	19.99	20.21	-4.26dB	15.62	15.73	15.95
	4Txslots	18.52	18.57	18.40	-3.01dB	15.51	15.56	15.39
GSM 1900 (WiFi Off)		Burst Conducted Power(dBm)			/	Average power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 64 of 370

		512/1850.2	661/1880	810/1909.8		512/1850.2	661/1880	810/1909.8
GSM		29.16	28.99	29.75	-9.03dB	20.13	19.96	20.72
GPRS (GMSK)	1Txslot	29.13	28.95	29.72	-9.03dB	20.10	19.92	20.69
	2Txslots	26.82	26.92	27.43	-6.02dB	20.80	20.90	21.41
	3Txslots	25.19	25.26	25.76	-4.26dB	20.93	21.00	21.50
	4Txslots	23.15	23.00	23.80	-3.01dB	20.14	19.99	20.79
EGPRS (GMSK)	1Txslot	29.16	28.93	29.76	-9.03dB	20.13	19.90	20.73
	2Txslots	27.25	27.02	27.48	-6.02dB	21.23	21.00	21.46
	3Txslots	25.51	25.29	25.81	-4.26dB	21.25	21.03	21.55
	4Txslots	23.54	23.47	23.64	-3.01dB	20.53	20.46	20.63
EGPRS (8PSK)	1Txslot	25.51	25.87	26.42	-9.03dB	16.48	16.84	17.39
	2Txslots	23.29	23.56	23.68	-6.02dB	17.27	17.54	17.66
	3Txslots	21.67	21.81	21.96	-4.26dB	17.41	17.55	17.70
	4Txslots	19.91	19.95	20.04	-3.01dB	16.90	16.94	17.03
GSM 1900 (WiFi On)		Burst Conducted Power(dBm)			/	Burst Conducted Power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8		512/1850.2	661/1880	810/1909.8
GSM		28.16	27.99	28.75	-9.03dB	19.13	18.96	19.72
GPRS (GMSK)	1Txslot	28.13	27.95	28.72	-9.03dB	19.10	18.92	19.69
	2Txslots	25.82	25.92	26.13	-6.02dB	19.80	19.90	20.11
	3Txslots	24.19	24.26	24.76	-4.26dB	19.93	20.00	20.50
	4Txslots	22.15	22.00	22.80	-3.01dB	19.14	18.99	19.79
EGPRS (GMSK)	1Txslot	28.16	27.93	28.76	-9.03dB	19.13	18.90	19.73
	2Txslots	25.25	25.02	25.48	-6.02dB	19.23	19.00	19.46
	3Txslots	24.51	24.29	24.55	-4.26dB	20.25	20.03	20.29
	4Txslots	22.54	22.47	22.64	-3.01dB	19.53	19.46	19.63
EGPRS (8PSK)	1Txslot	24.51	24.87	24.88	-9.03dB	15.48	15.84	15.85
	2Txslots	22.29	22.56	22.68	-6.02dB	16.27	16.54	16.66
	3Txslots	20.67	20.81	20.78	-4.26dB	16.41	16.55	16.52
	4Txslots	18.91	18.95	18.93	-3.01dB	15.90	15.94	15.92

Note:

1) Division Factors

To average the power, the division factor is as follows:

1Txslot = 1 transmit time slot out of 8 time slots

=> conducted power divided by (8/1) => -9.03 dB

2Txslots = 2 transmit time slots out of 8 time slots

=> conducted power divided by (8/2) => -6.02 dB

3Txslots = 3 transmit time slots out of 8 time slots

=> conducted power divided by (8/3) => -4.26 dB

4Txslots = 4 transmit time slots out of 8 time slots

=> conducted power divided by (8/4) => -3.01 dB

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 65 of 370

2) Average power numbers

The maximum power numbers are marks in bold.

UMTS Band II (WiFi Off)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		9262/1852.4	9400/1880	9538/1907.6
RMC	12.2kbps RMC	22.76	23.09	23.21
	64kbps RMC	22.66	22.99	22.18
	144kbps RMC	22.20	22.55	22.66
	384kbps RMC	22.26	22.49	22.71
HSDPA	Sub - Test 1	22.58	22.89	23.07
	Sub - Test 2	21.52	21.87	21.92
	Sub - Test 3	21.05	21.37	21.50
	Sub - Test 4	20.89	21.21	21.45
HSUPA	Sub - Test 1	21.18	21.46	21.43
	Sub - Test 2	19.26	19.74	19.65
	Sub - Test 3	21.01	21.36	21.12
	Sub - Test 4	19.49	19.94	19.80
	Sub - Test 5	21.70	22.14	22.18
DC-HSDPA	Sub - Test 1	22.26	22.57	22.75
	Sub - Test 2	21.00	21.35	21.50
	Sub - Test 3	20.83	21.15	21.23
	Sub - Test 4	20.87	21.19	21.15
UMTS Band II (WiFi On)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		9262/1852.4	9400/1880	9538/1907.6
RMC	12.2kbps RMC	18.96	19.29	19.21
	64kbps RMC	18.86	19.19	18.38
	144kbps RMC	18.40	18.75	18.86
	384kbps RMC	18.46	18.69	18.91
HSDPA	Sub - Test 1	18.68	18.99	19.17
	Sub - Test 2	17.32	17.67	17.72
	Sub - Test 3	16.85	17.17	17.30
	Sub - Test 4	16.69	17.01	17.25
HSUPA	Sub - Test 1	17.18	17.46	17.43
	Sub - Test 2	15.26	15.74	15.65
	Sub - Test 3	17.01	17.36	17.12
	Sub - Test 4	15.49	15.94	15.80
	Sub - Test 5	17.70	18.14	18.18

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 66 of 370

DC-HSDPA	Sub - Test 1	18.26	18.57	18.75
	Sub - Test 2	17.00	17.35	17.50
	Sub - Test 3	16.83	17.15	17.23
	Sub - Test 4	16.87	17.19	17.15
UMTS Band IV (WiFi Off)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		1312/1712.4	1413/1732.6	1513/1752.6
RMC	12.2kbps RMC	23.42	23.68	23.63
	64kbps RMC	22.63	22.94	22.96
	144kbps RMC	22.61	22.93	22.94
	384kbps RMC	22.70	22.57	22.59
HSDPA	Sub - Test 1	23.31	23.17	23.16
	Sub - Test 2	21.78	21.62	21.60
	Sub - Test 3	21.74	21.64	21.63
	Sub - Test 4	21.87	21.72	21.73
HSUPA	Sub - Test 1	21.43	21.20	21.36
	Sub - Test 2	19.60	19.83	19.98
	Sub - Test 3	20.66	20.38	20.58
	Sub - Test 4	19.59	19.99	19.89
	Sub - Test 5	21.48	21.26	21.40
DC-HSDPA	Sub - Test 1	21.99	21.85	21.84
	Sub - Test 2	21.96	21.80	21.78
	Sub - Test 3	21.82	21.72	21.71
	Sub - Test 4	21.85	21.70	21.71
UMTS Band IV (WiFi On)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		1312/1712.4	1413/1732.6	1513/1752.6
RMC	12.2kbps RMC	20.92	21.18	21.13
	64kbps RMC	20.13	20.44	20.46
	144kbps RMC	20.11	20.43	20.44
	384kbps RMC	20.20	20.07	20.09
HSDPA	Sub - Test 1	20.31	20.17	20.16
	Sub - Test 2	18.78	18.62	18.60
	Sub - Test 3	18.74	18.64	18.63
	Sub - Test 4	18.87	18.72	18.73
HSUPA	Sub - Test 1	18.43	18.20	18.36
	Sub - Test 2	16.60	16.83	16.75
	Sub - Test 3	18.86	18.58	18.78
	Sub - Test 4	16.59	16.76	16.89

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 67 of 370

	Sub - Test 5	18.48	18.26	18.40
DC-HSDPA	Sub - Test 1	19.99	19.85	19.84
	Sub - Test 2	18.96	18.80	18.78
	Sub - Test 3	18.82	18.72	18.71
	Sub - Test 4	18.85	18.70	18.71
UMTS Band V (WiFi Off)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		4132/826.4	4183/836.6	4233/846.6
RMC	12.2kbps RMC	23.57	23.34	23.38
	64kbps RMC	22.98	22.79	22.82
	144kbps RMC	22.33	22.38	22.46
	384kbps RMC	23.01	22.79	22.88
HSDPA	Sub - Test 1	23.31	23.17	23.16
	Sub - Test 2	22.28	22.12	22.10
	Sub - Test 3	22.14	22.04	21.73
	Sub - Test 4	22.17	22.02	22.03
HSUPA	Sub - Test 1	21.63	21.40	21.56
	Sub - Test 2	20.10	20.93	20.08
	Sub - Test 3	21.46	21.38	21.48
	Sub - Test 4	20.87	20.77	20.91
	Sub - Test 5	22.48	22.26	22.40
DC-HSDPA	Sub - Test 1	22.96	22.84	22.81
	Sub - Test 2	22.93	22.75	22.75
	Sub - Test 3	22.31	22.19	22.16
	Sub - Test 4	22.32	22.17	22.18
UMTS Band V (WiFi On)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		4132/826.4	4132/826.4	4132/826.4
RMC	12.2kbps RMC	20.57	20.41	20.43
	64kbps RMC	19.98	19.79	19.82
	144kbps RMC	19.33	19.38	19.46
	384kbps RMC	20.01	19.79	19.88
HSDPA	Sub - Test 1	19.81	19.67	19.66
	Sub - Test 2	18.78	18.62	18.60
	Sub - Test 3	18.64	18.54	18.23
	Sub - Test 4	18.67	18.52	18.53
HSUPA	Sub - Test 1	18.13	17.90	18.06
	Sub - Test 2	16.60	17.43	16.58
	Sub - Test 3	17.96	17.88	17.98

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 68 of 370

	Sub - Test 4	17.37	17.27	17.41
	Sub - Test 5	18.98	18.76	18.90
DC-HSDPA	Sub - Test 1	19.46	19.34	19.31
	Sub - Test 2	19.43	19.25	19.25
	Sub - Test 3	18.81	18.69	18.66
	Sub - Test 4	18.82	18.67	18.68

LTE FDD Band 2 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18607/1850.7	18900/1880	19193/1909.3
1.4MHz	QPSK	1	0	22.04	22.39	22.26
		1	2	22.17	21.97	22.77
		1	5	22.17	21.90	22.12
		3	0	21.11	21.04	21.50
		3	2	21.11	20.81	21.50
		3	3	21.00	20.70	21.48
		6	0	21.17	20.81	21.43
	16QAM	1	0	22.07	22.19	22.31
		1	2	21.66	21.79	21.91
		1	5	21.66	21.77	21.88
		3	0	20.90	21.03	21.13
		3	2	20.56	20.67	20.79
		3	3	20.43	20.57	20.67
		6	0	19.65	19.77	19.89
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18615/1851.5	18900/1880	19185/1908.5
3MHz	QPSK	1	0	22.20	22.55	22.42
		1	7	22.33	22.13	22.93
		1	14	22.33	22.06	22.28
		8	0	22.16	22.09	22.55
		8	4	22.16	21.86	22.55
		8	7	22.05	21.75	22.53
		15	0	21.33	20.97	21.59
	16QAM	1	0	21.51	21.63	21.75
		1	7	21.10	21.23	21.35
		1	14	21.10	21.21	21.32
		8	0	21.06	21.19	21.29
		8	4	20.72	20.83	20.95
		8	7	20.59	20.73	20.83
		15	0	19.81	19.93	20.05
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 69 of 370

				18625/1852.5	18900/1880	19175/1907.5
5MHz	QPSK	1	0	22.17	22.52	22.39
		1	13	22.30	22.10	22.90
		1	24	22.30	22.03	22.25
		12	0	21.24	21.17	21.63
		12	6	21.24	20.94	21.63
		12	13	21.13	20.83	21.61
		25	0	21.30	20.94	21.56
	16QAM	1	0	22.20	22.32	22.44
		1	13	21.79	21.92	22.04
		1	24	21.79	21.90	22.01
		12	0	21.03	21.16	21.26
		12	6	20.69	20.80	20.92
		12	13	20.56	20.70	20.80
		25	0	19.78	19.90	20.02
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18650/1855	18900/1880	19150/1905
10MHz	QPSK	1	0	22.18	22.53	22.40
		1	25	22.31	22.11	22.91
		1	49	22.31	22.04	22.26
		25	0	21.25	21.18	21.64
		25	13	21.25	20.95	21.64
		25	25	21.14	20.84	21.62
		50	0	21.31	20.95	21.57
	16QAM	1	0	22.21	22.33	22.45
		1	25	21.80	21.93	22.05
		1	49	21.80	21.91	22.02
		25	0	21.04	21.17	21.27
		25	13	20.70	20.81	20.93
		25	25	20.57	20.71	20.81
		50	0	19.79	19.91	20.03
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18675/1857.5	18900/1880	19125/1902.5
15MHz	QPSK	1	0	22.15	22.50	22.37
		1	38	22.28	22.08	22.88
		1	74	22.28	22.01	22.23
		36	0	21.22	21.15	21.61
		36	18	21.22	20.92	21.61
		36	39	21.11	20.81	21.59
		75	0	21.28	20.92	21.54
	16QAM	1	0	22.18	22.30	22.42
		1	38	21.77	21.90	22.02
		1	74	21.77	21.88	21.99
		36	0	21.01	21.14	21.24

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 70 of 370

		36	18	20.67	20.78	20.90
		36	39	20.54	20.68	20.78
		75	0	19.76	19.88	20.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18700/1860	18900/1880	19100/1900
20MHz	QPSK	1	0	22.04	22.77	22.26
		1	50	22.17	21.97	22.39
		1	99	22.37	21.90	22.12
		50	0	21.11	21.49	21.50
		50	25	21.21	20.81	21.05
		50	50	21.00	20.70	21.48
		100	0	21.17	20.81	21.43
	16QAM	1	0	22.07	22.19	22.31
		1	50	21.66	21.79	21.91
		1	99	21.66	21.77	21.88
		50	0	20.90	21.03	21.13
		50	25	20.56	20.67	20.79
		50	50	20.43	20.57	20.67
		100	0	19.65	19.77	19.89

LTE FDD Band 2 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18607/1850.7	18900/1880	19193/1909.3
1.4MHz	QPSK	1	0	17.56	17.91	17.78
		1	2	17.68	17.48	18.28
		1	5	17.67	17.40	17.62
		3	0	16.60	16.53	16.99
		3	2	16.59	16.29	16.98
		3	3	16.47	16.17	16.95
		6	0	16.66	16.30	16.92
	16QAM	1	0	17.55	17.67	17.79
		1	2	17.13	17.26	17.38
		1	5	17.18	17.29	17.40
		3	0	16.41	16.54	16.64
		3	2	16.06	16.17	16.29
		3	3	15.92	16.06	16.16
		6	0	15.13	15.25	15.37
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18615/1851.5	18900/1880	19185/1908.5
3MHz	QPSK	1	0	17.72	18.07	17.94

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 71 of 370

		1	7	17.84	17.64	18.44
		1	14	17.83	17.56	17.78
		8	0	17.65	17.58	18.04
		8	4	17.64	17.34	18.03
		8	7	17.52	17.22	18.00
		15	0	16.82	16.46	17.08
	16QAM	1	0	16.99	17.11	17.23
		1	7	16.57	16.70	16.82
		1	14	16.62	16.73	16.84
		8	0	16.57	16.70	16.80
		8	4	16.22	16.33	16.45
		8	7	16.08	16.22	16.32
		15	0	15.29	15.41	15.53
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18625/1852.5	18900/1880	19175/1907.5
5MHz	QPSK	1	0	17.69	18.04	17.91
		1	13	17.81	17.61	18.41
		1	24	17.80	17.53	17.75
		12	0	16.73	16.66	17.12
		12	6	16.72	16.42	17.11
		12	13	16.60	16.30	17.08
		25	0	16.79	16.43	17.05
	16QAM	1	0	17.68	17.80	17.92
		1	13	17.26	17.39	17.51
		1	24	17.31	17.42	17.53
		12	0	16.54	16.67	16.77
		12	6	16.19	16.30	16.42
		12	13	16.05	16.19	16.29
		25	0	15.26	15.38	15.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18650/1855	18900/1880	19150/1905
10MHz	QPSK	1	0	17.70	18.05	17.92
		1	25	17.82	17.62	18.42
		1	49	17.81	17.54	17.76
		25	0	16.74	16.67	17.13
		25	13	16.73	16.43	17.12
		25	25	16.61	16.31	17.09
		50	0	16.80	16.44	17.06
	16QAM	1	0	17.69	17.81	17.93
		1	25	17.27	17.40	17.52
		1	49	17.32	17.43	17.54
		25	0	16.55	16.68	16.78
		25	13	16.20	16.31	16.43
		25	25	16.06	16.20	16.30

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 72 of 370

		50	0	15.27	15.39	15.51
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18675/1857.5	18900/1880	19125/1902.5
15MHz	QPSK	1	0	17.67	18.02	17.89
		1	38	17.79	17.59	18.39
		1	74	17.78	17.51	17.73
		36	0	16.71	16.64	17.10
		36	18	16.70	16.40	17.09
		36	39	16.58	16.28	17.06
		75	0	16.77	16.41	17.03
	16QAM	1	0	17.66	17.78	17.90
		1	38	17.24	17.37	17.49
		1	74	17.29	17.40	17.51
		36	0	16.52	16.65	16.75
		36	18	16.17	16.28	16.40
		36	39	16.03	16.17	16.27
		75	0	15.24	15.36	15.48
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18700/1860	18900/1880	19100/1900
20MHz	QPSK	1	0	17.54	18.27	17.76
		1	50	17.67	17.47	17.89
		1	99	17.87	17.40	17.62
		50	0	16.61	16.99	17.00
		50	25	16.71	16.31	16.55
		50	50	16.50	16.20	16.98
		100	0	16.67	16.31	16.93
	16QAM	1	0	17.57	17.69	17.81
		1	50	17.16	17.29	17.41
		1	99	17.16	17.27	17.38
		50	0	16.40	16.53	16.63
		50	25	16.06	16.17	16.29
		50	50	15.93	16.07	16.17
		100	0	15.15	15.27	15.39

LTE FDD Band 4 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19957/1710.7	20175/1732.5	20393/1754.3
1.4MHz	QPSK	1	0	21.83	22.51	22.38
		1	2	21.71	22.16	22.01
		1	5	21.49	22.08	22.32
		3	0	21.77	22.43	21.94

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 73 of 370

		3	2	22.13	22.22	21.95
		3	3	22.34	22.02	21.96
		6	0	21.04	21.39	21.00
	16QAM	1	0	21.16	21.03	20.96
		1	2	20.76	20.65	20.58
		1	5	20.81	20.69	20.60
		3	0	20.40	20.30	20.20
		3	2	20.93	20.81	20.73
		3	3	20.89	20.80	20.70
		6	0	20.92	20.81	20.73
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19965/1711.5	20175/1732.5	20385/1753.5
3MHz	QPSK	1	0	21.80	22.48	22.35
		1	13	21.68	22.13	21.98
		1	24	21.46	22.05	22.29
		12	0	21.28	21.94	21.45
		12	6	21.64	21.73	21.46
		12	13	21.85	21.53	21.47
		25	0	21.13	21.48	21.09
	16QAM	1	0	21.63	21.50	21.43
		1	13	21.23	21.12	21.05
		1	24	21.28	21.16	21.07
		12	0	20.37	20.27	20.17
		12	6	21.40	21.28	21.20
		12	13	21.36	21.27	21.17
		25	0	21.39	21.28	21.20
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19975/1712.5	20175/1732.5	20375/1752.5
5MHz	QPSK	1	0	21.81	22.49	22.36
		1	13	21.69	22.14	21.99
		1	24	21.47	22.06	22.30
		12	0	20.79	21.45	20.96
		12	6	21.15	21.24	20.97
		12	13	21.36	21.04	20.98
		25	0	21.14	21.49	21.10
	16QAM	1	0	21.64	21.51	21.44
		1	13	21.24	21.13	21.06
		1	24	21.29	21.17	21.08
		12	0	20.38	20.28	20.18
		12	6	21.41	21.29	21.21
		12	13	21.37	21.28	21.18
		25	0	21.40	21.29	21.21
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20000/1715	20175/1732.5	20350/1750

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 74 of 370

10MHz	QPSK	1	0	21.77	22.45	22.32
		1	25	21.65	22.10	21.95
		1	49	21.43	22.02	22.26
		25	0	20.75	21.41	20.92
		25	13	21.11	21.20	20.93
		25	25	21.32	21.00	20.94
		50	0	21.10	21.45	21.06
	16QAM	1	0	21.60	21.47	21.40
		1	25	21.20	21.09	21.02
		1	49	21.25	21.13	21.04
		25	0	20.34	20.24	20.14
		25	13	21.37	21.25	21.17
		25	25	21.33	21.24	21.14
		50	0	21.36	21.25	21.17
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20025/1717.5	20175/1732.5	20325/1747.5
15MHz	QPSK	1	0	21.79	22.47	22.34
		1	38	21.67	22.12	21.97
		1	74	21.45	22.04	22.28
		36	0	20.77	21.43	20.94
		36	18	21.13	21.22	20.95
		36	39	21.34	21.02	20.96
		75	0	21.12	21.47	21.08
	16QAM	1	0	21.62	21.49	21.42
		1	38	21.22	21.11	21.04
		1	74	21.27	21.15	21.06
		36	0	20.36	20.26	20.16
		36	18	21.39	21.27	21.19
		36	39	21.35	21.26	21.16
		75	0	21.38	21.27	21.19
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20050/1720	20175/1732.5	20300/1745
20MHz	QPSK	1	0	21.66	22.34	22.21
		1	50	21.54	21.99	21.84
		1	99	21.32	21.91	22.15
		50	0	20.64	21.30	20.81
		50	25	21.00	21.09	20.82
		50	50	21.21	20.89	20.83
		100	0	20.99	21.34	20.95
	16QAM	1	0	21.49	21.36	21.29
		1	50	21.09	20.98	20.91
		1	99	21.14	21.02	20.93
		50	0	20.23	20.13	20.03

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 75 of 370

		50	25	21.26	21.14	21.06
		50	50	21.22	21.13	21.03
		100	0	21.25	21.14	21.06

LTE FDD Band 4 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19957/1710.7	20175/1732.5	20393/1754.3
1.4MHz	QPSK	1	0	18.85	19.53	19.40
		1	2	18.72	19.17	19.02
		1	5	18.49	19.08	19.32
		3	0	18.76	19.42	18.93
		3	2	19.11	19.20	18.93
		3	3	19.31	18.99	18.93
		6	0	18.03	18.38	17.99
	16QAM	1	0	18.14	18.01	17.94
		1	2	17.73	17.62	17.55
		1	5	17.83	17.71	17.62
		3	0	17.41	17.31	17.21
		3	2	17.93	17.81	17.73
		3	3	17.88	17.79	17.69
		6	0	17.90	17.79	17.71
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19965/1711.5	20175/1732.5	20385/1753.5
3MHz	QPSK	1	0	18.82	19.50	19.37
		1	13	18.69	19.14	18.99
		1	24	18.46	19.05	19.29
		12	0	18.27	18.93	18.44
		12	6	18.62	18.71	18.44
		12	13	18.82	18.50	18.44
		25	0	18.12	18.47	18.08
	16QAM	1	0	18.61	18.48	18.41
		1	13	18.20	18.09	18.02
		1	24	18.30	18.18	18.09
		12	0	17.38	17.28	17.18
		12	6	18.40	18.28	18.20
		12	13	18.35	18.26	18.16
		25	0	18.37	18.26	18.18
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19975/1712.5	20175/1732.5	20375/1752.5
5MHz	QPSK	1	0	18.83	19.51	19.38

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 76 of 370

		1	13	18.70	19.15	19.00
		1	24	18.47	19.06	19.30
		12	0	17.78	18.44	17.95
		12	6	18.13	18.22	17.95
		12	13	18.33	18.01	17.95
		25	0	18.13	18.48	18.09
	16QAM	1	0	18.62	18.49	18.42
		1	13	18.21	18.10	18.03
		1	24	18.31	18.19	18.10
		12	0	17.39	17.29	17.19
		12	6	18.41	18.29	18.21
		12	13	18.36	18.27	18.17
		25	0	18.38	18.27	18.19
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20000/1715	20175/1732.5	20350/1750
10MHz	QPSK	1	0	18.79	19.47	19.34
		1	25	18.66	19.11	18.96
		1	49	18.43	19.02	19.26
		25	0	17.74	18.40	17.91
		25	13	18.09	18.18	17.91
		25	25	18.29	17.97	17.91
		50	0	18.09	18.44	18.05
	16QAM	1	0	18.58	18.45	18.38
		1	25	18.17	18.06	17.99
		1	49	18.27	18.15	18.06
		25	0	17.35	17.25	17.15
		25	13	18.37	18.25	18.17
		25	25	18.32	18.23	18.13
		50	0	18.34	18.23	18.15
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20025/1717.5	20175/1732.5	20325/1747.5
15MHz	QPSK	1	0	18.81	19.49	19.36
		1	38	18.68	19.13	18.98
		1	74	18.45	19.04	19.28
		36	0	17.76	18.42	17.93
		36	18	18.11	18.20	17.93
		36	39	18.31	17.99	17.93
		75	0	18.11	18.46	18.07
	16QAM	1	0	18.60	18.47	18.40
		1	38	18.19	18.08	18.01
		1	74	18.29	18.17	18.08
		36	0	17.37	17.27	17.17
		36	18	18.39	18.27	18.19
		36	39	18.34	18.25	18.15

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 77 of 370

		75	0	18.36	18.25	18.17
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20050/1720	20175/1732.5	20300/1745
20MHz	QPSK	1	0	18.66	19.34	19.21
		1	50	18.54	18.99	18.84
		1	99	18.32	18.91	19.15
		50	0	17.64	18.30	17.81
		50	25	18.00	18.09	17.82
		50	50	18.21	17.89	17.83
		100	0	17.99	18.34	17.95
	16QAM	1	0	18.49	18.36	18.29
		1	50	18.09	17.98	17.91
		1	99	18.14	18.02	17.93
		50	0	17.23	17.13	17.03
		50	25	18.26	18.14	18.06
		50	50	18.22	18.13	18.03
		100	0	18.25	18.14	18.06

LTE FDD Band 5 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20407/824.7	20525/836.5	20643/848.3
1.4MHz	QPSK	1	0	23.02	22.82	23.26
		1	2	23.52	23.26	23.62
		1	5	23.08	23.55	23.02
		3	0	23.04	22.57	23.11
		3	2	22.98	22.66	23.03
		3	3	22.86	22.76	22.91
		6	0	22.06	21.93	22.13
	16QAM	1	0	22.18	21.92	22.55
		1	2	22.68	22.45	22.78
		1	5	22.22	22.78	22.11
		3	0	21.30	20.86	21.13
		3	2	21.38	21.06	21.28
		3	3	21.11	21.07	21.14
		6	0	21.86	21.77	21.78
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20415/825.5	20525/836.5	20635/847.5
3MHz	QPSK	1	0	23.01	22.81	23.25
		1	13	23.51	23.25	23.61
		1	24	23.07	23.54	23.01
		12	0	23.09	22.62	23.16

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 78 of 370

		12	6	23.03	22.71	23.08
		12	13	22.91	22.81	22.96
		25	0	22.05	21.91	22.12
	16QAM	1	0	22.16	21.91	22.54
		1	13	22.67	22.44	22.77
		1	24	22.21	22.77	22.10
		12	0	21.29	20.85	21.12
		12	6	21.37	21.04	21.27
		12	13	21.10	21.06	21.13
		25	0	21.92	21.82	21.83
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20425/826.5	20525/836.5	20625/846.5
5MHz	QPSK	1	0	23.03	22.82	23.27
		1	13	23.53	23.26	23.63
		1	24	23.09	23.55	23.03
		12	0	22.25	21.77	22.32
		12	6	22.19	21.86	22.24
		12	13	22.06	21.96	22.12
		25	0	22.07	21.93	22.14
	16QAM	1	0	22.19	21.92	22.56
		1	13	22.69	22.45	22.79
		1	24	22.23	22.78	22.12
		12	0	21.31	20.86	21.14
		12	6	21.39	21.06	21.29
		12	13	21.12	21.07	21.15
		25	0	21.08	20.97	20.99
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20450/829	20525/836.5	20600/844
10MHz	QPSK	1	0	22.90	22.70	23.15
		1	25	23.40	23.14	23.51
		1	49	22.96	23.44	22.91
		25	0	22.12	21.65	22.19
		25	13	22.06	21.74	22.12
		25	25	21.94	21.84	21.99
		50	0	21.94	21.81	22.02
	16QAM	1	0	22.06	21.80	22.43
		1	25	22.57	22.34	22.67
		1	49	22.11	22.66	21.99
		25	0	21.18	20.74	21.01
		25	13	21.27	20.94	21.16
		25	25	20.99	20.96	21.02
		50	0	20.95	20.86	20.86

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 79 of 370

LTE FDD Band 5 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20407/824.7	20525/836.5	20643/848.3
1.4MHz	QPSK	1	0	18.54	18.34	18.78
		1	2	19.03	18.77	19.13
		1	5	18.58	19.05	18.52
		3	0	18.53	18.06	18.60
		3	2	18.46	18.14	18.51
		3	3	18.33	18.23	18.38
		6	0	17.55	17.42	17.62
	16QAM	1	0	17.66	17.40	18.03
		1	2	18.15	17.92	18.25
		1	5	17.74	18.30	17.63
		3	0	16.81	16.37	16.64
		3	2	16.88	16.56	16.78
		3	3	16.60	16.56	16.63
		6	0	17.34	17.25	17.26
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20415/825.5	20525/836.5	20635/847.5
3MHz	QPSK	1	0	18.53	18.33	18.77
		1	13	19.02	18.76	19.12
		1	24	18.57	19.04	18.51
		12	0	18.58	18.11	18.65
		12	6	18.51	18.19	18.56
		12	13	18.38	18.28	18.43
		25	0	17.54	17.40	17.61
	16QAM	1	0	17.64	17.39	18.02
		1	13	18.14	17.91	18.24
		1	24	17.73	18.29	17.62
		12	0	16.80	16.36	16.63
		12	6	16.87	16.54	16.77
		12	13	16.59	16.55	16.62
		25	0	17.40	17.30	17.31
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20425/826.5	20525/836.5	20625/846.5
5MHz	QPSK	1	0	18.55	18.34	18.79
		1	13	19.04	18.77	19.14
		1	24	18.59	19.05	18.53
		12	0	17.74	17.26	17.81
		12	6	17.67	17.34	17.72
		12	13	17.53	17.43	17.59

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 80 of 370

	16QAM	25	0	17.56	17.42	17.63
		1	0	17.67	17.40	18.04
		1	13	18.16	17.92	18.26
		1	24	17.75	18.30	17.64
		12	0	16.82	16.37	16.65
		12	6	16.89	16.56	16.79
		12	13	16.61	16.56	16.64
		25	0	16.56	16.45	16.47
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20450/829	20525/836.5	20600/844
10MHz	QPSK	1	0	18.40	18.20	18.65
		1	25	18.90	18.64	19.01
		1	49	18.46	18.94	18.41
		25	0	17.62	17.15	17.69
		25	13	17.56	17.24	17.62
		25	25	17.44	17.34	17.49
		50	0	17.44	17.31	17.52
	16QAM	1	0	17.56	17.30	17.93
		1	25	18.07	17.84	18.17
		1	49	17.61	18.16	17.49
		25	0	16.68	16.24	16.51
		25	13	16.77	16.44	16.66
		25	25	16.49	16.46	16.52
		50	0	16.45	16.36	16.36

LTE FDD Band 7 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20775/2502.5	21100/2535	21425/2567.5
5MHz	QPSK	1	0	22.25	22.64	22.88
		1	13	22.87	22.81	22.81
		1	24	22.76	22.75	22.55
		12	0	21.69	21.88	21.68
		12	6	21.75	21.88	21.66
		12	13	22.07	21.88	21.66
		25	0	21.80	21.85	21.61
	16QAM	1	0	21.91	21.94	21.72
		1	13	21.89	21.95	21.72
		1	24	21.91	21.96	21.71
		12	0	20.80	20.86	20.61
		12	6	20.80	20.84	20.61
		12	13	20.79	20.86	20.61

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 81 of 370

		25	0	20.70	20.75	20.52
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20800/2505	21100/2535	21400/2565
10MHz	QPSK	1	0	22.26	22.65	22.89
		1	25	22.88	22.82	22.82
		1	49	22.77	22.76	22.56
		25	0	21.70	21.88	21.68
		25	13	21.76	21.89	21.66
		25	25	22.07	21.88	21.67
		50	0	21.80	21.86	21.61
	16QAM	1	0	21.91	21.95	21.72
		1	25	21.90	21.95	21.73
		1	49	21.92	21.96	21.72
		25	0	20.80	20.87	20.61
		25	13	20.80	20.85	20.61
		25	25	20.79	20.87	20.61
		50	0	20.70	20.75	20.52
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20825/2507.5	21100/2535	21375/2562.5
15MHz	QPSK	1	0	22.27	22.66	22.90
		1	38	22.89	22.83	22.83
		1	74	22.78	22.77	22.57
		36	0	21.71	21.90	21.70
		36	18	21.77	21.91	21.68
		36	39	22.09	21.90	21.68
		75	0	21.82	21.87	21.63
	16QAM	1	0	21.93	21.97	21.74
		1	38	21.91	21.97	21.74
		1	74	21.94	21.98	21.74
		36	0	20.82	20.88	20.63
		36	18	20.82	20.86	20.63
		36	39	20.81	20.88	20.63
		75	0	20.72	20.77	20.54
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20850/2510	21100/2535	21350/2560
20MHz	QPSK	1	0	22.15	22.54	22.78
		1	50	22.77	22.71	22.71
		1	99	22.66	22.65	22.45
		50	0	21.59	21.77	21.58
		50	25	21.65	21.78	21.56
		50	50	21.97	21.77	21.56
		100	0	21.70	21.75	21.51
	16QAM	1	0	21.81	21.84	21.62

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 82 of 370

		1	50	21.79	21.84	21.62
		1	99	21.81	21.85	21.61
		50	0	20.70	20.76	20.51
		50	25	20.70	20.74	20.51
		50	50	20.69	20.76	20.51
		100	0	20.60	20.65	20.42

LTE FDD Band 7 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20775/2502.5	21100/2535	21425/2567.5
5MHz	QPSK	1	0	18.77	19.16	19.40
		1	13	19.38	19.32	19.32
		1	24	19.26	19.25	19.05
		12	0	18.18	18.37	18.17
		12	6	18.23	18.36	18.14
		12	13	18.54	18.35	18.13
		25	0	18.29	18.34	18.10
	16QAM	1	0	18.39	18.42	18.20
		1	13	18.36	18.42	18.19
		1	24	18.43	18.48	18.23
		12	0	17.31	17.37	17.12
		12	6	17.30	17.34	17.11
		12	13	17.28	17.35	17.10
		25	0	17.18	17.23	17.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20800/2505	21100/2535	21400/2565
10MHz	QPSK	1	0	18.78	19.17	19.41
		1	25	19.39	19.33	19.33
		1	49	19.27	19.26	19.06
		25	0	18.19	18.37	18.17
		25	13	18.24	18.37	18.14
		25	25	18.54	18.35	18.14
		50	0	18.29	18.35	18.10
	16QAM	1	0	18.39	18.43	18.20
		1	25	18.37	18.42	18.20
		1	49	18.44	18.48	18.24
		25	0	17.31	17.38	17.12
		25	13	17.30	17.35	17.11
		25	25	17.28	17.36	17.10
		50	0	17.18	17.23	17.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 83 of 370

				20825/2507.5	21100/2535	21375/2562.5
15MHz	QPSK	1	0	18.79	19.18	19.42
		1	38	19.40	19.34	19.34
		1	74	19.28	19.27	19.07
		36	0	18.20	18.39	18.19
		36	18	18.25	18.39	18.16
		36	39	18.56	18.37	18.15
		75	0	18.31	18.36	18.12
	16QAM	1	0	18.41	18.45	18.22
		1	38	18.38	18.44	18.21
		1	74	18.46	18.50	18.26
		36	0	17.33	17.39	17.14
		36	18	17.32	17.36	17.13
		36	39	17.30	17.37	17.12
		75	0	17.20	17.25	17.02
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20850/2510	21100/2535	21350/2560
20MHz	QPSK	1	0	16.65	17.04	17.28
		1	50	17.27	17.21	17.21
		1	99	17.16	17.15	16.95
		50	0	16.09	16.27	16.08
		50	25	16.15	16.28	16.06
		50	50	16.47	16.27	16.06
		100	0	16.20	16.25	16.01
	16QAM	1	0	16.31	16.34	16.12
		1	50	16.29	16.34	16.12
		1	99	16.31	16.35	16.11
		50	0	15.20	15.26	15.01
		50	25	15.20	15.24	15.01
		50	50	15.19	15.26	15.01
		100	0	15.10	15.15	14.92

LTE FDD Band 12 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23017/699.7	23095/707.5	23173/715.3
1.4MHz	QPSK	1	0	22.35	22.55	22.53
		1	2	22.82	22.96	22.90
		1	5	22.61	22.78	22.54
		3	0	21.32	21.37	21.44
		3	2	21.27	21.55	21.52
		3	3	21.19	21.28	21.38

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 84 of 370

		6	0	21.19	21.18	21.25
		1	0	22.13	22.38	22.37
		1	2	22.68	22.82	22.72
		1	5	22.43	22.59	22.39
		3	0	21.17	21.21	21.20
		3	2	21.05	21.41	21.39
		3	3	21.05	21.02	21.21
		6	0	21.00	21.04	21.10
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23025/700.5	23095/707.5	23165/714.5
3MHz	QPSK	1	0	22.34	22.52	22.52
		1	7	22.81	22.95	22.89
		1	14	22.58	22.77	22.53
		8	0	21.31	21.36	21.42
		8	4	21.26	21.53	21.51
		8	7	21.18	21.27	21.35
		15	0	21.16	21.17	21.24
	16QAM	1	0	22.14	22.41	22.38
		1	7	22.70	22.83	22.73
		1	14	22.44	22.61	22.40
		8	0	21.18	21.22	21.23
		8	4	21.08	21.42	21.40
		8	7	21.06	21.05	21.22
		15	0	21.02	21.05	21.11
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23035/701.5	23095/707.5	23155/713.5
5MHz	QPSK	1	0	22.31	22.51	22.51
		1	13	22.80	22.94	22.87
		1	24	22.57	22.75	22.52
		12	0	21.30	21.35	21.39
		12	6	21.23	21.52	21.50
		12	13	21.17	21.24	21.34
		25	0	21.14	21.16	21.23
	16QAM	1	0	22.17	22.42	22.39
		1	13	22.71	22.84	22.75
		1	24	22.45	22.63	22.41
		12	0	21.19	21.23	21.26
		12	6	21.11	21.43	21.41
		12	13	21.07	21.08	21.23
		25	0	21.04	21.06	21.12
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23060/704	23095/707.5	23130/711
10MHz	QPSK	1	0	22.30	22.50	22.49

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 85 of 370

		1	25	22.79	22.93	22.86
		1	49	22.54	22.73	22.51
		25	0	21.29	21.34	21.36
		25	13	21.22	21.51	21.49
		25	25	21.16	21.21	21.33
		50	0	21.13	21.15	21.22
	16QAM	1	0	22.20	22.43	22.40
		1	25	22.72	22.85	22.77
		1	49	22.46	22.65	22.42
		25	0	21.20	21.24	21.29
		25	13	21.14	21.44	21.42
		25	25	21.08	21.11	21.24
		50	0	21.06	21.07	21.13

LTE FDD Band 12 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23017/699.7	23095/707.5	23173/715.3
1.4MHz	QPSK	1	0	17.87	18.07	18.05
		1	2	18.33	18.47	18.41
		1	5	18.11	18.28	18.04
		3	0	16.81	16.86	16.93
		3	2	16.75	17.03	17.00
		3	3	16.66	16.75	16.85
		6	0	16.68	16.67	16.74
	16QAM	1	0	17.61	17.86	17.85
		1	2	18.15	18.29	18.19
		1	5	17.95	18.11	17.91
		3	0	16.68	16.72	16.71
		3	2	16.55	16.91	16.89
		3	3	16.54	16.51	16.70
		6	0	16.48	16.52	16.58
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23025/700.5	23095/707.5	23165/714.5
3MHz	QPSK	1	0	17.86	18.04	18.04
		1	7	18.32	18.46	18.40
		1	14	18.08	18.27	18.03
		8	0	16.80	16.85	16.91
		8	4	16.74	17.01	16.99
		8	7	16.65	16.74	16.82
		15	0	16.65	16.66	16.73
	16QAM	1	0	17.62	17.89	17.86

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 86 of 370

		1	7	18.17	18.30	18.20
		1	14	17.96	18.13	17.92
		8	0	16.69	16.73	16.74
		8	4	16.58	16.92	16.90
		8	7	16.55	16.54	16.71
		15	0	16.50	16.53	16.59
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23035/701.5	23095/707.5	23155/713.5
5MHz	QPSK	1	0	17.83	18.03	18.03
		1	13	18.31	18.45	18.38
		1	24	18.07	18.25	18.02
		12	0	16.79	16.84	16.88
		12	6	16.71	17.00	16.98
		12	13	16.64	16.71	16.81
		25	0	16.63	16.65	16.72
	16QAM	1	0	17.65	17.90	17.87
		1	13	18.18	18.31	18.22
		1	24	17.97	18.15	17.93
		12	0	16.70	16.74	16.77
		12	6	16.61	16.93	16.91
		12	13	16.56	16.57	16.72
		25	0	16.52	16.54	16.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23060/704	23095/707.5	23130/711
10MHz	QPSK	1	0	17.80	18.00	17.99
		1	25	18.29	18.43	18.36
		1	49	18.04	18.23	18.01
		25	0	16.79	16.84	16.86
		25	13	16.72	17.01	16.99
		25	25	16.66	16.71	16.83
		50	0	16.63	16.65	16.72
	16QAM	1	0	17.70	17.93	17.90
		1	25	18.22	18.35	18.27
		1	49	17.96	18.15	17.92
		25	0	16.70	16.74	16.79
		25	13	16.64	16.94	16.92
		25	25	16.58	16.61	16.74
		50	0	16.56	16.57	16.63

LTE FDD Band 17 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23755/706.5	23790/710	23825/713.5

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 87 of 370

5MHz	QPSK	1	0	22.51	22.51	22.61
		1	13	23.07	23.06	22.95
		1	24	22.91	22.86	22.64
		12	0	21.54	21.56	21.35
		12	6	21.54	21.51	21.62
		12	13	21.50	21.92	21.90
		25	0	21.53	21.53	21.51
	16QAM	1	0	21.45	21.45	21.26
		1	13	21.41	21.40	21.53
		1	24	21.41	21.81	21.78
		12	0	21.43	21.43	21.41
		12	6	21.42	21.41	21.54
		12	13	21.39	21.82	21.78
		25	0	21.39	21.52	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23780/709	23790/710	23800/711
10MHz	QPSK	1	0	22.50	22.49	22.58
		1	25	23.04	23.05	22.94
		1	49	22.90	22.85	22.63
		25	0	21.53	21.55	21.34
		25	13	21.52	21.50	21.61
		25	25	21.49	21.91	21.87
		50	0	21.52	21.51	21.50
	16QAM	1	0	21.44	21.44	21.25
		1	25	21.40	21.39	21.52
		1	49	21.40	21.80	21.77
		25	0	21.42	21.42	21.40
		25	13	21.41	21.39	21.51
		25	25	21.38	21.81	21.77
		50	0	21.37	21.51	21.57

LTE FDD Band 17 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23755/706.5	23790/710	23825/713.5
5MHz	QPSK	1	0	18.03	18.03	18.13
		1	13	18.58	18.57	18.46
		1	24	18.41	18.36	18.14
		12	0	17.03	17.05	16.84
		12	6	17.02	16.99	17.10
		12	13	16.97	17.39	17.37
		25	0	17.02	17.02	17.00
	16QAM	1	0	16.93	16.93	16.74

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 88 of 370

		1	13	16.88	16.87	17.00
		1	24	16.93	17.33	17.30
		12	0	16.94	16.94	16.92
		12	6	16.92	16.91	17.04
		12	13	16.88	17.31	17.27
		25	0	16.87	17.00	17.08
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23780/709	23790/710	23800/711
10MHz	QPSK	1	0	18.00	17.99	18.08
		1	25	18.55	18.55	18.44
		1	49	18.40	18.35	18.13
		25	0	17.03	17.05	16.84
		25	13	17.02	17.00	17.11
		25	25	16.99	17.41	17.37
		50	0	17.02	17.01	17.00
	16QAM	1	0	16.94	16.94	16.75
		1	25	16.90	16.89	17.02
		1	49	16.90	17.30	17.27
		25	0	16.92	16.92	16.90
		25	13	16.91	16.89	17.01
		25	25	16.88	17.31	17.27
		50	0	16.87	17.01	17.07

LTE FDD Band 25 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26047/1850.7	26365/1882.5	26683/1914.3
1.4MHz	QPSK	1	0	22.30	22.55	23.22
		1	2	22.51	21.84	22.81
		1	5	22.89	22.37	22.18
		3	0	21.33	21.29	22.17
		3	2	21.29	20.89	21.45
		3	3	21.71	20.95	21.94
		6	0	21.61	21.72	21.20
	16QAM	1	0	21.34	21.87	22.30
		1	2	21.48	21.13	21.81
		1	5	21.96	21.68	21.37
		3	0	20.32	20.05	20.92
		3	2	20.23	19.95	20.44
		3	3	20.77	20.35	20.61
		6	0	20.57	20.20	20.66
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 89 of 370

				26055/1851.5	26365/1882.5	26675/1913.5
3MHz	QPSK	1	0	22.28	22.53	23.21
		1	13	22.50	21.82	22.80
		1	24	22.87	22.36	22.16
		12	0	21.32	21.28	22.16
		12	6	21.28	20.88	21.44
		12	13	21.69	20.94	21.93
		25	0	21.60	21.70	21.19
	16QAM	1	0	21.33	21.86	22.28
		1	13	21.47	21.12	21.80
		1	24	21.95	21.67	21.36
		12	0	20.31	20.04	20.91
		12	6	20.22	19.94	20.43
		12	13	20.75	20.34	20.60
		25	0	20.56	20.19	20.65
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26065/1852.5	26365/1882.5	26665/1912.5
5MHz	QPSK	1	0	22.27	22.52	23.20
		1	13	22.49	21.81	22.79
		1	24	22.86	22.34	22.15
		12	0	21.30	21.27	22.14
		12	6	21.27	20.87	21.43
		12	13	21.68	20.93	21.92
		25	0	21.59	21.69	21.18
	16QAM	1	0	21.32	21.85	22.27
		1	13	21.46	21.11	21.79
		1	24	21.94	21.66	21.35
		12	0	20.30	20.02	20.90
		12	6	20.21	19.93	20.42
		12	13	20.74	20.33	20.59
		25	0	20.54	20.18	20.63
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26090/1855	26365/1882.5	26640/1910
10MHz	QPSK	1	0	22.25	22.51	23.18
		1	25	22.48	21.80	22.78
		1	49	22.85	22.33	22.14
		25	0	21.29	21.25	22.13
		25	13	21.26	20.86	21.42
		25	25	21.67	20.92	21.91
		50	0	21.58	21.68	21.16
	16QAM	1	0	21.31	21.84	22.26
		1	25	21.45	21.10	21.78
		1	49	21.93	21.65	21.34
		25	0	20.28	20.01	20.89

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 90 of 370

		25	13	20.20	19.92	20.41
		25	25	20.73	20.32	20.58
		50	0	20.53	20.16	20.62
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26115/1857.5	26365/1882.5	26615/1907.5
15MHz	QPSK	1	0	22.25	22.51	23.18
		1	25	22.47	21.80	22.78
		1	49	22.85	22.33	22.14
		25	0	21.29	21.24	22.13
		25	13	21.25	20.86	21.42
		25	25	21.67	20.92	21.91
		50	0	21.58	21.68	21.15
	16QAM	1	0	21.31	21.84	22.26
		1	25	21.45	21.10	21.78
		1	49	21.93	21.64	21.34
		25	0	20.27	20.01	20.89
		25	13	20.20	19.92	20.41
		25	25	20.72	20.32	20.57
		50	0	20.53	20.15	20.62
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26140/1860	26365/1882.5	26590/1905
20MHz	QPSK	1	0	22.24	22.50	23.17
		1	50	22.46	21.79	22.77
		1	99	22.84	22.32	22.13
		50	0	21.28	21.23	22.12
		50	25	21.24	20.85	21.41
		50	50	21.66	20.91	21.90
		100	0	21.57	21.14	21.67
	16QAM	1	0	21.30	21.83	22.25
		1	50	21.44	21.09	21.77
		1	99	21.92	21.63	21.33
		50	0	20.26	20.00	20.88
		50	25	20.19	19.91	20.40
		50	50	20.71	20.31	20.56
		100	0	20.52	20.14	20.61

LTE FDD Band 25 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26047/1850.7	26365/1882.5	26683/1914.3
1.4MHz	QPSK	1	0	17.32	17.57	18.24
		1	2	17.52	16.85	17.82
		1	5	17.89	17.37	17.18

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 91 of 370

		3	0	16.32	16.28	17.16
		3	2	16.27	15.87	16.43
		3	3	16.68	15.92	16.91
		6	0	16.60	16.71	16.19
	16QAM	1	0	16.32	16.85	17.28
		1	2	16.45	16.10	16.78
		1	5	16.98	16.70	16.39
		3	0	15.33	15.06	15.93
		3	2	15.23	14.95	15.44
		3	3	15.76	15.34	15.60
		6	0	15.55	15.18	15.64
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26055/1851.5	26365/1882.5	26675/1913.5
3MHz	QPSK	1	0	17.30	17.55	18.23
		1	13	17.51	16.83	17.81
		1	24	17.87	17.36	17.16
		12	0	16.31	16.27	17.15
		12	6	16.26	15.86	16.42
		12	13	16.66	15.91	16.90
		25	0	16.59	16.69	16.18
	16QAM	1	0	16.31	16.84	17.26
		1	13	16.44	16.09	16.77
		1	24	16.97	16.69	16.38
		12	0	15.32	15.05	15.92
		12	6	15.22	14.94	15.43
		12	13	15.74	15.33	15.59
		25	0	15.54	15.17	15.63
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26065/1852.5	26365/1882.5	26665/1912.5
5MHz	QPSK	1	0	17.29	17.54	18.22
		1	13	17.50	16.82	17.80
		1	24	17.86	17.34	17.15
		12	0	16.29	16.26	17.13
		12	6	16.25	15.85	16.41
		12	13	16.65	15.90	16.89
		25	0	16.58	16.68	16.17
	16QAM	1	0	16.30	16.83	17.25
		1	13	16.43	16.08	16.76
		1	24	16.96	16.68	16.37
		12	0	15.31	15.03	15.91
		12	6	15.21	14.93	15.42
		12	13	15.73	15.32	15.58
		25	0	15.52	15.16	15.61
Bandwidth	Modulation	RB	RB offset	Channel/Frequency(MHz)		

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 92 of 370

		size		26090/1855	26365/1882.5	26640/1910
10MHz	QPSK	1	0	17.27	17.53	18.20
		1	25	17.49	16.81	17.79
		1	49	17.85	17.33	17.14
		25	0	16.28	16.24	17.12
		25	13	16.24	15.84	16.40
		25	25	16.64	15.89	16.88
		50	0	16.57	16.67	16.15
	16QAM	1	0	16.29	16.82	17.24
		1	25	16.42	16.07	16.75
		1	49	16.95	16.67	16.36
		25	0	15.29	15.02	15.90
		25	13	15.20	14.92	15.41
		25	25	15.72	15.31	15.57
		50	0	15.51	15.14	15.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26115/1857.5	26365/1882.5	26615/1907.5
15MHz	QPSK	1	0	17.27	17.53	18.20
		1	25	17.48	16.81	17.79
		1	49	17.85	17.33	17.14
		25	0	16.28	16.23	17.12
		25	13	16.23	15.84	16.40
		25	25	16.64	15.89	16.88
		50	0	16.57	16.67	16.14
	16QAM	1	0	16.29	16.82	17.24
		1	25	16.42	16.07	16.75
		1	49	16.95	16.66	16.36
		25	0	15.28	15.02	15.90
		25	13	15.20	14.92	15.41
		25	25	15.71	15.31	15.56
		50	0	15.51	15.13	15.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26140/1860	26365/1882.5	26590/1905
20MHz	QPSK	1	0	17.24	17.50	18.17
		1	50	17.46	16.79	17.77
		1	99	17.84	17.32	17.13
		50	0	16.28	16.23	17.12
		50	25	16.24	15.85	16.41
		50	50	16.66	15.91	16.90
		100	0	16.57	16.14	16.67
	16QAM	1	0	16.30	16.83	17.25
		1	50	16.44	16.09	16.77
		1	99	16.92	16.63	16.33

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 93 of 370

		50	0	15.26	15.00	15.88
		50	25	15.19	14.91	15.40
		50	50	15.71	15.31	15.56
		100	0	15.52	15.14	15.61

LTE FDD Band 26 (WiFi Off)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26697/814.7	26865/831.5	27033/848.3
1.4MHz	QPSK	1	0	23.48	23.90	23.25
		1	2	23.97	23.33	23.77
		1	5	23.20	23.36	23.02
		3	0	22.12	22.30	22.34
		3	2	22.10	22.35	22.55
		3	3	22.36	22.19	22.35
		6	0	22.19	22.21	22.35
	16QAM	1	0	22.42	22.64	22.63
		1	2	22.93	22.39	22.09
		1	5	22.16	22.43	22.45
		3	0	22.11	21.21	21.42
		3	2	22.52	21.22	21.61
		3	3	22.33	21.20	21.40
		6	0	22.23	21.20	21.41
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26705/815.5	26865/831.5	27025/847.5
3MHz	QPSK	1	0	23.47	23.99	23.24
		1	13	23.96	23.32	23.76
		1	24	23.19	23.35	23.01
		12	0	22.10	22.29	22.33
		12	6	22.09	22.34	22.54
		12	13	22.35	22.18	22.34
		25	0	22.18	22.19	22.34
	16QAM	1	0	22.41	22.63	22.62
		1	13	22.92	22.38	22.08
		1	24	22.15	22.42	22.44
		12	0	22.10	21.20	21.41
		12	6	22.50	21.21	21.60
		12	13	22.32	21.19	21.39
		25	0	22.22	21.19	21.40
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26715/816.5	26865/831.5	27015/846.5
5MHz	QPSK	1	0	23.46	23.98	23.22
		1	13	23.94	23.31	23.75

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 94 of 370

		1	24	23.18	23.34	23.00
		12	0	22.09	22.28	22.32
		12	6	22.08	22.33	22.53
		12	13	22.34	22.17	22.33
		25	0	22.17	22.18	22.33
	16QAM	1	0	22.40	22.62	22.60
		1	13	22.91	22.37	22.07
		1	24	22.14	22.40	22.43
		12	0	22.09	21.19	21.40
		12	6	22.49	21.20	21.59
		12	13	22.31	21.18	21.37
		25	0	22.20	21.18	21.39
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26750/820	26865/831.5	26990/844
10MHz	QPSK	1	0	23.45	23.97	23.21
		1	25	23.92	23.30	23.73
		1	49	23.17	23.32	22.99
		25	0	22.08	22.27	22.31
		25	13	22.07	22.32	22.52
		25	25	22.33	22.16	22.32
		50	0	22.16	22.17	22.32
	16QAM	1	0	22.39	22.61	22.59
		1	25	22.90	22.36	22.06
		1	49	22.12	22.39	22.42
		25	0	22.08	21.18	21.39
		25	13	22.48	21.18	21.58
		25	25	22.30	21.17	21.35
		50	0	22.19	21.17	21.38
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26775/822.5	26865/831.5	26965/841.5
15MHz	QPSK	1	0	23.44	23.95	23.20
		1	38	23.91	23.29	23.71
		1	74	23.15	23.31	22.98
		36	0	22.07	22.26	22.30
		36	18	22.06	22.31	22.51
		36	39	22.32	22.15	22.31
		75	0	22.15	22.16	22.31
	16QAM	1	0	22.37	22.60	22.58
		1	38	22.89	22.34	22.04
		1	74	22.11	22.38	22.41
		36	0	21.07	21.16	21.38
		36	18	21.47	21.17	21.57
		36	39	21.29	21.16	21.34

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 95 of 370

		75	0	21.17	21.16	21.37
--	--	----	---	-------	-------	-------

LTE FDD Band 26 (WiFi On)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26697/814.7	26865/831.5	27033/848.3
1.4MHz	QPSK	1	0	19.00	19.42	18.77
		1	2	19.48	18.84	19.28
		1	5	18.70	18.86	18.52
		3	0	17.61	17.79	17.83
		3	2	17.58	17.83	18.03
		3	3	17.83	17.66	17.82
	16QAM	6	0	17.68	17.70	17.84
		1	0	17.90	18.12	18.11
		1	2	18.40	17.86	17.56
		1	5	17.68	17.95	17.97
		3	0	17.62	16.72	16.93
		3	2	18.02	16.72	17.11
		3	3	17.82	16.69	16.89
		6	0	17.71	16.68	16.89
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26705/815.5	26865/831.5	27025/847.5
3MHz	QPSK	1	0	18.99	19.51	18.76
		1	13	19.47	18.83	19.27
		1	24	18.69	18.85	18.51
		12	0	17.59	17.78	17.82
		12	6	17.57	17.82	18.02
		12	13	17.82	17.65	17.81
		25	0	17.67	17.68	17.83
	16QAM	1	0	17.89	18.11	18.10
		1	13	18.39	17.85	17.55
		1	24	17.67	17.94	17.96
		12	0	17.61	16.71	16.92
		12	6	18.00	16.71	17.10
		12	13	17.81	16.68	16.88
		25	0	17.70	16.67	16.88
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26715/816.5	26865/831.5	27015/846.5
5MHz	QPSK	1	0	18.98	19.50	18.74
		1	13	19.45	18.82	19.26
		1	24	18.68	18.84	18.50
		12	0	17.58	17.77	17.81
		12	6	17.56	17.81	18.01

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 96 of 370

		12	13	17.81	17.64	17.80
		25	0	17.66	17.67	17.82
	16QAM	1	0	17.88	18.10	18.08
		1	13	18.38	17.84	17.54
		1	24	17.66	17.92	17.95
		12	0	17.60	16.70	16.91
		12	6	17.99	16.70	17.09
		12	13	17.80	16.67	16.86
		25	0	17.68	16.66	16.87
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26750/820	26865/831.5	26990/844
10MHz	QPSK	1	0	18.97	19.49	18.73
		1	25	19.43	18.81	19.24
		1	49	18.67	18.82	18.49
		25	0	17.57	17.76	17.80
		25	13	17.55	17.80	18.00
		25	25	17.80	17.63	17.79
		50	0	17.65	17.66	17.81
	16QAM	1	0	17.87	18.09	18.07
		1	25	18.37	17.83	17.53
		1	49	17.64	17.91	17.94
		25	0	17.59	16.69	16.90
		25	13	17.98	16.68	17.08
		25	25	17.79	16.66	16.84
		50	0	17.67	16.65	16.86
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26775/822.5	26865/831.5	26965/841.5
15MHz	QPSK	1	0	18.44	18.95	18.20
		1	38	18.91	18.29	18.71
		1	74	18.15	18.31	17.98
		36	0	17.57	17.76	17.80
		36	18	17.56	17.81	17.92
		36	39	17.82	17.65	17.81
		75	0	17.65	17.66	17.77
	16QAM	1	0	17.37	17.60	17.58
		1	38	17.89	17.34	17.04
		1	74	17.11	17.38	17.41
		36	0	16.57	16.66	16.88
		36	18	16.97	16.67	17.07
		36	39	16.79	16.66	16.84
		75	0	16.67	16.66	16.87

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 97 of 370

Antenna 2

GSM 850		Burst Conducted Power(dBm)			/	Average power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8		128/824.2	190/836.6	251/848.8
GSM		32.32	32.50	32.40	-9.03dB	23.29	23.47	23.37
GPRS (GMSK)	1Txslot	32.29	32.42	32.34	-9.03dB	23.26	23.39	23.31
	2Txslots	30.21	30.34	30.26	-6.02dB	24.19	24.32	24.24
	3Txslots	28.23	28.33	28.29	-4.26dB	23.97	24.07	24.03
	4Txslots	26.18	26.36	26.23	-3.01dB	23.17	23.35	23.22
EGPRS (GMSK)	1Txslot	32.26	32.50	32.37	-9.03dB	23.23	23.47	23.34
	2Txslots	30.19	30.41	30.27	-6.02dB	24.17	24.39	24.25
	3Txslots	28.02	28.13	28.21	-4.26dB	23.76	23.87	23.95
	4Txslots	26.71	26.84	26.96	-3.01dB	23.70	23.83	23.95
EGPRS (8PSK)	1Txslot	26.22	26.46	26.31	-9.03dB	17.19	17.43	17.28
	2Txslots	23.78	23.93	24.47	-6.02dB	17.76	17.91	18.45
	3Txslots	22.04	22.13	22.33	-4.26dB	17.78	17.87	18.07
	4Txslots	20.66	20.71	20.54	-3.01dB	17.65	17.70	17.53
GSM 1900 (Hotspot Close)		Burst Conducted Power(dBm)			/	Average power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8		512/1850.2	661/1880	810/1909.8
GSM		29.13	28.95	29.72	-9.03dB	20.10	19.92	20.69
GPRS (GMSK)	1Txslot	29.10	28.93	29.69	-9.03dB	20.07	19.90	20.66
	2Txslots	26.79	26.89	27.40	-6.02dB	20.77	20.87	21.38
	3Txslots	25.17	25.23	25.72	-4.26dB	20.91	20.97	21.46
	4Txslots	23.12	22.97	23.77	-3.01dB	20.11	19.96	20.76
EGPRS (GMSK)	1Txslot	29.13	28.91	29.73	-9.03dB	20.10	19.88	20.70
	2Txslots	27.22	26.98	27.45	-6.02dB	21.20	20.96	21.43
	3Txslots	25.49	25.26	25.77	-4.26dB	21.23	21.00	21.51
	4Txslots	23.51	23.44	23.61	-3.01dB	20.50	20.43	20.60
EGPRS (8PSK)	1Txslot	25.48	25.85	26.49	-9.03dB	16.45	16.82	17.46
	2Txslots	23.26	23.52	23.65	-6.02dB	17.24	17.50	17.63
	3Txslots	21.65	21.78	21.92	-4.26dB	17.39	17.52	17.66
	4Txslots	19.88	19.92	20.01	-3.01dB	16.87	16.91	17.00
GSM 1900 (Hotspot Open)		Burst Conducted Power(dBm)			/	Burst Conducted Power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8		512/1850.2	661/1880	810/1909.8
GSM		28.12	27.93	28.74	-9.03dB	19.09	18.90	19.71
GPRS (GMSK)	1Txslot	28.09	27.97	28.67	-9.03dB	19.06	18.94	19.64
	2Txslots	25.76	25.82	26.45	-6.02dB	19.74	19.80	20.43
	3Txslots	24.14	24.06	24.80	-4.26dB	19.88	19.80	20.54

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 98 of 370

	4Txslots	22.08	21.96	22.78	-3.01dB	19.07	18.95	19.77
EGPRS (GMSK)	1Txslot	28.12	27.89	28.77	-9.03dB	19.09	18.86	19.74
	2Txslots	26.24	25.93	26.41	-6.02dB	20.22	19.91	20.39
	3Txslots	24.49	24.26	24.77	-4.26dB	20.23	20.00	20.51
	4Txslots	22.51	22.44	22.61	-3.01dB	19.50	19.43	19.60
EGPRS (8PSK)	1Txslot	24.45	24.89	25.45	-9.03dB	15.42	15.86	16.42
	2Txslots	22.39	22.47	22.66	-6.02dB	16.37	16.45	16.64
	3Txslots	20.65	20.78	20.92	-4.26dB	16.39	16.52	16.66
	4Txslots	18.88	18.92	19.01	-3.01dB	15.87	15.91	16.00

Note:

2) Division Factors

To average the power, the division factor is as follows:

1Txslot = 1 transmit time slot out of 8 time slots

=> conducted power divided by (8/1) => -9.03 dB

2Txslots = 2 transmit time slots out of 8 time slots

=> conducted power divided by (8/2) => -6.02 dB

3Txslots = 3 transmit time slots out of 8 time slots

=> conducted power divided by (8/3) => -4.26 dB

4Txslots = 4 transmit time slots out of 8 time slots

=> conducted power divided by (8/4) => -3.01 dB

2) Average power numbers

The maximum power numbers are marks in bold.

UMTS Band II (Hotspot Close)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		9262/1852.4	9400/1880	9538/1907.6
RMC	12.2kbps RMC	22.73	23.07	23.18
	64kbps RMC	22.63	22.95	22.15
	144kbps RMC	22.18	22.52	22.62
	384kbps RMC	22.23	22.46	22.68
HSDPA	Sub - Test 1	22.55	22.87	23.04
	Sub - Test 2	21.49	21.83	21.99
	Sub - Test 3	21.03	21.34	21.46
	Sub - Test 4	20.86	21.18	21.42
HSUPA	Sub - Test 1	21.21	21.48	21.46
	Sub - Test 2	20.29	20.78	20.68
	Sub - Test 3	21.03	21.39	21.16
	Sub - Test 4	19.52	20.07	19.83
	Sub - Test 5	21.67	22.11	22.15

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 99 of 370

DC-HSDPA	Sub - Test 1	22.23	22.55	22.72
	Sub - Test 2	22.17	22.51	22.67
	Sub - Test 3	22.01	22.32	22.57
	Sub - Test 4	22.04	22.36	22.60
UMTS Band II (Hotspot Open)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		9262/1852.4	9400/1880	9538/1907.6
RMC	12.2kbps RMC	20.24	20.58	20.69
	64kbps RMC	20.14	20.46	20.46
	144kbps RMC	20.06	20.03	20.13
	384kbps RMC	20.07	20.09	20.19
HSDPA	Sub - Test 1	22.55	22.87	23.04
	Sub - Test 2	21.49	21.83	21.99
	Sub - Test 3	21.03	21.34	21.46
	Sub - Test 4	20.86	21.18	21.42
HSUPA	Sub - Test 1	18.73	19.00	18.98
	Sub - Test 2	17.81	18.30	18.20
	Sub - Test 3	18.55	18.91	18.68
	Sub - Test 4	17.04	17.59	17.35
	Sub - Test 5	19.19	19.63	19.67
DC-HSDPA	Sub - Test 1	19.77	20.09	20.26
	Sub - Test 2	19.71	20.05	20.21
	Sub - Test 3	19.55	19.86	20.11
	Sub - Test 4	19.58	19.90	20.14
UMTS Band IV (Hotspot Close)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		1312/1712.4	1413/1732.6	1513/1752.6
RMC	12.2kbps RMC	23.36	23.64	23.57
	64kbps RMC	22.57	22.86	22.90
	144kbps RMC	22.57	22.87	22.86
	384kbps RMC	22.64	22.51	22.53
HSDPA	Sub - Test 1	23.28	23.15	23.13
	Sub - Test 2	21.75	21.58	21.57
	Sub - Test 3	21.72	21.61	21.59
	Sub - Test 4	21.84	21.69	21.70
HSUPA	Sub - Test 1	21.40	21.18	21.33
	Sub - Test 2	19.97	19.79	19.95
	Sub - Test 3	20.64	20.35	20.54
	Sub - Test 4	19.56	19.96	19.86

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 100 of 370

	Sub - Test 5	21.46	21.23	21.36
DC-HSDPA	Sub - Test 1	21.96	21.83	21.81
	Sub - Test 2	21.93	21.76	21.75
	Sub - Test 3	21.80	21.69	21.67
	Sub - Test 4	21.82	21.67	21.68
UMTS Band IV (Hotspot Open)		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		1312/1712.4	1413/1732.6	1513/1752.6
RMC	12.2kbps RMC	21.87	22.15	22.08
	64kbps RMC	21.08	21.37	21.41
	144kbps RMC	21.08	21.38	21.37
	384kbps RMC	21.15	21.02	21.04
HSDPA	Sub - Test 1	21.80	21.67	21.65
	Sub - Test 2	20.27	20.10	20.09
	Sub - Test 3	20.24	20.13	20.11
	Sub - Test 4	20.36	20.21	20.22
HSUPA	Sub - Test 1	19.90	19.68	19.83
	Sub - Test 2	18.47	18.29	18.45
	Sub - Test 3	19.14	18.85	19.04
	Sub - Test 4	18.06	18.46	18.36
	Sub - Test 5	19.96	19.73	19.86
DC-HSDPA	Sub - Test 1	20.49	20.36	20.34
	Sub - Test 2	20.46	20.29	20.28
	Sub - Test 3	20.33	20.22	20.20
	Sub - Test 4	20.35	20.20	20.21
UMTS Band V		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		4132/826.4	4183/836.6	4233/846.6
RMC	12.2kbps RMC	23.51	23.30	23.32
	64kbps RMC	22.92	22.71	22.76
	144kbps RMC	22.29	22.32	22.38
	384kbps RMC	22.95	22.73	22.82
HSDPA	Sub - Test 1	23.28	23.15	23.13
	Sub - Test 2	22.25	22.08	22.07
	Sub - Test 3	22.12	22.01	21.69
	Sub - Test 4	22.14	21.99	22.00
HSUPA	Sub - Test 1	21.60	21.38	21.53
	Sub - Test 2	20.07	20.89	20.05
	Sub - Test 3	21.64	21.35	21.54

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 101 of 370

	Sub - Test 4	20.84	20.74	20.88
	Sub - Test 5	22.46	22.23	22.36
DC-HSDPA	Sub - Test 1	22.99	22.86	22.84
	Sub - Test 2	22.96	22.79	22.78
	Sub - Test 3	22.83	22.72	22.70
	Sub - Test 4	22.85	22.70	22.71

LTE FDD Band 2 (Hotspot Close)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18607/1850.7	18900/1880	19193/1909.3
1.4MHz	QPSK	1	0	22.01	22.37	22.23
		1	2	22.14	21.93	22.74
		1	5	22.15	21.87	22.08
		3	0	21.08	21.01	21.47
		3	2	21.09	20.78	21.46
		3	3	20.97	20.68	21.45
		6	0	21.15	20.77	21.40
	16QAM	1	0	22.04	22.16	22.27
		1	2	21.64	21.76	21.87
		1	5	21.62	21.74	21.85
		3	0	20.87	20.99	21.10
		3	2	20.53	20.65	20.76
		3	3	20.41	20.53	20.64
		6	0	19.62	19.74	19.85
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18615/1851.5	18900/1880	19185/1908.5
3MHz	QPSK	1	0	22.17	22.53	22.39
		1	7	22.30	22.09	22.90
		1	14	22.31	22.03	22.24
		8	0	22.13	22.06	22.52
		8	4	22.14	21.83	22.51
		8	7	22.02	21.73	22.50
		15	0	21.31	20.93	21.56
	16QAM	1	0	21.48	21.60	21.71
		1	7	21.08	21.20	21.31
		1	14	21.06	21.18	21.29
		8	0	21.03	21.15	21.26
		8	4	20.69	20.81	20.92
		8	7	20.57	20.69	20.80
		15	0	19.78	19.90	20.01

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 102 of 370

Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18625/1852.5	18900/1880	19175/1907.5
5MHz	QPSK	1	0	22.14	22.50	22.36
		1	13	22.27	22.06	22.87
		1	24	22.28	22.00	22.21
		12	0	21.21	21.14	21.60
		12	6	21.22	20.91	21.59
		12	13	21.10	20.81	21.58
		25	0	21.28	20.90	21.53
	16QAM	1	0	22.17	22.29	22.40
		1	13	21.77	21.89	22.00
		1	24	21.75	21.87	21.98
		12	0	21.00	21.12	21.23
		12	6	20.66	20.78	20.89
		12	13	20.54	20.66	20.77
		25	0	19.75	19.87	19.98
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18650/1855	18900/1880	19150/1905
10MHz	QPSK	1	0	22.15	22.51	22.37
		1	25	22.28	22.07	22.88
		1	49	22.29	22.01	22.22
		25	0	21.22	21.15	21.61
		25	13	21.23	20.92	21.60
		25	25	21.11	20.82	21.59
		50	0	21.29	20.91	21.54
	16QAM	1	0	22.18	22.30	22.41
		1	25	21.78	21.90	22.01
		1	49	21.76	21.88	21.99
		25	0	21.01	21.13	21.24
		25	13	20.67	20.79	20.90
		25	25	20.55	20.67	20.78
		50	0	19.76	19.88	19.99
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18675/1857.5	18900/1880	19125/1902.5
15MHz	QPSK	1	0	22.12	22.48	22.34
		1	38	22.25	22.04	22.85
		1	74	22.26	21.98	22.19
		36	0	21.19	21.12	21.58
		36	18	21.20	20.89	21.57
		36	39	21.08	20.79	21.56
		75	0	21.26	20.88	21.51
	16QAM	1	0	22.15	22.27	22.38
		1	38	21.75	21.87	21.98
		1	74	21.73	21.85	21.96

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 103 of 370

		36	0	20.98	21.10	21.21
		36	18	20.64	20.76	20.87
		36	39	20.52	20.64	20.75
		75	0	19.73	19.85	19.96
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18700/1860	18900/1880	19100/1900
20MHz	QPSK	1	0	22.01	22.37	22.23
		1	50	22.14	21.93	22.74
		1	99	22.15	21.87	22.08
		50	0	21.08	21.46	21.47
		50	25	21.09	20.78	21.01
		50	50	20.97	20.68	21.45
		100	0	21.15	20.77	21.40
	16QAM	1	0	22.04	22.16	22.27
		1	50	21.64	21.76	21.87
		1	99	21.62	21.74	21.85
		50	0	20.87	20.99	21.10
		50	25	20.53	20.65	20.76
		50	50	20.41	20.53	20.64
		100	0	19.62	19.74	19.85

LTE FDD Band 2 (Hotspot Open)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18607/1850.7	18900/1880	19193/1909.3
1.4MHz	QPSK	1	0	17.50	17.86	17.72
		1	2	17.62	17.41	18.22
		1	5	17.62	17.34	17.55
		3	0	16.54	16.47	16.93
		3	2	16.55	16.24	16.92
		3	3	16.42	16.13	16.90
		6	0	16.59	16.21	16.84
	16QAM	1	0	17.47	17.59	17.70
		1	2	17.06	17.18	17.29
		1	5	17.11	17.23	17.34
		3	0	16.35	16.47	16.58
		3	2	16.00	16.12	16.23
		3	3	15.87	15.99	16.10
		6	0	15.10	15.22	15.33

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 104 of 370

Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18615/1851.5	18900/1880	19185/1908.5
3MHz	QPSK	1	0	17.62	17.98	17.84
		1	7	17.74	17.53	18.34
		1	14	17.74	17.46	17.67
		8	0	17.55	17.48	17.94
		8	4	17.63	17.32	18.00
		8	7	17.50	17.21	17.98
		15	0	16.78	16.40	17.03
	16QAM	1	0	16.94	17.06	17.17
		1	7	16.56	16.68	16.79
		1	14	16.53	16.65	16.76
		8	0	16.49	16.61	16.72
		8	4	16.14	16.26	16.37
		8	7	16.01	16.13	16.24
		15	0	15.21	15.33	15.44
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18625/1852.5	18900/1880	19175/1907.5
5MHz	QPSK	1	0	17.61	17.97	17.83
		1	13	17.73	17.52	18.33
		1	24	17.77	17.49	17.70
		12	0	16.69	16.62	17.08
		12	6	16.69	16.38	17.06
		12	13	16.59	16.30	17.07
		25	0	16.76	16.38	17.01
	16QAM	1	0	17.64	17.76	17.87
		1	13	17.23	17.35	17.46
		1	24	17.17	17.29	17.40
		12	0	16.41	16.53	16.64
		12	6	16.06	16.18	16.29
		12	13	16.03	16.15	16.26
		25	0	15.23	15.35	15.46
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18650/1855	18900/1880	19150/1905
10MHz	QPSK	1	0	17.61	17.97	17.83
		1	25	17.73	17.52	18.33
		1	49	17.73	17.45	17.66
		25	0	16.65	16.58	17.04
		25	13	16.65	16.34	17.02
		25	25	16.52	16.23	17.00
		50	0	16.69	16.31	16.94
	16QAM	1	0	17.68	17.80	17.91
		1	25	17.27	17.39	17.50
		1	49	17.24	17.36	17.47

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 105 of 370

		25	0	16.48	16.60	16.71
		25	13	16.13	16.25	16.36
		25	25	16.00	16.12	16.23
		50	0	15.20	15.32	15.43
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18675/1857.5	18900/1880	19125/1902.5
15MHz	QPSK	1	0	17.59	17.95	17.81
		1	38	17.71	17.50	18.31
		1	74	17.76	17.48	17.69
		36	0	16.68	16.61	17.07
		36	18	16.68	16.37	17.05
		36	39	16.55	16.26	17.03
		75	0	16.72	16.34	16.97
	16QAM	1	0	17.60	17.72	17.83
		1	38	17.19	17.31	17.42
		1	74	17.16	17.28	17.39
		36	0	16.40	16.52	16.63
		36	18	16.11	16.23	16.34
		36	39	15.98	16.10	16.21
		75	0	15.18	15.30	15.41
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				18700/1860	18900/1880	19100/1900
20MHz	QPSK	1	0	17.48	17.84	17.70
		1	50	17.60	17.39	18.20
		1	99	17.61	17.32	17.53
		50	0	16.56	16.95	16.97
		50	25	16.58	16.27	16.51
		50	50	16.45	16.16	16.93
		100	0	16.62	16.24	16.87
	16QAM	1	0	17.50	17.62	17.73
		1	50	17.09	17.21	17.32
		1	99	17.06	17.18	17.29
		50	0	16.34	16.46	16.57
		50	25	15.99	16.11	16.22
		50	50	15.86	15.98	16.09
		100	0	15.06	15.18	15.29

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 106 of 370

LTE FDD Band 4 (Hotspot Close)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19957/1710.7	20175/1732.5	20393/1754.3
1.4MHz	QPSK	1	0	21.80	22.48	22.35
		1	2	21.68	22.13	21.98
		1	5	21.46	22.05	22.29
		3	0	21.74	22.40	21.91
		3	2	22.10	22.19	21.92
		3	3	22.31	21.99	21.93
		6	0	21.01	21.36	20.97
	16QAM	1	0	21.12	21.01	20.92
		1	2	20.74	20.63	20.54
		1	5	20.77	20.66	20.57
		3	0	20.37	20.26	20.17
		3	2	20.90	20.79	20.70
		3	3	20.87	20.76	20.67
		6	0	20.89	20.78	20.69
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19965/1711.5	20175/1732.5	20385/1753.5
3MHz	QPSK	1	0	21.77	22.45	22.32
		1	13	21.65	22.10	21.95
		1	24	21.43	22.02	22.26
		12	0	21.25	21.91	21.42
		12	6	21.61	21.70	21.43
		12	13	21.82	21.50	21.44
		25	0	21.10	21.45	21.06
	16QAM	1	0	21.59	21.48	21.39
		1	13	21.21	21.10	21.01
		1	24	21.24	21.13	21.04
		12	0	20.34	20.23	20.14
		12	6	21.37	21.26	21.17
		12	13	21.34	21.23	21.14
		25	0	21.36	21.25	21.16
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19975/1712.5	20175/1732.5	20375/1752.5
5MHz	QPSK	1	0	21.78	22.46	22.33
		1	13	21.66	22.11	21.96
		1	24	21.44	22.03	22.27
		12	0	20.76	21.42	20.93
		12	6	21.12	21.21	20.94
		12	13	21.33	21.01	20.95

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 107 of 370

		25	0	21.11	21.46	21.07
	16QAM	1	0	21.60	21.49	21.40
		1	13	21.22	21.11	21.02
		1	24	21.25	21.14	21.05
		12	0	20.35	20.24	20.15
		12	6	21.38	21.27	21.18
		12	13	21.35	21.24	21.15
		25	0	21.37	21.26	21.17
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20000/1715	20175/1732.5	20350/1750
10MHz	QPSK	1	0	21.74	22.42	22.29
		1	25	21.62	22.07	21.92
		1	49	21.40	21.99	22.23
		25	0	20.72	21.38	20.89
		25	13	21.08	21.17	20.90
		25	25	21.29	20.97	20.91
		50	0	21.07	21.42	21.03
	16QAM	1	0	21.56	21.45	21.36
		1	25	21.18	21.07	20.98
		1	49	21.21	21.10	21.01
		25	0	20.31	20.20	20.11
		25	13	21.34	21.23	21.14
		25	25	21.31	21.20	21.11
		50	0	21.33	21.22	21.13
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20025/1717.5	20175/1732.5	20325/1747.5
15MHz	QPSK	1	0	21.76	22.44	22.31
		1	38	21.64	22.09	21.94
		1	74	21.42	22.01	22.25
		36	0	20.74	21.40	20.91
		36	18	21.10	21.19	20.92
		36	39	21.31	20.99	20.93
		75	0	21.09	21.44	21.05
	16QAM	1	0	21.58	21.47	21.38
		1	38	21.20	21.09	21.00
		1	74	21.23	21.12	21.03
		36	0	20.33	20.22	20.13
		36	18	21.36	21.25	21.16
		36	39	21.33	21.22	21.13
		75	0	21.35	21.24	21.15
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20050/1720	20175/1732.5	20300/1745
20MHz	QPSK	1	0	21.63	22.31	22.18

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 108 of 370

		1	50	21.51	21.96	21.81
		1	99	21.29	21.88	22.12
		50	0	20.61	21.27	20.78
		50	25	20.97	21.06	20.79
		50	50	21.18	20.86	20.80
		100	0	20.96	21.31	20.92
	16QAM	1	0	21.45	21.34	21.25
		1	50	21.07	20.96	20.87
		1	99	21.10	20.99	20.90
		50	0	20.20	20.09	20.00
		50	25	21.23	21.12	21.03
		50	50	21.20	21.09	21.00
		100	0	21.22	21.11	21.02

LTE FDD Band 4 (Hotspot Open)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19957/1710.7	20175/1732.5	20393/1754.3
1.4MHz	QPSK	1	0	20.79	21.47	21.34
		1	2	20.66	21.11	20.96
		1	5	20.43	21.02	21.26
		3	0	20.70	21.36	20.87
		3	2	21.06	21.15	20.88
		3	3	21.26	20.94	20.88
		6	0	19.95	20.30	19.91
	16QAM	1	0	20.05	19.94	19.85
		1	2	19.66	19.55	19.46
		1	5	19.76	19.65	19.56
		3	0	19.35	19.24	19.15
		3	2	19.87	19.76	19.67
		3	3	19.83	19.72	19.63
		6	0	19.87	19.76	19.67
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19965/1711.5	20175/1732.5	20385/1753.5
3MHz	QPSK	1	0	20.72	21.40	21.27
		1	13	20.59	21.04	20.89
		1	24	20.36	20.95	21.19
		12	0	20.17	20.83	20.34
		12	6	20.60	20.69	20.42
		12	13	20.80	20.48	20.42
		25	0	20.07	20.42	20.03

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 109 of 370

		1	0	20.55	20.44	20.35
		1	13	20.19	20.08	19.99
		1	24	20.21	20.10	20.01
	16QAM	12	0	19.30	19.19	19.10
		12	6	20.32	20.21	20.12
		12	13	20.28	20.17	20.08
		25	0	20.29	20.18	20.09
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				19975/1712.5	20175/1732.5	20375/1752.5
5MHz	QPSK	1	0	20.75	21.43	21.30
		1	13	20.62	21.07	20.92
		1	24	20.43	21.02	21.26
		12	0	19.74	20.40	19.91
		12	6	20.09	20.18	19.91
		12	13	20.32	20.00	19.94
		25	0	20.09	20.44	20.05
	16QAM	1	0	20.57	20.46	20.37
		1	13	20.18	20.07	19.98
		1	24	20.17	20.06	19.97
		12	0	19.26	19.15	19.06
		12	6	20.28	20.17	20.08
		12	13	20.34	20.23	20.14
		25	0	20.35	20.24	20.15
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20000/1715	20175/1732.5	20350/1750
10MHz	QPSK	1	0	20.70	21.38	21.25
		1	25	20.57	21.02	20.87
		1	49	20.34	20.93	21.17
		25	0	19.65	20.31	19.82
		25	13	20.00	20.09	19.82
		25	25	20.20	19.88	19.82
		50	0	19.97	20.32	19.93
	16QAM	1	0	20.56	20.45	20.36
		1	25	20.17	20.06	19.97
		1	49	20.19	20.08	19.99
		25	0	19.28	19.17	19.08
		25	13	20.30	20.19	20.10
		25	25	20.26	20.15	20.06
		50	0	20.27	20.16	20.07
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20025/1717.5	20175/1732.5	20325/1747.5
15MHz	QPSK	1	0	20.73	21.41	21.28
		1	38	20.60	21.05	20.90
		1	74	20.42	21.01	21.25

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 110 of 370

		36	0	19.73	20.39	19.90	
		36	18	20.08	20.17	19.90	
		36	39	20.28	19.96	19.90	
		75	0	20.05	20.40	20.01	
	16QAM	1	0	20.53	20.42	20.33	
		1	38	20.14	20.03	19.94	
		1	74	20.16	20.05	19.96	
		36	0	19.25	19.14	19.05	
		36	18	20.33	20.22	20.13	
		36	39	20.29	20.18	20.09	
		75	0	20.30	20.19	20.10	
	Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
					20050/1720	20175/1732.5	20300/1745
20MHz	QPSK	1	0	20.60	21.28	21.15	
		1	50	20.47	20.92	20.77	
		1	99	20.24	20.83	21.07	
		50	0	19.61	20.27	19.76	
		50	25	19.96	20.05	19.79	
		50	50	20.16	19.84	19.88	
		100	0	19.93	20.28	19.89	
	16QAM	1	0	20.41	20.30	20.21	
		1	50	20.02	19.91	19.82	
		1	99	20.04	19.93	19.84	
		50	0	19.17	19.06	18.97	
		50	25	20.19	20.08	19.99	
		50	50	20.15	20.04	19.95	
		100	0	20.16	20.05	19.96	

LTE FDD Band 5				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20407/824.7	20525/836.5	20643/848.3
1.4MHz	QPSK	1	0	22.99	22.79	23.23
		1	2	23.49	23.23	23.59
		1	5	23.05	23.52	22.99
		3	0	23.01	22.54	23.08
		3	2	22.95	22.63	23.00
		3	3	22.83	22.73	22.88
		6	0	22.03	21.90	22.10
	16QAM	1	0	22.14	21.90	22.51
		1	2	22.66	22.43	22.74
		1	5	22.18	22.75	22.08

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 111 of 370

		3	0	21.27	20.82	21.10
		3	2	21.35	21.04	21.25
		3	3	21.09	21.03	21.11
		6	0	21.83	21.74	21.74
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20415/825.5	20525/836.5	20635/847.5
3MHz	QPSK	1	0	22.98	22.78	23.22
		1	13	23.48	23.22	23.58
		1	24	23.04	23.51	22.98
		12	0	23.06	22.59	23.13
		12	6	23.00	22.68	23.05
		12	13	22.88	22.78	22.93
		25	0	22.02	21.88	22.09
	16QAM	1	0	22.12	21.89	22.50
		1	13	22.65	22.42	22.73
		1	24	22.17	22.74	22.07
		12	0	21.26	20.81	21.09
		12	6	21.34	21.02	21.24
		12	13	21.08	21.02	21.10
		25	0	21.89	21.79	21.79
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20425/826.5	20525/836.5	20625/846.5
5MHz	QPSK	1	0	23.00	22.79	23.24
		1	13	23.50	23.23	23.60
		1	24	23.06	23.52	23.00
		12	0	22.22	21.74	22.29
		12	6	22.16	21.83	22.21
		12	13	22.03	21.93	22.09
		25	0	22.04	21.90	22.11
	16QAM	1	0	22.15	21.90	22.52
		1	13	22.67	22.43	22.75
		1	24	22.19	22.75	22.09
		12	0	21.28	20.82	21.11
		12	6	21.36	21.04	21.26
		12	13	21.10	21.03	21.12
		25	0	21.05	20.94	20.95
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20450/829	20525/836.5	20600/844
10MHz	QPSK	1	0	22.87	22.67	23.12
		1	25	23.37	23.11	23.48
		1	49	22.93	23.41	22.88
		25	0	22.09	21.62	22.16
		25	13	22.03	21.71	22.09

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 112 of 370

		25	25	21.91	21.81	21.96
		50	0	21.91	21.78	21.99
	16QAM	1	0	22.02	21.78	22.39
		1	25	22.55	22.32	22.63
		1	49	22.07	22.63	21.96
		25	0	21.15	20.70	20.98
		25	13	21.24	20.92	21.13
		25	25	20.97	20.92	20.99
		50	0	20.92	20.83	20.82

LTE FDD Band 7 (Hotspot Close)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20775/2502.5	21100/2535	21425/2567.5
5MHz	QPSK	1	0	22.22	22.61	22.85
		1	13	22.84	22.78	22.78
		1	24	22.73	22.72	22.52
		12	0	21.66	21.85	21.65
		12	6	21.72	21.85	21.63
		12	13	22.04	21.85	21.63
		25	0	21.77	21.82	21.58
	16QAM	1	0	21.87	21.92	21.68
		1	13	21.87	21.93	21.68
		1	24	21.87	21.93	21.68
		12	0	20.77	20.82	20.58
		12	6	20.77	20.82	20.58
		12	13	20.77	20.82	20.58
		25	0	20.67	20.72	20.48
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20800/2505	21100/2535	21400/2565
10MHz	QPSK	1	0	22.23	22.62	22.86
		1	25	22.85	22.79	22.79
		1	49	22.74	22.73	22.53
		25	0	21.67	21.85	21.65
		25	13	21.73	21.86	21.63
		25	25	22.04	21.85	21.64
		50	0	21.77	21.83	21.58
	16QAM	1	0	21.87	21.93	21.68
		1	25	21.88	21.93	21.69
		1	49	21.88	21.93	21.69
		25	0	20.77	20.83	20.58

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 113 of 370

		25	13	20.77	20.83	20.58
		25	25	20.77	20.83	20.58
		50	0	20.67	20.72	20.48
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20825/2507.5	21100/2535	21375/2562.5
15MHz	QPSK	1	0	22.24	22.63	22.87
		1	38	22.86	22.80	22.80
		1	74	22.75	22.74	22.54
		36	0	21.68	21.87	21.67
		36	18	21.74	21.88	21.65
		36	39	22.06	21.87	21.65
		75	0	21.79	21.84	21.60
	16QAM	1	0	21.89	21.95	21.70
		1	38	21.89	21.95	21.70
		1	74	21.90	21.95	21.71
		36	0	20.79	20.84	20.60
		36	18	20.79	20.84	20.60
		36	39	20.79	20.84	20.60
		75	0	20.69	20.74	20.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20850/2510	21100/2535	21350/2560
20MHz	QPSK	1	0	22.12	22.51	22.75
		1	50	22.74	22.68	22.68
		1	99	22.63	22.62	22.42
		50	0	21.56	21.74	21.55
		50	25	21.62	21.75	21.53
		50	50	21.94	21.74	21.53
		100	0	21.67	21.72	21.48
	16QAM	1	0	21.77	21.82	21.58
		1	50	21.77	21.82	21.58
		1	99	21.77	21.82	21.58
		50	0	20.67	20.72	20.48
		50	25	20.67	20.72	20.48
		50	50	20.67	20.72	20.48
		100	0	20.57	20.62	20.38

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 114 of 370

LTE FDD Band 7 (Hotspot Open)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20775/2502.5	21100/2535	21425/2567.5
5MHz	QPSK	1	0	21.71	22.10	22.34
		1	13	22.32	22.26	22.26
		1	24	22.20	22.19	21.99
		12	0	21.12	21.31	21.11
		12	6	21.18	21.31	21.09
		12	13	21.49	21.30	21.08
		25	0	21.21	21.26	21.02
	16QAM	1	0	21.30	21.35	21.11
		1	13	21.29	21.35	21.10
		1	24	21.36	21.42	21.17
		12	0	20.25	20.30	20.06
		12	6	20.24	20.29	20.05
		12	13	20.23	20.28	20.04
		25	0	20.15	20.20	19.96
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20800/2505	21100/2535	21400/2565
10MHz	QPSK	1	0	21.68	22.07	22.31
		1	25	22.29	22.23	22.23
		1	49	22.17	22.16	21.96
		25	0	21.09	21.27	21.07
		25	13	21.22	21.35	21.12
		25	25	21.52	21.33	21.12
		50	0	21.24	21.30	21.05
	16QAM	1	0	21.33	21.39	21.14
		1	25	21.36	21.41	21.17
		1	49	21.35	21.40	21.16
		25	0	20.23	20.29	20.04
		25	13	20.22	20.28	20.03
		25	25	20.21	20.27	20.02
		50	0	20.10	20.15	19.91
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20825/2507.5	21100/2535	21375/2562.5
15MHz	QPSK	1	0	21.71	22.10	22.34
		1	38	22.32	22.26	22.26
		1	74	22.24	22.23	22.03
		36	0	21.16	21.35	21.15
		36	18	21.21	21.35	21.12
		36	39	21.55	21.36	21.14

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 115 of 370

	16QAM	75	0	21.27	21.32	21.08
		1	0	21.36	21.42	21.17
		1	38	21.35	21.41	21.16
		1	74	21.32	21.37	21.13
		36	0	20.20	20.25	20.01
		36	18	20.19	20.24	20.00
		36	39	20.28	20.33	20.09
		75	0	20.17	20.22	19.98
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20850/2510	21100/2535	21350/2560
20MHz	QPSK	1	0	21.58	21.97	22.21
		1	50	22.19	22.13	22.13
		1	99	22.07	22.06	21.86
		50	0	20.99	21.17	20.98
		50	25	21.04	21.18	20.95
		50	50	21.35	21.15	20.94
		100	0	21.07	21.12	20.88
	16QAM	1	0	21.27	21.32	21.08
		1	50	21.26	21.31	21.07
		1	99	21.25	21.30	21.06
		50	0	20.14	20.19	19.95
		50	25	20.13	20.18	19.94
		50	50	20.12	20.17	19.93
		100	0	20.01	20.06	19.82

LTE FDD Band 12				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23017/699.7	23095/707.5	23173/715.3
1.4MHz	QPSK	1	0	22.32	22.52	22.50
		1	2	22.79	22.93	22.87
		1	5	22.58	22.75	22.51
		3	0	21.29	21.34	21.41
		3	2	21.24	21.52	21.49
		3	3	21.16	21.25	21.35
		6	0	21.16	21.15	21.22
	16QAM	1	0	-22.17	-22.40	-22.41
		1	2	-22.70	-22.84	-22.76
		1	5	-22.47	-22.62	-22.42
		3	0	-21.20	-21.25	-21.23
		3	2	-21.08	-21.43	-21.42
		3	3	-21.07	-21.06	-21.24
		6	0	-21.03	-21.07	-21.14

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 116 of 370

Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23025/700.5	23095/707.5	23165/714.5
3MHz	QPSK	1	0	22.31	22.49	22.49
		1	7	22.78	22.92	22.86
		1	14	22.55	22.74	22.50
		8	0	21.28	21.33	21.39
		8	4	21.23	21.50	21.48
		8	7	21.15	21.24	21.32
		15	0	21.13	21.14	21.21
	16QAM	1	0	-22.18	-22.43	-22.42
		1	7	-22.72	-22.85	-22.77
		1	14	-22.48	-22.64	-22.43
		8	0	-21.21	-21.26	-21.26
		8	4	-21.11	-21.44	-21.43
		8	7	-21.08	-21.09	-21.25
		15	0	-21.05	-21.08	-21.15
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23035/701.5	23095/707.5	23155/713.5
5MHz	QPSK	1	0	22.28	22.48	22.48
		1	13	22.77	22.91	22.84
		1	24	22.54	22.72	22.49
		12	0	21.27	21.32	21.36
		12	6	21.20	21.49	21.47
		12	13	21.14	21.21	21.31
		25	0	21.11	21.13	21.20
	16QAM	1	0	-22.21	-22.44	-22.43
		1	13	-22.73	-22.86	-22.79
		1	24	-22.49	-22.66	-22.44
		12	0	-21.22	-21.27	-21.29
		12	6	-21.14	-21.45	-21.44
		12	13	-21.09	-21.12	-21.26
		25	0	-21.07	-21.09	-21.16
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23060/704	23095/707.5	23130/711
10MHz	QPSK	1	0	22.27	22.47	22.46
		1	25	22.76	22.90	22.83
		1	49	22.51	22.70	22.48
		25	0	21.26	21.31	21.33
		25	13	21.19	21.48	21.46
		25	25	21.13	21.18	21.30
		50	0	21.10	21.12	21.19
	16QAM	1	0	-22.24	-22.45	-22.44
		1	25	-22.74	-22.87	-22.81

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 117 of 370

		1	49	-22.50	-22.68	-22.45
		25	0	-21.23	-21.28	-21.32
		25	13	-21.17	-21.46	-21.45
		25	25	-21.10	-21.15	-21.27
		50	0	-21.09	-21.10	-21.17

LTE FDD Band 17				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23755/706.5	23790/710	23825/713.5
5MHz	QPSK	1	0	22.48	22.48	22.58
		1	13	23.04	23.03	22.92
		1	24	22.88	22.83	22.61
		12	0	21.51	21.53	21.32
		12	6	21.51	21.48	21.59
		12	13	21.47	21.89	21.87
		25	0	21.50	21.50	21.48
	16QAM	1	0	21.41	21.43	21.22
		1	13	21.39	21.38	21.49
		1	24	21.37	21.78	21.75
		12	0	21.40	21.39	21.38
		12	6	21.39	21.39	21.51
		12	13	21.37	21.78	21.75
		25	0	21.36	21.49	21.56
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				23780/709	23790/710	23800/711
10MHz	QPSK	1	0	22.47	22.46	22.55
		1	25	23.02	23.02	22.91
		1	49	22.87	22.82	22.60
		25	0	21.50	21.52	21.31
		25	13	21.49	21.47	21.58
		25	25	21.46	21.88	21.84
		50	0	21.49	21.48	21.47
	16QAM	1	0	21.40	21.42	21.21
		1	25	21.38	21.37	21.48
		1	49	21.36	21.77	21.74
		25	0	21.39	21.38	21.37
		25	13	21.38	21.37	21.48
		25	25	21.36	21.77	21.74
		50	0	21.34	21.48	21.53

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 118 of 370

LTE FDD Band 25 (Hotspot Close)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26047/1850.7	26365/1882.5	26683/1914.3
1.4MHz	QPSK	1	0	22.27	22.52	23.19
		1	2	22.48	21.81	22.78
		1	5	22.86	22.34	22.15
		3	0	21.30	21.26	22.14
		3	2	21.26	20.86	21.42
		3	3	21.68	20.92	21.91
		6	0	21.58	21.69	21.17
	16QAM	1	0	21.30	21.85	22.26
		1	2	21.46	21.11	21.77
		1	5	21.92	21.65	21.34
		3	0	20.29	20.01	20.89
		3	2	20.20	19.93	20.41
		3	3	20.75	20.31	20.58
		6	0	20.54	20.17	20.62
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26055/1851.5	26365/1882.5	26675/1913.5
3MHz	QPSK	1	0	22.25	22.50	23.18
		1	13	22.47	21.79	22.77
		1	24	22.84	22.33	22.13
		12	0	21.29	21.25	22.13
		12	6	21.25	20.85	21.41
		12	13	21.66	20.91	21.90
		25	0	21.57	21.67	21.16
	16QAM	1	0	21.29	21.84	22.24
		1	13	21.45	21.10	21.76
		1	24	21.91	21.64	21.33
		12	0	20.28	20.00	20.88
		12	6	20.19	19.92	20.40
		12	13	20.73	20.30	20.57
		25	0	20.53	20.16	20.61
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26065/1852.5	26365/1882.5	26665/1912.5
5MHz	QPSK	1	0	22.24	22.49	23.17
		1	13	22.46	21.78	22.76
		1	24	22.83	22.31	22.12
		12	0	21.27	21.24	22.11
		12	6	21.24	20.84	21.40
		12	13	21.65	20.90	21.89

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 119 of 370

		25	0	21.56	21.66	21.15
	16QAM	1	0	21.28	21.83	22.23
		1	13	21.44	21.09	21.75
		1	24	21.90	21.63	21.32
		12	0	20.27	19.98	20.87
		12	6	20.18	19.91	20.39
		12	13	20.72	20.29	20.56
		25	0	20.51	20.15	20.59
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26090/1855	26365/1882.5	26640/1910
10MHz	QPSK	1	0	22.22	22.48	23.15
		1	25	22.45	21.77	22.75
		1	49	22.82	22.30	22.11
		25	0	21.26	21.22	22.10
		25	13	21.23	20.83	21.39
		25	25	21.64	20.89	21.88
		50	0	21.55	21.65	21.13
	16QAM	1	0	21.27	21.82	22.22
		1	25	21.43	21.08	21.74
		1	49	21.89	21.62	21.31
		25	0	20.25	19.97	20.86
		25	13	20.17	19.90	20.38
		25	25	20.71	20.28	20.55
		50	0	20.50	20.13	20.58
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26115/1857.5	26365/1882.5	26615/1907.5
15MHz	QPSK	1	0	22.22	22.48	23.15
		1	25	22.44	21.77	22.75
		1	49	22.82	22.30	22.11
		25	0	21.26	21.21	22.10
		25	13	21.22	20.83	21.39
		25	25	21.64	20.89	21.88
		50	0	21.55	21.65	21.12
	16QAM	1	0	21.27	21.82	22.22
		1	25	21.43	21.08	21.74
		1	49	21.89	21.61	21.31
		25	0	20.24	19.97	20.86
		25	13	20.17	19.90	20.38
		25	25	20.70	20.28	20.54
		50	0	20.50	20.12	20.58
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26140/1860	26365/1882.5	26590/1905
20MHz	QPSK	1	0	22.21	22.47	23.14

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 120 of 370

		1	50	22.43	21.76	22.74
		1	99	22.81	22.29	22.10
		50	0	21.25	21.20	22.09
		50	25	21.21	20.82	21.38
		50	50	21.63	20.88	21.87
		100	0	21.54	21.11	21.64
	16QAM	1	0	21.26	21.81	22.21
		1	50	21.42	21.07	21.73
		1	99	21.88	21.60	21.30
		50	0	20.23	19.96	20.85
		50	25	20.16	19.89	20.37
		50	50	20.69	20.27	20.53
		100	0	20.49	20.11	20.57

LTE FDD Band 25 (Hotspot Open)				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26047/1850.7	26365/1882.5	26683/1914.3
1.4MHz	QPSK	1	0	17.79	18.04	18.71
		1	2	18.00	17.33	18.30
		1	5	18.38	17.86	17.67
		3	0	16.79	16.75	17.63
		3	2	16.76	16.36	16.92
		3	3	17.18	16.42	17.41
		6	0	17.05	17.16	16.64
	16QAM	1	0	16.77	17.32	17.73
		1	2	16.93	16.58	17.24
		1	5	17.43	17.16	16.85
		3	0	15.80	15.52	16.40
		3	2	15.71	15.44	15.92
		3	3	16.26	15.82	16.09
		6	0	16.08	15.71	16.16
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26055/1851.5	26365/1882.5	26675/1913.5
3MHz	QPSK	1	0	17.73	17.98	18.66
		1	13	17.95	17.27	18.25
		1	24	18.32	17.81	17.61
		12	0	16.74	16.70	17.58
		12	6	16.78	16.38	16.94
		12	13	17.19	16.44	17.43
		25	0	17.07	17.17	16.66

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 121 of 370

		1	0	16.79	17.34	17.74
		1	13	16.98	16.63	17.29
		1	24	17.40	17.13	16.82
		12	0	15.77	15.49	16.37
		12	6	15.68	15.41	15.89
		12	13	16.22	15.79	16.06
		25	0	16.02	15.65	16.10
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26065/1852.5	26365/1882.5	26665/1912.5
5MHz	QPSK	1	0	17.74	17.99	18.67
		1	13	17.96	17.28	18.26
		1	24	18.37	17.85	17.66
		12	0	16.78	16.75	17.62
		12	6	16.75	16.35	16.91
		12	13	17.19	16.44	17.43
		25	0	17.07	17.17	16.66
	16QAM	1	0	16.79	17.34	17.74
		1	13	16.95	16.60	17.26
		1	24	17.34	17.07	16.76
		12	0	15.71	15.42	16.31
		12	6	15.62	15.35	15.83
		12	13	16.26	15.83	16.10
		25	0	16.05	15.69	16.13
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26090/1855	26365/1882.5	26640/1910
10MHz	QPSK	1	0	17.71	17.97	18.64
		1	25	17.94	17.26	18.24
		1	49	18.31	17.79	17.60
		25	0	16.72	16.68	17.56
		25	13	16.69	16.29	16.85
		25	25	17.10	16.35	17.34
		50	0	16.98	17.08	16.56
	16QAM	1	0	16.81	17.36	17.76
		1	25	16.97	16.62	17.28
		1	49	17.39	17.12	16.81
		25	0	15.75	15.47	16.36
		25	13	15.67	15.40	15.88
		25	25	16.21	15.78	16.05
		50	0	16.00	15.63	16.08
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26115/1857.5	26365/1882.5	26615/1907.5
15MHz	QPSK	1	0	17.71	17.97	18.64
		1	25	17.93	17.26	18.24
		1	49	18.31	17.79	17.60

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 122 of 370

		25	0	16.72	16.67	17.56
		25	13	16.68	16.29	16.85
		25	25	17.10	16.35	17.34
		50	0	16.98	17.08	16.55
	16QAM	1	0	16.81	17.36	17.76
		1	25	16.97	16.62	17.28
		1	49	17.39	17.11	16.81
		25	0	15.74	15.47	16.36
		25	13	15.67	15.40	15.88
		25	25	16.20	15.78	16.04
		50	0	16.00	15.62	16.08
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26140/1860	26365/1882.5	26590/1905
20MHz	QPSK	1	0	17.71	17.97	18.64
		1	50	17.93	17.26	18.24
		1	99	18.36	17.84	17.65
		50	0	16.77	16.72	17.61
		50	25	16.73	16.34	16.90
		50	50	17.15	16.40	17.39
		100	0	17.03	16.60	17.13
	16QAM	1	0	16.75	17.30	17.70
		1	50	16.91	16.56	17.22
		1	99	17.33	17.05	16.75
		50	0	15.68	15.41	16.30
		50	25	15.67	15.40	15.88
		50	50	16.20	15.78	16.04
		100	0	16.00	15.62	16.08

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 123 of 370

LTE FDD Band 26				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26697/814.7	26865/831.5	27033/848.3
1.4MHz	QPSK	1	0	23.45	23.97	23.22
		1	2	23.94	23.30	23.74
		1	5	23.17	23.33	22.99
		3	0	22.09	22.27	22.31
		3	2	22.07	22.32	22.52
		3	3	22.33	22.16	22.32
		6	0	22.16	22.18	22.32
	16QAM	1	0	22.36	22.61	22.57
		1	2	22.90	22.35	22.41
		1	5	22.10	22.38	22.41
		3	0	21.07	21.15	21.38
		3	2	21.47	21.18	21.57
		3	3	21.30	21.15	21.34
		6	0	21.17	21.16	21.36
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26705/815.5	26865/831.5	27025/847.5
3MHz	QPSK	1	0	23.44	23.96	23.21
		1	13	23.93	23.29	23.73
		1	24	23.16	23.32	22.98
		12	0	22.07	22.26	22.30
		12	6	22.06	22.31	22.51
		12	13	22.32	22.15	22.31
		25	0	22.15	22.16	22.31
	16QAM	1	0	22.35	22.60	22.56
		1	13	22.89	22.34	22.40
		1	24	22.09	22.37	22.40
		12	0	21.06	21.14	21.37
		12	6	21.46	21.17	21.56
		12	13	21.29	21.14	21.33
		25	0	21.16	21.15	21.35
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26715/816.5	26865/831.5	27015/846.5
5MHz	QPSK	1	0	23.43	23.95	23.19
		1	13	23.91	23.28	23.72
		1	24	23.15	23.31	22.97
		12	0	22.06	22.25	22.29
		12	6	22.05	22.30	22.50
		12	13	22.31	22.14	22.30
		25	0	22.14	22.15	22.30

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 124 of 370

		1	0	22.34	22.59	22.55
		1	13	22.88	22.33	22.39
		1	24	22.08	22.36	22.39
	16QAM	12	0	21.05	21.13	21.36
		12	6	21.45	21.16	21.55
		12	13	21.28	21.13	21.32
		25	0	21.15	21.14	21.34
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26750/820	26865/831.5	26990/844
10MHz	QPSK	1	0	23.42	23.94	23.18
		1	25	23.89	23.27	23.70
		1	49	23.14	23.29	22.96
		25	0	22.05	22.24	22.28
		25	13	22.04	22.29	22.49
		25	25	22.30	22.13	22.29
		50	0	22.13	22.14	22.29
	16QAM	1	0	22.32	22.57	22.53
		1	25	22.86	22.31	22.37
		1	49	22.06	22.34	22.37
		25	0	21.03	21.11	21.34
		25	13	21.43	21.14	21.53
		25	25	21.26	21.11	21.30
		50	0	21.13	21.12	21.32
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26775/822.5	26865/831.5	26965/841.5
15MHz	QPSK	1	0	23.41	23.92	23.17
		1	38	23.88	23.26	23.68
		1	74	23.12	23.28	22.95
		36	0	22.04	22.23	22.27
		36	18	22.03	22.28	22.48
		36	39	22.29	22.12	22.28
		75	0	22.12	22.13	22.28
	16QAM	1	0	22.33	22.58	22.54
		1	38	22.87	22.32	22.38
		1	74	22.07	22.35	22.38
		36	0	21.04	21.12	21.35
		36	18	21.44	21.15	21.54
		36	39	21.27	21.12	21.31
		75	0	21.14	21.13	21.33

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 125 of 370

BT	AV Power (dBm)		
	Channel/Frequency(MHz)		
	0/2402	39/2441	78/2480
GFSK	7.50	8.20	8.10
$\pi/4$ DQPSK	5.20	6.30	5.70
8DPSK	4.90	6.10	5.50
BT LE	0/2402	19/2440	39/2480
Test Results	-0.33	-0.22	-0.11

Mode	Channel/ Frequency(MHz)	Data rate (Mbps)	AV Power (dBm)
802.11b	1/2412	1	15.18
		2	15.02
		5.5	14.26
		11	14.22
	6/2437	1	14.91
		2	14.69
		5.5	13.85
		11	14.01
	11/2462	1	15.08
		2	15.14
		5.5	14.57
		11	14.37
802.11g	1/2412	6	14.14
		9	14.12
		12	14.11
		18	14.11
		24	14.09
		36	14.09
		48	14.09
		54	14.08
	6/2437	6	14.20
		9	14.22
		12	14.26
		18	14.25
		24	14.24
		36	14.25
		48	14.25

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 126 of 370

		54	14.26
	11/2462	6	13.81
		9	13.78
		12	13.82
		18	13.77
		24	13.83
		36	13.89
		48	13.76
		54	13.82
802.11n HT20	1/2412	MCS0	12.39
		MCS1	12.35
		MCS2	12.36
		MCS3	12.00
		MCS4	12.14
		MCS5	12.13
		MCS6	12.12
		MCS7	12.13
	6/2437	MCS0	12.30
		MCS1	12.40
		MCS2	12.50
		MCS3	12.50
		MCS4	12.50
		MCS5	12.49
		MCS6	12.37
		MCS7	12.45
	11/2462	MCS0	11.89
		MCS1	11.88
		MCS2	11.86
		MCS3	11.87
		MCS4	11.86
		MCS5	11.85
		MCS6	11.82
		MCS7	11.83
802.11n HT40	3/2422	MCS0	12.39
		MCS1	12.35
		MCS2	12.36
		MCS3	12.36
		MCS4	12.37
		MCS5	12.40
		MCS6	12.43
		MCS7	12.49
	6/2437	MCS0	12.56
		MCS1	12.55

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 127 of 370

		MCS2	12.61
		MCS3	12.63
		MCS4	12.64
		MCS5	12.65
		MCS6	12.57
		MCS7	12.57
	9/2452	MCS0	12.26
		MCS1	12.28
		MCS2	12.25
		MCS3	12.23
		MCS4	12.33
		MCS5	12.29
		MCS6	12.31
		MCS7	12.28

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 128 of 370

7.2. Standalone SAR Test Exclusion Considerations

Per FCC KDB 447498 D01, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Band	Configuration	Frequency (MHz)	Maximum Power (dBm)	Separation Distance (mm)	Calculation Result	SAR Exclusion Thresholds	Standalone SAR
Bluetooth	Body	2480	10	15	1.05	3.0	No
Wifi 2.4GHz	Head	2462	16	5	12.49	3.0	Yes
	Body	2462	16	15	4.16	3.0	Yes

Page 129 of 370

Test Position	Channel/ Frequency (MHz)	Time slot	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	190/836.6	GSM	1:8.3	33.30	32.52	0.074	0.663	1.20	0.793	/
Left/Tilt	190/836.6	GSM	1:8.3	33.30	32.52	0.040	0.633	1.20	0.758	/
Right/Cheek	251/848.8	GSM	1:8.3	33.30	32.43	0.080	0.876	1.22	1.070	/
	190/836.6	GSM	1:8.3	33.30	32.52	0.040	0.973	1.20	1.164	/
	128/824.2	GSM	1:8.3	33.30	32.35	0.022	1.030	1.24	1.282	Figure.27
Right/Tilt	251/848.8	GSM	1:8.3	33.30	32.43	0.050	0.847	1.22	1.035	/
	190/836.6	GSM	1:8.3	33.30	32.52	0.040	0.948	1.20	1.135	/
	128/824.2	GSM	1:8.3	33.30	32.35	0.040	0.951	1.24	1.184	/
Worst position of Head With Battery 2										
Right/Cheek	128/824.2	GSM	1:8.3	33.30	32.35	0.020	0.963	1.24	1.198	/
Test Position of Head (WiFi on)										
Left/Cheek	190/836.6	GSM	1:8.3	30.80	30.62	0.049	0.498	1.04	0.519	/
Left/Tilt	190/836.6	GSM	1:8.3	30.80	30.62	-0.010	0.626	1.04	0.652	/
Worst Case Position of Head (1 st Repeated SAR)										
Right/Cheek	128/824.2	GSM	1:8.3	33.30	32.35	0.120	0.948	1.24	1.180	/
Test position of Body-worn (Distance 15mm)										
Back Side	190/836.6	GSM	1:8.3	33.30	32.52	-0.044	0.084	1.20	0.101	/
Front Side	190/836.6	GSM	1:8.3	33.30	32.52	0.074	0.096	1.20	0.114	Figure.28
Test position of Hotspot (Distance 10mm)										
Back Side	190/836.6	2Txslots	1:4.15	30.50	30.37	-0.027	0.155	1.03	0.160	/
Front Side	190/836.6	2Txslots	1:4.15	30.50	30.37	-0.038	0.202	1.03	0.208	/
Left Edge	190/836.6	2Txslots	1:4.15	30.50	30.37	0.050	0.088	1.03	0.091	/
Right Edge	190/836.6	2Txslots	1:4.15	30.50	30.37	-0.034	0.019	1.03	0.020	/
Top Edge	190/836.6	2Txslots	1:4.15	30.50	30.37	-0.038	0.172	1.03	0.177	/
Bottom Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Worst Case Position of Body with EGPRS (Distance 10mm)										
Front Side	190/836.6	2Txslots	1:4.15	30.50	30.44	-0.042	0.213	1.01	0.216	Figure.29
Worst case test Position With Battery 2 (Distance 10mm)										
Front Side	190/836.6	2Txslots	1:4.15	30.50	30.37	0.023	0.211	1.03	0.217	/

Note: 1.The value with blue color is the maximum SAR Value of each test band.

2. When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.

3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 130 of 370

Table 15: SAR Measurement Variability Results [GSM 850(GSM/GPRS/EGPRS)]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Right/Cheek	128/824.2	1.030	0.948	1.09	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Page 131 of 370

Test Position	Channel/ Frequency (MHz)	Time slot	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	661/1880	GSM	1:8.3	30.50	28.99	0.080	0.147	1.42	0.208	/
Left/Tilt	661/1880	GSM	1:8.3	30.50	28.99	0.100	0.223	1.42	0.316	/
Right/Cheek	810/1909.8	GSM	1:8.3	30.50	29.75	0.030	0.964	1.19	1.146	/
	661/1880	GSM	1:8.3	30.50	28.99	0.070	0.703	1.42	0.995	/
	512/1850.2	GSM	1:8.3	30.50	29.16	0.080	0.586	1.36	0.798	/
Right/Tilt	810/1909.8	GSM	1:8.3	30.50	29.75	0.200	0.817	1.19	0.971	/
	661/1880	GSM	1:8.3	30.50	28.99	-0.030	0.616	1.42	0.872	/
	512/1850.2	GSM	1:8.3	30.50	29.16	0.020	0.573	1.36	0.780	/
Worst position of Head With Battery 2										
Right/Cheek	810/1909.8	GSM	1:8.3	30.50	29.75	0.040	0.966	1.19	1.148	Figure.30
Worst Case Position of Head (1 st Repeated SAR)										
Right/Cheek	810/1909.8	GSM	1:8.3	30.50	29.75	0.070	0.898	1.19	1.067	/
Test position of Body-worn (Distance 15mm)										
Back Side	661/1880	GSM	1:8.3	30.50	28.99	0.150	0.058	1.42	0.082	/
Front Side	661/1880	GSM	1:8.3	30.50	28.99	0.144	0.065	1.42	0.091	Figure.31
Test position of Hotspot (Distance 10mm)										
Back Side	661/1880	3Txslots	1:4.15	26.00	25.26	0.058	0.097	1.19	0.115	/
Front Side	661/1880	3Txslots	1:4.15	26.00	25.26	0.059	0.081	1.19	0.096	/
Left Edge	661/1880	3Txslots	1:4.15	26.00	25.26	-0.060	0.168	1.19	0.199	/
Right Edge	661/1880	3Txslots	1:4.15	26.00	25.26	0.050	0.025	1.19	0.029	/
Top Edge	661/1880	3Txslots	1:4.15	26.00	25.26	0.032	0.014	1.19	0.017	/
Bottom Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Worst Case Position of Body with EGPRS (Distance 10mm)										
Left Edge	661/1880	3Txslots	1:4.15	26.00	25.29	-0.040	0.172	1.18	0.203	/
Worst case test Position With Battery 2 (Distance 10mm)										
Left Edge	661/1880	3Txslots	1:4.15	26.00	25.26	0.020	0.200	1.19	0.237	Figure.32
Note: 1.The value with blue color is the maximum SAR Value of each test band.										
2. When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.										
3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.										

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 132 of 370

Table 17: SAR Measurement Variability Results [GSM 1900(GSM/GPRS/EGPRS)]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Right/Cheek	810/1909.8	0.966	0.898	1.08	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 133 of 370

7.3.3. UMTS Band II (Antenna 1)

Table 18: SAR Values [UMTS Band II (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	9400/1880	RMC 12.2K	1:1	24.00	23.09	-0.010	0.149	1.23	0.184	/
Left/Tilt	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.190	0.174	1.23	0.215	/
Right/Cheek	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.040	0.494	1.23	0.609	Figure.33
Right/Tilt	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.060	0.493	1.23	0.608	/
Worst position of Head with Battery 2										
Right/Cheek	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.044	0.407	1.23	0.502	/
Test position of Body-worn (Distance 15mm)										
Back Side	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.026	0.078	1.23	0.096	Figure.34
Front Side	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.037	0.066	1.23	0.082	/
Test position of Hotspot (Distance 10mm)										
Back Side	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.026	0.078	1.23	0.096	/
Front Side	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.037	0.066	1.23	0.082	/
Left Edge	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.020	0.147	1.23	0.181	/
Right Edge	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.045	0.011	1.23	0.014	/
Top Edge	9400/1880	RMC 12.2K	1:1	24.00	23.09	-0.150	0.094	1.23	0.116	/
Bottom Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (Distance 10mm)										
Left Edge	9400/1880	RMC 12.2K	1:1	24.00	23.09	0.020	0.178	1.23	0.219	Figure.35

Note: 1.The value with blue color is the maximum SAR Value of each test band.

- When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode
- Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 134 of 370

7.3.4. UMTS Band IV (Antenna 1)

Table 19: SAR Values [UMTS Band IV (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.110	0.476	1.21	0.575	/
Left/Tilt	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.070	0.273	1.21	0.330	/
Right/Cheek	1513/1752.6	RMC 12.2K	1:1	24.50	23.63	-0.010	0.905	1.22	1.106	/
	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.043	0.967	1.21	1.168	Figure.36
	1312/1712.4	RMC 12.2K	1:1	24.50	23.42	0.030	0.835	1.28	1.071	/
Right/Tilt	1513/1752.6	RMC 12.2K	1:1	24.50	23.63	0.080	0.681	1.22	0.832	/
	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.050	0.669	1.21	0.808	/
	1312/1712.4	RMC 12.2K	1:1	24.50	23.42	0.013	0.612	1.28	0.785	/
Worst position of Head with Battery 2										
Right/Cheek	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.022	0.931	1.21	1.124	/
Worst Case Position of Head (1 st Repeated SAR)										
Right/Cheek	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.040	0.916	1.21	1.106	/
Test position of Body-worn (Distance 15mm)										
Back Side	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.167	0.064	1.21	0.078	Figure.37
Front Side	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.045	0.058	1.21	0.070	/
Test position of Hotspot (Distance 10mm)										
Back Side	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.022	0.183	1.21	0.221	/
Front Side	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.026	0.153	1.21	0.185	/
Left Edge	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	-0.032	0.198	1.21	0.239	Figure.38
Right Edge	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	0.134	0.025	1.21	0.031	/
Top Edge	1513/1752.6	RMC 12.2K	1:1	24.50	23.68	0.024	0.196	1.21	0.237	/
Bottom Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (Distance 10mm)										
Left Edge	1413/1732.6	RMC 12.2K	1:1	24.50	23.68	-0.080	0.165	1.21	0.199	/

Note: 1.The value with blue color is the maximum SAR Value of each test band.

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode

3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Page 135 of 370

4) Repeated measurements are not required when the original highest measured SAR is $< 0.80 \text{ W/kg}$

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 136 of 370

7.3.5. UMTS Band V (Antenna 1)

Table 21: SAR Values [UMTS Band V (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	4183/836.6	RMC 12.2K	1:1	24.50	23.34	-0.030	0.422	1.31	0.551	/
Left/Tilt	4233/846.6	RMC 12.2K	1:1	24.50	23.38	0.010	0.439	1.29	0.568	/
	4183/836.6	RMC 12.2K	1:1	24.50	23.34	0.049	0.645	1.31	0.842	Figure.39
	4132/826.4	RMC 12.2K	1:1	24.50	23.57	0.070	0.447	1.24	0.554	/
Right/Cheek	4183/836.6	RMC 12.2K	1:1	24.50	23.34	-0.010	0.549	1.31	0.717	/
Right/Tilt	4183/836.6	RMC 12.2K	1:1	24.50	23.34	0.080	0.612	1.31	0.799	/
Worst position of Head with Battery 2										
Left/Tilt	4183/836.6	RMC 12.2K	1:1	24.50	23.34	0.040	0.428	1.31	0.559	/
Test Position of Head (WiFi on)										
Left/Tilt	4183/836.6	RMC 12.2K	1:1	21.00	20.41	-0.010	0.565	1.15	0.647	/
Test position of Body-worn (Distance 15mm)										
Back Side	4183/836.6	RMC 12.2K	1:1	24.50	23.34	-0.050	0.056	1.31	0.072	Figure.40
Front Side	4183/836.6	RMC 12.2K	1:1	24.50	23.34	0.042	0.051	1.31	0.066	/
Test position of Hotspot (Distance 10mm)										
Back Side	4183/836.6	RMC 12.2K	1:1	24.50	23.34	0.063	0.119	1.31	0.155	/
Front Side	4183/836.6	RMC 12.2K	1:1	24.50	23.34	-0.081	0.130	1.31	0.170	/
Left Edge	4183/836.6	RMC 12.2K	1:1	24.50	23.34	0.030	0.048	1.31	0.063	/
Right Edge	4183/836.6	RMC 12.2K	1:1	24.50	23.34	-0.051	0.008	1.31	0.010	/
Top Edge	4183/836.6	RMC 12.2K	1:1	24.50	23.34	-0.038	0.165	1.31	0.216	Figure.41
Bottom Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (Distance 10mm)										
Top Edge	4183/836.6	RMC 12.2K	1:1	24.50	23.34	-0.034	0.132	1.31	0.172	/

Note: 1.The value with blue color is the maximum SAR Value of each test band.

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode

3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Page 137 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	18900/1880	1RB, 0%	23.50	22.77	0.120	0.183	1.18	0.216	/
Left/Tilt	18900/1880	1RB, 0%	23.50	22.77	0.070	0.201	1.18	0.238	/
Right/Cheek	19100/1900	1RB, 50%	23.50	22.39	0.030	1.020	1.29	1.317	/
	18900/1880	1RB, 0%	23.50	22.77	0.049	0.740	1.18	0.875	/
	18700/1860	1RB, 99%	23.50	22.37	0.060	0.745	1.30	0.966	/
Right/Tilt	18900/1880	1RB, 0%	23.50	22.77	0.020	0.555	1.18	0.657	/
Left/Cheek	19100/1900	50%RB, 0%	22.50	21.50	0.080	0.260	1.26	0.327	/
Left/Tilt	19100/1900	50%RB, 0%	22.50	21.50	0.100	0.264	1.26	0.332	/
Right/Cheek	19100/1900	50%RB, 0%	22.50	21.50	0.050	0.948	1.26	1.193	/
	18900/1880	50%RB, 0%	22.50	21.49	0.080	0.546	1.26	0.689	/
	18700/1860	50%RB, 50%	22.50	21.21	0.060	0.800	1.35	1.077	/
Right/Tilt	19100/1900	50%RB, 0%	22.50	21.50	-0.040	0.741	1.26	0.933	/
	18900/1880	50%RB, 0%	22.50	21.49	0.047	0.425	1.26	0.536	/
	18700/1860	50%RB, 50%	22.50	21.21	0.050	0.636	1.35	0.856	/
Right/Cheek	19100/1900	100%RB, 0%	22.50	21.43	0.040	0.816	1.28	1.044	/
Right/Tilt	19100/1900	100%RB, 0%	22.50	21.43	-0.110	0.412	1.28	0.527	/
Worst position of Head for Battery 2 (QPSK)									
Right/Cheek	19100/1900	1RB, 50%	23.50	22.39	0.040	1.030	1.29	1.330	/
Worst Case Position of Head for 1 st Repeated SAR(QPSK)									
Right/Cheek	19100/1900	1RB, 50%	23.50	22.39	0.090	1.090	1.29	1.407	Figure.42
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 138 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	18900/1880	1RB, 0%	23.50	22.77	0.030	0.058	1.18	0.069	/
Front Side	18900/1880	1RB, 0%	23.50	22.77	0.170	0.049	1.18	0.058	/
Back Side	19100/1900	50%RB, 0%	22.50	21.50	0.021	0.062	1.26	0.078	Figure.43
Front Side	19100/1900	50%RB, 0%	22.50	21.50	0.071	0.059	1.26	0.074	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	18900/1880	1RB, 0%	23.50	22.77	0.150	0.137	1.18	0.162	/
Front Side	18900/1880	1RB, 0%	23.50	22.77	0.049	0.112	1.18	0.133	/
Left Edge	18900/1880	1RB, 0%	23.50	22.77	0.020	0.134	1.18	0.159	/
Right Edge	18900/1880	1RB, 0%	23.50	22.77	0.074	0.006	1.18	0.007	/
Top Edge	18900/1880	1RB, 0%	23.50	22.77	0.100	0.139	1.18	0.164	/
Bottom Edge	18900/1880	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Back Side	19100/1900	50%RB, 0%	22.50	21.50	0.052	0.145	1.26	0.183	/
Front Side	19100/1900	50%RB, 0%	22.50	21.50	0.051	0.123	1.26	0.155	/
Left Edge	19100/1900	50%RB, 0%	22.50	21.50	-0.010	0.186	1.26	0.234	Figure.44
Right Edge	19100/1900	50%RB, 0%	22.50	21.50	-0.040	0.012	1.26	0.014	/
Top Edge	19100/1900	50%RB, 0%	22.50	21.50	-0.090	0.178	1.26	0.224	/
Bottom Edge	19100/1900	50%RB, 0%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Left Edge	19100/1900	50%RB, 0%	22.50	21.50	0.030	0.185	1.26	0.233	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Table 23: SAR Measurement Variability Results [LTE Band II]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Right/Cheek	19100/1900	1.020	1.090	1.07	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Page 139 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK, 1RB)									
Left/Cheek	20175/1732.5	1RB, 0%	23.50	22.34	0.030	0.317	1.31	0.414	/
Left/Tilt	20175/1732.5	1RB, 0%	23.50	22.34	0.180	0.197	1.31	0.257	/
Right/Cheek	20300/1745	1RB, 0%	23.50	22.21	0.050	0.835	1.35	1.124	/
	20175/1732.5	1RB, 0%	23.50	22.34	-0.020	0.730	1.31	0.954	/
	20050/1720	1RB, 0%	23.50	21.66	0.060	0.657	1.53	1.004	/
Right/Tilt	20175/1732.5	1RB, 0%	23.50	22.34	0.050	0.513	1.31	0.670	/
Left/Cheek	20175/1732.5	50%RB, 0%	22.50	21.30	-0.070	0.320	1.32	0.422	/
Left/Tilt	20175/1732.5	50%RB, 0%	22.50	21.30	0.120	0.192	1.32	0.253	/
Right/Cheek	20300/1745	50%RB, 99%	22.50	20.83	0.070	0.634	1.47	0.931	/
	20175/1732.5	50%RB, 0%	22.50	21.30	0.050	0.749	1.32	0.987	/
	20050/1720	50%RB, 99%	22.50	21.21	0.080	0.608	1.35	0.818	/
Right/Tilt	20175/1732.5	50%RB, 0%	22.50	21.30	0.030	0.532	1.32	0.701	/
Right/Cheek	20175/1732.5	100%RB, 0%	22.50	21.34	0.030	0.754	1.31	0.985	/
Worst position of Head for Battery 2 (QPSK)									
Right/Cheek	20300/1745	1RB, 0%	23.50	22.21	0.057	0.937	1.35	1.261	Figure.45
Worst Case Position of Head for 1 st Repeated SAR									
Right/Cheek	20300/1745	1RB, 0%	23.50	22.21	0.030	0.753	1.35	1.013	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 140 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	20175/1732.5	1RB, 0%	23.50	22.34	0.020	0.058	1.31	0.076	Figure.46
Front Side	20175/1732.5	1RB, 0%	23.50	22.34	0.093	0.051	1.31	0.067	/
Back Side	20175/1732.5	50%RB, 0%	22.50	21.30	0.138	0.044	1.32	0.058	/
Front Side	20175/1732.5	50%RB, 0%	22.50	21.30	0.086	0.038	1.32	0.050	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	20175/1732.5	1RB, 0%	23.50	22.34	0.080	0.138	1.31	0.180	/
Front Side	20175/1732.5	1RB, 0%	23.50	22.34	0.120	0.113	1.31	0.148	/
Left Edge	20175/1732.5	1RB, 0%	23.50	22.34	-0.070	0.153	1.31	0.200	Figure.47
Right Edge	20175/1732.5	1RB, 0%	23.50	22.34	0.038	0.017	1.31	0.022	/
Top Edge	20175/1732.5	1RB, 0%	23.50	22.34	-0.090	0.134	1.31	0.175	/
Bottom Edge	20175/1732.5	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Back Side	20175/1732.5	50%RB, 0%	22.50	21.30	0.110	0.126	1.32	0.170	/
Front Side	20175/1732.5	50%RB, 0%	22.50	21.30	0.051	0.105	1.32	0.138	/
Left Edge	20175/1732.5	50%RB, 0%	22.50	21.30	0.030	0.146	1.32	0.192	/
Right Edge	20175/1732.5	50%RB, 0%	22.50	21.30	0.052	0.018	1.32	0.023	/
Top Edge	20175/1732.5	50%RB, 0%	22.50	21.30	-0.090	0.129	1.32	0.170	/
Bottom Edge	20175/1732.5	50%RB, 0%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Left Edge	20175/1732.5	1RB, 0%	23.50	22.34	0.100	0.134	1.31	0.175	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 141 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	20600/844	1RB, 50%	24.00	23.51	0.061	0.531	1.12	0.594	/
Left/Tilt	20600/844	1RB, 50%	24.00	23.51	0.180	0.484	1.12	0.542	/
Right/Cheek	20600/844	1RB, 50%	24.00	23.51	0.031	0.796	1.12	0.891	/
	20525/836.5	1RB, 99%	24.00	23.44	-0.026	0.695	1.14	0.791	/
	20450/829	1RB, 50%	24.00	23.40	0.020	0.817	1.15	0.938	Figure.48
Right/Tilt	20600/844	1RB, 50%	24.00	23.51	0.100	0.724	1.12	0.810	/
	20525/836.5	1RB, 99%	24.00	23.44	0.070	0.615	1.14	0.700	/
	20450/829	1RB, 50%	24.00	23.40	-0.130	0.703	1.15	0.807	/
Left/Cheek	20600/844	50%RB, 0%	23.00	22.19	0.090	0.476	1.21	0.574	/
Left/Tilt	20600/844	50%RB, 0%	23.00	22.19	0.020	0.424	1.21	0.511	/
Right/Cheek	20600/844	50%RB, 0%	23.00	22.19	0.020	0.681	1.21	0.821	/
	20525/836.5	50%RB, 99%	23.00	21.84	0.120	0.559	1.31	0.730	/
	20450/829	50%RB, 0%	23.00	22.12	0.120	0.720	1.22	0.882	/
Right/Tilt	20600/844	50%RB, 0%	23.00	22.19	0.090	0.625	1.21	0.753	/
Right/Cheek	20600/844	100%RB, 0%	23.00	22.02	0.080	0.462	1.25	0.579	/
Right/Tilt	20600/844	100%RB, 0%	23.00	22.02	0.058	0.210	1.25	0.263	/
Worst position of Head for Battery 2 (QPSK)									
Right/Cheek	20450/829	1RB, 50%	24.00	23.40	0.042	0.696	1.15	0.799	/
Worst Case Position of Head for 1 st Repeated SAR									
Right/Cheek	20450/829	1RB, 50%	24.00	23.40	0.070	0.771	1.15	0.885	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 142 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	20600/844	1RB, 50%	24.00	23.51	0.192	0.039	1.12	0.044	/
Front Side	20600/844	1RB, 50%	24.00	23.51	0.144	0.048	1.12	0.054	Figure.49
Back Side	20600/844	50%RB, 0%	23.00	22.19	0.030	0.038	1.21	0.046	/
Front Side	20600/844	50%RB, 0%	23.00	22.19	-0.077	0.038	1.21	0.046	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	20600/844	1RB, 50%	24.00	23.51	0.044	0.172	1.12	0.193	/
Front Side	20600/844	1RB, 50%	24.00	23.51	0.150	0.156	1.12	0.175	/
Left Edge	20600/844	1RB, 50%	24.00	23.51	0.130	0.084	1.12	0.094	/
Right Edge	20600/844	1RB, 50%	24.00	23.51	0.026	0.022	1.12	0.025	/
Top Edge	20600/844	1RB, 50%	24.00	23.51	-0.070	0.177	1.12	0.198	Figure.50
Bottom Edge	20600/844	1RB, 50%	NA	NA	NA	NA	NA	NA	NA
Back Side	20600/844	50%RB, 0%	23.00	22.19	-0.020	0.163	1.21	0.196	/
Front Side	20600/844	50%RB, 0%	23.00	22.19	0.160	0.162	1.21	0.195	/
Left Edge	20600/844	50%RB, 0%	23.00	22.19	0.020	0.088	1.21	0.106	/
Right Edge	20600/844	50%RB, 0%	23.00	22.19	0.037	0.024	1.21	0.029	/
Top Edge	20600/844	50%RB, 0%	23.00	22.19	-0.050	0.176	1.21	0.212	/
Bottom Edge	20600/844	50%RB, 0%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Top Edge	20600/844	50%RB, 0%	23.00	22.19	0.099	0.073	1.21	0.088	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

Table 26: SAR Measurement Variability Results [LTE Band V]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Right/Cheek	20450/829	0.817	0.771	1.06	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Page 143 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	21350/2560	1RB, 0%	24.00	22.78	-0.055	0.282	1.32	0.373	/
Left/Tilt	21350/2560	1RB, 0%	24.00	22.78	0.040	0.289	1.32	0.383	/
Right/Cheek	21350/2560	1RB, 0%	24.00	22.78	-0.030	0.819	1.32	1.085	/
	21100/2535	1RB, 50%	24.00	22.71	0.100	0.830	1.35	1.117	/
	20850/2510	1RB, 50%	24.00	22.77	0.170	0.713	1.33	0.946	/
Right/Tilt	21350/2560	1RB, 0%	24.00	22.78	0.020	0.860	1.32	1.139	/
	21100/2535	1RB, 50%	24.00	22.71	0.150	0.851	1.35	1.145	/
	20850/2510	1RB, 50%	24.00	22.77	0.039	0.848	1.33	1.126	/
Left/Cheek	20850/2510	50%RB, 99%	23.00	21.97	0.090	0.295	1.27	0.374	/
Left/Tilt	20850/2510	50%RB, 99%	23.00	21.97	0.007	0.290	1.27	0.368	/
Right/Cheek	21350/2560	50%RB, 0%	23.00	21.58	0.150	0.953	1.39	1.322	/
	21100/2535	50%RB, 50%	23.00	21.78	0.150	0.987	1.32	1.307	/
	20850/2510	50%RB, 99%	23.00	21.97	0.130	1.030	1.27	1.306	Figure.51
Right/Tilt	21350/2560	50%RB, 0%	23.00	21.58	0.190	0.837	1.39	1.161	/
	21100/2535	50%RB, 50%	23.00	21.78	0.120	0.847	1.32	1.122	/
	20850/2510	50%RB, 99%	23.00	21.97	0.050	0.880	1.27	1.116	/
Right/Cheek	21100/2535	100%RB, 0%	23.00	21.75	0.050	0.819	1.33	1.092	/
Right/Tilt	21100/2535	100%RB, 0%	23.00	21.75	0.108	0.651	1.33	0.868	/
Worst position of Head for Battery 2 (QPSK)									
Right/Cheek	21350/2560	50%RB, 0%	23.00	21.58	0.030	0.971	1.39	1.347	/
Worst Case Position of Head for 1 st Repeated SAR									
Right/Cheek	20850/2510	50%RB, 99%	23.00	21.97	0.030	0.945	1.27	1.198	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 144 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	21350/2560	1RB, 0%	24.00	22.78	-0.103	0.057	1.32	0.075	/
Front Side	21350/2560	1RB, 0%	24.00	22.78	0.100	0.057	1.32	0.076	Figure.52
Back Side	20850/2510	50%RB, 99%	23.00	21.97	0.135	0.044	1.27	0.055	/
Front Side	20850/2510	50%RB, 99%	23.00	21.97	0.064	0.043	1.27	0.054	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	21350/2560	1RB, 0%	24.00	22.78	0.065	0.179	1.32	0.237	/
Front Side	21350/2560	1RB, 0%	24.00	22.78	0.144	0.187	1.32	0.248	/
Left Edge	21350/2560	1RB, 0%	24.00	22.78	0.160	0.209	1.32	0.277	/
Right Edge	21350/2560	1RB, 0%	24.00	22.78	0.099	0.013	1.32	0.018	/
Top Edge	21350/2560	1RB, 0%	24.00	22.78	0.020	0.080	1.32	0.106	/
Bottom Edge	21350/2560	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Back Side	20850/2510	50%RB, 99%	23.00	21.97	0.044	0.192	1.27	0.243	/
Front Side	20850/2510	50%RB, 99%	23.00	21.97	0.057	0.178	1.27	0.226	/
Left Edge	20850/2510	50%RB, 99%	23.00	21.97	0.130	0.221	1.27	0.280	Figure.53
Right Edge	20850/2510	50%RB, 99%	23.00	21.97	0.049	0.003	1.27	0.004	/
Top Edge	20850/2510	50%RB, 99%	23.00	21.97	0.190	0.090	1.27	0.114	/
Bottom Edge	20850/2510	50%RB, 99%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Left Edge	20850/2510	50%RB, 99%	23.00	21.97	0.140	0.218	1.27	0.276	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Table 28: SAR Measurement Variability Results [LTE Band VII]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Right/Cheek	20850/2510	1.030	0.945	1.09	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Page 145 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	23095/707.5	1RB,50%	24.00	22.93	-0.010	0.415	1.28	0.531	/
Left/Tilt	23095/707.5	1RB,50%	24.00	22.93	0.020	0.291	1.28	0.372	/
Right/Cheek	23095/707.5	1RB,50%	24.00	22.93	0.060	0.517	1.28	0.661	/
Right/Tilt	23095/707.5	1RB,50%	24.00	22.93	0.000	0.450	1.28	0.576	/
Left/Cheek	23095/707.5	50%RB,50%	23.00	21.51	0.073	0.462	1.41	0.651	/
Left/Tilt	23095/707.5	50%RB,50%	23.00	21.51	0.029	0.333	1.41	0.469	/
Right/Cheek	23130/711	50%RB,50%	23.00	21.49	0.023	0.413	1.42	0.585	/
	23095/707.5	50%RB,50%	23.00	21.51	0.040	0.602	1.41	0.848	/
	23060/704	50%RB,0%	23.00	21.29	0.020	0.616	1.48	0.913	Figure.54
Right/Tilt	23095/707.5	50%RB,50%	23.00	21.51	0.030	0.485	1.41	0.684	/
Right/Cheek	23130/711	100%RB,0%	23.00	21.22	-0.200	0.480	1.51	0.723	/
Worst position of Head with Battery 2 (QPSK)									
Right/Cheek	23060/704	50%RB,0%	23.00	21.29	0.040	0.501	1.48	0.743	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

Page 146 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	23095/707.5	1RB,50%	24.00	22.93	0.111	0.029	1.28	0.037	Figure.55
Front Side	23095/707.5	1RB,50%	24.00	22.93	0.010	0.023	1.28	0.029	/
Back Side	23095/707.5	50%RB,50%	23.00	21.51	0.028	0.024	1.41	0.034	/
Front Side	23095/707.5	50%RB,50%	23.00	21.51	0.152	0.017	1.41	0.025	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	23095/707.5	1RB,50%	24.00	22.93	0.174	0.053	1.28	0.068	Figure.56
Front Side	23095/707.5	1RB,50%	24.00	22.93	0.105	0.033	1.28	0.042	/
Left Edge	23095/707.5	1RB,50%	24.00	22.93	-0.035	0.034	1.28	0.043	/
Right Edge	23095/707.5	1RB,50%	24.00	22.93	0.120	0.021	1.28	0.027	/
Top Edge	23095/707.5	1RB,50%	24.00	22.93	0.160	0.044	1.28	0.056	/
Bottom Edge	23095/707.5	1RB,50%	NA	NA	NA	NA	NA	NA	NA
Back Side	23095/707.5	50%RB,50%	23.00	21.51	0.062	0.040	1.41	0.057	/
Front Side	23095/707.5	50%RB,50%	23.00	21.51	0.010	0.032	1.41	0.046	/
Left Edge	23095/707.5	50%RB,50%	23.00	21.51	0.028	0.043	1.41	0.061	/
Right Edge	23095/707.5	50%RB,50%	23.00	21.51	0.150	0.019	1.41	0.027	/
Top Edge	23095/707.5	50%RB,50%	23.00	21.51	0.098	0.045	1.41	0.063	/
Bottom Edge	23095/707.5	50%RB,50%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Back Side	23095/707.5	1RB,50%	24.00	22.93	0.043	0.039	1.28	0.050	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 147 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	23790/710	1RB,50%	24.00	23.05	-0.110	0.326	1.24	0.406	/
Left/Tilt	23790/710	1RB,50%	24.00	23.05	-0.020	0.369	1.24	0.459	/
Right/Cheek	23790/710	1RB,50%	24.00	23.05	0.050	0.422	1.24	0.525	/
Right/Tilt	23790/710	1RB,50%	24.00	23.05	0.040	0.383	1.24	0.477	/
Left/Cheek	23790/710	50%RB,99%	23.00	21.91	0.000	0.374	1.29	0.481	/
Left/Tilt	23790/710	50%RB,99%	23.00	21.91	-0.050	0.416	1.29	0.535	/
Right/Cheek	23790/710	50%RB,99%	23.00	21.91	-0.020	0.481	1.29	0.618	/
Right/Tilt	23790/710	50%RB,99%	23.00	21.91	0.028	0.460	1.29	0.591	/
Worst position of Head with Battery 2 (QPSK)									
Right/Cheek	23790/710	50%RB,99%	23.00	21.91	-0.060	0.519	1.29	0.667	Figure.57
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 148 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	23790/7110	1RB, 50%	24.00	23.05	-0.035	0.059	1.24	0.073	/
Front Side	23790/7110	1RB, 50%	24.00	23.05	-0.070	0.061	1.24	0.076	/
Back Side	23790/7110	50%RB,99%	23.00	21.91	0.010	0.077	1.29	0.099	/
Front Side	23790/7110	50%RB,99%	23.00	21.91	0.090	0.078	1.29	0.100	Figure.58
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	23790/7110	1RB, 50%	24.00	23.05	0.030	0.147	1.24	0.183	/
Front Side	23790/7110	1RB, 50%	24.00	23.05	-0.100	0.120	1.24	0.149	/
Left Edge	23790/7110	1RB, 50%	24.00	23.05	0.180	0.064	1.24	0.079	/
Right Edge	23790/7110	1RB, 50%	24.00	23.05	0.024	0.023	1.24	0.028	/
Top Edge	23790/7110	1RB, 50%	24.00	23.05	0.089	0.038	1.24	0.047	/
Bottom Edge	23790/7110	1RB, 50%	NA	NA	NA	NA	NA	NA	NA
Back Side	23790/7110	50%RB,99%	23.00	21.91	0.010	0.160	1.29	0.206	/
Front Side	23790/7110	50%RB,99%	23.00	21.91	0.080	0.152	1.29	0.195	/
Left Edge	23790/7110	50%RB,99%	23.00	21.91	-0.020	0.075	1.29	0.097	/
Right Edge	23790/7110	50%RB,99%	23.00	21.91	0.035	0.029	1.29	0.037	/
Top Edge	23790/7110	50%RB,99%	23.00	21.91	0.022	0.107	1.29	0.138	/
Bottom Edge	23790/7110	50%RB,99%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Back Side	23790/7110	50%RB,99%	23.00	21.91	0.030	0.164	1.29	0.211	Figure.59
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 149 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	26590/1905	1RB, 0%	23.50	23.17	0.010	0.245	1.08	0.264	/
Left/Tilt	26590/1905	1RB, 0%	23.50	23.17	0.130	0.227	1.08	0.245	/
Right/Cheek	26590/1905	1RB, 0%	23.50	23.17	0.080	0.848	1.08	0.915	/
	26365/1882.5	1RB, 0%	23.50	22.50	0.028	0.446	1.26	0.561	/
	26140/1860	1RB, 99%	23.50	22.84	-0.021	0.545	1.16	0.634	/
Right/Tilt	26590/1905	1RB, 0%	23.50	23.17	0.070	0.768	1.08	0.829	/
	26365/1882.5	1RB, 0%	23.50	22.50	-0.064	0.359	1.26	0.452	/
	26140/1860	1RB, 99%	23.50	22.84	0.020	0.313	1.16	0.364	/
Left/Cheek	26590/1905	50%RB,0%	22.50	22.12	0.060	0.229	1.09	0.250	/
Left/Tilt	26590/1905	50%RB,0%	22.50	22.12	0.050	0.210	1.09	0.229	/
Right/Cheek	26590/1905	50%RB,0%	22.50	22.12	0.110	0.726	1.09	0.792	/
Right/Tilt	26590/1905	50%RB,0%	22.50	22.12	0.025	0.647	1.09	0.706	/
Right/Cheek	26590/1905	100%RB,0%	22.50	21.67	0.052	0.647	1.21	0.783	/
Right/Tilt	26590/1905	100%RB,0%	22.50	21.67	0.109	0.548	1.21	0.663	/
Worst position of Head with Battery 2 (QPSK)									
Right/Cheek	26590/1905	1RB, 0%	23.50	23.17	0.020	0.875	1.08	0.944	Figure.60
Worst Case Position of Head for 1 st Repeated SAR									
Right/Cheek	26590/1905	1RB, 0%	23.50	23.17	-0.070	0.743	1.08	0.802	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 150 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	26590/1905	1RB, 0%	23.50	23.17	0.010	0.065	1.08	0.070	/
Front Side	26590/1905	1RB, 0%	23.50	23.17	0.028	0.070	1.08	0.076	Figure.61
Back Side	26590/1905	50%RB, 0%	22.50	22.12	-0.160	0.046	1.09	0.050	/
Front Side	26590/1905	50%RB, 0%	22.50	22.12	0.143	0.049	1.09	0.053	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	26590/1905	1RB, 0%	23.50	23.17	0.026	0.136	1.08	0.147	/
Front Side	26590/1905	1RB, 0%	23.50	23.17	0.036	0.107	1.08	0.115	/
Left Edge	26590/1905	1RB, 0%	23.50	23.17	0.010	0.176	1.08	0.190	Figure.62
Right Edge	26590/1905	1RB, 0%	23.50	23.17	0.094	0.013	1.08	0.014	/
Top Edge	26590/1905	1RB, 0%	23.50	23.17	-0.090	0.143	1.08	0.154	/
Bottom Edge	26590/1905	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Back Side	26590/1905	50%RB, 0%	22.50	22.12	0.140	0.107	1.09	0.117	/
Front Side	26590/1905	50%RB, 0%	22.50	22.12	0.054	0.102	1.09	0.111	/
Left Edge	26590/1905	50%RB, 0%	22.50	22.12	0.020	0.168	1.09	0.183	/
Right Edge	26590/1905	50%RB, 0%	22.50	22.12	0.047	0.009	1.09	0.010	/
Top Edge	26590/1905	50%RB, 0%	22.50	22.12	-0.042	0.142	1.09	0.155	/
Bottom Edge	26590/1905	50%RB, 0%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Left Edge	26590/1905	1RB, 0%	23.50	23.17	0.110	0.154	1.08	0.166	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

Page 151 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK, 1RB)									
Left/Cheek	26865/831.5	1RB, 0%	24.00	23.95	0.040	0.757	1.01	0.766	/
Left/Tilt	26965/841.5	1RB, 50%	24.00	23.71	-0.020	0.818	1.07	0.874	/
	26865/831.5	1RB, 0%	24.00	23.95	-0.030	0.854	1.01	0.864	/
	26775/822.5	1RB, 50%	24.00	23.91	-0.120	0.787	1.02	0.803	/
Right/Cheek	26965/841.5	1RB, 50%	24.00	23.71	-0.100	0.725	1.07	0.775	/
	26865/831.5	1RB, 0%	24.00	23.95	0.070	0.810	1.01	0.819	/
	26775/822.5	1RB, 50%	24.00	23.91	0.050	0.785	1.02	0.801	/
Right/Tilt	26965/841.5	1RB, 50%	24.00	23.71	-0.076	0.594	1.07	0.635	/
	26865/831.5	1RB, 0%	24.00	23.95	0.070	0.830	1.01	0.840	/
	26775/822.5	1RB, 50%	24.00	23.91	0.060	0.645	1.02	0.659	/
Left/Cheek	26965/841.5	50%RB, 50%	23.00	22.51	0.000	0.577	1.12	0.646	/
Left/Tilt	26965/841.5	50%RB, 50%	23.00	22.51	0.040	0.683	1.12	0.765	/
Right/Cheek	26965/841.5	50%RB, 50%	23.00	22.51	0.020	0.645	1.12	0.722	/
Right/Tilt	26965/841.5	50%RB, 50%	23.00	22.51	0.120	0.669	1.12	0.749	/
Left/Tilt	26965/841.5	100%RB, 0%	23.00	22.31	0.026	0.676	1.17	0.792	/
Right/Cheek	26965/841.5	100%RB, 0%	23.00	22.31	0.100	0.208	1.17	0.244	/
Right/Tilt	26965/841.5	100%RB, 0%	23.00	22.31	0.050	0.166	1.17	0.195	/
Worst position of Head with Battery 2 (QPSK)									
Left/Tilt	26965/841.5	1RB, 50%	24.00	23.71	0.080	0.857	1.07	0.916	Figure.63
Worst Case Position of Head (1 st Repeated SAR)									
Left/Tilt	26965/841.5	1RB, 50%	24.00	23.71	0.102	0.785	1.07	0.839	/
Test Position of Head (QPSK, WiFi on)									
Left/Cheek	26865/831.5	1RB, 0%	19.50	18.95	0.023	0.423	1.14	0.480	/
Left/Tilt	26965/841.5	1RB, 50%	19.50	18.71	0.069	0.418	1.20	0.501	/
	26865/831.5	1RB, 0%	19.50	18.95	-0.040	0.464	1.14	0.527	/
	26775/822.5	1RB, 50%	19.50	18.91	0.010	0.436	1.15	0.499	/
Left/Tilt	26965/841.5	50%RB, 50%	18.50	17.92	0.170	0.358	1.14	0.409	/
Left/Tilt	26965/841.5	100%RB, 0%	18.50	17.77	0.034	0.365	1.18	0.432	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 152 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	26865/831.5	1RB, 0%	24.00	23.95	-0.030	0.138	1.01	0.140	/
Front Side	26865/831.5	1RB, 0%	24.00	23.95	-0.043	0.157	1.14	0.179	Figure.64
Back Side	26965/841.5	50%RB, 50%	23.00	22.51	0.080	0.138	1.12	0.154	/
Front Side	26965/841.5	50%RB, 50%	23.00	22.51	0.070	0.136	1.12	0.152	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	26865/831.5	1RB, 0%	24.00	23.95	0.010	0.248	1.01	0.251	/
Front Side	26865/831.5	1RB, 0%	24.00	23.95	0.130	0.249	1.14	0.284	/
Left Edge	26865/831.5	1RB, 0%	24.00	23.95	0.070	0.106	1.01	0.107	/
Right Edge	26865/831.5	1RB, 0%	24.00	23.95	0.044	0.021	1.01	0.021	/
Top Edge	26865/831.5	1RB, 0%	24.00	23.95	0.070	0.193	1.01	0.195	/
Bottom Edge	26865/831.5	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Back Side	26965/841.5	50%RB, 50%	23.00	22.51	0.070	0.207	1.12	0.232	/
Front Side	26965/841.5	50%RB, 50%	23.00	22.51	0.080	0.210	1.12	0.235	/
Left Edge	26965/841.5	50%RB, 50%	23.00	22.51	0.160	0.104	1.12	0.116	/
Right Edge	26965/841.5	50%RB, 50%	23.00	22.51	-0.010	0.029	1.12	0.033	/
Top Edge	26965/841.5	50%RB, 50%	23.00	22.51	0.030	0.176	1.12	0.197	/
Bottom Edge	26965/841.5	50%RB, 50%	NA	NA	NA	NA	NA	NA	NA
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Front Side	26865/831.5	1RB, 0%	24.00	23.95	0.080	0.310	1.01	0.314	Figure.65
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 153 of 370

Test Position	Channel/ Frequency (MHz)	Time slot	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift $\pm 0.21\text{dB}$	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	190/836.6	GSM	1:8.3	33.30	32.50	-0.030	0.135	1.20	0.162	/
Left/Tilt	190/836.6	GSM	1:8.3	33.30	32.50	0.160	0.070	1.20	0.085	/
Right/Cheek	190/836.6	GSM	1:8.3	33.30	32.50	0.177	0.234	1.20	0.281	Figure.66
Right/Tilt	190/836.6	GSM	1:8.3	33.30	32.50	-0.060	0.091	1.20	0.109	/
Worst case test Position With Battery 2										
Right/Cheek	190/836.6	GSM	1:8.3	33.30	32.50	0.028	0.226	1.20	0.272	/
Test position of Body-worn (Distance 15mm)										
Back Side	190/836.6	GSM	1:8.3	33.30	32.50	0.010	0.340	1.20	0.409	Figure.67
Front Side	190/836.6	GSM	1:8.3	33.30	32.50	-0.050	0.205	1.20	0.246	/
Test position of Hotspot (Distance 10mm)										
Back Side	190/836.6	2Txslots	1:4.15	30.50	30.34	-0.006	0.393	1.04	0.408	/
Front Side	190/836.6	2Txslots	1:4.15	30.50	30.34	0.041	0.251	1.04	0.260	/
Left Edge	190/836.6	2Txslots	1:4.15	30.50	30.34	-0.043	0.168	1.04	0.174	/
Right Edge	190/836.6	2Txslots	1:4.15	30.50	30.34	0.084	0.279	1.04	0.289	/
Top Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	190/836.6	2Txslots	1:4.15	30.50	30.34	0.026	0.143	1.04	0.148	/
Worst Case Position of Body with EGPRS (Distance 10mm)										
Back Side	190/836.6	2Txslots	1:4.15	30.50	30.41	-0.070	0.415	1.02	0.424	/
Worst case test Position With Battery 2 (Distance 10mm)										
Back Side	190/836.6	2Txslots	1:4.15	30.50	30.34	-0.029	0.415	1.04	0.431	Figure.68
Note: 1.The value with blue color is the maximum SAR Value of each test band. 2. When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power. 3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.										

Page 154 of 370

Test Position	Channel/ Frequency (MHz)	Time slot	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	661/1880	GSM	1:8.3	30.50	28.95	-0.110	0.364	1.43	0.520	Figure.69
Left/Tilt	661/1880	GSM	1:8.3	30.50	28.95	-0.097	0.132	1.43	0.189	/
Right/Cheek	661/1880	GSM	1:8.3	30.50	28.95	0.117	0.148	1.43	0.211	/
Right/Tilt	661/1880	GSM	1:8.3	30.50	28.95	-0.100	0.120	1.43	0.171	/
Worst case test Position With Battery 2										
Left/Cheek	661/1880	GSM	1:8.3	30.50	28.95	0.099	0.335	1.43	0.479	/
Test position of Body-worn (Distance 15mm)										
Back Side	810/1909.8	GSM	1:8.3	30.50	29.72	0.020	1.030	1.20	1.233	Figure.70
	661/1880	GSM	1:8.3	30.50	28.95	-0.029	0.806	1.43	1.152	/
	512/1850.2	GSM	1:8.3	30.50	29.13	-0.080	0.731	1.37	1.002	/
Front Side	661/1880	GSM	1:8.3	30.50	28.95	0.021	0.555	1.43	0.793	/
Worst case test Position With Earphone (Distance 15mm)										
Back Side	810/1909.8	GSM	1:8.3	30.50	29.72	-0.110	0.960	1.20	1.149	/
Test position of Hotspot (Distance 10mm)										
Back Side	810/1909.8	3Txslots	1:2.77	25.00	24.80	-0.050	1.200	1.05	1.257	Figure.71
	661/1880	3Txslots	1:2.77	25.00	24.06	0.170	0.944	1.24	1.172	/
	512/1850.2	3Txslots	1:2.77	25.00	24.14	0.130	0.859	1.22	1.047	/
Front Side	661/1880	3Txslots	1:2.77	25.00	24.06	0.040	0.634	1.24	0.787	/
Left Edge	661/1880	3Txslots	1:2.77	25.00	24.06	0.078	0.257	1.24	0.319	/
Right Edge	661/1880	3Txslots	1:2.77	25.00	24.06	0.028	0.105	1.24	0.130	/
Top Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	810/1909.8	3Txslots	1:2.77	25.00	24.80	0.090	0.889	1.05	0.931	/
	661/1880	3Txslots	1:2.77	25.00	24.06	0.190	0.871	1.24	1.081	/
	512/1850.2	3Txslots	1:2.77	25.00	24.14	-0.020	0.786	1.22	0.958	/
Worst Case Position of Body with EGPRS (Distance 10mm)										
Back Side	810/1909.8	3Txslots	1:2.77	25.00	24.77	-0.100	0.767	1.05	0.809	/
Worst case test Position With Battery 2 (Distance 10mm)										
Back Side	810/1909.8	3Txslots	1:2.77	25.00	24.80	-0.080	1.090	1.05	1.141	/
Worst Case Position of Body (1 st Repeated SAR, Distance 10mm)										

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 155 of 370

Back Side	810/1909.8	3Txslots	1:2.77	25.00	24.80	-0.100	1.100	1.05	1.152	/
-----------	------------	----------	--------	-------	-------	--------	-------	------	-------	---

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.
3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Table 35: SAR Measurement Variability Results [GSM 1900(GSM/GPRS/EGPRS)]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Back Side	810/1909.8	1.200	1.100	1.09	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 156 of 370

7.3.16. UMTS Band II (Antenna 2)

Table 36: SAR Values [UMTS Band II (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	9400/1880	RMC 12.2K	1:1	24.00	23.07	0.036	0.547	1.24	0.678	/
Left/Tilt	9400/1880	RMC 12.2K	1:1	24.00	23.07	-0.063	0.180	1.24	0.223	/
Right/Cheek	9400/1880	RMC 12.2K	1:1	24.00	23.07	-0.036	0.196	1.24	0.243	/
Right/Tilt	9400/1880	RMC 12.2K	1:1	24.00	23.07	0.120	0.171	1.24	0.212	/
Worst position of Head with Battery 2										
Left/Cheek	9400/1880	RMC 12.2K	1:1	24.00	23.07	0.102	0.551	1.24	0.683	Figure.72
Test Position of Body-worn (Distance 15mm)										
Back Side	9538/1907.6	RMC 12.2K	1:1	24.00	23.18	-0.100	0.808	1.21	0.976	Figure.73
	9400/1880	RMC 12.2K	1:1	24.00	23.07	-0.180	0.806	1.24	0.998	/
	9262/1852.4	RMC 12.2K	1:1	24.00	22.73	-0.070	0.759	1.34	1.017	/
Front Side	9400/1880	RMC 12.2K	1:1	24.00	23.07	0.170	0.575	1.24	0.712	/
Test position of Hotspot (Distance 10mm)										
Back Side	9538/1907.6	RMC 12.2K	1:1	22.00	20.69	0.027	0.914	1.35	1.236	/
	9400/1880	RMC 12.2K	1:1	22.00	20.58	0.044	0.927	1.39	1.286	/
	9262/1852.4	RMC 12.2K	1:1	22.00	20.24	0.025	0.880	1.50	1.320	/
Front Side	9538/1907.6	RMC 12.2K	1:1	22.00	20.69	0.090	0.459	1.35	0.621	/
	9400/1880	RMC 12.2K	1:1	22.00	20.58	0.056	0.641	1.39	0.889	/
	9262/1852.4	RMC 12.2K	1:1	22.00	20.24	0.038	0.649	1.50	0.973	/
Left Edge	9400/1880	RMC 12.2K	1:1	22.00	20.58	-0.140	0.218	1.39	0.302	/
Right Edge	9400/1880	RMC 12.2K	1:1	22.00	20.58	0.030	0.046	1.39	0.063	/
Top Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	9538/1907.6	RMC 12.2K	1:1	22.00	20.69	0.060	0.795	1.35	1.075	/
	9400/1880	RMC 12.2K	1:1	22.00	20.58	-0.021	0.928	1.39	1.287	/
	9262/1852.4	RMC 12.2K	1:1	22.00	20.24	0.030	0.949	1.50	1.423	Figure.74
Worst position of Body with Battery 2 (Distance 10mm)										
Bottom Edge	9262/1852.4	RMC 12.2K	1:1	22.00	20.24	0.080	0.772	1.50	1.158	/
Worst Case Position of Body (1 st Repeated SAR, Distance 10mm)										
Bottom Edge	9262/1852.4	RMC 12.2K	1:1	22.00	20.24	-0.021	0.906	1.50	1.359	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output

Page 157 of 370

3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

[illegible]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Bottom Edge	9262/1852.4	0.949	0.906	1.05	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 158 of 370

7.3.17. UMTS Band IV (Antenna 2)

Table 39: SAR Values [UMTS Band IV (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	1513/1752.6	RMC 12.2K	1:1	24.50	23.57	0.130	0.565	1.24	0.700	/
	1413/1732.6	RMC 12.2K	1:1	24.50	23.64	0.033	0.670	1.22	0.817	
	1312/1712.4	RMC 12.2K	1:1	24.50	23.36	0.036	0.394	1.30	0.512	
Left/Tilt	1413/1732.6	RMC 12.2K	1:1	24.50	23.64	-0.050	0.227	1.22	0.277	/
Right/Cheek	1413/1732.6	RMC 12.2K	1:1	24.50	23.64	-0.160	0.331	1.22	0.403	/
Right/Tilt	1413/1732.6	RMC 12.2K	1:1	24.50	23.64	0.070	0.314	1.22	0.383	/
Worst position of Head with Battery 2										
Left/Cheek	1413/1732.6	RMC 12.2K	1:1	24.50	23.64	0.034	0.788	1.22	0.961	Figure.75
Test Position of Body-worn (Distance 15mm)										
Back Side	1413/1732.6	RMC 12.2K	1:1	24.50	23.64	-0.050	0.446	1.22	0.544	Figure.76
Front Side	1413/1732.6	RMC 12.2K	1:1	24.50	23.64	-0.023	0.337	1.22	0.411	/
Test position of Hotspot (Distance 10mm)										
Back Side	1413/1732.6	RMC 12.2K	1:1	23.00	22.15	-0.021	0.611	1.22	0.743	/
Front Side	1413/1732.6	RMC 12.2K	1:1	23.00	22.15	-0.130	0.496	1.22	0.603	/
Left Edge	1413/1732.6	RMC 12.2K	1:1	23.00	22.15	-0.100	0.392	1.22	0.477	/
Right Edge	1413/1732.6	RMC 12.2K	1:1	23.00	22.15	0.064	0.054	1.22	0.066	/
Top Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	1513/1752.6	RMC 12.2K	1:1	23.00	22.08	-0.050	1.030	1.24	1.273	/
	1413/1732.6	RMC 12.2K	1:1	23.00	22.15	0.037	0.855	1.22	1.040	/
	1312/1712.4	RMC 12.2K	1:1	23.00	21.87	-0.030	0.544	1.30	0.706	/
Worst position of Body with Battery 2 (Distance 10mm)										
Bottom Edge	1513/1752.6	RMC 12.2K	1:1	23.00	22.08	-0.030	1.100	1.24	1.360	Figure.77
Worst Case Position of Body (1 st Repeated SAR, Distance 10mm)										
Bottom Edge	1513/1752.6	RMC 12.2K	1:1	23.00	22.08	-0.041	0.984	1.24	1.216	/

Note: 1.The value with blue color is the maximum SAR Value of each test band.

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode

3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Page 159 of 370

[illegible]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Bottom Edge	1513/1752.6	1.100	0.984	1.12	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 160 of 370

7.3.18. UMTS Band V (Antenna 2)

Table 42: SAR Values [UMTS Band V (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	4183/836.6	RMC 12.2K	1:1	24.50	23.30	0.114	0.206	1.32	0.272	/
Left/Tilt	4183/836.6	RMC 12.2K	1:1	24.50	23.30	0.035	0.129	1.32	0.170	/
Right/Cheek	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.028	0.262	1.32	0.346	Figure.78
Right/Tilt	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.048	0.142	1.32	0.187	/
Worst position of Head with Battery 2										
Right/Cheek	4183/836.6	RMC 12.2K	1:1	24.50	23.30	0.031	0.255	1.32	0.336	/
Test position of Body-worn (Distance 15mm)										
Back Side	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.187	0.128	1.32	0.169	Figure.79
Front Side	4183/836.6	RMC 12.2K	1:1	24.50	23.30	0.073	0.120	1.32	0.158	/
Test position of Hotspot (Distance 10mm)										
Back Side	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.010	0.281	1.32	0.370	Figure.80
Front Side	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.080	0.202	1.32	0.266	/
Left Edge	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.088	0.107	1.32	0.141	/
Right Edge	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.095	0.269	1.32	0.355	/
Top Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.103	0.137	1.32	0.181	/
Worst position of Body with Battery 2 (Distance 10mm)										
Back Side	4183/836.6	RMC 12.2K	1:1	24.50	23.30	-0.052	0.158	1.32	0.208	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode

3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Page 161 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	19100/1900	1RB,50%	23.50	22.74	0.028	0.538	1.19	0.641	Figure.81
Left/Tilt	19100/1900	1RB,50%	23.50	22.74	-0.090	0.204	1.19	0.243	/
Right/Cheek	19100/1900	1RB,50%	23.50	22.74	-0.049	0.204	1.19	0.243	/
Right/Tilt	19100/1900	1RB,50%	23.50	22.74	0.029	0.141	1.19	0.168	/
Left/Cheek	19100/1900	50%RB,0%	22.50	21.47	-0.060	0.496	1.27	0.629	/
Left/Tilt	19100/1900	50%RB,0%	22.50	21.47	-0.046	0.193	1.27	0.245	/
Right/Cheek	19100/1900	50%RB,0%	22.50	21.47	-0.032	0.229	1.27	0.290	/
Right/Tilt	19100/1900	50%RB,0%	22.50	21.47	0.030	0.156	1.27	0.198	/
Worst position of Head with Battery 2 (QPSK)									
Left/Cheek	19100/1900	1RB,50%	23.50	22.74	0.044	0.499	1.19	0.594	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

Page 162 of 370

Note: 1. The value with blue color is the maximum SAR Value of each test band.

Page 163 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	20175/1732.5	1RB, 0%	23.5	22.31	0.060	0.603	1.32	0.793	/
Left/Tilt	20175/1732.5	1RB, 0%	23.5	22.31	0.070	0.188	1.32	0.247	/
Right/Cheek	20175/1732.5	1RB, 0%	23.5	22.31	-0.040	0.250	1.32	0.329	/
Right/Tilt	20175/1732.5	1RB, 0%	23.5	22.31	0.038	0.237	1.32	0.312	/
Left/Cheek	20175/1732.5	50%RB, 0%	22.50	21.27	0.057	0.418	1.33	0.555	/
Left/Tilt	20175/1732.5	50%RB, 0%	22.50	21.27	-0.040	0.129	1.33	0.171	/
Right/Cheek	20175/1732.5	50%RB, 0%	22.50	21.27	0.048	0.186	1.33	0.247	/
Right/Tilt	20175/1732.5	50%RB, 0%	22.50	21.27	0.050	0.173	1.33	0.230	/
Left/Cheek	20175/1732.5	100%RB, 0%	22.50	21.31	0.058	0.316	1.32	0.416	/
Worst position of Head with Battery 2 (QPSK, 1RB)									
Left/Cheek	20175/1732.5	1RB, 0%	23.5	22.31	0.120	0.636	1.32	0.836	Figure.84

Note: 1. The value with blue color is the maximum SAR Value of each test band.

Page 164 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test case position of Body-worn (QPSK, Distance 15mm)									
Back Side	20175/1732.5	1RB, 0%	23.50	22.31	0.021	0.416	1.32	0.547	Figure.85
Front Side	20175/1732.5	1RB, 0%	23.50	22.31	0.040	0.363	1.32	0.477	/
Back Side	20175/1732.5	50%RB, 0%	22.50	21.27	-0.022	0.332	1.33	0.441	/
Front Side	20175/1732.5	50%RB, 0%	22.50	21.27	0.100	0.256	1.33	0.340	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	20300/1745	1RB, 0%	22.50	21.15	-0.027	0.609	1.36	0.831	/
	20175/1732.5	1RB, 0%	22.50	21.28	0.021	0.654	1.32	0.866	Figure.86
	20050/1720	1RB, 0%	22.50	20.60	-0.060	0.461	1.55	0.714	/
Front Side	20175/1732.5	1RB, 0%	22.50	21.28	0.100	0.390	1.32	0.516	/
Left Edge	20175/1732.5	1RB, 0%	22.50	21.28	-0.060	0.279	1.32	0.369	/
Right Edge	20175/1732.5	1RB, 0%	22.50	21.28	0.160	0.027	1.32	0.036	/
Top Edge	NA	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	20300/1745	1RB, 0%	22.50	21.15	0.100	0.619	1.36	0.845	/
	20175/1732.5	1RB, 0%	22.50	21.28	-0.090	0.610	1.32	0.808	/
	20050/1720	1RB, 0%	22.50	20.60	-0.040	0.497	1.55	0.770	/
Back Side	20175/1732.5	50%RB, 0%	21.50	20.27	0.170	0.542	1.33	0.665	/
Front Side	20175/1732.5	50%RB, 0%	21.50	20.27	0.034	0.337	1.33	0.447	/
Left Edge	20175/1732.5	50%RB, 0%	21.50	20.27	-0.100	0.244	1.33	0.324	/
Right Edge	20175/1732.5	50%RB, 0%	21.50	20.27	0.100	0.028	1.33	0.037	/
Top Edge	NA	50%RB, 0%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	20175/1732.5	50%RB, 0%	21.50	20.27	-0.040	0.501	1.33	0.665	/
Back Side	20175/1732.5	100%RB, 0%	21.50	20.28	-0.060	0.468	1.32	0.620	/
Bottom Edge	20175/1732.5	100%RB, 0%	21.50	20.28	0.010	0.387	1.32	0.513	/
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Back Side	20175/1732.5	1RB, 0%	22.50	21.28	0.042	0.613	1.32	0.812	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 165 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	20600/844	1RB, 50%	24.00	23.48	0.031	0.108	1.13	0.122	/
Left/Tilt	20600/844	1RB, 50%	24.00	23.48	-0.073	0.063	1.13	0.071	/
Right/Cheek	20600/844	1RB, 50%	24.00	23.48	-0.028	0.261	1.13	0.294	Figure.87
Right/Tilt	20600/844	1RB, 50%	24.00	23.48	-0.390	0.094	1.13	0.106	/
Left/Cheek	20600/844	50%RB,0%	23.00	22.16	0.130	0.064	1.21	0.077	/
Left/Tilt	20600/844	50%RB,0%	23.00	22.16	0.135	0.038	1.21	0.046	/
Right/Cheek	20600/844	50%RB,0%	23.00	22.16	0.027	0.177	1.21	0.215	/
Right/Tilt	20600/844	50%RB,0%	23.00	22.16	0.128	0.068	1.21	0.083	/
Worst position of Head with Battery 2 (QPSK)									
Right/Cheek	20600/844	1RB, 50%	24.00	23.48	-0.021	0.157	1.13	0.177	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 166 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	20600/844	1RB, 50%	24.00	23.48	0.016	0.138	1.13	0.156	Figure.88
Front Side	20600/844	1RB, 50%	24.00	23.48	-0.016	0.133	1.13	0.150	/
Back Side	20600/844	50%RB,0%	23.00	22.16	0.123	0.100	1.21	0.121	/
Front Side	20600/844	50%RB,0%	23.00	22.16	0.068	0.094	1.21	0.115	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	20600/844	1RB, 50%	24.00	23.48	-0.024	0.316	1.13	0.356	Figure.89
Front Side	20600/844	1RB, 50%	24.00	23.48	-0.106	0.212	1.13	0.239	/
Left Edge	20600/844	1RB, 50%	24.00	23.48	0.047	0.126	1.13	0.142	/
Right Edge	20600/844	1RB, 50%	24.00	23.48	0.024	0.219	1.13	0.247	/
Top Edge	20600/844	1RB, 50%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	20600/844	1RB, 50%	24.00	23.48	0.008	0.151	1.13	0.170	/
Back Side	20600/844	50%RB,0%	23.00	22.16	0.056	0.203	1.21	0.246	/
Front Side	20600/844	50%RB,0%	23.00	22.16	0.101	0.150	1.21	0.182	/
Left Edge	20600/844	50%RB,0%	23.00	22.16	0.011	0.048	1.21	0.058	/
Right Edge	20600/844	50%RB,0%	23.00	22.16	0.067	0.160	1.21	0.194	/
Top Edge	20600/844	50%RB,0%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	20600/844	50%RB,0%	23.00	22.16	0.024	0.108	1.21	0.131	/
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Back Side	20600/844	1RB, 50%	24.00	23.48	0.114	0.216	1.13	0.243	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 167 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	21350/2560	1RB, 0%	24.00	22.75	0.133	0.232	1.33	0.309	/
Left/Tilt	21350/2560	1RB, 0%	24.00	22.75	0.074	0.245	1.33	0.327	/
Right/Cheek	21350/2560	1RB, 0%	24.00	22.75	0.187	0.564	1.33	0.752	/
Right/Tilt	21350/2560	1RB, 0%	24.00	22.75	0.050	0.184	1.33	0.245	/
Left/Cheek	20850/2510	50%RB,99%	23.00	21.94	0.033	0.206	1.28	0.263	/
Left/Tilt	20850/2510	50%RB,99%	23.00	21.94	0.050	0.266	1.28	0.340	/
Right/Cheek	20850/2510	50%RB,99%	23.00	21.94	0.025	0.450	1.28	0.575	/
Right/Tilt	20850/2510	50%RB,99%	23.00	21.94	0.059	0.166	1.28	0.212	/
Worst position of Head with Battery 2 (QPSK)									
Left/Cheek	21350/2560	1RB, 0%	24.00	22.75	0.176	0.577	1.33	0.769	Figure.90
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 168 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test case position of Body-worn (QPSK, Distance 15mm)									
Back Side	21350/2560	1RB, 0%	24.00	22.75	0.140	0.273	1.33	0.364	/
Front Side	21350/2560	1RB, 0%	24.00	22.75	-0.020	0.326	1.33	0.435	Figure.91
Back Side	20850/2510	50%RB,99%	23.00	21.94	0.040	0.215	1.28	0.275	/
Front Side	20850/2510	50%RB,99%	23.00	21.94	0.010	0.275	1.28	0.351	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	21350/2560	1RB, 0%	23.00	22.21	0.029	0.349	1.20	0.419	/
Front Side	21350/2560	1RB, 0%	23.00	22.21	0.050	0.399	1.20	0.479	Figure.92
Left Edge	21350/2560	1RB, 0%	23.00	22.21	0.125	0.010	1.20	0.012	/
Right Edge	21350/2560	1RB, 0%	23.00	22.21	0.060	0.358	1.20	0.429	/
Top Edge	21350/2560	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	21350/2560	1RB, 0%	23.00	22.21	0.054	0.026	1.20	0.032	/
Back Side	20850/2510	50%RB,99%	22.00	21.35	0.050	0.328	1.16	0.381	/
Front Side	20850/2510	50%RB,99%	22.00	21.35	0.080	0.374	1.16	0.434	/
Left Edge	20850/2510	50%RB,99%	22.00	21.35	0.069	0.013	1.16	0.015	/
Right Edge	20850/2510	50%RB,99%	22.00	21.35	0.023	0.335	1.16	0.389	/
Top Edge	20850/2510	50%RB,99%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	20850/2510	50%RB,99%	22.00	21.35	0.039	0.022	1.16	0.026	/
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Front Side	21350/2560	1RB, 0%	23.00	22.21	0.010	0.360	1.20	0.432	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 169 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	23095/707.5	1RB, 50%	24.00	22.90	0.058	0.025	1.29	0.033	/
Left/Tilt	23095/707.5	1RB, 50%	24.00	22.90	-0.044	0.019	1.29	0.025	/
Right/Cheek	23095/707.5	1RB, 50%	24.00	22.90	-0.121	0.043	1.29	0.055	/
Right/Tilt	23095/707.5	1RB, 50%	24.00	22.90	-0.199	0.024	1.29	0.031	/
Left/Cheek	23095/707.5	50%RB,50%	23.00	21.48	-0.058	0.019	1.42	0.027	/
Left/Tilt	23095/707.5	50%RB,50%	23.00	21.48	-0.092	0.016	1.42	0.022	/
Right/Cheek	23095/707.5	50%RB,50%	23.00	21.48	-0.043	0.031	1.42	0.044	/
Right/Tilt	23095/707.5	50%RB,50%	23.00	21.48	-0.136	0.018	1.42	0.026	/
Worst position of Head with Battery 2 (QPSK)									
Right/Cheek	23095/707.5	1RB, 50%	24.00	22.90	-0.094	0.046	1.29	0.059	Figure.93

Note: 1.The value with blue color is the maximum SAR Value of each test band.

Page 170 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	23095/707.5	1RB, 50%	24.00	22.90	0.044	0.069	1.29	0.088	Figure.94
Front Side	23095/707.5	1RB, 50%	24.00	22.90	-0.048	0.031	1.29	0.040	/
Back Side	23095/707.5	50%RB,50%	23.00	21.48	-0.162	0.044	1.42	0.063	/
Front Side	23095/707.5	50%RB,50%	23.00	21.48	0.022	0.025	1.42	0.036	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	23095/707.5	1RB, 50%	24.00	22.90	0.031	0.108	1.29	0.139	/
Front Side	23095/707.5	1RB, 50%	24.00	22.90	0.049	0.044	1.29	0.057	/
Left Edge	23095/707.5	1RB, 50%	24.00	22.90	-0.049	0.030	1.29	0.039	/
Right Edge	23095/707.5	1RB, 50%	24.00	22.90	0.124	0.078	1.29	0.100	/
Top Edge	23095/707.5	1RB, 50%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	23095/707.5	1RB, 50%	24.00	22.90	-0.061	0.046	1.29	0.059	/
Back Side	23095/707.5	50%RB,50%	23.00	21.48	0.026	0.092	1.42	0.131	/
Front Side	23095/707.5	50%RB,50%	23.00	21.48	-0.020	0.042	1.42	0.059	/
Left Edge	23095/707.5	50%RB,50%	23.00	21.48	0.035	0.032	1.42	0.045	/
Right Edge	23095/707.5	50%RB,50%	23.00	21.48	0.027	0.052	1.42	0.073	/
Top Edge	23095/707.5	50%RB,50%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	23095/707.5	50%RB,50%	23.00	21.48	-0.071	0.045	1.42	0.063	/
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Back Side	23095/707.5	1RB, 50%	24.00	22.90	-0.052	0.114	1.29	0.147	Figure.95
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 171 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	23790/710	1RB, 50%	24.00	23.02	-0.158	0.026	1.25	0.032	/
Left/Tilt	23790/710	1RB, 50%	24.00	23.02	-0.027	0.014	1.25	0.018	/
Right/Cheek	23790/710	1RB, 50%	24.00	23.02	-0.020	0.054	1.25	0.067	Figure.96
Right/Tilt	23790/710	1RB, 50%	24.00	23.02	-0.047	0.012	1.25	0.015	/
Left/Cheek	23790/710	50%RB,50%	23.00	21.88	-0.075	0.029	1.30	0.038	/
Left/Tilt	23790/710	50%RB,50%	23.00	21.88	0.075	0.020	1.30	0.026	/
Right/Cheek	23790/710	50%RB,50%	23.00	21.88	-0.037	0.043	1.30	0.056	/
Right/Tilt	23790/710	50%RB,50%	23.00	21.88	0.023	0.022	1.30	0.028	/
Worst position of Head with Battery 2 (QPSK)									
Right/Cheek	23790/710	1RB, 50%	24.00	23.02	0.058	0.034	1.25	0.042	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

Page 172 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	23790/710	1RB, 50%	24.00	23.02	0.032	0.053	1.25	0.066	Figure.97
Front Side	23790/710	1RB, 50%	24.00	23.02	-0.109	0.031	1.25	0.039	/
Back Side	23790/710	50%RB,50%	23.00	21.88	-0.034	0.039	1.30	0.050	/
Front Side	23790/710	50%RB,50%	23.00	21.88	-0.051	0.023	1.30	0.030	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	23790/710	1RB, 50%	24.00	23.02	0.043	0.093	1.25	0.116	/
Front Side	23790/710	1RB, 50%	24.00	23.02	0.124	0.061	1.25	0.077	/
Left Edge	23790/710	1RB, 50%	24.00	23.02	0.029	0.064	1.25	0.080	/
Right Edge	23790/710	1RB, 50%	24.00	23.02	0.014	0.089	1.25	0.112	/
Top Edge	23790/710	1RB, 50%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	23790/710	1RB, 50%	24.00	23.02	-0.098	0.038	1.25	0.048	/
Back Side	23790/710	50%RB,50%	23.00	21.88	0.014	0.097	1.30	0.126	/
Front Side	23790/710	50%RB,50%	23.00	21.88	-0.020	0.069	1.30	0.089	/
Left Edge	23790/710	50%RB,50%	23.00	21.88	-0.163	0.067	1.30	0.087	/
Right Edge	23790/710	50%RB,50%	23.00	21.88	-0.026	0.106	1.30	0.137	Figure.98
Top Edge	23790/710	50%RB,50%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	23790/710	50%RB,50%	23.00	21.88	-0.004	0.044	1.30	0.056	/
Worst position of Body with Battery 2 (QPSK, 1RB, Distance 10mm)									
Right Edge	23790/710	50%RB,50%	23.00	21.88	-0.055	0.074	1.30	0.096	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Page 173 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	26590/1905	1RB, 0%	23.50	23.14	0.085	0.752	1.09	0.817	Figure.99
	26365/1882.5	1RB, 0%	23.50	22.47	0.058	0.346	1.27	0.438	/
	26140/1860	1RB, 99%	23.50	22.81	0.040	0.485	1.17	0.569	/
Left/Tilt	26590/1905	1RB, 0%	23.50	23.14	-0.068	0.221	1.09	0.240	/
Right/Cheek	26590/1905	1RB, 0%	23.50	23.14	0.030	0.335	1.09	0.364	/
Right/Tilt	26590/1905	1RB, 0%	23.50	23.14	0.090	0.205	1.09	0.223	/
Left/Cheek	26590/1905	50%RB,0%	22.50	22.09	-0.121	0.502	1.10	0.552	/
Left/Tilt	26590/1905	50%RB,0%	22.50	22.09	0.032	0.143	1.10	0.157	/
Right/Cheek	26590/1905	50%RB,0%	22.50	22.09	0.060	0.225	1.10	0.247	/
Right/Tilt	26590/1905	50%RB,0%	22.50	22.09	0.160	0.130	1.10	0.143	/
Left/Cheek	26590/1905	100%RB,0%	22.50	21.64	0.055	0.344	1.22	0.419	/
Worst position of Head with Battery 2 (QPSK, 1RB)									
Left/Cheek	26590/1905	1RB, 0%	23.50	23.14	0.024	0.612	1.09	0.665	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 174 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test case position of Body-worn (QPSK, Distance 15mm)									
Back Side	26590/1905	1RB, 0%	23.50	23.14	0.040	0.415	1.09	0.451	Figure.100
Front Side	26590/1905	1RB, 0%	23.50	23.14	0.190	0.259	1.09	0.281	/
Back Side	26590/1905	50%RB,0%	22.50	22.09	0.031	0.298	1.10	0.328	/
Front Side	26590/1905	50%RB,0%	22.50	22.09	0.045	0.176	1.10	0.194	/
Test position of Hotspot (QPSK, Distance 10mm)									
Back Side	26590/1905	1RB, 0%	19.50	18.64	0.020	1.050	1.22	1.280	Figure.101
	26365/1882.5	1RB, 0%	19.50	17.97	-0.010	0.632	1.42	0.898	/
	26140/1860	1RB, 99%	19.50	18.36	0.031	0.791	1.30	1.029	/
Front Side	26590/1905	1RB, 0%	19.50	18.64	0.074	0.390	1.22	0.475	/
Left Edge	26590/1905	1RB, 0%	19.50	18.64	-0.030	0.289	1.22	0.352	/
Right Edge	26590/1905	1RB, 0%	19.50	18.64	0.047	0.067	1.22	0.081	/
Top Edge	26590/1905	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	26590/1905	1RB, 0%	19.50	18.64	0.000	0.691	1.22	0.842	/
	26365/1882.5	1RB, 0%	19.50	17.97	-0.070	0.381	1.42	0.542	/
	26140/1860	1RB, 99%	19.50	18.36	-0.020	0.520	1.30	0.676	/
Back Side	26590/1905	50%RB,0%	18.50	17.61	0.042	0.766	1.23	0.941	/
	26365/1882.5	50%RB,0%	18.50	16.72	0.084	0.395	1.51	0.595	/
	26140/1860	50%RB,99%	18.50	17.15	0.100	0.656	1.37	0.896	/
Front Side	26590/1905	50%RB,0%	18.50	17.61	0.041	0.328	1.23	0.403	/
Left Edge	26590/1905	50%RB,0%	18.50	17.61	-0.040	0.201	1.23	0.247	/
Right Edge	26590/1905	50%RB,0%	18.50	17.61	0.033	0.077	1.23	0.094	/
Top Edge	26590/1905	50%RB,0%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	26590/1905	50%RB,0%	18.50	17.61	0.028	0.493	1.23	0.605	/
Back Side	26590/1905	100%RB,0%	18.50	17.13	0.074	0.381	1.37	0.522	/
Bottom Edge	26590/1905	100%RB,0%	18.50	17.13	-0.020	0.545	1.37	0.747	/
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Back Side	26590/1905	1RB, 0%	19.50	18.64	0.025	0.928	1.22	1.131	/
Worst Case Position of Body (1 st Repeated SAR, Distance 10mm)									
Back Side	26590/1905	1RB, 0%	19.50	18.64	0.038	0.944	1.22	1.150	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.									

Note: 1. The value with blue color is the maximum SAR Value of each test band.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 175 of 370

Table 50: SAR Measurement Variability Results [LTE Band 25/20MHz]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Back Side	26590/1905	1.050	0.944	1.11	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Page 176 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head (QPSK)									
Left/Cheek	26865/831.5	1RB, 0%	24.00	23.92	0.178	0.148	1.02	0.151	/
Left/Tilt	26865/831.5	1RB, 0%	24.00	23.92	-0.051	0.087	1.02	0.089	/
Right/Cheek	26865/831.5	1RB, 0%	24.00	23.92	0.056	0.207	1.02	0.211	Figure.102
Right/Tilt	26865/831.5	1RB, 0%	24.00	23.92	-0.042	0.103	1.02	0.105	/
Left/Cheek	26965/841.5	50%RB,50%	23.00	22.48	-0.094	0.100	1.13	0.112	/
Left/Tilt	26965/841.5	50%RB,50%	23.00	22.48	0.015	0.076	1.13	0.086	/
Right/Cheek	26965/841.5	50%RB,50%	23.00	22.48	-0.077	0.170	1.13	0.192	/
Right/Tilt	26965/841.5	50%RB,50%	23.00	22.48	-0.087	0.069	1.13	0.078	/
Worst position of Head with Battery 2 (QPSK)									
Right/Cheek	26865/831.5	1RB, 0%	24.00	23.92	0.156	0.207	1.02	0.211	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Test Report

Page 177 of 370

Test Position	Channel/ Frequency (MHz)	RB Offset	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
					Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test position of Body-worn (QPSK, Distance 15mm)									
Back Side	26865/831.5	1RB, 0%	24.00	23.92	0.047	0.126	1.02	0.128	Figure.103
Front Side	26865/831.5	1RB, 0%	24.00	23.92	-0.031	0.116	1.02	0.118	/
Back Side	26965/841.5	50%RB,50%	23.00	22.48	-0.053	0.102	1.13	0.115	/
Front Side	26965/841.5	50%RB,50%	23.00	22.48	-0.095	0.096	1.13	0.108	/
Test position of Hotspot (QPSK, 1RB, Distance 10mm)									
Back Side	26865/831.5	1RB, 0%	24.00	23.92	0.174	0.201	1.02	0.205	/
Front Side	26865/831.5	1RB, 0%	24.00	23.92	0.139	0.113	1.14	0.129	/
Left Edge	26865/831.5	1RB, 0%	24.00	23.92	-0.054	0.025	1.02	0.025	/
Right Edge	26865/831.5	1RB, 0%	24.00	23.92	0.034	0.134	1.02	0.137	/
Top Edge	26865/831.5	1RB, 0%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	26865/831.5	1RB, 0%	24.00	23.92	0.026	0.070	1.02	0.071	/
Back Side	26965/841.5	50%RB,50%	23.00	22.48	-0.017	0.197	1.13	0.222	/
Front Side	26965/841.5	50%RB,50%	23.00	22.48	0.048	0.107	1.13	0.121	/
Left Edge	26965/841.5	50%RB,50%	23.00	22.48	0.002	0.163	1.13	0.184	/
Right Edge	26965/841.5	50%RB,50%	23.00	22.48	0.022	0.035	1.13	0.039	/
Top Edge	26965/841.5	50%RB,50%	NA	NA	NA	NA	NA	NA	NA
Bottom Edge	26965/841.5	50%RB,50%	23.00	22.48	-0.041	0.027	1.13	0.030	/
Worst position of Body with Battery 2 (QPSK, Distance 10mm)									
Back Side	26865/831.5	50%RB,50%	23.00	22.48	-0.061	0.249	1.13	0.281	Figure.104
Note: 1.The value with blue color is the maximum SAR Value of each test band.									

Page 178 of 370

Test Position	Channel/ Frequency (MHz)	Service	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit of SAR 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left/Cheek	11/2462	DSSS	1:1	16.00	15.08	0.110	0.690	1.24	0.853	/
	6/2437	DSSS	1:1	16.00	14.91	0.046	0.537	1.29	0.690	/
	1/2412	DSSS	1:1	16.00	15.18	0.057	0.724	1.21	0.874	Figure.105
Left/Tilt	11/2462	DSSS	1:1	16.00	15.08	0.028	0.695	1.24	0.859	/
	6/2437	DSSS	1:1	16.00	14.91	0.050	0.633	1.29	0.814	/
	1/2412	DSSS	1:1	16.00	15.18	0.028	0.780	1.21	0.942	Figure.106
Right/Cheek	1/2412	DSSS	1:1	16.00	15.18	-0.030	0.156	1.21	0.188	/
Right/Tilt	1/2412	DSSS	1:1	16.00	15.18	0.090	0.169	1.21	0.204	/
Worst case test Position With Battery 2										
Left/Tilt	1/2412	DSSS	1:1	16.00	15.18	-0.060	0.468	1.21	0.565	/
Test position of Body-worn (Distance 15mm)										
Back Side	1/2412	DSSS	1:1	16.00	15.18	0.050	0.078	1.21	0.094	Figure.107
Front Side	1/2412	DSSS	1:1	16.00	15.18	0.118	0.051	1.21	0.062	/
Test position of Hotspot (Distance 10mm)										
Back Side	1/2412	DSSS	1:1	16.00	15.18	0.060	0.138	1.21	0.167	/
Front Side	1/2412	DSSS	1:1	16.00	15.18	0.037	0.095	1.21	0.115	/
Left Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Right Edge	1/2412	DSSS	1:1	16.00	15.18	-0.070	0.131	1.21	0.158	/
Top Edge	1/2412	DSSS	1:1	16.00	15.18	0.029	0.103	1.21	0.124	/
Bottom Edge	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Worst case test Position With Battery 2 (Distance 10mm)										
Back Side	1/2412	DSSS	1:1	16.00	15.18	0.036	0.152	1.21	0.184	Figure.108

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. KDB 248227-SAR is not required for 802.11g/n channels when the maximum average output power is less than ¼ dB higher than measured on the corresponding 802.11b channels.

3. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 179 of 370

7.4. Simultaneous Transmission Conditions

Air-Interface	Band (MHz)	Type	SimultaneousTransmissions	Voice Over Digital Transport (Data)
GSM	850	Voice	Yes	NA
	1900	Voice	GPRS, EGPRS, BT or WiFi	
	GPRS	Data	Yes	NA
	EGPRS	Data	GSM, BT or WiFi	
WCDMA	UMTS Band II	Voice	Yes BT or WiFi	NA
	UMTS Band IV	Voice		
	UMTS Band V	Voice		
	RMC	Data	Yes BT or WiFi	NA
	HSDPA	Data		
	HSUPA	Data		
	DC-HSDPA	Data		
LTE	Band 2	Data	Yes BT or WiFi	NA
	Band 4	Data		
	Band 5	Data		
	Band 7	Data		
	Band 12	Data		
	Band17	Data		
	Band 25	Data		
	Band 26	Data		
WiFi	2450	Data	Yes GSM, GPRS, EGPRS, RMC, HSDPA, HSUPA, DC-HSDPA, LTE	Yes
Bluetooth (BT)	2450	Data	Yes GSM, GPRS, EGPRS, RMC, HSDPA, HSUPA, DC-HSDPA, LTE	NA

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 180 of 370

When standalone SAR is not required to be measured per FCC KDB 447498 D01, the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} * \frac{\sqrt{f \text{ (GHz)}}}{7.5}$$

Band	Configuration	Frequency (MHz)	Maximum Power (dBm)	Separation Distance (mm)	Estimated SAR (W/kg)
Bluetooth	Body	2480	10	15	0.140

Per FCC KDB 447498 D01, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. When the sum is greater than the SAR limit, SAR test exclusion is determined by the SAR to peak location separation ratio.

$$\text{Ratio} = \frac{(\text{SAR}_1 + \text{SAR}_2)^{1.5}}{(\text{peak location separation, mm})} < 0.04$$

Antenna 1 & Antenna 2 Mode

Antenna 1 and Antenna 2 cannot transmit simultaneously.

WiFi & BT Mode

BT and WiFi antenna cannot transmit simultaneously.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 181 of 370

About BT and GSM/UMTS/LTE Antenna 1

SAR _{1g} (W/kg) Test Position	GSM 850	GSM 1900	UMTS Band II	UMTS Band IV	UMTS Band V	LTE 2	LTE 4	LTE 5	LTE 7	LTE 12	LTE 17	LTE 25	LTE 26	BT	MAX. ΣSAR _{1g}	Peak location separation ratio
Back Side(15mm)	0.101	0.082	0.096	0.078	0.072	0.078	0.076	0.046	0.075	0.037	0.099	0.070	0.154	0.140	0.294	NA
Front Side(15mm)	0.114	0.091	0.082	0.070	0.066	0.074	0.067	0.054	0.076	0.029	0.100	0.076	0.179	0.140	0.319	NA

Note: 1.The value with blue color is the maximum ΣSAR_{1g} Value.
2. MAX. ΣSAR_{1g} =Unlicensed SAR_{MAX} +Licensed SAR_{MAX}

MAX. ΣSAR_{1g} = 0.319 W/kg <1.6 W/kg, so the Simultaneous transimition SAR with volum scan are not required for BT and GSM/UMTS/LTE antenna 1.

About WiFi and GSM/UMTS/LTE Antenna 1

SAR _{1g} (W/kg) Test Position	GSM 850	GSM 1900	UMTS Band II	UMTS Band IV	UMTS Band V	LTE 2	LTE 4	LTE 5	LTE 7	LTE 12	LTE 17	LTE 25	LTE 26	WiFi	MAX. ΣSAR _{1g}	Peak location separation ratio
Left, Touch	0.519	0.208	0.184	0.575	0.551	0.327	0.422	0.594	0.374	0.651	0.481	0.264	0.480	0.874	1.525	NA
Left, Tilt	0.652	0.316	0.215	0.330	0.647	0.332	0.257	0.542	0.383	0.469	0.535	0.245	0.527	0.942	1.594	NA
Right, Touch	1.282	1.148	0.609	1.168	0.717	1.407	1.261	0.938	1.322	0.913	0.667	0.944	0.819	0.188	1.595	NA
Right, Tilt	1.184	0.971	0.608	0.832	0.799	0.933	0.701	0.810	1.161	0.684	0.591	0.829	0.840	0.204	1.388	NA
Back Side(15mm)	0.101	0.082	0.096	0.078	0.072	0.078	0.076	0.046	0.075	0.037	0.099	0.070	0.154	0.094	0.248	NA
Front Side(15mm)	0.114	0.091	0.082	0.070	0.066	0.074	0.067	0.054	0.076	0.029	0.100	0.076	0.179	0.062	0.241	NA
Back Side(10mm)	0.160	0.115	0.096	0.221	0.155	0.183	0.180	0.196	0.243	0.068	0.211	0.147	0.251	0.184	0.435	NA
Front Side(10mm)	0.217	0.096	0.082	0.185	0.170	0.155	0.148	0.195	0.248	0.046	0.195	0.115	0.314	0.115	0.429	NA
Left Edge(10mm)	0.091	0.237	0.219	0.239	0.063	0.234	0.200	0.106	0.280	0.061	0.097	0.190	0.116	NA	0.280	NA
Right Edge(10mm)	0.020	0.029	0.014	0.031	0.010	0.014	0.023	0.029	0.018	0.027	0.037	0.014	0.033	0.158	0.195	NA
Top Edge(10mm)	0.177	0.017	0.116	0.237	0.216	0.224	0.175	0.212	0.114	0.063	0.138	0.155	0.197	0.124	0.361	NA
Bottom Edge(10mm)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

Note: 1.The value with blue color is the maximum ΣSAR_{1g} Value.
2. MAX. ΣSAR_{1g} =Unlicensed SAR_{MAX} +Licensed SAR_{MAX}

MAX. ΣSAR_{1g} = 1.595 W/kg <1.6 W/kg, so the Simultaneous transimition SAR with volum scan are not required for WiFi and GSM/UMTS/LTE Antenna 1.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 182 of 370

About BT and GSM/UMTS/LTE Antenna 2

SAR _{1g} (W/kg) Test Position	GSM 850	GSM 1900	UMTS Band II	UMTS Band IV	UMTS Band V	LTE 2	LTE 4	LTE 5	LTE 7	LTE 12	LTE 17	LTE 25	LTE 26	BT	MAX. ΣSAR _{1g}	Peak location separation ratio
Back Side(15mm)	0.409	1.233	1.017	0.544	0.169	1.005	0.547	0.156	0.364	0.088	0.066	0.451	0.128	0.140	1.373	NA
Front Side(15mm)	0.246	0.793	0.712	0.411	0.158	0.625	0.477	0.150	0.435	0.040	0.039	0.281	0.118	0.140	0.933	NA

Note: 1.The value with blue color is the maximum ΣSAR_{1g} Value.

2. MAX. ΣSAR_{1g} =Unlicensed SAR_{MAX} +Licensed SAR_{MAX}

MAX. ΣSAR_{1g} = 1.373 W/kg <1.6 W/kg, so the Simultaneous transimition SAR with volum scan are not required for BT and GSM/UMTS/LTE antenna.

About WiFi and GSM/UMTS/LTE Antenna 2

SAR _{1g} (W/kg) Test Position	GSM 850	GSM 1900	UMTS Band II	UMTS Band IV	UMTS Band V	LTE 2	LTE 4	LTE 5	LTE 7	LTE 12	LTE 17	LTE 25	LTE 26	WiFi	MAX. ΣSAR _{1g}	Peak location separation ratio
Left, Touch	0.162	0.520	0.683	0.961	0.272	0.641	0.836	0.122	0.309	0.033	0.038	0.817	0.151	0.874	1.835	Yes
Left, Tilt	0.085	0.189	0.223	0.277	0.170	0.245	0.247	0.071	0.340	0.025	0.026	0.240	0.089	0.942	1.282	NA
Right, Touch	0.281	0.211	0.243	0.403	0.346	0.290	0.329	0.294	0.769	0.059	0.067	0.364	0.211	0.188	0.957	NA
Right, Tilt	0.109	0.171	0.212	0.383	0.187	0.198	0.312	0.106	0.245	0.031	0.028	0.223	0.105	0.204	0.587	NA
Back Side(15mm)	0.409	1.233	1.017	0.544	0.169	1.005	0.547	0.156	0.364	0.088	0.066	0.451	0.128	0.094	1.327	NA
Front Side(15mm)	0.246	0.793	0.712	0.411	0.158	0.625	0.477	0.150	0.435	0.040	0.039	0.281	0.118	0.062	0.855	NA
Back Side(10mm)	0.431	1.257	1.320	0.743	0.370	0.901	0.866	0.356	0.419	0.147	0.126	1.280	0.281	0.184	1.504	NA
Front Side(10mm)	0.260	0.787	0.973	0.603	0.266	0.190	0.516	0.239	0.479	0.059	0.089	0.475	0.129	0.115	1.088	NA
Left Edge(10mm)	0.174	0.319	0.302	0.477	0.141	0.237	0.369	0.142	0.015	0.045	0.087	0.352	0.184	NA	0.477	NA
Right Edge(10mm)	0.289	0.130	0.063	0.066	0.355	0.064	0.037	0.247	0.429	0.100	0.137	0.094	0.137	0.158	0.587	NA
Top Edge(10mm)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	0.124	0.124	NA
Bottom Edge(10mm)	0.148	1.081	1.423	1.360	0.181	0.850	0.845	0.170	0.032	0.063	0.056	0.842	0.071	NA	1.423	NA

Note: 1.The value with blue color is the maximum ΣSAR_{1g} Value.

2. MAX. ΣSAR_{1g} =Unlicensed SAR_{MAX} +Licensed SAR_{MAX}

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 183 of 370

Simultaneous Transmission for test position of Left Touch


SAR _{1g} (W/kg)	GSM 850	GSM 1900	UMTS Band II	UMTS Band IV	UMTS Band V	LTE 2	LTE 4	LTE 5	LTE 7	LTE 12	LTE 17	LTE 25	LTE 26	WiFi	MAX. Σ SAR _{1g}	Peak location separation ratio
Test Position																
Left, Touch	0.162	/	/	/	/	/	/	/	/	/	/	/	/	0.874	1.036	NA
	/	0.520	/	/	/	/	/	/	/	/	/	/	/	0.874	1.394	NA
	/	/	0.683	/	/	/	/	/	/	/	/	/	/	0.874	1.557	NA
	/	/	/	0.961	/	/	/	/	/	/	/	/	/	0.874	1.835	Yes
	/	/	/	/	0.272	/	/	/	/	/	/	/	/	0.874	1.146	NA
	/	/	/	/	/	0.641	/	/	/	/	/	/	/	0.874	1.515	NA
	/	/	/	/	/	/	0.836	/	/	/	/	/	/	0.874	1.710	Yes
	/	/	/	/	/	/	/	0.122	/	/	/	/	/	0.874	0.996	NA
	/	/	/	/	/	/	/	/	0.309	/	/	/	/	0.874	1.183	NA
	/	/	/	/	/	/	/	/	/	0.033	/	/	/	0.874	0.907	NA
	/	/	/	/	/	/	/	/	/	/	0.038	/	/	0.874	0.912	NA
	/	/	/	/	/	/	/	/	/	/	/	0.817	/	0.874	1.691	Yes
	/	/	/	/	/	/	/	/	/	/	/	/	0.151	0.874	1.025	NA

● Pair Simultaneous Transmission for UMTS Band IV and WiFi

The position SAR_{UMTS Band IV} is ($x_1= 73.75$, $y_1= 251.4$, $z_1= -171.5$),

The position SAR_{Max.WiFi} is($x_2= 31.89$, $y_2= 336$, $z_2= -173.4$)

so the distance between the SAR_{Max. UMTS Band IV} and SAR_{Max.WiFi} is 94.41mm.




The peak location separation ratio is $0.026 < 0.04$, so the Simultaneous transmission SAR with volume scan are not required for WiFi and UMTS Band IV antenna.

- **Pair Simultaneous Transmission for LTE 4 and WiFi**

The position $SAR_{UMTS\ LTE\ 4}$ is $(x_1= 72.33, y_1= 252.2, z_1= -171.6)$,

The position $SAR_{Max.WiFi}$ is $(x_2= 31.89, y_2= 336, z_2= -173.4)$

so the distance between the $SAR_{Max.LTE\ 4}$ and $SAR_{Max.WiFi}$ is 93.06mm.




The peak location separation ratio is $0.024 < 0.04$, so the Simultaneous transmission SAR with volumetric scan are not required for WiFi and LTE 4 antenna.

- **Pair Simultaneous Transmission for LTE 25 and WiFi**

The position $SAR_{UMTS\ LTE\ 25}$ is ($x_1= 72.34, y_1= 252.2, z_1= -171.6$),

The position $SAR_{Max.WiFi}$ is($x_2= 31.89, y_2= 336, z_2= -173.4$)

so the distance between the $SAR_{Max.LTE\ 25}$ and $SAR_{Max.WiFi}$ is 93.07mm.



The peak location separation ratio is $0.023 < 0.04$, so the Simultaneous transmission SAR with volumetric scan are not required for WiFi and LTE 25 antenna.

Page 186 of 370

No.	source	Type	Uncertainty Value (%)	Probability Distribution	k	c _i	Standard Uncertainty u_i' (%)	Degree of freedom V_{eff} or v_i
1	System repetivity	A	0.5	N	1	1	0.5	9
Measurement system								
2	-probe calibration	B	6.0	N	1	1	6.0	∞
3	-axial isotropy of the probe	B	4.7	R	$\sqrt{3}$	$\sqrt{0.5}$	1.9	∞
4	- Hemispherical isotropy of the probe	B	9.4	R	$\sqrt{3}$	$\sqrt{0.5}$	3.9	∞
5	-boundary effect	B	1.9	R	$\sqrt{3}$	1	1.1	∞
6	-probe linearity	B	4.7	R	$\sqrt{3}$	1	2.7	∞
7	- System detection limits	B	1.0	R	$\sqrt{3}$	1	0.6	∞
8	-readout Electronics	B	1.0	N	1	1	1.0	∞
9	-response time	B	0.8	R	$\sqrt{3}$	1	0.5	∞
10	-integration time	B	4.3	R	$\sqrt{3}$	1	2.5	∞
11	-RF Ambient noise	B	3.0	R	$\sqrt{3}$	1	1.7	∞
12	-RF Ambient Conditions	B	3.0	R	$\sqrt{3}$	1	1.7	∞
13	-Probe Positioner Mechanical Tolerance	B	0.4	R	$\sqrt{3}$	1	0.2	∞
14	-Probe Positioning with respect to Phantom Shell	B	2.9	R	$\sqrt{3}$	1	1.7	∞
15	-Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	B	3.9	R	$\sqrt{3}$	1	2.3	∞
Test sample Related								
16	-Test Sample Positioning	A	2.9	N	1	1	2.9	71
17	-Device Holder Uncertainty	A	4.1	N	1	1	4.1	5
18	- Power drift	B	5.0	R	$\sqrt{3}$	1	2.9	∞
Physical parameter								

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 187 of 370

19	-phantom Uncertainty	B	4.0	R	$\sqrt{3}$	1	2.3	∞
20	Algorithm for correcting SAR for deviations in permittivity and conductivity	B	1.9	N	1	0.84	0.9	∞
21	-Liquid conductivity (measurement uncertainty)	B	2.5	N	1	0.71	1.8	9
22	-Liquid permittivity (measurement uncertainty)	B	2.5	N	1	0.26	0.7	9
23	-Liquid conductivity -temperature uncertainty	B	1.7	R	$\sqrt{3}$	0.71	0.7	∞
24	-Liquid permittivity -temperature uncertainty	B	0.3	R	$\sqrt{3}$	0.26	0.05	∞
Combined standard uncertainty		$u_c' = \sqrt{\sum_{i=1}^{24} c_i^2 u_i^2}$					11.34	
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$		N	k=2		22.68	

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 188 of 370

9. Main Test Instruments

Table 53: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Expiration Time	Valid Period
01	Network analyzer	E5071B	MY42404014	2014-05-26	2015-05-25	1 year
02	Dielectric Probe Kit	Agilent 85070E	US44020115	No Calibration Requested		
03	Power meter	Agilent E4417A	GB41291714	2015-03-08	2016-03-07	1 year
04	Power sensor	Agilent N8481H	MY50350004	2014-09-24	2015-09-23	1 year
05	Power sensor	E9327A	US40441622	2015-01-02	2016-01-01	1 year
06	Signal Generator	HP 8341B	2730A00804	2014-09-02	2015-09-01	1 year
07	Dual directional coupler	778D-012	50519	2015-03-02	2016-03-01	1 year
08	Dual directional coupler	777D	50146	2015-03-02	2016-03-01	1 year
09	Amplifier	IXA-020	0401	No Calibration Requested		
10	Wideband radio communication tester	CMW 500	113645	2014-09-28	2015-09-27	1 year
11	E-field Probe	EX3DV4	3677	2015-01-30	2016-01-29	1 year
12	DAE	DAE4	1291	2014-11-14	2015-11-13	1 year
13	Validation Kit 750MHz	D750V3	1017	2014-08-28	2017-08-27	3 years
14	Validation Kit 835MHz	D835V2	4d020	2014-08-28	2017-08-27	3 years
15	Validation Kit 1750MHz	D1750V2	1033	2014-01-26	2017-01-25	3 years
16	Validation Kit 1900MHz	D1900V2	5d060	2014-09-01	2017-08-31	3 years
17	Validation Kit 2450MHz	D2450V2	786	2014-09-01	2017-08-31	3 years
18	Validation Kit 2600MHz	D2600V2	1025	2014-12-08	2017-12-07	3 years
19	Temperature Probe	JM222	AA1009129	2015-03-02	2016-03-01	1 year
20	Hygrothermograph	WS-1	64591	2014-09-25	2015-09-24	1 year


*****END OF REPORT *****

ANNEX A: Test Layout






Picture 1: Liquid depth in the flat Phantom (750MHz, 15.4cm depth)



Picture 2: Liquid depth in the head Phantom (750MHz, 15.3cm depth)



Picture 3: Liquid depth in the flat Phantom (835MHz, 15.4cm depth)




Picture 4: Liquid depth in the head Phantom (835MHz, 15.3cm depth)

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1


Page 192 of 370



Picture 5: Liquid depth in the flat Phantom (1750 MHz, 15.2cm depth)




Picture 6: liquid depth in the head Phantom (1750 MHz, 15.3cm depth)



Picture 7: Liquid depth in the flat Phantom (1900 MHz, 15.2cm depth)




Picture 8: liquid depth in the head Phantom (1900 MHz, 15.3cm depth)



Picture 9: Liquid depth in the flat Phantom (2450 MHz, 15.3cm depth)



Picture 10: Liquid depth in the head Phantom (2450 MHz, 15.4cm depth)



Picture 11: Liquid depth in the flat Phantom (2600 MHz, 15.3cm depth)



Picture 12: Liquid depth in the head Phantom (2600 MHz, 15.4cm depth)

ANNEX B: System Check Results

System Performance Check at 750 MHz Head TSL

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1017

Date: 3/15/2015

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.91 \text{ S/m}$; $\epsilon_r = 42.0$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.79, 9.79, 9.79); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=15mm, Pin=250mW/Area Scan (41x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.29 W/kg

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 50.653 V/m ; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 3.16 W/kg

SAR(1 g) = 2.13 W/kg ; SAR(10 g) = 1.41 W/kg

Maximum value of SAR (measured) = 2.29 W/kg




Figure 7 System Performance Check 750MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 197 of 370

System Performance Check at 750 MHz Body TSL

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1017

Date: 3/13/2015

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.97$ S/m; $\epsilon_r = 54.3$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=15mm, Pin=250mW/Area Scan (41x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.36 W/kg

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 48.998 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 3.24 W/kg

SAR(1 g) = 2.22 W/kg; SAR(10 g) = 1.49 W/kg

Maximum value of SAR (measured) = 2.39 W/kg




Figure 8 System Performance Check 750MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 198 of 370

System Performance Check at 750 MHz Body TSL

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1017

Date: 3/14/2015

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 54.5$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=15mm, Pin=250mW/Area Scan (41x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.36 W/kg

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 48.998 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 3.24 W/kg

SAR(1 g) = 2.17 W/kg; SAR(10 g) = 1.46 W/kg

Maximum value of SAR (measured) = 2.365 W/kg




Figure 9 System Performance Check 750MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 199 of 370

System Performance Check at 835 MHz Head TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 3/11/2015

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 41.4$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.64 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 54.4 V/m ; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.44 mW/g ; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.64 mW/g




Figure 10 System Performance Check 835MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 200 of 370

System Performance Check at 835 MHz Head TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 3/28/2015

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.91 \text{ mho/m}$; $\epsilon_r = 41.5$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (interpolated) = 2.71 mW/g

d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 55.2 V/m ; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 3.79 W/kg

SAR(1 g) = 2.46 mW/g ; SAR(10 g) = 1.58 mW/g

Maximum value of SAR (measured) = 2.66 mW/g




Figure 11 System Performance Check 835MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 201 of 370

System Performance Check at 835 MHz Body TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 3/10/2015

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 55.9$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.58 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.9 V/m ; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 3.5 W/kg

SAR(1 g) = 2.41 mW/g ; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.6 mW/g




Figure 12 System Performance Check 835MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 202 of 370

System Performance Check at 835 MHz Body TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 3/18/2015

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.97 \text{ mho/m}$; $\epsilon_r = 56.1$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.61 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 52.09 V/m ; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 3.48 W/kg

SAR(1 g) = 2.46 mW/g ; SAR(10 g) = 1.67 mW/g

Maximum value of SAR (measured) = 2.73 mW/g




Figure 13 System Performance Check 835MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 203 of 370

System Performance Check at 835 MHz Body TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 3/19/2015

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.97 \text{ mho/m}$; $\epsilon_r = 56.2$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.61 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 52.09 V/m ; Power Drift = -0.036 dB

Peak SAR (extrapolated) = 3.48 W/kg

SAR(1 g) = 2.49 mW/g ; SAR(10 g) = 1.72 mW/g

Maximum value of SAR (measured) = 2.79 mW/g




Figure 14 System Performance Check 835MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 204 of 370

System Performance Check at 1750 MHz Head TSL

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1033

Date: 3/12/2015

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.32$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.02, 8.02, 8.02); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (51x81x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 9.78 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 80 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 15.5 W/kg

SAR(1 g) = 8.95 mW/g; SAR(10 g) = 4.5 mW/g

Maximum value of SAR (measured) = 9.46 mW/g




Figure 15 System Performance Check 1750MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 205 of 370

System Performance Check at 1750 MHz Body TSL

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1033

Date: 3/23/2015

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 52.9$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.7 °C

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (51x81x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 10.6 mW/g

d=10mm, Pin=250mW/Area Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 77.7 V/m; Power Drift = 0.097 dB

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 9.24 mW/g; SAR(10 g) = 4.9 mW/g

Maximum value of SAR (measured) = 10.3 mW/g




Figure 16 System Performance Check 1750MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 206 of 370

System Performance Check at 1750 MHz Body TSL

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1033

Date: 3/30/2015

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.7 °C

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (51x81x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 10.6 mW/g

d=10mm, Pin=250mW/Area Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 77.7 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 9.27 mW/g; SAR(10 g) = 4.95 mW/g

Maximum value of SAR (measured) = 10.8 mW/g




Figure 17 System Performance Check 1750MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 207 of 370

System Performance Check at 1900 MHz Head TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 3/17/2015

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 11.3 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 85.5 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.48 mW/g; SAR(10 g) = 4.9 mW/g

Maximum value of SAR (measured) = 10.7 mW/g




Figure 18 System Performance Check 1900MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 208 of 370

System Performance Check at 1900 MHz Head TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 3/27/2015

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.40$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 12.9 mW/g

d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 87.8 V/m; Power Drift = 0.041 dB

Peak SAR (extrapolated) = 20.1 W/kg

SAR(1 g) = 9.59 mW/g; SAR(10 g) = 5.09 mW/g

Maximum value of SAR (measured) = 11.12 mW/g




Figure 19 System Performance Check 1900MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 209 of 370

System Performance Check at 1900 MHz Body TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 3/21/2015

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 12.2 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 82.3 V/m; Power Drift = 0.068 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.93 mW/g; SAR(10 g) = 5.25 mW/g

Maximum value of SAR (measured) = 11.3 mW/g




Figure 20 System Performance Check 1900MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 210 of 370

System Performance Check at 1900 MHz Body TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 3/24/2015

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 11.9 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 80.8 V/m; Power Drift = -0.063 dB

Peak SAR (extrapolated) = 17.6 W/kg

SAR(1 g) = 9.82 mW/g; SAR(10 g) = 5.2 mW/g

Maximum value of SAR (measured) = 11 mW/g




Figure 21 System Performance Check 1900MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 211 of 370

System Performance Check at 1900 MHz Body TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 3/26/2015

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.49$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 11.9 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 80.8 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 17.6 W/kg

SAR(1 g) = 9.83 mW/g; SAR(10 g) = 5.2 mW/g

Maximum value of SAR (measured) = 11.52 mW/g




Figure 22 System Performance Check 1900MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 212 of 370

System Performance Check at 2450 MHz Head TSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 786

Date: 3/25/2015

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.81$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.22, 7.22, 7.22); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 18.2 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.8 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 30 W/kg

SAR(1 g) = 13.7 mW/g; SAR(10 g) = 6.22 mW/g

Maximum value of SAR (measured) = 15.9 mW/g




Figure 23 System Performance Check 2450MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 213 of 370

System Performance Check at 2450 MHz Body TSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 786

Date: 3/25/2015

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.99$ mho/m; $\epsilon_r = 52.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.42, 7.42, 7.42); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM2; Type: SAM; Serial: TP-1524

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 16 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 81.2 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 25.4 W/kg

SAR(1 g) = 12.5 mW/g; SAR(10 g) = 6.20 mW/g

Maximum value of SAR (measured) = 14.4 mW/g




Figure 24 System Performance Check 2450MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 214 of 370

System Performance Check at 2600 MHz Head TSL

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1025

Date: 3/9/2015

Communication System: CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(6.94, 6.94, 6.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 17.439 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.998 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 31.858 W/kg

SAR(1 g) = 13.9 mW/g; SAR(10 g) = 6.07 mW/g

Maximum value of SAR (measured) = 15.617 mW/g




Figure 25 System Performance Check 2600MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 215 of 370

System Performance Check at 2600 MHz Body TSL

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1025

Date: 3/9/2015

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.20$ mho/m; $\epsilon_r = 52.3$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.29, 7.29, 7.29); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

d=10mm, Pin=250mW /Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 17.7 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 74 V/m; Power Drift = -0.0027 dB

Peak SAR (extrapolated) = 28.5 W/kg

SAR(1 g) = 13.5 mW/g; SAR(10 g) = 5.99 mW/g

Maximum value of SAR (measured) = 15.7 mW/g




Figure 26 System Performance Check 2600MHz 250mW

ANNEX C: Highest Graph Results

ANNEX C1: Antenna 1

GSM 850 Right Cheek Low (Battery 1)

Date: 3/28/2015

Communication System: UID 0, GSM (0); Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.919$ S/m; $\epsilon_r = 41.459$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Low/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.15 W/kg

Right Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.28 V/m; Power Drift = 0.022 dB

Peak SAR (extrapolated) = 2.27 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.527 W/kg

Maximum value of SAR (measured) = 1.06 W/kg




Figure 27 Right Hand Touch Cheek GSM 850 Channel 128

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 217 of 370

GSM 850 Front Side Middle (Battery 1, Distance 15mm)

Date: 3/19/2015

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 837$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Front Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.098 mW/g

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.06 V/m; Power Drift = 0.074 dB

Peak SAR (extrapolated) = 0.147 W/kg

SAR(1 g) = 0.096 mW/g; SAR(10 g) = 0.060 mW/g

Maximum value of SAR (measured) = 0.103 mW/g




Figure 28 Body, Front Side, GSM 850 Channel 190

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 218 of 370

GSM 850 EGPRS (2Txslots) Front Side Middle (Battery 1, Distance 10mm)

Date: 3/19/2015

Communication System: GSM850 + EGPRS(2Up); Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium parameters used: $f = 837$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.247 mW/g

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.46 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 0.377 W/kg

SAR(1 g) = 0.213 mW/g; SAR(10 g) = 0.095 mW/g

Maximum value of SAR (measured) = 0.242 mW/g




Figure 29 Body, Front Side, GSM 850 EGPRS (2Txslots) Channel 190

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 219 of 370

GSM 1900 Right Cheek High (Battery 2)

Date: 3/27/2015

Communication System: UID 0, GSM (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.44$ S/m; $\epsilon_r = 39.607$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.06 W/kg

Right Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.36 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 0.966 W/kg; SAR(10 g) = 0.491 W/kg

Maximum value of SAR (measured) = 1.09 W/kg




Figure 30 Right Hand Touch Cheek GSM 1900 Channel 810

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 220 of 370

GSM 1900 Front Side Middle (Battery 1, Distance 15mm)

Date: 3/21/2015

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ S/m; $\epsilon_r = 52.509$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0692 W/kg

Front side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.164 V/m; Power Drift = 0.144 dB

Peak SAR (extrapolated) = 0.0960 W/kg

SAR(1 g) = 0.065 W/kg; SAR(10 g) = 0.041 W/kg

Maximum value of SAR (measured) = 0.0685 W/kg




Figure 31 Body, Front Side, GSM 1900 Channel 661

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 221 of 370

GSM 1900 GPRS (3Txslots) Left Edge Middle (Battery 2, Distance 10mm)

Date: 3/21/2015

Communication System: UID 0, GPRS 3TX (0); Frequency: 1909.8 MHz; Duty Cycle: 1:2.76694

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.532$ S/m; $\epsilon_r = 52.459$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Edge High/Area Scan (51x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.222 W/kg

Left Edge High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.147 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.331 W/kg

SAR(1 g) = 0.200 W/kg; SAR(10 g) = 0.112 W/kg

Maximum value of SAR (measured) = 0.201 W/kg




Figure 32 Body, Left Edge, GSM 1900 GPRS (3Txslots) Channel 661

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 222 of 370

UMTS Band II Right Cheek Middle (Battery 1)

Date: 3/27/2015

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.574 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.01 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.991 W/kg

SAR(1 g) = 0.494 W/kg; SAR(10 g) = 0.255 W/kg

Maximum value of SAR (measured) = 0.558 W/kg




Figure 33 Right Hand Touch Cheek UMTS Band II Channel 9400

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 223 of 370

UMTS Band II Back Side Middle (Battery 1, Distance 15mm)

Date: 3/21/2015

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ S/m; $\epsilon_r = 52.509$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0849 W/kg

Back side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.944 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.140 W/kg

SAR(1 g) = 0.078 W/kg; SAR(10 g) = 0.041 W/kg

Maximum value of SAR (measured) = 0.0814 W/kg




Figure 34 Body, Back Side, UMTS Band II Channel 9400

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 224 of 370

UMTS Band II Left Edge Middle (Battery 2, Distance 10mm)

Date: 3/21/2015

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ S/m; $\epsilon_r = 52.509$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Edge Middle/Area Scan (51x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.196 W/kg

Left Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.50 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.292 W/kg

SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.100 W/kg

Maximum value of SAR (measured) = 0.175 W/kg




Figure 35 Body, Left Edge, UMTS Band II Channel 9400

UMTS Band IV Right Cheek Middle (Battery 1)

Date: 3/12/2015

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.306$ S/m; $\epsilon_r = 39.731$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.02, 8.02, 8.02); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.04 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.03 V/m; Power Drift = 0.043 dB

Peak SAR (extrapolated) = 2.05 W/kg

SAR(1 g) = 0.967 W/kg; SAR(10 g) = 0.480 W/kg

Maximum value of SAR (measured) = 1.08 W/kg




Figure 36 Right Hand Touch Cheek UMTS Band IV Channel 1413

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 226 of 370

UMTS Band IV Back Side Middle (Battery 1, Distance 15mm)

Date: 3/30/2015

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.489$ S/m; $\epsilon_r = 52.919$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0651 W/kg

Back side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.193 V/m; Power Drift = 0.167 dB

Peak SAR (extrapolated) = 0.0970 W/kg

SAR(1 g) = 0.064 W/kg; SAR(10 g) = 0.039 W/kg

Maximum value of SAR (measured) = 0.0672 W/kg




Figure 37 Body, Back Side, UMTS Band IV Channel 1413

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 227 of 370

UMTS Band IV Left Edge Middle (Battery 1, Distance 10mm)

Date: 3/30/2015

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.489$ S/m; $\epsilon_r = 52.919$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Edge Middle/Area Scan (51x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.206 W/kg

Left Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.68 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 0.324 W/kg

SAR(1 g) = 0.198 W/kg; SAR(10 g) = 0.115 W/kg

Maximum value of SAR (measured) = 0.198 W/kg




Figure 38 Body, Left Edge, UMTS Band IV Channel 1413

UMTS Band V Left Tilt Middle (Battery 1)

Date: 3/28/2015

Communication System: UID 0, WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Tilt Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.737 W/kg

Left Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.46 V/m; Power Drift = 0.049 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.645 W/kg; SAR(10 g) = 0.337 W/kg

Maximum value of SAR (measured) = 0.659 W/kg




Figure 39 Left Hand Tilt 15° UMTS Band V Channel 4183

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 229 of 370

UMTS Band V Back Side Middle (Battery 1, Distance 15mm)

Date: 3/19/2015

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.081 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.47 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 0.084 W/kg

SAR(1 g) = 0.056 mW/g; SAR(10 g) = 0.033 mW/g

Maximum value of SAR (measured) = 0.061 mW/g




Figure 40 Body, Back Side, UMTS Band V Channel 4183

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 230 of 370

UMTS Band V Top Edge Middle (Battery 1, Distance 10mm)

Date: 3/19/2015

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Top Edge Middle/Area Scan (51x171x1): Measurement grid: dx=1.000mm, dy=1.000mm

Maximum value of SAR (interpolated) = 0.229 mW/g

Top Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.6 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 0.317 W/kg

SAR(1 g) = 0.165 mW/g; SAR(10 g) = 0.081 mW/g

Maximum value of SAR (measured) = 0.182 mW/g




Figure 41 Body, Top Edge, UMTS Band V Channel 4183

LTE Band 2 1RB Right Cheek High (1st Repeated SAR)

Date: 3/27/2015

Communication System: UID 0, LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.431$ S/m; $\epsilon_r = 39.602$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.21 W/kg

Right Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.60 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 2.10 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.578 W/kg

Maximum value of SAR (measured) = 1.23 W/kg




Figure 42 Right Hand Touch Cheek LTE Band 2 1RB Channel 19100

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 232 of 370

LTE Band 2 50%RB Back Side High (Battery 1, Distance 15mm)

Date: 3/26/2015

Communication System: UID 0, LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.522$ S/m; $\epsilon_r = 52.463$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0698 W/kg

Back side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.775 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 0.0910 W/kg

SAR(1 g) = 0.062 W/kg; SAR(10 g) = 0.040 W/kg

Maximum value of SAR (measured) = 0.0653 W/kg




Figure 43 Body, Back Side, LTE Band 2 50%RB Channel 19100

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 233 of 370

LTE Band 2 50%RB Left Edge High (Battery 1, Distance 10mm)

Date: 3/26/2015

Communication System: UID 0, LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.522$ S/m; $\epsilon_r = 52.463$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Edge High/Area Scan (51x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.203 W/kg

Left Edge High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.006 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.307 W/kg

SAR(1 g) = 0.186 W/kg; SAR(10 g) = 0.105 W/kg

Maximum value of SAR (measured) = 0.187 W/kg




Figure 44 Body, Left Edge, LTE Band 2 50%RB Channel 19100

LTE Band 4 1RB Right Cheek High (Battery 2)

Date: 3/12/2015

Communication System: UID 0, LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.315$ S/m; $\epsilon_r = 39.688$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.02, 8.02, 8.02); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.948 W/kg

Right Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.10 V/m; Power Drift = 0.057 dB

Peak SAR (extrapolated) = 1.99 W/kg

SAR(1 g) = 0.937 W/kg; SAR(10 g) = 0.464 W/kg

Maximum value of SAR (measured) = 1.01 W/kg




Figure 45 Right Hand Touch Cheek LTE Band 4 1RB Channel 20300

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 235 of 370

LTE Band 4 1RB Back Side Middle (Battery 1, Distance 15mm)

Date: 3/30/2015

Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.488$ S/m; $\epsilon_r = 52.928$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0650 W/kg

Back side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.945 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.0860 W/kg

SAR(1 g) = 0.058 W/kg; SAR(10 g) = 0.038 W/kg

Maximum value of SAR (measured) = 0.0625 W/kg




Figure 46 Body, Back Side, LTE Band 2 1RB Channel 20175

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 236 of 370

LTE Band 4 1RB Left Edge Middle (Battery 1, Distance 10mm)

Date: 3/30/2015

Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.488$ S/m; $\epsilon_r = 52.928$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Edge Middle/Area Scan (51x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.170 W/kg

Left Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.680 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.243 W/kg

SAR(1 g) = 0.153 W/kg; SAR(10 g) = 0.089 W/kg

Maximum value of SAR (measured) = 0.153 W/kg




Figure 47 Body, Left Edge, LTE Band 4 1RB Channel 20175

LTE Band 5 1RB Right Cheek Low (Battery 1)

Date: 3/28/2015

Communication System: UID 0, LTE (0); Frequency: 829 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 829$ MHz; $\sigma = 0.924$ S/m; $\epsilon_r = 41.415$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Low/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.934 W/kg

Right Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.32 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.79 W/kg

SAR(1 g) = 0.817 W/kg; SAR(10 g) = 0.424 W/kg

Maximum value of SAR (measured) = 0.837 W/kg




Figure 48 Right Hand Touch Cheek LTE Band 5 1RB Channel 20450

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 238 of 370

LTE Band 5 1RB Front Side High (Battery 1, Distance 15mm)

Date: 3/18/2015

Communication System: LTE Band 5; Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844 \text{ MHz}$; $\sigma = 1.01 \text{ mho/m}$; $\epsilon_r = 55$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Front Side High/Area Scan (61x111x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.050 mW/g

Front Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.71 V/m ; Power Drift = 0.144 dB

Peak SAR (extrapolated) = 0.071 W/kg

SAR(1 g) = 0.048 mW/g ; SAR(10 g) = 0.036 mW/g

Maximum value of SAR (measured) = 0.051 mW/g




Figure 49 Body, Front Side, LTE Band 5 1RB Channel 20600

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 239 of 370

LTE Band 5 1RB Top Edge High (Battery 1, Distance 10mm)

Date: 3/18/2015

Communication System: UID 0, LTE (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844 \text{ MHz}$; $\sigma = 1.001 \text{ S/m}$; $\epsilon_r = 55.801$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Top Edge High/Area Scan (51x111x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.193 W/kg

Top Edge High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.37 V/m ; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.340 W/kg

SAR(1 g) = 0.177 W/kg ; SAR(10 g) = 0.087 W/kg

Maximum value of SAR (measured) = 0.166 W/kg




Figure 50 Body, Top Edge, LTE Band 5 1RB Channel 20600

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 240 of 370

LTE Band 7 50%RB Right Cheek Low (Battery 2)

Date: 3/9/2015

Communication System: UID 0, LTE (0); Frequency: 2510 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2510$ MHz; $\sigma = 1.889$ S/m; $\epsilon_r = 38.958$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.22, 7.22, 7.22); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Low/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.07 W/kg

Right Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.125 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 2.38 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.487 W/kg

Maximum value of SAR (measured) = 1.15 W/kg




Figure 51 Right Hand Touch Cheek LTE Band 7 50%RB Channel 20850

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 241 of 370

LTE Band 7 1RB Front Side High (Battery 1, Distance 15mm)

Date: 3/9/2015

Communication System: UID 0, LTE (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 2.151$ S/m; $\epsilon_r = 52.442$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.29, 7.29, 7.29); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front side High/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0580 W/kg

Front side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.625 V/m; Power Drift = 0.100 dB

Peak SAR (extrapolated) = 0.0990 W/kg

SAR(1 g) = 0.057 W/kg; SAR(10 g) = 0.034 W/kg

Maximum value of SAR (measured) = 0.0603 W/kg




Figure 52 Body, Front Side, LTE Band 7 1RB Channel 21350

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 242 of 370

LTE Band 7 50%RB Left Edge Low (Battery 1, Distance 10mm)

Date: 3/9/2015

Communication System: UID 0, LTE (0); Frequency: 2510 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2510$ MHz; $\sigma = 2.093$ S/m; $\epsilon_r = 52.611$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.29, 7.29, 7.29); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Edge Low/Area Scan (51x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.246 W/kg

Left Edge Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.732 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.392 W/kg

SAR(1 g) = 0.221 W/kg; SAR(10 g) = 0.115 W/kg

Maximum value of SAR (measured) = 0.212 W/kg




Figure 53 Body, Left Edge, LTE Band 7 1RB Channel 20850

LTE Band 12 1RB Right Cheek Low (Battery 1)

Date: 3/15/2015

Communication System: UID 0, LTE (0); Frequency: 704 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 704 \text{ MHz}$; $\sigma = 0.865 \text{ S/m}$; $\epsilon_r = 42.628$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.79, 9.79, 9.79); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Low/Area Scan (71x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.690 W/kg

Right Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.98 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.37 W/kg

SAR(1 g) = 0.616 W/kg ; SAR(10 g) = 0.317 W/kg

Maximum value of SAR (measured) = 0.647 W/kg




Figure 54 Right Hand Touch Cheek LTE Band 12 1RB Channel 23060

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 244 of 370

LTE Band 12 1RB Back Side Middle (Battery 1, Distance 15mm)

Date: 3/13/2015

Communication System: LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 800$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 55.5$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.030 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.00 V/m; Power Drift = 0.111 dB

Peak SAR (extrapolated) = 0.044 W/kg

SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.023 mW/g

Maximum value of SAR (measured) = 0.030 mW/g




Figure 55 Body, Back Side, LTE Band 12 1RB Channel 23095

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 245 of 370

LTE Band 12 1RB Back Side Middle (Battery 1, Distance 10mm)

Date: 3/13/2015

Communication System: LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 800$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 55.5$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.056 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.08 V/m; Power Drift = 0.174 dB

Peak SAR (extrapolated) = 0.099 W/kg

SAR(1 g) = 0.053 mW/g; SAR(10 g) = 0.032 mW/g

Maximum value of SAR (measured) = 0.057 mW/g




Figure 56 Body, Back Side, LTE Band 12 1RB Channel 23095

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 246 of 370

LTE Band 17 50%RB Right Cheek Middle (Battery 2)

Date: 3/15/2015

Communication System: UID 0, LTE (0); Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710 \text{ MHz}$; $\sigma = 0.87 \text{ S/m}$; $\epsilon_r = 42.553$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.79, 9.79, 9.79); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Middle/Area Scan (71x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.633 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.39 V/m ; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.16 W/kg

SAR(1 g) = 0.519 W/kg ; SAR(10 g) = 0.269 W/kg

Maximum value of SAR (measured) = 0.510 W/kg




Figure 57 Right Hand Touch Cheek LTE Band 17 50%RB Channel 23790

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 247 of 370

LTE Band 17 50%RB Front Side Middle (Battery1, Distance 15mm)

Date: 3/13/2015

Communication System: UID 0, LTE (0); Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710 \text{ MHz}$; $\sigma = 0.931 \text{ S/m}$; $\epsilon_r = 54.734$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front side Middle/Area Scan (71x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.0841 W/kg

Front side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.927 V/m ; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.127 W/kg

SAR(1 g) = 0.078 W/kg ; SAR(10 g) = 0.048 W/kg

Maximum value of SAR (measured) = 0.0822 W/kg




Figure 58 Body, Front Side, LTE Band 17 50%RB Channel 23790

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 248 of 370

LTE Band 17 50%RB Back Side Middle (Battery 2, Distance 10mm)

Date: 3/13/2015

Communication System: UID 0, LTE (0); Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710 \text{ MHz}$; $\sigma = 0.931 \text{ S/m}$; $\epsilon_r = 54.734$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: $22.3 \text{ }^\circ\text{C}$ Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.174 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.480 V/m ; Power Drift = 0.030 dB

Peak SAR (extrapolated) = 0.274 W/kg

SAR(1 g) = 0.164 W/kg ; SAR(10 g) = 0.094 W/kg

Maximum value of SAR (measured) = 0.178 W/kg




Figure 59 Body, Back Side, LTE Band 17 50%RB Channel 23790

LTE Band 25 1RB Right Cheek High (Battery 2)

Date: 3/27/2015

Communication System: UID 0, LTE (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1905$ MHz; $\sigma = 1.436$ S/m; $\epsilon_r = 39.583$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.927 W/kg

Right Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.60 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.68 W/kg

SAR(1 g) = 0.875 W/kg; SAR(10 g) = 0.452 W/kg

Maximum value of SAR (measured) = 0.991 W/kg




Figure 60 Right Hand Touch Cheek LTE Band 25 1RB Channel 26590

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 250 of 370

LTE Band 25 1RB Front Side High (Battery 1, Distance 15mm)

Date: 3/21/2015

Communication System: UID 0, LTE (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1905$ MHz; $\sigma = 1.529$ S/m; $\epsilon_r = 53.065$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0721 W/kg

Front side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.084 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 0.102 W/kg

SAR(1 g) = 0.070 W/kg; SAR(10 g) = 0.047 W/kg

Maximum value of SAR (measured) = 0.0728 W/kg




Figure 61 Body, Front Side, LTE Band 25 1RB Channel 26590

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 251 of 370

LTE Band 25 1RB Left Edge High (Battery 1, Distance 10mm)

Date: 3/21/2015

Communication System: UID 0, LTE (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1905$ MHz; $\sigma = 1.529$ S/m; $\epsilon_r = 53.065$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM; Serial:

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Edge High/Area Scan (51x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.192 W/kg

Left Edge High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.643 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.283 W/kg

SAR(1 g) = 0.176 W/kg; SAR(10 g) = 0.102 W/kg

Maximum value of SAR (measured) = 0.174 W/kg




Figure 62 Body, Left Edge, LTE Band 25 1RB Channel 26590

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 252 of 370

LTE Band 26 50%RB Left Tilt High (Battery 2)

Date: 3/28/2015

Communication System: UID 0, LTE (0); Frequency: 841.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 841.5$ MHz; $\sigma = 0.936$ S/m; $\epsilon_r = 41.326$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Tilt High/Area Scan (71x111x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.927 W/kg

Left Tilt High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 31.04 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.01 W/kg

SAR(1 g) = 0.857 W/kg; SAR(10 g) = 0.406 W/kg

Maximum value of SAR (measured) = 0.959 W/kg




Figure 63 Left Hand Tilt 15° LTE Band 26 50%RB Channel 26965

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 253 of 370

LTE Band 26 1RB Front Side Middle (Battery 1, Distance 15mm)

Date: 3/19/2015

Communication System: UID 0, LTE (0); Frequency: 831.5 MHz; Duty Cycle: 1:1.57943

Medium parameters used (interpolated): $f = 831.5$ MHz; $\sigma = 0.986$ S/m; $\epsilon_r = 55.913$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front Side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.168 W/kg

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.68 V/m; Power Drift = -0.043 dB

Peak SAR (extrapolated) = 0.199 W/kg

SAR(1 g) = 0.157 W/kg; SAR(10 g) = 0.118 W/kg

Maximum value of SAR (measured) = 0.165 W/kg




Figure 64 Body, Front Side, LTE Band 26 1RB Channel 26865

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 254 of 370

LTE Band 26 1RB Front Side Middle (Battery 2, Distance 10mm)

Date: 3/19/2015

Communication System: UID 0, LTE (0); Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 831.5$ MHz; $\sigma = 0.986$ S/m; $\epsilon_r = 55.913$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front Side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.339 W/kg

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.60 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.553 W/kg

SAR(1 g) = 0.310 W/kg; SAR(10 g) = 0.174 W/kg

Maximum value of SAR (measured) = 0.331 W/kg




Figure 65 Body, Front Side, LTE Band 26 1RB Channel 26865

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 255 of 370

ANNEX C2: Antenna 2

GSM 850 Right Cheek Middle (Battery 1)

Date: 3/11/2015

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Right Cheek Middle/Area Scan (61x111x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 0.249 mW/g

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.15 V/m; Power Drift = 0.177 dB

Peak SAR (extrapolated) = 0.330 W/kg

SAR(1 g) = 0.234 mW/g; SAR(10 g) = 0.169 mW/g

Maximum value of SAR (measured) = 0.249 mW/g




Figure 66 Right Hand Touch Cheek GSM 850 Channel 190

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 256 of 370

GSM 850 Back Side Middle (Battery 1, Distance 15mm)

Date: 3/10/2015

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.992$ S/m; $\epsilon_r = 55.882$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.363 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.99 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.436 W/kg

SAR(1 g) = 0.340 W/kg; SAR(10 g) = 0.249 W/kg

Maximum value of SAR (measured) = 0.358 W/kg




Figure 67 Body, Back Side, GSM 850 Channel 190

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 257 of 370

GSM 850 GPRS (2Txslots) Back Side Middle (Battery 2, Distance 10mm)

Date: 3/10/2015

Communication System: GSM850 + GPRS(2Up); Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium parameters used: $f = 837 \text{ MHz}$; $\sigma = 1 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: $22.3 \text{ }^\circ\text{C}$ Liquid Temperature: $21.5 \text{ }^\circ\text{C}$

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (interpolated) = 0.424 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.4 V/m ; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.545 W/kg

SAR(1 g) = 0.415 mW/g ; SAR(10 g) = 0.299 mW/g

Maximum value of SAR (measured) = 0.430 mW/g




Figure 68 Body, Back Side, GSM 850 GPRS (2Txslots) Channel 190

GSM 1900 Left Cheek Middle (Battery 1)

Date: 3/17/2015

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.427 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.462 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.569 W/kg

SAR(1 g) = 0.364 W/kg; SAR(10 g) = 0.223 W/kg

Maximum value of SAR (measured) = 0.377 W/kg




Figure 69 Left Hand Touch Cheek GSM 1900 Channel 661

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 259 of 370

GSM 1900 Back Side High (Battery 1, Distance 15mm)

Date: 3/24/2015

Communication System: UID 0, GSM (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.532$ S/m; $\epsilon_r = 52.459$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.933 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.562 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 1.91 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.485 W/kg

Maximum value of SAR (measured) = 1.13 W/kg




Figure 70 Body, Back Side, GSM 1900 Channel 810

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 260 of 370

GSM 1900 GPRS (3Txslots) Back Side High (Battery 1, Distance 10mm)

Date: 3/24/2015

Communication System: UID 0, GPRS 3TX (0); Frequency: 1909.8 MHz; Duty Cycle: 1:2.76694

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.532$ S/m; $\epsilon_r = 52.459$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.44 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.816 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 2.29 W/kg

SAR(1 g) = 1.2 W/kg; SAR(10 g) = 0.578 W/kg

Maximum value of SAR (measured) = 1.17 W/kg




Figure 71 Body, Back Side, GSM 1900 GPRS (3Txslots) Channel 810

UMTS Band II Left Cheek Middle (Battery 2)

Date: 3/17/2015

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.636 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.688 V/m; Power Drift = 0.102 dB

Peak SAR (extrapolated) = 0.865 W/kg

SAR(1 g) = 0.551 W/kg; SAR(10 g) = 0.337 W/kg

Maximum value of SAR (measured) = 0.561 W/kg




Figure 72 Left Hand Touch Cheek UMTS Band II Channel 9400

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 262 of 370

UMTS Band II Back Side High (Battery 1, Distance 15mm)

Date: 3/24/2015

Communication System: UID 0, WCDMA (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.528$ S/m; $\epsilon_r = 52.463$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.859 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.362 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.808 W/kg; SAR(10 g) = 0.420 W/kg

Maximum value of SAR (measured) = 0.850 W/kg




Figure 73 Body, Back Side, UMTS Band II Channel 9538

UMTS Band II Bottom Edge Low (Battery 1, Distance 10mm)

Date: 3/24/2015

Communication System: UID 0, WCDMA (0); Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.476$ S/m; $\epsilon_r = 52.546$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Bottom Edge Low/Area Scan (51x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.13 W/kg

Bottom Edge Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.61 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.67 W/kg

SAR(1 g) = 0.949 W/kg; SAR(10 g) = 0.484 W/kg

Maximum value of SAR (measured) = 0.851 W/kg




Figure 74 Body, Bottom Edge, UMTS Band II Channel 9262

UMTS Band IV Left Cheek Middle (Battery 2)

Date: 3/12/2015

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.306$ S/m; $\epsilon_r = 39.731$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.02, 8.02, 8.02); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.907 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.326 V/m; Power Drift = 0.034 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.788 W/kg; SAR(10 g) = 0.486 W/kg

Maximum value of SAR (measured) = 0.830 W/kg




Figure 75 Left Hand Touch Cheek UMTS Band IV Channel 1413

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 265 of 370

UMTS Band IV Back Side Middle (Battery 1, Distance 15mm)

Date: 3/23/2015

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.489$ S/m; $\epsilon_r = 52.919$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.493 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.832 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.752 W/kg

SAR(1 g) = 0.446 W/kg; SAR(10 g) = 0.253 W/kg

Maximum value of SAR (measured) = 0.454 W/kg




Figure 76 Body, Back Side, UMTS Band IV Channel 1413

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 266 of 370

UMTS Band IV Bottom Edge High (Battery 2, Distance 10mm)

Date: 3/23/2015

Communication System: UID 0, WCDMA (0); Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.507$ S/m; $\epsilon_r = 52.874$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Bottom Edge High/Area Scan (51x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.27 W/kg

Bottom Edge High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.96 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.96 W/kg

SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.571 W/kg

Maximum value of SAR (measured) = 1.06 W/kg




Figure 77 Body, Bottom Edge, UMTS Band IV Channel 1513

UMTS Band V Right Cheek Middle (Battery 1)

Date: 3/11/2015

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Right Cheek Middle/Area Scan (61x111x1): Measurement grid: dx=1.500mm, dy=1.500mm
Maximum value of SAR (interpolated) = 0.284 mW/g

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.45 V/m; Power Drift = -0.028 dB
Peak SAR (extrapolated) = 0.351 W/kg

SAR(1 g) = 0.262 mW/g; SAR(10 g) = 0.196 mW/g

Maximum value of SAR (measured) = 0.273 mW/g




Figure 78 Right Hand Touch Cheek UMTS Band V Channel 4183

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 268 of 370

UMTS Band V Back Side Middle (Battery 1, Distance 15mm)

Date: 3/18/2015

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.135 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.7 V/m; Power Drift = -0.187 dB
Peak SAR (extrapolated) = 0.162 W/kg

SAR(1 g) = 0.128 mW/g; SAR(10 g) = 0.099 mW/g

Maximum value of SAR (measured) = 0.133 mW/g




Figure 79 Body, Back Side, UMTS Band V Channel 4183

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 269 of 370

UMTS Band V Back Side Middle (Battery 1, Distance 10mm)

Date: 3/18/2015

Communication System: UID 0, WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.992$ S/m; $\epsilon_r = 55.882$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.312 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.88 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.497 W/kg

SAR(1 g) = 0.281 W/kg; SAR(10 g) = 0.160 W/kg

Maximum value of SAR (measured) = 0.302 W/kg




Figure 80 Body, Back Side, UMTS Band V Channel 4183

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 270 of 370

LTE Band 2 1RB Left Cheek High (Battery 1)

Date: 3/17/2015

Communication System: UID 0, LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.431$ S/m; $\epsilon_r = 39.602$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.625 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.023 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 0.840 W/kg

SAR(1 g) = 0.538 W/kg; SAR(10 g) = 0.330 W/kg

Maximum value of SAR (measured) = 0.552 W/kg




Figure 81 Left Hand Touch Cheek LTE Band 2 1RB Channel 19100

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 271 of 370

LTE Band 2 50%RB Back Side High (Battery 1, Distance 15mm)

Date: 3/24/2015

Communication System: UID 0, LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.522$ S/m; $\epsilon_r = 52.463$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.846 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.310 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.793 W/kg; SAR(10 g) = 0.408 W/kg

Maximum value of SAR (measured) = 0.770 W/kg




Figure 82 Body, Back Side, LTE Band 2 50%RB Channel 19100

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 272 of 370

LTE Band 2 1RB Back Side High (Battery 1, Distance 10mm)

Date: 3/24/2015

Communication System: UID 0, LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.524$ S/m; $\epsilon_r = 53.079$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.790 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.272 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.736 W/kg; SAR(10 g) = 0.357 W/kg

Maximum value of SAR (measured) = 0.713 W/kg




Figure 83 Body, Back Side, LTE Band 2 1RB Channel 19100

LTE Band 4 1RB Left Cheek Middle (Battery 2)

Date: 3/12/2015

Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.305$ S/m; $\epsilon_r = 39.699$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.02, 8.02, 8.02); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.725 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.010 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.979 W/kg

SAR(1 g) = 0.636 W/kg; SAR(10 g) = 0.393 W/kg

Maximum value of SAR (measured) = 0.645 W/kg




Figure 84 Left Hand Touch Cheek LTE Band 4 1RB Channel 20175

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 274 of 370

LTE Band 4 1RB Back Side Middle (Battery 1, Distance 15mm)

Date: 3/23/2015

Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.488$ S/m; $\epsilon_r = 52.928$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.439 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.431 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 0.692 W/kg

SAR(1 g) = 0.416 W/kg; SAR(10 g) = 0.239 W/kg

Maximum value of SAR (measured) = 0.459 W/kg




Figure 85 Body, Back Side, LTE Band 2 1RB Channel 20175

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 275 of 370

LTE Band 4 1RB Back Side Middle (Battery 1, Distance 10mm)

Date: 3/23/2015

Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.488$ S/m; $\epsilon_r = 52.928$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.74, 7.74, 7.74); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.735 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.749 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.654 W/kg; SAR(10 g) = 0.339 W/kg

Maximum value of SAR (measured) = 0.623 W/kg




Figure 86 Body, Back Side, LTE Band 4 1RB Channel 20175

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 276 of 370

LTE Band 5 1RB Right Cheek High (Battery 1)

Date: 3/11/2015

Communication System: LTE Band 5; Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 40$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Right Cheek High/Area Scan (61x111x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (interpolated) = 0.267 mW/g

Right Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.39 V/m ; Power Drift = -0.028 dB

Peak SAR (extrapolated) = 0.384 W/kg

SAR(1 g) = 0.261 mW/g ; SAR(10 g) = 0.196 mW/g

Maximum value of SAR (measured) = 0.273 mW/g




Figure 87 Right Hand Touch Cheek LTE Band 5 1RB Channel 20600

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 277 of 370

LTE Band 5 1RB Back Side High (Battery 1, Distance 15mm)

Date: 3/10/2015

Communication System: LTE Band 5; Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844 \text{ MHz}$; $\sigma = 1.01 \text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side High/Area Scan (61x111x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.146 mW/g

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.9 V/m ; Power Drift = 0.016 dB

Peak SAR (extrapolated) = 0.177 W/kg

SAR(1 g) = 0.138 mW/g ; SAR(10 g) = 0.107 mW/g

Maximum value of SAR (measured) = 0.144 mW/g




Figure 88 Body, Back Side, LTE Band 5 1RB Channel 20600

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 278 of 370

LTE Band 5 1RB Back Side High (Battery 1, Distance 10mm)

Date: 3/10/2015

Communication System: LTE Band 5; Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844 \text{ MHz}$; $\sigma = 1.01 \text{ mho/m}$; $\epsilon_r = 55$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side High/Area Scan (71x111x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (interpolated) = 0.311 mW/g

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.5 V/m ; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 0.406 W/kg

SAR(1 g) = 0.316 mW/g ; SAR(10 g) = 0.227 mW/g

Maximum value of SAR (measured) = 0.330 mW/g




Figure 89 Body, Back Side, LTE Band 5 1RB Channel 20600

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 279 of 370

LTE Band 7 1RB Right Cheek High (Battery 2)

Date: 3/9/2015

Communication System: UID 0, LTE (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.941$ S/m; $\epsilon_r = 38.761$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(6.94, 6.94, 6.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek High/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.603 W/kg

Right Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.702 V/m; Power Drift = 0.176 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.577 W/kg; SAR(10 g) = 0.297 W/kg

Maximum value of SAR (measured) = 0.613 W/kg




Figure 90 Right Hand Touch Cheek LTE Band 7 1RB Channel 21350

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 280 of 370

LTE Band 7 1RB Front Side High (Battery 1, Distance 15mm)

Date: 3/9/2015

Communication System: UID 0, LTE (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 2.151$ S/m; $\epsilon_r = 52.442$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.29, 7.29, 7.29); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front Side High/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.352 W/kg

Front Side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.250 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.581 W/kg

SAR(1 g) = 0.326 W/kg; SAR(10 g) = 0.181 W/kg

Maximum value of SAR (measured) = 0.329 W/kg




Figure 91 Body, Front Side, LTE Band 7 1RB Channel 21350

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 281 of 370

LTE Band 7 1RB Front Side High (Battery 1, Distance 10mm)

Date: 3/9/2015

Communication System: UID 0, LTE (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 2.151$ S/m; $\epsilon_r = 52.442$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.29, 7.29, 7.29); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front Side High/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.456 W/kg

Front Side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.489 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.703 W/kg

SAR(1 g) = 0.399 W/kg; SAR(10 g) = 0.220 W/kg

Maximum value of SAR (measured) = 0.405 W/kg




Figure 92 Body, Front Side, LTE Band 7 1RB Channel 21350

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 282 of 370

LTE Band 12 1RB Right Cheek Middle (Battery 2)

Date: 3/15/2015

Communication System: LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.868$ mho/m; $\epsilon_r = 42.6$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.79, 9.79, 9.79); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Right Cheek Middle/Area Scan (61x111x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 0.051 mW/g

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.88 V/m; Power Drift = -0.094 dB

Peak SAR (extrapolated) = 0.061 W/kg

SAR(1 g) = 0.046 mW/g; SAR(10 g) = 0.037 mW/g

Maximum value of SAR (measured) = 0.051 mW/g




Figure 93 Right Hand Touch Cheek LTE Band 12 1RB Channel 23095

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 283 of 370

LTE Band 12 1RB Back Side Middle (Battery 1, Distance 15mm)

Date: 3/14/2015

Communication System: LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.928$ mho/m; $\epsilon_r = 54.8$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.073 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.99 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 0.105 W/kg

SAR(1 g) = 0.069 mW/g; SAR(10 g) = 0.048 mW/g

Maximum value of SAR (measured) = 0.073 mW/g




Figure 94 Body, Back Side, LTE Band 12 1RB Channel 23095

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 284 of 370

LTE Band 12 1RB Back Side Middle (Battery 2, Distance 10mm)

Date: 3/14/2015

Communication System: LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.928$ mho/m; $\epsilon_r = 54.8$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (71x111x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 0.120 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.43 V/m; Power Drift = -0.052 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.114 mW/g; SAR(10 g) = 0.075 mW/g

Maximum value of SAR (measured) = 0.122 mW/g




Figure 95 Body, Back Side, LTE Band 12 1RB Channel 23095

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 285 of 370

LTE Band 17 1RB Right Cheek Middle (Battery 1)

Date: 3/15/2015

Communication System: LTE B17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710 \text{ MHz}$; $\sigma = 0.87 \text{ mho/m}$; $\epsilon_r = 42.6$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.79, 9.79, 9.79); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Right Cheek Middle/Area Scan (61x111x1): Measurement grid: $dx=1.500\text{mm}$, $dy=1.500\text{mm}$

Maximum value of SAR (interpolated) = 0.046 mW/g

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.75 V/m ; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.134 W/kg

SAR(1 g) = 0.054 mW/g ; SAR(10 g) = 0.031 mW/g

Maximum value of SAR (measured) = 0.089 mW/g




Figure 96 Right Hand Touch Cheek LTE Band 17 1RB Channel 23790

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 286 of 370

LTE Band 17 1RB Back Side Middle (Battery1, Distance 15mm)

Date: 3/14/2015

Communication System: LTE B17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710$ MHz; $\sigma = 0.931$ mho/m; $\epsilon_r = 54.7$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.059 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.29 V/m; Power Drift = 0.032 dB
Peak SAR (extrapolated) = 0.081 W/kg
SAR(1 g) = 0.053 mW/g; SAR(10 g) = 0.038 mW/g

Maximum value of SAR (measured) = 0.056 mW/g




Figure 97 Body, Back Side, LTE Band 17 1RB Channel 23790

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 287 of 370

LTE Band 17 50%RB Right Edge Middle (Battery 1, Distance 10mm)

Date: 3/14/2015

Communication System: LTE B17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710 \text{ MHz}$; $\sigma = 0.931 \text{ mho/m}$; $\epsilon_r = 54.7$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.53, 9.53, 9.53); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Right Edge Middle/Area Scan (51x171x1): Measurement grid: $dx=1.000\text{mm}$, $dy=1.000\text{mm}$

Maximum value of SAR (interpolated) = 0.114 mW/g

Right Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.2 V/m ; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 0.145 W/kg

SAR(1 g) = 0.106 mW/g ; SAR(10 g) = 0.075 mW/g

Maximum value of SAR (measured) = 0.113 mW/g




Figure 98 Body, Right Edge, LTE Band 17 50%RB Channel 23790

LTE Band 25 1RB Left Cheek High (Battery 1)

Date: 3/17/2015

Communication System: UID 0, LTE (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1905$ MHz; $\sigma = 1.436$ S/m; $\epsilon_r = 39.583$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.94, 7.94, 7.94); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.861 W/kg

Left Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.133 V/m; Power Drift = 0.085 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.752 W/kg; SAR(10 g) = 0.460 W/kg

Maximum value of SAR (measured) = 0.766 W/kg




Figure 99 Left Hand Touch Cheek LTE Band 25 1RB Channel 26590

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 289 of 370

LTE Band 25 1RB Back Side High (Battery 1, Distance 15mm)

Date: 3/26/2015

Communication System: UID 0, LTE (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1905$ MHz; $\sigma = 1.529$ S/m; $\epsilon_r = 53.065$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.458 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.364 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.735 W/kg

SAR(1 g) = 0.415 W/kg; SAR(10 g) = 0.212 W/kg

Maximum value of SAR (measured) = 0.407 W/kg




Figure 100 Body, Back Side, LTE Band 25 1RB Channel 26590

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 290 of 370

LTE Band 25 1RB Back Side High (Battery 1, Distance 10mm)

Date: 3/26/2015

Communication System: UID 0, LTE (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1905$ MHz; $\sigma = 1.529$ S/m; $\epsilon_r = 53.065$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.57, 7.57, 7.57); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (71x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.08 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.460 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 2.03 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.489 W/kg

Maximum value of SAR (measured) = 1.16 W/kg




Figure 101 Body, Back Side, LTE Band 25 1RB Channel 26590

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 291 of 370

LTE Band 26 1RB Right Cheek Middle (Battery 1)

Date: 3/11/2015

Communication System: LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 831.5$ MHz; $\sigma = 0.917$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.30, 9.30, 9.30); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Right Cheek Middle/Area Scan (61x111x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 0.224 mW/g

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.74 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 0.273 W/kg

SAR(1 g) = 0.207 mW/g; SAR(10 g) = 0.158 mW/g

Maximum value of SAR (measured) = 0.213 mW/g




Figure 102 Right Hand Touch Cheek LTE Band 26 1RB Channel 26865

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 292 of 370

LTE Band 26 1RB Back Side Middle (Battery 1, Distance 15mm)

Date: 3/10/2015

Communication System: LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 831.5$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (61x111x1): Measurement grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.133 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.3 V/m; Power Drift = 0.047 dB
Peak SAR (extrapolated) = 0.161 W/kg

SAR(1 g) = 0.126 mW/g; SAR(10 g) = 0.098 mW/g

Maximum value of SAR (measured) = 0.131 mW/g




Figure 103 Body, Back Side, LTE Band 26 1RB Channel 26865

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 293 of 370

LTE Band 26 1RB Back Side Middle (Battery 2, Distance 10mm)

Date: 3/10/2015

Communication System: LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 831.5$ MHz; $\sigma = 0.998$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.45, 9.45, 9.45); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 11; Type: SAM V4.0; Serial: TP-1246

Measurement SW: DASY5, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Back Side Middle/Area Scan (71x111x1): Measurement grid: dx=1.500mm, dy=1.500mm

Maximum value of SAR (interpolated) = 0.282 mW/g

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.2 V/m; Power Drift = -0.061 dB

Peak SAR (extrapolated) = 0.361 W/kg

SAR(1 g) = 0.249 mW/g; SAR(10 g) = 0.170 mW/g

Maximum value of SAR (measured) = 0.288 mW/g




Figure 104 Body, Back Side, LTE Band 26 1RB Channel 26865

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 294 of 370

ANNEX C3: WiFi Antenna

802.11b Left Cheek Low (Battery 1)

Date: 3/25/2015

Communication System: UID 0, 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.771$ S/m; $\epsilon_r = 38.872$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.22, 7.22, 7.22); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Low/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.778 W/kg

Left Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.085 V/m; Power Drift = 0.057 dB

Peak SAR (extrapolated) = 1.93 W/kg

SAR(1 g) = 0.724 W/kg; SAR(10 g) = 0.315 W/kg

Maximum value of SAR (measured) = 0.755 W/kg




Figure 105 Left Hand Touch Cheek 802.11b Channel 1

802.11b Left Tilt Low (Battery 1)

Date: 3/25/2015

Communication System: UID 0, 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.771$ S/m; $\epsilon_r = 38.872$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.22, 7.22, 7.22); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Tilt Low/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.770 W/kg

Left Tilt Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.049 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 2.27 W/kg

SAR(1 g) = 0.780 W/kg; SAR(10 g) = 0.302 W/kg

Maximum value of SAR (measured) = 0.804 W/kg




Figure 106 Left Hand Tilt 15° 802.11b Channel 1

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 296 of 370

802.11b Back Side Low (Battery 1, Distance 15mm)

Date: 3/25/2015

Communication System: UID 0, 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.945$ S/m; $\epsilon_r = 52.239$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.42, 7.42, 7.42); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Low/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0873 W/kg

Back Side Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.434 V/m; Power Drift = 0.050 dB

Peak SAR (extrapolated) = 0.140 W/kg

SAR(1 g) = 0.078 W/kg; SAR(10 g) = 0.042 W/kg

Maximum value of SAR (measured) = 0.0846 W/kg




Figure 107 Body, Back Side, 802.11b Channel 1

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 297 of 370

802.11b Back Side Low (Battery 2, Distance 10mm)

Date: 3/25/2015

Communication System: UID 0, 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.945$ S/m; $\epsilon_r = 52.239$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.42, 7.42, 7.42); Calibrated: 1/30/2015;

Electronics: DAE4 Sn1291; Calibrated: 11/14/2014

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Low/Area Scan (91x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.183 W/kg

Back Side Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.487 V/m; Power Drift = 0.036 dB

Peak SAR (extrapolated) = 0.304 W/kg

SAR(1 g) = 0.152 W/kg; SAR(10 g) = 0.078 W/kg

Maximum value of SAR (measured) = 0.157 W/kg




Figure 108 Body, Back Side, 802.11b Channel 1

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 298 of 370

ANNEX D: Probe Calibration Certificate



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.cn <http://www.chinattl.cn>



Client **TA-ShangHai**

Certificate No: Z15-97010

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3677**

Calibration Procedure(s) **FD-Z11-2-004-01**
Calibration Procedures for Dosimetric E-field Probes

Calibration date: **January 30, 2015**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	01-Jul-14 (CTTL, No.J14X02146)	Jun-15
Power sensor NRP-Z91	101547	01-Jul-14 (CTTL, No.J14X02146)	Jun-15
Power sensor NRP-Z91	101548	01-Jul-14 (CTTL, No.J14X02146)	Jun-15
Reference10dBAttenuator	18N50W-10dB	13-Mar-14(TMC,No.JZ14-1103)	Mar-16
Reference20dBAttenuator	18N50W-20dB	13-Mar-14(TMC,No.JZ14-1104)	Mar-16
Reference Probe EX3DV4	SN 3617	28-Aug-14(SPEAG,No.EX3-3617_Aug14)	Aug-15
DAE4	SN 777	17-Sep-14 (SPEAG, DAE4-777_Sep14)	Sep -15
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGeneratorMG3700A	6201052605	01-Jul-14 (CTTL, No.J14X02145)	Jun-15
Network Analyzer E5071C	MY46110673	15-Feb-14 (TMC, No.JZ14-781)	Feb-15

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Qi Dianyuan	SAR Project Leader	
Approved by:	Lu Bingsong	Deputy Director of the laboratory	

Issued: January 31, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z15-97010

Page 1 of 11

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 299 of 370



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A,B,C,D	modulation dependent linearization parameters
Polarization Φ	Φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), $\theta=0$ is normal to probe axis

Connector Angle information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization $\theta=0$ ($f \leq 900\text{MHz}$ in TEM-cell; $f > 1800\text{MHz}$: waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}: A,B,C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800\text{MHz}$) and inside waveguide using analytical field distributions based on power measurements for $f > 800\text{MHz}$. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from $\pm 50\text{MHz}$ to $\pm 100\text{MHz}$.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Probe EX3DV4

SN: 3677

Calibrated: January 30, 2015

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 301 of 370



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3677

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.41	0.46	0.40	±10.8%
DCP(mV) ^B	101.9	102.0	104.6	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	182.5	±2.3%
		Y	0.0	0.0	1.0		198.5	
		Z	0.0	0.0	1.0		179.8	

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X, Y, Z do not affect the E²-field uncertainty inside TSL (see Page 5 and Page 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3677

Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz] ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	9.79	9.79	9.79	0.30	0.84	±12%
835	41.5	0.90	9.30	9.30	9.30	0.19	1.05	±12%
1750	40.1	1.37	8.02	8.02	8.02	0.21	1.14	±12%
1900	40.0	1.40	7.94	7.94	7.94	0.24	1.04	±12%
2450	39.2	1.80	7.22	7.22	7.22	0.65	0.68	±12%
2600	39.0	1.96	6.94	6.94	6.94	0.33	0.95	±12%
5200	36.0	4.66	5.55	5.55	5.55	0.42	1.18	±13%
5300	35.9	4.76	5.35	5.35	5.35	0.45	1.05	±13%
5600	35.5	5.07	5.05	5.05	5.05	0.42	1.26	±13%
5800	35.3	5.27	5.01	5.01	5.01	0.48	1.13	±13%

^C Frequency validity of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequency below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3677

Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz] ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	9.53	9.53	9.53	0.15	1.46	± 12%
835	55.2	0.97	9.45	9.45	9.45	0.17	1.35	± 12%
1750	53.4	1.49	7.74	7.74	7.74	0.18	1.36	± 12%
1900	53.3	1.52	7.57	7.57	7.57	0.18	1.31	± 12%
2450	52.7	1.95	7.42	7.42	7.42	0.37	1.08	± 12%
2600	52.5	2.16	7.29	7.29	7.29	0.40	0.97	± 12%
5200	49.0	5.30	4.96	4.96	4.96	0.45	1.42	± 13%
5300	48.9	5.42	4.76	4.76	4.76	0.46	1.48	± 13%
5600	48.5	5.77	4.36	4.36	4.36	0.49	1.80	± 13%
5800	48.2	6.00	4.45	4.45	4.45	0.50	1.20	± 13%

^C Frequency validity of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.


^F At frequency below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 7.5\%$ ($k=2$)

TA Technology (Shanghai) Co., Ltd. Test Report

Report No.: RHA1502-0012SAR02R1


Page 305 of 370





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Receiving Pattern (Φ), $\theta=0^\circ$

f=600 MHz, TEM



f=1800 MHz, R22



Uncertainty of Axial Isotropy Assessment: $\pm 0.9\%$ ($k=2$)

TA Technology (Shanghai) Co., Ltd.
Test Report


Report No.: RHA1502-0012SAR02R1

Page 306 of 370



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: ttl@chinattl.com Http://www.chinattl.cn

Dynamic Range $f(\text{SAR}_{\text{head}})$
(TEM cell, $f = 900 \text{ MHz}$)







Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn


Conversion Factor Assessment

f=835 MHz, WGLS R9(H_convF)

f=1750 MHz, WGLS R22(H_convF)



Deviation from Isotropy in Liquid



TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RHA1502-0012SAR02R1

Page 308 of 370



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3677

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	116.7
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disable
Probe Overall Length	337mm
Probe Body Diameter	10mm
Tip Length	9mm
Tip Diameter	2.5mm
Probe Tip to Sensor X Calibration Point	1mm
Probe Tip to Sensor Y Calibration Point	1mm
Probe Tip to Sensor Z Calibration Point	1mm
Recommended Measurement Distance from Surface	1.4mm

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 309 of 370

ANNEX E: D750V3 Dipole Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client **CTTL (Auden)**

Certificate No: **D750V3-1017_Aug14**

CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1017**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **August 28, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	18-Aug-14 (No. DAE4-601_Aug14)	Aug-15
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Michael Weber** **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** **Technical Manager**

Issued: August 28, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RHA1502-0012SAR02R1

Page 310 of 370

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.