FCC SAR Compliance Test Report

Product Name: Smart Phone

Model: H1611

Report No.: SYBH(Z-SAR)049052016-2

FCC ID: QISH1611

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	Wei Huanbin	Pan Man
DATE	2016-07-18	2016-07-18

Reliability Laboratory of Huawei Technologies Co., Ltd.

(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Tel: +86 755 28780808 Fax: +86 755 89652518

※ ※ Notice ※ ※

1. The laboratory has passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.

2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01 & 2174.02 & 2174.03

3. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.

4. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.

5. The test report is invalid if there is any evidence of erasure and/or falsification.

6. The test report is only valid for the test samples.

7. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

Copyright © Huawei Technologies Co., Ltd

Table of Contents

1 General Information 6
1.1 Statement of Compliance 6
1.2 RF exposure limits 7
1.3 EUT Description 8
1.3.1 General Description 10
1.3.2 Power reduction specification 11
1.4 Test specification(s) 12
1.5 Testing laboratory 12
1.6 Applicant and Manufacturer 12
1.7 Application details 12
1.8 Ambient Condition 12
2 SAR Measurement System 13
2.1 SAR Measurement Set-up 13
2.2 Test environment 14
2.3 Data Acquisition Electronics description 14
2.4 Probe description 15
2.5 Phantom description 16
2.6 Device holder description 17
2.7 Test Equipment List 18
3 SAR Measurement Procedure 19
3.1 Scanning procedure 19
3.2 Spatial Peak SAR Evaluation 20
3.3 Data Storage and Evaluation 21
4 System Verification Procedure 23
4.1 Tissue Verification 23
4.2 System Check 25
4.3 System check Procedure 27
5 SAR measurement variability and uncertainty 28
5.1 SAR measurement variability 28
5.2 SAR measurement uncertainty 28
6 SAR Test Configuration 29
6.1 Test Positions Configuration 29
6.1.1 General considerations 29
6.1.2 Head Exposure Condition 29
6.1.3 Body-worn Exposure Condition 30
6.1.4 Hotspot Exposure Condition 31
6.1.5 Product Specific 10-g Exposure Condition 31
6.2 3G SAR Test Reduction Procedure 31
6.3 GSM Test Configuration 32
6.4 UMTS Test Configuration 32
6.5 LTE Test Configuration 38
6.6 WiFi Test Configuration 40
6.6.1 Initial Test Position Procedure 40
6.6.2 Initial Test Configuration Procedure 40
6.6.3 Sub Test Configuration Procedure 40
6.6.4 WiFi 2.4G SAR Test Procedures 41
6.6.5 WiFi 5G SAR Test Procedures 41
6.6.6 BT SAR Test Procedures 44
7 SAR Measurement Results 45
7.1 Conducted power measurements 45
7.1.1 Conducted power measurements of GSM850 46
7.1.2 Conducted power measurements of GSM1900 46
7.1.3 Conducted power measurements of UMTS Band II 47
7.1.4 Conducted power measurements of UMTS Band V 49
7.1.5 Conducted power measurements of LTE Band II 51
7.1.6 Conducted power measurements of LTE Band IV 57
7.1.7 Conducted power measurements of LTE Band V 63

Copyright © Huawei Technologies Co., Ltd

7.1.8 Conducted power measurements of LTE Band XII 67
7.1.9 Conducted power measurements of LTE Band XXX 69
7.1.10 Conducted power measurements of WiFi 2.4G 70
7.1.11 Conducted power measurements of WiFi 5G 71
7.1.12 Conducted power measurements of BT 74
7.2 SAR measurement Results 75
7.2.1 SAR measurement Result of GSM850 77
7.2.2 SAR measurement Result of GSM1900 78
7.2.3 SAR measurement Result of UMTS Band II 80
7.2.4 SAR measurement Result of UMTS Band V 82
7.2.5 SAR measurement Result of LTE Band II 84
7.2.6 SAR measurement Result of LTE Band IV 88
7.2.7 SAR measurement Result of LTE Band V 91
7.2.8 SAR measurement Result of LTE Band XII 94
7.2.9 SAR measurement Result of LTE Band XXX 96
7.2.10 SAR measurement Result of WiFi 2.4G 98
7.2.11 SAR measurement Result of WiFi 5G 101
7.2.12 SAR measurement Result of BT 105
7.3 Multiple Transmitter Evaluation 106
7.3.1 Simultaneous Transmission Possibilities 107
7.3.2 SAR Summation Scenario 108
7.3.3 Simultaneous Transmission Conlcusion 108
Appendix A. System Check Plots 109
Appendix B. SAR Measurement Plots 109
Appendix C. Calibration Certificate 109
Appendix D. Photo documentation 109

Copyright © Huawei Technologies Co., Ltd

※ ※ Modified History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	2016-07-08	Pan Man
Rev.1.1	Page 98: Update the Head SAR test results table for WiFi 2.4G	2016-07-18	Pan Man

Copyright © Huawei Technologies Co., Ltd

1 General Information

1.1 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for H1611 is as below Table 1.

Band	Max Reported SAR(W/kg)			
	1-g Head SAR	1-g Body-worn SAR (15mm) *	1-g Hotspot SAR (10mm)	Product Specific 10-g SAR(0mm)**
GSM850	0.46	0.51	0.69	/
GSM1900	0.09	0.42	**0.78**	2.40
UMTS Band II	0.18	**0.81**	0.61	**3.27**
UMTS Band V	0.36	0.30	0.49	/
LTE Band II	0.18	0.71	0.59	3.19
LTE Band IV	0.20	0.50	0.55	/
LTE Band V	0.33	0.33	0.36	/
LTE Band XII	0.24	0.32	0.43	/
LTE Band XXX	0.08	0.29	0.75	/
WiFi 2.4G	0.85	0.11	0.23	/
WiFi 5G	**0.98**	0.19	/	0.75
BT	**/**	0.01	/	0.09
The highest simultaneous SAR value is 1.44 W/kg per KDB690783 D01				

Table 1:Summary of test result

Note:

1)* For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and that positions the handset a minimum of 15mm from the body. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

2)** For Product Specific 10-g SAR, this device has been tested and meets the 10-g SAR limits of 4.0 W/kg for general population/ uncontrolled exposure according to ANSI C95.1:1992/IEEE C95.1:1991 and Industry Canada Radio Standards Specification RSS-102.

The device is in compliance with Specific Absorption Rate（SAR）for general population/uncontraolled exposure limits according to the FCC rule §2.1093, the ANSI C95.1:1992/IEEE C95.1:1991, the NCRP Report Number 86 for uncontrolled environment, according to the Industry Canada Radio Standards Specification RSS-102 for General Population/Uncontrolled exposure, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013.

Copyright © Huawei Technologies Co., Ltd

1.2 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain/Body/Arms/Legs)	**1.60 W/kg**	8.00 W/kg
Spatial Average SAR** (Whole Body)	0.08 W/kg	0.40 W/kg
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	**4.00 W/kg**	20.00 W/kg

Table 2: RF exposure limits

The limit applied in this test report is shown in **bold** letters

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.

Copyright © Huawei Technologies Co., Ltd

1.3 EUT Description

Device Information:			
Product Name:	Smart Phone		
Model:	H1611		
FCC ID :	QISH1611		
SN No.:	A9M0116430000198 A9M0116430000334		
Device Type :	Portable device		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment / general population		
Hardware Version :	HL1H1611M		
Software Version :	H1611C07B013		
Antenna Type :	Internal antenna		
Others Accessories	Headset		
Device Operating Configurations:			
Supporting Mode(s)	GSM850/1900, UMTS Band II/V, LTE Band II/IV/V/XII/XXX, WiFi 2.4G/5G, BT		
Test Modulation	GSM(GMSK/8PSK),UMTS(QPSK),LTE(QPSK/16QAM), WiFi(DSSS/OFDM),BT(GFSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824-849	869-894
	GSM1900	1850-1910	1930-1990
	UMTS Band II	1850-1910	1930-1990
	UMTS Band V	824-849	869-894
	LTE Band II	1850-1910	1930-1990
	LTE Band IV	1710-1755	2110-2155
	LTE Band V	824-849	869-894
	LTE Band XII	699-716	729-746
	LTE Band XXX	2305-2315	2350-2360
	BT	2400-2483.5	
	WiFi 2.4G	2412-2462	
	WiFi 5G	5150-5350 5470-5725 5725-5850	
GPRS Multislot Class(10)	Max Number of Timeslots in Uplink:	2	
	Max Number of Timeslots in Downlink:	4	
	Max Total Timeslot:	5	
EGPRS Multislot Class(10)	Max Number of Timeslots in Uplink:	2	
	Max Number of Timeslots in Downlink:	4	
	Max Total Timeslot:	5	
HSDPA UE Category	14		
HSUPA UE Category	6		
DC-HSDPA UE Category	24		

Copyright © Huawei Technologies Co., Ltd

Power Class:	4,tested with power level 5(GSM850)
	1,tested with power level 0(GSM1900)
	3, tested with power control “all 1”(UMTS Band II)
	3, tested with power control “all 1”(UMTS Band V)
	3, tested with power control all Max.(LTE Band II)
	3, tested with power control all Max.(LTE Band IV)
	3, tested with power control all Max.(LTE Band V)
	3, tested with power control all Max.(LTE Band XII)
	3, tested with power control all Max.(LTE Band XXX)
Test Channels (low-mid-high):	128-190-251(GSM850)
	512-661-810(GSM1900)
	9262-9400-9538(UMTS Band II)
	4132-4182-4233(UMTS Band V)
	18607-18900-19193(LTE Band II BW=1.4MHz)
	18615-18900-19185(LTE Band II BW=3MHz)
	18625-18900-19175(LTE Band II BW=5MHz)
	18650-18900-19150(LTE Band II BW=10MHz)
	18675-18900-19125(LTE Band II BW=15MHz)
	18700-18900-19100(LTE Band II BW=20MHz)
	19957-20175-20393(LTE Band IV BW=1.4MHz)
	19965-20175-20385(LTE Band IV BW=3MHz)
	19975-20175-20375(LTE Band IV BW=5MHz)
	20000-20175-20350(LTE Band IV BW=10MHz)
	20025-20175-20325(LTE Band IV BW=15MHz)
	20050-20175-20300(LTE Band IV BW=20MHz)
	20407-20525-20643(LTE Band V BW=1.4MHz)
	20415-20525-20635(LTE Band V BW=3MHz)
	20425-20525-20625(LTE Band V BW=5MHz)
	20450-20525-20600(LTE Band V BW=10MHz)
	23017-23095-23173(LTE Band XII BW=1.4MHz)
	23025-23095-23165(LTE Band XII BW=3MHz)
	23035-23095-23155(LTE Band XII BW=5MHz)
	23060-23095-23130(LTE Band XII BW=10MHz)
	27685-27710-27735(LTE Band XXX BW=5MHz)
	27710(LTE Band XXX BW=10M)
	802.11b/g/n 20M:1-6-11 802.11n 40M:3-6-9 (WiFi 2.4G)
	802.11a/n 20M: 36-40-44-48-52-56-60-64-100-104-108-112-116-120-124-128-132-136-140-149-153-157-161-165 802.11 n 40M: 38-46-54-62-102-110-118-126-134-151-159 (WiFi 5G)

Table 3:Device information and operating configuration
Note: WiFi 5G does not support hotspot function.

Copyright © Huawei Technologies Co., Ltd

1.3.1 General Description

H1611 is subscriber equipment in the GSM/UMTS/LTE system.
The GSM frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only GSM850/1900 test data included in this report.The UMTS frequency band is band I and band II and band V, but only Band II and Band V test data included in this report.The LTE frequency band is Band II band IV and band V and band XII and Band XXX,all bands test data included in this report.The Mobile Phone implements such functions as RF signal receiving/transmitting, LTE/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS and Wi-Fi etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

Battery information:

Name	Manufacture	Serials number	Description
Li-Polymer Battery	Sunwoda Electronic Co., LTD	NA	Battery Model: HB4242B4EBW Rated capacity: 3000mAh Nominal Voltage: ⎓ +3.8V

Copyright © Huawei Technologies Co., Ltd

1.3.2 Power reduction specification

This device uses a single fixed level of power reduction through static table look-up for SAR compliance and it is triggered by a single event or operation:
A fixed level power reduction is applied for some frequency bands when hotspot mode becomes active. When the hotspot is disabled, the power value will be recovered.

The following tables summerize the key power reduction information.The detailed full power and reduced tune-up specifications and conducted power measurement results are provided in Section 7 of this report. The PAG requirements can be excluded per KDB 388624D02.

Band	Power Reduction Level Amount (dB)	
	Hotspot is active	Hotspot is disabled
GSM850	0.0	0.0
GSM1900	3.0	0.0
UMTS Band II	5.0	0.0
UMTS Band V	1.0	0.0
LTE Band II	4.5	0.0
LTE Band IV	1.0	0.0
LTE Band V	1.0	0.0
LTE Band XII	0.0	0.0
LTE Band XXX	0.0	0.0

Copyright © Huawei Technologies Co., Ltd

1.4 Test specification(s)

ANSI C95.1:1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
IEEE Std 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
RSS-102	Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands (Issue 5 of March 2015)
KDB941225 D01	3G SAR Procedures v03r01
KDB941225 D05	SAR for LTE Devices v02r05
KDB941225 D06	Hotspot SAR v02r01
KDB447498 D01	General RF Exposure Guidance v06
KDB648474 D04	Handsets SAR v01r03
KDB248227 D01	SAR Guidance for IEEE 802 11 Wi-Fi SAR v02r02
KDB865664 D01	SAR measurement 100 MHz to 6 GHz v01r04
KDB865664 D02	SAR Reporting v01r02
KDB690783 D01	SAR Listings on Grants v01r03

1.5 Testing laboratory

Test Site	The Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	Section G1,Huawei Base Bantian, Longgang District, Shenzhen 518129, P.R. China
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01 & 2174.02 & 2174.03

1.6 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.7 Application details

Start Date of test	2016-06-03
End Date of test	2016-07-07

1.8 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

Copyright © Huawei Technologies Co., Ltd

2 SAR Measurement System

2.1 SAR Measurement Set-up



The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- A unit to operate the optical surface detector which is connected to the EOC.
- The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
- The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 7.
- DASY5 software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- System check dipoles allowing to validate the proper functioning of the system.

Copyright © Huawei Technologies Co., Ltd

2.2 Test environment

The DASY5 measurement system is placed at the head end of a room with dimensions:
5 x 2.5 x 3 m³, the SAM phantom is placed in a distance of 75 cm from the side walls and 1.1m from the rear wall. Above the test system a 1.5 x 1.5 m² array of pyramid absorbers is installed to reduce reflections from the ceiling.
Picture 1 of the photo documentation shows a complete view of the test environment.
The system allows the measurement of SAR values larger than 0.005 mW/g.

2.3 Data Acquisition Electronics description

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

DAE4

Input Impedance	200MOhm	
The Inputs	symmetrical and floating	
Common mode rejection	above 80 dB	

Copyright © Huawei Technologies Co., Ltd

2.4 Probe description

These probes are specially designed and calibrated for use in liquids with high permittivities. They should not be used in air, since the spherical isotropy in air is poor (±2 dB). The dosimetric probes have special calibrations in various liquids at different frequencies.

Isotropic E-Field Probe ES3DV3 for Dosimetric Measurements

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Calibration	ISO/IEC 17025 calibration service available.	
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB (30 MHz to 4 GHz)	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic range	5 µW/g to > 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones	

Isotropic E-Field Probe EX3DV4 for Dosimetric Measurements

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Calibration	ISO/IEC 17025 calibration service available.	
Frequency	10 MHz to >6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic range	10 µW/g to > 100 mW/g; Linearity: ± 0.2 dB(noise:typically<1µW/g)	
Dimensions	Overall length: 337 mm (Tip:20 mm) Tip diameter:2.5 mm (Body:12 mm) Typical distance from probe tip to dipole centers: 1mm	
Application	High precision dosimetric measurements in any exposure scenario(e.g.,very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%	

Copyright © Huawei Technologies Co., Ltd

2.5 Phantom description

SAM Twin Phantom

Shell Thickness	2mm±0.2mm;The ear region:6.0±0.2mm	
Filling Volume	Approximately 25 liters	
Dimensions	Length:1000mm; Width:500mm; Height: adjustable feet	
Measurement Areas	Left hand Right hand Flat phantom	
The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible. Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.		

The following figure shows the definition of reference point:



ELI4 Phantom

Shell Thickness	2mm±0.2mm	
Filling Volume	Approximately 30 liters	
Dimensions	Major axis:600mm; Minor axis:400mm;	
Measurement Areas	Flat phantom	
The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30MHz to 6GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209-2 and all known tissue simulating liquids.		

The phantom shell material is resistant to all ingredients used in the tissue-equivalent liquid recipes. The shell of the phantom including ear spacers is constructed from low permittivity and low loss material, with a relative permittivity 2≤εr≤5 at ≤3 GHz,3≤ εr≤4 at >3 GHz and and a loss tangent ⩽0.05.

Copyright © Huawei Technologies Co., Ltd

2.6 Device holder description

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity ε =3 and loss tangent σ =0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.
The device holder permits the device to be positioned with a tolerance of ±1° in the tilt angle.

Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values.
Therefore those devices are normally only tested at the flat part of the SAM.

Copyright © Huawei Technologies Co., Ltd

2.7 Test Equipment List

This table gives a complete overview of the SAR measurement equipment.
Devices used during the test described are marked ☒

	Manufacturer	Device	Type	Serial number	Date of last calibration) *	Valid period
☒	SPEAG	Dosimetric E-Field Probe	EX3DV4	3736	2016-04-26	One year
☒	SPEAG	Dosimetric E-Field Probe	EX3DV4	3744	2015-07-24	One year
☒	SPEAG	Dosimetric E-Field Probe	EX3DV4	7351	2015-10-30	One year
☒	SPEAG	750MHz Dipole	D750V3	1044	2015-09-14	Three years
☒	SPEAG	835MHz Dipole	D835V2	4d059	2016-04-20	Three years
☒	SPEAG	1750MHz Dipole	D1750V2	1123	2016-02-02	Three years
☒	SPEAG	1900MHz Dipole	D1900V2	5d091	2015-09-21	Three years
☒	SPEAG	2300MHz Dipole	D2300V2	1020	2015-09-21	Three years
☒	SPEAG	2450MHz Dipole	D2450V2	860	2016-02-08	Three years
☒	SPEAG	5GHz Dipole	D5GHzV2	1155	2015-04-27	Three years
☒	SPEAG	Data acquisition electronics	DAE4	1236	2015-11-23	One year
☒	SPEAG	Software	DASY 5	N/A	NCR	NCR
☐	SPEAG	Twin Phantom	SAM1	TP-1475	NCR	NCR
☐	SPEAG	Twin Phantom	SAM2	TP-1474	NCR	NCR
☒	SPEAG	Twin Phantom	SAM3	TP-1597	NCR	NCR
☒	SPEAG	Twin Phantom	SAM4	TP-1620	NCR	NCR
☐	SPEAG	Twin Phantom	SAM5	TP-1894	NCR	NCR
☐	SPEAG	Twin Phantom	SAM6	TP-1892	NCR	NCR
☒	R & S	Universal Radio Communication Tester	CMU 200	113989	2016-05-12	One year
☒	R & S	Universal Radio Communication Tester	CMW 500	126854	2016-01-08	One year
☒	Agilent	Wireless Connectivity Test Set	N4010A	MY49081592	2015-10-30	One year
☒	Agilent	Network Analyser	E5071C	MY46213349	2016-01-08	One year
☒	Agilent	Dielectric Probe Kit	85070E	2484	NCR	NCR
☒	Agilent	Signal Generator	N5181A	MY47420989	2015-10-30	One year
☒	MINI-CIRCUITS	Amplifier	ZHL-42W	QA1402001	NCR	NCR
☒	MINI-CIRCUITS	Amplifier	ZVE-8G+	N523101139	NCR	NCR
☒	AR	Directional Coupler	DC7144M1	0423264	2016-04-07	One year
☒	Agilent	Dual Directional Coupler	772D	MY52180173	2016-01-06	One year
☒	Agilent	Power Meter	E4417A	MY54100027	2016-03-31	One year
☒	Agilent	Power Meter Sensor	E9321A	MY54130007	2016-03-31	One year
☒	Agilent	Power Meter	E4417A	MY45101339	2016-01-06	One year
☒	Agilent	Power Meter Sensor	E9321A	MY44420359	2016-01-06	One year

Note:

1) Per KDB865664D01 requirements for dipole calibration, the test laboratory has adopted three-year extended calibration interval. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

a) There is no physical damage on the dipole;

b) System check with specific dipole is within 10% of calibrated value;

c) The most recent return-loss result, measured at least annually, deviates by no more than 20% from the previous measurement.

d) The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

3) *All the equipments are within the valid period when the tests are performed.

Copyright © Huawei Technologies Co., Ltd

3 SAR Measurement Procedure

3.1 Scanning procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and system check. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

- The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max. +/- 5 %.

- The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1mm). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within ± 30°.)

- The “area scan” measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The standard scan uses large grid spacing for faster measurement. Standard grid spacing for head measurements is 15 mm in x- and y- dimension(⩽2GHz)，12 mm in x- and y-dimension(2-4 GHz) and 10mm in x- and y- dimension(4-6GHz). If a finer resolution is needed, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation.
  Results of this coarse scan are shown in Appendix B.

- A “zoom scan” measures the field in a volume around the 2D peak SAR value acquired in the previous “coarse” scan. This is a fine grid with maximum scan spatial resolution: Δx_{zoom}, Δy_{zoom}⩽ 2GHz - ⩽8mm, 2-4GHz - ⩽5 mm and 4-6 GHz-⩽4mm; Δz_{zoom} ⩽3GHz - ⩽5 mm, 3-4 GHz- ⩽4mm and 4-6GHz-⩽2mm where the robot additionally moves the probe along the z-axis away from the bottom of the Phantom. DASY is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in Appendix B. Test results relevant for the specified standard (see chapter 1.4.)are shown in table form form in chapter 7.2.

- A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 2 mm steps. This measurement shows the continuity of the liquid and can - depending in the field strength – also show the liquid depth. A z-axis scan of the measurement with maximum SAR value is shown in Appendix B.

Copyright © Huawei Technologies Co., Ltd

The following table summarizes the area scan and zoom scan resolutions per FCC KDB 865664D01:

Frequency	Maximun Area Scan resolution (Δx_{area}, Δy_{area})	Maximun Zoom Scan spatial resolution (Δx_{Zoom}, Δy_{Zoom})	Maximun Zoom Scan spatial resolution			Minimum zoom scan volume (x,y,z)
			Uniform Grid	Graded Grad		
			$\Delta z_{Zoom}(n)$	$\Delta z_{Zoom}(1)$*	$\Delta z_{Zoom}(n>1)$*	
≤2GHz	≤15mm	≤8mm	≤5mm	≤4mm	≤1.5*$\Delta z_{Zoom}(n-1)$	≥30mm
2-3GHz	≤12mm	≤5mm	≤5mm	≤4mm	≤1.5*$\Delta z_{Zoom}(n-1)$	≥30mm
3-4GHz	≤12mm	≤5mm	≤4mm	≤3mm	≤1.5*$\Delta z_{Zoom}(n-1)$	≥28mm
4-5GHz	≤10mm	≤4mm	≤3mm	≤2.5mm	≤1.5*$\Delta z_{Zoom}(n-1)$	≥25mm
5-6GHz	≤10mm	≤4mm	≤2mm	≤2mm	≤1.5*$\Delta z_{Zoom}(n-1)$	≥22mm

3.2 Spatial Peak SAR Evaluation

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of 5 x 5 x 7 points(with 8mm horizontal resolution) or 7 x 7 x 7 points(with 5mm horizontal resolution) or 8 x 8 x 7 points(with 4mm horizontal resolution). The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting 'Graph Evaluated'.

- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR - values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.

- All neighboring volumes are evaluated until no neighboring volume with a higher average value is found.

Extrapolation

The extrapolation is based on a least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computermathematik, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff].

Volume Averaging

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

Advanced Extrapolation

DASY5 uses the advanced extrapolation option which is able to compansate boundary effects on E-field probes.

Copyright © Huawei Technologies Co., Ltd

3.3 Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension "DAE4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i$, a_{i0}, a_{i1}, a_{i2}
	- Conversion factor	$ConvF_i$
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \bullet cf/dcp_i$$

with	V_i	= compensated signal of channel i	(i = x, y, z)
	U_i	= input signal of channel i	(i = x, y, z)
	cf	= crest factor of exciting field	(DASY parameter)
	dcp_i	= diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be

Copyright © Huawei Technologies Co., Ltd

evaluated:

E-field probes: $E_i = (V_i / Norm_i \bullet ConvF)^{1/2}$

H-field probes: $H_i = (V_i)^{1/2} \bullet (a_{i0} + a_{i1}f + a_{i2}f^2)/f$

with V_i = compensated signal of channel i (i = x, y, z)

$Norm_i$ = sensor sensitivity of channel i (i = x, y, z) [mV/(V/m)^2] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_Y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \bullet \sigma) / (\rho \bullet 1000)$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm^3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.The power flow density is calculated assuming the excitation field to be a free space field.

$P_{pwe} = E_{tot}^2 / 3770$ or $P_{pwe} = H_{tot}^2 \bullet 37.7$

with P_{pwe} = equivalent power density of a plane wave in mW/cm^2

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

Copyright © Huawei Technologies Co., Ltd

4 System Verification Procedure

4.1 Tissue Verification

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectic parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within ± 5% of the target values.

The following materials are used for producing the tissue-equivalent materials.

Ingredients (% of weight)	**Head Tissue**						
Frequency Band (MHz)	**750**	**835**	**1750**	**1900**	**2300**	**2450**	2600
Water	39.2	41.45	52.64	55.242	62.82	62.7	55.242
Salt (NaCl)	2.7	1.45	0.36	0.306	0.51	0.5	0.306
Sugar	57.0	56.0	0.0	0.0	0.0	0.0	0.0
HEC	0.0	1.0	0.0	0.0	0.0	0.0	0.0
Bactericide	0.0	0.1	0.0	0.0	0.0	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0
DGBE	0.0	0.0	47.0	44.542	36.67	36.8	44.452
Ingredients (% of weight)	**Body Tissue**						
Frequency Band (MHz)	**750**	**835**	**1750**	**1900**	**2300**	**2450**	2600
Water	50.3	52.4	69.91	69.91	73.32	73.2	64.493
Salt (NaCl)	1.60	1.40	0.13	0.13	0.06	0.04	0.024
Sugar	47.0	45.0	0.0	0.0	0.0	0.0	0.0
HEC	0.0	1.0	0.0	0.0	0.0	0.0	0.0
Bactericide	0.0	0.1	0.0	0.0	0.0	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0
DGBE	0.0	0.0	29.96	29.96	26.62	26.7	32.252

Table 4: Tissue Dielectric Properties

Salt: 99+% Pure Sodium Chloride; Sugar: 98+% Pure Sucrose; Water: De-ionized, 16MΩ+ resistivity
HEC: Hydroxyethyl Cellulose; DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]
Triton X-100(ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

☒**Simulating Head Liquid for 5G(HBBL3500-5800MHz), Manufactured by SPEAG:**

Ingredients	(% by weight)
Water	50-65%
Mineral oil	10-30%
Emulsifiers	8-25%
Sodium salt	0-1.5%

☒**Simulating Body Liquid for 5G(MBBL3500-5800MHz),Manufactured by SPEAG:**

Ingredients	(% by weight)
Water	60-80%
Esters,Emulsifiers,Inhibitors	20-40%
Sodium salt	0-1.5%

Copyright © Huawei Technologies Co., Ltd

Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Deviation (Within +/-5%)		Liquid Temp.	Test Date
		εr	σ (S/m)	εr	σ (S/m)	$\Delta\varepsilon_r$	Δσ		
750H	705	42.14	0.89	43.72	0.847	3.75%	-4.80%	21.4°C	2016/06/12
	710	42.11	0.89	43.61	0.855	3.56%	-3.94%		
	750	41.90	0.89	43.17	0.894	3.03%	0.44%		
750B	705	55.70	0.96	53.94	0.922	-3.16%	-4.01%	21.6°C	2016/06/12
	710	55.70	0.96	53.01	0.926	-4.83%	-3.55%		
	750	55.50	0.96	53.59	0.977	-3.44%	1.80%		
835H	825	41.60	0.90	41.93	0.930	0.79%	3.34%	21°C	2016/06/04
	835	41.50	0.90	41.83	0.936	0.80%	3.96%		
	850	41.50	0.92	41.67	0.945	0.41%	2.75%		
835B	825	55.20	0.97	53.64	0.976	-2.83%	0.58%	21°C	2016/06/06
	835	55.20	0.97	53.53	0.985	-3.03%	1.60%		
	850	55.20	0.99	53.35	1.001	-3.35%	1.11%		
1750H	1710	40.10	1.35	39.92	1.317	-0.45%	-2.44%	21.5°C	2016/06/11
	1730	40.10	1.36	39.83	1.342	-0.67%	-1.32%		
	1750	40.10	1.37	39.74	1.365	-0.90%	-0.36%		
	1800	40.00	1.40	39.49	1.415	-1.28%	1.07%		
1750B	1710	53.50	1.46	51.95	1.443	-2.90%	-1.16%	21.1°C	2016/06/12
	1730	53.50	1.48	51.94	1.462	-2.92%	-1.22%		
	1750	53.40	1.49	51.91	1.482	-2.79%	-0.54%		
	1800	53.30	1.52	51.78	1.540	-2.85%	1.32%		
1900H	1850	40.00	1.40	40.13	1.378	0.33%	-1.57%	21.5°C	2016/06/07
	1880	40.00	1.40	39.97	1.406	-0.08%	0.43%		
	1900	40.00	1.40	39.96	1.422	-0.10%	1.57%		
	1910	40.00	1.40	39.88	1.433	-0.30%	2.36%		
1900B	1850	53.30	1.52	52.26	1.485	-1.95%	-2.30%	21.4°C	2016/06/08
	1880	53.30	1.52	52.20	1.515	-2.06%	-0.33%		
	1900	53.30	1.52	52.14	1.530	-2.18%	0.66%		
	1910	53.30	1.52	52.08	1.535	-2.29%	0.99%		
2300H	2300	39.46	1.67	38.26	1.695	-3.07%	1.68%	21.8°C	2016/06/11
	2310	39.44	1.68	38.26	1.708	-2.99%	1.91%		
	2355	39.36	1.72	38.08	1.741	-3.25%	1.46%		
2300B	2300	52.90	1.81	55.01	1.844	3.99%	2.05%	21.8°C	2016/06/11
	2310	52.89	1.82	54.97	1.858	3.93%	2.31%		
	2355	52.83	1.86	54.84	1.912	3.80%	2.85%		
2450H	2410	39.30	1.76	40.36	1.775	2.70%	0.85%	21.3°C	2016/06/03
	2435	39.20	1.79	40.27	1.802	2.73%	0.67%		
	2450	39.20	1.80	40.21	1.818	2.58%	1.00%		
	2460	39.20	1.81	40.15	1.828	2.42%	0.99%		

Copyright © Huawei Technologies Co., Ltd

2450B	2410	52.80	1.91	52.32	1.956	-0.91%	2.41%	21.3°C	2016/06/11
	2435	52.70	1.94	52.24	1.990	-0.87%	2.58%		
	2450	52.70	1.95	52.19	2.008	-0.97%	2.97%		
	2460	52.70	1.96	52.15	2.019	-1.04%	3.01%		
2450B	2410	52.80	1.91	54.17	1.953	2.59%	2.25%	21.8°C	2016/07/07
	2435	52.70	1.94	54.09	1.984	2.64%	2.27%		
	2450	52.70	1.95	54.04	2.004	2.54%	2.77%		
	2460	52.70	1.96	54.00	2.017	2.47%	2.91%		
5G H	5250	35.95	4.71	36.43	4.734	1.34%	0.51%	21.8°C	2016/06/14
	5600	35.50	5.07	35.90	5.056	1.13%	-0.28%	21.8°C	2016/06/14
	5750	35.85	5.22	36.25	5.264	1.12%	0.84%	21.4°C	2016/06/14
5G B	5250	48.95	5.36	48.36	5.481	-1.21%	2.26%	21.5°C	2016/06/18
	5600	48.47	5.77	48.02	5.944	-0.92%	3.02%	21.8°C	2016/06/19
	5750	48.27	5.94	48.83	6.184	1.16%	4.11%	21.4°C	2016/06/21
ε_r= Relative permittivity, σ= Conductivity									

Table 5:Measured Tissue Parameter

Note: 1）The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2°C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

2）KDB 865664 was ensured to be applied for probe calibration frequencies greater than or equal to 50MHz of the EUT frequencies.

3）The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies. The SAR test plots may slightly differ from the table above since the DASY rounds to three significant digits.

4.2 System Check

The system check is performed for verifying the accuracy of the complete measurement system and performance of the software. The system check is performed with tissue equivalent material according to IEEE P1528 (described above). The following table shows system check results for all frequency bands and tissue liquids used during the tests(Graphic Plot(s) see Appendix A).

System Check	Target SAR (1W)		Measured SAR (Normalized to 1W)		Deviation (Within +/-10%)		Liquid Temp.	Test Date
	1-g (W/kg)	10-g (W/kg)	1-g (W/kg)	10-g (W/kg)	Δ1g	Δ10g		
750MHz Head	8.22	5.41	8.40	5.52	2.19%	2.03%	21.4°C	2016/06/12
835MHz Head	9.30	6.05	9.80	6.36	5.38%	5.12%	21°C	2016/06/04
1750MHz Head	35.10	18.60	34.40	18.28	-1.99%	-1.72%	21.5°C	2016/06/11
1900MHz Head	40.80	21.40	41.60	21.56	1.96%	0.75%	21.5°C	2016/06/07
2300MHz Head	48.20	23.20	51.60	24.64	7.05%	6.21%	21.8°C	2016/06/11
2450MHz Head	50.80	23.70	52.40	24.04	3.15%	1.43%	21.3°C	2016/06/03

Copyright © Huawei Technologies Co., Ltd

5250MHz Head	74.40	21.60	79.50	22.60	6.85%	4.63%	21.8°C	2016/06/14
5600MHz Head	80.40	23.20	81.20	23.00	1.00%	-0.86%	21.8°C	2016/06/14
5750MHz Head	76.70	21.90	80.40	22.80	4.82%	4.11%	21.4°C	2016/06/14
750MHz Body	8.69	5.76	8.88	5.80	2.19%	0.69%	21.6°C	2016/06/12
835MHz Body	9.41	6.20	9.40	6.12	-0.11%	-1.29%	21°C	2016/06/06
1750MHz Body	36.30	19.50	36.56	19.32	0.72%	-0.92%	21.1°C	2016/06/12
1900MHz Body	40.20	21.30	42.80	22.04	6.47%	3.47%	21.4°C	2016/06/08
2300MHz Body	48.10	23.30	49.60	23.84	3.12%	2.32%	21.8°C	2016/06/11
2450MHz Body	51.90	24.30	51.20	23.40	-1.35%	-3.70%	21.3°C	2016/06/03
2450MHz Body	51.90	24.30	52.80	25.32	1.73%	4.20%	21.8°C	2016/07/07
5250MHz Body	72.20	20.40	76.00	21.10	5.26%	3.43%	21.5°C	2016/06/18
5600MHz Body	76.40	21.50	78.10	21.70	2.23%	0.93%	21.8°C	2016/06/19
5750MHz Body	73.20	20.60	71.20	19.80	-2.73%	-3.88%	21.4°C	2016/06/21

Table 6:System Check Results

Copyright © Huawei Technologies Co., Ltd

4.3 System check Procedure

The system check is performed by using a system check dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a plexiglass spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 250 mW(below 5GHz) or 100mW(above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system check to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system check to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

System check results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system.



Copyright © Huawei Technologies Co., Ltd

5 SAR measurement variability and uncertainty

5.1 SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
2) When the original highest measured SAR is ⩾ 0.80 W/kg, repeat that measurement once.
3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ⩾ 1.45 W/kg (~ 10% from the 1-g SAR limit).
4) Perform a third repeated measurement only if the original, first or second repeated measurement is ⩾ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The detailed repeated measurement results are shown in Section 7.2.

5.2 SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04,when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

Copyright © Huawei Technologies Co., Ltd

6 SAR Test Configuration

6.1 Test Positions Configuration

6.1.1 General considerations

Per IEEE 1528-2013，two imaginary lines on the handset were established: the vertical centerline and the horizontal line (See Figure 1).



Figure 1 Hand Vertical Center & Horizontal Line Reference Points

6.1.2 Head Exposure Condition

Per IEEE 1528-2013, Head SAR measurements were made in the “cheek” position (See Figure 2) and the “tilt” position (See Figure 3). The device should be tested in both positions on left and right sides of the SAM phantom.



Figure 2 Front, Side and Top View of Cheek Position

Copyright © Huawei Technologies Co., Ltd

Figure 3 Front, Side and Top View of Tilt 15° Position

Note:

M Mouth reference point

LE Left ear reference point (ERP)

RE Right ear reference point(ERP)

6.1.3 Body-worn Exposure Condition

Body-worn operating configurations are tested with the holder attached to the device and positioned against a flat phantom with test separation distance of 15mm in a normal use configuration (See Figure 4). Per FCC KDB648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



Figure 4 Test position for Body-Worn device

Copyright © Huawei Technologies Co., Ltd

6.1.4 Hotspot Exposure Condition

Per FCC KDB 941225D06, The SAR test separation distance for hotspot mode is determined according to device form factor. When the overall length and width of a device is > 9 cm x 5 cm, a test separation distance of 10 mm is required for hotspot mode SAR measurements. A test separation distance of 5 mm or less is required for smaller devices. Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge; for the data modes, wireless technologies and frequency bands supporting hotspot mode. The SAR results are used to determine simultaneous transmission SAR test exclusion for hotspot mode; otherwise, simultaneous transmission SAR measurement is required.

6.1.5 Product Specific 10-g Exposure Condition

Per FCC KDB 648474D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the device is marketed as "Phablet".

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for Product Specific 10-g SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.

6.2 3G SAR Test Reduction Procedure

Per KDB941225 D01v03, in the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode. This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as "otherwise" in the applicable procedures; SAR measurement is required for the secondary mode.

Copyright © Huawei Technologies Co., Ltd

6.3 GSM Test Configuration

SAR tests for GSM850 and GSM1900, a communication link is set up with a base station by air link. Using CMU200 the power lever is set to “5”and “0” in SAR of GSM850 and GSM1900. The tests in the band of GSM850 and GSM1900 are performed in the mode of GPRS/EGPRS function. Since the GPRS class is 10 for this EUT, it has at most 2 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslot is 5. The EGPRS class is 10 for this EUT, it has at most 2 timeslots in uplink, and at most 4 timeslots in downlink, the maximum total timeslot is 5.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

6.4 UMTS Test Configuration

1) Output Power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1’s” for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are requied in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

2) WCDMA

a. Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

b. Body SAR Measurements

SAR for body-worn accessory configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode

3) HSDPA

SAR for body exposure configurations is measured according to the “Body SAR Measurements’’ procedures of 3G device. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode. This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that

Copyright © Huawei Technologies Co., Ltd

procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as “otherwise” in the applicable procedures; SAR measurement is required for the secondary mode.

Per KDB941225 D01v03, the 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures for the highest reported SAR body exposure configuration in 12.2 kbps RMC.

HSDPA should be configured according to UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HAPRQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission condition, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. The β_c and β_d gain factors for DPCCH and DPDCH were set according to the values in the below table, β_{hs} for HS-DPCCH is set automatically to the correct value when ΔACK, ΔNACK, ΔCQI = 8. The variation of the β_c /β_d ratio causes a power reduction at sub-tests 2 - 4.

Sub-test	β_c	β_d	β_d (SF)	β_c /β_d	β_{hs} (1)	CM(dB)(2)	MPR (dB)
1	2/15	15/15	64	2/15	4/15	0.0	0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0	0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: △ACK, △NACK and △CQI = 8 $A_{hs} = \beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$

Note 2 : CM=1 for β_c/β_d= 12/15, β_{hs}/β_c = 24/15. For all other combinations of DPDCH,DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 3 : For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1,TF1) to β_c = 11/15 and β_d = 15/15

Table 7: Sub-tests for UMTS Release 5 HSDPA

The measurements were performed with a Fixed Reference Channel (FRC) and H-Set 1 QPSK.

Parameter	Value
Nominal average inf. bit rate	534 kbit/s
Inter-TTI Distance	3 TTI’s
Number of HARQ Processes	2 Processes
Information Bit Payload	3202 Bits
MAC-d PDU size	336 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	4800 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	9600 SMLs
Coding Rate	0.67
Number of Physical Channel Codes	5

Table 8:settings of required H-Set 1 QPSK acc. to 3GPP 34.121

Copyright © Huawei Technologies Co., Ltd

HS-DSCH Category	Maximum HS-DSCH Codes Received	Minimum Inter-TTI Interval	Maximum HS-DSCH Transport Block Bits/HS-DSCH TTI	Total Soft Channel Bits
1	5	3	7298	19200
2	5	3	7298	28800
3	5	2	7298	28800
4	5	2	7298	38400
5	5	1	7298	57600
6	5	1	7298	67200
7	10	1	14411	115200
8	10	1	14411	134400
9	15	1	25251	172800
10	15	1	27952	172800
11	5	2	3630	14400
12	5	1	3630	28800
13	15	1	34800	259200
14	15	1	42196	259200
15	15	1	23370	345600
16	15	1	27952	345600

Table 9:HSDPA UE category

4) HSUPA

SAR for body exposure configurations is measured according to the "Body SAR Measurements" procedures of 3G device. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

Per KDB941225 D01v03, the 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures for the highest reported body exposure SAR configuration in 12.2 kbps RMC.

Due to inner loop power control requirements in HSDPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSDPA should be configured according to the values indicated below as well as other applicable procedures described in the 'WCDMA Handset' and 'Release 5 HSDPA Data Device' sections of 3G device.

Copyright © Huawei Technologies Co., Ltd

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs}(1)	β_{ec}	β_{ed}	β_{ec} (SF)	β_{ed} (code)	CM(2) (dB)	MPR (dB)	AG(4) Index	E-TFCI
1	11/15(3)	15/15(3)	64	11/15(3)	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1}:47/15 β_{ed2}:47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15(4)	15/15(4)	64	15/15(4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ ACK, Δ NACK and Δ CQI = 8 $A_{hs} = \beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference

Note 3 : For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1,TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$

Note 4 : For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1,TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$

Note 5 : Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Table 10:Subtests for UMTS Release 6 HSUPA

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E-DCH TTI(ms)	Minimum Speading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	10	2SF2&2SF4	11484	5.76
	4	4	2		20000	2.00
7 (No DPDCH)	4	8	2	2SF2&2SF4	22996	?
	4	4	10		20000	?

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4.UE categories 1 to 6 support QPSK only. UE category 7 supports QPSK and 16QAM.(TS25.306-7.3.0).

Table 11:HSUPA UE category

Copyright © Huawei Technologies Co., Ltd

5) DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a Second serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS 34.108 v9.5.0. A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0

Table E.5.0: Levels for HSDPA connection setup

Parameter During Connection setup	Unit	Value
P-CPICH_Ec/Ior	dB	-10
P-CCPCH and SCH_Ec/Ior	dB	-12
PICH _Ec/Ior	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/Ior	dB	-5
OCNS_Ec/Ior	dB	-3.1

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13
The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.
The measurements were performed with a Fixed Reference Channel (FRC) H-Set 12 with QPSK

Parameter	Value
Nominal average inf. bit rate	60 kbit/s
Inter-TTI Distance	1 TTI's
Number of HARQ Processes	6 Processes
Information Bit Payload	120 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	960 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	3200 SMLs
Coding Rate	0.15
Number of Physical Channel Codes	1

Table 12:settings of required H-Set 12 QPSK acc. to 3GPP 34.121
Note:

1.The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table above.
2.Maximum number of transmission is limited to 1,i.e.,retransmission is not allowed. The redundancy and constellation version 0 shall be used.

Copyright © Huawei Technologies Co., Ltd



Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 5 procedures. A summary of subtest settings are illustrated below:

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (1)	CM(dB)(2)	MPR (dB)
1	2/15	15/15	64	2/15	4/15	0.0	0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0	0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ ACK, Δ NACK and Δ CQI = 8 $A_{hs} = \beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$

Note 2: CM=1 for β_c/β_d= 12/15, β_{hs}/β_c = 24/15. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to β_c = 11/15 and β_d = 15/15

Up commands are set continuously to set the UE to Max power.

Note:

1.The Dual Carriers transmission only applies to HSDPA physical channels

2.The Dual Carriers belong to the same Node and are on adjacent carriers.

3.The Dual Carriers do not support MIMO to serve UEs configured for dual cell operation

4.The Dual Carriers operate in the same frequency band .

5.The device doesn't support the modulation of 16QAM in uplink but 64QAM in downlink for DC-HSDPA mode.

6.The device doesn’t support carrier aggregation for it just can operate in Release 8.

Copyright © Huawei Technologies Co., Ltd

6.5 LTE Test Configuration

SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02r05. The CMW500 WideBand Radio Communication Tester was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing.SAR test were performed with the same number of RB and RB offsets transmitting on all TTI frames(Maximum TTI)

1) Spectrum Plots for RB configurations

A properly configured base station simulator was used for LTE output power measurements and SAR testing.Therefore, spectrum plots for RB configurations were not required to be included in this report.

2) MPR

When MPR is implemented permanently within the UE, regardless of network requirements, only those RB configurations allowed by 3GPP for the channel bandwidth and modulation combinations may be tested with MPR active. Configurations with RB allocations less than the RB thresholds required by 3GPP must be tested without MPR.

The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

3) A-MPR

A-MPR(Additional MPR) has been disabled for all SAR tests by using Network Signalling Value of “NS_01”on the base station simulator.

4) LTE procedures for SAR testing

A) Largest channel bandwidth standalone SAR test requirements

i) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

ii) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in i) are applied to measure the SAR for QPSK with 50% RB allocation.

Copyright © Huawei Technologies Co., Ltd

iii) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in i) and ii) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

iv) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is > ½ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

B) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is > ½ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

Copyright © Huawei Technologies Co., Ltd

6.6 WiFi Test Configuration

For WiFi SAR testing, a communication link is set up with the testing software for WiFi mode test. During the test,at the each test frequency channel, the EUT is operated at the RF continuous emission mode. The RF signal utilized in SAR measurement has 100% duty cycle and its crest factor is 1. The test procedures in KDB 248227D01v02r02 are applied.

6.6.1 Initial Test Position Procedure

For exposure condition with multiple test position, such as handsets operating next to the ear, devices with hotspot mode or UMPC mini-tablet , procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all position in an exposure condition. The test position with the highest extrapolated(peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4W/kg, no additional testing for the remaining test position is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is ≤ 0.8W/kg or all test position are measured. For all positions/configurations tested using the initial test position and subsequent test positions, when the *reported* SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the *reported* SAR is ≤ 1.2 W/kg or all required channels are tested.

6.6.2 Initial Test Configuration Procedure

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required (see section 5.3.2 of KDB 248227D01v02). SAR test reduction of subsequent highest output test channels is based on the *reported* SAR of the initial test configuration.

For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.

When the *reported* SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until the *reported* SAR is ≤ 1.2 W/kg or all required channels are tested.

6.6.3 Sub Test Configuration Procedure

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units.

When the highest reported SAR for the initial test configuration, according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

Copyright © Huawei Technologies Co., Ltd

6.6.4 WiFi 2.4G SAR Test Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions.

A) 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

1) When the *reported* SAR of the highest measured maximum output power channel (section 3.1 of of KDB 248227D01v02) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

2) When the *reported* SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any *reported* SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

B) 2.4GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3 of of KDB 248227D01v02r01). SAR is not required for the following 2.4 GHz OFDM conditions.

1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.

2) When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

6.6.5 WiFi 5G SAR Test Procedures

A) U-NII-1 and U-NII-2A Bands

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following：

1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.

2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.

3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the

Copyright © Huawei Technologies Co., Ltd

bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

B) U-NII-2C and U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. when Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

Copyright © Huawei Technologies Co., Ltd

C) OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.

2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.

3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.

4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.

After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.

1) The channel closest to mid-band frequency is selected for SAR measurement.

2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

D) SAR Test Requirements for OFDM configurations

When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

Copyright © Huawei Technologies Co., Ltd

6.7 BT SAR Test Configuration

For BT SAR testing,the EUT's BT test mode is open and the EUT is connected with N4010A which provides continuous transmitting RFsignal with maximum output power.The N4010A controls the EUT operating at 2441MHz(39CH) with hopping off,and data rata is set for HD5. This RF signal utilized in SAR measurement has almost 100% duty cycle and crest factor is 1.

Copyright © Huawei Technologies Co., Ltd

7 SAR Measurement Results

7.1 Conducted power measurements

For the measurements a Rohde & Schwarz Radio Communication Tester CMU 200&CMW500 was used. SAR drift measured at the same position in liquid before and after each SAR test as below 7.2 chapter.

Note: CMU200 measures GSM peak and average output power for active timeslots.For SAR the timebased average power is relevant. The difference in between depends on the duty cycle of the TDMA signal :

No. of timeslots	1	2	3	4
Duty Cycle	1:8.3	1:4.1	1:2.77	1:2.08
timebased avg. power compared to slotted avg. power	-9.19dB	-6.13dB	-4.42dB	-3.18dB

The signalling modes differ as follows:

mode	coding scheme	modulation
GPRS	CS1 to CS4	GMSK
EDGE	MCS1 to MCS4	GMSK
EDGE	MCS5 to MCS9	8PSK

Apart from modulation change (GMSK/8PSK) coding schemes differ in code rate without influence on the RF signal. Therefore one coding scheme per mode was selected for conducted power measurements.

Copyright © Huawei Technologies Co., Ltd

7.1.1 Conducted power measurements of GSM850

GSM850		Burst-Averaged output Power (dBm)				Division Factors	Frame-Averaged output Power (dBm)			
		Tune-up	128CH	190CH	251CH		Tune-up	128CH	190CH	251CH
GSM (CS)		33.5	33.08	33.25	33.32	-9.19	24.31	23.89	24.06	24.13
GPRS/ EDGE (GMSK)	1 Tx Slot	33.5	33.14	33.23	33.31	-9.19	24.31	23.95	24.04	24.12
	2 Tx Slots	**31.5**	**30.91**	**30.72**	**30.82**	**-6.13**	**25.37**	**24.78**	**24.59**	**24.69**
EDGE (8PSK)	1 Tx Slot	27.0	26.91	26.82	26.88	-9.19	17.81	17.72	17.63	17.69
	2 Tx Slots	26.0	24.79	24.73	24.67	-6.13	19.87	18.66	18.6	18.54

Table 13:Conducted power measurement results of GSM850

Note:

1) The conducted power of GSM850 is measured with RMS detector.

2) Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timesolts.

3) Per KDB941225 D01v03r01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

7.1.2 Conducted power measurements of GSM1900

GSM1900		Burst-Averaged output Power (dBm)				Division Factors	Frame-Averaged output Power (dBm)			
		Tune-up	512CH	661CH	810CH		Tune-up	512CH	661CH	810CH
GSM (CS)		30.5	29.7	30.06	29.68	-9.19	21.31	20.51	20.87	20.49
GPRS/ EDGE (GMSK)	1 Tx Slot	30.5	29.78	29.78	29.75	-9.19	21.31	20.59	20.59	20.56
	2 Tx Slots	**29.2**	**29.05**	**28.85**	**29.06**	**-6.13**	**23.07**	**22.92**	**22.72**	**22.93**
EDGE (8PSK)	1 Tx Slot	27.5	26.43	26.37	26.27	-9.19	18.31	17.24	17.18	17.08
	2 Tx Slots	25.7	24.1	24.11	24.04	-6.13	19.57	17.97	17.98	17.91

Table 14: Conducted power measurement results of GSM1900(Hotspot disable)

Note:

1) The conducted power of GSM1900 is measured with RMS detector.

2) Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timesolts.

3) Per KDB941225 D01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

Copyright © Huawei Technologies Co., Ltd

GSM1900		Burst-Averaged output Power (dBm)				Division Factors	Frame-Averaged output Power (dBm)			
		Tune-up	512CH	661CH	810CH		Tune-up	512CH	661CH	810CH
GSM (CS)		27.5	26.72	26.62	26.85	-9.19	18.31	17.53	17.43	17.66
GPRS/ EDGE (GMSK)	1 Tx Slot	27.5	26.71	26.65	26.87	-9.19	18.31	17.52	17.46	17.68
	2 Tx Slots	**26.2**	**24.62**	**24.64**	**24.61**	**-6.13**	**20.07**	**18.49**	**18.51**	**18.48**
EDGE (8PSK)	1 Tx Slot	26.5	26.18	26.13	26.16	-9.19	17.31	16.99	16.94	16.97
	2 Tx Slots	24.7	24.51	24.54	24.61	-6.13	18.57	18.38	18.41	18.48

Table 15: Conducted power measurement results of GSM1900(Hotspot activated)

Note:

1) The conducted power of GSM1900 is measured with RMS detector.

2) Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timesolts.

3) Per KDB941225 D01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

7.1.3 Conducted power measurements of UMTS Band II

UMTS Band II		Tune-up	Conducted Power (dBm)		
			9262CH	9400CH	9538CH
WCDMA	12.2kbps RMC	**22.6**	**21.98**	**22.01**	**21.93**
	12.2kbps AMR	22.6	21.97	21.98	21.92
HSDPA	Subtest 1	22.6	20.87	20.89	20.93
	Subtest 2	21.6	20.63	20.87	20.92
	Subtest 3	21.0	20.39	20.32	20.42
	Subtest 4	21.0	20.04	20.04	20.39
HSUPA	Subtest 1	21.6	20.81	20.92	20.20
	Subtest 2	21.1	19.80	19.75	19.79
	Subtest 3	21.1	19.85	19.15	19.11
	Subtest 4	21.1	20.08	20.11	20.15
	Subtest 5	21.6	20.47	20.46	20.37
DC-HSDPA	Subtest 1	22.6	20.89	20.89	20.93
	Subtest 2	21.6	20.61	20.87	20.91
	Subtest 3	21.0	20.35	20.31	20.44
	Subtest 4	21.0	20.04	20.04	20.32

Copyright © Huawei Technologies Co., Ltd

Table 16: Conducted power measurement results of UMTS Band II(Hotspot disable)
Note:
1) The conducted power of UMTS Band II is measured with RMS detector.
2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).
3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is ≤ ¼ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the Second mode.

UMTS Band II		Tune-up	Conducted Power (dBm)		
			9262CH	9400CH	9538CH
WCDMA	12.2kbps RMC	**17.6**	**17.01**	**16.81**	**16.67**
	12.2kbps AMR	17.6	16.99	16.78	16.65
HSDPA	Subtest 1	17.6	16.26	16.29	16.28
	Subtest 2	16.6	16.07	16.05	16.06
	Subtest 3	16.0	15.61	15.5	15.21
	Subtest 4	16.0	15.58	15.43	15.19
HSUPA	Subtest 1	16.6	16.21	16.35	15.75
	Subtest 2	16.1	15.32	15.27	15.33
	Subtest 3	16.1	15.24	15.28	15.15
	Subtest 4	16.1	15.6	15.56	15.47
	Subtest 5	16.6	15.93	15.96	15.87
DC-HSDPA	Subtest 1	17.6	16.21	16.21	16.24
	Subtest 2	16.6	16.04	16.07	16.06
	Subtest 3	16.0	15.51	15.51	15.21
	Subtest 4	16.0	15.54	15.41	15.13

Table 17: Conducted power measurement results of UMTS Band II(Hotspot activated)
Note:
1) The conducted power of UMTS Band II is measured with RMS detector.
2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).
3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is ≤ ¼ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the Second mode.

Copyright © Huawei Technologies Co., Ltd

7.1.4 Conducted power measurements of UMTS Band V

UMTS Band V		Tune-up	Conducted Power (dBm)		
			4132CH	4182CH	4233CH
WCDMA	12.2kbps RMC	**24.0**	**23.35**	**23.41**	**23.32**
	12.2kbps AMR	24.0	23.35	23.41	23.32
HSDPA	Subtest 1	23.5	22.36	22.45	22.37
	Subtest 2	23.0	22.20	22.37	22.27
	Subtest 3	22.5	21.42	21.48	21.42
	Subtest 4	22.5	21.72	21.81	21.72
HSUPA	Subtest 1	22.5	22.13	22.23	22.20
	Subtest 2	22.0	21.21	21.23	21.15
	Subtest 3	21.0	20.41	20.40	20.50
	Subtest 4	22.0	21.59	21.54	21.49
	Subtest 5	23.0	21.68	21.70	21.99
DC-HSDPA	Subtest 1	23.5	22.31	22.42	22.35
	Subtest 2	23.0	22.22	22.35	22.24
	Subtest 3	22.5	21.43	21.41	21.41
	Subtest 4	22.5	21.71	21.74	21.74

Table 18: Conducted power measurement results of UMTS Band V(Hotspot disable)

Note:

1) The conducted power of UMTS Band V is measured with RMS detector.

2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).

3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is ≤ ¼ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the Second mode.

Copyright © Huawei Technologies Co., Ltd

UMTS Band V		Tune-up	Conducted Power (dBm)		
			4132CH	4182CH	4233CH
WCDMA	12.2kbps RMC	**23.0**	**22.55**	**22.58**	**22.45**
	12.2kbps AMR	23.0	22.54	22.56	22.42
HSDPA	Subtest 1	22.5	21.37	21.51	21.45
	Subtest 2	22.0	21.05	21.15	21.12
	Subtest 3	21.5	20.44	20.61	20.49
	Subtest 4	21.5	20.45	20.59	20.48
HSUPA	Subtest 1	21.5	21.31	21.14	20.98
	Subtest 2	21.0	20.26	20.33	20.17
	Subtest 3	20.0	19.59	19.31	19.45
	Subtest 4	21.0	20.55	20.59	20.66
	Subtest 5	22.0	21.1	20.93	21.87
DC-HSDPA	Subtest 1	22.5	21.31	21.52	21.41
	Subtest 2	22.0	21.01	21.14	21.12
	Subtest 3	21.5	20.46	20.63	20.45
	Subtest 4	21.5	20.41	20.58	20.44

Table 19: Conducted power measurement results of UMTS Band V(Hotspot activated)

Note:

1) The conducted power of UMTS Band V is measured with RMS detector.

2) The bolded 12.2kbps RMC mode was selected for SAR testing(the primary mode).

3) Per KDB941225 D01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is ≤ ¼ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the Second mode.

Copyright © Huawei Technologies Co., Ltd

7.1.5 Conducted power measurements of LTE Band II

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
					18607CH	18900CH	19193CH
1.4MHz	QPSK	1	0	22.3	21.41	21.30	21.44
		1	3	22.3	21.56	21.38	21.60
		1	5	22.3	21.55	21.27	21.40
		3	0	22.3	21.39	21.23	21.40
		3	2	22.3	21.46	21.34	21.47
		3	3	22.3	21.46	21.33	21.46
		6	0	21.3	20.37	20.23	20.38
	16QAM	1	0	21.3	20.91	20.86	20.90
		1	3	21.3	21.18	20.95	21.09
		1	5	21.3	21.19	20.87	21.13
		3	0	21.3	20.67	20.57	20.56
		3	2	21.3	20.74	20.65	20.30
		3	3	21.3	20.74	20.67	20.40
		6	0	20.8	19.92	19.66	19.43
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
					18615CH	18900CH	19185CH
3MHz	QPSK	1	0	22.3	21.64	21.55	21.37
		1	7	22.3	21.66	21.43	21.81
		1	14	22.3	21.68	21.54	21.54
		8	0	21.3	20.38	20.33	20.30
		8	4	21.3	20.36	20.30	20.35
		8	7	21.3	20.41	20.39	20.43
		15	0	21.3	20.36	20.32	20.47
	16QAM	1	0	21.3	20.63	20.39	20.31
		1	7	21.3	20.58	20.64	20.57
		1	14	21.3	20.55	20.34	20.54
		8	0	20.8	19.36	18.88	19.39
		8	4	20.8	19.53	18.97	19.42
		8	7	20.8	19.19	18.98	19.55
		15	0	20.8	19.23	19.28	19.54

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18625CH	Channel 18900CH	Channel 19175CH
5MHz	QPSK	1	0	22.3	21.16	21.42	21.37
		1	13	22.3	21.46	21.45	21.33
		1	24	22.3	21.45	21.46	21.65
		12	0	21.3	20.40	20.34	20.34
		12	6	21.3	20.42	20.29	20.41
		12	13	21.3	20.39	20.37	20.46
		25	0	21.3	20.40	20.31	20.31
	16QAM	1	0	21.3	20.21	20.38	20.35
		1	13	21.3	20.24	20.34	20.31
		1	24	21.3	20.31	20.29	20.26
		12	0	20.8	19.22	19.11	19.22
		12	6	20.8	19.43	19.32	19.30
		12	13	20.8	19.61	19.27	19.30
		25	0	20.8	19.45	19.43	19.37
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18650CH	Channel 18900CH	Channel 19150CH
10MHz	QPSK	1	0	22.3	21.68	21.49	21.77
		1	25	22.3	21.70	21.50	21.58
		1	49	22.3	21.65	21.65	21.69
		25	0	21.3	20.45	20.36	20.58
		25	13	21.3	20.41	20.44	20.52
		25	25	21.3	20.39	20.39	20.36
		50	0	21.3	20.43	20.38	20.50
	16QAM	1	0	21.3	20.58	20.58	20.75
		1	25	21.3	20.40	21.02	20.56
		1	49	21.3	21.00	21.14	21.03
		25	0	20.8	19.42	19.31	19.34
		25	13	20.8	19.16	19.35	19.48
		25	25	20.8	19.14	19.13	19.30
		50	0	20.8	19.37	19.29	19.19

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18675CH	Channel 18900CH	Channel 19125CH
15MHz	QPSK	1	0	22.3	21.79	21.74	21.63
		1	38	22.3	21.73	21.65	21.61
		1	74	22.3	21.83	21.78	21.55
		36	0	21.3	20.54	20.37	20.50
		36	18	21.3	20.39	20.40	20.47
		36	39	21.3	20.39	20.35	20.39
		75	0	21.3	20.50	20.33	20.39
	16QAM	1	0	21.3	20.91	20.33	20.33
		1	38	21.3	20.74	20.32	20.18
		1	74	21.3	20.85	20.93	20.92
		36	0	20.8	19.48	19.28	19.37
		36	18	20.8	19.34	19.28	19.35
		36	39	20.8	19.47	19.36	19.19
		75	0	20.8	19.39	19.30	19.36
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18700CH	Channel 18900CH	Channel 19100CH
20MHz	QPSK	1	0	22.3	**21.58**	21.44	21.49
		1	50	22.3	21.46	21.43	21.50
		1	99	22.3	21.35	**21.51**	**21.64**
		50	0	21.3	**20.57**	**20.47**	**20.54**
		50	25	21.3	20.52	20.38	20.46
		50	50	21.3	20.53	20.42	20.47
		100	0	21.3	**20.54**	20.41	20.50
	16QAM	1	0	21.3	20.41	20.35	20.81
		1	50	21.3	20.35	20.27	20.47
		1	99	21.3	20.11	20.50	20.43
		50	0	20.8	19.44	19.38	19.51
		50	25	20.8	19.48	19.51	19.34
		50	50	20.8	19.42	19.40	19.38
		100	0	20.8	19.43	19.32	19.43

Table 20: Conducted power measurement results of LTE Band II(Hotspot disable)

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18607CH	Channel 18900CH	Channel 19193CH
1.4MHz	QPSK	1	0	17.8	15.89	15.81	16.25
		1	3	17.8	15.96	15.89	16.06
		1	5	17.8	15.93	15.90	15.98
		3	0	17.8	15.85	15.87	15.94
		3	2	17.8	15.93	15.96	16.05
		3	3	17.8	15.84	15.95	16.04
		6	0	16.8	15.91	15.82	15.90
	16QAM	1	0	16.8	16.21	16.56	16.61
		1	3	16.8	16.38	16.67	16.64
		1	5	16.8	16.29	16.59	16.71
		3	0	16.8	15.95	16.23	16.21
		3	2	16.8	16.11	16.25	16.30
		3	3	16.8	15.56	16.18	16.11
		6	0	16.3	15.98	15.85	15.98
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18615CH	Channel 18900CH	Channel 19185CH
3MHz	QPSK	1	0	17.8	16.15	16.08	16.05
		1	7	17.8	16.14	16.06	16.19
		1	14	17.8	16.06	16.13	16.19
		8	0	16.8	15.84	15.84	15.99
		8	4	16.8	15.90	15.93	15.96
		8	7	16.8	15.94	15.88	15.98
		15	0	16.8	15.91	15.83	16.05
	16QAM	1	0	16.8	16.16	15.95	16.23
		1	7	16.8	16.13	16.13	16.47
		1	14	16.8	16.09	16.17	16.03
		8	0	16.3	15.87	15.87	15.65
		8	4	16.3	16.04	15.85	16.07
		8	7	16.3	15.92	15.84	16.25
		15	0	16.3	15.84	16.03	16.17

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18625CH	Channel 18900CH	Channel 19175CH
5MHz	QPSK	1	0	17.8	16.02	16.11	16.05
		1	13	17.8	16.16	16.11	16.15
		1	24	17.8	15.83	16.01	16.21
		12	0	16.8	15.87	15.88	15.92
		12	6	16.8	15.95	15.84	15.94
		12	13	16.8	16.04	15.97	15.92
		25	0	16.8	15.96	15.93	15.94
	16QAM	1	0	16.8	15.96	16.05	15.97
		1	13	16.8	15.91	15.89	16.01
		1	24	16.8	15.89	15.80	15.84
		12	0	16.3	15.89	15.81	15.79
		12	6	16.3	15.84	15.88	15.79
		12	13	16.3	15.99	15.92	16.08
		25	0	16.3	16.11	16.02	16.12
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18650CH	Channel 18900CH	Channel 19150CH
10MHz	QPSK	1	0	17.8	16.05	16.30	16.36
		1	25	17.8	16.14	16.23	16.18
		1	49	17.8	16.16	16.24	16.19
		25	0	16.8	15.91	15.91	16.09
		25	13	16.8	15.86	15.96	15.97
		25	25	16.8	15.95	16.08	16.01
		50	0	16.8	15.96	15.89	16.11
	16QAM	1	0	16.8	16.16	16.21	16.23
		1	25	16.8	16.60	16.58	16.55
		1	49	16.8	16.57	16.64	16.64
		25	0	16.3	15.84	15.83	15.97
		25	13	16.3	15.97	15.85	16.03
		25	25	16.3	15.90	15.89	15.90
		50	0	16.3	15.89	15.88	15.96

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18675CH	Channel 18900CH	Channel 19125CH
15MHz	QPSK	1	0	17.8	16.30	16.35	16.18
		1	38	17.8	16.04	16.01	16.13
		1	74	17.8	16.11	16.29	16.13
		36	0	16.8	16.01	15.86	16.03
		36	18	16.8	15.93	15.92	16.00
		36	39	16.8	15.97	16.04	15.92
		75	0	16.8	15.96	15.94	16.10
	16QAM	1	0	16.8	16.42	15.88	15.86
		1	38	16.8	16.26	16.23	15.73
		1	74	16.8	16.43	16.49	16.43
		36	0	16.3	15.83	15.81	16.01
		36	18	16.3	15.89	15.79	16.17
		36	39	16.3	15.98	15.88	15.93
		75	0	16.3	15.91	15.90	15.96
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 18700CH	Channel 18900CH	Channel 19100CH
20MHz	QPSK	1	0	17.8	16.28	16.03	16.11
		1	50	17.8	**16.31**	**16.18**	**16.15**
		1	99	17.8	16.16	16.02	16.09
		50	0	16.8	**16.30**	16.06	16.12
		50	25	16.8	16.24	16.01	16.09
		50	50	16.8	16.22	15.94	16.03
		100	0	16.8	16.04	15.93	16.06
	16QAM	1	0	16.8	15.96	16.15	16.10
		1	50	16.8	16.24	16.01	16.33
		1	99	16.8	16.06	16.04	16.67
		50	0	16.3	16.15	15.95	16.10
		50	25	16.3	16.10	16.00	16.18
		50	50	16.3	16.07	16.06	16.19
		100	0	16.3	16.01	15.94	15.92

Table 21: Conducted power measurement results of LTE Band II(Hotspot activated)

Copyright © Huawei Technologies Co., Ltd

7.1.6 Conducted power measurements of LTE Band IV

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 19957CH	Channel 20175CH	Channel 20393CH
1.4MHz	QPSK	1	0	24.0	23.14	23.08	23.08
		1	3	24.0	23.08	23.14	23.01
		1	5	24.0	23.07	23.09	22.94
		3	0	24.0	23.08	23.02	22.87
		3	2	24.0	23.06	23.05	23.05
		3	3	24.0	23.05	22.92	22.94
		6	0	23.0	22.12	22.01	21.94
	16QAM	1	0	23.5	22.74	22.49	21.97
		1	3	23.5	22.82	22.57	22.06
		1	5	23.5	22.82	22.54	22.10
		3	0	23.5	22.01	22.25	22.26
		3	2	23.5	21.90	22.15	22.46
		3	3	23.5	21.81	22.24	22.20
		6	0	22.5	20.86	21.25	21.07
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 19965CH	Channel 20175CH	Channel 20385CH
3MHz	QPSK	1	0	24.0	23.32	23.14	23.14
		1	7	24.0	23.22	23.10	23.15
		1	14	24.0	23.18	23.06	22.88
		8	0	23.0	22.07	21.95	21.94
		8	4	23.0	22.03	21.91	21.98
		8	7	23.0	22.07	21.99	21.95
		15	0	23.0	22.03	22.03	21.99
	16QAM	1	0	23.5	22.27	22.37	22.00
		1	7	23.5	22.14	22.26	21.81
		1	14	23.5	22.10	22.26	21.59
		8	0	22.5	20.72	21.00	20.93
		8	4	22.5	20.70	21.05	20.89
		8	7	22.5	20.66	20.93	20.86
		15	0	22.5	20.88	21.05	21.02

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 19975CH	Channel 20175CH	Channel 20375CH
5MHz	QPSK	1	0	24.0	22.87	22.96	23.03
		1	13	24.0	22.81	22.80	22.84
		1	24	24.0	22.88	22.98	23.04
		12	0	23.0	22.11	22.06	21.97
		12	6	23.0	22.04	21.92	21.94
		12	13	23.0	22.07	21.96	21.94
		25	0	23.0	21.98	21.99	21.99
	16QAM	1	0	23.5	21.98	22.08	22.31
		1	13	23.5	21.66	21.55	22.28
		1	24	23.5	21.65	21.67	22.30
		12	0	22.5	20.83	20.95	20.94
		12	6	22.5	21.03	20.93	20.90
		12	13	22.5	21.00	20.92	21.06
		25	0	22.5	21.08	20.97	20.91
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20000CH	Channel 20175CH	Channel 20350CH
10MHz	QPSK	1	0	24.0	23.29	23.41	23.30
		1	25	24.0	23.34	23.21	23.02
		1	49	24.0	23.14	23.37	22.84
		25	0	23.0	22.05	22.06	22.05
		25	13	23.0	22.09	21.99	21.98
		25	25	23.0	22.09	21.98	21.99
		50	0	23.0	22.11	22.06	22.03
	16QAM	1	0	23.5	21.98	22.27	22.14
		1	25	23.5	21.86	22.64	21.85
		1	49	23.5	21.79	22.80	22.10
		25	0	22.5	20.91	20.93	21.19
		25	13	22.5	20.87	21.01	21.12
		25	25	22.5	20.97	20.96	21.04
		50	0	22.5	20.96	20.95	20.92

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20025CH	Channel 20175CH	Channel 20325CH
15MHz	QPSK	1	0	24.0	23.49	23.25	23.12
		1	38	24.0	23.40	23.09	22.91
		1	74	24.0	23.43	23.19	22.96
		36	0	23.0	22.04	22.00	22.03
		36	18	23.0	22.01	21.91	22.05
		36	39	23.0	22.03	21.88	21.96
		75	0	23.0	21.95	21.99	21.98
	16QAM	1	0	23.5	22.07	22.09	22.95
		1	38	23.5	21.95	21.78	22.72
		1	74	23.5	22.00	21.76	22.76
		36	0	22.5	21.01	21.04	21.05
		36	18	22.5	21.06	20.94	20.83
		36	39	22.5	20.99	20.92	20.78
		75	0	22.5	20.91	20.95	21.01
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20050CH	Channel 20175CH	Channel 20300CH
20MHz	QPSK	1	0	24.0	**23.16**	**23.14**	**22.84**
		1	50	24.0	22.91	22.97	22.81
		1	99	24.0	23.02	22.98	22.65
		50	0	23.0	**22.06**	22.05	22.03
		50	25	23.0	22.02	21.97	22.02
		50	50	23.0	21.96	21.93	21.95
		100	0	23.0	22.01	22.05	22.03
	16QAM	1	0	23.5	22.63	22.65	22.44
		1	50	23.5	22.40	22.57	22.39
		1	99	23.5	21.96	21.94	22.24
		50	0	22.5	20.98	21.00	21.16
		50	25	22.5	21.02	20.93	21.05
		50	50	22.5	21.00	21.00	21.07
		100	0	22.5	21.05	21.02	21.08

Table 22: Conducted power measurement results of LTE Band IV(Hotspot disable)

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 19957CH	Channel 20175CH	Channel 20393CH
1.4MHz	QPSK	1	0	23.0	22.26	22.26	22.26
		1	3	23.0	22.30	22.34	22.32
		1	5	23.0	22.30	22.29	22.26
		3	0	23.0	22.32	22.21	22.22
		3	2	23.0	22.29	22.33	22.33
		3	3	23.0	22.28	22.30	22.29
		6	0	22.0	21.36	21.32	21.31
	16QAM	1	0	22.5	22.08	21.91	21.81
		1	3	22.5	22.06	22.08	21.87
		1	5	22.5	22.07	22.07	22.08
		3	0	22.5	21.68	21.54	21.54
		3	2	22.5	21.67	21.48	21.56
		3	3	22.5	21.67	21.13	21.41
		6	0	21.5	20.88	20.00	20.34
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 19965CH	Channel 20175CH	Channel 20385CH
3MHz	QPSK	1	0	23.0	22.46	22.44	22.52
		1	7	23.0	22.41	22.58	22.47
		1	14	23.0	22.47	22.38	22.47
		8	0	22.0	21.40	21.26	21.23
		8	4	22.0	21.37	21.23	21.24
		8	7	22.0	21.32	21.22	21.24
		15	0	22.0	21.29	21.26	21.30
	16QAM	1	0	22.5	21.59	21.26	21.55
		1	7	22.5	21.86	21.63	21.43
		1	14	22.5	21.62	21.65	21.46
		8	0	21.5	20.53	20.37	20.25
		8	4	21.5	20.36	20.35	20.19
		8	7	21.5	20.56	20.48	20.17
		15	0	21.5	20.44	20.35	20.30

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 19975CH	Channel 20175CH	Channel 20375CH
5MHz	QPSK	1	0	23.0	22.40	22.45	22.42
		1	13	23.0	22.31	22.34	22.23
		1	24	23.0	22.47	22.21	22.34
		12	0	22.0	21.36	21.25	21.26
		12	6	22.0	21.25	21.22	21.22
		12	13	22.0	21.27	21.27	21.24
		25	0	22.0	21.33	21.31	21.31
	16QAM	1	0	22.5	21.18	21.12	21.13
		1	13	22.5	21.19	20.81	20.90
		1	24	22.5	21.29	20.90	20.70
		12	0	21.5	20.31	20.37	20.15
		12	6	21.5	20.34	20.40	20.27
		12	13	21.5	20.33	20.33	20.28
		25	0	21.5	20.41	20.42	20.35
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20000CH	Channel 20175CH	Channel 20350CH
10MHz	QPSK	1	0	23.0	22.58	22.60	22.60
		1	25	23.0	22.51	22.52	22.51
		1	49	23.0	22.70	22.57	22.65
		25	0	22.0	21.37	21.36	21.45
		25	13	22.0	21.28	21.34	21.26
		25	25	22.0	21.33	21.37	21.25
		50	0	22.0	21.40	21.30	21.30
	16QAM	1	0	22.5	21.62	21.59	21.53
		1	25	22.5	21.34	22.04	21.92
		1	49	22.5	22.11	22.04	21.94
		25	0	21.5	20.37	20.25	20.45
		25	13	21.5	20.37	20.19	20.35
		25	25	21.5	20.42	20.35	20.15
		50	0	21.5	20.38	20.27	20.28

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20025CH	Channel 20175CH	Channel 20325CH
15MHz	QPSK	1	0	23.0	22.64	22.72	22.61
		1	38	23.0	22.57	22.47	22.38
		1	74	23.0	22.60	22.47	22.44
		36	0	22.0	21.38	21.32	21.51
		36	18	22.0	21.40	21.31	21.36
		36	39	22.0	21.40	21.35	21.34
		75	0	22.0	21.35	21.37	21.42
	16QAM	1	0	22.5	21.48	21.35	21.30
		1	38	22.5	21.26	21.13	21.11
		1	74	22.5	21.36	21.16	21.11
		36	0	21.5	20.40	20.24	20.32
		36	18	21.5	20.40	20.18	20.27
		36	39	21.5	20.41	20.12	20.14
		75	0	21.5	20.36	20.52	20.32
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20050CH	Channel 20175CH	Channel 20300CH
20MHz	QPSK	1	0	23.0	**22.59**	22.28	22.55
		1	50	23.0	22.51	**22.29**	**22.70**
		1	99	23.0	22.34	22.14	22.41
		50	0	22.0	21.44	21.42	21.47
		50	25	22.0	21.45	21.46	**21.48**
		50	50	22.0	21.38	21.27	21.32
		100	0	22.0	21.38	21.34	21.38
	16QAM	1	0	22.5	21.87	21.43	21.24
		1	50	22.5	21.94	21.33	21.28
		1	99	22.5	21.16	20.99	20.95
		50	0	21.5	20.35	20.32	20.45
		50	25	21.5	20.44	20.30	20.53
		50	50	21.5	20.18	20.22	20.41
		100	0	21.5	20.29	20.31	20.43

Table 23: Conducted power measurement results of LTE Band IV(Hotspot activated)

Copyright © Huawei Technologies Co., Ltd

7.1.7 Conducted power measurements of LTE Band V

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20407CH	Channel 20525CH	Channel 20643CH
1.4MHz	QPSK	1	0	24.0	22.96	22.96	22.68
		1	3	24.0	23.05	22.92	22.96
		1	5	24.0	22.95	22.85	22.83
		3	0	24.0	22.86	22.89	22.94
		3	2	24.0	22.85	22.85	22.93
		3	3	24.0	22.97	22.96	22.76
		6	0	23.0	21.84	21.89	21.91
	16QAM	1	0	23.0	22.59	22.79	21.94
		1	3	23.0	22.64	22.73	22.01
		1	5	23.0	22.67	22.67	21.95
		3	0	23.0	21.70	22.02	22.17
		3	2	23.0	21.79	21.52	22.11
		3	3	23.0	21.62	21.60	22.28
		6	0	22.0	20.68	20.67	21.01
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20415CH	Channel 20525CH	Channel 20635CH
3MHz	QPSK	1	0	24.0	22.88	23.17	23.03
		1	7	24.0	22.99	23.04	22.72
		1	14	24.0	22.98	22.99	22.76
		8	0	23.0	21.89	21.97	21.85
		8	4	23.0	21.76	21.94	21.89
		8	7	23.0	21.86	21.85	21.84
		15	0	23.0	21.96	21.98	21.92
	16QAM	1	0	23.0	22.09	22.11	21.75
		1	7	23.0	21.93	21.92	21.50
		1	14	23.0	21.96	21.82	21.43
		8	0	22.0	20.98	20.62	20.69
		8	4	22.0	20.95	20.83	20.63
		8	7	22.0	20.89	20.86	20.71
		15	0	22.0	20.65	20.96	20.90

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
					20425CH	20525CH	20625CH
5MHz	QPSK	1	0	24.0	22.97	23.11	22.85
		1	13	24.0	22.77	22.76	22.72
		1	24	24.0	22.68	22.76	22.67
		12	0	23.0	21.94	21.97	21.93
		12	6	23.0	21.90	21.91	21.85
		12	13	23.0	21.78	21.81	21.90
		25	0	23.0	21.85	21.98	21.87
	16QAM	1	0	23.0	21.97	22.09	22.31
		1	13	23.0	21.57	21.54	22.28
		1	24	23.0	21.61	21.58	22.31
		12	0	22.0	20.88	20.95	20.99
		12	6	22.0	20.83	20.94	20.94
		12	13	22.0	20.80	20.85	21.06
		25	0	22.0	21.16	21.18	21.05
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
					20450CH	20525CH	20600CH
10MHz	QPSK	1	0	24.0	23.07	23.13	**23.07**
		1	25	24.0	23.03	23.19	22.92
		1	49	24.0	**23.09**	**23.25**	22.80
		25	0	23.0	21.96	21.99	**22.01**
		25	13	23.0	22.00	21.87	21.85
		25	25	23.0	21.96	21.86	21.81
		50	0	23.0	22.05	22.03	21.98
	16QAM	1	0	23.0	22.07	22.24	22.15
		1	25	23.0	22.21	22.75	21.62
		1	49	23.0	22.62	22.68	21.50
		25	0	22.0	21.01	21.02	20.98
		25	13	22.0	20.95	20.81	20.98
		25	25	22.0	20.99	20.91	20.92
		50	0	22.0	20.98	20.97	20.95

Table 24: Conducted power measurement results of LTE Band V(Hotspot disable)

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20407CH	Channel 20525CH	Channel 20643CH
1.4MHz	QPSK	1	0	23.0	22.28	22.33	22.33
		1	3	23.0	22.26	22.22	22.34
		1	5	23.0	22.29	22.34	22.37
		3	0	23.0	22.25	22.36	22.25
		3	2	23.0	22.29	22.35	22.25
		3	3	23.0	22.31	22.4	22.23
		6	0	22.0	21.29	21.4	21.24
	16QAM	1	0	22.0	21.85	21.87	21.78
		1	3	22.0	21.99	21.54	21.94
		1	5	22.0	21.68	21.84	21.45
		3	0	22.0	21.59	21.62	21.63
		3	2	22.0	21.21	21.59	21.28
		3	3	22.0	21.14	21.65	20.97
		6	0	21.0	20.21	20.55	19.99
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 20415CH	Channel 20525CH	Channel 20635CH
3MHz	QPSK	1	0	23.0	22.57	22.47	22.46
		1	7	23.0	22.63	22.43	22.45
		1	14	23.0	22.6	22.47	22.4
		8	0	22.0	21.29	21.37	21.38
		8	4	22.0	21.28	21.34	21.22
		8	7	22.0	21.3	21.26	21.29
		15	0	22.0	21.28	21.39	21.35
	16QAM	1	0	22.0	21.6	21.54	21.31
		1	7	22.0	21.54	21.47	21.44
		1	14	22.0	21.57	21.28	21.21
		8	0	21.0	20.52	20.07	20.18
		8	4	21.0	20.45	20.03	20.11
		8	7	21.0	20.21	19.96	20.2
		15	0	21.0	20.36	20.18	20.43

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
					20425CH	20525CH	20625CH
5MHz	QPSK	1	0	23.0	22.43	22.5	22.49
		1	13	23.0	22.32	22.26	22.36
		1	24	23.0	22.47	22.33	22.26
		12	0	22.0	21.35	21.35	21.28
		12	6	22.0	21.22	21.35	21.29
		12	13	22.0	21.19	21.29	21.31
		25	0	22.0	21.39	21.37	21.32
	16QAM	1	0	22.0	21.21	21.34	21.22
		1	13	22.0	21.07	21.29	20.77
		1	24	22.0	21.08	21.3	20.87
		12	0	21.0	20.26	20.24	20.31
		12	6	21.0	20.14	20.22	20.21
		12	13	21.0	20.13	20.12	20.16
		25	0	21.0	20.44	20.41	20.48
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
					20450CH	20525CH	20600CH
10MHz	QPSK	1	0	23.0	22.48	22.57	**22.48**
		1	25	23.0	22.47	**22.69**	22.47
		1	49	23.0	**22.61**	22.6	22.46
		25	0	22.0	21.37	**21.41**	21.34
		25	13	22.0	21.4	21.26	21.3
		25	25	22.0	21.38	21.35	21.26
		50	0	22.0	21.49	21.44	21.41
	16QAM	1	0	22.0	21.29	21.98	21.47
		1	25	22.0	21.95	21.69	21.45
		1	49	22.0	21.15	21.63	21.96
		25	0	21.0	20.42	20.23	20.28
		25	13	21.0	20.3	20.35	20.34
		25	25	21.0	20.43	20.4	20.3
		50	0	21.0	20.44	20.36	20.35

Table 25: Conducted power measurement results of LTE Band V(Hotspot activated)

Copyright © Huawei Technologies Co., Ltd

7.1.8 Conducted power measurements of LTE Band XII

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 23107CH	Channel 23095CH	Channel 23173CH
1.4MHz	QPSK	1	0	24.0	23.43	23.68	23.44
		1	3	24.0	23.48	23.69	23.56
		1	5	24.0	23.38	23.61	23.50
		3	0	24.0	23.29	23.47	23.38
		3	2	24.0	23.38	23.51	23.48
		3	3	24.0	23.38	23.58	23.48
		6	0	23.0	22.45	22.58	22.55
	16QAM	1	0	23.0	22.64	22.88	22.54
		1	3	23.0	22.88	22.96	22.61
		1	5	23.0	22.81	22.93	22.59
		3	0	23.0	22.69	22.82	22.45
		3	2	23.0	22.78	22.54	22.40
		3	3	23.0	22.70	22.33	22.19
		6	0	22.0	21.37	21.29	21.57
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 23025CH	Channel 23095CH	Channel 23165CH
3MHz	QPSK	1	0	24.0	23.58	23.87	23.34
		1	7	24.0	23.65	23.59	23.57
		1	14	24.0	23.67	23.66	23.53
		8	0	23.0	22.47	22.52	22.34
		8	4	23.0	22.35	22.51	22.50
		8	7	23.0	22.63	22.52	22.50
		15	0	23.0	22.58	22.54	22.49
	16QAM	1	0	23.0	22.83	22.73	22.36
		1	7	23.0	22.90	22.61	22.13
		1	14	23.0	22.81	22.77	22.58
		8	0	22.0	21.42	21.49	21.15
		8	4	22.0	21.41	21.08	21.24
		8	7	22.0	21.49	21.11	21.43
		15	0	22.0	21.58	21.50	21.34

Copyright © Huawei Technologies Co., Ltd

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 23035CH	Channel 23095CH	Channel 23155CH
5MHz	QPSK	1	0	24.0	23.56	23.45	23.50
		1	13	24.0	23.33	23.38	23.31
		1	24	24.0	23.41	23.28	23.52
		12	0	23.0	22.31	22.50	22.45
		12	6	23.0	22.44	22.49	22.50
		12	13	23.0	22.49	22.40	22.59
		25	0	23.0	22.39	22.50	22.58
	16QAM	1	0	23.0	22.50	22.64	22.67
		1	13	23.0	22.11	22.18	22.82
		1	24	23.0	22.24	22.50	22.95
		12	0	22.0	21.24	21.35	21.39
		12	6	22.0	21.69	21.25	21.49
		12	13	22.0	21.52	21.55	21.59
		25	0	22.0	21.50	21.52	21.64
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel 23060CH	Channel 23095CH	Channel 23130CH
10MHz	QPSK	1	0	24.0	23.60	23.66	23.74
		1	25	24.0	**23.77**	**23.76**	23.35
		1	49	24.0	23.66	23.70	**23.76**
		25	0	23.0	22.33	22.55	22.51
		25	13	23.0	22.45	22.48	22.42
		25	25	23.0	22.60	22.50	**22.62**
		50	0	23.0	22.51	22.45	22.53
	16QAM	1	0	23.0	22.56	22.63	22.48
		1	25	23.0	22.25	22.13	22.13
		1	49	23.0	22.48	22.63	22.44
		25	0	22.0	21.12	21.28	21.45
		25	13	22.0	21.39	21.34	21.56
		25	25	22.0	21.57	21.37	21.73
		50	0	22.0	21.40	21.37	21.43

Table 26: Conducted power measurement results of LTE Band XII

Copyright © Huawei Technologies Co., Ltd

7.1.9 Conducted power measurements of LTE Band XXX

Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
					27685CH	27710CH	27735CH
5MHz	QPSK	1	0	24.0	23.46	23.59	23.69
		1	13	24.0	23.38	23.81	23.50
		1	24	24.0	23.51	23.87	23.76
		12	0	23.0	22.69	22.88	22.74
		12	6	23.0	22.70	22.94	22.74
		12	13	23.0	22.69	22.96	22.75
		25	0	23.0	22.70	22.96	22.72
	16QAM	1	0	23.0	22.50	22.69	22.67
		1	13	23.0	22.42	22.53	22.58
		1	24	23.0	22.36	22.46	22.73
		12	0	22.0	21.45	21.81	21.69
		12	6	22.0	21.85	21.96	21.85
		12	13	22.0	21.34	21.92	21.65
		25	0	22.0	21.77	21.83	21.66
Bandwidth	Modulation	RB size	RB offset	Tune-up	Channel	Channel	Channel
						27710CH	
10MHz	QPSK	1	0	24.0	/	23.85	/
		1	25	24.0	/	23.76	/
		1	49	24.0	/	**23.87**	/
		25	0	23.0	/	**22.97**	/
		25	13	23.0	/	22.91	/
		25	25	23.0	/	22.96	/
		50	0	23.0	/	22.94	/
	16QAM	1	0	23.0	/	21.92	/
		1	25	23.0	/	21.94	/
		1	49	23.0	/	21.87	/
		25	0	22.0	/	21.77	/
		25	13	22.0	/	21.94	/
		25	25	22.0	/	21.75	/
		50	0	22.0	/	21.73	/

Table 27: Conducted power measurement results of LTE Band XXX

Copyright © Huawei Technologies Co., Ltd

7.1.10 Conducted power measurements of WiFi 2.4G

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune-up	Average Power (dBm)	SAR Test (Yes/No)
802.11b	1	2412	1	17.5	16.23	Yes
	6	2437		17.5	**16.71**	Yes
	11	2462		17.5	16.63	Yes
802.11g	1	2412	6	16.0	Not Required	No
	6	2437		16.0	Not Required	No
	11	2462		16.0	Not Required	No
802.11n-20M	1	2412	6.5	14.5	Not Required	No
	6	2437		14.5	Not Required	No
	11	2462		14.5	Not Required	No
802.11n-40M	3	2422	13.5	13.5	Not Required	No
	6	2437		13.5	Not Required	No
	9	2452		13.5	Not Required	No

Table 28: Conducted power measurement results of WiFi 2.4G

Note: 1) The Average conducted power of WiFi is measured with RMS detector.

Copyright © Huawei Technologies Co., Ltd

7.1.11 Conducted power measurements of WiFi 5G

Band (GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune-up	Average Power (dBm)	SAR Test (Yes/No)
5.2	802.11a	CH 36	5180	6M	14.5	13.89	Yes
		CH 40	5200		14.5	13.97	Yes
		CH 44	5220		14.5	13.48	Yes
		CH 48	5240		14.5	13.64	Yes
	802.11n 20M	CH 36	5180	6.5M	12.5	Not Required	No
		CH 40	5200		12.5	Not Required	No
		CH 44	5220		12.5	Not Required	No
		CH 48	5240		12.5	Not Required	No
	802.11n 40M	CH 38	5190	13.5M	12.5	Not Required	No
		CH 46	5230		12.5	Not Required	No
		CH 38	5190		12.5	Not Required	No
		CH 46	5230		12.5	Not Required	No
Band (GHz)	**Mode**	**Channel**	**Frequency (MHz)**	**Data Rate (Mbps)**	**Tune-up**	**Average Power (dBm)**	**SAR Test (Yes/No)**
5.3	802.11a	CH 52	5260	6M	14.5	13.74	Yes
		CH 56	5280		14.5	13.47	Yes
		CH 60	5300		14.5	13.32	Yes
		CH 64	5320		14.5	13.37	Yes
	802.11n 20M	CH 52	5260	6.5M	12.5	Not Required	No
		CH 56	5280		12.5	Not Required	No
		CH 60	5300		12.5	Not Required	No
		CH 64	5320		12.5	Not Required	No
	802.11n 40M	CH 54	5270	13.5M	12.5	Not Required	No
		CH 62	5310		12.5	Not Required	No
		CH 54	5270		12.5	Not Required	No
		CH 62	5310		12.5	Not Required	No

Copyright © Huawei Technologies Co., Ltd

Band (GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune-up	Average Power (dBm)	SAR Test (Yes/No)
5.5	802.11a	CH 100	5500	6M	14.5	14.27	Yes
		CH 104	5520		14.5	14.12	Yes
		CH 108	5540		14.5	14.09	Yes
		CH 112	5560		14.5	14.01	Yes
		CH 116	5580		14.5	14.04	Yes
		CH 120	5600		14.5	14.27	Yes
		CH 124	5620		14.5	14.34	Yes
		CH 128	5640		14.5	14.40	Yes
		CH 132	5660		14.5	14.31	Yes
		CH 136	5680		14.5	14.02	Yes
		CH 140	5700		14.5	14.17	Yes
		CH 144	5720		14.5	14.12	Yes
	802.11n 20M	CH 100	5500	6.5M	12.5	Not Required	No
		CH 104	5520		12.5	Not Required	No
		CH 108	5540		12.5	Not Required	No
		CH 112	5560		12.5	Not Required	No
		CH 116	5580		12.5	Not Required	No
		CH 120	5600		12.5	Not Required	No
		CH 124	5620		12.5	Not Required	No
		CH 128	5640		12.5	Not Required	No
		CH 132	5660		12.5	Not Required	No
		CH 136	5680		12.5	Not Required	No
		CH 140	5700		12.5	Not Required	No
		CH 144	5720		12.5	Not Required	No
	802.11n 40M	CH 102	5510	13.5M	12.5	Not Required	No
		CH 110	5550		12.5	Not Required	No
		CH 118	5590		12.5	Not Required	No
		CH 126	5630		12.5	Not Required	No
		CH 134	5670		12.5	Not Required	No
		CH 142	5710		12.5	Not Required	No

Copyright © Huawei Technologies Co., Ltd

Band (GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune-up	Average Power (dBm)	SAR Test (Yes/No)
5.8	802.11a	CH 149	5745	6M	14.5	14.33	Yes
		CH 153	5765		14.5	14.21	Yes
		CH 157	5785		14.5	14.34	Yes
		CH 161	5805		14.5	14.18	Yes
		CH 165	5825		14.5	14.12	Yes
	802.11n 20M	CH 149	5745	6.5M	12.5	Not Required	No
		CH 153	5765		12.5	Not Required	No
		CH 157	5785		12.5	Not Required	No
		CH 161	5805		12.5	Not Required	No
		CH 165	5825		12.5	Not Required	No
	802.11n 40M	CH 151	5755	13.5M	12.5	Not Required	No
		CH 159	5795		12.5	Not Required	No

Table 29: Conducted power measurement results of WiFi 5G.

Note: 1) The Average conducted power of WiFi is measured with RMS detector.

Copyright © Huawei Technologies Co., Ltd

7.1.12 Conducted power measurements of BT

The output power of BT antenna is as following:

BT 2450	Tune-up	Average Conducted Power (dBm)		
		0CH	39CH	78CH
DH5	11.0	9.69	10.17	9.93
2DH5	11.0	7.57	8.35	8.11
3DH5	11.0	7.58	7.81	7.88

BT 2450	Tune-up	Average Conducted Power (dBm)		
		0CH	19CH	39CH
BT 4.1	2.5	0.61	2.08	0.54

Table 30: Conducted power measurement results of BT.

Note: The conducted power of BT is measured with RMS detector.

Copyright © Huawei Technologies Co., Ltd

7.2 SAR measurement Results

General Notes:

1) Per KDB447498 D01v06, all SAR measurement results are scaled to the maximum tune-up tolerance limit to demonstrate SAR compliance.

2) Per KDB447498 D01v06, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

● ≤ 0.8W/kg for 1-g or 2.0W/kg for 10-g respectively, when the transmission band is ≤ 100MHz.

● ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz.

● ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz.

When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel must be used.

3) Per KDB865664 D01v01r04,for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/Kg; if the deviation among the repeated measurement is ≤20%, and the measured SAR <1.45W/Kg, only one repeated measurement is required.

4) Per KDB941225 D06v02, the DUT Dimension is bigger than 9 cm x 5 cm, so 10mm is chosen as the test separation distance for Hotspot mode. When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.

5) Per KDB648474 D04v01r03, SAR is evaluated without a headset connected to the device. When the standalone reported body-worn SAR is ≤1.2 W/kg, no additional SAR evaluations using a headset are required.

6) Per KDB865664 D02v01r02, SAR plot is only required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination; Plots are also required when the measured SAR is > 1.5 W/kg, or > 7.0 W/kg for occupational exposure. The published RF exposure KDB procedures may require additional plots; for example, to support SAR to peak location separation ratio test exclusion and/or volume scan post-processing(Refer to appendix B for detailed SAR plots).

GSM Notes:

1) Per KDB941225 D01v03r01, SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

2) Per KDB648474 D04v01r03, the device does not support DTM function. Body-worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.

Copyright © Huawei Technologies Co., Ltd

UMTS Notes:

1) Per KDB941225 D01v03r01, When the maximum output power and tune-up tolerance specified for production units in a Second mode is ≤ ¼ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of Second to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the Second mode.

LTE Notes:

1) The LTE test configurations are determined according to KDB941225 D05 SAR for LTE Devices v02r03.The general test procedures used for SAR testing can be found in Section 6.5.

2) A-MPR was disabled for all SAR test by setting NS_01 on the base station simulator.SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames(maximum TTI)

WiFi Notes:

Per KDB248227D01v02r02:

1) When reported SAR for the initial test position is ≤ 0.4W/kg, no additional testing for the remaining test position is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is ≤ 0.8W/kg or all test position are measured. For all positions/configurations tested using the initial test position and subsequent test positions, when the *reported* SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the *reported* SAR is ≤ 1.2 W/kg or all required channels are tested.

2) The highest SAR measured for the initial test position or initial test configuration should be used to determine SAR test exclusion according to the sum of 1-g SAR and SAR peak to location ratio provisions in KDB 447498. In addition, a test lab may also choose to perform standalone SAR measurements for test positions and 802.11 configurations that are not required by the initial test position or initial test configuration procedures and apply the results to determine simultaneous transmission SAR test exclusion, according to sum of 1-g and SAR peak to location ratio requirements to reduce the number of simultaneous transmission SAR measurements.

Copyright © Huawei Technologies Co., Ltd

7.2.1 SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Left touch	190/836.6	GSM	0.426	0.328	-0.10	33.25	33.50	0.451	/
Left tilt	190/836.6	GSM	0.287	0.200	0.06	33.25	33.50	0.304	/
Right touch	190/836.6	GSM	0.433	0.333	0.10	33.25	33.50	**0.459**	Yes
Right tilt	190/836.6	GSM	0.272	0.190	0.02	33.25	33.50	0.288	/
Right touch	128/824.2	GSM	0.356	0.275	-0.17	33.08	33.50	0.392	/
Right touch	251/848.8	GSM	0.367	0.254	0.12	33.32	33.50	0.383	/

Table 31: Head SAR test results of GSM850

Test Position of Body-Worn with 15mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	190/836.6	GSM	0.399	0.306	0.00	33.25	33.50	0.423	/
Back Side	190/836.6	GSM	0.484	0.369	0.00	33.25	33.50	**0.513**	Yes

Table 32: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	190/836.6	GPRS 2TS	0.421	0.322	-0.02	30.72	31.50	0.504	/
Back Side	190/836.6	GPRS 2TS	0.577	0.462	0.06	30.72	31.50	**0.691**	Yes
Left Side	190/836.6	GPRS 2TS	0.509	0.345	0.07	30.72	31.50	0.609	/
Right Side	190/836.6	GPRS 2TS	0.401	0.268	-0.01	30.72	31.50	0.480	/
Bottom Side	190/836.6	GPRS 2TS	0.448	0.287	-0.15	30.72	31.50	0.536	/

Table 33: Hotspot SAR test results of GSM850

Note: Per KDB 648474 D04, Product Specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

Copyright © Huawei Technologies Co., Ltd

7.2.2 SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Left touch	661/1880	GSM	0.034	0.020	0.17	30.06	30.50	0.038	/
Left tilt	661/1880	GSM	0.023	0.014	0.19	30.06	30.50	0.026	/
Right touch	661/1880	GSM	0.074	0.045	0.04	30.06	30.50	0.081	/
Right tilt	661/1880	GSM	0.013	0.007	-0.15	30.06	30.50	0.014	/
Right touch	512/1850.2	GSM	0.076	0.047	0.11	29.68	30.50	**0.092**	Yes
Right touch	810/1909.8	GSM	0.060	0.037	0.03	29.70	30.50	0.072	/

Table 34: Head SAR test results of GSM1900

Test Position of Body-Worn with 15mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	661/1880	GSM	0.242	0.144	0.15	30.06	30.50	0.268	/
Back Side	661/1880	GSM	0.383	0.219	0.13	30.06	30.50	**0.424**	Yes

Table 35: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	661/1880	GPRS 2TS	0.291	0.162	0.12	24.64	26.20	0.417	/
Back Side	661/1880	GPRS 2TS	0.477	0.249	0.16	24.64	26.20	0.683	/
Left Side	661/1880	GPRS 2TS	0.020	0.012	0.18	24.64	26.20	0.028	/
Right Side	661/1880	GPRS 2TS	0.063	0.035	-0.02	24.64	26.20	0.090	/
Bottom Side	661/1880	GPRS 2TS	0.544	0.291	-0.18	24.64	26.20	**0.779**	Yes

Table 36: Hotspot SAR test results of GSM1900

Copyright © Huawei Technologies Co., Ltd

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	Product Specific 10-g SAR Exclusion
			1-g	10-g					
Front Side	661/1880	GPRS 2TS	0.291	0.162	0.12	24.64	29.20	0.832	Yes
Back Side	661/1880	GPRS 2TS	0.477	0.249	0.16	24.64	29.20	1.363	No
Left Side	661/1880	GPRS 2TS	0.020	0.012	0.18	24.64	29.20	0.056	Yes
Right Side	661/1880	GPRS 2TS	0.063	0.035	-0.02	24.64	29.20	0.180	Yes
Bottom Side	661/1880	GPRS 2TS	0.544	0.291	-0.18	24.64	29.20	1.555	No

Table 37: Product Specific 10-g SAR test reduction evaluation of GSM1900

Note : According to the table above , Product Specific 10-g SAR test is required for this frequency band.

According to the table above , only **Back Side** and **Bottom Side** Product Specific 10-g SAR test are required for this frequency band:

Product Specific 10-g SAR 0mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR10-g (W/kg)	SAR Plot
			1-g	10-g					
Back Side	661/1880	GPRS 2TS	5.310	2.220	0.14	28.95	29.20	2.352	/
Back Side	512/1850.2	GPRS 2TS	4.660	1.960	0.15	29.05	29.20	2.029	/
Back Side	810/1909.8	GPRS 2TS	5.600	2.320	0.02	29.06	29.20	**2.396**	Yes
Back Side-Repeated	810/1909.8	GPRS 2TS	5.530	2.300	0.17	29.06	29.20	2.375	/
Bottom Side	661/1880	GPRS 2TS	4.330	1.850	0.13	28.95	29.20	1.960	/

Table 38: Product Specific 10-g SAR results of GSM1900

Copyright © Huawei Technologies Co., Ltd

7.2.3 SAR measurement Result of UMTS Band II

Test Position of Head	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Left touch	9400/1880	RMC	0.058	0.036	0.14	22.01	22.60	0.066	/
Left tilt	9400/1880	RMC	0.041	0.023	0.11	22.01	22.60	0.047	/
Right touch	9400/1880	RMC	0.149	0.092	0.18	22.01	22.60	0.171	/
Right tilt	9400/1880	RMC	0.031	0.017	0.10	22.01	22.60	0.035	/
Right touch	9262/1852.4	RMC	0.156	0.097	0.16	21.98	22.60	**0.180**	Yes
Right touch	9538/1907.6	RMC	0.126	0.077	0.10	21.93	22.60	0.147	/

Table 39: Head SAR test results of UMTS Band II

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	9400/1880	RMC	0.486	0.284	0.15	22.01	22.60	0.557	/
Back Side	9400/1880	RMC	0.706	0.399	0.19	22.01	22.60	**0.809**	Yes
Back Side	9262/1852.4	RMC	0.664	0.377	0.14	22.01	22.60	0.761	/
Back Side	9538/1907.6	RMC	0.672	0.377	0.18	22.01	22.60	0.770	/

Table 40: Body-Worn SAR test results of UMTS Band II

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	9400/1880	RMC	0.316	0.174	0.16	16.81	17.60	0.379	/
Back Side	9400/1880	RMC	0.467	0.240	0.14	16.81	17.60	0.560	/
Left Side	9400/1880	RMC	0.020	0.012	0.01	16.81	17.60	0.023	/
Right Side	9400/1880	RMC	0.055	0.030	0.14	16.81	17.60	0.066	/
Bottom Side	9400/1880	RMC	0.508	0.273	-0.19	16.81	17.60	**0.609**	Yes

Table 41: Hotspot SAR test results of UMTS Band II

Copyright © Huawei Technologies Co., Ltd

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	Product Specific 10-g SAR Exclusion
			1-g	10-g					
Front Side	9400/1880	RMC	0.316	0.174	0.16	16.81	22.60	1.199	Yes
Back Side	9400/1880	RMC	0.467	0.240	0.14	16.81	22.60	1.771	No
Left Side	9400/1880	RMC	0.020	0.012	0.01	16.81	22.60	0.074	Yes
Right Side	9400/1880	RMC	0.055	0.030	0.14	16.81	22.60	0.208	Yes
Bottom Side	9400/1880	RMC	0.508	0.273	-0.19	16.81	22.60	1.927	No

Table 42: Product Specific 10-g SAR test reduction evaluation of UMTS Band II

Note : According to the table above , Product Specific 10-g SAR test is required for this frequency band.

According to the table above , only **Back Side** and **Bottom Side** Product Specific 10-g SAR test are required for this frequency band:

Product Specific 10-g SAR 0mm	Test channel /Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR10-g (W/kg)	SAR Plot
			1-g	10-g					
Back Side	9400/1880	RMC	5.950	2.480	0.16	22.01	22.60	2.841	/
Back Side	9262/1852.4	RMC	5.550	2.310	0.13	21.98	22.60	2.664	/
Back Side	9538/1907.6	RMC	6.210	2.580	0.16	21.93	22.60	3.010	/
Bottom Side	9400/1880	RMC	5.660	2.370	-0.12	22.01	22.60	2.715	/
Bottom Side	9262/1852.4	RMC	4.960	2.110	-0.12	21.98	22.60	2.434	/
Bottom Side	9538/1907.6	RMC	6.740	2.800	-0.13	21.93	22.60	**3.267**	Yes
Bottom Side-Repeated	9538/1907.6	RMC	6.400	2.690	0.13	21.93	22.60	3.139	/

Table 43: Product Specific 10-g SAR results of UMTS Band II

Copyright © Huawei Technologies Co., Ltd

7.2.4 SAR measurement Result of UMTS Band V

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Left touch	4182/836.4	RMC	0.300	0.229	0.15	23.41	24.00	0.344	/
Left tilt	4182/836.4	RMC	0.167	0.117	0.14	23.41	24.00	0.191	/
Right touch	4182/836.4	RMC	0.312	0.238	0.07	23.41	24.00	**0.357**	Yes
Right tilt	4182/836.4	RMC	0.149	0.106	0.02	23.41	24.00	0.171	/
Right touch	4132/826.4	RMC	0.252	0.175	0.13	23.35	24.00	0.293	/
Right touch	4233/846.6	RMC	0.310	0.238	0.10	23.32	24.00	0.363	/

Table 44: Head SAR test results of UMTS Band V

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	4182/836.4	RMC	0.256	0.196	0.00	23.41	24.00	0.293	/
Back Side	4182/836.4	RMC	0.258	0.158	0.00	23.41	24.00	**0.296**	Yes

Table 45: Body-Worn SAR test results of UMTS Band V

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	SAR Plot
			1-g	10-g					
Front Side	4182/836.4	RMC	0.241	0.156	-0.02	22.58	23.00	0.265	/
Back Side	4182/836.4	RMC	0.444	0.254	0.07	22.58	23.00	**0.489**	Yes
Left Side	4182/836.4	RMC	0.233	0.158	0.04	22.58	23.00	0.257	/
Right Side	4182/836.4	RMC	0.217	0.148	0.09	22.58	23.00	0.239	/
Bottom Side	4182/836.4	RMC	0.240	0.150	-0.09	22.58	23.00	0.264	/

Table 46: Hotspot SAR test results of UMTS Band V

Copyright © Huawei Technologies Co., Ltd

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR1-g (W/kg)	Product Specific 10-g SAR Exclusion
			1-g	10-g					
Front Side	4182/836.4	RMC	0.241	0.156	-0.02	22.58	24.00	0.334	Yes
Back Side	4182/836.4	RMC	0.444	0.254	0.07	22.58	24.00	0.616	Yes
Left Side	4182/836.4	RMC	0.233	0.158	0.04	22.58	24.00	0.323	Yes
Right Side	4182/836.4	RMC	0.217	0.148	0.09	22.58	24.00	0.301	Yes
Bottom Side	4182/836.4	RMC	0.240	0.150	-0.09	22.58	24.00	0.333	Yes

Table 47: Product Specific 10-g SAR test reduction evaluation of UMTS Band II

Note : According to the table above , Product Specific 10-g SAR test is not required for this frequency band.

Copyright © Huawei Technologies Co., Ltd

7.2.5 SAR measurement Result of LTE Band II

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Left touch	19100/1900	20M QPSK 1RB#99	0.054	0.034	0.17	21.64	22.30	0.063	/
Left tilt	19100/1900	20M QPSK 1RB#99	0.029	0.017	0.13	21.64	22.30	0.034	/
Right touch	19100/1900	20M QPSK 1RB#99	0.113	0.068	0.16	21.64	22.30	0.132	/
Right tilt	19100/1900	20M QPSK 1RB#99	0.034	0.018	0.13	21.64	22.30	0.040	/
Right touch	18700/1860	20M QPSK 1RB#0	0.148	0.092	0.13	21.58	22.30	**0.175**	Yes
Right touch	18900/1880	20M QPSK 1RB#99	0.123	0.075	0.12	21.51	22.30	0.148	/
50%RB									
Left touch	18700/1860	20M QPSK 50%RB#0	0.044	0.026	0.13	20.57	21.30	0.052	/
Left tilt	18700/1860	20M QPSK 50%RB#0	0.029	0.017	0.04	20.57	21.30	0.035	/
Right touch	18700/1860	20M QPSK 50%RB#0	0.104	0.061	0.18	20.57	21.30	0.123	/
Right tilt	18700/1860	20M QPSK 50%RB#0	0.039	0.022	0.04	20.57	21.30	0.046	/

Table 48: Head SAR test results of LTE Band II

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	19100/1900	20M QPSK 1RB#99	0.396	0.227	0.03	21.64	22.30	0.461	/
Back Side	19100/1900	20M QPSK 1RB#99	0.611	0.338	-0.01	21.64	22.30	0.711	Yes
50%RB									
Front Side	18700/1860	20M QPSK 50%RB#0	0.344	0.199	0.16	20.57	21.30	0.407	/
Back Side	18700/1860	20M QPSK 50%RB#0	0.571	0.319	0.19	20.57	21.30	0.676	/

Table 49: Body-Worn SAR test results of LTE Band II

Copyright © Huawei Technologies Co., Ltd

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	18700/1860	20M QPSK 1RB#50	0.270	0.147	0.17	16.31	17.80	0.381	/
Back Side	18700/1860	20M QPSK 1RB#50	0.421	0.216	0.14	16.31	17.80	0.593	Yes
Left Side	18700/1860	20M QPSK 1RB#50	0.061	0.038	0.09	16.31	17.80	0.085	/
Right Side	18700/1860	20M QPSK 1RB#50	0.202	0.113	0.11	16.31	17.80	0.285	/
Bottom Side	18700/1860	20M QPSK 1RB#50	0.398	0.215	0.10	16.31	17.80	0.561	/
50%RB									
Front Side	18700/1860	20M QPSK 50%RB#0	0.230	0.124	0.17	16.30	16.80	0.258	/
Back Side	18700/1860	20M QPSK 50%RB#0	0.339	0.173	0.16	16.30	16.80	0.380	/
Left Side	18700/1860	20M QPSK 50%RB#0	0.047	0.027	0.16	16.30	16.80	0.053	/
Right Side	18700/1860	20M QPSK 50%RB#0	0.167	0.093	0.00	16.30	16.80	0.187	/
Bottom Side	18700/1860	20M QPSK 50%RB#0	0.371	0.199	0.11	16.30	16.80	0.416	/

Table 50: Hotspot SAR test results of LTE Band II

Copyright © Huawei Technologies Co., Ltd

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	Product Specific 10-g SAR Exclusion
			1-g	10-g					
1RB									
Front Side	18700/1860	20M QPSK 1RB#50	0.270	0.147	0.17	16.31	22.30	1.072	Yes
Back Side	18700/1860	20M QPSK 1RB#50	0.421	0.216	0.14	16.31	22.30	1.672	No
Left Side	18700/1860	20M QPSK 1RB#50	0.061	0.038	0.09	16.31	22.30	0.240	Yes
Right Side	18700/1860	20M QPSK 1RB#50	0.202	0.113	0.11	16.31	22.30	0.802	Yes
Bottom Side	18700/1860	20M QPSK 1RB#50	0.398	0.215	0.10	16.31	22.30	1.581	No
50%RB									
Front Side	18700/1860	20M QPSK 50%RB#0	0.230	0.124	0.17	16.30	16.80	0.258	No
Back Side	18700/1860	20M QPSK 50%RB#0	0.339	0.173	0.16	16.30	16.80	0.380	No
Left Side	18700/1860	20M QPSK 50%RB#0	0.047	0.027	0.16	16.30	16.80	0.053	No
Right Side	18700/1860	20M QPSK 50%RB#0	0.167	0.093	0.00	16.30	16.80	0.187	No
Bottom Side	18700/1860	20M QPSK 50%RB#0	0.371	0.199	0.11	16.30	16.80	0.416	No

Table 51: Product Specific 10-g SAR test reduction evaluation of LTE Band II

Note : According to the table above , Product Specific 10-g SAR test is required for this frequency band.

Copyright © Huawei Technologies Co., Ltd

According to the table above , only **Back Side** and **Bottom Side** Product Specific 10-g SAR test are required for this frequency band:

Product Specific 10-g SAR 0mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{10-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Back Side	19100/1900	20M QPSK 1RB#99	6.460	2.650	0.11	21.64	22.30	3.085	/
Back Side	18700/1860	20M QPSK 1RB#0	5.850	2.420	0.17	21.58	22.30	2.856	/
Back Side	18900/1880	20M QPSK 1RB#99	6.520	2.660	0.18	21.51	22.30	**3.191**	Yes
Back Side-Repeated	18900/1880	20M QPSK 1RB#99	6.350	2.610	0.11	21.51	22.30	3.131	/
Bottom Side	19100/1900	20M QPSK 1RB#99	5.750	2.420	-0.11	21.64	22.30	2.817	/
Bottom Side	18700/1860	20M QPSK 1RB#0	5.490	2.310	0.11	21.58	22.30	2.727	
Bottom Side	18900/1880	20M QPSK 1RB#99	4.790	2.030	0.10	21.51	22.30	2.435	
50%RB									
Bottom Side	18700/1860	20M QPSK 50%RB#0	3.700	1.560	0.16	20.57	21.30	1.846	/
Back Side	18700/1860	20M QPSK 50%RB#0	4.410	2.020	0.09	20.57	21.30	2.390	/
Back Side	18900/1880	20M QPSK 50%RB#0	4.470	2.050	0.19	20.47	21.30	2.482	/
Back Side	19100/1900	20M QPSK 50%RB#0	4.540	2.080	0.13	20.54	21.30	2.478	/
100%RB									
Bottom Side	18700/1860	20M QPSK 100%RB#0	3.890	1.640	-0.19	20.54	21.30	1.954	
Back Side	18700/1860	20M QPSK 100%RB#0	4.230	1.940	0.15	20.54	21.30	2.311	

Table 52: Product Specific 10-g SAR results of LTE Band II

Copyright © Huawei Technologies Co., Ltd

7.2.6 SAR measurement Result of LTE Band IV

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Left touch	20050/1720	20M QPSK 1RB#0	0.067	0.045	0.11	23.16	24.00	0.081	/
Left tilt	20050/1720	20M QPSK 1RB#0	0.048	0.031	-0.06	23.16	24.00	0.059	/
Right touch	20050/1720	20M QPSK 1RB#0	0.134	0.090	0.14	23.16	24.00	0.163	/
Right tilt	20050/1720	20M QPSK 1RB#0	0.058	0.038	0.16	23.16	24.00	0.070	/
Right touch	20175/1732.5	20M QPSK 1RB#0	0.133	0.081	0.04	23.14	24.00	0.162	/
Right touch	20300/1745	20M QPSK 1RB#0	0.156	0.103	0.11	22.84	24.00	0.204	Yes
50%RB									
Left touch	20050/1720	20M QPSK 50%RB#0	0.050	0.030	0.12	22.06	23.00	0.062	/
Left tilt	20050/1720	20M QPSK 50%RB#0	0.038	0.025	0.15	22.06	23.00	0.048	/
Right touch	20050/1720	20M QPSK 50%RB#0	0.092	0.056	0.14	22.06	23.00	0.114	/
Right tilt	20050/1720	20M QPSK 50%RB#0	0.048	0.029	0.11	22.06	23.00	0.060	/

Table 53: Head SAR test results of LTE Band IV

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	20050/1720	20M QPSK 1RB#0	0.325	0.193	-0.02	23.16	24.00	0.394	/
Back Side	20050/1720	20M QPSK 1RB#0	0.408	0.235	0.12	23.16	24.00	0.495	Yes
50%RB									
Front Side	20050/1720	20M QPSK 50%RB#0	0.243	0.140	0.06	22.06	23.00	0.302	/
Back Side	20050/1720	20M QPSK 50%RB#0	0.296	0.165	0.14	22.06	23.00	0.368	/

Table 54: Body-Worn SAR test results of LTE Band IV

Copyright © Huawei Technologies Co., Ltd

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	20300/1745	20M QPSK 1RB#50	0.414	0.232	0.13	22.70	23.00	0.444	/
Back Side	20300/1745	20M QPSK 1RB#50	0.514	0.272	0.12	22.70	23.00	0.551	Yes
Left Side	20300/1745	20M QPSK 1RB#50	0.066	0.036	0.13	22.70	23.00	0.070	/
Right Side	20300/1745	20M QPSK 1RB#50	0.173	0.099	-0.04	22.70	23.00	0.185	/
Bottom Side	20300/1745	20M QPSK 1RB#50	0.391	0.204	-0.03	22.70	23.00	0.419	/
50%RB									
Front Side	20300/1745	20M QPSK 50%RB#25	0.372	0.216	0.13	22.70	22.00	0.317	/
Back Side	20300/1745	20M QPSK 50%RB#25	0.490	0.244	0.16	22.70	22.00	0.417	/
Left Side	20300/1745	20M QPSK 50%RB#25	0.062	0.034	0.15	22.70	22.00	0.053	/
Right Side	20300/1745	20M QPSK 50%RB#25	0.165	0.095	0.00	22.70	22.00	0.140	/
Bottom Side	20300/1745	20M QPSK 50%RB#25	0.389	0.202	-0.04	22.70	22.00	0.331	/

Table 55: Hotspot SAR test results of LTE Band IV

Copyright © Huawei Technologies Co., Ltd

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	Product Specific 10-g SAR Exclusion
			1-g	10-g					
1RB									
Front Side	20300/1745	20M QPSK 1RB#50	0.414	0.232	0.13	22.70	24.00	0.558	Yes
Back Side	20300/1745	20M QPSK 1RB#50	0.514	0.272	0.12	22.70	24.00	0.693	Yes
Left Side	20300/1745	20M QPSK 1RB#50	0.066	0.036	0.13	22.70	24.00	0.089	Yes
Right Side	20300/1745	20M QPSK 1RB#50	0.173	0.099	-0.04	22.70	24.00	0.233	Yes
Bottom Side	20300/1745	20M QPSK 1RB#50	0.391	0.204	-0.03	22.70	24.00	0.527	Yes
50%RB									
Front Side	20300/1745	20M QPSK 50%RB#25	0.372	0.216	0.13	22.70	23.00	0.399	Yes
Back Side	20300/1745	20M QPSK 50%RB#25	0.490	0.244	0.16	22.70	23.00	0.525	Yes
Left Side	20300/1745	20M QPSK 50%RB#25	0.062	0.034	0.15	22.70	23.00	0.066	Yes
Right Side	20300/1745	20M QPSK 50%RB#25	0.165	0.095	0.00	22.70	23.00	0.177	Yes
Bottom Side	20300/1745	20M QPSK 50%RB#25	0.389	0.202	-0.04	22.70	23.00	0.417	Yes

Table 56: Product Specific 10-g SAR test reduction evaluation of LTE Band IV

Note : According to the table above , Product Specific 10-g SAR test is not required for this frequency band.

Copyright © Huawei Technologies Co., Ltd

7.2.7 SAR measurement Result of LTE Band V

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Left touch	20525/836.5	10M QPSK 1RB#49	0.257	0.198	0.05	23.25	24.00	0.305	/
Left tilt	20525/836.5	10M QPSK 1RB#49	0.149	0.104	0.08	23.25	24.00	0.177	/
Right touch	20525/836.5	10M QPSK 1RB#49	0.253	0.193	0.17	23.25	24.00	0.301	/
Right tilt	20525/836.5	10M QPSK 1RB#49	0.156	0.108	0.08	23.25	24.00	0.185	/
Left touch	20450/829	10M QPSK 1RB#49	0.242	0.168	0.15	23.09	24.00	0.298	/
Left touch	20600/844	10M QPSK 1RB#0	0.267	0.206	0.17	23.07	24.00	0.331	Yes
50%RB									
Left touch	20600/844	10M QPSK 50%RB#0	0.201	0.139	0.01	22.01	23.00	0.252	/
Left tilt	20600/844	10M QPSK 50%RB#0	0.128	0.090	0.15	22.01	23.00	0.161	/
Right touch	20600/844	10M QPSK 50%RB#0	0.205	0.139	0.12	22.01	23.00	0.257	/
Right tilt	20600/844	10M QPSK 50%RB#0	0.130	0.090	0.07	22.01	23.00	0.163	/

Table 57: Head SAR test results of LTE Band V

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	20525/836.5	10M QPSK 1RB#49	0.254	0.193	-0.01	23.25	24.00	0.302	/
Back Side	20525/836.5	10M QPSK 1RB#49	0.232	0.137	0.07	23.25	24.00	0.276	/
50%RB									
Front Side	20600/844	10M QPSK 50%RB#0	0.260	0.198	-0.09	22.01	23.00	0.327	Yes
Back Side	20600/844	10M QPSK 50%RB#0	0.226	0.159	0.02	22.01	23.00	0.284	/

Table 58: Body-Worn SAR test results of LTE Band V

Copyright © Huawei Technologies Co., Ltd

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	20525/836.5	10M QPSK 1RB#25	0.228	0.151	0.01	22.69	23.00	0.245	/
Back Side	20525/836.5	10M QPSK 1RB#25	0.321	0.186	0.00	22.69	23.00	**0.345**	Yes
Left Side	20525/836.5	10M QPSK 1RB#25	0.292	0.192	-0.01	22.69	23.00	0.314	/
Right Side	20525/836.5	10M QPSK 1RB#25	0.233	0.155	-0.14	22.69	23.00	0.250	/
Bottom Side	20525/836.5	10M QPSK 1RB#25	0.204	0.130	0.09	22.69	23.00	0.219	/
50%RB									
Front Side	20525/836.5	10M QPSK 50%RB#0	0.224	0.149	0.01	21.41	22.00	0.257	/
Back Side	20525/836.5	10M QPSK 50%RB#0	0.311	0.214	-0.02	21.41	22.00	0.356	/
Left Side	20525/836.5	10M QPSK 50%RB#0	0.285	0.188	0.00	21.41	22.00	0.326	/
Right Side	20525/836.5	10M QPSK 50%RB#0	0.239	0.159	-0.05	21.41	22.00	0.274	/
Bottom Side	20525/836.5	10M QPSK 50%RB#0	0.217	0.138	-0.09	21.41	22.00	0.249	/

Table 59: Hotspot SAR test results of LTE Band V

Copyright © Huawei Technologies Co., Ltd

Per KDB648474D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold:

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	Product Specific 10-g SAR Exclusion
			1-g	10-g					
1RB									
Front Side	20525/836.5	10M QPSK 1RB#25	0.228	0.151	0.01	22.69	24.00	0.308	Yes
Back Side	20525/836.5	10M QPSK 1RB#25	0.321	0.186	0.00	22.69	24.00	0.434	Yes
Left Side	20525/836.5	10M QPSK 1RB#25	0.292	0.192	-0.01	22.69	24.00	0.395	Yes
Right Side	20525/836.5	10M QPSK 1RB#25	0.233	0.155	-0.14	22.69	24.00	0.315	Yes
Bottom Side	20525/836.5	10M QPSK 1RB#25	0.204	0.130	0.09	22.69	24.00	0.276	Yes
50%RB									
Front Side	20525/836.5	10M QPSK 50%RB#0	0.224	0.149	0.01	21.41	23.00	0.323	Yes
Back Side	20525/836.5	10M QPSK 50%RB#0	0.311	0.214	-0.02	21.41	23.00	0.448	Yes
Left Side	20525/836.5	10M QPSK 50%RB#0	0.285	0.188	0.00	21.41	23.00	0.411	Yes
Right Side	20525/836.5	10M QPSK 50%RB#0	0.239	0.159	-0.05	21.41	23.00	0.345	Yes
Bottom Side	20525/836.5	10M QPSK 50%RB#0	0.217	0.138	-0.09	21.41	23.00	0.313	Yes

Table 60: Product Specific 10-g SAR test reduction evaluation of LTE Band V

Note : According to the table above , Product Specific 10-g SAR test is not required for this frequency band.

Copyright © Huawei Technologies Co., Ltd

7.2.8 SAR measurement Result of LTE Band XII

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Left touch	23060/704	10M QPSK 1RB#25	0.230	0.181	0.02	23.77	24.00	0.243	Yes
Left tilt	23060/704	10M QPSK 1RB#25	0.124	0.101	0.03	23.77	24.00	0.131	/
Right touch	23060/704	10M QPSK 1RB#25	0.205	0.161	-0.08	23.77	24.00	0.216	/
Right tilt	23060/704	10M QPSK 1RB#25	0.102	0.083	0.01	23.77	24.00	0.108	/
Left touch	23095/707.5	10M QPSK 1RB#25	0.224	0.179	0.16	23.76	24.00	0.237	/
Left touch	23130/711	10M QPSK 1RB#49	0.207	0.165	0.12	23.76	24.00	0.219	/
50%RB									
Left touch	23130/711	10M QPSK 50%RB#25	0.178	0.140	0.10	22.62	23.00	0.194	/
Left tilt	23130/711	10M QPSK 50%RB#25	0.097	0.079	0.09	22.62	23.00	0.106	/
Right touch	23130/711	10M QPSK 50%RB#25	0.155	0.123	0.15	22.62	23.00	0.169	/
Right tilt	23130/711	10M QPSK 50%RB#25	0.075	0.062	0.03	22.62	23.00	0.082	/

Table 61: Head SAR test results of LTE Band XII

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	23060/704	10M QPSK 1RB#25	0.223	0.173	-0.14	23.77	24.00	0.235	/
Back Side	23060/704	10M QPSK 1RB#25	0.302	0.230	0.16	23.77	24.00	**0.318**	Yes
50%RB									
Front Side	23130/711	10M QPSK 50%RB#25	0.167	0.130	0.01	22.62	23.00	0.182	/
Back Side	23130/711	10M QPSK 50%RB#25	0.217	0.167	-0.01	22.62	23.00	0.237	/

Table 62: Body-Worn SAR test results of LTE Band XII

Copyright © Huawei Technologies Co., Ltd

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	23060/704	10M QPSK 1RB#25	0.254	0.199	-0.15	23.77	24.00	0.268	/
Back Side	23060/704	10M QPSK 1RB#25	0.306	0.201	0.09	23.77	24.00	0.323	/
Left Side	23060/704	10M QPSK 1RB#25	0.361	0.244	-0.16	23.77	24.00	0.381	/
Right Side	23060/704	10M QPSK 1RB#25	0.405	0.273	-0.05	23.77	24.00	0.427	Yes
Bottom Side	23060/704	10M QPSK 1RB#25	0.113	0.069	-0.15	23.77	24.00	0.119	/
50%RB									
Front Side	23130/711	10M QPSK 50%RB#25	0.183	0.132	-0.08	22.62	23.00	0.200	/
Back Side	23130/711	10M QPSK 50%RB#25	0.265	0.181	0.01	22.62	23.00	0.289	/
Left Side	23130/711	10M QPSK 50%RB#25	0.318	0.214	-0.04	22.62	23.00	0.347	/
Right Side	23130/711	10M QPSK 50%RB#25	0.326	0.216	-0.01	22.62	23.00	0.356	/
Bottom Side	23130/711	10M QPSK 50%RB#25	0.092	0.057	-0.11	22.62	23.00	0.101	/

Table 63: Hotspot SAR test results of LTE Band XII

Note: Per KDB 648474 D04, Product Specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

Copyright © Huawei Technologies Co., Ltd

7.2.9 SAR measurement Result of LTE Band XXX

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Left touch	27710/2310	10M QPSK 1RB#49	0.048	0.023	0.15	23.87	24.00	0.049	/
Left tilt	27710/2310	10M QPSK 1RB#49	0.033	0.016	0.11	23.87	24.00	0.034	/
Right touch	27710/2310	10M QPSK 1RB#49	0.080	0.044	0.13	23.87	24.00	**0.083**	Yes
Right tilt	27710/2310	10M QPSK 1RB#49	0.036	0.011	0.13	23.87	24.00	0.037	/
50%RB									
Left touch	27710/2310	10M QPSK 50%RB#0	0.037	0.014	0.00	22.97	23.00	0.037	/
Left tilt	27710/2310	10M QPSK 50%RB#0	0.025	0.012	0.11	22.97	23.00	0.026	/
Right touch	27710/2310	10M QPSK 50%RB#0	0.058	0.031	-0.12	22.97	23.00	0.059	/
Right tilt	27710/2310	10M QPSK 50%RB#0	0.023	0.088	0.12	22.97	23.00	0.023	/

Table 64: Head SAR test results of LTE Band XXX

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	27710/2310	10M QPSK 1RB#49	0.220	0.123	0.11	23.87	24.00	0.227	/
Back Side	27710/2310	10M QPSK 1RB#49	0.282	0.161	0.14	23.87	24.00	**0.291**	Yes
50%RB									
Front Side	23800/711	10M QPSK 50%RB#0	0.152	0.110	-0.03	22.38	23.00	0.175	/
Back Side	23800/711	10M QPSK 50%RB#0	0.174	0.125	-0.04	22.38	23.00	0.201	/

Table 65: Body-Worn SAR test results of LTE Band XXX

Copyright © Huawei Technologies Co., Ltd

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
1RB									
Front Side	27710/2310	10M QPSK 1RB#49	0.255	0.137	0.18	23.87	24.00	0.263	/
Back Side	27710/2310	10M QPSK 1RB#49	0.438	0.242	0.11	23.87	24.00	0.451	/
Left Side	27710/2310	10M QPSK 1RB#49	0.048	0.029	-0.11	23.87	24.00	0.050	/
Right Side	27710/2310	10M QPSK 1RB#49	0.098	0.050	0.17	23.87	24.00	0.101	/
Bottom Side	27710/2310	10M QPSK 1RB#49	0.727	0.378	0.06	23.87	24.00	0.749	Yes
50%RB									
Front Side	27710/2310	10M QPSK 50%RB#0	0.245	0.127	0.15	22.97	23.00	0.247	/
Back Side	27710/2310	10M QPSK 50%RB#0	0.341	0.178	0.19	22.97	23.00	0.343	/
Left Side	27710/2310	10M QPSK 50%RB#0	0.040	0.024	0.18	22.97	23.00	0.040	/
Right Side	27710/2310	10M QPSK 50%RB#0	0.078	0.040	0.01	22.97	23.00	0.079	/
Bottom Side	27710/2310	10M QPSK 50%RB#0	0.588	0.288	0.10	22.97	23.00	0.592	/

Table 66: Hotspot SAR test results of LTE Band XXX

Note: Per KDB 648474 D04, Product Specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

Copyright © Huawei Technologies Co., Ltd

7.2.10 SAR measurement Result of WiFi 2.4G

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g Area Scan	1-g Zoom Scan					
Left touch	6/2437	802.11 b	0.696	0.675	0.090	16.71	17.50	0.810	/
Left tilt	6/2437	802.11 b	0.696	**0.689**	0.070	16.71	17.50	0.826	Yes
Right touch	6/2437	802.11 b	0.278	0.274	0.160	16.71	17.50	0.329	/
Right tilt	6/2437	802.11 b	0.293	0.293	0.030	16.71	17.50	0.351	/
Left tilt	1/2412	802.11 b	0.576	0.571	0.080	16.23	17.50	0.765	/
Left tilt	11/2462	802.11 b	0.651	0.648	0.110	16.63	17.50	0.792	/
Left touch	11/2462	802.11 b	0.645	0.638	0.190	16.63	17.50	0.780	/

Table 67: Head SAR test results of WiFi 2450MHz

According to KDB248227 D01,The reported SAR must be scaled to 100% transmission duty factor to determine compliance at maximum tune-up tolerance limit.The reported SAR is presented as below.

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	Scaled SAR_{1-g} (W/kg)	Actual duty factor	Maximum duty factor	Reported SAR_{1-g} (W/kg)
Left touch	6/2437	802.11 b	0.810	97.0%	100%	0.835
Left tilt	6/2437	802.11 b	0.826	97.0%	100%	**0.852**
Right touch	6/2437	802.11 b	0.329	97.0%	100%	0.339
Right tilt	6/2437	802.11 b	0.351	97.0%	100%	0.362
Left tilt	1/2412	802.11 b	0.765	97.0%	100%	0.789
Left tilt	11/2462	802.11 b	0.792	97.0%	100%	0.816
Left touch	11/2462	802.11 b	0.780	97.0%	100%	0.804

Mode	Tune-up （dBm）	Tune-up （mW）	Hightest Reported SAR(W/kg)	Adjusted SAR (W/kg)	SAR test
802.11b	17.50	56.23	0.852	/	Yes
802.11g	16.00	39.81	/	0.603	No
802.11n 20M	14.50	28.18	/	0.427	No
802.11n 40M	13.50	22.39	/	0.339	No

Note:

1) Per KDB248227D01, for Head SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. As the highest reported SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is < 1.2 W/kg, so SAR for 802.11g/n is not required.

Copyright © Huawei Technologies Co., Ltd

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g Area Scan	1-g Zoom Scan					
Front Side	6/2437	802.11 b	0.081	0.082	0.000	16.71	17.50	0.099	/
Back Side	6/2437	802.11 b	0.093	0.089	0.170	16.71	17.50	**0.107**	Yes

Table 68: Body-Worn SAR test results of WiFi 2450MHz

According to KDB248227 D01,The reported SAR must be scaled to 100% transmission duty factor to determine compliance at maximum tune-up tolerance limit.The reported SAR is presented as below.

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	Scaled SAR_{1-g} (W/kg)	Actual duty factor	Maximum duty factor	Reported SAR_{1-g} (W/kg)
Front Side	6/2437	802.11 b	0.099	97.0%	100%	0.102
Back Side	6/2437	802.11 b	0.107	97.0%	100%	**0.111**

Mode	Tune-up （dBm）	Tune-up （mW）	Hightest Reported SAR(W/kg)	Adjusted SAR (W/kg)	SAR test
802.11b	17.50	56.23	0.111	/	Yes
802.11g	16.00	39.81	/	0.079	No
802.11n 20M	14.50	28.18	/	0.056	No
802.11n 40M	13.50	22.39	/	0.044	No

Note: Per KDB248227D01, for Body-Worn SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. As the highest reported SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is < 1.2 W/kg, so SAR for 802.11g/n is not required.

Copyright © Huawei Technologies Co., Ltd

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g Area Scan	1-g Zoom Scan					
Front Side	6/2437	802.11 b	0.145	0.137	0.000	16.71	17.50	0.164	/
Back Side	6/2437	802.11 b	0.198	0.185	0.140	16.71	17.50	0.222	Yes
Right Side	6/2437	802.11 b	0.126	/	0.090	16.71	17.50	/	/
Top Side	6/2437	802.11 b	0.168	/	0.190	16.71	17.50	/	/

Table 69: Hotspot SAR test results of WiFi 2450MHz

According to KDB248227 D01,The reported SAR must be scaled to 100% transmission duty factor to determine compliance at maximum tune-up tolerance limit.The scaled reported SAR is presented as below.

Test Position of Hotspot with 10mm	Test channel / Freq.(MHz)	Test Mode	Scaled SAR_{1-g} (W/kg)	Actual duty factor	Maximum duty factor	Scaled Reported SAR_{1-g} (W/kg)
Front Side	6/2437	802.11 b	0.164	97.0%	100%	0.169
Back Side	6/2437	802.11 b	0.222	97.0%	100%	**0.229**
Right Side	6/2437	802.11 b	/	97.0%	100%	/
Top Side	6/2437	802.11 b	/	97.0%	100%	/

Mode	Tune-up （dBm）	Tune-up （mW）	Hightest Reported SAR(W/kg)	Adjusted SAR (W/kg)	SAR test
802.11b	17.50	56.23	0.229	/	Yes
802.11g	16.00	39.81	/	0.162	No
802.11n 20M	14.50	28.18	/	0.115	No
802.11n 40M	13.50	22.39	/	0.091	No

Note :

1) Per KDB248227D01, for Hotspot SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. As the highest reported SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is < 1.2 W/kg, so SAR for 802.11g/n is not required.

2) Per KDB 648474 D04, Product Specific 10-g SAR test is not required for this frequency band since hotspot mode 1-g reported SAR < 1.2 W/kg.

Copyright © Huawei Technologies Co., Ltd

7.2.11 SAR measurement Result of WiFi 5G

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g Area Scan	1-g Zoom Scan					
5.3G(UNII-2A Band)									
Left touch	52/5260	802.11a	0.297	0.520	0.170	13.74	14.50	0.619	
Left tilt	52/5260	802.11a	0.402	0.563	0.130	13.74	14.50	0.671	/
Right touch	52/5260	802.11a	0.439	0.683	-0.090	13.74	14.50	**0.814**	Yes
Right touch	56/5280	802.11a	0.393	0.665	-0.130	13.47	14.50	0.843	/
Right tilt	52/5260	802.11a	0.437	0.662	-0.020	13.74	14.50	0.789	/
Right tilt	56/5280	802.11a	0.388	0.554	0.080	13.47	14.50	0.702	/
5.5G(U-NII-2C Band)									
Left touch	128/5640	802.11a	0.242	0.283	0.110	14.40	14.50	0.290	/
Left tilt	128/5640	802.11a	0.233	/	0.130	14.40	14.50	/	/
Right touch	128/5640	802.11a	0.224	/	0.070	14.40	14.50	/	/
Right tilt	128/5640	802.11a	0.248	0.280	0.040	14.40	14.50	0.287	/
5.8G(U-NII-3 Band)									
Left touch	157/5785	802.11a	0.190	/	-0.110	14.34	14.50	/	/
Left tilt	157/5785	802.11a	0.263	0.229	-0.140	14.34	14.50	0.238	/
Right touch	157/5785	802.11a	0.240	/	0.170	14.34	14.50	/	/
Right tilt	157/5785	802.11a	0.260	0.248	0.160	14.34	14.50	0.257	/

Table 70: Head SAR test results of WiFi 5G

According to KDB248227 D01,The reported SAR must be scaled to 100% transmission duty factor to determine compliance at maximum tune-up tolerance limit.The reported SAR is presented as below.

Test Position of Head	Test channel / Freq.(MHz)	Test Mode	Scaled SAR_{1-g} (W/kg)	Actual duty factor	Maximum duty factor	Reported SAR_{1-g} (W/kg)
5.3G(UNII-2A Band)						
Left touch	52/5260	802.11a	0.619	86.0%	100%	0.720
Left tilt	52/5260	802.11a	0.671	86.0%	100%	0.780
Right touch	52/5260	802.11a	0.814	86.0%	100%	0.946
Right touch	56/5280	802.11a	0.843	86.0%	100%	**0.980**
Right tilt	52/5260	802.11a	0.789	86.0%	100%	0.917
Right tilt	56/5280	802.11a	0.702	86.0%	100%	0.817
5.5G(U-NII-2C Band)						
Left touch	128/5640	802.11a	0.290	86.0%	100%	0.337
Left tilt	128/5640	802.11a	/	86.0%	100%	/
Right touch	128/5640	802.11a	/	86.0%	100%	/
Right tilt	128/5640	802.11a	0.287	86.0%	100%	0.333
5.8G(U-NII-3 Band)						
Left touch	157/5785	802.11a	/	86.0%	100%	/
Left tilt	157/5785	802.11a	0.238	86.0%	100%	0.276

Copyright © Huawei Technologies Co., Ltd

Right touch	157/5785	802.11a	/	86.0%	100%	/
Right tilt	157/5785	802.11a	0.257	86.0%	100%	0.299

Mode	Tune-up（dBm）	Tune-up（mW）	Hightest Reported SAR(W/kg)	Adjusted SAR (W/kg)	SAR test
802.11a	14.5	28.18	0.980	/	Yes
802.11n 20M	12.5	17.78	/	0.618	No
802.11n 40M	12.5	17.78	/	0.618	No

Note:

1) Per KDB 248227D01, as the same maximum output power is specified for U-NII-1(5.2G) and U-NII-2A(5.3G) bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. as the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration.

2) The 802.11a mode is selected as Initial Test Configuration for SAR test according to the specified maximum output power. as the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required.

Copyright © Huawei Technologies Co., Ltd

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g Area Scan	1-g Zoom Scan					
5.3G(UNII-2A Band)									
Front Side	52/5260	802.11a	0.053	/	0.000	13.74	14.50	/	/
Back Side	52/5260	802.11a	0.117	0.108	0.000	13.74	14.50	0.129	/
5.5G(U-NII-2C Band)									
Front Side	128/5640	802.11a	0.013	/	0.190	14.40	14.50	/	
Back Side	128/5640	802.11a	0.168	0.141	0.190	14.40	14.50	0.144	/
5.8G(U-NII-3 Band)									
Front Side	157/5785	802.11a	0.010	/	0.190	14.34	14.50	/	
Back Side	157/5785	802.11a	0.160	0.156	0.180	14.34	14.50	0.162	Yes

Table 71: Body-Worn SAR test results of WiFi 5G.

According to KDB248227 D01,The reported SAR must be scaled to 100% transmission duty factor to determine compliance at maximum tune-up tolerance limit.The reported SAR is presented as below.

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	Scaled SAR_{1-g} (W/kg)	Actual duty factor	Maximum duty factor	Reported SAR_{1-g} (W/kg)
5.3G(UNII-2A Band)						
Front Side	52/5260	802.11a	/	86.0%	100%	/
Back Side	52/5260	802.11a	0.129	86.0%	100%	0.150
5.5G(U-NII-2C Band)						
Front Side	128/5640	802.11a	/	86.0%	100%	/
Back Side	128/5640	802.11a	0.144	86.0%	100%	0.168
5.8G(U-NII-3 Band)						
Front Side	157/5785	802.11a	/	86.0%	100%	/
Back Side	157/5785	802.11a	0.162	86.0%	100%	**0.188**

Mode	Tune-up（dBm）	Tune-up（mW）	Hightest Reported SAR(W/kg)	Adjusted SAR (W/kg)	SAR test
802.11a	14.5	28.18	0.188	/	Yes
802.11n 20M	12.5	17.78	/	0.119	No
802.11n 40M	12.5	17.78	/	0.119	No

1) Per KDB 248227D01, as the same maximum output power is specified for U-NII-1(5.2G) and U-NII-2A(5.3G) bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. as the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration.

2) The 802.11a mode is selected as Initial Test Configuration for SAR test according to the specified maximum output power. as the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required.

Copyright © Huawei Technologies Co., Ltd

Product Specific 10-g SAR 0mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{10-g} (W/kg)	SAR Plot
			10-g Area Scan	10-g Zoom Scan					
5.3G(UNII-2A Band)									
Front Side	52/5260	802.11a	0.242	/	0.000	13.74	14.50	/	/
Back Side	52/5260	802.11a	0.247	0.343	0.000	13.74	14.50	0.409	/
Left Side	52/5260	802.11a	0.017	/	-0.140	13.74	14.50	/	/
Right Side	52/5260	802.11a	0.005	/	0.190	13.74	14.50	/	/
Top Side	52/5260	802.11a	0.360	0.544	0.080	13.74	14.50	0.648	/
5.5G(U-NII-2C Band)									
Front Side	128/5640	802.11a	0.103	/	0.000	14.40	14.50	/	/
Back Side	128/5640	802.11a	0.467	0.598	-0.190	14.40	14.50	0.612	/
Left Side	128/5640	802.11a	0.013	/	0.000	14.40	14.50	/	/
Right Side	128/5640	802.11a	0.017	/	-0.120	14.40	14.50	/	/
Top Side	128/5640	802.11a	0.442	0.604	0.000	14.40	14.50	0.618	Yes
5.8G(U-NII-3 Band)									
Front Side	157/5785	802.11a	0.077	/	0.190	14.34	14.50	/	/
Back Side	157/5785	802.11a	0.509	0.585	0.190	14.34	14.50	0.607	/
Left Side	157/5785	802.11a	0.021	/	0.000	14.34	14.50	/	/
Right Side	157/5785	802.11a	0.022	/	0.190	14.34	14.50	/	/
Top Side	157/5785	802.11a	0.477	0.512	0.110	14.34	14.50	0.531	/

Table 72: Product Specific SAR test results of WiFi 5G

Note: As WiFi 5G does not support hotspot function, so full Product Specific 10-g SAR tests were evaluated for WiFi 5G bands.

According to KDB248227 D01,The reported SAR must be scaled to 100% transmission duty factor to determine compliance at maximum tune-up tolerance limit.The scaled reported SAR is presented as below.

Product Specific 10-g SAR 0mm	Test channel / Freq.(MHz)	Test Mode	Scaled SAR_{10-g} (W/kg)	Actual duty factor	Maximum duty factor	Scaled Reported SAR_{10-g} (W/kg)
5.3G(UNII-2A Band)						
Front Side	52/5260	802.11a	/	86.0%	100%	/
Back Side	52/5260	802.11a	0.409	86.0%	100%	0.475
Left Side	52/5260	802.11a	/	86.0%	100%	/
Right Side	52/5260	802.11a	/	86.0%	100%	/
Top Side	52/5260	802.11a	0.648	86.0%	100%	0.754
5.5G(U-NII-2C Band)						
Front Side	128/5640	802.11a	/	86.0%	100%	/
Back Side	128/5640	802.11a	0.612	86.0%	100%	0.712
Left Side	128/5640	802.11a	/	86.0%	100%	/
Right Side	128/5640	802.11a	/	86.0%	100%	/
Top Side	128/5640	802.11a	0.618	86.0%	100%	0.719

Copyright © Huawei Technologies Co., Ltd

5.8G(U-NII-3 Band)						
Front Side	157/5785	802.11a	/	86.0%	100%	/
Back Side	157/5785	802.11a	0.607	86.0%	100%	0.706
Left Side	157/5785	802.11a	/	86.0%	100%	/
Right Side	157/5785	802.11a	/	86.0%	100%	/
Top Side	157/5785	802.11a	0.531	86.0%	100%	0.618

Mode	Tune-up（dBm）	Tune-up（mW）	Hightest Reported SAR(W/kg)	Adjusted SAR (W/kg)	SAR test
802.11a	14.5	28.18	0.754	/	Yes
802.11n 20M	12.5	17.78	/	0.476	No
802.11n 40M	12.5	17.78	/	0.476	No

Note :

1) Per KDB 248227D01, as the same maximum output power is specified for U-NII-1(5.2G) and U-NII-2A(5.3G) bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. as the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration.

3) The 802.11a mode is selected as Initial Test Configuration for SAR test according to the specified maximum output power. as the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required.

7.2.12 SAR measurement Result of BT

Test Position of Body-Worn with 15mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{1-g} (W/kg)	SAR Plot
			1-g	10-g					
Front Side	39/2441	DH5	0.004	0.003	0.00	10.17	11.00	**0.005**	Yes
Back Side	39/2441	DH5	0.004	0.002	-0.02	10.17	11.00	0.005	/

Table 73: Body-Worn SAR test results of BT

Product Specific 10-g SAR 0mm	Test channel / Freq.(MHz)	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR_{10-g} (W/kg)	SAR Plot
			1-g	10-g					
Front Side	39/2441	DH5	0.137	0.060	0.150	10.17	11.00	0.073	/
Back Side	39/2441	DH5	0.141	0.064	0.040	10.17	11.00	0.077	/
Right Side	39/2441	DH5	0.094	0.039	0.080	10.17	11.00	0.047	/
Top Side	39/2441	DH5	0.168	0.070	-0.080	10.17	11.00	0.085	Yes

Table 74: Product Specific 10-g SAR test results of BT

Copyright © Huawei Technologies Co., Ltd

7.3 Multiple Transmitter Evaluation

The following tables list information which is relevant for the decision if a simultaneous transmit evaluation is necessary according to FCC KDB 447498D01 General RF Exposure Guidance v06.
The location of the antennas inside the device is shown as below picture:



Per KDB 648474 D04, because the diagonal distance of this device is about 175.4mm > 160mm, it is considered a “Phablet” device.

Mode	Exposure Condition	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
Main antenna	Hotspot/ Product Specific 10-g	Yes	Yes	Yes	Yes	No	Yes
WiFi 2.4G/BT antenna	Hotspot/ Product Specific 10-g	Yes	Yes	No	Yes	Yes	No
WiFi 5G antenna	Hotspot/ Product Specific 10-g	Yes	Yes	Yes	Yes	Yes	No

Table 75: Sides for Hotspot SAR testing

Note:

1)The Diversity antenna does not support Tx function.

2) Per KDB 941225 D06 and KDB 648474 D04, particular DUT edges were not required to be evaluated for Hotspot and/or Extremity SAR if the antenna-to-edge distance is greater than 2.5cm.

3) Per KDB 648474 D04, when hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg;

Copyright © Huawei Technologies Co., Ltd

7.3.1 Simultaneous Transmission Possibilities

The Simultaneous Transmission Possibilities of this device are as below:

No.	Configuration	Head	Body-worn	Hotspot	Product Specific 10-g
1	GSM(Voice) + BT	No	Yes	No	Yes
2	GSM(Data) + BT	No	No	No	Yes
3	GSM(Voice)+ WiFi 2.4G	Yes	Yes	No	Yes
4	GSM(Data) + WiFi 2.4G	No	No	Yes	Yes
5	GSM(Voice)+ WiFi 5G	Yes	Yes	No	Yes
6	GSM(Data) + WiFi 5G	No	No	No	Yes
7	GSM(Voice) + BT+ WiFi 5G	No	Yes	No	Yes
8	GSM(Data) + BT+ WiFi 5G	No	No	No	Yes
9	UMTS(Voice) + BT	No	Yes	No	Yes
10	UMTS(Data) + BT	No	Yes	No	Yes
11	UMTS(Voice) + WiFi 2.4G	Yes	Yes	No	Yes
12	UMTS(Data) + WiFi 2.4G	No	Yes	Yes	Yes
13	UMTS(Voice) + WiFi 5G	Yes	Yes	No	Yes
14	UMTS(Data) + WiFi 5G	No	Yes	No	Yes
15	UMTS(Voice) + BT+WiFi 5G	No	Yes	No	Yes
16	UMTS(Data) + BT+ WiFi 5G	No	Yes	No	Yes
17	LTE(Data) + BT	No	Yes*	No	Yes*
18	LTE(Data) + WiFi 2.4G	Yes*	Yes*	Yes	Yes*
19	LTE(Data) + WiFi 5G	Yes*	Yes*	No	Yes*
20	LTE(Data) + BT+ WiFi 5G	No	Yes*	No	Yes*

Table 76: Simultaneous Transmission Possibilities

Note:

1) WiFi 2.4G and BT can't transmit simultaneously.

2) The device does not support VoLTE and WiFi VOIP function.

3) The device does not support DTM function. Body-worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.

4) Held to ear configurations are not applicable to Bluetooth for this device.

5) * VOIP 3rd party applications may possibly be installed and used by the user.

6) WiFi 5G does not support hotspot function.

Copyright © Huawei Technologies Co., Ltd

7.3.2 SAR Summation Scenario

Test Position		Main antenna SAR_{Max}									WiFi /BT antenna SARMax			Σ1-g or 10-g Product Specific	SPLSR
		GSM850	GSM1900	UMTS Band II	UMTS Band V	LTE Band II	LTE Band IV	LTE Band V	LTE Band XII	LTE Band XXX	WiFi 2.4G	WiFi 5G	BT		
Head	Left touch	0.451	0.038	0.066	0.344	0.063	0.081	0.305	0.243	0.049	0.835	0.720	/	1.286	N/A
	Left tilt	0.304	0.026	0.047	0.191	0.034	0.059	0.177	0.131	0.034	0.852	0.780	/	1.156	N/A
	Right touch	0.459	0.092	0.180	0.363	0.175	0.204	0.331	0.216	0.083	0.339	0.980	/	**1.439**	N/A
	Right tilt	0.288	0.014	0.035	0.171	0.040	0.070	0.185	0.108	0.037	0.362	0.917	/	1.205	N/A
Body-worn 15mm	Front side	0.423	0.268	0.557	0.293	0.461	0.394	0.327	0.235	0.227	0.102	0.188	0.005	0.745	N/A
	Back side	0.513	0.424	0.809	0.296	0.711	0.495	0.284	0.318	0.291	0.111	0.188	0.005	0.997	N/A
Hotspot 10mm	Front side	0.504	0.417	0.379	0.265	0.381	0.444	0.257	0.268	0.263	0.169	/	/	0.673	N/A
	Back side	0.691	0.683	0.560	0.489	0.593	0.551	0.345	0.323	0.451	0.229	/	/	0.920	N/A
	Left side	0.609	0.028	0.023	0.257	0.085	0.070	0.326	0.381	0.050	/	/	/	0.609	N/A
	Right side	0.480	0.090	0.066	0.239	0.285	0.185	0.274	0.427	0.101	0.229	/	/	0.709	N/A
	Top side	/	/	/	/	/	/	/	/	/	0.229	/	/	0.229	N/A
	Bottom side	0.536	0.779	0.609	0.264	0.561	0.419	0.249	0.119	0.749	/	/	/	0.779	N/A
10-g Product Specific 0mm	Front side	/	/	/	/	/	/	/	/	/	/	0.754	0.073	0.754	N/A
	Back side	/	2.396	3.010	/	3.191	/	/	/	/	/	0.712	0.077	**3.903**	N/A
	Left side	/	/	/	/	/	/	/	/	/	/	0.754	/	0.754	N/A
	Right side	/	/	/	/	/	/	/	/	/	/	0.754	0.047	0.754	N/A
	Top side	/	/	/	/	/	/	/	/	/	/	0.754	0.085	0.754	N/A
	Bottom side	/	1.960	3.267	/	2.817	/	/	/	/	/	/	/	3.267	N/A

Table 77: SAR Simultaneous Tx Combination of Main antenna and WiFi 2.4G/5G/BT.

Test Position		Main antenna SAR_{Max}									WiFi antenna	BT antenna	Σ1-g or 10-g Product Specific	SPLSR
		GSM850	GSM1900	UMTS Band II	UMTS Band V	LTE Band II	LTE Band IV	LTE Band V	LTE Band XII	LTE Band XXX	WiFi 5G	BT		
Head	Left touch	0.451	0.038	0.066	0.344	0.063	0.081	0.305	0.243	0.049	0.720	/	1.172	N/A
	Left tilt	0.304	0.026	0.047	0.191	0.034	0.059	0.177	0.131	0.034	0.780	/	1.084	N/A
	Right touch	0.459	0.092	0.180	0.363	0.175	0.204	0.331	0.216	0.083	0.980	/	**1.439**	N/A
	Right tilt	0.288	0.014	0.035	0.171	0.040	0.070	0.185	0.108	0.037	0.917	/	1.205	N/A
Body-worn 15mm	Front side	0.423	0.268	0.557	0.293	0.461	0.394	0.327	0.235	0.227	0.188	0.005	0.750	N/A
	Back side	0.513	0.424	0.809	0.296	0.711	0.495	0.284	0.318	0.291	0.188	0.005	1.002	N/A
Hotspot 10mm	Front side	0.504	0.417	0.379	0.265	0.381	0.444	0.257	0.268	0.263	/	/	0.504	N/A
	Back side	0.691	0.683	0.560	0.489	0.593	0.551	0.345	0.323	0.451	/	/	0.691	N/A
	Left side	0.609	0.028	0.023	0.257	0.085	0.070	0.326	0.381	0.050	/	/	0.609	N/A
	Right side	0.480	0.090	0.066	0.239	0.285	0.185	0.274	0.427	0.101	/	/	0.480	N/A
	Top side	/	/	/	/	/	/	/	/	/	/	/	0.000	N/A
	Bottom side	0.536	0.779	0.609	0.264	0.561	0.419	0.249	0.119	0.749	/	/	0.779	N/A
10-g Product Specific 0mm	Front side	/	/	/	/	/	/	/	/	/	0.754	0.073	0.827	N/A
	Back side	/	2.396	3.010	/	3.191	/	/	/	/	0.712	0.077	**3.980**	N/A
	Left side	/	/	/	/	/	/	/	/	/	0.754	/	0.754	N/A
	Right side	/	/	/	/	/	/	/	/	/	0.754	0.047	0.801	N/A
	Top side	/	/	/	/	/	/	/	/	/	0.754	0.085	0.839	N/A
	Bottom side	/	1.960	3.267	/	2.817	/	/	/	/	/		3.267	N/A

Table 78: SAR Simultaneous Tx Combination of Main antenna and WiFi 5G and BT.

Note: Per KDB 648474 D04, simultaneous transmission SAR consideration for Product Specific 10-g SAR requires consideration only when standalone 10-g SAR is required.

7.3.3 Simultaneous Transmission Conlcusion

The above numeral summed SAR results and/or SPLSR analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore simultaneous transmission SAR with Volume Scans is not required per KDB 447498 D01v06.

Copyright © Huawei Technologies Co., Ltd

Appendix A. System Check Plots
(Pls See Appendix No.: SYBH(Z-SAR)049052016-2A, total: 20 pages)

Appendix B. SAR Measurement Plots
(Pls See Appendix No.: SYBH(Z-SAR)049052016-2B, total: 39 pages)

Appendix C. Calibration Certificate
(Pls See Appendix No.: SYBH(Z-SAR)049052016-2C, total: 102 pages)

Appendix D. Photo documentation
(Pls See Appendix No.: SYBH(Z-SAR)049052016-2D, total: 9 pages)

End

Copyright © Huawei Technologies Co., Ltd