



RF TEST REPORT

Applicant Huawei Technologies Co., Ltd.
FCC ID QISLIO-LX9
Product Smart Phone
Model LIO-L29, LIO-L09
Report No. R1907H0137-R9V2
Issue Date January 21, 2020

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C (2018)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the test report.....	4
1.2. Test facility	4
1.3. Testing Location.....	5
2. General Description of Equipment under Test.....	6
3. Applied Standards	8
4. Test Configuration	9
5. Test Case Results	10
5.1. 20dB Bandwidth	10
5.2. Frequency Stability.....	12
5.3. Radiates Emission	18
5.4. Conducted Emission	25
6. Main Test Instruments	29



Summary of measurement results

Number	Test Case	Clause in FCC rules	Verdict
1	20 dB bandwidth	2.1049	PASS
2	Frequency Stability Tolerance	15.225(e)	PASS
3	Radiated Emissions	15.225 (a) (b) (c) (d) and 15.209	PASS
4	Conducted Emissions	15.207	PASS
Date of Testing: July 20, 2019~ August 11, 2019			

Note: This revised report (Report No.: R1907H0137-R9V2) supersedes and replaces the previously issued report (Report No.: R1907H0137-R9V1). Please discard or destroy the previously issued report and dispose of it accordingly.



1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

Client Information

Applicant	Huawei Technologies Co., Ltd.
Applicant address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Manufacturer	Huawei Technologies Co., Ltd.
Manufacturer address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

General information

EUT Description				
Model:	LIO-L29, LIO-L09			
SN:	YDM0119625000032			
Hardware Version:	HL1LIONM			
Software Version:	5.0.1.103M(C432E103R4P1)			
Power Supply:	Battery/AC adapter			
Antenna Type:	Internal Antenna			
Antenna Connector	A permanently attached antenna (meet with the standard FCC Part 15.203 requirement)			
Test Mode:	NFC-A	NFC-B	NFC-F	NFC-V
Modulation Type:	ASK	ASK, BPSK	ASK	ASK
Operating Frequency Range(s)	13.56MHz			
Operating temperature range:	-20 ° C to 50° C			
Operating voltage range:	3.6 V to 4.35 V			
State DC voltage:	3.8 V			
EUT Accessory				
Battery 1	Manufacturer: HUAWEI Technologies Co., Ltd. (Sunwoda, Murata) Model: HB555591EEW			
Battery 2	Manufacturer: HUAWEI Technologies Co., Ltd. (Sunwoda, ATL) Model: HB555591EEW			
Battery 3	Manufacturer: HUAWEI Technologies Co., Ltd. (SCUD) Model: HB555591EEW			



Earphone 1	Manufacturer: Jiangxi Lianchuang Hongsheng Electronic Co.,LTD Model: MEND1632B729001
Earphone 2	Manufacturer: Jiangxi Lianchuang Hongsheng Electronic Co.,LTD Model: MEND1632B729000
Earphone 3	Manufacturer: GoerTek Inc Model: WINDY-C
Earphone 4	Manufacturer: Boluo County Quancheng Electronic Co.,Ltd Model: 1331-3301-6001-TC-296
Earphone 5	Manufacturer: Foster Electric Co.,(GuangZhou)LTD.Sales Dep. Model: 618017
Note: The information of the EUT is declared by the manufacturer.	

LIO-L29 is dual SIM smart phone. LIO-L09 is single SIM smart phone. The model LIO-L29 and LIO-L09 are identical except for LIO-L09 support single SIM card which deleted by software.



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

- FCC CFR47 Part 2 (2018)
- FCC CFR47 Part 15C (2018)
- ANSI C63.10 (2013)



4. Test Configuration

Test Mode

The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

5. Test Case Results

5.1. 20dB Bandwidth


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable. RBW is set to 10 kHz; VBW is set to 3 times thw RBW on spectrum analyzer.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 936$ Hz.

Test Results:**NFC-A**

Carrier frequency (MHz)	99% Bandwidth (kHz)	20dB Bandwidth (kHz)	Conclusion
13.56MHz	22.848	26.92	PASS

NFC-B

Carrier frequency (MHz)	99% Bandwidth (kHz)	20dB Bandwidth (kHz)	Conclusion
13.56MHz	22.854	26.92	PASS

NFC-F

Carrier frequency (MHz)	99% Bandwidth (kHz)	20dB Bandwidth (kHz)	Conclusion
13.56MHz	22.856	26.93	PASS

NFC-V

Carrier frequency (MHz)	99% Bandwidth (kHz)	20dB Bandwidth (kHz)	Conclusion
13.56MHz	22.851	26.93	PASS

5.2. Frequency Stability

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -20°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -20°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

2. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.6V and 4.35V, with a nominal voltage of 3.8V.

Test setup



**Limits**

Rule Part 15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+ 50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.



Test Result

NFC-A

Test status	Frequency				Tolerance (MHz)			
	13.56MHz							
	1min	2min	5min	10min	1min	2min	5min	10min
-20°C/3.8 V	13.559350	13.559350	13.559343	13.559349	0.000650	0.000650	0.000657	0.000651
-10°C/3.8 V	13.559341	13.559346	13.559340	13.559339	0.000659	0.000654	0.000660	0.000661
0°C/3.8 V	13.559339	13.559337	13.559338	13.559331	0.000661	0.000663	0.000662	0.000669
15°C/3.8V	13.559334	13.559334	13.559331	13.559329	0.000666	0.000666	0.000669	0.000671
20°C/3.8 V	13.559328	13.559333	13.559329	13.559327	0.000672	0.000667	0.000671	0.000673
25°C/3.8 V	13.559318	13.559324	13.559323	13.559322	0.000682	0.000676	0.000677	0.000678
30°C/3.8 V	13.559310	13.559323	13.559320	13.559318	0.000690	0.000677	0.000680	0.000682
35°C/3.8 V	13.559309	13.559320	13.559311	13.559317	0.000691	0.000680	0.000689	0.000683
40°C/3.8 V	13.559308	13.559318	13.559305	13.559310	0.000692	0.000682	0.000695	0.000690
45°C/3.8 V	13.559302	13.559314	13.559298	13.559301	0.000698	0.000686	0.000702	0.000699
50°C/3.8 V	13.559294	13.559306	13.559288	13.559297	0.000706	0.000694	0.000712	0.000703
25°C/3.6 V	13.559299	13.559319	13.559306	13.559309	0.000701	0.000681	0.000694	0.000691
25°C/4.35 V	13.559299	13.559313	13.559297	13.559307	0.000701	0.000687	0.000703	0.000693

Test status	Tolerance (%)				Limit (%)	Conclusion
	1min	2min	5min	10min		
-20°C/3.8 V	0.004796	0.004791	0.004847	0.004804	±0.01	PASS
-10°C/3.8 V	0.004862	0.004823	0.004871	0.004875	±0.01	PASS
0°C/3.8 V	0.004871	0.004888	0.004885	0.004933	±0.01	PASS
15°C/3.8V	0.004913	0.004909	0.004934	0.004949	±0.01	PASS
20°C/3.8 V	0.004956	0.004916	0.004951	0.004961	±0.01	PASS
25°C/3.8 V	0.005026	0.004984	0.004996	0.005002	±0.01	PASS
30°C/3.8 V	0.005085	0.004996	0.005018	0.005029	±0.01	PASS
35°C/3.8 V	0.005099	0.005012	0.005084	0.005033	±0.01	PASS
40°C/3.8 V	0.005166	0.005021	0.005119	0.005093	±0.01	PASS
45°C/3.8 V	0.005170	0.005069	0.005188	0.005111	±0.01	PASS
50°C/3.8 V	0.005101	0.005026	0.005128	0.005090	±0.01	PASS
25°C/3.6 V	0.005166	0.005021	0.005119	0.005093	±0.01	PASS
25°C/4.35 V	0.005170	0.005069	0.005188	0.005111	±0.01	PASS



NFC-B

Test status	Frequency				Tolerance (MHz)			
	13.56MHz							
	1min	2min	5min	10min	1min	2min	5min	10min
-20°C/3.8 V	13.559343	13.559348	13.559352	13.559341	0.000657	0.000652	0.000648	0.000659
-10°C/3.8 V	13.559334	13.559340	13.559348	13.559339	0.000666	0.000660	0.000652	0.000661
0°C/3.8 V	13.559325	13.559332	13.559347	13.559338	0.000675	0.000668	0.000653	0.000662
15°C/3.8V	13.559324	13.559325	13.559345	13.559330	0.000676	0.000675	0.000655	0.000670
20°C/3.8 V	13.559315	13.559324	13.559337	13.559323	0.000685	0.000676	0.000663	0.000677
25°C/3.8 V	13.559315	13.559315	13.559337	13.559319	0.000685	0.000685	0.000663	0.000681
30°C/3.8 V	13.559307	13.559305	13.559336	13.559316	0.000693	0.000695	0.000664	0.000684
35°C/3.8 V	13.559305	13.559300	13.559328	13.559312	0.000695	0.000700	0.000672	0.000688
40°C/3.8 V	13.559304	13.559300	13.559325	13.559304	0.000696	0.000700	0.000675	0.000696
45°C/3.8 V	13.559298	13.559298	13.559320	13.559303	0.000702	0.000702	0.000680	0.000697
50°C/3.8 V	13.559295	13.559298	13.559314	13.559293	0.000705	0.000702	0.000686	0.000707
25°C/3.6 V	13.559305	13.559296	13.559322	13.559305	0.000695	0.000704	0.000678	0.000695
25°C/4.35 V	13.559302	13.559294	13.559317	13.559295	0.000698	0.000706	0.000683	0.000705

Test status	Tolerance (%)				Limit (%)	Conclusion
	1min	2min	5min	10min		
-20°C/3.8 V	0.004844	0.004808	0.004780	0.004862	±0.01	PASS
-10°C/3.8 V	0.004908	0.004865	0.004811	0.004876	±0.01	PASS
0°C/3.8 V	0.004980	0.004929	0.004813	0.004882	±0.01	PASS
15°C/3.8V	0.004987	0.004975	0.004833	0.004944	±0.01	PASS
20°C/3.8 V	0.005050	0.004984	0.004886	0.004990	±0.01	PASS
25°C/3.8 V	0.005053	0.005052	0.004892	0.005025	±0.01	PASS
30°C/3.8 V	0.005112	0.005123	0.004899	0.005046	±0.01	PASS
35°C/3.8 V	0.005123	0.005163	0.004953	0.005070	±0.01	PASS
40°C/3.8 V	0.005124	0.005194	0.005001	0.005124	±0.01	PASS
45°C/3.8 V	0.005151	0.005205	0.005040	0.005197	±0.01	PASS
50°C/3.8 V	0.005136	0.005164	0.004977	0.005130	±0.01	PASS
25°C/3.6 V	0.005124	0.005194	0.005001	0.005124	±0.01	PASS
25°C/4.35 V	0.005151	0.005205	0.005040	0.005197	±0.01	PASS



NFC-F

Test status	Frequency				Tolerance (MHz)			
	13.56MHz							
	1min	2min	5min	10min	1min	2min	5min	10min
-20°C/3.8 V	13.559350	13.559336	13.559349	13.559348	0.000650	0.000664	0.000651	0.000652
-10°C/3.8 V	13.559349	13.559331	13.559348	13.559345	0.000651	0.000669	0.000652	0.000655
0°C/3.8 V	13.559345	13.559326	13.559341	13.559344	0.000655	0.000674	0.000659	0.000656
15°C/3.8V	13.559340	13.559325	13.559333	13.559335	0.000660	0.000675	0.000667	0.000665
20°C/3.8 V	13.559338	13.559323	13.559325	13.559332	0.000662	0.000677	0.000675	0.000668
25°C/3.8 V	13.559330	13.559318	13.559322	13.559323	0.000670	0.000682	0.000678	0.000677
30°C/3.8 V	13.559321	13.559315	13.559320	13.559315	0.000679	0.000685	0.000680	0.000685
35°C/3.8 V	13.559313	13.559308	13.559318	13.559306	0.000687	0.000692	0.000682	0.000694
40°C/3.8 V	13.559309	13.559299	13.559318	13.559302	0.000691	0.000701	0.000682	0.000698
45°C/3.8 V	13.559306	13.559292	13.559312	13.559301	0.000694	0.000708	0.000688	0.000699
50°C/3.8 V	13.559301	13.559291	13.559304	13.559292	0.000699	0.000709	0.000696	0.000708
25°C/3.6 V	13.559305	13.559300	13.559316	13.559305	0.000695	0.000700	0.000684	0.000695
25°C/4.35 V	13.559296	13.559299	13.559312	13.559297	0.000704	0.000701	0.000688	0.000703

Test status	Tolerance (%)				Limit (%)	Conclusion
	1min	2min	5min	10min		
-20°C/3.8 V	0.004795	0.004894	0.004803	0.004810	±0.01	PASS
-10°C/3.8 V	0.004798	0.004935	0.004805	0.004828	±0.01	PASS
0°C/3.8 V	0.004832	0.004971	0.004863	0.004838	±0.01	PASS
15°C/3.8V	0.004871	0.004980	0.004917	0.004907	±0.01	PASS
20°C/3.8 V	0.004881	0.004992	0.004976	0.004928	±0.01	PASS
25°C/3.8 V	0.004942	0.005028	0.005000	0.004991	±0.01	PASS
30°C/3.8 V	0.005008	0.005051	0.005013	0.005054	±0.01	PASS
35°C/3.8 V	0.005069	0.005103	0.005030	0.005117	±0.01	PASS
40°C/3.8 V	0.005127	0.005160	0.005047	0.005124	±0.01	PASS
45°C/3.8 V	0.005193	0.005167	0.005077	0.005185	±0.01	PASS
50°C/3.8 V	0.005099	0.005159	0.005054	0.005150	±0.01	PASS
25°C/3.6 V	0.005127	0.005160	0.005047	0.005124	±0.01	PASS
25°C/4.35 V	0.005193	0.005167	0.005077	0.005185	±0.01	PASS



NFC-V

Test status	Frequency				Tolerance (MHz)			
	13.56MHz							
	1min	2min	5min	10min	1min	2min	5min	10min
-20°C/3.8 V	13.559338	13.559345	13.559342	13.559343	0.000662	0.000655	0.000658	0.000657
-10°C/3.8 V	13.559330	13.559345	13.559333	13.559343	0.000670	0.000655	0.000667	0.000657
0°C/3.8 V	13.559329	13.559343	13.559328	13.559339	0.000671	0.000657	0.000672	0.000661
15°C/3.8V	13.559320	13.559341	13.559326	13.559338	0.000680	0.000659	0.000674	0.000662
20°C/3.8 V	13.559317	13.559332	13.559316	13.559336	0.000683	0.000668	0.000684	0.000664
25°C/3.8 V	13.559308	13.559332	13.559312	13.559329	0.000692	0.000668	0.000688	0.000671
30°C/3.8 V	13.559303	13.559324	13.559310	13.559322	0.000697	0.000676	0.000690	0.000678
35°C/3.8 V	13.559296	13.559322	13.559305	13.559314	0.000704	0.000678	0.000695	0.000686
40°C/3.8 V	13.559289	13.559321	13.559297	13.559311	0.000711	0.000679	0.000703	0.000689
45°C/3.8 V	13.559287	13.559313	13.559288	13.559301	0.000713	0.000687	0.000712	0.000699
50°C/3.8 V	13.559279	13.559304	13.559281	13.559293	0.000721	0.000696	0.000719	0.000707
25°C/3.6 V	13.559295	13.559316	13.559302	13.559304	0.000705	0.000684	0.000698	0.000696
25°C/4.35 V	13.559286	13.559316	13.559298	13.559304	0.000714	0.000684	0.000702	0.000696

Test status	Tolerance (%)				Limit (%)	Conclusion
	1min	2min	5min	10min		
-20°C/3.8 V	0.004878	0.004828	0.004854	0.004843	±0.01	PASS
-10°C/3.8 V	0.004939	0.004833	0.004922	0.004848	±0.01	PASS
0°C/3.8 V	0.004952	0.004842	0.004958	0.004873	±0.01	PASS
15°C/3.8V	0.005014	0.004859	0.004973	0.004880	±0.01	PASS
20°C/3.8 V	0.005035	0.004923	0.005045	0.004897	±0.01	PASS
25°C/3.8 V	0.005106	0.004928	0.005073	0.004951	±0.01	PASS
30°C/3.8 V	0.005141	0.004988	0.005087	0.004998	±0.01	PASS
35°C/3.8 V	0.005190	0.005000	0.005124	0.005061	±0.01	PASS
40°C/3.8 V	0.005202	0.005041	0.005144	0.005131	±0.01	PASS
45°C/3.8 V	0.005265	0.005044	0.005175	0.005135	±0.01	PASS
50°C/3.8 V	0.005244	0.005009	0.005187	0.005081	±0.01	PASS
25°C/3.6 V	0.005202	0.005041	0.005144	0.005131	±0.01	PASS
25°C/4.35 V	0.005265	0.005044	0.005175	0.005135	±0.01	PASS

5.3. Radiates Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	102.5kPa

Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10-2013. The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna. The radiated emissions measurements were made in a typical installation configuration.

Sweep the whole frequency band through the range from 9 kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

During the test, below 30MHz, the center of the loop shall be 1 meters; above 30MHz, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing.

Set the spectrum analyzer in the following:

Out-of-band

Below 30MHz

RBW=9KHz, VBW=30KHz, detector=peak;

Above 30MHz,

RBW=100KHz, VBW=300KHz, Detector=peak

In-band


RBW=9KHz, VBW=30KHz, detector=peak;

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the loop antenna is vertical, the other antennas are vertical and horizontal.


The test is in transmitting mode NFC-A, NFC-B, NFC-F and NFC-V, choose worst mode NFC-A in report.

Test setup


9kHz~~~ 30MHz



30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Clause 15.225(a) the field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

Clause 15.225(b) within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

Clause 15.225(c) within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

Clause 15.225(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
0.009–0.490	2400/F(kHz)	128.519dBuV/m -93.8dBuV/m
0.490–1.705	24000/F(kHz)	73.8dBuV/m -62.969dBuV/m
1.705–30.0	30	69.5 dBuV/m
30-88	100	40 dBuV/m
88-216	150	43.5 dBuV/m
216-960	200	46 dBuV/m
Above960	500	54 dBuV/m

When using other measurement distance, according to the standard C63.10, If that point is closer to the EUT than $\lambda/2\pi$ and the limit distance is greater than $\lambda/2\pi$, the data was extrapolated to the specified measurement distance of 30m using extrapolation factor as specified in §6.4.4.2. Extrapolation Factor = $40\log(d \text{ near filed}/ d \text{ measure}) + 20\log(d \text{ limit} / d \text{ near filed})$

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

§15.209 (d) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.02 dB
200MHz-1GHz	3.28 dB
Above 1GHz	3.70 dB

Test result

NFC-A was selected as the worst condition. The test data of the worst-case condition was recorded in this report.

In-band




Radiates Emission from 13.11MHz to 14.01MHz


Note: This graph displays the maximum values of horizontal and vertical by software

Out-of-band


The following graphs display the maximum values of horizontal and vertical by software.
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.




Radiates Emission from 9kHz to 90kHz




Radiates Emission from 90kHz to 110kHz



Radiates Emission from 110kHz to 490kHz



Radiates Emission from 490kHz to 30MHz



Radiates Emission from 30MHz to 1GHz

Note: This graph displays the maximum values of horizontal and vertical by software

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
31.819203	28.8	101.0	V	200.0	-3.1	11.2	40.0
95.435366	31.9	101.0	V	80.0	-10.2	11.6	43.5
105.715850	27.6	175.0	H	245.0	-10.9	15.9	43.5
184.249425	34.0	100.0	H	190.0	-13.0	9.5	43.5
299.469750	26.1	100.0	H	222.0	-8.9	19.9	46.0
938.258250	41.7	206.0	V	22.0	1.9	4.3	46.0

5.4. Conducted Emission


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10-2013. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.
The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 110V/60Hz.

Limits

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency (MHz)	Conducted Limits(dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46




5 - 30	60	50
*: Decreases with the logarithm of the frequency.		

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 2.69$ dB.

Test Results:


Following plots, Blue trace uses the peak detection and Green trace uses the average detection.



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.34	---	26.41	49.17	22.76	1000.0	9.000	L1	ON	19.18
0.34	34.67	---	59.17	24.50	1000.0	9.000	L1	ON	19.18
0.65	---	34.82	46.00	11.18	1000.0	9.000	L1	ON	19.28
0.83	41.09	---	56.00	14.91	1000.0	9.000	L1	ON	19.24
0.91	---	34.77	46.00	11.23	1000.0	9.000	L1	ON	19.24
1.43	38.85	---	56.00	17.15	1000.0	9.000	L1	ON	19.18
2.22	37.42	---	56.00	18.58	1000.0	9.000	L1	ON	19.07
2.22	---	33.59	46.00	12.41	1000.0	9.000	L1	ON	19.07
5.35	30.30	---	60.00	29.70	1000.0	9.000	L1	ON	19.10
10.55	---	28.23	50.00	21.77	1000.0	9.000	L1	ON	19.37
13.55	30.24	---	60.00	29.76	1000.0	9.000	L1	ON	19.48
14.07	---	28.26	50.00	21.74	1000.0	9.000	L1	ON	19.48

Remark: Correct factor=cable loss + LISN factor

L line Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.34	39.92	---	59.23	19.31	1000.0	9.000	N	ON	19.18
0.34	---	33.95	49.12	15.17	1000.0	9.000	N	ON	19.18
0.65	---	39.45	46.00	6.55	1000.0	9.000	N	ON	19.28
0.84	47.90	---	56.00	8.10	1000.0	9.000	N	ON	19.24
0.91	---	39.20	46.00	6.80	1000.0	9.000	N	ON	19.24
0.91	43.39	---	56.00	12.61	1000.0	9.000	N	ON	19.24
2.22	---	37.35	46.00	8.65	1000.0	9.000	N	ON	19.07
3.00	42.39	---	56.00	13.61	1000.0	9.000	N	ON	19.11
5.34	37.18	---	60.00	22.82	1000.0	9.000	N	ON	19.10
5.34	---	29.71	50.00	20.29	1000.0	9.000	N	ON	19.10
12.77	31.05	---	60.00	28.95	1000.0	9.000	N	ON	19.46
14.85	---	27.29	50.00	22.71	1000.0	9.000	N	ON	19.48

Remark: Correct factor=cable loss + LISN factor

N line Conducted Emission from 150 KHz to 30 MHz



6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Time
Spectrum Analyzer	R&S	FSV30	100815	2018-12-16	2019-12-15
EMI Test Receiver	R&S	ESCI	100948	2019-05-19	2020-05-18
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-09-26	2019-09-25
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-201	2017-11-18	2019-11-17
EMI Test Receiver	R&S	ESR	101667	2019-05-19	2020-05-18
LISN	R&S	ENV216	101171	2016-12-16	2019-12-15
Spectrum Analyzer	Agilent	N9020A	MY52330084	2019-05-19	2020-05-18
TEMPERATURE CHAMBER	WEISS	VT4002	582261194500 10	2018-12-16	2019-12-15
RF Cable	Agilent	SMA 15cm	0001	2019-06-14	2019-09-13
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****