



FCC Maximum Permissible Exposure(MPE) Estimation Report

Product Name: LTE Module

Model: ME209u-526D

Report No.: SYBH(Z-SAR)016012015-2

FCC ID: QISME209U-526

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	<i>Wei Huanbin</i>	<i>Sun Shaobin</i>
DATE	2015-01-31	2015-01-31

The test results of this test report relate exclusively to the item(s) tested. The HUAWEI does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of HUAWEI.

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian,
Longgang District, Shenzhen, 518129, P.R.C
Tel: +86 755 28780808 Fax: +86 755 89652518



※ ※ Modified History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	2015-01-31	Sun Shaobin



Table of Contents

1	EUT Description	4
1.1	General Description	4
2	Test specification(s)	5
3	Testing laboratory	5
4	Applicant and Manufacturer	5
5	Application details	5
6	Ambient Condition	5
7	RF Exposure Requirements	6
8	RF Exposure Evaluation	9
8.1	Operation in LTE Band IV	9
8.2	Operation in LTE Band XIII	9



1 EUT Description

Device Information:			
DUT Name:	LTE Module		
Type Identification:	ME209u-526D		
Device Type :	Mobile device		
FCC ID:	QISME209U-526		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment/general population		
Hardware Version :	ML1ME209UM		
Software Version :	11.535.05.00.00		
Antenna Type :	External Antenna		
Device Operating Configurations:			
Supporting Mode(s)	LTE Band IV/XIII		
Test Modulation	QPSK/16QAM		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	LTE Band IV	1710-1755	2110-2155
	LTE Band XIII	777 -787	746 -756

1.1 General Description

ME209u-526D Wireless PCIe Module is subscriber equipment in the LTE system.

ME209u-526D implement such functions as RF signal receiving/transmitting, LTE protocol processing, data service etc.



2 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
KDB 447498 D01	General RF Exposure Guidance v05r02

3 Testing laboratory

Test Site	The Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	Zone K3,Huawei Industrial Base, Bantian Industry Area, Longgang District, Shenzhen, Guangdong, China
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01

4 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

5 Application details

Start Date of test	2015-01-31
End Date of test	2015-01-31

6 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

7 RF Exposure Requirements

An estimation of MPE in this application for product is used to ensure if it complies to the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC's MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

Table: Limits For Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/controlled Exposure				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm ²)	Averaging Time (minute) E ² , H ² or S
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/uncontrolled Exposure				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm ²)	Averaging Time (minute) E ² , H ² or S
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
f=frequency in MHz			*Plane-wave equivalent power density	

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator



R = distance to the centre of radiation of the antenna

$$EIRP = P \cdot G$$

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with $R=20\text{cm}$, and if it is below the limit S , then we can conclude the device complies with the rules.



8 RF Exposure Evaluation

8.1 Operation in LTE Band IV

(uplink: 1710-1755MHz, downlink: 2110-2155MHz)

Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
24.0	2.5	26.5	446.7	20	0.089	1.000	PASS

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.089mW/cm², which is below the uncontrolled exposure limit of 1.000mW/cm² at 1710MHz, so we can conclude it is into compliance.

8.2 Operation in LTE Band XIII

(uplink: 777 -787MHz, downlink: 746 -756MHz)

Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
24.0	2.5	26.5	446.7	20	0.089	0.518	PASS

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.089mW/cm², which is below the uncontrolled exposure limit of 0.518mW/cm² at 777MHz, so we can conclude it is into compliance.

-----END-----