

**Appendix B. SAR Measurement Plots**

Table of contents
GSM850 Head Second Antenna
GSM850 Body Second Antenna
GSM1900 Head Second Antenna
GSM1900 Body Second Antenna
UMTS Band II Head Second Antenna
UMTS Band II Body Second Antenna
UMTS Band IV Head Second Antenna
UMTS Band IV Body Second Antenna
UMTS Band V Head Second Antenna
UMTS Band V Body Second Antenna
LTE Band II Head Second Antenna
LTE Band II Body Second Antenna
LTE Band IV Head Second Antenna
LTE Band IV Body Second Antenna
LTE Band V Head Second Antenna
LTE Band V Body Second Antenna
LTE Band VII Head Second Antenna
LTE Band VII Body Second Antenna
LTE Band XII Head Second Antenna
LTE Band XII Body Second Antenna
LTE Band XVII Head Second Antenna
LTE Band XVII Body Second Antenna
LTE Band XXVI Head Second Antenna
LTE Band XXVI Body Second Antenna
LTE Band XXXVIII Head Second Antenna
LTE Band XXXVIII Body Second Antenna
LTE Band XLI Head Second Antenna
LTE Band XLI Body Second Antenna

GSM850 Head Main Antenna
GSM850 Body Main Antenna
GSM1900 Head Main Antenna
GSM1900 Body Main Antenna
UMTS Band II Head Main Antenna
UMTS Band II Body Main Antenna
UMTS Band IV Head Main Antenna
UMTS Band IV Body Main Antenna
UMTS Band V Head Main Antenna
UMTS Band V Body Main Antenna
LTE Band II Head Main Antenna
LTE Band II Body Main Antenna
LTE Band IV Head Main Antenna
LTE Band IV Body Main Antenna
LTE Band V Head Main Antenna
LTE Band V Body Main Antenna
LTE Band VII Head Main Antenna
LTE Band VII Body Main Antenna
LTE Band XII Head Main Antenna
LTE Band XII Body Main Antenna
LTE Band XVII Head Main Antenna
LTE Band XVII Body Main Antenna
LTE Band XXVI Head Main Antenna
LTE Band XXVI Body Main Antenna
LTE Band XXXVIII Head Main Antenna
LTE Band XXXVIII Body Main Antenna
LTE Band XLI Head Main Antenna
LTE Band XLI Body Main Antenna
WiFi 2.4G Head
WiFi 2.4G Body
WiFi 5G Head
WiFi 5G Body

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM850 190CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.917$ S/m; $\epsilon_r = 40.611$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.17, 9.17, 9.17); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 2.14 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 26.44 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 2.95 W/kg

SAR(1 g) = 1.22 W/kg; SAR(10 g) = 0.632 W/kg

Maximum value of SAR (measured) = 2.18 W/kg



0 dB = 2.18 W/kg = 3.38 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM850 190CH Back Side 15mm-Second Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.972$ S/m; $\epsilon_r = 54.519$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.231 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 8.665 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.273 W/kg

SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.097 W/kg

Maximum value of SAR (measured) = 0.234 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 8.665 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.170 W/kg

SAR(1 g) = 0.120 W/kg; SAR(10 g) = 0.082 W/kg

Maximum value of SAR (measured) = 0.150 W/kg



0 dB = 0.150 W/kg = -8.24 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM850 GPRS 3TS 190CH Back Side 10mm-Second Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-3TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:2.77013

Medium parameters used: $f = 837$ MHz; $\sigma = 0.972$ S/m; $\epsilon_r = 54.519$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.733 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 11.99 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.925 W/kg

SAR(1 g) = 0.518 W/kg; SAR(10 g) = 0.291 W/kg

Maximum value of SAR (measured) = 0.764 W/kg



0 dB = 0.764 W/kg = -1.17 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM1900 512CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.374$ S/m; $\epsilon_r = 39.016$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.45, 7.45, 7.45); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.27 W/kg

Configuration/Head/Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 18.98 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 2.18 W/kg

SAR(1 g) = 1.19 W/kg; SAR(10 g) = 0.675 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.43 W/kg



0 dB = 1.43 W/kg = 1.54 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM1900 661CH Front Side 15mm-Second Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.511$ S/m; $\epsilon_r = 52.543$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.205 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 5.896 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.245 W/kg

SAR(1 g) = 0.160 W/kg; SAR(10 g) = 0.104 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.216 W/kg



0 dB = 0.216 W/kg = -6.66 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM1900 GPRS 2TS 661CH Top Side 10mm-Second Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM\GPRS\EGPRS-2TS (0); Frequency: 1880 MHz; Duty Cycle: 1:4.10015

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.642 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 18.69 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.836 W/kg

SAR(1 g) = 0.445 W/kg; SAR(10 g) = 0.229 W/kg

Maximum value of SAR (measured) = 0.681 W/kg



0 dB = 0.681 W/kg = -1.67 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band II 9538CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.44$ S/m; $\epsilon_r = 38.788$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.45, 7.45, 7.45); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.25 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 18.65 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.10 W/kg

SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.627 W/kg

Maximum value of SAR (measured) = 1.38 W/kg



0 dB = 1.38 W/kg = 1.40 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band II 9400CH Back Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.197 W/kg

Configuration/Body/Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.383 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.255 W/kg

SAR(1 g) = 0.143 W/kg; SAR(10 g) = 0.078 W/kg

Maximum value of SAR (measured) = 0.206 W/kg


Configuration/Body/Zoom Scan (6x5x7)/Cube 1: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.383 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.213 W/kg

SAR(1 g) = 0.134 W/kg; SAR(10 g) = 0.087 W/kg

Maximum value of SAR (measured) = 0.184 W/kg



0 dB = 0.184 W/kg = -7.35 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band II 9400CH Top Side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ⌄ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ⌄ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ⌄ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ⌄ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ⌄ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.674 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 15.09 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.844 W/kg

SAR(1 g) = 0.440 W/kg; SAR(10 g) = 0.223 W/kg

Maximum value of SAR (measured) = 0.700 W/kg



0 dB = 0.700 W/kg = -1.55 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band IV 1513CH Right touch-Second Antenna-Repeated

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.359$ S/m; $\epsilon_r = 40.508$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(8.09, 8.09, 8.09); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.95 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 23.66 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 3.22 W/kg

SAR(1 g) = 1.27 W/kg; SAR(10 g) = 0.698 W/kg

Maximum value of SAR (measured) = 2.29 W/kg



0 dB = 2.29 W/kg = 3.59 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band IV 1413CH Front side 15mm-Second Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.416$ S/m; $\epsilon_r = 51.786$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x15x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.139 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.679 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.173 W/kg

SAR(1 g) = 0.101 W/kg; SAR(10 g) = 0.058 W/kg

Maximum value of SAR (measured) = 0.149 W/kg



0 dB = 0.149 W/kg = -8.27 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band IV 1413CH Top side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.416$ S/m; $\epsilon_r = 51.786$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.337 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 14.77 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.547 W/kg

SAR(1 g) = 0.299 W/kg; SAR(10 g) = 0.158 W/kg

Maximum value of SAR (measured) = 0.451 W/kg



0 dB = 0.451 W/kg = -3.46 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band V 4132CH Right touch-Second Antenna-Repeated

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 40.689$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ⌘ Probe: EX3DV4 - SN3736; ConvF(9.17, 9.17, 9.17); Calibrated: 2016-4-26;
- ⌘ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ⌘ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ⌘ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ⌘ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.61 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 30.28 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.52 W/kg

SAR(1 g) = 0.977 W/kg; SAR(10 g) = 0.496 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.83 W/kg



0 dB = 1.83 W/kg = 2.62 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band V 4182CH Back Side 15mm-Second Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 54.326$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.171 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.63 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.208 W/kg

SAR(1 g) = 0.125 W/kg; SAR(10 g) = 0.074 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.177 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.63 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.181 W/kg

SAR(1 g) = 0.131 W/kg; SAR(10 g) = 0.094 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.164 W/kg



0 dB = 0.164 W/kg = -7.85 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band V 4182CH Back Side 10mm with Battery 2-Second Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.971$ S/m; $\epsilon_r = 54.526$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.448 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.34 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.551 W/kg

SAR(1 g) = 0.305 W/kg; SAR(10 g) = 0.169 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.458 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.34 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.534 W/kg

SAR(1 g) = 0.254 W/kg; SAR(10 g) = 0.142 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.437 W/kg



0 dB = 0.437 W/kg = -3.59 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band II 20M QPSK 1RB 50 offset 18900CH Right touch-Second Antenna-Repeated

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.408$ S/m; $\epsilon_r = 38.863$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(7.45, 7.45, 7.45); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.35 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 20.07 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.27 W/kg

SAR(1 g) = 1.21 W/kg; SAR(10 g) = 0.667 W/kg

Maximum value of SAR (measured) = 1.41 W/kg



0 dB = 1.41 W/kg = 1.49 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band II 20M QPSK 1RB 50 offset 18900CH Front Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.524$ S/m; $\epsilon_r = 51.429$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.147 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.090 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.169 W/kg

SAR(1 g) = 0.111 W/kg; SAR(10 g) = 0.072 W/kg



0 dB = 0.147 W/kg = -8.33 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band II 20M QPSK 1RB 50 offset 18900CH Top Side 10mm -Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.524$ S/m; $\epsilon_r = 51.429$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.462 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.19 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.563 W/kg

SAR(1 g) = 0.308 W/kg; SAR(10 g) = 0.159 W/kg

Maximum value of SAR (measured) = 0.473 W/kg



0 dB = 0.473 W/kg = -3.25 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band IV 20M QPSK 1RB 50 offset 20300CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.352$ S/m; $\epsilon_r = 40.556$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(8.09, 8.09, 8.09); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.55 W/kg


Configuration/Head/Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 20.43 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 3.15 W/kg

SAR(1 g) = 1.32 W/kg; SAR(10 g) = 0.741 W/kg

Maximum value of SAR (measured) = 2.28 W/kg



0 dB = 2.28 W/kg = 3.58 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band IV 20M QPSK 1RB 50 offset 20300CH Front side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.428$ S/m; $\epsilon_r = 51.728$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;
- ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ε Phantom: SAM3; Type: SAM; Serial: TP-1597
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.138 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.223 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.193 W/kg

SAR(1 g) = 0.114 W/kg; SAR(10 g) = 0.065 W/kg

Maximum value of SAR (measured) = 0.164 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.223 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.130 W/kg

SAR(1 g) = 0.085 W/kg; SAR(10 g) = 0.055 W/kg

Maximum value of SAR (measured) = 0.113 W/kg



0 dB = 0.113 W/kg = -9.49 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band IV 20M QPSK 1RB 50 offset 20300CH Top side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.428$ S/m; $\epsilon_r = 51.728$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.473 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.36 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.608 W/kg

SAR(1 g) = 0.331 W/kg; SAR(10 g) = 0.175 W/kg

Maximum value of SAR (measured) = 0.508 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29LTE Band V 10M QPSK 1RB 25 offset 20600CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.049$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(9.17, 9.17, 9.17); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.94 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 23.83 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 2.87 W/kg

SAR(1 g) = 1.19 W/kg; SAR(10 g) = 0.624 W/kg

Maximum value of SAR (measured) = 2.16 W/kg



0 dB = 2.16 W/kg = 3.34 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band V 10M QPSK 1RB 25 offset 20600CH Back Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 1.003$ S/m; $\epsilon_r = 54.23$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.236 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.86 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.364 W/kg

SAR(1 g) = 0.224 W/kg; SAR(10 g) = 0.132 W/kg

Maximum value of SAR (measured) = 0.270 W/kg



0 dB = 0.270 W/kg = -5.69 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band V 10M QPSK 1RB 25 offset 20600CH Top Side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 1.003$ S/m; $\epsilon_r = 54.23$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.658 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 23.54 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.877 W/kg

SAR(1 g) = 0.443 W/kg; SAR(10 g) = 0.215 W/kg

Maximum value of SAR (measured) = 0.699 W/kg



0 dB = 0.699 W/kg = -1.56 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band VII QPSK 20M 1RB 99 offset 21350CH Right tilt-Second Antenna-Repeated

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.972$ S/m; $\epsilon_r = 37.796$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.48, 4.48, 4.48); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM1; Type: SAM; Serial: TP-1475

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.46 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.904 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 3.21 W/kg

SAR(1 g) = 1.2 W/kg; SAR(10 g) = 0.495 W/kg

Maximum value of SAR (measured) = 1.71 W/kg



0 dB = 1.46 W/kg = 1.64 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band VII QPSK 20M 50RB 0 offset 21350CH Right tilt-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.972$ S/m; $\epsilon_r = 37.796$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.48, 4.48, 4.48); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM1; Type: SAM; Serial: TP-1475

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.32 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.149 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 2.92 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.445 W/kg

Maximum value of SAR (measured) = 1.47 W/kg



0 dB = 1.32 W/kg = 1.21 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band VII QPSK 20M 1RB 50 offset 21100CH Front Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 2.042$ S/m; $\epsilon_r = 51.708$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.0666 W/kg


Configuration/Body/Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.013 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.106 W/kg

SAR(1 g) = 0.056 W/kg; SAR(10 g) = 0.032 W/kg

Maximum value of SAR (measured) = 0.0696 W/kg



0 dB = 0.0666 W/kg = -11.77 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band VII QPSK 20M 1RB 50 offset 21100CH Left Side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 2.042$ S/m; $\epsilon_r = 51.708$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (7x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.172 W/kg


Configuration/Body/Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.504 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.283 W/kg

SAR(1 g) = 0.143 W/kg; SAR(10 g) = 0.072 W/kg

Maximum value of SAR (measured) = 0.182 W/kg



0 dB = 0.172 W/kg = -7.64 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XII 10M QPSK 1RB 25 offset 23060CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 704 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 704$ MHz; $\sigma = 0.847$ S/m; $\epsilon_r = 43.716$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.7, 9.7, 9.7); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.95 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 23.95 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 2.51 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.518 W/kg

Maximum value of SAR (measured) = 1.69 W/kg



0 dB = 1.69 W/kg = 2.28 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XII 10M QPSK 25RB 25 offset 23130CH Back Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 54.145$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.135 W/kg


Configuration/Body/Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.024 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.161 W/kg

SAR(1 g) = 0.097 W/kg; SAR(10 g) = 0.058 W/kg

Maximum value of SAR (measured) = 0.137 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XII 10M QPSK 25RB 25 offset 23130CH Back Side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 54.145$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.276 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.387 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.418 W/kg

SAR(1 g) = 0.226 W/kg; SAR(10 g) = 0.126 W/kg

Maximum value of SAR (measured) = 0.319 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XVII 10M QPSK 1RB 25 offset 23800CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.854$ S/m; $\epsilon_r = 43.624$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.7, 9.7, 9.7); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.37 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 17.67 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.81 W/kg

SAR(1 g) = 0.761 W/kg; SAR(10 g) = 0.380 W/kg

Maximum value of SAR (measured) = 1.34 W/kg



0 dB = 1.34 W/kg = 1.27 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XVII 10M QPSK 1RB 25 offset 23790CH Back side 15mm with Battery 2-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710$ MHz; $\sigma = 0.933$ S/m; $\epsilon_r = 54.152$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;
- ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ε Phantom: SAM3; Type: SAM; Serial: TP-1597
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.139 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.299 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.165 W/kg

SAR(1 g) = 0.098 W/kg; SAR(10 g) = 0.059 W/kg



0 dB = 0.139 W/kg = -8.57 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XVII 10M QPSK 1RB 25 offset 23790CH Front side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 710 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 710$ MHz; $\sigma = 0.933$ S/m; $\epsilon_r = 54.152$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.284 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.033 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.367 W/kg

SAR(1 g) = 0.203 W/kg; SAR(10 g) = 0.114 W/kg

Maximum value of SAR (measured) = 0.298 W/kg



0 dB = 0.298 W/kg = -5.26 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXVI 15M QPSK 1RB 38 offset 26965CH Right touch with Battery 2-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 15MHz, QPSK/16-QAM) (0); Frequency: 841.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 841.5$ MHz; $\sigma = 0.921$ S/m; $\epsilon_r = 42.062$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(9.17, 9.17, 9.17); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 2.05 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 23.04 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.72 W/kg

SAR(1 g) = 1.17 W/kg; SAR(10 g) = 0.612 W/kg

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 2.02 W/kg



0 dB = 2.02 W/kg = 3.05 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXVI 15M QPSK 1RB 38 offset 26965CH Back Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 15MHz, QPSK/16-QAM) (0); Frequency: 841.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 841.5$ MHz; $\sigma = 1$ S/m; $\epsilon_r = 54.261$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ε Phantom: SAM3; Type: SAM; Serial: TP-1597
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.226 W/kg

Configuration/Body/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.92 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.253 W/kg

SAR(1 g) = 0.189 W/kg; SAR(10 g) = 0.137 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.231 W/kg

Configuration/Body/Zoom Scan (6x6x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 12.92 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.258 W/kg

SAR(1 g) = 0.158 W/kg; SAR(10 g) = 0.095 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.221 W/kg



0 dB = 0.221 W/kg = -6.57 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXVI 15M QPSK 1RB 38 offset 26965CH Back Side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 15MHz, QPSK/16-QAM) (0); Frequency: 841.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 841.5$ MHz; $\sigma = 1$ S/m; $\epsilon_r = 54.261$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ε Phantom: SAM3; Type: SAM; Serial: TP-1597
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.524 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 13.02 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.690 W/kg

SAR(1 g) = 0.393 W/kg; SAR(10 g) = 0.221 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.569 W/kg



0 dB = 0.569 W/kg = -2.45 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXXVIII QPSK 20M 1RB 50 offset 38150CH Right touch-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2610 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2610$ MHz; $\sigma = 2.029$ S/m; $\epsilon_r = 37.605$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.48, 4.48, 4.48); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM1; Type: SAM; Serial: TP-1475

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.43 W/kg


Configuration/Head/Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.313 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 2.96 W/kg

SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.527 W/kg

Maximum value of SAR (measured) = 1.56 W/kg



0 dB = 1.43 W/kg = 1.55 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXXVIII QPSK 20M 1RB 99 offset 38000CH Front Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2595 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2595$ MHz; $\sigma = 2.113$ S/m; $\epsilon_r = 51.515$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm



Maximum value of SAR (measured) = 0.119 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.500 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.097 W/kg; SAR(10 g) = 0.054 W/kg



0 dB = 0.119 W/kg = -9.24 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXXVIII QPSK 20M 1RB 99 offset 38000CH Left Side 10mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2595 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2595$ MHz; $\sigma = 2.113$ S/m; $\epsilon_r = 51.515$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

Electronics: DAE4 Sn852; Calibrated: 2016-4-20

Phantom: SAM2; Type: SAM; Serial: TP:1474

DASY52 52.8.8(1222);

Configuration/Body/Area Scan (6x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.260 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.078 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.425 W/kg

SAR(1 g) = 0.214 W/kg; SAR(10 g) = 0.108 W/kg

Maximum value of SAR (measured) = 0.271 W/kg



0 dB = 0.260 W/kg = -5.85 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XLI QPSK 20M 1RB 99 offset 41140CH Right touch-Second Antenna-repeated

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2645 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2645$ MHz; $\sigma = 2.069$ S/m; $\epsilon_r = 37.495$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.48, 4.48, 4.48); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM1; Type: SAM; Serial: TP-1475

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.03 W/kg



Configuration/Head/Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.776 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 2.64 W/kg

SAR(1 g) = 0.989 W/kg; SAR(10 g) = 0.450 W/kg

Maximum value of SAR (measured) = 1.35 W/kg



0 dB = 1.03 W/kg = 0.13 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XLI QPSK 20M 1RB 50 offset 40340CH Front Side 15mm-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2565 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2565$ MHz; $\sigma = 2.076$ S/m; $\epsilon_r = 51.617$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

Electronics: DAE4 Sn852; Calibrated: 2016-4-20

Phantom: SAM2; Type: SAM; Serial: TP:1474

DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.0425 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.442 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.0660 W/kg

SAR(1 g) = 0.035 W/kg; SAR(10 g) = 0.019 W/kg

Maximum value of SAR (measured) = 0.0439 W/kg



0 dB = 0.0425 W/kg = -13.72 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XLI QPSK 20M 1RB 50 offset 40340CH Left Side 10mm with Battery 3-Second Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2565 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2565$ MHz; $\sigma = 2.076$ S/m; $\epsilon_r = 51.617$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

Electronics: DAE4 Sn852; Calibrated: 2016-4-20

Phantom: SAM2; Type: SAM; Serial: TP:1474

DASY52 52.8.8(1222);

Configuration/Body/Area Scan (6x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.133 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.942 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.229 W/kg

SAR(1 g) = 0.118 W/kg; SAR(10 g) = 0.060 W/kg

Maximum value of SAR (measured) = 0.150 W/kg



0 dB = 0.133 W/kg = -8.76 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM850 251CH Right touch with Battery 2-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 849$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 40.602$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.17, 9.17, 9.17); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.423 W/kg



Configuration/Head/Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 8.858 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.466 W/kg

SAR(1 g) = 0.352 W/kg; SAR(10 g) = 0.267 W/kg

Maximum value of SAR (measured) = 0.422 W/kg



0 dB = 0.422 W/kg = -3.75 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM850 190CH Back Side 15mm-Main Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.972$ S/m; $\epsilon_r = 54.519$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.431 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 21.90 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.470 W/kg

SAR(1 g) = 0.360 W/kg; SAR(10 g) = 0.274 W/kg

Maximum value of SAR (measured) = 0.433 W/kg



0 dB = 0.433 W/kg = -3.64 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM850 GPRS 2TS 190CH Right Side 10mm-Main Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-2TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:4.10015

Medium parameters used: $f = 837$ MHz; $\sigma = 0.972$ S/m; $\epsilon_r = 54.519$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.812 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 30.23 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.940 W/kg

SAR(1 g) = 0.624 W/kg; SAR(10 g) = 0.420 W/kg

Maximum value of SAR (measured) = 0.831 W/kg



0 dB = 0.831 W/kg = -0.80 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM1900 512CH Right touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.374$ S/m; $\epsilon_r = 39.861$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: ES3DV3 - SN3168; ConvF(5.13, 5.13, 5.13); Calibrated: 2015-9-28;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.276 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 4.992 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.399 W/kg

SAR(1 g) = 0.264 W/kg; SAR(10 g) = 0.166 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.309 W/kg



0 dB = 0.309 W/kg = -5.10 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM1900 661CH Back Side 15mm-Main Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM/GPRS/EGPRS-1TS (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.369 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.961 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.475 W/kg

SAR(1 g) = 0.275 W/kg; SAR(10 g) = 0.153 W/kg

Maximum value of SAR (measured) = 0.407 W/kg



0 dB = 0.407 W/kg = -3.91 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM1900 GPRS 2TS 661CH Bottom Side 10mm-Main Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM\GPRS\EGPRS-2TS (0); Frequency: 1880 MHz; Duty Cycle: 1:4.10015

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.52 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 31.76 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.04 W/kg

SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.587 W/kg

Maximum value of SAR (measured) = 1.69 W/kg



0 dB = 1.69 W/kg = 2.28 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 GSM1900 GPRS 2TS 661CH Bottom Side 0mm-Main Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-GSM\GPRS\EGPRS-2TS (0); Frequency: 1880 MHz; Duty Cycle: 1:4.10015

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.09 W/kg



Configuration/Body/Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 16.55 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.68 W/kg

SAR(1 g) = 0.491 W/kg; SAR(10 g) = 0.207 W/kg

Maximum value of SAR (measured) = 1.36 W/kg



0 dB = 1.36 W/kg = 1.34 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band II 9262CH Right touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.351$ S/m; $\epsilon_r = 39.969$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ⌄ Probe: EX3DV4 - SN3744; ConvF(7.74, 7.74, 7.74); Calibrated: 2016-7-26;
- ⌄ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ⌄ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ⌄ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ⌄ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.741 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 7.202 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.963 W/kg

SAR(1 g) = 0.622 W/kg; SAR(10 g) = 0.385 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.843 W/kg



0 dB = 0.843 W/kg = -0.74 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band II 9400CH Back Side 15mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.543$ S/m; $\epsilon_r = 52.917$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.567 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.559 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.812 W/kg

SAR(1 g) = 0.475 W/kg; SAR(10 g) = 0.266 W/kg

Maximum value of SAR (measured) = 0.675 W/kg



0 dB = 0.675 W/kg = -1.71 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band II 9538CH Bottom Side 10mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.567$ S/m; $\epsilon_r = 52.842$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.52 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 27.17 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 2.02 W/kg

SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.603 W/kg

Maximum value of SAR (measured) = 1.71 W/kg



0 dB = 1.71 W/kg = 2.33 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band II 9538CH Back Side 0mm-Main Antenna-Repeated

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.567$ S/m; $\epsilon_r = 52.842$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 6.91 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.205 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 12.0 W/kg

SAR(1 g) = 5.01 W/kg; SAR(10 g) = 2.11 W/kg

Maximum value of SAR (measured) = 8.79 W/kg



0 dB = 8.79 W/kg = 9.44 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band IV 1513CH Right tiouch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1752.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.342$ S/m; $\epsilon_r = 38.931$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(8.09, 8.09, 8.09); Calibrated: 2016-7-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.691 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.804 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.966 W/kg

SAR(1 g) = 0.656 W/kg; SAR(10 g) = 0.423 W/kg

Maximum value of SAR (measured) = 0.756 W/kg



0 dB = 0.756 W/kg = -1.21 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band IV 1413CH Front side 15mm-Main Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.416$ S/m; $\epsilon_r = 51.786$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.423 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 10.29 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.493 W/kg

SAR(1 g) = 0.333 W/kg; SAR(10 g) = 0.228 W/kg

Maximum value of SAR (measured) = 0.436 W/kg



0 dB = 0.436 W/kg = -3.61 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band IV 1413CH Back side 10mm-Main Antenna**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.416$ S/m; $\epsilon_r = 51.786$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.772 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 11.03 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.604 W/kg; SAR(10 g) = 0.370 W/kg

Maximum value of SAR (measured) = 0.825 W/kg



0 dB = 0.825 W/kg = -0.84 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band V 4233CH Right touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.925$ S/m; $\epsilon_r = 40.385$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ⌄ Probe: EX3DV4 - SN3744; ConvF(8.86, 8.86, 8.86); Calibrated: 2016-7-26;
- ⌄ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ⌄ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ⌄ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ⌄ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.448 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 9.211 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.503 W/kg

SAR(1 g) = 0.374 W/kg; SAR(10 g) = 0.281 W/kg

Maximum value of SAR (measured) = 0.458 W/kg



0 dB = 0.458 W/kg = -3.39 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band V 4182CH Back Side 15mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 54.326$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.406 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 20.86 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.454 W/kg

SAR(1 g) = 0.344 W/kg; SAR(10 g) = 0.262 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.417 W/kg



0 dB = 0.417 W/kg = -3.80 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 UMTS Band V 4182CH Right Side 10mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 54.326$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x14x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.760 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 28.81 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.893 W/kg

SAR(1 g) = 0.586 W/kg; SAR(10 g) = 0.391 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.788 W/kg



0 dB = 0.788 W/kg = -1.03 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band II 20M QPSK 1RB 50 offset 18700CH Right touch with Battery 2-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1860$ MHz; $\sigma = 1.382$ S/m; $\epsilon_r = 39.815$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(5.13, 5.13, 5.13); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.508 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 8.029 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.742 W/kg

SAR(1 g) = 0.494 W/kg; SAR(10 g) = 0.312 W/kg

Maximum value of SAR (measured) = 0.577 W/kg



0 dB = 0.577 W/kg = -2.39 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band II 20M QPSK 1RB 50 offset 18900CH Back Side 15mm with Battery 2-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.524$ S/m; $\epsilon_r = 51.429$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ⌘ Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;
- ⌘ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ⌘ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ⌘ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ⌘ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.737 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.387 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.886 W/kg

SAR(1 g) = 0.525 W/kg; SAR(10 g) = 0.295 W/kg

Maximum value of SAR (measured) = 0.754 W/kg



0 dB = 0.754 W/kg = -1.23 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band II 20M QPSK 1 RB 50 offset 18700CH Bottom Side 10mm -Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1860$ MHz; $\sigma = 1.505$ S/m; $\epsilon_r = 51.539$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.51 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.99 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.563 W/kg

Maximum value of SAR (measured) = 1.62 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band II 20M QPSK 1RB 50 offset 18900CH Bottom Side 0mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.524$ S/m; $\epsilon_r = 51.429$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(7.15, 7.15, 7.15); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.62 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.87 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 2.06 W/kg

SAR(1 g) = 0.670 W/kg; SAR(10 g) = 0.293 W/kg

Maximum value of SAR (measured) = 1.72 W/kg



0 dB = 1.72 W/kg = 2.34 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band IV 20M QPSK 1RB 50 offset 20300CH Right touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.352$ S/m; $\epsilon_r = 40.556$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(8.09, 8.09, 8.09); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (8x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.679 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.743 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.844 W/kg

SAR(1 g) = 0.569 W/kg; SAR(10 g) = 0.369 W/kg

Maximum value of SAR (measured) = 0.746 W/kg



0 dB = 0.746 W/kg = -1.27 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band IV 20M QPSK 1RB 50 offset 20300CH Front side 15mm with Battery 3-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.428$ S/m; $\epsilon_r = 51.728$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.365 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.57 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.416 W/kg

SAR(1 g) = 0.281 W/kg; SAR(10 g) = 0.191 W/kg

Maximum value of SAR (measured) = 0.367 W/kg



0 dB = 0.367 W/kg = -4.35 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band IV 20M QPSK 1RB 50 offset 20300CH Back side 10mm with Battery 3-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.428$ S/m; $\epsilon_r = 51.728$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(7.61, 7.61, 7.61); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.685 W/kg


Configuration/Body/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.14 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.583 W/kg; SAR(10 g) = 0.345 W/kg

Maximum value of SAR (measured) = 0.849 W/kg



0 dB = 0.849 W/kg = -0.71 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29LTE Band V 10M QPSK 1RB 25 offset 20600CH Right touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 0.922$ S/m; $\epsilon_r = 40.557$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(9.17, 9.17, 9.17); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.378 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.919 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.434 W/kg

SAR(1 g) = 0.320 W/kg; SAR(10 g) = 0.242 W/kg

Maximum value of SAR (measured) = 0.386 W/kg



0 dB = 0.386 W/kg = -4.13 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band V 10M QPSK 1RB 25 offset 20600CH Back Side 15mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 0.98$ S/m; $\epsilon_r = 54.431$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ε Phantom: SAM3; Type: SAM; Serial: TP-1597
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.353 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.74 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.387 W/kg

SAR(1 g) = 0.293 W/kg; SAR(10 g) = 0.222 W/kg

Maximum value of SAR (measured) = 0.356 W/kg



0 dB = 0.356 W/kg = -4.49 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band V 10M QPSK 1RB 25 offset 20600CH Right Side 10mm- Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 0.98$ S/m; $\epsilon_r = 54.431$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.602 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 19.53 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.697 W/kg

SAR(1 g) = 0.467 W/kg; SAR(10 g) = 0.314 W/kg

Maximum value of SAR (measured) = 0.619 W/kg



0 dB = 0.619 W/kg = -2.08 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band VII QPSK 20M 1RB 50 offset 21100CH Left touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 1.937$ S/m; $\epsilon_r = 37.927$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.48, 4.48, 4.48); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM1; Type: SAM; Serial: TP-1475

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.377 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.333 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.540 W/kg

SAR(1 g) = 0.320 W/kg; SAR(10 g) = 0.175 W/kg

Maximum value of SAR (measured) = 0.394 W/kg



0 dB = 0.377 W/kg = -4.24 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band VII QPSK 20M 1RB 50 offset 21100CH Back Side 15mm- Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 2.042$ S/m; $\epsilon_r = 51.708$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.341 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.327 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.542 W/kg

SAR(1 g) = 0.263 W/kg; SAR(10 g) = 0.123 W/kg

Maximum value of SAR (measured) = 0.338 W/kg



Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.327 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.485 W/kg

SAR(1 g) = 0.238 W/kg; SAR(10 g) = 0.111 W/kg

Maximum value of SAR (measured) = 0.308 W/kg



0 dB = 0.341 W/kg = -4.67 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band VII QPSK 20M 1RB 50 offset 21100CH Bottom Side 10mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-FDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 2.042$ S/m; $\epsilon_r = 51.708$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (6x11x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.957 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 14.70 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 0.734 W/kg; SAR(10 g) = 0.285 W/kg

Maximum value of SAR (measured) = 1.03 W/kg



0 dB = 0.957 W/kg = -0.19 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XII 10M QPSK 1RB 25 offset 23060CH Right touch with Battery 2-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 704 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 704$ MHz; $\sigma = 0.847$ S/m; $\epsilon_r = 43.716$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.7, 9.7, 9.7); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.202 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.298 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.214 W/kg

SAR(1 g) = 0.176 W/kg; SAR(10 g) = 0.139 W/kg

Maximum value of SAR (measured) = 0.201 W/kg



0 dB = 0.201 W/kg = -6.97 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XII 10M QPSK 25RB 13 offset 23130CH Back side 15mm- Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 54.145$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.205 W/kg


Configuration/Body/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.88 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.227 W/kg

SAR(1 g) = 0.170 W/kg; SAR(10 g) = 0.131 W/kg

Maximum value of SAR (measured) = 0.206 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XII 10M QPSK 25RB 13 offset 23130CH Right side 10mm- Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 54.145$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (5x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.267 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.10 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.306 W/kg

SAR(1 g) = 0.207 W/kg; SAR(10 g) = 0.143 W/kg

Maximum value of SAR (measured) = 0.271 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XVII 10M QPSK 1RB 25 offset 23800CH Right touch with Battery 2-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.854$ S/m; $\epsilon_r = 43.624$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.7, 9.7, 9.7); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM4; Type: SAM; Serial: TP-1620

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.241 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.190 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.260 W/kg

SAR(1 g) = 0.207 W/kg; SAR(10 g) = 0.162 W/kg

Maximum value of SAR (measured) = 0.239 W/kg



0 dB = 0.239 W/kg = -6.22 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XVII 10M QPSK 1RB 25 offset 23800CH Back side 15mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 54.145$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.324 W/kg


Configuration/Body/Zoom Scan (6x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.72 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.358 W/kg

SAR(1 g) = 0.272 W/kg; SAR(10 g) = 0.213 W/kg

Maximum value of SAR (measured) = 0.326 W/kg



0 dB = 0.326 W/kg = -4.87 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XVII 10M QPSK 1RB 25 offset 23800CH Back side 10mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 10MHz, QPSK/16-QAM) (0); Frequency: 711 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 711$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 54.145$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: EX3DV4 - SN3744; ConvF(9.03, 9.03, 9.03); Calibrated: 2016-7-26;

ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

ε Phantom: SAM3; Type: SAM; Serial: TP-1597

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.461 W/kg


Configuration/Body/Zoom Scan (6x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.33 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.620 W/kg

SAR(1 g) = 0.349 W/kg; SAR(10 g) = 0.203 W/kg

Maximum value of SAR (measured) = 0.506 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXVI 15M QPSK 1RB 38 offset 26865CH Right touch with Battery 3-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 15MHz, QPSK/16-QAM) (0); Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 831.5$ MHz; $\sigma = 0.909$ S/m; $\epsilon_r = 40.726$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3736; ConvF(9.17, 9.17, 9.17); Calibrated: 2016-4-26;

- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$

- Electronics: DAE4 Sn1236; Calibrated: 2015-11-23

- Phantom: SAM4; Type: SAM; Serial: TP-1620

- DASY52 52.8.8(1222);

Configuration/Head/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.353 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 8.058 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.394 W/kg

SAR(1 g) = 0.296 W/kg; SAR(10 g) = 0.224 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.360 W/kg



0 dB = 0.360 W/kg = -4.44 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXVI 15M QPSK 1RB 38 offset 26965CH Back Side 15mm with Battery 2-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 15MHz, QPSK/16-QAM) (0); Frequency: 841.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 841.5$ MHz; $\sigma = 1$ S/m; $\epsilon_r = 54.261$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ε Phantom: SAM3; Type: SAM; Serial: TP-1597
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.229 W/kg

Configuration/Body/Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 13.52 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.248 W/kg

SAR(1 g) = 0.188 W/kg; SAR(10 g) = 0.143 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.227 W/kg



0 dB = 0.227 W/kg = -6.44 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXVI 15M QPSK 1RB 38 offset 26965CH Back Side 10mm- Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR2

Communication System: UID 0, LTE-FDD (SC-FDMA, 15MHz, QPSK/16-QAM) (0); Frequency: 841.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 841.5$ MHz; $\sigma = 1$ S/m; $\epsilon_r = 54.261$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: EX3DV4 - SN3736; ConvF(9.08, 9.08, 9.08); Calibrated: 2016-4-26;
- ε Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- ε Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ε Phantom: SAM3; Type: SAM; Serial: TP-1597
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.246 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.98 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.270 W/kg

SAR(1 g) = 0.205 W/kg; SAR(10 g) = 0.154 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.248 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm



Reference Value = 13.98 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.262 W/kg

SAR(1 g) = 0.158 W/kg; SAR(10 g) = 0.099 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.217 W/kg



0 dB = 0.217 W/kg = -6.64 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXXVIII QPSK 20M 1RB 50 offset 38000CH Left touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2595 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2595$ MHz; $\sigma = 2.013$ S/m; $\epsilon_r = 37.654$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.48, 4.48, 4.48); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM1; Type: SAM; Serial: TP-1475

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.166 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.992 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.238 W/kg

SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.071 W/kg

Maximum value of SAR (measured) = 0.167 W/kg



0 dB = 0.166 W/kg = -7.80 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXXVIII QPSK 20M 1RB 99 offset 38150CH Back Side 15mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2610 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2610$ MHz; $\sigma = 2.134$ S/m; $\epsilon_r = 51.471$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.163 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.290 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.274 W/kg

SAR(1 g) = 0.130 W/kg; SAR(10 g) = 0.059 W/kg

Maximum value of SAR (measured) = 0.171 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.290 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.229 W/kg

SAR(1 g) = 0.110 W/kg; SAR(10 g) = 0.051 W/kg

Maximum value of SAR (measured) = 0.142 W/kg



0 dB = 0.163 W/kg = -7.88 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XXXVIII QPSK 20M 1RB 99 offset 38150CH Front Side 10mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2610 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2610$ MHz; $\sigma = 2.134$ S/m; $\epsilon_r = 51.471$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.470 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.329 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.835 W/kg

SAR(1 g) = 0.353 W/kg; SAR(10 g) = 0.147 W/kg

Maximum value of SAR (measured) = 0.483 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.329 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.701 W/kg

SAR(1 g) = 0.310 W/kg; SAR(10 g) = 0.134 W/kg

Maximum value of SAR (measured) = 0.402 W/kg



0 dB = 0.470 W/kg = -3.28 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XLI QPSK 20M 1RB 99 offset 40740CH Left touch-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2605 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2605$ MHz; $\sigma = 2.027$ S/m; $\epsilon_r = 37.627$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.48, 4.48, 4.48); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM1; Type: SAM; Serial: TP-1475

ε DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.227 W/kg



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.659 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.320 W/kg

SAR(1 g) = 0.181 W/kg; SAR(10 g) = 0.095 W/kg

Maximum value of SAR (measured) = 0.224 W/kg



0 dB = 0.227 W/kg = -6.44 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XLI QPSK 20M 50RB 50 offset 40340CH Back Side 15mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2565 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2565$ MHz; $\sigma = 2.076$ S/m; $\epsilon_r = 51.617$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;
- ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20
- ε Phantom: SAM2; Type: SAM; Serial: TP:1474
- ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.130 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.610 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.255 W/kg

SAR(1 g) = 0.117 W/kg; SAR(10 g) = 0.052 W/kg

Maximum value of SAR (measured) = 0.155 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.610 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.200 W/kg

SAR(1 g) = 0.095 W/kg; SAR(10 g) = 0.045 W/kg

Maximum value of SAR (measured) = 0.123 W/kg



0 dB = 0.130 W/kg = -8.86 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 LTE Band XLI QPSK 20M 1RB 50 offset 40340CH Back Side 10mm-Main Antenna

DUT: MHA-L29; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, LTE-TDD (SC-FDMA, 20MHz, QPSK/16-QAM) (0); Frequency: 2565 MHz; Duty Cycle: 1:1.57906

Medium parameters used: $f = 2565$ MHz; $\sigma = 2.076$ S/m; $\epsilon_r = 51.617$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

ε Probe: ES3DV3 - SN3168; ConvF(4.23, 4.23, 4.23); Calibrated: 2015-9-28;

ε Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$

ε Electronics: DAE4 Sn852; Calibrated: 2016-4-20

ε Phantom: SAM2; Type: SAM; Serial: TP:1474

ε DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.736 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.723 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.533 W/kg; SAR(10 g) = 0.222 W/kg

Maximum value of SAR (measured) = 0.726 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.723 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.835 W/kg

SAR(1 g) = 0.418 W/kg; SAR(10 g) = 0.204 W/kg

Maximum value of SAR (measured) = 0.520 W/kg



0 dB = 0.736 W/kg = -1.33 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WiFi 2.4G 11b 6CH Left touch**DUT: MHA-L29; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2437 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.823$ S/m; $\epsilon_r = 39.053$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- ζ Probe: ES3DV3 - SN3168; ConvF(4.55, 4.55, 4.55); Calibrated: 2015-9-28;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2016-4-20
- ζ Phantom: SAM1; Type: SAM; Serial: TP-1475
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.34 W/kg



Configuration/Head/Zoom Scan (7x9x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.669 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.78 W/kg

SAR(1 g) = 1.22 W/kg; SAR(10 g) = 0.538 W/kg

Maximum value of SAR (measured) = 1.72 W/kg



0 dB = 1.34 W/kg = 1.27 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WiFi 2.4G 11b 6CH Front side 15mm**DUT: MHA-L29; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.942$ S/m; $\epsilon_r = 50.916$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: ES3DV3 - SN3168; ConvF(4.35, 4.35, 4.35); Calibrated: 2015-9-28;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2016-4-20
- ζ Phantom: SAM2; Type: SAM; Serial: TP:1474
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.0985 W/kg



Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.059 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.171 W/kg

SAR(1 g) = 0.093 W/kg; SAR(10 g) = 0.052 W/kg

Maximum value of SAR (measured) = 0.113 W/kg



0 dB = 0.0985 W/kg = -10.07 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WiFi 2.4G 11b 6CH Front side 10mm**DUT: MHA-L29; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.942$ S/m; $\epsilon_r = 50.916$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: ES3DV3 - SN3168; ConvF(4.35, 4.35, 4.35); Calibrated: 2015-9-28;
- ζ Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- ζ Electronics: DAE4 Sn852; Calibrated: 2016-4-20
- ζ Phantom: SAM2; Type: SAM; Serial: TP:1474
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (10x17x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.215 W/kg



Configuration/Body/Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.385 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.374 W/kg

SAR(1 g) = 0.200 W/kg; SAR(10 g) = 0.106 W/kg

Maximum value of SAR (measured) = 0.249 W/kg



0 dB = 0.215 W/kg = -6.68 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WIFI 5G 802.11ac 20M 120CH Left Touch**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.224$ S/m; $\epsilon_r = 36.254$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(4.29, 4.29, 4.29); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 25.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (12x20x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 2.11 W/kg



Configuration/Head/Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 2.395 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 4.50 W/kg

SAR(1 g) = 0.949 W/kg; SAR(10 g) = 0.301 W/kg

Maximum value of SAR (measured) = 2.52 W/kg



0 dB = 2.52 W/kg = 4.01 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WIFI 5G 802.11ac 80M 106CH Right Touch**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 5530 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5530$ MHz; $\sigma = 5.111$ S/m; $\epsilon_r = 36.402$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(4.29, 4.29, 4.29); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 25.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (12x20x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.340 W/kg



Configuration/Head/Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 1.440 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.157 W/kg; SAR(10 g) = 0.051 W/kg

Maximum value of SAR (measured) = 0.399 W/kg



0 dB = 0.399 W/kg = -3.99 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WIFI 5G 802.11ac 80M 106CH Right Tilt**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 5530 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5530$ MHz; $\sigma = 5.111$ S/m; $\epsilon_r = 36.402$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(4.29, 4.29, 4.29); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 25.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM4; Type: SAM; Serial: TP-1620
- ζ DASY52 52.8.8(1222);

Configuration/Head/Area Scan (12x20x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.337 W/kg


Configuration/Head/Zoom Scan (9x9x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 1.174 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.619 W/kg

SAR(1 g) = 0.155 W/kg; SAR(10 g) = 0.052 W/kg

Maximum value of SAR (measured) = 0.381 W/kg



0 dB = 0.381 W/kg = -4.19 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WIFI 5G 802.11n 40M 118CH Front Side 15mm with Battery 2**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 5590 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5590$ MHz; $\sigma = 5.896$ S/m; $\epsilon_r = 48.338$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(3.48, 3.48, 3.48); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 25.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (11x19x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.139 W/kg


Configuration/Body/Zoom Scan (9x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 0.5740 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.245 W/kg

SAR(1 g) = 0.069 W/kg; SAR(10 g) = 0.025 W/kg

Maximum value of SAR (measured) = 0.164 W/kg



0 dB = 0.164 W/kg = -7.84 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WIFI 5G 802.11n 40M 151CH Right Side 10mm**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 5755 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5755$ MHz; $\sigma = 5.978$ S/m; $\epsilon_r = 49.01$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(3.6, 3.6, 3.6); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 25.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (7x19x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.289 W/kg


Configuration/Body/Zoom Scan (8x9x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 2.294 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.513 W/kg

SAR(1 g) = 0.139 W/kg; SAR(10 g) = 0.048 W/kg

Maximum value of SAR (measured) = 0.328 W/kg



0 dB = 0.328 W/kg = -4.84 dBW/kg

Test Laboratory: HUAWEI SAR/HAC Lab

MHA-L29 WIFI 5G 802.11n 40M 118CH Right Side 0mm**DUT: MHA-L29; Type: Smart Phone; Serial: SAR2**

Communication System: UID 0, WiFi(802.11a/b/g/n/ac) (0); Frequency: 5590 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5590$ MHz; $\sigma = 5.896$ S/m; $\epsilon_r = 48.338$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- ζ Probe: EX3DV4 - SN3736; ConvF(3.48, 3.48, 3.48); Calibrated: 2016-4-26;
- ζ Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 25.0$
- ζ Electronics: DAE4 Sn1236; Calibrated: 2015-11-23
- ζ Phantom: SAM3; Type: SAM; Serial: TP-1597
- ζ DASY52 52.8.8(1222);

Configuration/Body/Area Scan (7x20x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 6.78 W/kg


Configuration/Body/Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 4.221 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 16.0 W/kg

SAR(1 g) = 2.68 W/kg; SAR(10 g) = 0.623 W/kg

Maximum value of SAR (measured) = 8.55 W/kg



0 dB = 8.55 W/kg = 9.32 dBW/kg