

## SAR TEST REPORT



The following samples were submitted and identified on behalf of the client as:

**Equipment Under Test** Smart Phone  
**Brand Name** HUAWEI  
**Model No.** HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02  
**Company Name** Huawei Technologies Co., Ltd  
**Company Address** Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C  
**Standards** IEEE/ANSI C95.1-1992, IEEE 1528-2013, KDB248227D01v02r02, KDB865664D01v01r04, KDB865664D02v01r02, KDB941225D01v03r01, KDB941225D05v02r05, KDB941225D06v02r01, KDB447498D01v06, KDB648474D04v01r03, KDB941225D05Av01r02  
**FCC ID** QISMLA-LX2  
**Date of Receipt** Jul. 20, 2016  
**Date of Test(s)** Jul. 30, 2016 ~ Aug. 06, 2016  
**Date of Issue** Aug. 10, 2016

In the configuration tested, the EUT complied with the standards specified above.

**Remarks:**

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Taiwan Electronic & Communication Laboratory or testing done by SGS Taiwan Electronic & Communication Laboratory in connection with distribution or use of the product described in this report must be approved by SGS Taiwan Electronic & Communication Laboratory in writing.

**Signed on behalf of SGS****Asst. Supervisor**

Kevin Li

Date: Aug. 10, 2016

**Supervisor**

John Yeh

Date: Aug. 10, 2016

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Revision History

| Report Number | Revision | Description                  | Issue Date    |
|---------------|----------|------------------------------|---------------|
| E5/2016/70026 | Rev.00   | Initial creation of document | Aug. 10, 2016 |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |
|               |          |                              |               |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Contents

|                                                                   |            |
|-------------------------------------------------------------------|------------|
| <b>1. General Information.....</b>                                | <b>4</b>   |
| 1.1 Testing Laboratory .....                                      | 4          |
| 1.2 Details of Applicant.....                                     | 4          |
| 1.3 Description of EUT .....                                      | 5          |
| 1.4 Test Environment .....                                        | 56         |
| 1.5 Operation Description .....                                   | 56         |
| 1.6 Positioning Procedure .....                                   | 62         |
| 1.7 Power reduction information .....                             | 64         |
| 1.8 Evaluation Procedures .....                                   | 73         |
| 1.9 Probe Calibration Procedures .....                            | 75         |
| 1.10 The SAR Measurement System.....                              | 78         |
| 1.11 System Components .....                                      | 80         |
| 1.12 SAR System Verification .....                                | 82         |
| 1.13 Tissue Simulant Fluid for the Frequency Band .....           | 84         |
| 1.14 Test Standards and Limits .....                              | 87         |
| <b>2. Summary of Results .....</b>                                | <b>89</b>  |
| <b>3. Simultaneous Transmission Analysis.....</b>                 | <b>112</b> |
| 3.1 Estimated SAR calculation.....                                | 113        |
| 3.2 SPLSR evaluation and analysis .....                           | 113        |
| <b>4. Instruments List .....</b>                                  | <b>122</b> |
| <b>5. Measurements.....</b>                                       | <b>124</b> |
| <b>6. SAR System Performance Verification .....</b>               | <b>163</b> |
| <b>7. DAE &amp; Probe Calibration Certificate .....</b>           | <b>172</b> |
| <b>8. Phantom Description.....</b>                                | <b>204</b> |
| <b>9. System Validation from Original Equipment Supplier.....</b> | <b>205</b> |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

# 1. General Information

## 1.1 Testing Laboratory

|                                                                                          |                                                             |
|------------------------------------------------------------------------------------------|-------------------------------------------------------------|
| SGS Taiwan Ltd. Electronics & Communication Laboratory                                   |                                                             |
| No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan |                                                             |
| Tel                                                                                      | +886-2-2299-3279                                            |
| Fax                                                                                      | +886-2-2298-0488                                            |
| Internet                                                                                 | <a href="http://www.tw.sgs.com/">http://www.tw.sgs.com/</a> |

## 1.2 Details of Applicant

|                 |                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------|
| Company Name    | Huawei Technologies Co., Ltd                                                                                                |
| Company Address | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### 1.3 Description of EUT

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| EUT Name                               | Smart Phone                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                     |
| Brand Name                             | HUAWEI                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                     |
| Model No.                              | HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                     |
| Difference between MLA-L12 and MLA-L02 | <p>The only differences between the new model and the original model are:</p> <ul style="list-style-type: none"> <li>- Model HUAWEI MLA-L12, MLA-L12 is a smart phone with dual SIM.</li> <li>- Model HUAWEI MLA-L02, MLA-L02 is a smart phone with single SIM.</li> <li>- The difference of them is only for SIM CARD. HUAWEI MLA-L02, MLA-L02 delete one SIM by software.</li> </ul>                                                                            |                                                                     |
| FCC ID                                 | QISMLA-LX2                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                     |
| Mode of Operation                      | <input checked="" type="checkbox"/> GSM <input checked="" type="checkbox"/> GPRS <input checked="" type="checkbox"/> EDGE<br><input checked="" type="checkbox"/> WCDMA <input checked="" type="checkbox"/> HSDPA <input checked="" type="checkbox"/> HSUPA <input checked="" type="checkbox"/> DC-HSDPA<br><input checked="" type="checkbox"/> LTE FDD <input checked="" type="checkbox"/> WLAN802.11 b/g/n(20M)<br><input checked="" type="checkbox"/> Bluetooth |                                                                     |
| Duty Cycle                             | GSM (DTM multi class B)                                                                                                                                                                                                                                                                                                                                                                                                                                           | 1/8.3                                                               |
|                                        | GPRS (support multi class 12 max)                                                                                                                                                                                                                                                                                                                                                                                                                                 | 1/2 (1Dn4UP)<br>1/2.76 (1Dn3UP)<br>1/4.1 (1Dn2UP)<br>1/8.3 (1Dn1UP) |
|                                        | EDGE (support multi class 12 max)                                                                                                                                                                                                                                                                                                                                                                                                                                 | 1/2 (1Dn4UP)<br>1/2.76 (1Dn3UP)<br>1/4.1 (1Dn2UP)<br>1/8.3 (1Dn1UP) |
|                                        | LTE FDD (LTE Release Version: R10)                                                                                                                                                                                                                                                                                                                                                                                                                                | 1                                                                   |
|                                        | LTE TDD                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0.633                                                               |
|                                        | WCDMA (HSDPA Category 24) (HSUPA Category 6)                                                                                                                                                                                                                                                                                                                                                                                                                      | 1                                                                   |
|                                        | WLAN802.11 b/g/n(20M)                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1                                                                   |
|                                        | Bluetooth                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1                                                                   |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

|                          |                       |       |   |       |
|--------------------------|-----------------------|-------|---|-------|
| TX Frequency Range (MHz) | GSM850                | 824   | — | 849   |
|                          | GSM1900               | 1850  | — | 1910  |
|                          | WCDMA Band V          | 824   | — | 849   |
|                          | LTE FDD Band V        | 824   | — | 849   |
|                          | LTE FDD Band VII      | 2500  | — | 2570  |
|                          | LTE TDD Band XXXVIII  | 2570  | — | 2620  |
|                          | WLAN802.11 b/g/n(20M) | 2412  | — | 2462  |
|                          | Bluetooth             | 2402  | — | 2480  |
| RX Frequency Range (MHz) | GSM850                | 869   | — | 894   |
|                          | GSM1900               | 1930  | — | 1990  |
|                          | WCDMA Band V          | 869   | — | 894   |
|                          | LTE FDD Band V        | 869   | — | 894   |
|                          | LTE FDD Band VII      | 2620  | — | 2690  |
|                          | LTE TDD Band XXXVIII  | 2570  | — | 2620  |
|                          | WLAN802.11 b/g/n(20M) | 2412  | — | 2462  |
|                          | Bluetooth             | 2402  | — | 2480  |
| Channel Number (ARFCN)   | GSM850                | 128   | — | 251   |
|                          | GSM1900               | 512   | — | 810   |
|                          | WCDMA Band V          | 4132  | — | 4233  |
|                          | LTE FDD Band V        | 20407 | — | 20643 |
|                          | LTE FDD Band VII      | 20775 | — | 21425 |
|                          | LTE TDD Band XXXVIII  | 37775 | — | 38225 |
|                          | WLAN802.11 b/g/n(20M) | 1     | — | 11    |
|                          | Bluetooth             | 0     | — | 78    |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Max. SAR (1 g) (Unit: W/Kg) |                      |          |          |          |                                                                                                                                                                     |
|-----------------------------|----------------------|----------|----------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mode                        | Band                 | Distance | Measured | Reported | Position / Channel                                                                                                                                                  |
| Head                        | GSM 850              | -        | 1.00     | 1.23     | <input type="checkbox"/> Left <input checked="" type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>128 Channel   |
|                             | GSM 1900             | -        | 0.36     | 0.44     | <input type="checkbox"/> Left <input checked="" type="checkbox"/> Right<br><input type="checkbox"/> Cheek <input checked="" type="checkbox"/> Tilt<br>661 Channel   |
|                             | WCDMA Band V         | -        | 0.84     | 1.05     | <input type="checkbox"/> Left <input checked="" type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>4132 Channel  |
|                             | LTE FDD Band V       | -        | 0.93     | 1.19     | <input type="checkbox"/> Left <input checked="" type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>20450 Channel |
|                             | LTE FDD Band VII     | -        | 0.79     | 0.83     | <input type="checkbox"/> Left <input checked="" type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>21350 Channel |
|                             | LTE TDD Band XXXVIII | -        | 0.66     | 0.76     | <input type="checkbox"/> Left <input checked="" type="checkbox"/> Right<br><input checked="" type="checkbox"/> Cheek <input type="checkbox"/> Tilt<br>38000 Channel |
|                             | WLAN802.11 b         | -        | 0.40     | 0.42     | <input checked="" type="checkbox"/> Left <input type="checkbox"/> Right<br><input type="checkbox"/> Cheek <input checked="" type="checkbox"/> Tilt<br>11 Channel    |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Max. SAR (1 g) (Unit: W/Kg) |                      |          |          |          |                                                                                          |
|-----------------------------|----------------------|----------|----------|----------|------------------------------------------------------------------------------------------|
| Mode                        | Band                 | Distance | Measured | Reported | Position / Channel                                                                       |
| Body-worn                   | GSM 850              | 15mm     | 0.27     | 0.31     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br>128 Channel   |
|                             | GSM 1900             | 15mm     | 0.25     | 0.30     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br>512 Channel   |
|                             | WCDMA Band V         | 15mm     | 0.31     | 0.38     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br>4233 Channel  |
|                             | LTE FDD Band V       | 15mm     | 0.26     | 0.30     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br>20600 Channel |
|                             | LTE FDD Band VII     | 15mm     | 0.26     | 0.27     | <input checked="" type="checkbox"/> Front <input type="checkbox"/> Back<br>21350 Channel |
|                             | LTE TDD Band XXXVIII | 15mm     | 0.09     | 0.10     | <input checked="" type="checkbox"/> Front <input type="checkbox"/> Back<br>37850 Channel |
|                             | WLAN802.11 b         | 15mm     | 0.15     | 0.15     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br>11 Channel    |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| Max. SAR (1 g) (Unit: W/Kg) |                      |          |          |          |                                                                                                                                                                                                                          |
|-----------------------------|----------------------|----------|----------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mode                        | Band                 | Distance | Measured | Reported | Position / Channel                                                                                                                                                                                                       |
| Hotspot mode                | GPRS 850 (1Dn2UP)    | 10mm     | 0.62     | 0.67     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Top<br><input type="checkbox"/> Right <input type="checkbox"/> Left<br>190 Channel   |
|                             | GPRS 1900 (1Dn2UP)   | 10mm     | 0.89     | 1.09     | <input type="checkbox"/> Front <input type="checkbox"/> Back<br><input checked="" type="checkbox"/> Bottom <input type="checkbox"/> Top<br><input type="checkbox"/> Right <input type="checkbox"/> Left<br>661 Channel   |
|                             | WCDMA Band V         | 10mm     | 0.62     | 0.77     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Top<br><input type="checkbox"/> Right <input type="checkbox"/> Left<br>4233 Channel  |
|                             | LTE FDD Band V       | 10mm     | 0.53     | 0.61     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Top<br><input type="checkbox"/> Right <input type="checkbox"/> Left<br>20600 Channel |
|                             | LTE FDD Band VII     | 10mm     | 1.00     | 1.05     | <input type="checkbox"/> Front <input type="checkbox"/> Back<br><input checked="" type="checkbox"/> Bottom <input type="checkbox"/> Top<br><input type="checkbox"/> Right <input type="checkbox"/> Left<br>21100 Channel |
|                             | LTE TDD Band XXXVIII | 10mm     | 0.36     | 0.39     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Top<br><input type="checkbox"/> Right <input type="checkbox"/> Left<br>37850 Channel |
|                             | WLAN802.11 b         | 10mm     | 0.32     | 0.32     | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back<br><input type="checkbox"/> Bottom <input type="checkbox"/> Top<br><input type="checkbox"/> Right <input type="checkbox"/> Left<br>11 Channel    |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Name      | Manufacturer                       |
|-----------|------------------------------------|
| Battery 1 | Harbin Coslight Power Co., Ltd     |
| Battery 2 | Sunwoda Electronic Co., Ltd        |
| Battery 3 | Huizhou Desay Battery Co., Ltd     |
| Battery 4 | SCUD (FUJIAN) Electronics Co., Ltd |

### Difference description

The differences between MLA-L12 and MLA-L13 are described as below.

The differences between HUAWEI MLA-L13 and HUAWEI MLA-L12 are shown in the following table. Other parts of the mobile phone are the same, including the appearance, the antenna, Chipset, Bluetooth mode, Wifi mode, Adapter, Battery, Mainboard and so on.

|                         | MLA-L12                              | MLA-L13                                                    |
|-------------------------|--------------------------------------|------------------------------------------------------------|
| GSM four bands          | B2/B3/B5/B8                          | B2/B3/B5/B8                                                |
| WCDMA bands             | B1/ B5/B8                            | B1/B2/B4/B5/B8                                             |
| LTE bands               | B1/B3/B5/B7/B8/B28/B38/B40           | B2/B4/B5/B7/B12/B17/B28                                    |
| FCC bands               | GSM850/1900<br>W850<br>LTE B5/B7/B38 | GSM850/1900<br>W850/W1700/W1900<br>LTE B2/B4/B5/B7/B12/B17 |
| SIM card                | Two                                  | Two                                                        |
| External camera         | the same                             | the same                                                   |
| internal camera         | the same                             | the same                                                   |
| FLASH                   | the same                             | the same                                                   |
| Mainboard               | the same                             | the same                                                   |
| PCB layout              | the same                             | the same                                                   |
| Appearance              | the same                             | the same                                                   |
| Bluetooth mode          | the same                             | the same                                                   |
| WLAN mode               | the same                             | the same                                                   |
| BT/ WLAN antenna        | the same                             | the same                                                   |
| GSM/ WCDMA /LTE antenna | the same                             | the same                                                   |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

|                   |                                        |                                        |
|-------------------|----------------------------------------|----------------------------------------|
| Adapter           | the same                               | the same                               |
| Battery           | the same                               | the same                               |
| Chipset           | the same                               | the same                               |
| Memory            | the same                               | the same                               |
| RF Parameter      | The same RF Parameter in the same band | The same RF Parameter in the same band |
| Dimension         | the same                               | the same                               |
| Main Frequency NV | The same NV in the same band           | The same NV in the same band           |

According to the difference description above, for the same frequency bands (GSM850/1900, UMTS Band V, LTE Band V/VII and WiFi 2.4G), MLA-L12 SAR is tested at the worst case of MLA-L13 (FCC ID: QISMLA-LX3). For the new bands (LTE Band XXXVIII), new full SAR test is performed on MLA-L12.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## GSM/GPRS/EDGE conducted power table:

### Main antenna + Hotspot Off

| EUT mode                                                   | Frequency (MHz) | CH  | Max. Rated Avg. Power + Max. Tolerance (dBm) | Burst average power | Source-based time average power |
|------------------------------------------------------------|-----------------|-----|----------------------------------------------|---------------------|---------------------------------|
|                                                            |                 |     |                                              | Avg. (dBm)          | Avg. (dBm)                      |
| GSM850 (GMSK)                                              | 824.2           | 128 | 33                                           | 32.12               | 23.09                           |
|                                                            | 836.6           | 190 | 33                                           | 32.32               | 23.29                           |
|                                                            | 848.8           | 251 | 33                                           | 32.46               | 23.43                           |
| The division factor compared to the number of TX time slot |                 |     |                                              |                     |                                 |
| Division factor                                            |                 |     |                                              | 1 TX time slot      |                                 |
|                                                            |                 |     |                                              | -9.03               |                                 |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 33             | 30.5           | 27.5           | 26.5           |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 850                                                   | 824.2           | 128 | 32.12          | 29.85          | 27.13          | 25.86          |
|                                                            | 836.6           | 190 | 32.32          | 30.00          | 27.18          | 26.12          |
|                                                            | 848.8           | 251 | 32.46          | 30.12          | 27.35          | 26.16          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 850                                                   | 824.2           | 128 | 23.09          | 23.83          | 22.87          | 22.85          |
|                                                            | 836.6           | 190 | 23.29          | 23.98          | 22.92          | 23.11          |
|                                                            | 848.8           | 251 | 23.43          | 24.10          | 23.09          | 23.15          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                    |     |                |                |                |                |
|------------------------------------------------------------|--------------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power +<br>Max. Tolerance (dBm)            |                    |     | 27             | 27             | 26             | 24             |
|                                                            |                    |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency<br>(MHz) | CH  | Avg.<br>(dBm)  | Avg.<br>(dBm)  | Avg.<br>(dBm)  | Avg.<br>(dBm)  |
| EDGE<br>850<br>(MCS5)                                      | 824.2              | 128 | 26.15          | 26.07          | 24.12          | 23.14          |
|                                                            | 836.6              | 190 | 26.09          | 25.99          | 24.23          | 23.21          |
|                                                            | 848.8              | 251 | 26.14          | 26.04          | 24.19          | 23.00          |
| Source-based time average power                            |                    |     |                |                |                |                |
| EDGE<br>850<br>(MCS5)                                      | 824.2              | 128 | 17.12          | 20.05          | 19.86          | 20.13          |
|                                                            | 836.6              | 190 | 17.06          | 19.97          | 19.97          | 20.20          |
|                                                            | 848.8              | 251 | 17.11          | 20.02          | 19.93          | 19.99          |
| The division factor compared to the number of TX time slot |                    |     |                |                |                |                |
| Division factor                                            |                    |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                    |     | -9.03          | -6.02          | -4.26          | -3.01          |

| EUT mode                                                   | Frequency<br>(MHz) | CH  | Max.<br>Rated<br>Avg.<br>Power +<br>Max.<br>Tolerance<br>(dBm) | Burst<br>average<br>power | Source<br>-based<br>time<br>average<br>power |
|------------------------------------------------------------|--------------------|-----|----------------------------------------------------------------|---------------------------|----------------------------------------------|
|                                                            |                    |     |                                                                | Avg.<br>(dBm)             | Avg.<br>(dBm)                                |
| GSM1900<br>(GMSK)                                          | 1850.2             | 512 | 30                                                             | 29.18                     | 20.15                                        |
|                                                            | 1800               | 661 | 30                                                             | 29.12                     | 20.09                                        |
|                                                            | 1909.8             | 810 | 30                                                             | 29.17                     | 20.14                                        |
| The division factor compared to the number of TX time slot |                    |     |                                                                |                           |                                              |
| Division factor                                            |                    |     |                                                                | 1 TX time slot            |                                              |
|                                                            |                    |     |                                                                | -9.03                     |                                              |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 30             | 28             | 26             | 24             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 1900                                                  | 1850.2          | 512 | 29.18          | 27.34          | 24.80          | 23.88          |
|                                                            | 1880            | 661 | 29.12          | 27.30          | 24.73          | 23.80          |
|                                                            | 1909.8          | 810 | 29.17          | 27.36          | 24.93          | 23.86          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 1900                                                  | 1850.2          | 512 | 20.15          | 21.32          | 20.54          | 20.87          |
|                                                            | 1880            | 661 | 20.09          | 21.28          | 20.47          | 20.79          |
|                                                            | 1909.8          | 810 | 20.14          | 21.34          | 20.67          | 20.85          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 26             | 26             | 24             | 23             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 25.24          | 25.11          | 23.38          | 22.23          |
|                                                            | 1880            | 661 | 25.26          | 25.21          | 23.27          | 22.16          |
|                                                            | 1909.8          | 810 | 25.12          | 25.09          | 23.32          | 22.14          |
| Source-based time average power                            |                 |     |                |                |                |                |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 16.21          | 19.09          | 19.12          | 19.22          |
|                                                            | 1880            | 661 | 16.23          | 19.19          | 19.01          | 19.15          |
|                                                            | 1909.8          | 810 | 16.09          | 19.07          | 19.06          | 19.13          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### Main antenna + Hotspot On

| EUT mode                                                   | Frequency (MHz) | CH  | Max. Rated Avg. Power + Max. Tolerance (dBm) | Burst average power | Source -based time average power |
|------------------------------------------------------------|-----------------|-----|----------------------------------------------|---------------------|----------------------------------|
|                                                            |                 |     |                                              | Avg. (dBm)          | Avg. (dBm)                       |
| GSM850 (GMSK)                                              | 824.2           | 128 | 33                                           | 32.12               | 23.09                            |
|                                                            | 836.6           | 190 | 33                                           | 32.32               | 23.29                            |
|                                                            | 848.8           | 251 | 33                                           | 32.46               | 23.43                            |
| The division factor compared to the number of TX time slot |                 |     |                                              |                     |                                  |
| Division factor                                            |                 |     |                                              | 1 TX time slot      |                                  |
|                                                            |                 |     |                                              |                     | -9.03                            |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 33             | 30.5           | 27.5           | 26.5           |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 850                                                   | 824.2           | 128 | 32.12          | 29.85          | 27.13          | 25.86          |
|                                                            | 836.6           | 190 | 32.32          | 30.00          | 27.18          | 26.12          |
|                                                            | 848.8           | 251 | 32.46          | 30.12          | 27.35          | 26.16          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 850                                                   | 824.2           | 128 | 23.09          | 23.83          | 22.87          | 22.85          |
|                                                            | 836.6           | 190 | 23.29          | 23.98          | 22.92          | 23.11          |
|                                                            | 848.8           | 251 | 23.43          | 24.10          | 23.09          | 23.15          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                    |     |                |                |                |                |
|------------------------------------------------------------|--------------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power +<br>Max. Tolerance (dBm)            |                    |     | 27             | 27             | 26             | 24             |
|                                                            |                    |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency<br>(MHz) | CH  | Avg.<br>(dBm)  | Avg.<br>(dBm)  | Avg.<br>(dBm)  | Avg.<br>(dBm)  |
| EDGE<br>850<br>(MCS5)                                      | 824.2              | 128 | 26.15          | 26.07          | 24.12          | 23.14          |
|                                                            | 836.6              | 190 | 26.09          | 25.99          | 24.23          | 23.21          |
|                                                            | 848.8              | 251 | 26.14          | 26.04          | 24.19          | 23.00          |
| Source-based time average power                            |                    |     |                |                |                |                |
| EDGE<br>850<br>(MCS5)                                      | 824.2              | 128 | 17.12          | 20.05          | 19.86          | 20.13          |
|                                                            | 836.6              | 190 | 17.06          | 19.97          | 19.97          | 20.20          |
|                                                            | 848.8              | 251 | 17.11          | 20.02          | 19.93          | 19.99          |
| The division factor compared to the number of TX time slot |                    |     |                |                |                |                |
| Division factor                                            |                    |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                    |     | -9.03          | -6.02          | -4.26          | -3.01          |

| EUT mode                                                   | Frequency<br>(MHz) | CH  | Max.<br>Rated<br>Avg.<br>Power +<br>Max.<br>Tolerance<br>(dBm) | Burst<br>average<br>power | Source<br>-based<br>time<br>average<br>power |
|------------------------------------------------------------|--------------------|-----|----------------------------------------------------------------|---------------------------|----------------------------------------------|
|                                                            |                    |     |                                                                | Avg.<br>(dBm)             | Avg.<br>(dBm)                                |
| GSM1900<br>(GMSK)                                          | 1850.2             | 512 | 27                                                             | 25.33                     | 16.3                                         |
|                                                            | 1800               | 661 | 27                                                             | 25.29                     | 16.26                                        |
|                                                            | 1909.8             | 810 | 27                                                             | 25.34                     | 16.31                                        |
| The division factor compared to the number of TX time slot |                    |     |                                                                |                           |                                              |
| Division factor                                            |                    |     |                                                                | 1 TX time slot            |                                              |
|                                                            |                    |     |                                                                | -9.03                     |                                              |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 27             | 28             | 26             | 24             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 1900                                                  | 1850.2          | 512 | 25.33          | 27.34          | 24.80          | 23.88          |
|                                                            | 1880            | 661 | 25.29          | 27.30          | 24.73          | 23.80          |
|                                                            | 1909.8          | 810 | 25.34          | 27.36          | 24.93          | 23.86          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 1900                                                  | 1850.2          | 512 | 16.30          | 21.32          | 20.54          | 20.87          |
|                                                            | 1880            | 661 | 16.26          | 21.28          | 20.47          | 20.79          |
|                                                            | 1909.8          | 810 | 16.31          | 21.34          | 20.67          | 20.85          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 26             | 26             | 24             | 23             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 25.24          | 25.11          | 23.38          | 22.23          |
|                                                            | 1880            | 661 | 25.26          | 25.21          | 23.27          | 22.16          |
|                                                            | 1909.8          | 810 | 25.12          | 25.09          | 23.32          | 22.14          |
| Source-based time average power                            |                 |     |                |                |                |                |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 16.21          | 19.09          | 19.12          | 19.22          |
|                                                            | 1880            | 661 | 16.23          | 19.19          | 19.01          | 19.15          |
|                                                            | 1909.8          | 810 | 16.09          | 19.07          | 19.06          | 19.13          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### Sub antenna + Sensor Off

| EUT mode                                                   | Frequency (MHz) | CH  | Max. Rated Avg. Power + Max. Tolerance (dBm) | Burst average power | Source -based time average power |
|------------------------------------------------------------|-----------------|-----|----------------------------------------------|---------------------|----------------------------------|
|                                                            |                 |     |                                              | Avg. (dBm)          | Avg. (dBm)                       |
| GSM850 (GMSK)                                              | 824.2           | 128 | 33                                           | 32.33               | 23.3                             |
|                                                            | 836.6           | 190 | 33                                           | 32.44               | 23.41                            |
|                                                            | 848.8           | 251 | 33                                           | 32.52               | 23.49                            |
| The division factor compared to the number of TX time slot |                 |     |                                              |                     |                                  |
| Division factor                                            |                 |     |                                              | 1 TX time slot      |                                  |
|                                                            |                 |     |                                              | -9.03               |                                  |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 33             | 30.5           | 27.5           | 26.5           |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 850                                                   | 824.2           | 128 | 32.33          | 29.89          | 27.15          | 25.84          |
|                                                            | 836.6           | 190 | 32.44          | 30.12          | 27.19          | 26.17          |
|                                                            | 848.8           | 251 | 32.52          | 30.19          | 27.39          | 26.26          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 850                                                   | 824.2           | 128 | 23.30          | 23.87          | 22.89          | 22.83          |
|                                                            | 836.6           | 190 | 23.41          | 24.10          | 22.93          | 23.16          |
|                                                            | 848.8           | 251 | 23.49          | 24.17          | 23.13          | 23.25          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                    |     |                |                |                |                |
|------------------------------------------------------------|--------------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power +<br>Max. Tolerance (dBm)            |                    |     | 27             | 27             | 26             | 24             |
|                                                            |                    |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency<br>(MHz) | CH  | Avg.<br>(dBm)  | Avg.<br>(dBm)  | Avg.<br>(dBm)  | Avg.<br>(dBm)  |
| EDGE<br>850<br>(MCS5)                                      | 824.2              | 128 | 26.00          | 26.00          | 24.15          | 23.19          |
|                                                            | 836.6              | 190 | 26.12          | 26.11          | 24.25          | 23.22          |
|                                                            | 848.8              | 251 | 26.18          | 26.11          | 24.21          | 23.11          |
| Source-based time average power                            |                    |     |                |                |                |                |
| EDGE<br>850<br>(MCS5)                                      | 824.2              | 128 | 16.97          | 19.98          | 19.89          | 20.18          |
|                                                            | 836.6              | 190 | 17.09          | 20.09          | 19.99          | 20.21          |
|                                                            | 848.8              | 251 | 17.15          | 20.09          | 19.95          | 20.10          |
| The division factor compared to the number of TX time slot |                    |     |                |                |                |                |
| Division factor                                            |                    |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                    |     | -9.03          | -6.02          | -4.26          | -3.01          |

| EUT mode                                                   | Frequency<br>(MHz) | CH  | Max.<br>Rated<br>Avg.<br>Power +<br>Max.<br>Tolerance<br>(dBm) | Burst<br>average<br>power | Source<br>-based<br>time<br>average<br>power |
|------------------------------------------------------------|--------------------|-----|----------------------------------------------------------------|---------------------------|----------------------------------------------|
|                                                            |                    |     |                                                                | Avg.<br>(dBm)             | Avg.<br>(dBm)                                |
| GSM1900<br>(GMSK)                                          | 1850.2             | 512 | 30                                                             | 28.85                     | 19.82                                        |
|                                                            | 1800               | 661 | 30                                                             | 28.75                     | 19.72                                        |
|                                                            | 1909.8             | 810 | 30                                                             | 28.72                     | 19.69                                        |
| The division factor compared to the number of TX time slot |                    |     |                                                                |                           |                                              |
| Division factor                                            |                    |     |                                                                | 1 TX time slot            |                                              |
|                                                            |                    |     |                                                                | -9.03                     |                                              |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 30             | 28             | 26             | 24             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 1900                                                  | 1850.2          | 512 | 28.85          | 27.15          | 24.67          | 23.50          |
|                                                            | 1880            | 661 | 28.75          | 27.08          | 24.73          | 23.53          |
|                                                            | 1909.8          | 810 | 28.72          | 27.05          | 24.76          | 23.47          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 1900                                                  | 1850.2          | 512 | 19.82          | 21.13          | 20.41          | 20.49          |
|                                                            | 1880            | 661 | 19.72          | 21.06          | 20.47          | 20.52          |
|                                                            | 1909.8          | 810 | 19.69          | 21.03          | 20.50          | 20.46          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 26             | 26             | 24             | 23             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 25.00          | 24.99          | 23.39          | 22.19          |
|                                                            | 1880            | 661 | 25.11          | 25.04          | 23.38          | 22.19          |
|                                                            | 1909.8          | 810 | 25.28          | 25.21          | 23.31          | 22.19          |
| Source-based time average power                            |                 |     |                |                |                |                |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 15.97          | 18.97          | 19.13          | 19.18          |
|                                                            | 1880            | 661 | 16.08          | 19.02          | 19.12          | 19.18          |
|                                                            | 1909.8          | 810 | 16.25          | 19.19          | 19.05          | 19.18          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### Sub antenna + Sensor On

| EUT mode                                                   | Frequency (MHz) | CH  | Max. Rated Avg. Power + Max. Tolerance (dBm) | Burst average power | Source -based time average power |
|------------------------------------------------------------|-----------------|-----|----------------------------------------------|---------------------|----------------------------------|
|                                                            |                 |     |                                              | Avg. (dBm)          | Avg. (dBm)                       |
| GSM850 (GMSK)                                              | 824.2           | 128 | 30.5                                         | 29.62               | 20.59                            |
|                                                            | 836.6           | 190 | 30.5                                         | 29.78               | 20.75                            |
|                                                            | 848.8           | 251 | 30.5                                         | 29.87               | 20.84                            |
| The division factor compared to the number of TX time slot |                 |     |                                              |                     |                                  |
| Division factor                                            |                 |     |                                              | 1 TX time slot      |                                  |
|                                                            |                 |     |                                              |                     | -9.03                            |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 30.5           | 30.5           | 27.5           | 26.5           |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 850                                                   | 824.2           | 128 | 30.02          | 29.89          | 27.15          | 25.84          |
|                                                            | 836.6           | 190 | 30.18          | 30.12          | 27.19          | 26.17          |
|                                                            | 848.8           | 251 | 30.27          | 30.19          | 27.39          | 26.26          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 850                                                   | 824.2           | 128 | 20.99          | 23.87          | 22.89          | 22.83          |
|                                                            | 836.6           | 190 | 21.15          | 24.10          | 22.93          | 23.16          |
|                                                            | 848.8           | 251 | 21.24          | 24.17          | 23.13          | 23.25          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 27             | 27             | 26             | 24             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| EDGE 850 (MCS5)                                            | 824.2           | 128 | 26.00          | 26.00          | 24.15          | 23.19          |
|                                                            | 836.6           | 190 | 26.12          | 26.11          | 24.25          | 23.22          |
|                                                            | 848.8           | 251 | 26.18          | 26.11          | 24.21          | 23.11          |
| Source-based time average power                            |                 |     |                |                |                |                |
| EDGE 850 (MCS5)                                            | 824.2           | 128 | 16.97          | 19.98          | 19.89          | 20.18          |
|                                                            | 836.6           | 190 | 17.09          | 20.09          | 19.99          | 20.21          |
|                                                            | 848.8           | 251 | 17.15          | 20.09          | 19.95          | 20.10          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

| EUT mode                                                   | Frequency (MHz) | CH  | Max. Rated Avg. Power + Max. Tolerance (dBm) | Burst average power | Source-based time average power |
|------------------------------------------------------------|-----------------|-----|----------------------------------------------|---------------------|---------------------------------|
|                                                            |                 |     |                                              | Avg. (dBm)          | Avg. (dBm)                      |
| GSM1900 (GMSK)                                             | 1850.2          | 512 | 29                                           | 28.10               | 19.07                           |
|                                                            | 1800            | 661 | 29                                           | 28.12               | 19.09                           |
|                                                            | 1909.8          | 810 | 29                                           | 28.10               | 19.07                           |
| The division factor compared to the number of TX time slot |                 |     |                                              |                     |                                 |
| Division factor                                            |                 |     |                                              | 1 TX time slot      |                                 |
|                                                            |                 |     |                                              | -9.03               |                                 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 29             | 28             | 26             | 24             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| GPRS 1900                                                  | 1850.2          | 512 | 28.10          | 27.15          | 24.67          | 23.50          |
|                                                            | 1880            | 661 | 28.12          | 27.08          | 24.73          | 23.53          |
|                                                            | 1909.8          | 810 | 28.10          | 27.05          | 24.76          | 23.47          |
| Source-based time average power                            |                 |     |                |                |                |                |
| GPRS 1900                                                  | 1850.2          | 512 | 19.07          | 21.13          | 20.41          | 20.49          |
|                                                            | 1880            | 661 | 19.09          | 21.06          | 20.47          | 20.52          |
|                                                            | 1909.8          | 810 | 19.07          | 21.03          | 20.50          | 20.46          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

| Burst average power                                        |                 |     |                |                |                |                |
|------------------------------------------------------------|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm)               |                 |     | 26             | 26             | 24             | 23             |
|                                                            |                 |     | 1Dn1UP         | 1Dn2UP         | 1Dn3UP         | 1Dn4UP         |
| EUT mode                                                   | Frequency (MHz) | CH  | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     | Avg. (dBm)     |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 25.00          | 24.99          | 23.39          | 22.19          |
|                                                            | 1880            | 661 | 25.11          | 25.04          | 23.38          | 22.19          |
|                                                            | 1909.8          | 810 | 25.28          | 25.21          | 23.31          | 2.19           |
| Source-based time average power                            |                 |     |                |                |                |                |
| EDGE 1900 (MCS5)                                           | 1850.2          | 512 | 15.97          | 18.97          | 19.13          | 19.18          |
|                                                            | 1880            | 661 | 16.08          | 19.02          | 19.12          | 19.18          |
|                                                            | 1909.8          | 810 | 16.25          | 19.19          | 19.05          | -0.82          |
| The division factor compared to the number of TX time slot |                 |     |                |                |                |                |
| Division factor                                            |                 |     | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
|                                                            |                 |     | -9.03          | -6.02          | -4.26          | -3.01          |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### WCDMA Band V - HSDPA / HSUPA / DC-HSDPA conducted power table:

Main antenna

| Band                                       |                    | WCDMA V |       |       |
|--------------------------------------------|--------------------|---------|-------|-------|
| TX Channel                                 |                    | 4132    | 4183  | 4233  |
| Frequency (MHz)                            |                    | 826.4   | 836.6 | 846.6 |
| Max. Rated Avg. Power+Max. Tolerance (dBm) |                    | 24.50   |       |       |
| 3GPP Rel 99                                | RMC 12.2Kbps       | 23.65   | 23.67 | 23.56 |
| 3GPP Rel 5                                 | HSDPA Subtest-1    | 22.68   | 22.72 | 22.53 |
|                                            | HSDPA Subtest-2    | 22.67   | 22.71 | 22.51 |
|                                            | HSDPA Subtest-3    | 22.09   | 22.23 | 22.04 |
|                                            | HSDPA Subtest-4    | 22.09   | 22.23 | 22.04 |
| 3GPP Rel 6                                 | HSUPA Subtest-1    | 22.46   | 22.50 | 22.30 |
|                                            | HSUPA Subtest-2    | 21.98   | 21.99 | 21.87 |
|                                            | HSUPA Subtest-3    | 22.35   | 22.51 | 22.29 |
|                                            | HSUPA Subtest-4    | 22.47   | 22.47 | 22.34 |
|                                            | HSUPA Subtest-5    | 22.48   | 22.52 | 22.36 |
| 3GPP Rel 8                                 | DC-HSDPA Subtest-1 | 22.61   | 22.66 | 22.43 |
|                                            | DC-HSDPA Subtest-2 | 22.56   | 22.64 | 22.41 |
|                                            | DC-HSDPA Subtest-3 | 22.01   | 22.14 | 21.95 |
|                                            | DC-HSDPA Subtest-4 | 21.94   | 22.15 | 21.94 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### Sub antenna

| Band                                       |                    | WCDMA V |       |       |
|--------------------------------------------|--------------------|---------|-------|-------|
| TX Channel                                 |                    | 4132    | 4183  | 4233  |
| Frequency (MHz)                            |                    | 826.4   | 836.6 | 846.6 |
| Max. Rated Avg. Power+Max. Tolerance (dBm) |                    | 21.50   |       |       |
| 3GPP Rel 99                                | RMC 12.2Kbps       | 20.52   | 20.63 | 20.42 |
| 3GPP Rel 5                                 | HSDPA Subtest-1    | 19.42   | 19.43 | 19.29 |
|                                            | HSDPA Subtest-2    | 19.41   | 19.53 | 19.27 |
|                                            | HSDPA Subtest-3    | 18.92   | 19.04 | 18.87 |
|                                            | HSDPA Subtest-4    | 19.01   | 19.02 | 18.87 |
| 3GPP Rel 6                                 | HSUPA Subtest-1    | 19.37   | 19.59 | 19.30 |
|                                            | HSUPA Subtest-2    | 18.90   | 19.10 | 18.84 |
|                                            | HSUPA Subtest-3    | 19.46   | 19.48 | 19.28 |
|                                            | HSUPA Subtest-4    | 19.46   | 19.48 | 19.31 |
|                                            | HSUPA Subtest-5    | 19.48   | 19.49 | 19.33 |
| 3GPP Rel 8                                 | DC-HSDPA Subtest-1 | 19.34   | 19.34 | 19.19 |
|                                            | DC-HSDPA Subtest-2 | 19.33   | 19.32 | 19.17 |
|                                            | DC-HSDPA Subtest-3 | 18.85   | 18.92 | 18.81 |
|                                            | DC-HSDPA Subtest-4 | 18.86   | 18.94 | 18.82 |

### Sub-Test for HSDPA

| SUB-TEST | $\beta_c$ | $\beta_d$ | $\beta_d$<br>(SF) | $\beta_c/\beta_d$ | $\beta_{HS}$<br>(Note 1, Note 2) | CM (dB)<br>(Note 3) | MPR (dB)<br>(Note 3) |
|----------|-----------|-----------|-------------------|-------------------|----------------------------------|---------------------|----------------------|
| 1        | 2/15      | 15/15     | 64                | 2/15              | 4/15                             | 0.0                 | 0.0                  |
| 2        | 12/15     | 15/15     | 64                | 12/15             | 24/15                            | 1.0                 | 0.0                  |
| 3        | 15/15     | 8/15      | 64                | 15/8              | 30/15                            | 1.5                 | 0.5                  |
| 4        | 15/15     | 4/15      | 64                | 15/4              | 30/15                            | 1.5                 | 0.5                  |

### Sub-Test for HSUPA

| SUB-TEST | $\beta_c$ | $\beta_d$ | $\beta_d$<br>(SF) | $\beta_c/\beta_d$ | $\beta_{HS}$<br>(Note 1) | $\beta_{ec}$ | $\beta_{ed}$<br>(Note 5)<br>(Note 6)         | $\beta_{ed}$<br>(SF) | $\beta_{ed}$<br>(Codes) | CM<br>(dB)<br>(Note 2) | MPR<br>(dB)<br>(Note 2) | AG<br>Index<br>(Note 6) | E-TFCI |
|----------|-----------|-----------|-------------------|-------------------|--------------------------|--------------|----------------------------------------------|----------------------|-------------------------|------------------------|-------------------------|-------------------------|--------|
| 1        | 11/15     | 15/15     | 64                | 11/15             | 22/15                    | 209/225      | 1309/225                                     | 4                    | 1                       | 1.0                    | 0.0                     | 20                      | 75     |
| 2        | 6/15      | 15/15     | 64                | 6/15              | 12/15                    | 12/15        | 94/75                                        | 4                    | 1                       | 3.0                    | 2.0                     | 12                      | 67     |
| 3        | 15/15     | 9/15      | 64                | 15/9              | 30/15                    | 30/15        | $\beta_{ed1}: 47/15$<br>$\beta_{ed2}: 47/15$ | 4<br>4               | 2                       | 2.0                    | 1.0                     | 15                      | 92     |
| 4        | 2/15      | 15/15     | 64                | 2/15              | 4/15                     | 2/15         | 56/75                                        | 4                    | 1                       | 3.0                    | 2.0                     | 17                      | 71     |
| 5        | 15/15     | 15/15     | 64                | 15/15             | 30/15                    | 24/15        | 134/15                                       | 4                    | 1                       | 1.0                    | 0.0                     | 21                      | 81     |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## LTE FDD Band V / VII power table:

| FDD Band 5 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |     |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|-----|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 10                        | QPSK       | 1 RB    | 0         | 829             | 20450   | 22.79                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 22.74                 | 24                                  | 0                        |     |
|                           |            |         |           | 844             | 20600   | 22.93                 | 24                                  | 0                        |     |
|                           |            |         | 25        | 829             | 20450   | 23.35                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 23.17                 | 24                                  | 0                        |     |
|                           |            |         |           | 844             | 20600   | 23.35                 | 24                                  | 0                        |     |
|                           |            |         | 49        | 829             | 20450   | 22.85                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 22.90                 | 24                                  | 0                        |     |
|                           |            |         |           | 844             | 20600   | 22.73                 | 24                                  | 0                        |     |
|                           |            | 25 RB   | 0         | 829             | 20450   | 22.20                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.29                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 844             | 20600   | 22.14                 | 23                                  | 0-1                      |     |
|                           |            |         | 12        | 829             | 20450   | 22.13                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.26                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 844             | 20600   | 22.09                 | 23                                  | 0-1                      |     |
|                           |            |         | 25        | 829             | 20450   | 22.18                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.28                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 844             | 20600   | 22.11                 | 23                                  | 0-1                      |     |
|                           |            | 50RB    |           |                 | 829     | 20450                 | 22.17                               | 23                       | 0-1 |
|                           |            |         |           |                 | 836.5   | 20525                 | 22.29                               | 23                       | 0-1 |
|                           |            |         |           |                 | 844     | 20600                 | 22.17                               | 23                       | 0-1 |
|                           | 16-QAM     | 1 RB    | 0         | 829             | 20450   | 21.91                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 21.64                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 844             | 20600   | 21.84                 | 23                                  | 0-1                      |     |
|                           |            |         | 25        | 829             | 20450   | 22.03                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.40                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 844             | 20600   | 22.05                 | 23                                  | 0-1                      |     |
|                           |            |         | 49        | 829             | 20450   | 21.90                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.20                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 844             | 20600   | 21.94                 | 23                                  | 0-1                      |     |
|                           |            | 25 RB   | 0         | 829             | 20450   | 21.38                 | 22                                  | 0-2                      |     |
|                           |            |         |           | 836.5           | 20525   | 21.21                 | 22                                  | 0-2                      |     |
|                           |            |         |           | 844             | 20600   | 21.34                 | 22                                  | 0-2                      |     |
|                           |            |         | 12        | 829             | 20450   | 20.97                 | 22                                  | 0-2                      |     |
|                           |            |         |           | 836.5           | 20525   | 21.14                 | 22                                  | 0-2                      |     |
|                           |            |         |           | 844             | 20600   | 21.03                 | 22                                  | 0-2                      |     |
|                           |            |         | 25        | 829             | 20450   | 21.22                 | 22                                  | 0-2                      |     |
|                           |            |         |           | 836.5           | 20525   | 21.43                 | 22                                  | 0-2                      |     |
|                           |            |         |           | 844             | 20600   | 21.03                 | 22                                  | 0-2                      |     |
|                           |            | 50RB    |           |                 | 829     | 20450                 | 21.20                               | 22                       | 0-2 |
|                           |            |         |           |                 | 836.5   | 20525                 | 21.35                               | 22                       | 0-2 |
|                           |            |         |           |                 | 844     | 20600                 | 21.22                               | 22                       | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 5 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5                         | QPSK       | 1 RB    | 0         | 826.5           | 20425   | 22.82                 | 24                                  | 0                        |
|                           |            |         |           | 836.5           | 20525   | 22.80                 | 24                                  | 0                        |
|                           |            |         |           | 846.5           | 20625   | 22.87                 | 24                                  | 0                        |
|                           |            |         | 12        | 826.5           | 20425   | 22.92                 | 24                                  | 0                        |
|                           |            |         |           | 836.5           | 20525   | 22.97                 | 24                                  | 0                        |
|                           |            |         |           | 846.5           | 20625   | 23.23                 | 24                                  | 0                        |
|                           |            |         | 24        | 826.5           | 20425   | 22.70                 | 24                                  | 0                        |
|                           |            |         |           | 836.5           | 20525   | 22.64                 | 24                                  | 0                        |
|                           |            |         |           | 846.5           | 20625   | 22.59                 | 24                                  | 0                        |
|                           |            | 12 RB   | 0         | 826.5           | 20425   | 22.24                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.22                 | 23                                  | 0-1                      |
|                           |            |         |           | 846.5           | 20625   | 22.22                 | 23                                  | 0-1                      |
|                           |            |         | 6         | 826.5           | 20425   | 22.30                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.27                 | 23                                  | 0-1                      |
|                           |            |         |           | 846.5           | 20625   | 22.27                 | 23                                  | 0-1                      |
|                           |            |         | 13        | 826.5           | 20425   | 22.18                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.18                 | 23                                  | 0-1                      |
|                           |            |         |           | 846.5           | 20625   | 22.17                 | 23                                  | 0-1                      |
|                           |            |         | 25RB      | 826.5           | 20425   | 22.19                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.15                 | 23                                  | 0-1                      |
|                           |            |         |           | 846.5           | 20625   | 22.14                 | 23                                  | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 826.5           | 20425   | 21.67                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 21.91                 | 23                                  | 0-1                      |
|                           |            |         |           | 846.5           | 20625   | 22.16                 | 23                                  | 0-1                      |
|                           |            |         | 12        | 826.5           | 20425   | 22.25                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 21.60                 | 23                                  | 0-1                      |
|                           |            |         |           | 846.5           | 20625   | 22.07                 | 23                                  | 0-1                      |
|                           |            |         | 24        | 826.5           | 20425   | 21.85                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 21.82                 | 23                                  | 0-1                      |
|                           |            |         |           | 846.5           | 20625   | 21.64                 | 23                                  | 0-1                      |
|                           |            | 12 RB   | 0         | 826.5           | 20425   | 21.14                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.28                 | 22                                  | 0-2                      |
|                           |            |         |           | 846.5           | 20625   | 21.15                 | 22                                  | 0-2                      |
|                           |            |         | 6         | 826.5           | 20425   | 21.10                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.13                 | 22                                  | 0-2                      |
|                           |            |         |           | 846.5           | 20625   | 21.20                 | 22                                  | 0-2                      |
|                           |            |         | 13        | 826.5           | 20425   | 20.95                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.19                 | 22                                  | 0-2                      |
|                           |            |         |           | 846.5           | 20625   | 21.18                 | 22                                  | 0-2                      |
|                           |            |         | 25RB      | 826.5           | 20425   | 21.24                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.15                 | 22                                  | 0-2                      |
|                           |            |         |           | 846.5           | 20625   | 21.12                 | 22                                  | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 5 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 3                         | QPSK       | 1 RB    | 0         | 825.5           | 20415   | 23.25                 | 24                                  | 0                        |
|                           |            |         |           | 836.5           | 20525   | 23.07                 | 24                                  | 0                        |
|                           |            |         |           | 847.5           | 20635   | 23.22                 | 24                                  | 0                        |
|                           |            |         | 7         | 825.5           | 20415   | 23.24                 | 24                                  | 0                        |
|                           |            |         |           | 836.5           | 20525   | 22.98                 | 24                                  | 0                        |
|                           |            |         |           | 847.5           | 20635   | 23.18                 | 24                                  | 0                        |
|                           |            |         | 14        | 825.5           | 20415   | 23.10                 | 24                                  | 0                        |
|                           |            |         |           | 836.5           | 20525   | 23.12                 | 24                                  | 0                        |
|                           |            |         |           | 847.5           | 20635   | 23.11                 | 24                                  | 0                        |
|                           |            | 8 RB    | 0         | 825.5           | 20415   | 22.18                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.13                 | 23                                  | 0-1                      |
|                           |            |         |           | 847.5           | 20635   | 22.26                 | 23                                  | 0-1                      |
|                           |            |         | 4         | 825.5           | 20415   | 22.21                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.07                 | 23                                  | 0-1                      |
|                           |            |         |           | 847.5           | 20635   | 22.17                 | 23                                  | 0-1                      |
|                           |            |         | 7         | 825.5           | 20415   | 22.25                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.06                 | 23                                  | 0-1                      |
|                           |            |         |           | 847.5           | 20635   | 22.14                 | 23                                  | 0-1                      |
|                           |            |         | 15RB      | 825.5           | 20415   | 22.22                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.19                 | 23                                  | 0-1                      |
|                           |            |         |           | 847.5           | 20635   | 22.08                 | 23                                  | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 825.5           | 20415   | 22.38                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 21.83                 | 23                                  | 0-1                      |
|                           |            |         |           | 847.5           | 20635   | 22.09                 | 23                                  | 0-1                      |
|                           |            |         | 7         | 825.5           | 20415   | 22.00                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 22.14                 | 23                                  | 0-1                      |
|                           |            |         |           | 847.5           | 20635   | 22.22                 | 23                                  | 0-1                      |
|                           |            |         | 14        | 825.5           | 20415   | 21.84                 | 23                                  | 0-1                      |
|                           |            |         |           | 836.5           | 20525   | 21.97                 | 23                                  | 0-1                      |
|                           |            |         |           | 847.5           | 20635   | 22.11                 | 23                                  | 0-1                      |
|                           |            | 8 RB    | 0         | 825.5           | 20415   | 21.28                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.54                 | 22                                  | 0-2                      |
|                           |            |         |           | 847.5           | 20635   | 21.27                 | 22                                  | 0-2                      |
|                           |            |         | 4         | 825.5           | 20415   | 21.35                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.02                 | 22                                  | 0-2                      |
|                           |            |         |           | 847.5           | 20635   | 21.08                 | 22                                  | 0-2                      |
|                           |            |         | 7         | 825.5           | 20415   | 21.40                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.20                 | 22                                  | 0-2                      |
|                           |            |         |           | 847.5           | 20635   | 21.21                 | 22                                  | 0-2                      |
|                           |            |         | 15RB      | 825.5           | 20415   | 21.07                 | 22                                  | 0-2                      |
|                           |            |         |           | 836.5           | 20525   | 21.06                 | 22                                  | 0-2                      |
|                           |            |         |           | 847.5           | 20635   | 21.16                 | 22                                  | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 5 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |     |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|-----|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |     |
| 1.4                       | QPSK       | 1 RB    | 0         | 824.7           | 20407   | 23.11                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 22.82                 | 24                                  | 0                        |     |
|                           |            |         |           | 848.3           | 20643   | 23.03                 | 24                                  | 0                        |     |
|                           |            |         | 2         | 824.7           | 20407   | 23.18                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 22.83                 | 24                                  | 0                        |     |
|                           |            |         |           | 848.3           | 20643   | 23.31                 | 24                                  | 0                        |     |
|                           |            |         | 5         | 824.7           | 20407   | 23.11                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 22.81                 | 24                                  | 0                        |     |
|                           |            |         |           | 848.3           | 20643   | 23.19                 | 24                                  | 0                        |     |
|                           |            | 3 RB    | 0         | 824.7           | 20407   | 23.18                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 23.09                 | 24                                  | 0                        |     |
|                           |            |         |           | 848.3           | 20643   | 23.00                 | 24                                  | 0                        |     |
|                           |            |         | 2         | 824.7           | 20407   | 23.12                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 23.14                 | 24                                  | 0                        |     |
|                           |            |         |           | 848.3           | 20643   | 23.00                 | 24                                  | 0                        |     |
|                           |            |         | 3         | 824.7           | 20407   | 23.13                 | 24                                  | 0                        |     |
|                           |            |         |           | 836.5           | 20525   | 23.11                 | 24                                  | 0                        |     |
|                           |            |         |           | 848.3           | 20643   | 23.16                 | 24                                  | 0                        |     |
|                           |            | 6RB     |           |                 | 824.7   | 20407                 | 22.18                               | 23                       | 0-1 |
|                           |            |         |           |                 | 836.5   | 20525                 | 22.08                               | 23                       | 0-1 |
|                           |            |         |           |                 | 848.3   | 20643                 | 22.05                               | 23                       | 0-1 |
|                           | 16-QAM     | 1 RB    | 0         | 824.7           | 20407   | 22.03                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.02                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 848.3           | 20643   | 22.01                 | 23                                  | 0-1                      |     |
|                           |            |         | 2         | 824.7           | 20407   | 21.97                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 21.88                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 848.3           | 20643   | 21.92                 | 23                                  | 0-1                      |     |
|                           |            |         | 5         | 824.7           | 20407   | 22.26                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 21.87                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 848.3           | 20643   | 22.13                 | 23                                  | 0-1                      |     |
|                           |            |         | 3 RB      | 0               | 824.7   | 20407                 | 21.64                               | 23                       | 0-1 |
|                           |            |         |           |                 | 836.5   | 20525                 | 22.00                               | 23                       | 0-1 |
|                           |            |         |           |                 | 848.3   | 20643                 | 22.04                               | 23                       | 0-1 |
|                           |            | 2       |           | 824.7           | 20407   | 21.91                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.00                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 848.3           | 20643   | 22.40                 | 23                                  | 0-1                      |     |
|                           |            | 3       |           | 824.7           | 20407   | 22.10                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 836.5           | 20525   | 22.10                 | 23                                  | 0-1                      |     |
|                           |            |         |           | 848.3           | 20643   | 22.10                 | 23                                  | 0-1                      |     |
|                           |            | 6RB     |           |                 | 824.7   | 20407                 | 20.98                               | 22                       | 0-2 |
|                           |            |         |           |                 | 836.5   | 20525                 | 20.79                               | 22                       | 0-2 |
|                           |            |         |           |                 | 848.3   | 20643                 | 20.98                               | 22                       | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 5 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 10                       | QPSK       | 1 RB    | 0         | 829             | 20450   | 20.72                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 20.76                 | 22                                  | 0                        |
|                          |            |         |           | 844             | 20600   | 20.64                 | 22                                  | 0                        |
|                          |            |         | 25        | 829             | 20450   | 20.92                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.12                 | 22                                  | 0                        |
|                          |            |         |           | 844             | 20600   | 21.18                 | 22                                  | 0                        |
|                          |            |         | 49        | 829             | 20450   | 20.86                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 20.83                 | 22                                  | 0                        |
|                          |            |         |           | 844             | 20600   | 20.64                 | 22                                  | 0                        |
|                          |            | 25 RB   | 0         | 829             | 20450   | 20.09                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.08                 | 21                                  | 0-1                      |
|                          |            |         |           | 844             | 20600   | 20.11                 | 21                                  | 0-1                      |
|                          |            |         | 12        | 829             | 20450   | 20.06                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.16                 | 21                                  | 0-1                      |
|                          |            |         |           | 844             | 20600   | 20.15                 | 21                                  | 0-1                      |
|                          |            |         | 25        | 829             | 20450   | 20.00                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.12                 | 21                                  | 0-1                      |
|                          |            |         |           | 844             | 20600   | 20.07                 | 21                                  | 0-1                      |
|                          |            | 50RB    |           | 829             | 20450   | 20.05                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.10                 | 21                                  | 0-1                      |
|                          |            |         |           | 844             | 20600   | 20.16                 | 21                                  | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 829             | 20450   | 19.71                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 19.73                 | 21                                  | 0-1                      |
|                          |            |         |           | 844             | 20600   | 19.63                 | 21                                  | 0-1                      |
|                          |            |         | 25        | 829             | 20450   | 19.76                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.12                 | 21                                  | 0-1                      |
|                          |            |         |           | 844             | 20600   | 20.26                 | 21                                  | 0-1                      |
|                          |            |         | 49        | 829             | 20450   | 19.73                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 19.46                 | 21                                  | 0-1                      |
|                          |            |         |           | 844             | 20600   | 19.75                 | 21                                  | 0-1                      |
|                          |            | 25 RB   | 0         | 829             | 20450   | 19.04                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.05                 | 20                                  | 0-2                      |
|                          |            |         |           | 844             | 20600   | 19.01                 | 20                                  | 0-2                      |
|                          |            |         | 12        | 829             | 20450   | 18.94                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.24                 | 20                                  | 0-2                      |
|                          |            |         |           | 844             | 20600   | 19.00                 | 20                                  | 0-2                      |
|                          |            |         | 25        | 829             | 20450   | 19.10                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.03                 | 20                                  | 0-2                      |
|                          |            |         |           | 844             | 20600   | 18.93                 | 20                                  | 0-2                      |
|                          |            | 50RB    |           | 829             | 20450   | 19.11                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.21                 | 20                                  | 0-2                      |
|                          |            |         |           | 844             | 20600   | 19.00                 | 20                                  | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 5 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5                        | QPSK       | 1 RB    | 0         | 826.5           | 20425   | 20.64                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 20.63                 | 22                                  | 0                        |
|                          |            |         |           | 846.5           | 20625   | 20.86                 | 22                                  | 0                        |
|                          |            |         | 12        | 826.5           | 20425   | 21.15                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.24                 | 22                                  | 0                        |
|                          |            |         |           | 846.5           | 20625   | 21.22                 | 22                                  | 0                        |
|                          |            |         | 24        | 826.5           | 20425   | 20.56                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 20.71                 | 22                                  | 0                        |
|                          |            |         |           | 846.5           | 20625   | 20.67                 | 22                                  | 0                        |
|                          |            | 12 RB   | 0         | 826.5           | 20425   | 20.10                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.16                 | 21                                  | 0-1                      |
|                          |            |         |           | 846.5           | 20625   | 20.11                 | 21                                  | 0-1                      |
|                          |            |         | 6         | 826.5           | 20425   | 20.10                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.14                 | 21                                  | 0-1                      |
|                          |            |         |           | 846.5           | 20625   | 20.09                 | 21                                  | 0-1                      |
|                          |            |         | 13        | 826.5           | 20425   | 20.05                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.11                 | 21                                  | 0-1                      |
|                          |            |         |           | 846.5           | 20625   | 20.04                 | 21                                  | 0-1                      |
|                          |            | 25RB    |           | 826.5           | 20425   | 20.08                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.14                 | 21                                  | 0-1                      |
|                          |            |         |           | 846.5           | 20625   | 20.05                 | 21                                  | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 826.5           | 20425   | 19.60                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 19.68                 | 21                                  | 0-1                      |
|                          |            |         |           | 846.5           | 20625   | 19.44                 | 21                                  | 0-1                      |
|                          |            |         | 12        | 826.5           | 20425   | 20.24                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.14                 | 21                                  | 0-1                      |
|                          |            |         |           | 846.5           | 20625   | 20.41                 | 21                                  | 0-1                      |
|                          |            |         | 24        | 826.5           | 20425   | 19.78                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 19.50                 | 21                                  | 0-1                      |
|                          |            |         |           | 846.5           | 20625   | 19.96                 | 21                                  | 0-1                      |
|                          |            | 12 RB   | 0         | 826.5           | 20425   | 18.80                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.11                 | 20                                  | 0-2                      |
|                          |            |         |           | 846.5           | 20625   | 19.11                 | 20                                  | 0-2                      |
|                          |            |         | 6         | 826.5           | 20425   | 18.92                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.17                 | 20                                  | 0-2                      |
|                          |            |         |           | 846.5           | 20625   | 19.12                 | 20                                  | 0-2                      |
|                          |            |         | 13        | 826.5           | 20425   | 18.85                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.12                 | 20                                  | 0-2                      |
|                          |            |         |           | 846.5           | 20625   | 19.06                 | 20                                  | 0-2                      |
|                          |            | 25RB    |           | 826.5           | 20425   | 19.02                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.19                 | 20                                  | 0-2                      |
|                          |            |         |           | 846.5           | 20625   | 19.02                 | 20                                  | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 5 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 3                        | QPSK       | 1 RB    | 0         | 825.5           | 20415   | 20.80                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 20.72                 | 22                                  | 0                        |
|                          |            |         |           | 847.5           | 20635   | 20.96                 | 22                                  | 0                        |
|                          |            |         | 7         | 825.5           | 20415   | 21.15                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.41                 | 22                                  | 0                        |
|                          |            |         |           | 847.5           | 20635   | 20.97                 | 22                                  | 0                        |
|                          |            |         | 14        | 825.5           | 20415   | 20.91                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.10                 | 22                                  | 0                        |
|                          |            |         |           | 847.5           | 20635   | 20.80                 | 22                                  | 0                        |
|                          |            | 8 RB    | 0         | 825.5           | 20415   | 20.07                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.10                 | 21                                  | 0-1                      |
|                          |            |         |           | 847.5           | 20635   | 20.09                 | 21                                  | 0-1                      |
|                          |            |         | 4         | 825.5           | 20415   | 20.16                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.13                 | 21                                  | 0-1                      |
|                          |            |         |           | 847.5           | 20635   | 20.02                 | 21                                  | 0-1                      |
|                          |            |         | 7         | 825.5           | 20415   | 19.95                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.16                 | 21                                  | 0-1                      |
|                          |            |         |           | 847.5           | 20635   | 20.15                 | 21                                  | 0-1                      |
|                          |            | 15RB    |           | 825.5           | 20415   | 20.04                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.05                 | 21                                  | 0-1                      |
|                          |            |         |           | 847.5           | 20635   | 20.02                 | 21                                  | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 825.5           | 20415   | 19.86                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 19.43                 | 21                                  | 0-1                      |
|                          |            |         |           | 847.5           | 20635   | 20.08                 | 21                                  | 0-1                      |
|                          |            |         | 7         | 825.5           | 20415   | 19.73                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.56                 | 21                                  | 0-1                      |
|                          |            |         |           | 847.5           | 20635   | 20.15                 | 21                                  | 0-1                      |
|                          |            |         | 14        | 825.5           | 20415   | 20.05                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 19.72                 | 21                                  | 0-1                      |
|                          |            |         |           | 847.5           | 20635   | 19.76                 | 21                                  | 0-1                      |
|                          |            | 8 RB    | 0         | 825.5           | 20415   | 19.24                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 18.89                 | 20                                  | 0-2                      |
|                          |            |         |           | 847.5           | 20635   | 18.70                 | 20                                  | 0-2                      |
|                          |            |         | 4         | 825.5           | 20415   | 19.01                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.14                 | 20                                  | 0-2                      |
|                          |            |         |           | 847.5           | 20635   | 18.97                 | 20                                  | 0-2                      |
|                          |            |         | 7         | 825.5           | 20415   | 19.04                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.21                 | 20                                  | 0-2                      |
|                          |            |         |           | 847.5           | 20635   | 18.87                 | 20                                  | 0-2                      |
|                          |            | 15RB    |           | 825.5           | 20415   | 18.83                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 18.90                 | 20                                  | 0-2                      |
|                          |            |         |           | 847.5           | 20635   | 18.86                 | 20                                  | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| FDD Band 5 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 1.4                      | QPSK       | 1 RB    | 0         | 824.7           | 20407   | 21.10                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.04                 | 22                                  | 0                        |
|                          |            |         |           | 848.3           | 20643   | 20.98                 | 22                                  | 0                        |
|                          |            |         | 2         | 824.7           | 20407   | 21.16                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.15                 | 22                                  | 0                        |
|                          |            |         |           | 848.3           | 20643   | 21.10                 | 22                                  | 0                        |
|                          |            |         | 5         | 824.7           | 20407   | 20.95                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.08                 | 22                                  | 0                        |
|                          |            |         |           | 848.3           | 20643   | 21.11                 | 22                                  | 0                        |
|                          |            | 3 RB    | 0         | 824.7           | 20407   | 21.21                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.04                 | 22                                  | 0                        |
|                          |            |         |           | 848.3           | 20643   | 21.20                 | 22                                  | 0                        |
|                          |            |         | 2         | 824.7           | 20407   | 21.38                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.26                 | 22                                  | 0                        |
|                          |            |         |           | 848.3           | 20643   | 21.08                 | 22                                  | 0                        |
|                          |            |         | 3         | 824.7           | 20407   | 21.26                 | 22                                  | 0                        |
|                          |            |         |           | 836.5           | 20525   | 21.30                 | 22                                  | 0                        |
|                          |            |         |           | 848.3           | 20643   | 21.07                 | 22                                  | 0                        |
|                          |            | 6RB     |           | 824.7           | 20407   | 20.10                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.11                 | 21                                  | 0-1                      |
|                          |            |         |           | 848.3           | 20643   | 20.01                 | 21                                  | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 824.7           | 20407   | 19.74                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 19.81                 | 21                                  | 0-1                      |
|                          |            |         |           | 848.3           | 20643   | 19.83                 | 21                                  | 0-1                      |
|                          |            |         | 2         | 824.7           | 20407   | 19.80                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.51                 | 21                                  | 0-1                      |
|                          |            |         |           | 848.3           | 20643   | 19.77                 | 21                                  | 0-1                      |
|                          |            |         | 5         | 824.7           | 20407   | 20.08                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.45                 | 21                                  | 0-1                      |
|                          |            |         |           | 848.3           | 20643   | 20.03                 | 21                                  | 0-1                      |
|                          |            | 3 RB    | 0         | 824.7           | 20407   | 20.31                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.05                 | 21                                  | 0-1                      |
|                          |            |         |           | 848.3           | 20643   | 19.86                 | 21                                  | 0-1                      |
|                          |            |         | 2         | 824.7           | 20407   | 20.29                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.10                 | 21                                  | 0-1                      |
|                          |            |         |           | 848.3           | 20643   | 20.01                 | 21                                  | 0-1                      |
|                          |            |         | 3         | 824.7           | 20407   | 20.27                 | 21                                  | 0-1                      |
|                          |            |         |           | 836.5           | 20525   | 20.00                 | 21                                  | 0-1                      |
|                          |            |         |           | 848.3           | 20643   | 19.95                 | 21                                  | 0-1                      |
|                          |            | 6RB     |           | 824.7           | 20407   | 19.12                 | 20                                  | 0-2                      |
|                          |            |         |           | 836.5           | 20525   | 19.03                 | 20                                  | 0-2                      |
|                          |            |         |           | 848.3           | 20643   | 18.76                 | 20                                  | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 7 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 20                        | QPSK       | 1 RB    | 0         | 2510            | 20850   | 22.65                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 22.81                 | 23.5                                | 0                        |
|                           |            |         |           | 2560            | 21350   | 22.74                 | 23.5                                | 0                        |
|                           |            |         | 50        | 2510            | 20850   | 23.26                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 23.24                 | 23.5                                | 0                        |
|                           |            |         |           | 2560            | 21350   | 23.44                 | 23.5                                | 0                        |
|                           |            |         | 99        | 2510            | 20850   | 23.27                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 23.09                 | 23.5                                | 0                        |
|                           |            |         |           | 2560            | 21350   | 23.13                 | 23.5                                | 0                        |
|                           |            | 50 RB   | 0         | 2510            | 20850   | 22.09                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.90                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2560            | 21350   | 22.19                 | 22.5                                | 0-1                      |
|                           |            |         | 25        | 2510            | 20850   | 22.01                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.15                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2560            | 21350   | 22.28                 | 22.5                                | 0-1                      |
|                           |            |         | 50        | 2510            | 20850   | 22.10                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.07                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2560            | 21350   | 22.32                 | 22.5                                | 0-1                      |
|                           |            | 100RB   |           | 2510            | 20850   | 22.03                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.12                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2560            | 21350   | 22.35                 | 22.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2510            | 20850   | 21.92                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.13                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2560            | 21350   | 22.23                 | 22.5                                | 0-1                      |
|                           |            |         | 50        | 2510            | 20850   | 22.36                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.13                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2560            | 21350   | 21.95                 | 22.5                                | 0-1                      |
|                           |            |         | 99        | 2510            | 20850   | 21.74                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.13                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2560            | 21350   | 22.36                 | 22.5                                | 0-1                      |
|                           |            | 50 RB   | 0         | 2510            | 20850   | 21.13                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 20.95                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2560            | 21350   | 21.25                 | 21.5                                | 0-2                      |
|                           |            |         | 25        | 2510            | 20850   | 21.24                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.24                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2560            | 21350   | 21.36                 | 21.5                                | 0-2                      |
|                           |            |         | 50        | 2510            | 20850   | 21.18                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.25                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2560            | 21350   | 21.32                 | 21.5                                | 0-2                      |
|                           |            | 100RB   |           | 2510            | 20850   | 21.18                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.18                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2560            | 21350   | 21.33                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| FDD Band 7 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 15                        | QPSK       | 1 RB    | 0         | 2507.5          | 20825   | 23.14                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 22.93                 | 23.5                                | 0                        |
|                           |            |         |           | 2562.5          | 21375   | 23.21                 | 23.5                                | 0                        |
|                           |            |         | 36        | 2507.5          | 20825   | 23.42                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 23.27                 | 23.5                                | 0                        |
|                           |            |         |           | 2562.5          | 21375   | 23.29                 | 23.5                                | 0                        |
|                           |            |         | 74        | 2507.5          | 20825   | 23.04                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 22.96                 | 23.5                                | 0                        |
|                           |            |         |           | 2562.5          | 21375   | 23.42                 | 23.5                                | 0                        |
|                           |            | 36 RB   | 0         | 2507.5          | 20825   | 22.20                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.99                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2562.5          | 21375   | 22.20                 | 22.5                                | 0-1                      |
|                           |            |         | 18        | 2507.5          | 20825   | 22.23                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.11                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2562.5          | 21375   | 22.48                 | 22.5                                | 0-1                      |
|                           |            |         | 37        | 2507.5          | 20825   | 22.25                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.19                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2562.5          | 21375   | 22.40                 | 22.5                                | 0-1                      |
|                           |            |         | 75RB      | 2507.5          | 20825   | 22.16                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.99                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2562.5          | 21375   | 22.33                 | 22.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2507.5          | 20825   | 22.05                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.77                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2562.5          | 21375   | 21.87                 | 22.5                                | 0-1                      |
|                           |            |         | 36        | 2507.5          | 20825   | 22.28                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.89                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2562.5          | 21375   | 22.39                 | 22.5                                | 0-1                      |
|                           |            |         | 74        | 2507.5          | 20825   | 22.07                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.93                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2562.5          | 21375   | 22.47                 | 22.5                                | 0-1                      |
|                           |            | 36 RB   | 0         | 2507.5          | 20825   | 21.28                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 20.92                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2562.5          | 21375   | 21.19                 | 21.5                                | 0-2                      |
|                           |            |         | 18        | 2507.5          | 20825   | 21.30                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.18                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2562.5          | 21375   | 21.36                 | 21.5                                | 0-2                      |
|                           |            |         | 37        | 2507.5          | 20825   | 21.35                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.12                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2562.5          | 21375   | 21.43                 | 21.5                                | 0-2                      |
|                           |            |         | 75RB      | 2507.5          | 20825   | 21.24                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.14                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2562.5          | 21375   | 21.23                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 7 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 10                        | QPSK       | 1 RB    | 0         | 2505            | 20800   | 23.06                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 22.56                 | 23.5                                | 0                        |
|                           |            |         |           | 2565            | 21400   | 22.72                 | 23.5                                | 0                        |
|                           |            |         | 25        | 2505            | 20800   | 23.34                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 23.43                 | 23.5                                | 0                        |
|                           |            |         |           | 2565            | 21400   | 23.43                 | 23.5                                | 0                        |
|                           |            |         | 49        | 2505            | 20800   | 23.41                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 22.89                 | 23.5                                | 0                        |
|                           |            |         |           | 2565            | 21400   | 23.26                 | 23.5                                | 0                        |
|                           |            | 25 RB   | 0         | 2505            | 20800   | 22.09                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.98                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2565            | 21400   | 22.35                 | 22.5                                | 0-1                      |
|                           |            |         | 12        | 2505            | 20800   | 22.30                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.27                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2565            | 21400   | 22.39                 | 22.5                                | 0-1                      |
|                           |            |         | 25        | 2505            | 20800   | 22.32                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.13                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2565            | 21400   | 22.41                 | 22.5                                | 0-1                      |
|                           |            | 50RB    |           | 2505            | 20800   | 22.26                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.15                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2565            | 21400   | 22.44                 | 22.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2505            | 20800   | 22.47                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.67                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2565            | 21400   | 22.00                 | 22.5                                | 0-1                      |
|                           |            |         | 25        | 2505            | 20800   | 22.32                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.41                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2565            | 21400   | 22.49                 | 22.5                                | 0-1                      |
|                           |            |         | 49        | 2505            | 20800   | 22.12                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.23                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2565            | 21400   | 22.39                 | 22.5                                | 0-1                      |
|                           |            | 25 RB   | 0         | 2505            | 20800   | 21.41                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.38                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2565            | 21400   | 21.46                 | 21.5                                | 0-2                      |
|                           |            |         | 12        | 2505            | 20800   | 21.50                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.46                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2565            | 21400   | 21.42                 | 21.5                                | 0-2                      |
|                           |            |         | 25        | 2505            | 20800   | 21.48                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.19                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2565            | 21400   | 21.45                 | 21.5                                | 0-2                      |
|                           |            | 50RB    |           | 2505            | 20800   | 21.29                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.31                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2565            | 21400   | 21.48                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| FDD Band 7 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5                         | QPSK       | 1 RB    | 0         | 2502.5          | 20775   | 23.37                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 22.78                 | 23.5                                | 0                        |
|                           |            |         |           | 2567.5          | 21425   | 22.89                 | 23.5                                | 0                        |
|                           |            |         | 12        | 2502.5          | 20775   | 23.25                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 23.42                 | 23.5                                | 0                        |
|                           |            |         |           | 2567.5          | 21425   | 23.43                 | 23.5                                | 0                        |
|                           |            |         | 24        | 2502.5          | 20775   | 23.30                 | 23.5                                | 0                        |
|                           |            |         |           | 2535            | 21100   | 22.81                 | 23.5                                | 0                        |
|                           |            |         |           | 2567.5          | 21425   | 23.19                 | 23.5                                | 0                        |
|                           |            | 12 RB   | 0         | 2502.5          | 20775   | 22.25                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.17                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2567.5          | 21425   | 22.40                 | 22.5                                | 0-1                      |
|                           |            |         | 6         | 2502.5          | 20775   | 22.34                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.28                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2567.5          | 21425   | 22.45                 | 22.5                                | 0-1                      |
|                           |            |         | 13        | 2502.5          | 20775   | 22.23                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.17                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2567.5          | 21425   | 22.50                 | 22.5                                | 0-1                      |
|                           |            |         | 25RB      | 2502.5          | 20775   | 22.34                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.25                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2567.5          | 21425   | 22.41                 | 22.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2502.5          | 20775   | 22.40                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 21.77                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2567.5          | 21425   | 22.22                 | 22.5                                | 0-1                      |
|                           |            |         | 12        | 2502.5          | 20775   | 21.94                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.27                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2567.5          | 21425   | 22.38                 | 22.5                                | 0-1                      |
|                           |            |         | 24        | 2502.5          | 20775   | 22.20                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2535            | 21100   | 22.09                 | 22.5                                | 0-1                      |
|                           |            |         |           | 2567.5          | 21425   | 22.20                 | 22.5                                | 0-1                      |
|                           |            | 12 RB   | 0         | 2502.5          | 20775   | 21.46                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.07                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2567.5          | 21425   | 21.39                 | 21.5                                | 0-2                      |
|                           |            |         | 6         | 2502.5          | 20775   | 21.31                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.15                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2567.5          | 21425   | 21.34                 | 21.5                                | 0-2                      |
|                           |            |         | 13        | 2502.5          | 20775   | 21.18                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.05                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2567.5          | 21425   | 21.44                 | 21.5                                | 0-2                      |
|                           |            |         | 25RB      | 2502.5          | 20775   | 21.24                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2535            | 21100   | 21.33                 | 21.5                                | 0-2                      |
|                           |            |         |           | 2567.5          | 21425   | 21.40                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 7 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 20                       | QPSK       | 1 RB    | 0         | 2510            | 20850   | 16.78                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 16.67                 | 17.5                                | 0                        |
|                          |            |         |           | 2560            | 21350   | 16.77                 | 17.5                                | 0                        |
|                          |            |         | 50        | 2510            | 20850   | 17.50                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 17.31                 | 17.5                                | 0                        |
|                          |            |         |           | 2560            | 21350   | 17.27                 | 17.5                                | 0                        |
|                          |            |         | 99        | 2510            | 20850   | 16.90                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 16.96                 | 17.5                                | 0                        |
|                          |            |         |           | 2560            | 21350   | 17.29                 | 17.5                                | 0                        |
|                          |            | 50 RB   | 0         | 2510            | 20850   | 16.10                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.27                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2560            | 21350   | 16.04                 | 16.5                                | 0-1                      |
|                          |            |         | 25        | 2510            | 20850   | 16.13                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.17                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2560            | 21350   | 16.12                 | 16.5                                | 0-1                      |
|                          |            |         | 50        | 2510            | 20850   | 16.13                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.11                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2560            | 21350   | 16.26                 | 16.5                                | 0-1                      |
|                          |            | 100RB   |           | 2510            | 20850   | 16.15                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.22                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2560            | 21350   | 16.07                 | 16.5                                | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 2510            | 20850   | 16.10                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.07                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2560            | 21350   | 16.10                 | 16.5                                | 0-1                      |
|                          |            |         | 50        | 2510            | 20850   | 16.41                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 14.62                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2560            | 21350   | 15.94                 | 16.5                                | 0-1                      |
|                          |            |         | 99        | 2510            | 20850   | 16.03                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 15.79                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2560            | 21350   | 16.25                 | 16.5                                | 0-1                      |
|                          |            | 50 RB   | 0         | 2510            | 20850   | 15.17                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.14                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2560            | 21350   | 15.08                 | 15.5                                | 0-2                      |
|                          |            |         | 25        | 2510            | 20850   | 15.25                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.18                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2560            | 21350   | 15.22                 | 15.5                                | 0-2                      |
|                          |            |         | 50        | 2510            | 20850   | 15.22                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.21                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2560            | 21350   | 15.33                 | 15.5                                | 0-2                      |
|                          |            | 100RB   |           | 2510            | 20850   | 15.14                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.17                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2560            | 21350   | 15.11                 | 15.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| FDD Band 7 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 15                       | QPSK       | 1 RB    | 0         | 2507.5          | 20825   | 16.96                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 16.86                 | 17.5                                | 0                        |
|                          |            |         |           | 2562.5          | 21375   | 16.87                 | 17.5                                | 0                        |
|                          |            |         | 36        | 2507.5          | 20825   | 17.31                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 16.85                 | 17.5                                | 0                        |
|                          |            |         |           | 2562.5          | 21375   | 17.34                 | 17.5                                | 0                        |
|                          |            |         | 74        | 2507.5          | 20825   | 17.30                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 17.21                 | 17.5                                | 0                        |
|                          |            |         |           | 2562.5          | 21375   | 17.26                 | 17.5                                | 0                        |
|                          |            | 36 RB   | 0         | 2507.5          | 20825   | 16.14                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.21                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2562.5          | 21375   | 16.07                 | 16.5                                | 0-1                      |
|                          |            |         | 18        | 2507.5          | 20825   | 16.13                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.22                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2562.5          | 21375   | 16.25                 | 16.5                                | 0-1                      |
|                          |            |         | 37        | 2507.5          | 20825   | 16.18                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.27                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2562.5          | 21375   | 16.22                 | 16.5                                | 0-1                      |
|                          |            |         | 75RB      | 2507.5          | 20825   | 16.17                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.17                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2562.5          | 21375   | 16.13                 | 16.5                                | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 2507.5          | 20825   | 16.17                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.09                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2562.5          | 21375   | 15.85                 | 16.5                                | 0-1                      |
|                          |            |         | 36        | 2507.5          | 20825   | 15.92                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.18                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2562.5          | 21375   | 16.35                 | 16.5                                | 0-1                      |
|                          |            |         | 74        | 2507.5          | 20825   | 15.73                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.16                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2562.5          | 21375   | 16.38                 | 16.5                                | 0-1                      |
|                          |            | 36 RB   | 0         | 2507.5          | 20825   | 15.14                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.35                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2562.5          | 21375   | 15.11                 | 15.5                                | 0-2                      |
|                          |            |         | 18        | 2507.5          | 20825   | 15.23                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.18                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2562.5          | 21375   | 15.35                 | 15.5                                | 0-2                      |
|                          |            |         | 37        | 2507.5          | 20825   | 15.31                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.20                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2562.5          | 21375   | 15.21                 | 15.5                                | 0-2                      |
|                          |            |         | 75RB      | 2507.5          | 20825   | 15.32                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.24                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2562.5          | 21375   | 15.06                 | 15.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 7 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 10                       | QPSK       | 1 RB    | 0         | 2505            | 20800   | 16.85                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 16.87                 | 17.5                                | 0                        |
|                          |            |         |           | 2565            | 21400   | 16.93                 | 17.5                                | 0                        |
|                          |            |         | 25        | 2505            | 20800   | 17.35                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 17.04                 | 17.5                                | 0                        |
|                          |            |         |           | 2565            | 21400   | 17.39                 | 17.5                                | 0                        |
|                          |            |         | 49        | 2505            | 20800   | 17.27                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 17.11                 | 17.5                                | 0                        |
|                          |            |         |           | 2565            | 21400   | 17.26                 | 17.5                                | 0                        |
|                          |            | 25 RB   | 0         | 2505            | 20800   | 16.12                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.20                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2565            | 21400   | 16.23                 | 16.5                                | 0-1                      |
|                          |            |         | 12        | 2505            | 20800   | 16.21                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.20                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2565            | 21400   | 16.22                 | 16.5                                | 0-1                      |
|                          |            |         | 25        | 2505            | 20800   | 16.24                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.14                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2565            | 21400   | 16.38                 | 16.5                                | 0-1                      |
|                          |            | 50RB    |           | 2505            | 20800   | 16.14                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.20                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2565            | 21400   | 16.30                 | 16.5                                | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 2505            | 20800   | 15.96                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 15.98                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2565            | 21400   | 16.36                 | 16.5                                | 0-1                      |
|                          |            |         | 25        | 2505            | 20800   | 15.93                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.42                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2565            | 21400   | 16.47                 | 16.5                                | 0-1                      |
|                          |            |         | 49        | 2505            | 20800   | 15.97                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.28                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2565            | 21400   | 16.49                 | 16.5                                | 0-1                      |
|                          |            | 25 RB   | 0         | 2505            | 20800   | 15.26                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.13                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2565            | 21400   | 15.45                 | 15.5                                | 0-2                      |
|                          |            |         | 12        | 2505            | 20800   | 15.39                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.19                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2565            | 21400   | 15.27                 | 15.5                                | 0-2                      |
|                          |            |         | 25        | 2505            | 20800   | 15.29                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.12                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2565            | 21400   | 15.37                 | 15.5                                | 0-2                      |
|                          |            | 50RB    |           | 2505            | 20800   | 15.21                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.22                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2565            | 21400   | 15.35                 | 15.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| FDD Band 7 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|--------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                  | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5                        | QPSK       | 1 RB    | 0         | 2502.5          | 20775   | 16.85                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 16.78                 | 17.5                                | 0                        |
|                          |            |         |           | 2567.5          | 21425   | 16.73                 | 17.5                                | 0                        |
|                          |            |         | 12        | 2502.5          | 20775   | 17.19                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 17.11                 | 17.5                                | 0                        |
|                          |            |         |           | 2567.5          | 21425   | 17.44                 | 17.5                                | 0                        |
|                          |            |         | 24        | 2502.5          | 20775   | 17.14                 | 17.5                                | 0                        |
|                          |            |         |           | 2535            | 21100   | 16.96                 | 17.5                                | 0                        |
|                          |            |         |           | 2567.5          | 21425   | 17.11                 | 17.5                                | 0                        |
|                          |            | 12 RB   | 0         | 2502.5          | 20775   | 16.33                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.18                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2567.5          | 21425   | 16.22                 | 16.5                                | 0-1                      |
|                          |            |         | 6         | 2502.5          | 20775   | 16.32                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.15                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2567.5          | 21425   | 16.34                 | 16.5                                | 0-1                      |
|                          |            |         | 13        | 2502.5          | 20775   | 16.20                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.14                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2567.5          | 21425   | 16.38                 | 16.5                                | 0-1                      |
|                          |            |         | 25RB      | 2502.5          | 20775   | 16.21                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.16                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2567.5          | 21425   | 16.25                 | 16.5                                | 0-1                      |
|                          | 16-QAM     | 1 RB    | 0         | 2502.5          | 20775   | 16.33                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 16.11                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2567.5          | 21425   | 15.96                 | 16.5                                | 0-1                      |
|                          |            |         | 12        | 2502.5          | 20775   | 15.90                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 15.88                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2567.5          | 21425   | 15.73                 | 16.5                                | 0-1                      |
|                          |            |         | 24        | 2502.5          | 20775   | 15.89                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2535            | 21100   | 15.88                 | 16.5                                | 0-1                      |
|                          |            |         |           | 2567.5          | 21425   | 16.45                 | 16.5                                | 0-1                      |
|                          |            | 12 RB   | 0         | 2502.5          | 20775   | 15.40                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.06                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2567.5          | 21425   | 15.29                 | 15.5                                | 0-2                      |
|                          |            |         | 6         | 2502.5          | 20775   | 15.45                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.32                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2567.5          | 21425   | 15.41                 | 15.5                                | 0-2                      |
|                          |            |         | 13        | 2502.5          | 20775   | 15.26                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.17                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2567.5          | 21425   | 15.40                 | 15.5                                | 0-2                      |
|                          |            |         | 25RB      | 2502.5          | 20775   | 15.22                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2535            | 21100   | 15.18                 | 15.5                                | 0-2                      |
|                          |            |         |           | 2567.5          | 21425   | 15.27                 | 15.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## LTE TDD Band XXXVIII

| TDD Band 38 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|----------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 20                         | QPSK       | 1 RB    | 0         | 2580            | 37850   | 22.86                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.48                 | 23.5                                | 0                        |
|                            |            |         |           | 2610            | 38150   | 23.47                 | 23.5                                | 0                        |
|                            |            |         | 50        | 2580            | 37850   | 23.14                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 22.98                 | 23.5                                | 0                        |
|                            |            |         |           | 2610            | 38150   | 23.11                 | 23.5                                | 0                        |
|                            |            |         | 99        | 2580            | 37850   | 22.81                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.11                 | 23.5                                | 0                        |
|                            |            |         |           | 2610            | 38150   | 22.98                 | 23.5                                | 0                        |
|                            |            | 50 RB   | 0         | 2580            | 37850   | 22.20                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.18                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2610            | 38150   | 22.18                 | 22.5                                | 0-1                      |
|                            |            |         | 25        | 2580            | 37850   | 22.17                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.15                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2610            | 38150   | 22.24                 | 22.5                                | 0-1                      |
|                            |            |         | 50        | 2580            | 37850   | 22.17                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.05                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2610            | 38150   | 22.27                 | 22.5                                | 0-1                      |
|                            |            | 100RB   |           | 2580            | 37850   | 22.16                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.11                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2610            | 38150   | 22.17                 | 22.5                                | 0-1                      |
|                            | 16-QAM     | 1 RB    | 0         | 2580            | 37850   | 21.81                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.85                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2610            | 38150   | 21.87                 | 22.5                                | 0-1                      |
|                            |            |         | 50        | 2580            | 37850   | 22.00                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.97                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2610            | 38150   | 22.18                 | 22.5                                | 0-1                      |
|                            |            |         | 99        | 2580            | 37850   | 21.73                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.73                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2610            | 38150   | 21.61                 | 22.5                                | 0-1                      |
|                            |            | 50 RB   | 0         | 2580            | 37850   | 21.14                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 20.91                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2610            | 38150   | 20.91                 | 21.5                                | 0-2                      |
|                            |            |         | 25        | 2580            | 37850   | 21.23                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.10                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2610            | 38150   | 21.03                 | 21.5                                | 0-2                      |
|                            |            |         | 50        | 2580            | 37850   | 21.06                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 20.96                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2610            | 38150   | 21.17                 | 21.5                                | 0-2                      |
|                            |            | 100RB   |           | 2580            | 37850   | 21.07                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 20.93                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2610            | 38150   | 21.07                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| TDD Band 38 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|----------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 15                         | QPSK       | 1 RB    | 0         | 2577.5          | 37825   | 23.04                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.02                 | 23.5                                | 0                        |
|                            |            |         |           | 2612.5          | 38175   | 23.12                 | 23.5                                | 0                        |
|                            |            |         | 36        | 2577.5          | 37825   | 23.19                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.07                 | 23.5                                | 0                        |
|                            |            |         |           | 2612.5          | 38175   | 22.89                 | 23.5                                | 0                        |
|                            |            |         | 74        | 2577.5          | 37825   | 23.10                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.10                 | 23.5                                | 0                        |
|                            |            |         |           | 2612.5          | 38175   | 23.01                 | 23.5                                | 0                        |
|                            |            | 36 RB   | 0         | 2577.5          | 37825   | 22.28                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.12                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2612.5          | 38175   | 22.27                 | 22.5                                | 0-1                      |
|                            |            |         | 18        | 2577.5          | 37825   | 22.23                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.12                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2612.5          | 38175   | 22.30                 | 22.5                                | 0-1                      |
|                            |            |         | 37        | 2577.5          | 37825   | 22.11                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.03                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2612.5          | 38175   | 22.19                 | 22.5                                | 0-1                      |
|                            |            |         | 75RB      | 2577.5          | 37825   | 22.18                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.15                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2612.5          | 38175   | 22.12                 | 22.5                                | 0-1                      |
|                            | 16-QAM     | 1 RB    | 0         | 2577.5          | 37825   | 21.69                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.84                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2612.5          | 38175   | 21.84                 | 22.5                                | 0-1                      |
|                            |            |         | 36        | 2577.5          | 37825   | 21.84                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.79                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2612.5          | 38175   | 21.88                 | 22.5                                | 0-1                      |
|                            |            |         | 74        | 2577.5          | 37825   | 21.64                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.75                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2612.5          | 38175   | 21.73                 | 22.5                                | 0-1                      |
|                            |            | 36 RB   | 0         | 2577.5          | 37825   | 21.03                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 20.98                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2612.5          | 38175   | 21.22                 | 21.5                                | 0-2                      |
|                            |            |         | 18        | 2577.5          | 37825   | 21.10                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.16                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2612.5          | 38175   | 21.08                 | 21.5                                | 0-2                      |
|                            |            |         | 37        | 2577.5          | 37825   | 20.90                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 20.93                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2612.5          | 38175   | 21.07                 | 21.5                                | 0-2                      |
|                            |            |         | 75RB      | 2577.5          | 37825   | 21.10                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.06                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2612.5          | 38175   | 21.11                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| TDD Band 38 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|----------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 10                         | QPSK       | 1 RB    | 0         | 2575            | 37800   | 23.13                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.02                 | 23.5                                | 0                        |
|                            |            |         |           | 2615            | 38200   | 23.07                 | 23.5                                | 0                        |
|                            |            |         | 25        | 2575            | 37800   | 23.15                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 22.90                 | 23.5                                | 0                        |
|                            |            |         |           | 2615            | 38200   | 23.00                 | 23.5                                | 0                        |
|                            |            |         | 49        | 2575            | 37800   | 23.07                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.08                 | 23.5                                | 0                        |
|                            |            |         |           | 2615            | 38200   | 23.04                 | 23.5                                | 0                        |
|                            |            | 25 RB   | 0         | 2575            | 37800   | 22.13                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.08                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2615            | 38200   | 22.11                 | 22.5                                | 0-1                      |
|                            |            |         | 12        | 2575            | 37800   | 22.22                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.07                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2615            | 38200   | 22.22                 | 22.5                                | 0-1                      |
|                            |            |         | 25        | 2575            | 37800   | 22.07                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.01                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2615            | 38200   | 22.17                 | 22.5                                | 0-1                      |
|                            |            | 50RB    |           | 2575            | 37800   | 22.11                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.10                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2615            | 38200   | 22.15                 | 22.5                                | 0-1                      |
|                            | 16-QAM     | 1 RB    | 0         | 2575            | 37800   | 21.78                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.75                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2615            | 38200   | 21.88                 | 22.5                                | 0-1                      |
|                            |            |         | 25        | 2575            | 37800   | 22.05                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.87                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2615            | 38200   | 22.03                 | 22.5                                | 0-1                      |
|                            |            |         | 49        | 2575            | 37800   | 21.62                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.79                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2615            | 38200   | 21.74                 | 22.5                                | 0-1                      |
|                            |            | 25 RB   | 0         | 2575            | 37800   | 21.04                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 20.93                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2615            | 38200   | 20.88                 | 21.5                                | 0-2                      |
|                            |            |         | 12        | 2575            | 37800   | 21.06                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.34                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2615            | 38200   | 21.41                 | 21.5                                | 0-2                      |
|                            |            |         | 25        | 2575            | 37800   | 21.05                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.28                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2615            | 38200   | 21.36                 | 21.5                                | 0-2                      |
|                            |            | 50RB    |           | 2575            | 37800   | 21.08                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.09                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2615            | 38200   | 20.89                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| TDD Band 38 (Main antenna) |            |         |           |                 |         |                       |                                     |                          |
|----------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                    | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5                          | QPSK       | 1 RB    | 0         | 2572.5          | 37775   | 23.16                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.11                 | 23.5                                | 0                        |
|                            |            |         |           | 2617.5          | 38225   | 23.22                 | 23.5                                | 0                        |
|                            |            |         | 12        | 2572.5          | 37775   | 23.42                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.40                 | 23.5                                | 0                        |
|                            |            |         |           | 2617.5          | 38225   | 23.27                 | 23.5                                | 0                        |
|                            |            |         | 24        | 2572.5          | 37775   | 23.09                 | 23.5                                | 0                        |
|                            |            |         |           | 2595            | 38000   | 23.17                 | 23.5                                | 0                        |
|                            |            |         |           | 2617.5          | 38225   | 23.02                 | 23.5                                | 0                        |
|                            |            | 12 RB   | 0         | 2572.5          | 37775   | 22.35                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.35                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2617.5          | 38225   | 22.45                 | 22.5                                | 0-1                      |
|                            |            |         | 6         | 2572.5          | 37775   | 22.38                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.27                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2617.5          | 38225   | 22.39                 | 22.5                                | 0-1                      |
|                            |            |         | 13        | 2572.5          | 37775   | 22.35                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.35                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2617.5          | 38225   | 22.33                 | 22.5                                | 0-1                      |
|                            |            |         | 25RB      | 2572.5          | 37775   | 22.35                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.34                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2617.5          | 38225   | 22.42                 | 22.5                                | 0-1                      |
|                            | 16-QAM     | 1 RB    | 0         | 2572.5          | 37775   | 21.91                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.90                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2617.5          | 38225   | 21.91                 | 22.5                                | 0-1                      |
|                            |            |         | 12        | 2572.5          | 37775   | 22.05                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 22.04                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2617.5          | 38225   | 22.13                 | 22.5                                | 0-1                      |
|                            |            |         | 24        | 2572.5          | 37775   | 21.90                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2595            | 38000   | 21.80                 | 22.5                                | 0-1                      |
|                            |            |         |           | 2617.5          | 38225   | 21.84                 | 22.5                                | 0-1                      |
|                            |            | 12 RB   | 0         | 2572.5          | 37775   | 21.36                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.15                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2617.5          | 38225   | 21.27                 | 21.5                                | 0-2                      |
|                            |            |         | 6         | 2572.5          | 37775   | 21.18                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.18                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2617.5          | 38225   | 21.27                 | 21.5                                | 0-2                      |
|                            |            |         | 13        | 2572.5          | 37775   | 21.34                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.42                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2617.5          | 38225   | 21.22                 | 21.5                                | 0-2                      |
|                            |            |         | 25RB      | 2572.5          | 37775   | 21.19                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2595            | 38000   | 21.44                 | 21.5                                | 0-2                      |
|                            |            |         |           | 2617.5          | 38225   | 21.42                 | 21.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| TDD Band 38 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 20                        | QPSK       | 1 RB    | 0         | 2580            | 37850   | 19.49                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.94                 | 20.5                                | 0                        |
|                           |            |         |           | 2610            | 38150   | 19.92                 | 20.5                                | 0                        |
|                           |            |         | 50        | 2580            | 37850   | 19.91                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.90                 | 20.5                                | 0                        |
|                           |            |         |           | 2610            | 38150   | 20.12                 | 20.5                                | 0                        |
|                           |            |         | 99        | 2580            | 37850   | 19.79                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.82                 | 20.5                                | 0                        |
|                           |            |         |           | 2610            | 38150   | 19.68                 | 20.5                                | 0                        |
|                           |            | 50 RB   | 0         | 2580            | 37850   | 19.24                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.13                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2610            | 38150   | 19.13                 | 19.5                                | 0-1                      |
|                           |            |         | 25        | 2580            | 37850   | 19.18                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.06                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2610            | 38150   | 19.14                 | 19.5                                | 0-1                      |
|                           |            |         | 50        | 2580            | 37850   | 19.19                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.08                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2610            | 38150   | 19.17                 | 19.5                                | 0-1                      |
|                           |            | 100RB   |           | 2580            | 37850   | 19.18                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.05                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2610            | 38150   | 19.10                 | 19.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2580            | 37850   | 18.80                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.86                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2610            | 38150   | 18.75                 | 19.5                                | 0-1                      |
|                           |            |         | 50        | 2580            | 37850   | 18.95                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.92                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2610            | 38150   | 18.87                 | 19.5                                | 0-1                      |
|                           |            |         | 99        | 2580            | 37850   | 18.72                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.73                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2610            | 38150   | 18.66                 | 19.5                                | 0-1                      |
|                           |            | 50 RB   | 0         | 2580            | 37850   | 18.33                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.12                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2610            | 38150   | 18.13                 | 18.5                                | 0-2                      |
|                           |            |         | 25        | 2580            | 37850   | 18.18                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.15                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2610            | 38150   | 18.14                 | 18.5                                | 0-2                      |
|                           |            |         | 50        | 2580            | 37850   | 18.11                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.07                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2610            | 38150   | 18.26                 | 18.5                                | 0-2                      |
|                           |            | 100RB   |           | 2580            | 37850   | 18.27                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.14                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2610            | 38150   | 18.09                 | 18.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| TDD Band 38 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 15                        | QPSK       | 1 RB    | 0         | 2577.5          | 37825   | 20.03                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 20.04                 | 20.5                                | 0                        |
|                           |            |         |           | 2612.5          | 38175   | 20.07                 | 20.5                                | 0                        |
|                           |            |         | 36        | 2577.5          | 37825   | 19.98                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.85                 | 20.5                                | 0                        |
|                           |            |         |           | 2612.5          | 38175   | 19.89                 | 20.5                                | 0                        |
|                           |            |         | 74        | 2577.5          | 37825   | 19.88                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.88                 | 20.5                                | 0                        |
|                           |            |         |           | 2612.5          | 38175   | 19.94                 | 20.5                                | 0                        |
|                           |            | 36 RB   | 0         | 2577.5          | 37825   | 19.26                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.14                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2612.5          | 38175   | 19.27                 | 19.5                                | 0-1                      |
|                           |            |         | 18        | 2577.5          | 37825   | 19.23                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.09                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2612.5          | 38175   | 19.25                 | 19.5                                | 0-1                      |
|                           |            |         | 37        | 2577.5          | 37825   | 19.13                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.02                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2612.5          | 38175   | 19.22                 | 19.5                                | 0-1                      |
|                           |            |         | 75RB      | 2577.5          | 37825   | 19.18                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.16                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2612.5          | 38175   | 19.18                 | 19.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2577.5          | 37825   | 18.71                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.85                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2612.5          | 38175   | 18.75                 | 19.5                                | 0-1                      |
|                           |            |         | 36        | 2577.5          | 37825   | 18.76                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.72                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2612.5          | 38175   | 18.66                 | 19.5                                | 0-1                      |
|                           |            |         | 74        | 2577.5          | 37825   | 18.61                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.75                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2612.5          | 38175   | 18.67                 | 19.5                                | 0-1                      |
|                           |            | 36 RB   | 0         | 2577.5          | 37825   | 18.20                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.17                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2612.5          | 38175   | 18.29                 | 18.5                                | 0-2                      |
|                           |            |         | 18        | 2577.5          | 37825   | 18.16                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.22                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2612.5          | 38175   | 18.29                 | 18.5                                | 0-2                      |
|                           |            |         | 37        | 2577.5          | 37825   | 18.19                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 17.99                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2612.5          | 38175   | 18.28                 | 18.5                                | 0-2                      |
|                           |            |         | 75RB      | 2577.5          | 37825   | 18.26                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.16                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2612.5          | 38175   | 18.17                 | 18.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| TDD Band 38 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 10                        | QPSK       | 1 RB    | 0         | 2575            | 37800   | 19.98                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 20.01                 | 20.5                                | 0                        |
|                           |            |         |           | 2615            | 38200   | 19.97                 | 20.5                                | 0                        |
|                           |            |         | 25        | 2575            | 37800   | 19.97                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.91                 | 20.5                                | 0                        |
|                           |            |         |           | 2615            | 38200   | 20.01                 | 20.5                                | 0                        |
|                           |            |         | 49        | 2575            | 37800   | 19.77                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.79                 | 20.5                                | 0                        |
|                           |            |         |           | 2615            | 38200   | 19.79                 | 20.5                                | 0                        |
|                           |            | 25 RB   | 0         | 2575            | 37800   | 19.21                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.12                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2615            | 38200   | 19.10                 | 19.5                                | 0-1                      |
|                           |            |         | 12        | 2575            | 37800   | 19.24                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.08                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2615            | 38200   | 19.17                 | 19.5                                | 0-1                      |
|                           |            |         | 25        | 2575            | 37800   | 19.25                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.03                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2615            | 38200   | 19.15                 | 19.5                                | 0-1                      |
|                           |            | 50RB    |           | 2575            | 37800   | 19.28                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.13                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2615            | 38200   | 19.13                 | 19.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2575            | 37800   | 18.83                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.75                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2615            | 38200   | 18.88                 | 19.5                                | 0-1                      |
|                           |            |         | 25        | 2575            | 37800   | 19.09                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.84                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2615            | 38200   | 19.04                 | 19.5                                | 0-1                      |
|                           |            |         | 49        | 2575            | 37800   | 18.70                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.71                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2615            | 38200   | 18.69                 | 19.5                                | 0-1                      |
|                           |            | 25 RB   | 0         | 2575            | 37800   | 18.12                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.39                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2615            | 38200   | 18.11                 | 18.5                                | 0-2                      |
|                           |            |         | 12        | 2575            | 37800   | 18.23                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.46                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2615            | 38200   | 18.46                 | 18.5                                | 0-2                      |
|                           |            |         | 25        | 2575            | 37800   | 18.17                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.31                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2615            | 38200   | 18.43                 | 18.5                                | 0-2                      |
|                           |            | 50RB    |           | 2575            | 37800   | 18.28                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.11                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2615            | 38200   | 18.21                 | 18.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| TDD Band 38 (Sub antenna) |            |         |           |                 |         |                       |                                     |                          |
|---------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------------|--------------------------|
| BW(Mhz)                   | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted power (dBm) | Target Power + Max. Tolerance (dBm) | MPR Allowed per 3GPP(dB) |
| 5                         | QPSK       | 1 RB    | 0         | 2572.5          | 37775   | 19.79                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.85                 | 20.5                                | 0                        |
|                           |            |         |           | 2617.5          | 38225   | 19.91                 | 20.5                                | 0                        |
|                           |            |         | 12        | 2572.5          | 37775   | 19.93                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 20.05                 | 20.5                                | 0                        |
|                           |            |         |           | 2617.5          | 38225   | 20.00                 | 20.5                                | 0                        |
|                           |            | 24      | 24        | 2572.5          | 37775   | 19.80                 | 20.5                                | 0                        |
|                           |            |         |           | 2595            | 38000   | 19.64                 | 20.5                                | 0                        |
|                           |            |         |           | 2617.5          | 38225   | 19.71                 | 20.5                                | 0                        |
|                           |            | 12 RB   | 0         | 2572.5          | 37775   | 19.16                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.08                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2617.5          | 38225   | 19.13                 | 19.5                                | 0-1                      |
|                           |            |         | 6         | 2572.5          | 37775   | 19.15                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.10                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2617.5          | 38225   | 19.13                 | 19.5                                | 0-1                      |
|                           |            |         | 13        | 2572.5          | 37775   | 19.06                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.08                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2617.5          | 38225   | 19.09                 | 19.5                                | 0-1                      |
|                           |            | 25RB    |           | 2572.5          | 37775   | 19.16                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 19.08                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2617.5          | 38225   | 19.11                 | 19.5                                | 0-1                      |
|                           | 16-QAM     | 1 RB    | 0         | 2572.5          | 37775   | 18.67                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.57                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2617.5          | 38225   | 18.60                 | 19.5                                | 0-1                      |
|                           |            |         | 12        | 2572.5          | 37775   | 18.88                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.81                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2617.5          | 38225   | 18.75                 | 19.5                                | 0-1                      |
|                           |            |         | 24        | 2572.5          | 37775   | 18.55                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2595            | 38000   | 18.59                 | 19.5                                | 0-1                      |
|                           |            |         |           | 2617.5          | 38225   | 18.65                 | 19.5                                | 0-1                      |
|                           |            | 12 RB   | 0         | 2572.5          | 37775   | 18.05                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.17                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2617.5          | 38225   | 18.21                 | 18.5                                | 0-2                      |
|                           |            |         | 6         | 2572.5          | 37775   | 18.05                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.19                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2617.5          | 38225   | 18.30                 | 18.5                                | 0-2                      |
|                           |            |         | 13        | 2572.5          | 37775   | 18.03                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.16                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2617.5          | 38225   | 18.16                 | 18.5                                | 0-2                      |
|                           |            | 25RB    |           | 2572.5          | 37775   | 18.06                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2595            | 38000   | 18.37                 | 18.5                                | 0-2                      |
|                           |            |         |           | 2617.5          | 38225   | 18.11                 | 18.5                                | 0-2                      |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**LTE CA conducted power table:**

| Two Component Carrier Maximum Conducted Power |                     |                  |                          |            |            |                  |                  |                          |          |                     |                  |                          |                           |                          |                |         |
|-----------------------------------------------|---------------------|------------------|--------------------------|------------|------------|------------------|------------------|--------------------------|----------|---------------------|------------------|--------------------------|---------------------------|--------------------------|----------------|---------|
| PCC                                           |                     |                  |                          |            |            |                  |                  |                          | SCC      |                     |                  |                          | Power                     |                          | Configurations | Antenna |
| PCC Band                                      | PCC Bandwidth [MHz] | PCC (UL) Channel | PCC (UL) Frequency [MHz] | Modulation | PCC UL# RB | PCC UL RB Offset | PCC (DL) Channel | PCC (DL) Frequency [MHz] | SCC Band | SCC Bandwidth [MHz] | PCC (DL) Channel | PCC (DL) Frequency [MHz] | LTE Rel 10 Tx.Power (dBm) | LTE Rel 8 Tx.Power (dBm) |                |         |
| LTE B5                                        | 10                  | 20450            | 829                      | QPSK       | 1          | 25               | 2450             | 874                      | LTE B3   | 20                  | 1575             | 1842.5                   | 22.14                     | 23.35                    | 5A+3A          | Main    |
| LTE B7                                        | 20                  | 21350            | 2560                     | QPSK       | 1          | 50               | 3350             | 2680                     | LTE B3   | 20                  | 1575             | 1842.5                   | 23.01                     | 23.44                    | 7A+3A          |         |
| LTE B7                                        | 20                  | 21350            | 2560                     | QPSK       | 1          | 50               | 3350             | 2680                     | LTE B28  | 15                  | 9435             | 780.5                    | 22.22                     | 23.44                    | 7A+28A         |         |
| LTE B7                                        | 20                  | 21350            | 2560                     | QPSK       | 1          | 50               | 3350             | 2680                     | LTE B7   | 5                   | 2775             | 2622.5                   | 23.14                     | 23.44                    | 7A+7A          |         |
| LTE B7                                        | 20                  | 20850            | 2510                     | QPSK       | 1          | 99               | 2850             | 2630                     | LTE B7   | 20                  | 3048             | 2649.8                   | 22.51                     | 23.27                    | 7C             |         |
| LTE B7                                        | 20                  | 20850            | 2510                     | QPSK       | 1          | 99               | 2850             | 2630                     | LTE B7   | 15                  | 3021             | 2647.1                   | 22.92                     | 23.27                    | 7C             |         |
| LTE B7                                        | 20                  | 21350            | 2560                     | QPSK       | 1          | 50               | 3350             | 2680                     | LTE B7   | 10                  | 3206             | 2665.6                   | 22.74                     | 23.44                    | 7C             |         |
| LTE B7                                        | 15                  | 20825            | 2507.5                   | QPSK       | 1          | 36               | 2825             | 2627.5                   | LTE B7   | 15                  | 2975             | 2642.5                   | 22.62                     | 23.42                    | 7C             |         |
| LTE B7                                        | 15                  | 21375            | 2562.5                   | QPSK       | 1          | 36               | 3375             | 2682.5                   | LTE B7   | 15                  | 3225             | 2667.5                   | 22.84                     | 23.29                    | 7C             |         |
| LTE B38                                       | 20                  | 37850            | 2580                     | QPSK       | 1          | 50               | 37850            | 2580                     | LTE B38  | 20                  | 38048            | 2599.8                   | 22.32                     | 23.14                    | 38C            |         |
| LTE B38                                       | 20                  | 38150            | 2610                     | QPSK       | 1          | 0                | 38150            | 2610                     | LTE B38  | 20                  | 37952            | 2590.2                   | 22.73                     | 23.47                    | 38C            |         |
| LTE B38                                       | 15                  | 37825            | 2577.5                   | QPSK       | 1          | 36               | 37825            | 2577.5                   | LTE B38  | 15                  | 37975            | 2592.5                   | 22.58                     | 23.19                    | 38C            |         |
| LTE B7                                        | 20                  | 20850            | 2510                     | QPSK       | 1          | 50               | 2850             | 2630                     | LTE B3   | 20                  | 1575             | 1842.5                   | 15.92                     | 17.50                    | 7A+3A          | Sub     |
| LTE B7                                        | 20                  | 20850            | 2510                     | QPSK       | 1          | 50               | 2850             | 2630                     | LTE B28  | 15                  | 9435             | 780.5                    | 16.33                     | 17.50                    | 7A+28A         |         |
| LTE B7                                        | 20                  | 20850            | 2510                     | QPSK       | 1          | 50               | 2850             | 2630                     | LTE B7   | 5                   | 2775             | 2622.5                   | 17.00                     | 17.50                    | 7A+7A          |         |
| LTE B7                                        | 20                  | 20850            | 2510                     | QPSK       | 1          | 50               | 2850             | 2630                     | LTE B7   | 20                  | 3048             | 2649.8                   | 16.92                     | 17.50                    | 7C             |         |
| LTE B7                                        | 20                  | 20850            | 2510                     | QPSK       | 1          | 50               | 2850             | 2630                     | LTE B7   | 15                  | 3021             | 2647.1                   | 16.45                     | 17.50                    | 7C             |         |
| LTE B7                                        | 20                  | 21350            | 2560                     | QPSK       | 1          | 99               | 3350             | 2680                     | LTE B7   | 10                  | 3206             | 2665.6                   | 16.58                     | 17.29                    | 7C             |         |
| LTE B7                                        | 15                  | 20825            | 2507.5                   | QPSK       | 1          | 36               | 2825             | 2627.5                   | LTE B7   | 15                  | 2975             | 2642.5                   | 16.32                     | 17.31                    | 7C             |         |
| LTE B7                                        | 15                  | 21375            | 2562.5                   | QPSK       | 1          | 36               | 3375             | 2682.5                   | LTE B7   | 15                  | 3225             | 2667.5                   | 16.61                     | 17.34                    | 7C             |         |
| LTE B5                                        | 10                  | 20600            | 844                      | QPSK       | 1          | 25               | 2600             | 889                      | LTE B3   | 20                  | 1575             | 1842.5                   | 20.44                     | 21.18                    | 5A+3A          |         |
| LTE B38                                       | 20                  | 37850            | 2580                     | QPSK       | 1          | 50               | 37850            | 2580                     | LTE B38  | 20                  | 38048            | 2599.8                   | 19.11                     | 19.91                    | 38C            |         |
| LTE B38                                       | 20                  | 38150            | 2610                     | QPSK       | 1          | 50               | 38150            | 2610                     | LTE B38  | 20                  | 37952            | 2590.2                   | 19.14                     | 20.12                    | 38C            |         |
| LTE B38                                       | 15                  | 37825            | 2577.5                   | QPSK       | 1          | 0                | 37825            | 2577.5                   | LTE B38  | 15                  | 37975            | 2592.5                   | 18.54                     | 20.03                    | 38C            |         |

**LTE CA information**

**A)** The device supports downlink Release 10 LTE Carrier Aggregation (CA) only. It supports a maximum of 2 carriers in the downlink. Other Release 10 features are not supported, including Uplink Carrier Aggregation, Enhanced SC-FDMA and Uplink MIMO or other antenna diversity configurations etc. All uplink communications are identical to the Release 8 Specifications.

The possible downlink LTE CA combinations supported by this device are as below tables per 3GPP TS 36.101 V14.0.0. The conducted power measurement results of downlink LTE CA are provided in Section 7 of this report 3GPP TS 36.521-1 V13.2.0. According to KDB 941225 D05A, the downlink LTE CA SAR test is not required.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

B) i) Combinations supported for intra-band aggregation.

**Table 1: contiguous intra-band CA**

| E-UTRA CA configuration / Bandwidth combination set |  |                                                             |                                      |                                      |                                    |                           |
|-----------------------------------------------------|--|-------------------------------------------------------------|--------------------------------------|--------------------------------------|------------------------------------|---------------------------|
| E-UTRA CA configuration                             |  | Component carriers in order of increasing carrier frequency |                                      |                                      | Maximum aggregated bandwidth [MHz] | Bandwidth combination set |
|                                                     |  | Channel bandwidths for carrier [MHz]                        | Channel bandwidths for carrier [MHz] | Channel bandwidths for carrier [MHz] |                                    |                           |
| CA_7C                                               |  | 15                                                          | 15                                   |                                      | 40                                 | 0                         |
|                                                     |  | 20                                                          | 20                                   |                                      |                                    |                           |
|                                                     |  | 10                                                          | 20                                   |                                      | 40                                 | 1                         |
|                                                     |  | 15                                                          | 15, 20                               |                                      |                                    |                           |
|                                                     |  | 20                                                          | 10, 15, 20                           |                                      |                                    |                           |
| CA_38C                                              |  | 15                                                          | 15                                   |                                      | 40                                 | 0                         |
|                                                     |  | 20                                                          | 20                                   |                                      |                                    |                           |

**Table 2: non-contiguous intra-band CA (with two sub-blocks)**

| -UTRACA configuration | Component carriers in order of increasing carrier frequency |                                      |                                      | Maximum aggregated bandwidth [MHz] | Bandwidth combination set |
|-----------------------|-------------------------------------------------------------|--------------------------------------|--------------------------------------|------------------------------------|---------------------------|
|                       | Channel bandwidths for carrier [MHz]                        | Channel bandwidths for carrier [MHz] | Channel bandwidths for carrier [MHz] |                                    |                           |
| CA_7A-7A              | 5                                                           | 15                                   |                                      | 40                                 | 0                         |
|                       | 10                                                          | 10, 15                               |                                      |                                    |                           |
|                       | 15                                                          | 15, 20                               |                                      |                                    |                           |
|                       | 20                                                          | 20                                   |                                      |                                    |                           |
|                       | 5, 10, 15, 20                                               | 5, 10, 15, 20                        |                                      | 40                                 | 1                         |
|                       | 5, 10, 15, 20                                               | 5, 10                                |                                      | 30                                 | 2                         |

ii) The frequency band combinations supported for inter-band carrier aggregation.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Table 2: inter-band CA (two bands) Table 2: inter-band CA (two bands)

| E-UTRA CA Configuration | E-UTRA Bands | 1.4 MHz | 3 MHz | 5 MHz | 10 MHz | 15 MHz | 20 MHz | Maximum aggregated bandwidth [MHz] | Bandwidth combination set |
|-------------------------|--------------|---------|-------|-------|--------|--------|--------|------------------------------------|---------------------------|
| CA_3A-5A                | 3            |         |       |       | Yes    | Yes    | Yes    | 30                                 | 0                         |
|                         | 5            |         |       | Yes   | Yes    |        |        |                                    |                           |
|                         | 3            |         |       |       | Yes    |        |        | 20                                 | 1                         |
|                         | 5            |         |       | Yes   | Yes    |        |        |                                    |                           |
|                         | 3            |         |       | Yes   | Yes    | Yes    | Yes    | 30                                 | 2                         |
|                         | 5            |         |       | Yes   | Yes    |        |        |                                    |                           |
|                         | 3            |         |       | Yes   | Yes    | Yes    | Yes    | 30                                 | 3                         |
|                         | 5            |         | Yes   | Yes   | Yes    |        |        |                                    |                           |
| CA_3A-7A                | 3            |         |       | Yes   | Yes    | Yes    | Yes    | 40                                 | 0                         |
|                         | 7            |         |       |       | Yes    | Yes    | Yes    |                                    |                           |
|                         | 3            |         |       | Yes   | Yes    | Yes    | Yes    | 40                                 | 1                         |
|                         | 7            |         |       | Yes   | Yes    | Yes    | Yes    |                                    |                           |
| CA_7A-28A               | 7            |         |       | Yes   | Yes    | Yes    | Yes    | 35                                 | 0                         |
|                         | 28           |         |       | Yes   | Yes    | Yes    |        |                                    |                           |

Note:

- 1) For the inter-band CA combinations, the listed bands above can be used as PCC or SCC.
- 2) The channel spacing and aggregated channel bandwidth for CA are identical to the associated specification in 3GPP TS 36.101 V14.0.0
- 3) The reference test frequencies for CA refers to 3GPP TS 36.521-1 V13.2.0

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### WLAN802.11 b/g/n(20M) conducted power table:

| 802.11 b |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|----------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH       | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|          |                    |                                                    | 1                                       |
| 1        | 2412               | 19.5                                               | 19.43                                   |
| 6        | 2437               | 19.5                                               | 19.24                                   |
| 11       | 2462               | 19.5                                               | 19.48                                   |

| 802.11 g |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|----------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH       | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|          |                    |                                                    | 6                                       |
| 1        | 2412               | 17.5                                               | 17.21                                   |
| 6        | 2437               | 17.5                                               | 17.33                                   |
| 11       | 2462               | 17.5                                               | 17.42                                   |

| 802.11 n(20M) |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|---------------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH            | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|               |                    |                                                    | 6.5                                     |
| 1             | 2412               | 15.5                                               | 15.43                                   |
| 6             | 2437               | 15.5                                               | 15.34                                   |
| 11            | 2462               | 15.5                                               | 15.22                                   |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

# WiFi station+Sensor On

| 802.11 b |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|----------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH       | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|          |                    |                                                    | 1                                       |
| 1        | 2412               | 12.5                                               | 12.48                                   |
| 6        | 2437               | 12.5                                               | 12.33                                   |
| 11       | 2462               | 12.5                                               | 12.35                                   |

| 802.11 g |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|----------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH       | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|          |                    |                                                    | 6                                       |
| 1        | 2412               | 12.5                                               | 12.45                                   |
| 6        | 2437               | 12.5                                               | 12.35                                   |
| 11       | 2462               | 12.5                                               | 12.32                                   |

| 802.11 n(20M) |                    | Max. Rated Avg.<br>Power + Max.<br>Tolerance (dBm) | Average conducted output<br>power (dBm) |
|---------------|--------------------|----------------------------------------------------|-----------------------------------------|
| CH            | Frequency<br>(MHz) |                                                    | Data Rate (Mbps)                        |
|               |                    |                                                    | 6.5                                     |
| 1             | 2412               | 12.5                                               | 12.45                                   |
| 6             | 2437               | 12.5                                               | 12.33                                   |
| 11            | 2462               | 12.5                                               | 12.35                                   |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**Bluetooth conducted power table:**

| Frequency (MHz) | Data Rate | Max. tune-up power | Average |        |
|-----------------|-----------|--------------------|---------|--------|
|                 |           |                    | dBm     | mW     |
| 2402            | 1         | 11                 | 10.20   | 10.471 |
| 2441            | 1         | 11                 | 10.90   | 12.303 |
| 2480            | 1         | 11                 | 10.50   | 11.220 |
| 2402            | 2         | 11                 | 7.90    | 6.166  |
| 2441            | 2         | 11                 | 8.90    | 7.762  |
| 2480            | 2         | 11                 | 8.20    | 6.607  |
| 2402            | 3         | 11                 | 7.90    | 6.166  |
| 2441            | 3         | 11                 | 8.90    | 7.762  |
| 2480            | 3         | 11                 | 8.20    | 6.607  |

| Frequency (MHz) | BT4.0 Average |       |
|-----------------|---------------|-------|
|                 | dBm           | mW    |
| 2402            | -0.33         | 0.927 |
| 2442            | 0.27          | 1.064 |
| 2480            | -0.55         | 0.881 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.4 Test Environment

Ambient Temperature:  $22\pm 2^{\circ}\text{C}$

Tissue Simulating Liquid:  $22\pm 2^{\circ}\text{C}$

## 1.5 Operation Description

1. The EUT is controlled by using a Radio Communication Tester (Anritsu MT8820C / R&S CMW500), and the communication between the EUT and the tester is established by air link.
2. Measurements are performed respectively on the lowest, middle and highest channels of the operating band(s). The EUT is set to maximum power level during all tests, and at the beginning of each test the battery is fully charged.
3. During the SAR testing, the DASY 5 system checks power drift by comparing the e-field strength of one specific location measured at the beginning with that measured at the end of the SAR testing.
4. SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power. The data mode with highest specified time-averaged output power should be tested for SAR compliance. The GMSK EDGE configurations are grouped with GPRS and considered with respect to time-averaged maximum output power to determine compliance. The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode. Since the maximum output power in a secondary mode (8-PSK EDGE) is  $\leq 1/4$  dB higher than the primary mode (GMSK GPRS/EDGE), SAR measurement is not required for the secondary mode (8-PSK EDGE).
5. The 3G SAR test reduction procedure is applied to HSDPA with 12.2 kbps RMC as the primary mode. Since the maximum output power in a secondary mode (HSDPA) is  $\leq 1/4$  dB higher than the primary mode (WCDMA), SAR measurement is not required for the secondary mode (HSDPA).
6. The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) with 12.2 kbps RMC as the primary mode. Since the maximum output power in a secondary mode (HSPA) is  $\leq 1/4$  dB higher than the primary mode (WCDMA), SAR measurement is not required for the secondary mode (HSPA).
7. SAR test exclusion for DC-HSDPA  
The 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable. Since the maximum output power in a secondary mode (DC-HSDPA) is  $\leq \frac{1}{4}$  dB higher than the primary mode (WCDMA), SAR measurement is not required for the secondary mode (DC-HSDPA).

**Table C.8.1.12: Fixed Reference Channel H-Set 12**

| Parameter                                                                                                                                              | Unit      | Value |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
| Nominal Avg. Inf. Bit Rate                                                                                                                             | kbps      | 60    |
| Inter-TTI Distance                                                                                                                                     | TTI's     | 1     |
| Number of HARQ Processes                                                                                                                               | Processes | 6     |
| Information Bit Payload ( $N_{INF}$ )                                                                                                                  | Bits      | 120   |
| Number Code Blocks                                                                                                                                     | Blocks    | 1     |
| Binary Channel Bits Per TTI                                                                                                                            | Bits      | 960   |
| Total Available SML's in UE                                                                                                                            | SML's     | 19200 |
| Number of SML's per HARQ Proc.                                                                                                                         | SML's     | 3200  |
| Coding Rate                                                                                                                                            |           | 0.15  |
| Number of Physical Channel Codes                                                                                                                       | Codes     | 1     |
| Modulation                                                                                                                                             |           | QPSK  |
| Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.               |           |       |
| Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used. |           |       |



**Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)**

The following 4 sub-tests for HSDPA were completed according to Release 8 procedures in section 5.2 of 3GPP TS34.121. A summary of subtest settings are illustrated below:

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Sub-set | $\beta_c$         | $\beta_d$         | $\beta_d$<br>(SF) | $\beta_c/\beta_d$ | $\beta_{ns}$<br>(note 1, note 2) | CM(dB)<br>(note 3) | MPR(dB) |
|---------|-------------------|-------------------|-------------------|-------------------|----------------------------------|--------------------|---------|
| 1       | 2/15              | 15/15             | 64                | 2/15              | 4/15                             | 0.0                | 0.0     |
| 2       | 12/15<br>(note 4) | 15/15<br>(note 4) | 64                | 12/15<br>(note 4) | 24/15                            | 1.0                | 0.0     |
| 3       | 15/15             | 8/15              | 64                | 15/8              | 30/15                            | 1.5                | 0.5     |
| 4       | 15/15             | 4/15              | 64                | 15/4              | 30/15                            | 1.5                | 0.5     |

Note1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{ns} = \beta_{ns}/\beta_c = 30/15 \Leftrightarrow \beta_{ns} = 30/15 \cdot \beta_c$   
Note2: CM=1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{ns}/\beta_c = 24/15$ .  
Note3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC (TFC1,TF1) to  $\beta_c=11/15$  and  $\beta_d=15/15$ .

## 8. LTE modes test according to **KDB 941225D05v02r05**.

a. Per Section 5.2.1, the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation.

- Using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.

- When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.

- When the reported SAR of a required test channel is  $> 1.45$  W/kg, SAR is required for all three RB offset configurations for that required test channel.

b. Per Section 5.2.2, the largest channel bandwidth and measure SAR for QPSK with 50% RB allocation

- The procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.

c. Per Section 5.2.3, the largest channel bandwidth and measure SAR for QPSK with 100% RB allocation

- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are  $\leq 0.8$  W/kg.

- Otherwise, SAR is measured for the highest output power channel and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

d. Per Section 5.2.4, Higher order modulations

- For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in sections 5.2.1, 5.2.2 and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is  $>$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

$\frac{1}{2}$  dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45$  W/kg.

e. Per Section 5.3, other channel bandwidth standalone SAR test requirements

- For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section 5.2 to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is  $> \frac{1}{2}$  dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is  $> 1.45$  W/kg. The equivalent channel configuration for the RB allocation, RB offset and modulation etc. is determined for the smaller channel bandwidth according to the same number of RB allocated in the largest channel bandwidth.

LTE downlink CA (KDB942225 D05A)

9. The device supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 specifications. Uplink maximum output power is measured with downlink carrier aggregation active, only for the channel with highest measured maximum output power when downlink carrier aggregation is inactive, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than  $\frac{1}{4}$  dB higher than the maximum output power measured when downlink carrier aggregation inactive.
10. The downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements. The nominal channel spacing is determined by  $[BW1 + BW2 - 0.1 * |BW1 - BW2|] / 2$  MHz, where BW1 and BW2 are the channel bandwidths of the CC in a 2-CC aggregation configuration.
11. The downlink PCC channel should be paired with the uplink channel according to normal configurations, as if there is no carrier aggregation. The downlink SCC should be adjacent to the PCC and remain within the downlink transmission band for contiguous intra-band CA. For non-contiguous intra-band CA, the SCC should be selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band. For inter-band CA, the SCC should be near the middle of its transmission band.
12. When downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than  $\frac{1}{4}$  dB higher than the maximum output power measured when downlink carrier aggregation inactive, so SAR evaluation is not required for downlink carrier aggregation.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## WLAN

## 802.11b DSSS SAR Test Requirements:

13. SAR is measured for 2.4 GHz 802.11b DSSS mode using the highest measured maximum output power channel, when the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
14. When the reported SAR is  $> 0.8$  W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

## 802.11g/n OFDM SAR Test Exclusion Requirements:

15. SAR is not required for 802.11g/n since the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

## Initial Test Configuration:

16. An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band.
17. SAR is measured using the highest measured maximum output power channel. When the reported SAR of the initial test configuration is  $> 0.8$  W/kg, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.

## Other

18. BT and WLAN use the same antenna path and Bluetooth can't transmit simultaneously with WLAN.
19. There are two WWAN antennas (Main / Sub) but they can transmit simultaneously.
20. According to **KDB447498D01v06**, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is  $\leq 0.8$  W/kg, when the transmission band is  $\leq 100$  MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

21. According to **KDB865664D01v01r04**, SAR measurement variability must be assessed for each frequency band. When the original highest measured SAR is  $\geq 0.8$  W/kg, repeated that measurement once. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit)
22. According to **KDB447498D01v06** – The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for product specific 10-g SAR.

| mode | position                  | max. power (dB) | max. power (mW) | f(GHz) | calculation | SAR exclusion threshold | SAR test exclusion |
|------|---------------------------|-----------------|-----------------|--------|-------------|-------------------------|--------------------|
| BT   | body-worn                 | 11              | 12.589          | 2.48   | 1.322       | 3                       | yes                |
| BT   | product specific 10-g SAR | 11              | 12.589          | 2.48   | 3.965       | 7.5                     | yes                |

23. According to **KDB865664 D01v01r04** SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is  $\geq 1.5$  W/kg for 1-g SAR.


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## 1.6 Positioning Procedure

### Head SAR measurement statement



Phone position 1, "cheek" or "touch" position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.



Phone position 2, "tilted position." The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.

#### Cheek/Touch Position:

The handset was brought toward the mouth of the head phantom by pivoting against the ear reference point until any point of the mouthpiece or keypad touched the phantom.

#### Ear/Tilt Position:

With the phone aligned in the Cheek/Touch position, the handset was tilted away from the mouth with respect to the test device reference point by 15 degrees.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Body SAR measurement statement

### 1. Body-worn exposure: 15mm

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative test separation distance configuration may be used to support both SAR conditions. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2$  W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.

### 2. Hotspot exposure: 10mm

A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge when the form factor of a handset is larger than 9 cm  $\times$  5 cm,

Test configurations of WWAN Main

- (1) Front side
- (2) Back side
- (3) Bottom side.
- (4) Right side.
- (5) Left side.

Test configurations of WWAN Sub

- (1) Front side
- (2) Back side
- (3) Top side.
- (4) Left side.

Test configurations of WLAN :

- (1) Front side
- (2) Back side
- (3) Top side.
- (4) Right side

### 3. Phablet SAR test consideration

Since the device is a phablet (overall diagonal dimension  $> 16.0$  cm), the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at  $\leq 25$  mm from that surface or edge, in direct contact with a flat phantom, for product specific 10-g SAR. When hotspot mode applies, product specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR  $> 1.2$  W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.7 Power reduction information

This device uses a single fixed level of power reduction through static table look-up for SAR compliance.

### 1) Infrared proximity sensor

This device uses an infrared proximity sensor to facilitate triggering in typical user interactivity with the device. The proximity sensor locates on the front face of the device. Due to the operating configurations and exposure conditions required by the device, the proximity sensor is used to indicate when the phone is held close to a user's ear exposure condition. It utilizes the proximity sensor to reduce the output power of sub antenna and Wi-Fi antenna in held-to-ear scenario.

### 2) Hotspot on

A fixed level power reduction is applied for some frequency bands when hotspot mode becomes active. When the hotspot is disabled, the power value will be recovered.

The standalone SAR compliance still uses the standalone SAR results tested at the maximum output power level without any power reduction.

Table1~4 summarize the key power reduction information.

Table1: 2G&3G&4G sub ant + WiFi ant transmit simultaneously

| Band        | Power Reduction (dB)*                 |                                        |
|-------------|---------------------------------------|----------------------------------------|
|             | sub ant + WiFi station<br><sensor on> | sub ant + WiFi station<br><sensor off> |
| GSM 850(CS) | 2.5                                   | 0                                      |
| GSM1900(CS) | 1                                     | 0                                      |

Table 2: 2G&3G&4G main ant + WiFi ant transmit simultaneously

| Band                  | Power Reduction (dB)*        |                               |
|-----------------------|------------------------------|-------------------------------|
|                       | Main ant + WiFi <hotspot on> | Main ant + WiFi <hotspot off> |
| GSM1900<br>(CS&1slot) | 3                            | 0                             |

Table 3: 2G&3G&4G sub ant only transmit

| Band        | Power Reduction (dB)* |                      |
|-------------|-----------------------|----------------------|
|             | sub ant + sensor on   | sub ant + sensor off |
| GSM850(CS)  | 2.5                   | 0                    |
| GSM1900(CS) | 1                     | 0                    |

Table 4: 2G&3G&4G + WiFi ant transmit simultaneously

| Band | Power Reduction (dB)* |                      |
|------|-----------------------|----------------------|
|      | sub ant / main ant +  | sub ant / main ant + |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

|           | WiFi station <sensor on> | Wi-Fi station <sensor off> |
|-----------|--------------------------|----------------------------|
| WiFi 2.4G | 7                        | 0                          |

Note:

1)The device power reduction “implemented using a single fixed level of reduction through static table look-up for all exposure test configurations in a single wireless operating mode of a frequency band and it is triggered by a single event or operation” per PAG exclusion clause in KDB388624D02 item II.C.1.k and II.C.1.m.

The following procedure is used to determine the triggering distances, coverage and tilt angle influences per FCC KDB 616217 D04 §6 and FCC guidance.

### The specific device(s) covered by the KDB inquiry.

#### 1.7.1 General proximity sensor implementation description

This device uses an infrared proximity sensor to facilitate triggering in typical user interactivity with the device. Due to the operating configurations and exposure conditions required by the device, the proximity sensor is used to indicate when the phone is held close to a user's ear exposure condition. It utilizes the proximity sensor to reduce the output power of second antenna and Wi-Fi ant in held-to-ear scenario.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.7.2 Antennas and sensor placement details




Figure1: The location of the antennas (Front View)

Note:

- 1) The device has two 2G/3G/4G Tx antennas (Main Antenna and Sub/Div Antenna). It can transmit from either Main Antenna or Sub/Div Antenna, but they can not transmit simultaneously.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group




Figure2: The location of the IR proximity sensor (Front View)

| Antenna and sensor distances (front view , unit:mm)                                                                      |            |           |           |            |          |             |
|--------------------------------------------------------------------------------------------------------------------------|------------|-----------|-----------|------------|----------|-------------|
| Antenna                                                                                                                  | Front side | Back side | Left side | Right side | Top side | Bottom side |
| Sub Antenna(Div Antenna)                                                                                                 | 0          | 0         | 0         | 35         | 0        | 142         |
| Main Antenna                                                                                                             | 0          | 0         | 0         | 0          | 146      | 0           |
| 2.4G/5G WiFi & BT Antenna                                                                                                | 0          | 0         | 47        | 0          | 0        | 142         |
| Proximity Sensor                                                                                                         | 0          | 0         | 52        | 23         | 5.7      | 146         |
| The IR proximity sensor locates on the front face of the device and detects objects approaching only from the front side |            |           |           |            |          |             |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

### 1.7.3 proximity sensor coverage, distance and angle

#### 1.7.3.1 Procedures for determining proximity sensor triggering distances

Per FCC KDB 616217 D04v01§6.2, the following procedure is used to determine the triggering distances. As the proximity sensor locates on the front face of the device and detects objects approaching only from the front side, so triggering distance only need to be checked for the front side when 2G&3G&4G sub antenna transmit or Wi-Fi antenna and 2G&3G&4G antenna transmit simultaneously.



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279


f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Picture: Proximity sensor triggering distances assessment (Front side)  
the DUT is moved towards from the flat phantom

| Distance between phantom to DUT in mm               | 50  | 45  | 40  | 35  | 30  | 25 | 20 |
|-----------------------------------------------------|-----|-----|-----|-----|-----|----|----|
| Condition of Sensor in the front side of the device | off | off | off | off | off | on | on |




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

the DUT is moved away from the flat phantom

| Distance between phantom to DUT in mm               | 65  | 60  | 55  | 50  | 45  | 40 | 35 |
|-----------------------------------------------------|-----|-----|-----|-----|-----|----|----|
| Condition of Sensor in the front side of the device | off | off | off | off | off | on | on |



**Conclusion:** The Proximity sensor triggering distance is N mm (about 25-40mm), it can be ensured that the proximity sensor can be valid triggered in held-to-ear scenario.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### 1.7.3.2 Procedures for determining antenna and proximity sensor coverage

According to the location picture, proximity sensor is only applicable for the front side of DUT. As there is no spatial offset between the antenna and the proximity sensor element from the front view, so proximity sensor coverage does not need to be assessed.


### 1.7.3.3 Procedures for determining device tilt angle influences to proximity sensor triggering

The following procedure is used to determine the triggering angle. Distance need to be check when device under voice mode so that sensor is working.

For Head exposure condition, device tilt angle influences to proximity sensor triggering is determined as below:

Firstly, the DUT was positioned directly touch the SAM phantom (Left&Right hand touch cheek position) for each band. Rotate the DUT around the ear reference point of the phantom in 5° increments until the DUT is 15° or more away from the touch cheek position at 0°

Then the DUT is positioned at 15° or more away from the touch cheek position and moved towards the phantom in 5° increments until the DUT directly touch the SAM phantom at 0°(Left & Right hand touch cheek position).



The DUT is moved towards and away from SAM phantom.

| angle between phantom to DUT in degree | 0  | 5  | 10 | 15 | 20 | 25 |
|----------------------------------------|----|----|----|----|----|----|
| Condition of Sensor                    | on | on | on | on | on | on |

Based on the validation results above, angle tilt coverage can ensure that the proximity sensor is triggered for all the Head test positions(Left/Right Hand Touched cheek, Left/Right Hand tilted 15 °)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

#### 1.7.4 Summary SAR test Plan for Proximity sensor power reduction

**For Head SAR compliance:** Head SAR for Sub ant and Wi-Fi antenna are evaluated at reduced power levels according to the real held-to-ear proximity sensor power reduction usage scenarios.

**For Body SAR compliance,** Standalone SAR compliance is still tested at the maximum output power level without any sensor power reduction. Additional Body SAR tests at reduced power levels in Wi-Fi and 2G&3G&4G antenna simultaneous transmission power reduction scenarios may be tested for some frequency bands and test positions, which are only used to ensure simultaneous transmission SAR test exclusion.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.8 Evaluation Procedures

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan.
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters).
3. The generation of a high-resolution mesh within the measured volume.
4. The interpolation of all measured values from the measurement grid to the high-resolution grid.
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface.
6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within -2 dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7x7x7 scans.

The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30x30x30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. Boundary correction) to get the points

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is then moved around until the highest averaged SAR is found.

If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.9 Probe Calibration Procedures

For the calibration of E-field probes in lossy liquids, an electric field with an accurately known field strength must be produced within the measured liquid. For standardization purposes it would be desirable if all measurements which are necessary to assess the correct field strength would be traceable to standardized measurement procedures. In the following two different calibration techniques are summarized:

### 1.9.1 Transfer Calibration with Temperature Probes

In lossy liquids the specific absorption rate (SAR) is related both to the electric field ( $E$ ) and the temperature gradient ( $\delta T / \delta t$ ) in the liquid.

$$SAR = \frac{\sigma}{\rho} |E|^2 = c \frac{\delta T}{\delta t}$$

Whereby  $\sigma$  is the conductivity,  $\rho$  the density and  $c$  the heat capacity of the liquid.

Hence, the electric field in lossy liquid can be measured indirectly by measuring the temperature gradient in the liquid. Non-disturbing temperature probes (optical probes or thermistor probes with resistive lines) with high spatial resolution ( $<1\text{-}2\text{ mm}$ ) and fast reaction time ( $<1\text{ s}$ ) are available and can be easily calibrated with high precision [1]. The setup and the exciting source have no influence on the calibration; only the relative positioning uncertainties of the standard temperature probe and the E-field probe to be calibrated must be considered. However, several problems limit the available accuracy of probe calibrations with temperature probes:

1. The temperature gradient is not directly measurable but must be evaluated from temperature measurements at different time steps. Special precaution is necessary to avoid measurement errors caused by temperature gradients due to energy equalizing effects or convection currents in the liquid. Such effects cannot be completely avoided, as the measured field itself destroys the

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

thermal equilibrium in the liquid. With a careful setup these errors can be kept small.

2. The measured volume around the temperature probe is not well defined. It is difficult to calculate the energy transfer from a surrounding gradient temperature field into the probe. These effects must be considered, since temperature probes are calibrated in liquid with homogeneous temperatures. There is no traceable standard for temperature rise measurements.
3. The calibration depends on the assessment of the specific density, the heat capacity and the conductivity of the medium. While the specific density and heat capacity can be measured accurately with standardized procedures ( $\sim 2\%$  for  $c$ ; much better for  $\rho$ ), there is no standard for the measurement of the conductivity. Depending on the method and liquid, the error can well exceed  $\pm 5\%$ .
4. Temperature rise measurements are not very sensitive and therefore are often performed at a higher power level than the E-field measurements. The nonlinearities in the system (e.g., power measurements, different components, etc.) must be considered.

Considering these problems, the possible accuracy of the calibration of E-field probes with temperature gradient measurements in a carefully designed setup is about  $\pm 10\%$  (RSS) [2]. Recently, a setup which is a combination of the waveguide techniques and the thermal measurements was presented in [3]. The estimated uncertainty of the setup is  $\pm 5\%$  (RSS) when the same liquid is used for the calibration and for actual measurements and  $\pm 7-9\%$  (RSS) when not, which is in good agreement with the estimates given in [2].

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### 1.9.2 Calibration with Analytical Fields

In this method a technical setup is used in which the field can be calculated analytically from measurements of other physical magnitudes (e.g., input power). This corresponds to the standard field method for probe calibration in air; however, there is no standard defined for fields in lossy liquids.

When using calculated fields in lossy liquids for probe calibration, several points must be considered in the assessment of the uncertainty:

1. The setup must enable accurate determination of the incident power.
2. The accuracy of the calculated field strength will depend on the assessment of the dielectric parameters of the liquid.
3. Due to the small wavelength in liquids with high permittivity, even small setups might be above the resonant cutoff frequencies. The field distribution in the setup must be carefully checked for conformity with the theoretical field distribution.

### References

- (1) N. Kuster, Q. Balzano, and J.C. Lin, Eds., *Mobile Communications Safety*, Chapman & Hall, London, 1997.
- (2) K. Meier, M. Burkhardt, T. Schmid, and N. Kuster, "Broadband calibration of E-field probes in lossy media", *IEEE Transactions on Microwave Theory and Techniques*, vol. 44, no. 10, pp. 1954-1962, Oct. 1996.
- (3) K. Jokela, P. Hyysalo, and L. Puranen, "Calibration of specific absorption rate (SAR) probes in waveguide at 900 MHz", *IEEE Transactions on Instrumentation and Measurements*, vol. 47, no. 2, pp. 432-438, Apr. 1998.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## 1.10 The SAR Measurement System

A block diagram of the SAR measurement system is given in Fig. a. This SAR measurement system uses a Computer-controlled 3-D stepper motor system (SPEAG DASY 5 professional system). Model EX3DV4 field probes are used to determine the internal electric fields. The SAR can be obtained from the equation  $SAR = \sigma (|E_i|^2) / \rho$  where  $\sigma$  and  $\rho$  are the conductivity and mass density of the tissue-simulant.




Fig. a A block diagram of the SAR measurement system

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

The DASY 5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
5. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
6. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
7. A computer operating Windows7
8. DASY 5 software.
9. Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
10. The SAM twin phantom enabling testing left-hand and right-hand usage.
11. The device holder for handheld mobile phones.
12. Tissue simulating liquid mixed according to the given recipes.
13. Validation dipole kits allowing to validate the proper functioning of the system.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.11 System Components

### EX3DV4 E-Field Probe

|               |                                                                                                                                                                                                            |                                                                                     |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE)                                                |  |
| Calibration   | Basic Broad Band Calibration in air<br>Conversion Factors (CF) for<br>HSL835/1900/2450/2600 MHz Additional<br>CF for other liquids and frequencies upon request                                            |                                                                                     |
| Frequency     | 10 MHz to > 6 GHz, Linearity: $\pm 0.6$ dB                                                                                                                                                                 |                                                                                     |
| Directivity   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                                                                        |                                                                                     |
| Dynamic Range | 10 $\mu$ W/g to > 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)                                                                                                                     |                                                                                     |
| Dimensions    | Tip diameter: 2.5 mm                                                                                                                                                                                       |                                                                                     |
| Application   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |                                                                                     |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## SAM PHANTOM V4.0C

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                     |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Construction:    | <p>The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209.</p> <p>It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.</p> |                                                                                     |
| Shell Thickness: | 2 ± 0.2 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |
| Filling Volume:  | Approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                     |
| Dimensions:      | Height: 850 mm;<br>Length: 1000 mm;<br>Width: 500 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                     |

## DEVICE HOLDER

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                            |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Construction | <p>In combination with the Twin SAM Phantom V4.0/V4.0C or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).</p> |  <p>Device Holder</p> |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.12 SAR System Verification

The microwave circuit arrangement for system verification is sketched in Fig. b. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within  $\pm 10\%$  (according to KDB865664D01v01r04) from the target SAR values.

These tests were done at 835/1900/2450/2600 MHz. The tests were conducted on the same days as the measurement of the DUT. The obtained results from the system accuracy verification are displayed in the table 1. During the tests, the ambient temperature of the laboratory was 21.7°C, the relative humidity was 62% and the liquid depth above the ear reference points was above 15 cm ( $\leq 3G$ ) or 10 cm ( $> 3G$ ) in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.




Fig. b The block diagram of system verification

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Validation Kit | S/N   | Frequency (MHz) |      | 1W Target SAR-1g (mW/g) | Measured SAR-1g (mW/g) | Measured SAR-1g normalized to 1W (mW/g) | Deviation (%) | Measured Date |
|----------------|-------|-----------------|------|-------------------------|------------------------|-----------------------------------------|---------------|---------------|
| D835V2         | 4d063 | 835             | Head | 9.11                    | 2.38                   | 9.52                                    | 4.50%         | Aug. 01, 2016 |
|                |       |                 | Body | 9.28                    | 2.34                   | 9.36                                    | 0.86%         | Aug. 02, 2016 |
| D1900V2        | 5d027 | 1900            | Head | 38.7                    | 9.79                   | 39.16                                   | 1.19%         | Aug. 03, 2016 |
|                |       |                 | Body | 39.7                    | 9.95                   | 39.8                                    | 0.25%         | Jul. 30, 2016 |
| D2450V2        | 727   | 2450            | Head | 51                      | 13.3                   | 53.2                                    | 4.31%         | Jul. 31, 2016 |
|                |       |                 | Body | 49.6                    | 13                     | 52                                      | 4.84%         | Jul. 31, 2016 |
| D2600V2        | 1005  | 2600            | Head | 55.2                    | 14.4                   | 57.6                                    | 4.35%         | Aug. 04, 2016 |
|                |       |                 | Body | 53.9                    | 14                     | 56                                      | 3.90%         | Aug. 05, 2016 |
|                |       |                 |      | 53.9                    | 14                     | 56                                      | 3.90%         | Aug. 06, 2016 |

Table 1. Results of system validation

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### 1.13 Tissue Simulant Fluid for the Frequency Band

The dielectric properties for this Head-simulant fluid were measured by using the Agilent Model 85070E Dielectric Probe (rates frequency band 200 MHz to 20 GHz) in conjunction with Network Analyzer.

All dielectric parameters of tissue simulates were measured within 24 hours of SAR measurements. The depth of the tissue simulant in the flat section of the phantom was at least 15 cm ( $\leq 3G$ ) or 10 cm ( $> 3G$ ) during all tests. (Appendix Fig. 2)

| Tissue Type | Measurement Date | Measured Frequency (MHz) | Target Dielectric Constant, $\epsilon_r$ | Target Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon_r$ | Measured Conductivity, $\sigma$ (S/m) | % dev $\epsilon_r$ | % dev $\sigma$ |
|-------------|------------------|--------------------------|------------------------------------------|-------------------------------------|--------------------------------------------|---------------------------------------|--------------------|----------------|
| Head        | 2016/7/31        | 2450                     | 39.200                                   | 1.800                               | 40.583                                     | 1.831                                 | -3.53%             | -1.72%         |
|             |                  | 2462                     | 39.185                                   | 1.813                               | 40.552                                     | 1.844                                 | -3.49%             | -1.71%         |
|             | 2016/8/1         | 824.2                    | 41.556                                   | 0.899                               | 41.833                                     | 0.912                                 | -0.67%             | -1.43%         |
|             |                  | 826.4                    | 41.545                                   | 0.899                               | 41.821                                     | 0.913                                 | -0.67%             | -1.52%         |
|             |                  | 829                      | 41.531                                   | 0.900                               | 41.805                                     | 0.916                                 | -0.66%             | -1.83%         |
|             |                  | 835                      | 41.500                                   | 0.900                               | 41.782                                     | 0.921                                 | -0.68%             | -2.33%         |
|             | 2016/8/3         | 1850.2                   | 40.000                                   | 1.400                               | 41.366                                     | 1.367                                 | -3.42%             | 2.36%          |
|             |                  | 1880                     | 40.000                                   | 1.400                               | 41.301                                     | 1.392                                 | -3.25%             | 0.57%          |
|             |                  | 1900                     | 40.000                                   | 1.400                               | 41.252                                     | 1.414                                 | -3.13%             | -1.00%         |
|             | 2016/8/4         | 2560                     | 39.060                                   | 1.920                               | 40.491                                     | 1.932                                 | -3.66%             | -0.63%         |
|             |                  | 2580                     | 39.035                                   | 1.942                               | 40.453                                     | 1.958                                 | -3.63%             | -0.82%         |
|             |                  | 2595                     | 39.015                                   | 1.958                               | 40.414                                     | 1.974                                 | -3.59%             | -0.82%         |
|             |                  | 2600                     | 39.009                                   | 1.964                               | 40.403                                     | 1.981                                 | -3.57%             | -0.88%         |
|             |                  | 2610                     | 38.996                                   | 1.975                               | 40.392                                     | 1.995                                 | -3.58%             | -1.01%         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Tissue Type | Measurement Date | Measured Frequency (MHz) | Target Dielectric Constant, $\epsilon_r$ | Target Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon_r$ | Measured Conductivity, $\sigma$ (S/m) | % dev $\epsilon_r$ | % dev $\sigma$ |
|-------------|------------------|--------------------------|------------------------------------------|-------------------------------------|--------------------------------------------|---------------------------------------|--------------------|----------------|
| Body        | 2016/7/30        | 1850.2                   | 53.300                                   | 1.520                               | 52.713                                     | 1.484                                 | 1.10%              | 2.37%          |
|             |                  | 1880                     | 53.300                                   | 1.520                               | 52.684                                     | 1.507                                 | 1.16%              | 0.86%          |
|             |                  | 1900                     | 53.300                                   | 1.520                               | 52.633                                     | 1.522                                 | 1.25%              | -0.13%         |
|             |                  | 1909.8                   | 53.300                                   | 1.520                               | 52.601                                     | 1.529                                 | 1.31%              | -0.59%         |
|             | 2016/7/31        | 2450                     | 52.700                                   | 1.950                               | 51.233                                     | 1.982                                 | 2.78%              | -1.64%         |
|             |                  | 2462                     | 52.685                                   | 1.967                               | 51.204                                     | 1.995                                 | 2.81%              | -1.42%         |
|             | 2016/8/2         | 824.2                    | 55.242                                   | 0.969                               | 54.844                                     | 0.973                                 | 0.72%              | -0.40%         |
|             |                  | 826.4                    | 55.234                                   | 0.969                               | 54.821                                     | 0.974                                 | 0.75%              | -0.48%         |
|             |                  | 829                      | 55.223                                   | 0.970                               | 54.813                                     | 0.979                                 | 0.74%              | -0.98%         |
|             |                  | 835                      | 55.200                                   | 0.970                               | 54.800                                     | 0.984                                 | 0.72%              | -1.44%         |
|             |                  | 836.6                    | 55.195                                   | 0.972                               | 54.792                                     | 0.985                                 | 0.73%              | -1.34%         |
|             |                  | 844                      | 55.172                                   | 0.981                               | 54.763                                     | 0.994                                 | 0.74%              | -1.32%         |
|             |                  | 846.6                    | 55.164                                   | 0.984                               | 54.752                                     | 0.996                                 | 0.75%              | -1.19%         |
|             |                  | 848.8                    | 55.158                                   | 0.987                               | 54.741                                     | 0.999                                 | 0.76%              | -1.22%         |
|             | 2016/8/5         | 2535                     | 52.592                                   | 2.071                               | 52.244                                     | 2.134                                 | 0.66%              | -3.06%         |
|             |                  | 2560                     | 52.560                                   | 2.106                               | 52.203                                     | 2.165                                 | 0.68%              | -2.80%         |
|             |                  | 2580                     | 52.535                                   | 2.134                               | 52.177                                     | 2.189                                 | 0.68%              | -2.58%         |
|             |                  | 2595                     | 52.515                                   | 2.156                               | 52.144                                     | 2.213                                 | 0.71%              | -2.64%         |
|             |                  | 2600                     | 52.509                                   | 2.163                               | 52.135                                     | 2.221                                 | 0.71%              | -2.69%         |
|             |                  | 2610                     | 52.496                                   | 2.177                               | 52.119                                     | 2.236                                 | 0.72%              | -2.71%         |
|             | 2016/8/6         | 2580                     | 52.535                                   | 2.134                               | 52.114                                     | 2.181                                 | 0.80%              | -2.20%         |
|             |                  | 2595                     | 52.515                                   | 2.156                               | 52.074                                     | 2.215                                 | 0.84%              | -2.74%         |
|             |                  | 2600                     | 52.509                                   | 2.163                               | 52.053                                     | 2.219                                 | 0.87%              | -2.60%         |
|             |                  | 2610                     | 52.496                                   | 2.177                               | 52.042                                     | 2.229                                 | 0.86%              | -2.39%         |

Table 2. Dielectric Parameters of Tissue Simulant Fluid

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## The composition of the tissue simulating liquid:

| Frequency<br>(MHz) | Mode | Ingredient |          |         |                  |           |       | Total<br>amount |
|--------------------|------|------------|----------|---------|------------------|-----------|-------|-----------------|
|                    |      | DGMBE      | Water    | Salt    | Preventol<br>D-7 | Cellulose | Sugar |                 |
| 850                | Head | —          | 532.98 g | 18.3 g  | 2.4 g            | 3.2 g     | 766 g | 1.3L(Kg)        |
|                    | Body | —          | 631.68 g | 11.72 g | 1.2 g            | —         | 600 g | 1.0L(Kg)        |
| 1900               | Head | 444.52 g   | 552.42 g | 3.06 g  | —                | —         | —     | 1.0L(Kg)        |
|                    | Body | 300.67 g   | 716.56 g | 4.0 g   | —                | —         | —     | 1.0L(Kg)        |
| 2450               | Head | 550ml      | 450ml    | —       | —                | —         | —     | 1.0L(Kg)        |
|                    | Body | 301.7ml    | 698.3ml  | —       | —                | —         | —     | 1.0L(Kg)        |
| 2600               | Head | 550ml      | 450ml    | —       | —                | —         | —     | 1.0L(Kg)        |
|                    | Body | 301.7ml    | 698.3ml  | —       | —                | —         | —     | 1.0L(Kg)        |

Table 3. Recipes for tissue simulating liquid

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 1.14 Test Standards and Limits

According to FCC 47CFR §2.1093(d) The limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate ("SAR") in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.1, By the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.

These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86, Section 17.4.5. Copyright NCRP, 1986, Bethesda, Maryland 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards. The criteria to be used are specified in paragraphs (d)(1) and (d)(2) of this section and shall apply for portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified in § 1.1310 of this chapter.

Measurements and calculations to demonstrate compliance with MPE field strength or power density limits for devices operating above 6 GHz should be made at a minimum distance of 5 cm from the radiating source.

1. Limits for Occupational/Controlled exposure: 0.4 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 8 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 20 W/kg, as averaged over a 10 grams of tissue (defined as a tissue volume in the shape of a cube).

Occupational/Controlled limits apply when persons are exposed as a consequence of their employment provided these persons are fully aware of and exercise control over their exposure. Awareness of exposure can be accomplished by use of warning labels or by specific training or education through appropriate means, such as an RF safety program in a work environment.

2. Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube).

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube).

General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure.

Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.(Table .6)

| Human Exposure                               | Uncontrolled Environment<br>General Population | Controlled Environment<br>Occupational |
|----------------------------------------------|------------------------------------------------|----------------------------------------|
| Spatial Peak SAR<br>(Brain)                  | 1.60 m W/g                                     | 8.00 m W/g                             |
| Spatial Average SAR<br>(Whole Body)          | 0.08 m W/g                                     | 0.40 m W/g                             |
| Spatial Peak SAR<br>(Hands/Feet/Ankle/Wrist) | 4.00 m W/g                                     | 20.00 m W/g                            |

Table 4. RF exposure limits

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 2. Summary of Results

### GSM 850 MHz

#### Main Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                       | Position    | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------------|-------------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                            |             |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM850 (Head)              | Re Cheek    | -             | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.025                       | 0.028    | -         |
|                            | Re Tilt     | -             | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.007                       | 0.008    | -         |
|                            | Le Cheek    | -             | 128 | 824.2       | 1       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.034                       | 0.042    | -         |
|                            | Le Cheek    | -             | 128 | 824.2       | 1       | 2   | 33.00                                        | 32.12                     | 122.46% | 0.033                       | 0.040    | -         |
|                            | Le Cheek    | -             | 128 | 824.2       | 2       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.029                       | 0.036    | -         |
|                            | Le Cheek    | -             | 128 | 824.2       | 3       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.033                       | 0.040    | -         |
|                            | Le Cheek    | -             | 128 | 824.2       | 4       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.026                       | 0.032    | -         |
|                            | Le Cheek    | -             | 190 | 836.6       | 1       | 1   | 33.00                                        | 32.32                     | 116.95% | 0.026                       | 0.030    | -         |
|                            | Le Cheek    | -             | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.031                       | 0.035    | -         |
|                            | Le Tilt     | -             | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.007                       | 0.008    | -         |
| GSM850 (Body-Worn)         | Front side  | 15            | 128 | 824.2       | 1       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.144                       | 0.176    | -         |
|                            | Front side  | 15            | 190 | 836.6       | 1       | 1   | 33.00                                        | 32.32                     | 116.95% | 0.181                       | 0.212    | -         |
|                            | Front side  | 15            | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.241                       | 0.273    | -         |
|                            | Front side  | 15            | 251 | 848.8       | 1       | 2   | 33.00                                        | 32.46                     | 113.24% | 0.238                       | 0.270    | -         |
|                            | Front side  | 15            | 251 | 848.8       | 2       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.234                       | 0.265    | -         |
|                            | Front side  | 15            | 251 | 848.8       | 3       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.240                       | 0.272    | -         |
|                            | Front side  | 15            | 251 | 848.8       | 4       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.231                       | 0.262    | -         |
|                            | Back side   | 15            | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.198                       | 0.224    | -         |
| GPRS850 (Hotspot) (1Dn2Up) | Front side  | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.393                       | 0.429    | -         |
|                            | Back side   | 10            | 128 | 824.2       | 1       | 1   | 30.50                                        | 29.85                     | 116.14% | 0.420                       | 0.488    | -         |
|                            | Back side   | 10            | 190 | 836.6       | 1       | 1   | 30.50                                        | 30.00                     | 112.20% | 0.461                       | 0.517    | -         |
|                            | Back side   | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.523                       | 0.571    | -         |
|                            | Back side   | 10            | 251 | 848.8       | 1       | 2   | 30.50                                        | 30.12                     | 109.14% | 0.520                       | 0.568    | -         |
|                            | Back side   | 10            | 251 | 848.8       | 2       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.512                       | 0.559    | -         |
|                            | Back side   | 10            | 251 | 848.8       | 3       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.518                       | 0.565    | -         |
|                            | Back side   | 10            | 251 | 848.8       | 4       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.505                       | 0.551    | -         |
|                            | Bottom side | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.303                       | 0.331    | -         |
|                            | Right side  | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.303                       | 0.331    | -         |
|                            | Left side   | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.245                       | 0.267    | -         |
|                            |             |               |     |             |         |     |                                              |                           |         |                             |          |           |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                       | Position   | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------------|------------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                            |            |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM850 (Head)              | Le Cheek   | -             | 128 | 824.2       | 1       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.024                       | 0.029    | -         |
|                            | Le Cheek   | -             | 128 | 824.2       | 2       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.034                       | 0.042    | 124       |
|                            | Le Cheek   | -             | 128 | 824.2       | 3       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.030                       | 0.037    | -         |
|                            | Le Cheek   | -             | 128 | 824.2       | 4       | 1   | 33.00                                        | 32.12                     | 122.46% | 0.031                       | 0.038    | -         |
| GSM850 (Body-Worn)         | Front side | 15            | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.213                       | 0.241    | -         |
|                            | Front side | 15            | 251 | 848.8       | 2       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.231                       | 0.262    | -         |
|                            | Front side | 15            | 251 | 848.8       | 3       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.224                       | 0.254    | -         |
|                            | Front side | 15            | 251 | 848.8       | 4       | 1   | 33.00                                        | 32.46                     | 113.24% | 0.235                       | 0.266    | 125       |
| GPRS850 (Hotspot) (1Dn2Up) | Back side  | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.481                       | 0.525    | -         |
|                            | Back side  | 10            | 251 | 848.8       | 2       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.576                       | 0.629    | -         |
|                            | Back side  | 10            | 251 | 848.8       | 3       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.520                       | 0.568    | -         |
|                            | Back side  | 10            | 251 | 848.8       | 4       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.580                       | 0.633    | 126       |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Sub Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                       | Position   | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------------|------------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                            |            |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM850 (Head)              | Re Cheek   | -             | 128 | 824.2       | 1       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.998                       | 1.222    | -         |
|                            | Re Cheek*  | -             | 128 | 824.2       | 1       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.995                       | 1.218    | -         |
|                            | Re Cheek   | -             | 128 | 824.2       | 1       | 2   | 30.50                                        | 29.62                     | 122.46% | 0.995                       | 1.218    | -         |
|                            | Re Cheek   | -             | 128 | 824.2       | 2       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.989                       | 1.211    | -         |
|                            | Re Cheek   | -             | 128 | 824.2       | 3       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.968                       | 1.185    | -         |
|                            | Re Cheek   | -             | 128 | 824.2       | 4       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.952                       | 1.166    | -         |
|                            | Re Cheek   | -             | 190 | 836.6       | 1       | 1   | 30.50                                        | 29.78                     | 118.03% | 0.948                       | 1.119    | -         |
|                            | Re Cheek   | -             | 251 | 848.8       | 1       | 1   | 30.50                                        | 29.87                     | 115.61% | 0.843                       | 0.975    | -         |
|                            | Re Tilt    | -             | 128 | 824.2       | 1       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.845                       | 1.035    | -         |
|                            | Re Tilt    | -             | 190 | 836.6       | 1       | 1   | 30.50                                        | 29.78                     | 118.03% | 0.802                       | 0.947    | -         |
|                            | Re Tilt    | -             | 251 | 848.8       | 1       | 1   | 30.50                                        | 29.87                     | 115.61% | 0.708                       | 0.819    | -         |
|                            | Le Cheek   | -             | 251 | 848.8       | 1       | 1   | 30.50                                        | 29.87                     | 115.61% | 0.517                       | 0.598    | -         |
|                            | Le Tilt    | -             | 251 | 848.8       | 1       | 1   | 30.50                                        | 29.87                     | 115.61% | 0.519                       | 0.600    | -         |
| GSM850 (Body-Worn)         | Front side | 15            | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.52                     | 111.69% | 0.177                       | 0.198    | -         |
|                            | Back side  | 15            | 128 | 824.2       | 1       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.240                       | 0.280    | -         |
|                            | Back side  | 15            | 128 | 824.2       | 1       | 2   | 33.00                                        | 32.33                     | 116.68% | 0.238                       | 0.278    | -         |
|                            | Back side  | 15            | 128 | 824.2       | 2       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.248                       | 0.289    | -         |
|                            | Back side  | 15            | 128 | 824.2       | 3       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.212                       | 0.247    | -         |
|                            | Back side  | 15            | 128 | 824.2       | 4       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.201                       | 0.235    | -         |
|                            | Back side  | 15            | 190 | 836.6       | 1       | 1   | 33.00                                        | 32.44                     | 113.76% | 0.241                       | 0.274    | -         |
|                            | Back side  | 15            | 251 | 848.8       | 1       | 1   | 33.00                                        | 32.52                     | 111.69% | 0.207                       | 0.231    | -         |
| GPRS850 (Hotspot) (1Dn2Up) | Front side | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.19                     | 107.40% | 0.435                       | 0.467    | -         |
|                            | Back side  | 10            | 128 | 824.2       | 1       | 1   | 30.50                                        | 29.89                     | 115.08% | 0.520                       | 0.598    | -         |
|                            | Back side  | 10            | 190 | 836.6       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.562                       | 0.613    | -         |
|                            | Back side  | 10            | 190 | 836.6       | 1       | 2   | 30.50                                        | 30.12                     | 109.14% | 0.560                       | 0.611    | -         |
|                            | Back side  | 10            | 190 | 836.6       | 2       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.555                       | 0.606    | -         |
|                            | Back side  | 10            | 190 | 836.6       | 3       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.524                       | 0.572    | -         |
|                            | Back side  | 10            | 190 | 836.6       | 4       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.512                       | 0.559    | -         |
|                            | Back side  | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.19                     | 107.40% | 0.535                       | 0.575    | -         |
|                            | Top side   | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.19                     | 107.40% | 0.347                       | 0.373    | -         |
|                            | Left side  | 10            | 251 | 848.8       | 1       | 1   | 30.50                                        | 30.19                     | 107.40% | 0.262                       | 0.281    | -         |

\* - repeated at the highest SAR measurement according to the KDB865664D01v01r04

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                       | Position  | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|----------------------------|-----------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                            |           |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM850 (Head)              | Re Cheek  | -             | 128 | 824.2       | 1       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.944                       | 1.156    | -         |
|                            | Re Cheek  | -             | 128 | 824.2       | 2       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.989                       | 1.211    | -         |
|                            | Re Cheek  | -             | 128 | 824.2       | 3       | 1   | 30.50                                        | 29.62                     | 122.46% | 0.966                       | 1.183    | -         |
|                            | Re Cheek  | -             | 128 | 824.2       | 4       | 1   | 30.50                                        | 29.62                     | 122.46% | 1.000                       | 1.225    | 127       |
| GSM850 (Body-Worn)         | Back side | 15            | 128 | 824.2       | 1       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.213                       | 0.249    | -         |
|                            | Back side | 15            | 128 | 824.2       | 2       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.251                       | 0.293    | -         |
|                            | Back side | 15            | 128 | 824.2       | 3       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.268                       | 0.313    | 128       |
|                            | Back side | 15            | 128 | 824.2       | 4       | 1   | 33.00                                        | 32.33                     | 116.68% | 0.259                       | 0.302    | -         |
| GPRS850 (Hotspot) (1Dn2Up) | Back side | 10            | 190 | 836.6       | 1       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.551                       | 0.601    | -         |
|                            | Back side | 10            | 190 | 836.6       | 2       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.615                       | 0.671    | 129       |
|                            | Back side | 10            | 190 | 836.6       | 3       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.566                       | 0.618    | -         |
|                            | Back side | 10            | 190 | 836.6       | 4       | 1   | 30.50                                        | 30.12                     | 109.14% | 0.585                       | 0.638    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**GSM 1900 MHz****Main Antenna**

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                        | Position     | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------------------|--------------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                             |              |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM1900 (Head)              | Re Cheek     | -             | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.053                       | 0.064    | -         |
|                             | Re Tilt      | -             | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.032                       | 0.039    | -         |
|                             | Le Cheek     | -             | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.088                       | 0.106    | -         |
|                             | Le Cheek     | -             | 512 | 1850.2      | 1       | 2   | 30.00                                        | 29.18                     | 120.78% | 0.086                       | 0.104    | -         |
|                             | Le Cheek     | -             | 512 | 1850.2      | 2       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.081                       | 0.098    | -         |
|                             | Le Cheek     | -             | 512 | 1850.2      | 3       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.072                       | 0.087    | -         |
|                             | Le Cheek     | -             | 512 | 1850.2      | 4       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.075                       | 0.091    | -         |
|                             | Le Cheek     | -             | 661 | 1880        | 1       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.064                       | 0.078    | -         |
|                             | Le Cheek     | -             | 810 | 1909.8      | 1       | 1   | 30.00                                        | 29.17                     | 121.06% | 0.059                       | 0.071    | -         |
| GSM1900 (Body-Worn)         | Le Tilt      | -             | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.028                       | 0.034    | -         |
|                             | Front side   | 15            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.196                       | 0.237    | -         |
|                             | Back side    | 15            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.250                       | 0.302    | -         |
|                             | Back side    | 15            | 512 | 1850.2      | 1       | 2   | 30.00                                        | 29.18                     | 120.78% | 0.248                       | 0.300    | -         |
|                             | Back side    | 15            | 512 | 1850.2      | 2       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.235                       | 0.284    | -         |
|                             | Back side    | 15            | 512 | 1850.2      | 3       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.245                       | 0.296    | -         |
|                             | Back side    | 15            | 512 | 1850.2      | 4       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.231                       | 0.279    | -         |
|                             | Back side    | 15            | 661 | 1880        | 1       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.240                       | 0.294    | -         |
|                             | Back side    | 15            | 810 | 1909.8      | 1       | 1   | 30.00                                        | 29.17                     | 121.06% | 0.225                       | 0.272    | -         |
| GPRS1900 (Hotspot) (1Dn2Up) | Front side   | 10            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.368                       | 0.444    | -         |
|                             | Back side    | 10            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.435                       | 0.525    | -         |
|                             | Bottom side  | 10            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.864                       | 1.044    | -         |
|                             | Bottom side  | 10            | 661 | 1880        | 1       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.887                       | 1.086    | -         |
|                             | Bottom side* | 10            | 661 | 1880        | 1       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.882                       | 1.080    | -         |
|                             | Bottom side  | 10            | 661 | 1880        | 1       | 2   | 30.00                                        | 29.12                     | 122.46% | 0.885                       | 1.084    | -         |
|                             | Bottom side  | 10            | 661 | 1880        | 2       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.842                       | 1.031    | -         |
|                             | Bottom side  | 10            | 661 | 1880        | 3       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.878                       | 1.075    | -         |
|                             | Bottom side  | 10            | 661 | 1880        | 4       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.835                       | 1.023    | -         |
|                             | Bottom side  | 10            | 810 | 1909.8      | 1       | 1   | 30.00                                        | 29.17                     | 121.06% | 0.872                       | 1.056    | -         |
|                             | Right side   | 10            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.017                       | 0.021    | -         |
|                             | Left side    | 10            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.083                       | 0.100    | -         |

\* - repeated at the highest SAR measurement according to the KDB865664D01v01r04

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                        | Position    | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------------------|-------------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                             |             |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM1900 (Head)              | Le Cheek    | -             | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.048                       | 0.058    | -         |
|                             | Le Cheek    | -             | 512 | 1850.2      | 2       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.076                       | 0.092    | 130       |
|                             | Le Cheek    | -             | 512 | 1850.2      | 3       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.074                       | 0.089    | -         |
|                             | Le Cheek    | -             | 512 | 1850.2      | 4       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.063                       | 0.076    | -         |
| GSM1900 (Body-Worn)         | Back side   | 15            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.174                       | 0.210    | -         |
|                             | Back side   | 15            | 512 | 1850.2      | 2       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.219                       | 0.265    | 131       |
|                             | Back side   | 15            | 512 | 1850.2      | 3       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.213                       | 0.257    | -         |
|                             | Back side   | 15            | 512 | 1850.2      | 4       | 1   | 30.00                                        | 29.18                     | 120.78% | 0.192                       | 0.232    | -         |
| GPRS1900 (Hotspot) (1Dn2Up) | Bottom side | 10            | 661 | 1880        | 1       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.563                       | 0.689    | -         |
|                             | Bottom side | 10            | 661 | 1880        | 2       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.758                       | 0.928    | 132       |
|                             | Bottom side | 10            | 661 | 1880        | 3       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.742                       | 0.909    | -         |
|                             | Bottom side | 10            | 661 | 1880        | 4       | 1   | 30.00                                        | 29.12                     | 122.46% | 0.681                       | 0.834    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Sub Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                        | Position   | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------------------|------------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                             |            |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM1900 (Head)              | Re Cheek   | -             | 661 | 1880        | 1       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.353                       | 0.432    | -         |
|                             | Re Tilt    | -             | 512 | 1850.2      | 1       | 1   | 29.00                                        | 28.10                     | 123.03% | 0.328                       | 0.404    | -         |
|                             | Re Tilt    | -             | 661 | 1880        | 1       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.355                       | 0.435    | -         |
|                             | Re Tilt    | -             | 661 | 1880        | 1       | 2   | 29.00                                        | 28.12                     | 122.46% | 0.351                       | 0.430    | -         |
|                             | Re Tilt    | -             | 661 | 1880        | 2       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.342                       | 0.419    | -         |
|                             | Re Tilt    | -             | 661 | 1880        | 3       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.313                       | 0.383    | -         |
|                             | Re Tilt    | -             | 661 | 1880        | 4       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.350                       | 0.429    | -         |
|                             | Re Tilt    | -             | 810 | 1909.8      | 1       | 1   | 29.00                                        | 28.10                     | 123.03% | 0.317                       | 0.390    | -         |
|                             | Le Cheek   | -             | 661 | 1880        | 1       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.124                       | 0.152    | -         |
| GSM1900 (Body-Worn)         | Le Tilt    | -             | 661 | 1880        | 1       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.162                       | 0.198    | -         |
|                             | Front side | 15            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 28.85                     | 130.32% | 0.073                       | 0.095    | -         |
|                             | Front side | 15            | 661 | 1880        | 1       | 1   | 30.00                                        | 28.75                     | 133.35% | 0.077                       | 0.103    | -         |
|                             | Front side | 15            | 810 | 1909.8      | 1       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.083                       | 0.111    | -         |
|                             | Front side | 15            | 810 | 1909.8      | 1       | 2   | 30.00                                        | 28.72                     | 134.28% | 0.081                       | 0.109    | -         |
|                             | Front side | 15            | 810 | 1909.8      | 2       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.075                       | 0.101    | -         |
|                             | Front side | 15            | 810 | 1909.8      | 3       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.064                       | 0.086    | -         |
|                             | Front side | 15            | 810 | 1909.8      | 4       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.080                       | 0.107    | -         |
|                             | Back side  | 15            | 512 | 1850.2      | 1       | 1   | 30.00                                        | 28.85                     | 130.32% | 0.072                       | 0.094    | -         |
| GPRS1900 (Hotspot) (1Dn2Up) | Front side | 10            | 512 | 1850.2      | 1       | 1   | 28.00                                        | 27.15                     | 121.62% | 0.231                       | 0.281    | -         |
|                             | Back side  | 10            | 512 | 1850.2      | 1       | 1   | 28.00                                        | 27.15                     | 121.62% | 0.234                       | 0.285    | -         |
|                             | Top side   | 10            | 512 | 1850.2      | 1       | 1   | 28.00                                        | 27.15                     | 121.62% | 0.273                       | 0.332    | -         |
|                             | Top side   | 10            | 661 | 1880        | 1       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.284                       | 0.351    | -         |
|                             | Top side   | 10            | 661 | 1880        | 1       | 2   | 28.00                                        | 27.08                     | 123.59% | 0.281                       | 0.347    | -         |
|                             | Top side   | 10            | 661 | 1880        | 2       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.271                       | 0.335    | -         |
|                             | Top side   | 10            | 661 | 1880        | 3       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.242                       | 0.299    | -         |
|                             | Top side   | 10            | 661 | 1880        | 4       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.277                       | 0.342    | -         |
|                             | Top side   | 10            | 810 | 1909.8      | 1       | 1   | 28.00                                        | 27.05                     | 124.45% | 0.275                       | 0.342    | -         |
|                             | Left side  | 10            | 512 | 1850.2      | 1       | 1   | 28.00                                        | 27.15                     | 121.62% | 0.224                       | 0.272    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                        | Position   | Distance (mm) | CH  | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------------------|------------|---------------|-----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                             |            |               |     |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| GSM1900 (Head)              | Re Tilt    | -             | 661 | 1880        | 1       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.174                       | 0.213    | -         |
|                             | Re Tilt    | -             | 661 | 1880        | 2       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.353                       | 0.432    | 133       |
|                             | Re Tilt    | -             | 661 | 1880        | 3       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.346                       | 0.424    | -         |
|                             | Re Tilt    | -             | 661 | 1880        | 4       | 1   | 29.00                                        | 28.12                     | 122.46% | 0.315                       | 0.386    | -         |
| GSM1900 (Body-Worn)         | Front side | 15            | 810 | 1909.8      | 1       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.021                       | 0.028    | -         |
|                             | Front side | 15            | 810 | 1909.8      | 2       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.083                       | 0.111    | 134       |
|                             | Front side | 15            | 810 | 1909.8      | 3       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.081                       | 0.109    | -         |
|                             | Front side | 15            | 810 | 1909.8      | 4       | 1   | 30.00                                        | 28.72                     | 134.28% | 0.069                       | 0.093    | -         |
| GPRS1900 (Hotspot) (1Dn2Up) | Top side   | 10            | 661 | 1880        | 1       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.123                       | 0.152    | -         |
|                             | Top side   | 10            | 661 | 1880        | 2       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.285                       | 0.352    | 135       |
|                             | Top side   | 10            | 661 | 1880        | 3       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.262                       | 0.324    | -         |
|                             | Top side   | 10            | 661 | 1880        | 4       | 1   | 28.00                                        | 27.08                     | 123.59% | 0.223                       | 0.276    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**WCDMA Band V****Main Antenna**

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode            | Position    | Distance (mm) | CH   | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------|-------------|---------------|------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                 |             |               |      |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| R99 (Head)      | Re Cheek    | -             | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.033                       | 0.040    | -         |
|                 | Re Tilt     | -             | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.015                       | 0.018    | -         |
|                 | Le Cheek    | -             | 4132 | 826.4       | 1       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.049                       | 0.060    | -         |
|                 | Le Cheek    | -             | 4132 | 826.4       | 1       | 2   | 24.50                                        | 23.65                     | 121.62% | 0.047                       | 0.057    | -         |
|                 | Le Cheek    | -             | 4132 | 826.4       | 2       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.042                       | 0.051    | -         |
|                 | Le Cheek    | -             | 4132 | 826.4       | 3       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.041                       | 0.050    | -         |
|                 | Le Cheek    | -             | 4132 | 826.4       | 4       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.035                       | 0.043    | -         |
|                 | Le Cheek    | -             | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.036                       | 0.044    | -         |
|                 | Le Cheek    | -             | 4233 | 846.6       | 1       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.037                       | 0.046    | -         |
|                 | Le Tilt     | -             | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.026                       | 0.031    | -         |
| R99 (Body-Worn) | Front side  | 15            | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.066                       | 0.080    | -         |
|                 | Back side   | 15            | 4132 | 826.4       | 1       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.202                       | 0.246    | -         |
|                 | Back side   | 15            | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.179                       | 0.217    | -         |
|                 | Back side   | 15            | 4233 | 846.6       | 1       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.216                       | 0.268    | -         |
|                 | Back side   | 15            | 4233 | 846.6       | 1       | 2   | 24.50                                        | 23.56                     | 124.17% | 0.210                       | 0.261    | -         |
|                 | Back side   | 15            | 4233 | 846.6       | 2       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.200                       | 0.248    | -         |
|                 | Back side   | 15            | 4233 | 846.6       | 3       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.208                       | 0.258    | -         |
|                 | Back side   | 15            | 4233 | 846.6       | 4       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.191                       | 0.237    | -         |
| R99 (Hotspot)   | Front side  | 10            | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.315                       | 0.381    | -         |
|                 | Back side   | 10            | 4132 | 826.4       | 1       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.357                       | 0.434    | -         |
|                 | Back side   | 10            | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.404                       | 0.489    | -         |
|                 | Back side   | 10            | 4233 | 846.6       | 1       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.504                       | 0.626    | -         |
|                 | Back side   | 10            | 4233 | 846.6       | 2       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.521                       | 0.647    | -         |
|                 | Back side   | 10            | 4233 | 846.6       | 3       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.493                       | 0.612    | -         |
|                 | Back side   | 10            | 4233 | 846.6       | 4       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.482                       | 0.598    | -         |
|                 | Bottom side | 10            | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.177                       | 0.214    | -         |
|                 | Right side  | 10            | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.242                       | 0.293    | -         |
|                 | Left side   | 10            | 4183 | 836.6       | 1       | 1   | 24.50                                        | 23.67                     | 121.06% | 0.086                       | 0.104    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode            | Position  | Distance (mm) | CH   | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------|-----------|---------------|------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                 |           |               |      |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| R99 (Head)      | Le Cheek  | -             | 4132 | 826.4       | 1       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.052                       | 0.063    | -         |
|                 | Le Cheek  | -             | 4132 | 826.4       | 2       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.053                       | 0.064    | -         |
|                 | Le Cheek  | -             | 4132 | 826.4       | 3       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.061                       | 0.074    | -         |
|                 | Le Cheek  | -             | 4132 | 826.4       | 4       | 1   | 24.50                                        | 23.65                     | 121.62% | 0.067                       | 0.081    | 136       |
| R99 (Body-Worn) | Back side | 15            | 4233 | 846.6       | 1       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.283                       | 0.351    | -         |
|                 | Back side | 15            | 4233 | 846.6       | 2       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.305                       | 0.379    | 137       |
|                 | Back side | 15            | 4233 | 846.6       | 3       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.295                       | 0.366    | -         |
|                 | Back side | 15            | 4233 | 846.6       | 4       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.301                       | 0.374    | -         |
| R99 (Hotspot)   | Back side | 10            | 4233 | 846.6       | 1       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.592                       | 0.735    | -         |
|                 | Back side | 10            | 4233 | 846.6       | 2       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.588                       | 0.730    | -         |
|                 | Back side | 10            | 4233 | 846.6       | 3       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.613                       | 0.761    | -         |
|                 | Back side | 10            | 4233 | 846.6       | 4       | 1   | 24.50                                        | 23.56                     | 124.17% | 0.619                       | 0.769    | 138       |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Sub Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode            | Position   | Distance (mm) | CH   | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------|------------|---------------|------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                 |            |               |      |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| R99 (Head)      | Re Cheek   | -             | 4132 | 826.4       | 1       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.831                       | 1.041    | -         |
|                 | Re Cheek   | -             | 4132 | 826.4       | 1       | 2   | 21.50                                        | 20.52                     | 125.31% | 0.825                       | 1.034    | -         |
|                 | Re Cheek   | -             | 4132 | 826.4       | 2       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.828                       | 1.038    | -         |
|                 | Re Cheek   | -             | 4132 | 826.4       | 3       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.804                       | 1.008    | -         |
|                 | Re Cheek   | -             | 4132 | 826.4       | 4       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.782                       | 0.980    | -         |
|                 | Re Cheek   | -             | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.725                       | 0.886    | -         |
|                 | Re Cheek   | -             | 4233 | 846.6       | 1       | 1   | 21.50                                        | 20.42                     | 128.23% | 0.629                       | 0.807    | -         |
|                 | Re Tilt    | -             | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.643                       | 0.786    | -         |
|                 | Le Cheek   | -             | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.455                       | 0.556    | -         |
|                 | Le Tilt    | -             | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.446                       | 0.545    | -         |
| R99 (Body-Worn) | Front side | 15            | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.099                       | 0.121    | -         |
|                 | Back side  | 15            | 4132 | 826.4       | 1       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.112                       | 0.140    | -         |
|                 | Back side  | 15            | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.124                       | 0.152    | -         |
|                 | Back side  | 15            | 4183 | 836.6       | 1       | 2   | 21.50                                        | 20.63                     | 122.18% | 0.123                       | 0.150    | -         |
|                 | Back side  | 15            | 4183 | 836.6       | 2       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.131                       | 0.160    | -         |
|                 | Back side  | 15            | 4183 | 836.6       | 3       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.112                       | 0.137    | -         |
|                 | Back side  | 15            | 4183 | 836.6       | 4       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.102                       | 0.125    | -         |
|                 | Back side  | 15            | 4233 | 846.6       | 1       | 1   | 21.50                                        | 20.42                     | 128.23% | 0.091                       | 0.117    | -         |
| R99 (Hotspot)   | Front side | 10            | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.222                       | 0.271    | -         |
|                 | Back side  | 10            | 4132 | 826.4       | 1       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.291                       | 0.365    | -         |
|                 | Back side  | 10            | 4132 | 826.4       | 2       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.285                       | 0.357    | -         |
|                 | Back side  | 10            | 4132 | 826.4       | 3       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.273                       | 0.342    | -         |
|                 | Back side  | 10            | 4132 | 826.4       | 4       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.255                       | 0.320    | -         |
|                 | Back side  | 10            | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.273                       | 0.334    | -         |
|                 | Back side  | 10            | 4233 | 846.6       | 1       | 1   | 21.50                                        | 20.42                     | 128.23% | 0.245                       | 0.314    | -         |
|                 | Top side   | 10            | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.188                       | 0.230    | -         |
|                 | Left side  | 10            | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.125                       | 0.153    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode            | Position  | Distance (mm) | CH   | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-----------------|-----------|---------------|------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                 |           |               |      |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| R99 (Head)      | Re Cheek  | -             | 4132 | 826.4       | 1       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.841                       | 1.054    | 139       |
|                 | Re Cheek  | -             | 4132 | 826.4       | 2       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.834                       | 1.045    | -         |
|                 | Re Cheek  | -             | 4132 | 826.4       | 3       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.821                       | 1.029    | -         |
|                 | Re Cheek  | -             | 4132 | 826.4       | 4       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.824                       | 1.033    | -         |
| R99 (Body-Worn) | Back side | 15            | 4183 | 836.6       | 1       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.145                       | 0.177    | 140       |
|                 | Back side | 15            | 4183 | 836.6       | 2       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.141                       | 0.172    | -         |
|                 | Back side | 15            | 4183 | 836.6       | 3       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.125                       | 0.153    | -         |
|                 | Back side | 15            | 4183 | 836.6       | 4       | 1   | 21.50                                        | 20.63                     | 122.18% | 0.133                       | 0.162    | -         |
| R99 (Hotspot)   | Back side | 10            | 4132 | 826.4       | 1       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.307                       | 0.385    | -         |
|                 | Back side | 10            | 4132 | 826.4       | 2       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.298                       | 0.373    | -         |
|                 | Back side | 10            | 4132 | 826.4       | 3       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.285                       | 0.357    | -         |
|                 | Back side | 10            | 4132 | 826.4       | 4       | 1   | 21.50                                        | 20.52                     | 125.31% | 0.317                       | 0.397    | 141       |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## LTE FDD Band V

## Main Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Toleranc e (dBm) | Measure d Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|---------|-----|-----------------------------------------------|----------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |             |               |       |             |         |     |                                               |                            |         | Measured                    | Reported |           |
| LTE Band 5 (Head)      | 10MHz           | QPSK       | 1 RB    | 25       | RE Cheek    | -             | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.035                       | 0.041    | -         |
|                        |                 |            |         |          | RE Tilt     | -             | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.017                       | 0.020    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.043                       | 0.050    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20450 | 829         | 2       | 1   | 24                                            | 23.35                      | 116.14% | 0.042                       | 0.049    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20450 | 829         | 3       | 1   | 24                                            | 23.35                      | 116.14% | 0.037                       | 0.043    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20450 | 829         | 4       | 1   | 24                                            | 23.35                      | 116.14% | 0.032                       | 0.037    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20525 | 836.5       | 1       | 1   | 24                                            | 23.17                      | 121.06% | 0.027                       | 0.033    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20600 | 844         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.026                       | 0.030    | -         |
|                        |                 |            |         |          | LE Tilt     | -             | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.009                       | 0.011    | -         |
|                        |                 |            | 25 RB   | 0        | RE Cheek    | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.025                       | 0.029    | -         |
|                        |                 |            |         |          | RE Tilt     | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.012                       | 0.014    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.022                       | 0.026    | -         |
|                        |                 |            |         |          | LE Tilt     | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.007                       | 0.008    | -         |
|                        |                 |            | 50 RB   |          | RE Cheek    | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.025                       | 0.029    | -         |
|                        |                 |            |         |          | RE Tilt     | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.012                       | 0.014    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.021                       | 0.025    | -         |
|                        |                 |            |         |          | LE Tilt     | -             | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.007                       | 0.008    | -         |
| LTE Band 5 (Body-Worn) | 10MHz           | QPSK       | 1 RB    | 25       | Front side  | 15            | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.158                       | 0.184    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.176                       | 0.204    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20525 | 836.5       | 1       | 1   | 24                                            | 23.17                      | 121.06% | 0.174                       | 0.211    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20600 | 844         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.201                       | 0.233    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20600 | 844         | 2       | 1   | 24                                            | 23.35                      | 116.14% | 0.212                       | 0.246    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20600 | 844         | 3       | 1   | 24                                            | 23.35                      | 116.14% | 0.184                       | 0.214    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20600 | 844         | 4       | 1   | 24                                            | 23.35                      | 116.14% | 0.175                       | 0.203    | -         |
|                        |                 |            | 25 RB   | 0        | Front side  | 15            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.121                       | 0.142    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.135                       | 0.159    | -         |
|                        |                 |            |         |          | Front side  | 15            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.121                       | 0.142    | -         |
|                        |                 |            |         |          | Back side   | 15            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.134                       | 0.158    | -         |
|                        |                 |            | 50 RB   |          | Front side  | 10            | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.246                       | 0.286    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.329                       | 0.382    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20525 | 836.5       | 1       | 1   | 24                                            | 23.17                      | 121.06% | 0.380                       | 0.460    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20600 | 844         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.446                       | 0.518    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20600 | 844         | 2       | 1   | 24                                            | 23.35                      | 116.14% | 0.462                       | 0.537    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20600 | 844         | 3       | 1   | 24                                            | 23.35                      | 116.14% | 0.404                       | 0.469    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20600 | 844         | 4       | 1   | 24                                            | 23.35                      | 116.14% | 0.423                       | 0.491    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.164                       | 0.190    | -         |
| LTE Band 5 (Hotspot)   | 10MHz           | QPSK       | 1 RB    | 25       | Right side  | 10            | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.206                       | 0.239    | -         |
|                        |                 |            |         |          | Left side   | 10            | 20450 | 829         | 1       | 1   | 24                                            | 23.35                      | 116.14% | 0.088                       | 0.102    | -         |
|                        |                 |            | 25 RB   | 0        | Front side  | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.181                       | 0.213    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.254                       | 0.299    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.125                       | 0.147    | -         |
|                        |                 |            |         |          | Right side  | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.164                       | 0.193    | -         |
|                        |                 |            |         |          | Left side   | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.064                       | 0.075    | -         |
|                        |                 |            | 50 RB   |          | Front side  | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.185                       | 0.218    | -         |
|                        |                 |            |         |          | Back side   | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.256                       | 0.301    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.125                       | 0.147    | -         |
|                        |                 |            |         |          | Right side  | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.165                       | 0.194    | -         |
|                        |                 |            |         |          | Left side   | 10            | 20525 | 836.5       | 1       | 1   | 23                                            | 22.29                      | 117.76% | 0.064                       | 0.075    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position  | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|-----------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |           |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 5 (Head)      | 10MHz           | QPSK       | 1 RB    | 25       | LE Cheek  | -             | 20450 | 829         | 1       | 1   | 24                                           | 23.35                     | 116.14% | 0.044                       | 0.051    | -         |
|                        |                 |            |         |          | LE Cheek  | -             | 20450 | 829         | 2       | 1   | 24                                           | 23.35                     | 116.14% | 0.049                       | 0.057    | -         |
|                        |                 |            |         |          | LE Cheek  | -             | 20450 | 829         | 3       | 1   | 24                                           | 23.35                     | 116.14% | 0.056                       | 0.065    | 142       |
|                        |                 |            |         |          | LE Cheek  | -             | 20450 | 829         | 4       | 1   | 24                                           | 23.35                     | 116.14% | 0.052                       | 0.060    | -         |
| LTE Band 5 (Body-Worn) | 10MHz           | QPSK       | 1 RB    | 25       | Back side | 15            | 20600 | 844         | 1       | 1   | 24                                           | 23.35                     | 116.14% | 0.247                       | 0.287    | -         |
|                        |                 |            |         |          | Back side | 15            | 20600 | 844         | 2       | 1   | 24                                           | 23.35                     | 116.14% | 0.254                       | 0.295    | -         |
|                        |                 |            |         |          | Back side | 15            | 20600 | 844         | 3       | 1   | 24                                           | 23.35                     | 116.14% | 0.249                       | 0.289    | -         |
|                        |                 |            |         |          | Back side | 15            | 20600 | 844         | 4       | 1   | 24                                           | 23.35                     | 116.14% | 0.260                       | 0.302    | 143       |
| LTE Band 5 (Hotspot)   | 10MHz           | QPSK       | 1 RB    | 25       | Back side | 10            | 20600 | 844         | 1       | 1   | 24                                           | 23.35                     | 116.14% | 0.475                       | 0.552    | -         |
|                        |                 |            |         |          | Back side | 10            | 20600 | 844         | 2       | 1   | 24                                           | 23.35                     | 116.14% | 0.518                       | 0.602    | -         |
|                        |                 |            |         |          | Back side | 10            | 20600 | 844         | 3       | 1   | 24                                           | 23.35                     | 116.14% | 0.526                       | 0.611    | 144       |
|                        |                 |            |         |          | Back side | 10            | 20600 | 844         | 4       | 1   | 24                                           | 23.35                     | 116.14% | 0.523                       | 0.607    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Sub Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position   | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|------------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |            |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 5 (Head)      | 10MHz           | QPSK       | 1 RB    | 25       | RE Cheek   | -             | 20450 | 829         | 1       | 1   | 22                                           | 20.92                     | 128.23% | 0.930                       | 1.193    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 20450 | 829         | 2       | 1   | 22                                           | 20.92                     | 128.23% | 0.925                       | 1.186    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 20450 | 829         | 3       | 1   | 22                                           | 20.92                     | 128.23% | 0.902                       | 1.157    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 20450 | 829         | 4       | 1   | 22                                           | 20.92                     | 128.23% | 0.884                       | 1.134    | -         |
|                        |                 |            |         |          | RE Cheek*  | -             | 20450 | 829         | 1       | 1   | 22                                           | 20.92                     | 128.23% | 0.922                       | 1.182    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 20525 | 836.5       | 1       | 1   | 22                                           | 21.12                     | 122.46% | 0.825                       | 1.010    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.726                       | 0.877    | -         |
|                        |                 |            |         |          | RE Tilt    | -             | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.636                       | 0.768    | -         |
|                        |                 |            |         |          | LE Cheek   | -             | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.445                       | 0.537    | -         |
|                        |                 |            |         |          | LE Tilt    | -             | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.429                       | 0.518    | -         |
|                        |                 |            | 25 RB   | 12       | RE Cheek   | -             | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.653                       | 0.792    | -         |
|                        |                 |            |         |          | RE Tilt    | -             | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.525                       | 0.637    | -         |
|                        |                 |            |         |          | LE Cheek   | -             | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.394                       | 0.478    | -         |
|                        |                 |            | 50 RB   |          | LE Tilt    | -             | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.388                       | 0.471    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.603                       | 0.732    | -         |
|                        |                 |            |         |          | RE Tilt    | -             | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.491                       | 0.596    | -         |
|                        |                 |            |         |          | LE Cheek   | -             | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.359                       | 0.436    | -         |
|                        |                 |            |         |          | LE Tilt    | -             | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.348                       | 0.422    | -         |
| LTE Band 5 (Body-Worn) | 10MHz           | QPSK       | 1 RB    | 25       | Front side | 15            | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.105                       | 0.127    | -         |
|                        |                 |            |         |          | Back side  | 15            | 20450 | 829         | 1       | 1   | 22                                           | 20.92                     | 128.23% | 0.139                       | 0.178    | -         |
|                        |                 |            |         |          | Back side  | 15            | 20450 | 829         | 2       | 1   | 22                                           | 20.92                     | 128.23% | 0.145                       | 0.186    | -         |
|                        |                 |            |         |          | Back side  | 15            | 20450 | 829         | 3       | 1   | 22                                           | 20.92                     | 128.23% | 0.128                       | 0.164    | -         |
|                        |                 |            |         |          | Back side  | 15            | 20450 | 829         | 4       | 1   | 22                                           | 20.92                     | 128.23% | 0.121                       | 0.155    | -         |
|                        |                 |            |         |          | Back side  | 15            | 20525 | 836.5       | 1       | 1   | 22                                           | 21.12                     | 122.46% | 0.136                       | 0.167    | -         |
|                        |                 |            | 25 RB   | 12       | Back side  | 15            | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.123                       | 0.149    | -         |
|                        |                 |            |         |          | Front side | 15            | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.086                       | 0.104    | -         |
|                        |                 |            | 50 RB   |          | Back side  | 15            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.102                       | 0.124    | -         |
|                        |                 |            |         |          | Front side | 15            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.081                       | 0.098    | -         |
|                        |                 |            |         |          | Back side  | 15            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.097                       | 0.118    | -         |
|                        |                 |            |         |          | Front side | 10            | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.215                       | 0.260    | -         |
| LTE Band 5 (Hotspot)   | 10MHz           | QPSK       | 1 RB    | 25       | Back side  | 10            | 20450 | 829         | 1       | 1   | 22                                           | 20.92                     | 128.23% | 0.332                       | 0.426    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20450 | 829         | 2       | 1   | 22                                           | 20.92                     | 128.23% | 0.328                       | 0.421    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20450 | 829         | 3       | 1   | 22                                           | 20.92                     | 128.23% | 0.315                       | 0.404    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20450 | 829         | 4       | 1   | 22                                           | 20.92                     | 128.23% | 0.304                       | 0.390    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20525 | 836.5       | 1       | 1   | 22                                           | 21.12                     | 122.46% | 0.301                       | 0.369    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.279                       | 0.337    | -         |
|                        |                 |            |         |          | Top side   | 10            | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.180                       | 0.217    | -         |
|                        |                 |            |         |          | Left side  | 10            | 20600 | 844         | 1       | 1   | 22                                           | 21.18                     | 120.78% | 0.169                       | 0.204    | -         |
|                        |                 |            | 25 RB   | 12       | Front side | 10            | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.172                       | 0.209    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.241                       | 0.292    | -         |
|                        |                 |            |         |          | Top side   | 10            | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.154                       | 0.187    | -         |
|                        |                 |            | 50 RB   |          | Left side  | 10            | 20525 | 836.5       | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.142                       | 0.172    | -         |
|                        |                 |            |         |          | Front side | 10            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.161                       | 0.195    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.215                       | 0.261    | -         |
|                        |                 |            |         |          | Top side   | 10            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.134                       | 0.163    | -         |
|                        |                 |            |         |          | Left side  | 10            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.127                       | 0.154    | -         |
|                        |                 |            |         |          | Left side  | 10            | 20600 | 844         | 1       | 1   | 21                                           | 20.16                     | 121.34% | 0.127                       | 0.154    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position  | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|-----------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |           |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 5 (Head)      | 10MHz           | QPSK       | 1 RB    | 25       | RE Cheek  | -             | 20450 | 829         | 1       | 1   | 22                                           | 20.92                     | 128.23% | 0.900                       | 1.154    | 145       |
|                        |                 |            |         |          | RE Cheek  | -             | 20450 | 829         | 2       | 1   | 22                                           | 20.92                     | 128.23% | 0.842                       | 1.080    | -         |
|                        |                 |            |         |          | RE Cheek  | -             | 20450 | 829         | 3       | 1   | 22                                           | 20.92                     | 128.23% | 0.863                       | 1.107    | -         |
|                        |                 |            |         |          | RE Cheek  | -             | 20450 | 829         | 4       | 1   | 22                                           | 20.92                     | 128.23% | 0.895                       | 1.148    | -         |
| LTE Band 5 (Body-Worn) | 10MHz           | QPSK       | 1 RB    | 25       | Back side | 15            | 20450 | 829         | 1       | 1   | 22                                           | 20.92                     | 128.23% | 0.141                       | 0.181    | -         |
|                        |                 |            |         |          | Back side | 15            | 20450 | 829         | 2       | 1   | 22                                           | 20.92                     | 128.23% | 0.132                       | 0.169    | -         |
|                        |                 |            |         |          | Back side | 15            | 20450 | 829         | 3       | 1   | 22                                           | 20.92                     | 128.23% | 0.139                       | 0.178    | -         |
|                        |                 |            |         |          | Back side | 15            | 20450 | 829         | 4       | 1   | 22                                           | 20.92                     | 128.23% | 0.142                       | 0.182    | 146       |
| LTE Band 5 (Hotspot)   | 10MHz           | QPSK       | 1 RB    | 25       | Back side | 10            | 20450 | 829         | 1       | 1   | 22                                           | 20.92                     | 128.23% | 0.331                       | 0.424    | 147       |
|                        |                 |            |         |          | Back side | 10            | 20450 | 829         | 2       | 1   | 22                                           | 20.92                     | 128.23% | 0.301                       | 0.386    | -         |
|                        |                 |            |         |          | Back side | 10            | 20450 | 829         | 3       | 1   | 22                                           | 20.92                     | 128.23% | 0.297                       | 0.381    | -         |
|                        |                 |            |         |          | Back side | 10            | 20450 | 829         | 4       | 1   | 22                                           | 20.92                     | 128.23% | 0.330                       | 0.423    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## LTE FDD Band VII

## Main Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |             |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 7 (Head)      | 20MHz           | QPSK       | 1 RB    | 50       | RE Cheek    | -             | 21100 | 2535        | 1       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.028                       | 0.030    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.040                       | 0.041    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 2       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.035                       | 0.035    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 3       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.028                       | 0.028    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 4       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.026                       | 0.026    | -         |
|                        |                 |            |         |          | RE Tilt     | -             | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.038                       | 0.039    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.025                       | 0.025    | -         |
|                        |                 |            |         |          | LE Tilt     | -             | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.020                       | 0.020    | -         |
|                        |                 |            | 50 RB   | 50       | RE Cheek    | -             | 20850 | 2510        | 1       | 1   | 23.5                                         | 23.27                     | 105.44% | 0.015                       | 0.016    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.029                       | 0.030    | -         |
|                        |                 |            |         |          | RE Tilt     | -             | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.027                       | 0.028    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.017                       | 0.018    | -         |
|                        |                 |            |         |          | LE Tilt     | -             | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.013                       | 0.014    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.030                       | 0.031    | -         |
|                        |                 |            |         |          | RE Tilt     | -             | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.025                       | 0.026    | -         |
|                        |                 |            |         |          | LE Cheek    | -             | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.015                       | 0.016    | -         |
| LTE Band 7 (Body-Worn) | 20MHz           | QPSK       | 1 RB    | 50       | Front side  | 15            | 21100 | 2535        | 1       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.248                       | 0.263    | -         |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.263                       | 0.267    | -         |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 2       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.252                       | 0.256    | -         |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 3       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.202                       | 0.205    | -         |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 4       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.194                       | 0.197    | -         |
|                        |                 |            |         |          | Back side   | 15            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.247                       | 0.250    | -         |
|                        |                 |            |         |          | Front side  | 15            | 20850 | 2510        | 1       | 1   | 23.5                                         | 23.27                     | 105.44% | 0.226                       | 0.238    | -         |
|                        |                 |            | 50 RB   | 50       | Front side  | 15            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.208                       | 0.217    | -         |
|                        |                 |            |         |          | Back side   | 15            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.195                       | 0.203    | -         |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.210                       | 0.217    | -         |
|                        |                 |            |         |          | Back side   | 15            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.199                       | 0.206    | -         |
|                        |                 |            | 100 RB  | 50       | Front side  | 10            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.423                       | 0.429    | -         |
|                        |                 |            |         |          | Back side   | 10            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.419                       | 0.425    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21100 | 2535        | 1       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.991                       | 1.052    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21100 | 2535        | 2       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.957                       | 1.016    | -         |
| LTE Band 7 (Hotspot)   | 20MHz           | QPSK       | 1 RB    | 50       | Bottom side | 10            | 21100 | 2535        | 3       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.923                       | 0.980    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21100 | 2535        | 4       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.915                       | 0.971    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.895                       | 0.907    | -         |
|                        |                 |            |         |          | Right side  | 10            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.082                       | 0.083    | -         |
|                        |                 |            |         |          | Left side   | 10            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.316                       | 0.320    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 20850 | 2510        | 1       | 1   | 23.5                                         | 23.27                     | 105.44% | 0.778                       | 0.820    | -         |
|                        |                 |            | 50 RB   | 50       | Front side  | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.328                       | 0.342    | -         |
|                        |                 |            |         |          | Back side   | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.321                       | 0.335    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.684                       | 0.713    | -         |
|                        |                 |            |         |          | Right side  | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.065                       | 0.068    | -         |
|                        |                 |            |         |          | Left side   | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.32                     | 104.23% | 0.250                       | 0.261    | -         |
|                        |                 |            | 100 RB  | 50       | Front side  | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.328                       | 0.340    | -         |
|                        |                 |            |         |          | Back side   | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.323                       | 0.334    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.680                       | 0.704    | -         |
|                        |                 |            |         |          | Right side  | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.066                       | 0.068    | -         |
|                        |                 |            |         |          | Left side   | 10            | 21350 | 2560        | 1       | 1   | 22.5                                         | 22.35                     | 103.51% | 0.253                       | 0.262    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |             |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 7 (Head)      | 20MHz           | QPSK       | 1 RB    | 50       | RE Cheek    | -             | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.026                       | 0.026    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 2       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.032                       | 0.032    | 148       |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 3       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.021                       | 0.021    | -         |
|                        |                 |            |         |          | RE Cheek    | -             | 21350 | 2560        | 4       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.027                       | 0.027    | -         |
| LTE Band 7 (Body-Worn) | 20MHz           | QPSK       | 1 RB    | 50       | Front side  | 15            | 21350 | 2560        | 1       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.152                       | 0.154    | -         |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 2       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.216                       | 0.219    | 149       |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 3       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.127                       | 0.129    | -         |
|                        |                 |            |         |          | Front side  | 15            | 21350 | 2560        | 4       | 1   | 23.5                                         | 23.44                     | 101.39% | 0.162                       | 0.164    | -         |
| LTE Band 7 (Hotspot)   | 20MHz           | QPSK       | 1 RB    | 50       | Bottom side | 10            | 21100 | 2535        | 1       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.635                       | 0.674    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21100 | 2535        | 2       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.829                       | 0.880    | 150       |
|                        |                 |            |         |          | Bottom side | 10            | 21100 | 2535        | 3       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.532                       | 0.565    | -         |
|                        |                 |            |         |          | Bottom side | 10            | 21100 | 2535        | 4       | 1   | 23.5                                         | 23.24                     | 106.17% | 0.649                       | 0.689    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Sub Antenna

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position   | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|------------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |            |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 7 (Head)      | 20MHz           | QPSK       | 1 RB    | 50       | RE Cheek   | -             | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.454                       | 0.454    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 21100 | 2535        | 1       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.514                       | 0.537    | -         |
|                        |                 |            |         |          | RE Tilt    | -             | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.390                       | 0.390    | -         |
|                        |                 |            |         |          | LE Cheek   | -             | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.166                       | 0.166    | -         |
|                        |                 |            |         |          | LE Tilt    | -             | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.171                       | 0.171    | -         |
|                        |                 |            |         | 99       | RE Cheek   | -             | 21350 | 2560        | 1       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.558                       | 0.586    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 21350 | 2560        | 2       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.502                       | 0.527    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 21350 | 2560        | 3       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.515                       | 0.541    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 21350 | 2560        | 4       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.530                       | 0.556    | -         |
|                        |                 |            | 50 RB   | 0        | RE Cheek   | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.409                       | 0.431    | -         |
|                        |                 |            |         |          | RE Tilt    | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.337                       | 0.355    | -         |
|                        |                 |            |         |          | LE Cheek   | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.152                       | 0.160    | -         |
|                        |                 |            |         |          | LE Tilt    | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.156                       | 0.164    | -         |
|                        |                 |            | 100 RB  |          | RE Cheek   | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.404                       | 0.431    | -         |
|                        |                 |            |         |          | RE Tilt    | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.332                       | 0.354    | -         |
|                        |                 |            |         |          | LE Cheek   | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.150                       | 0.160    | -         |
|                        |                 |            |         |          | LE Tilt    | -             | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.151                       | 0.161    | -         |
| LTE Band 7 (Body-Worn) | 20MHz           | QPSK       | 1 RB    | 50       | Front side | 15            | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.046                       | 0.046    | -         |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 1       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.057                       | 0.060    | -         |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 2       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.041                       | 0.043    | -         |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 3       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.044                       | 0.046    | -         |
|                        |                 |            |         | 99       | Front side | 15            | 21100 | 2535        | 4       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.051                       | 0.053    | -         |
|                        |                 |            |         |          | Back side  | 15            | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.044                       | 0.044    | -         |
|                        |                 |            |         |          | Front side | 15            | 21350 | 2560        | 1       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.056                       | 0.059    | -         |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.043                       | 0.045    | -         |
|                        |                 |            | 50 RB   | 0        | Back side  | 15            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.038                       | 0.040    | -         |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.041                       | 0.044    | -         |
|                        |                 |            |         |          | Back side  | 15            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.035                       | 0.037    | -         |
|                        |                 |            | 100 RB  |          | Front side | 15            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.041                       | 0.044    | -         |
|                        |                 |            |         |          | Back side  | 15            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.035                       | 0.037    | -         |
| LTE Band 7 (Hotspot)   | 20MHz           | QPSK       | 1 RB    | 50       | Front side | 10            | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.092                       | 0.092    | -         |
|                        |                 |            |         |          | Front side | 10            | 21100 | 2535        | 1       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.119                       | 0.124    | -         |
|                        |                 |            |         |          | Back side  | 10            | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.080                       | 0.080    | -         |
|                        |                 |            |         |          | Top side   | 10            | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.053                       | 0.053    | -         |
|                        |                 |            |         | 99       | Left side  | 10            | 20850 | 2510        | 1       | 1   | 17.5                                         | 17.50                     | 100.00% | 0.084                       | 0.084    | -         |
|                        |                 |            |         |          | Front side | 10            | 21350 | 2560        | 1       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.122                       | 0.128    | -         |
|                        |                 |            |         |          | Front side | 10            | 21350 | 2560        | 2       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.095                       | 0.100    | -         |
|                        |                 |            |         |          | Front side | 10            | 21350 | 2560        | 3       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.105                       | 0.110    | -         |
|                        |                 |            | 50 RB   | 0        | Front side | 10            | 21350 | 2560        | 4       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.114                       | 0.120    | -         |
|                        |                 |            |         |          | Front side | 10            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.091                       | 0.096    | -         |
|                        |                 |            |         |          | Back side  | 10            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.061                       | 0.064    | -         |
|                        |                 |            |         |          | Top side   | 10            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.040                       | 0.042    | -         |
|                        |                 |            | 100 RB  |          | Left side  | 10            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.27                     | 105.44% | 0.069                       | 0.073    | -         |
|                        |                 |            |         |          | Front side | 10            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.087                       | 0.093    | -         |
|                        |                 |            |         |          | Back side  | 10            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.058                       | 0.062    | -         |
|                        |                 |            |         |          | Top side   | 10            | 21100 | 2535        | 1       | 1   | 16.5                                         | 16.22                     | 106.66% | 0.037                       | 0.039    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Mode                   | Bandwidth (MHz) | Modulation | RB Size | RB start | Position   | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|------------------------|-----------------|------------|---------|----------|------------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                        |                 |            |         |          |            |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 7 (Head)      | 20MHz           | QPSK       | 1 RB    | 99       | RE Cheek   | -             | 21350 | 2560        | 1       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.788                       | 0.827    | 151       |
|                        |                 |            |         |          | RE Cheek   | -             | 21350 | 2560        | 2       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.785                       | 0.824    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 21350 | 2560        | 3       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.743                       | 0.780    | -         |
|                        |                 |            |         |          | RE Cheek   | -             | 21350 | 2560        | 4       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.722                       | 0.758    | -         |
| LTE Band 7 (Body-Worn) | 20MHz           | QPSK       | 1 RB    | 50       | Front side | 15            | 21100 | 2535        | 1       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.081                       | 0.085    | 152       |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 2       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.080                       | 0.084    | -         |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 3       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.077                       | 0.080    | -         |
|                        |                 |            |         |          | Front side | 15            | 21100 | 2535        | 4       | 1   | 17.5                                         | 17.31                     | 104.47% | 0.074                       | 0.077    | -         |
| LTE Band 7 (Hotspot)   | 20MHz           | QPSK       | 1 RB    | 99       | Front side | 10            | 21350 | 2560        | 1       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.173                       | 0.182    | 153       |
|                        |                 |            |         |          | Front side | 10            | 21350 | 2560        | 2       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.171                       | 0.179    | -         |
|                        |                 |            |         |          | Front side | 10            | 21350 | 2560        | 3       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.159                       | 0.167    | -         |
|                        |                 |            |         |          | Front side | 10            | 21350 | 2560        | 4       | 1   | 17.5                                         | 17.29                     | 104.95% | 0.151                       | 0.158    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## LTE TDD Band XXXVIII

## Main Antenna

| Mode                    | Bandwidth (MHz) | Modulation | RB Size | RB start | Position    | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-------------------------|-----------------|------------|---------|----------|-------------|---------------|-------|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|                         |                 |            |         |          |             |               |       |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| LTE Band 38 (Head)      | 20MHz           | QPSK       | 1 RB    | 0        | RE Cheek    | -             | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.018                       | 0.018    | 154       |
|                         |                 |            |         |          | RE Cheek    | -             | 38150 | 2610        | 1       | 1   | 23.5                                         | 23.47                     | 100.69% | 0.017                       | 0.017    | -         |
|                         |                 |            |         |          | RE Tilt     | -             | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.014                       | 0.014    | -         |
|                         |                 |            |         |          | LE Cheek    | -             | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.013                       | 0.013    | -         |
|                         |                 |            |         | 50       | LE Tilt     | -             | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.011                       | 0.011    | -         |
|                         |                 |            |         |          | RE Cheek    | -             | 37850 | 2580        | 1       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.017                       | 0.018    | -         |
|                         |                 |            |         |          | RE Cheek    | -             | 37850 | 2580        | 2       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.016                       | 0.017    | -         |
|                         |                 |            |         |          | RE Cheek    | -             | 37850 | 2580        | 3       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.016                       | 0.017    | -         |
|                         |                 |            | 50 RB   | 50       | RE Cheek    | -             | 37850 | 2580        | 4       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.015                       | 0.016    | -         |
|                         |                 |            |         |          | RE Cheek    | -             | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.013                       | 0.014    | -         |
|                         |                 |            |         |          | RE Tilt     | -             | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.011                       | 0.012    | -         |
|                         |                 |            |         |          | LE Cheek    | -             | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.011                       | 0.012    | -         |
|                         |                 |            | 100 RB  | 50       | LE Tilt     | -             | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.008                       | 0.008    | -         |
|                         |                 |            |         |          | RE Cheek    | -             | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.013                       | 0.014    | -         |
|                         |                 |            |         |          | RE Tilt     | -             | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.010                       | 0.011    | -         |
|                         |                 |            |         |          | LE Cheek    | -             | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.011                       | 0.012    | -         |
| LTE Band 38 (Body-Worn) | 20MHz           | QPSK       | 1 RB    | 0        | Front side  | 15            | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.090                       | 0.090    | 155       |
|                         |                 |            |         |          | Front side  | 15            | 38150 | 2610        | 1       | 1   | 23.5                                         | 23.47                     | 100.69% | 0.087                       | 0.088    | -         |
|                         |                 |            |         |          | Back side   | 15            | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.089                       | 0.089    | -         |
|                         |                 |            |         |          | Front side  | 15            | 37850 | 2580        | 1       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.088                       | 0.096    | -         |
|                         |                 |            |         | 50       | Front side  | 15            | 37850 | 2580        | 2       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.084                       | 0.091    | -         |
|                         |                 |            |         |          | Front side  | 15            | 37850 | 2580        | 3       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.085                       | 0.092    | -         |
|                         |                 |            |         |          | Front side  | 15            | 37850 | 2580        | 4       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.081                       | 0.088    | -         |
|                         |                 |            | 50 RB   | 50       | Front side  | 15            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.066                       | 0.070    | -         |
|                         |                 |            |         |          | Back side   | 15            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.063                       | 0.066    | -         |
|                         |                 |            | 100 RB  | 50       | Front side  | 15            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.065                       | 0.070    | -         |
|                         |                 |            |         |          | Back side   | 15            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.065                       | 0.070    | -         |
| LTE Band 38 (Hotspot)   | 20MHz           | QPSK       | 1 RB    | 0        | Front side  | 10            | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.168                       | 0.169    | -         |
|                         |                 |            |         |          | Back side   | 10            | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.165                       | 0.166    | -         |
|                         |                 |            |         |          | Bottom side | 10            | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.366                       | 0.368    | -         |
|                         |                 |            |         |          | Bottom side | 10            | 38150 | 2610        | 1       | 1   | 23.5                                         | 23.47                     | 100.69% | 0.367                       | 0.370    | 156       |
|                         |                 |            |         | 50       | Right side  | 10            | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.025                       | 0.025    | -         |
|                         |                 |            |         |          | Left side   | 10            | 38000 | 2595        | 1       | 1   | 23.5                                         | 23.48                     | 100.46% | 0.082                       | 0.082    | -         |
|                         |                 |            |         |          | Bottom side | 10            | 37850 | 2580        | 1       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.362                       | 0.393    | -         |
|                         |                 |            |         |          | Bottom side | 10            | 37850 | 2580        | 2       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.302                       | 0.328    | -         |
|                         |                 |            | 50 RB   | 50       | Bottom side | 10            | 37850 | 2580        | 3       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.334                       | 0.363    | -         |
|                         |                 |            |         |          | Bottom side | 10            | 37850 | 2580        | 4       | 1   | 23.5                                         | 23.14                     | 108.64% | 0.300                       | 0.326    | -         |
|                         |                 |            |         |          | Front side  | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.129                       | 0.136    | -         |
|                         |                 |            |         |          | Back side   | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.127                       | 0.134    | -         |
|                         |                 |            | 100 RB  | 50       | Bottom side | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.274                       | 0.289    | -         |
|                         |                 |            |         |          | Right side  | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.019                       | 0.020    | -         |
|                         |                 |            |         |          | Left side   | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.27                     | 105.44% | 0.060                       | 0.063    | -         |
|                         |                 |            |         |          | Front side  | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.128                       | 0.138    | -         |
|                         |                 |            | 100 RB  | 50       | Back side   | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.127                       | 0.137    | -         |
|                         |                 |            |         |          | Bottom side | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.278                       | 0.300    | -         |
|                         |                 |            |         |          | Right side  | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.019                       | 0.020    | -         |
|                         |                 |            |         |          | Left side   | 10            | 38150 | 2610        | 1       | 1   | 22.5                                         | 22.17                     | 107.89% | 0.060                       | 0.065    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Sub Antenna

| Mode                    | Bandwidth (MHz) | Modulation | RB Size | RB start | Position   | Distance (mm) | CH    | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measure d Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|-------------------------|-----------------|------------|---------|----------|------------|---------------|-------|-------------|---------|-----|----------------------------------------------|----------------------------|---------|-----------------------------|----------|-----------|
|                         |                 |            |         |          |            |               |       |             |         |     |                                              |                            |         | Measured                    | Reported |           |
| LTE Band 38 (Head)      | 20MHz           | QPSK       | 1 RB    | 0        | RE Cheek   | -             | 38000 | 2595        | 1       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.664                       | 0.755    | -         |
|                         |                 |            |         |          | RE Cheek   | -             | 38000 | 2595        | 2       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.661                       | 0.752    | -         |
|                         |                 |            |         |          | RE Cheek   | -             | 38000 | 2595        | 3       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.633                       | 0.720    | -         |
|                         |                 |            |         |          | RE Cheek   | -             | 38000 | 2595        | 4       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.552                       | 0.628    | -         |
|                         |                 |            |         | 50       | RE Cheek   | -             | 37850 | 2580        | 1       | 1   | 20.5                                         | 19.91                      | 114.55% | 0.644                       | 0.738    | -         |
|                         |                 |            |         |          | RE Cheek   | -             | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.685                       | 0.748    | 157       |
|                         |                 |            |         |          | RE Tilt    | -             | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.646                       | 0.705    | -         |
|                         |                 |            |         |          | LE Cheek   | -             | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.290                       | 0.317    | -         |
|                         |                 |            | 50 RB   | 0        | LE Tilt    | -             | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.272                       | 0.297    | -         |
|                         |                 |            |         |          | RE Cheek   | -             | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.548                       | 0.582    | -         |
|                         |                 |            |         |          | RE Tilt    | -             | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.524                       | 0.556    | -         |
|                         |                 |            |         |          | LE Cheek   | -             | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.234                       | 0.248    | -         |
|                         |                 |            |         | 100 RB   | LE Tilt    | -             | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.220                       | 0.234    | -         |
|                         |                 |            |         |          | RE Cheek   | -             | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.542                       | 0.583    | -         |
|                         |                 |            |         |          | RE Tilt    | -             | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.521                       | 0.561    | -         |
|                         |                 |            |         |          | LE Cheek   | -             | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.233                       | 0.251    | -         |
| LTE Band 38 (Body-Worn) | 20MHz           | QPSK       | 1 RB    | 0        | Front side | 15            | 38000 | 2595        | 1       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.079                       | 0.090    | -         |
|                         |                 |            |         |          | Front side | 15            | 38000 | 2595        | 2       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.078                       | 0.089    | -         |
|                         |                 |            |         |          | Front side | 15            | 38000 | 2595        | 3       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.074                       | 0.084    | -         |
|                         |                 |            |         |          | Front side | 15            | 38000 | 2595        | 4       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.063                       | 0.072    | -         |
|                         |                 |            |         | 50       | Front side | 15            | 37850 | 2580        | 1       | 1   | 20.5                                         | 19.91                      | 114.55% | 0.077                       | 0.088    | -         |
|                         |                 |            |         |          | Front side | 15            | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.081                       | 0.088    | 158       |
|                         |                 |            |         |          | Back side  | 15            | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.080                       | 0.087    | -         |
|                         |                 |            |         | 50 RB    | Front side | 15            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.065                       | 0.069    | -         |
|                         |                 |            |         |          | Back side  | 15            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.064                       | 0.068    | -         |
|                         |                 |            |         | 100 RB   | Front side | 15            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.065                       | 0.070    | -         |
|                         |                 |            |         |          | Back side  | 15            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.063                       | 0.068    | -         |
| LTE Band 38 (Hotspot)   | 20MHz           | QPSK       | 1 RB    | 0        | Left side  | 10            | 38000 | 2595        | 1       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.180                       | 0.205    | -         |
|                         |                 |            |         |          | Left side  | 10            | 38000 | 2595        | 2       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.149                       | 0.170    | -         |
|                         |                 |            |         |          | Left side  | 10            | 38000 | 2595        | 3       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.159                       | 0.181    | -         |
|                         |                 |            |         |          | Left side  | 10            | 38000 | 2595        | 4       | 1   | 20.5                                         | 19.94                      | 113.76% | 0.116                       | 0.132    | -         |
|                         |                 |            |         | 50       | Front side | 10            | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.142                       | 0.155    | -         |
|                         |                 |            |         |          | Back side  | 10            | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.163                       | 0.178    | -         |
|                         |                 |            |         |          | Top side   | 10            | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.091                       | 0.099    | -         |
|                         |                 |            |         |          | Left side  | 10            | 37850 | 2580        | 1       | 1   | 20.5                                         | 19.91                      | 114.55% | 0.174                       | 0.199    | -         |
|                         |                 |            | 50 RB   | 0        | Left side  | 10            | 38150 | 2610        | 1       | 1   | 20.5                                         | 20.12                      | 109.14% | 0.184                       | 0.201    | 159       |
|                         |                 |            |         |          | Front side | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.123                       | 0.131    | -         |
|                         |                 |            |         |          | Back side  | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.126                       | 0.134    | -         |
|                         |                 |            |         |          | Top side   | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.072                       | 0.076    | -         |
|                         |                 |            |         | 100 RB   | Left side  | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.24                      | 106.17% | 0.138                       | 0.147    | -         |
|                         |                 |            |         |          | Front side | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.126                       | 0.136    | -         |
|                         |                 |            |         |          | Back side  | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.127                       | 0.137    | -         |
|                         |                 |            |         |          | Top side   | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.071                       | 0.076    | -         |
|                         |                 |            |         |          | Left side  | 10            | 37850 | 2580        | 1       | 1   | 19.5                                         | 19.18                      | 107.65% | 0.142                       | 0.153    | -         |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## WLAN802.11 b

The data of MLA-L13 and MLA-L03 from the SAR report of FCC ID: QISMLA-LX3

| Antenna | Mode                      | Position   | Distance (mm) | CH | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|---------|---------------------------|------------|---------------|----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|         |                           |            |               |    |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| WLAN    | WLAN 802.11 b (Head)      | RE Cheek   | -             | 1  | 2412        | 1       | 1   | 12.5                                         | 12.48                     | 100.46% | 0.108                       | 0.108    | -         |
|         |                           | RE Tilt    | -             | 1  | 2412        | 1       | 1   | 12.5                                         | 12.48                     | 100.46% | 0.117                       | 0.118    | -         |
|         |                           | LE Cheek   | -             | 1  | 2412        | 1       | 1   | 12.5                                         | 12.48                     | 100.46% | 0.287                       | 0.288    | -         |
|         |                           | LE Tilt    | -             | 1  | 2412        | 1       | 1   | 12.5                                         | 12.48                     | 100.46% | 0.312                       | 0.313    | -         |
|         |                           | LE Tilt    | -             | 6  | 2437        | 1       | 1   | 12.5                                         | 12.33                     | 103.99% | 0.301                       | 0.313    | -         |
|         |                           | LE Tilt    | -             | 11 | 2462        | 1       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.404                       | 0.418    | -         |
|         |                           | LE Tilt    | -             | 11 | 2462        | 2       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.302                       | 0.313    | -         |
|         |                           | LE Tilt    | -             | 11 | 2462        | 3       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.325                       | 0.336    | -         |
|         |                           | LE Tilt    | -             | 11 | 2462        | 4       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.367                       | 0.380    | -         |
|         | WLAN 802.11 b (Body-Worn) | Front side | 15            | 11 | 2462        | 1       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.137                       | 0.138    | -         |
|         |                           | Back side  | 15            | 1  | 2412        | 1       | 1   | 19.5                                         | 19.43                     | 101.62% | 0.091                       | 0.092    | -         |
|         |                           | Back side  | 15            | 6  | 2437        | 1       | 1   | 19.5                                         | 19.24                     | 106.17% | 0.100                       | 0.106    | -         |
|         |                           | Back side  | 15            | 11 | 2462        | 1       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.149                       | 0.150    | -         |
|         |                           | Back side  | 15            | 11 | 2462        | 2       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.094                       | 0.094    | -         |
|         |                           | Back side  | 15            | 11 | 2462        | 3       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.112                       | 0.113    | -         |
|         |                           | Back side  | 15            | 11 | 2462        | 4       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.123                       | 0.124    | -         |
|         | WLAN 802.11 b (Hotspot)   | Front side | 10            | 6  | 2437        | 1       | 1   | 19.5                                         | 19.24                     | 106.17% | 0.291                       | 0.309    | -         |
|         |                           | Back side  | 10            | 1  | 2412        | 1       | 1   | 19.5                                         | 19.43                     | 101.62% | 0.274                       | 0.278    | -         |
|         |                           | Back side  | 10            | 6  | 2437        | 1       | 1   | 19.5                                         | 19.24                     | 106.17% | 0.231                       | 0.245    | -         |
|         |                           | Back side  | 10            | 11 | 2462        | 1       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.323                       | 0.324    | -         |
|         |                           | Back side  | 10            | 11 | 2462        | 2       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.264                       | 0.265    | -         |
|         |                           | Back side  | 10            | 11 | 2462        | 3       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.283                       | 0.284    | -         |
|         |                           | Back side  | 10            | 11 | 2462        | 4       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.302                       | 0.303    | -         |
|         |                           | Top side   | 10            | 11 | 2462        | 1       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.277                       | 0.278    | -         |
|         |                           | Right side | 10            | 11 | 2462        | 1       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.303                       | 0.304    | -         |

Tested MLA-L12 and MLA-L02 at the worst position with battery #1, #2, #3, #4.

| Antenna | Mode                      | Position  | Distance (mm) | CH | Freq. (MHz) | Battery | SIM | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) |          | Plot page |
|---------|---------------------------|-----------|---------------|----|-------------|---------|-----|----------------------------------------------|---------------------------|---------|-----------------------------|----------|-----------|
|         |                           |           |               |    |             |         |     |                                              |                           |         | Measured                    | Reported |           |
| WLAN    | WLAN 802.11 b (Head)      | LE Tilt   | -             | 11 | 2462        | 1       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.392                       | 0.406    | -         |
|         |                           | LE Tilt   | -             | 11 | 2462        | 2       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.381                       | 0.394    | -         |
|         |                           | LE Tilt   | -             | 11 | 2462        | 3       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.398                       | 0.412    | 160       |
|         |                           | LE Tilt   | -             | 11 | 2462        | 4       | 1   | 12.5                                         | 12.35                     | 103.51% | 0.382                       | 0.395    | -         |
|         | WLAN 802.11 b (Body-Worn) | Back side | 15            | 11 | 2462        | 1       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.141                       | 0.142    | -         |
|         |                           | Back side | 15            | 11 | 2462        | 2       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.132                       | 0.133    | -         |
|         |                           | Back side | 15            | 11 | 2462        | 3       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.145                       | 0.146    | 161       |
|         |                           | Back side | 15            | 11 | 2462        | 4       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.136                       | 0.137    | -         |
|         | WLAN 802.11 b (Hotspot)   | Back side | 10            | 11 | 2462        | 1       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.302                       | 0.303    | -         |
|         |                           | Back side | 10            | 11 | 2462        | 2       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.311                       | 0.312    | -         |
|         |                           | Back side | 10            | 11 | 2462        | 3       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.294                       | 0.295    | -         |
|         |                           | Back side | 10            | 11 | 2462        | 4       | 1   | 19.5                                         | 19.48                     | 100.46% | 0.315                       | 0.316    | 162       |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### 3. Simultaneous Transmission Analysis

#### Simultaneous Transmission Scenarios:

| Simultaneous Transmit Configurations | Head | Body-Worn | Hotspot | Product specific 10-g SAR |
|--------------------------------------|------|-----------|---------|---------------------------|
| Main_GSM + 2.4GHz Wi-Fi              | Yes  | Yes       | No      | Yes                       |
| Main_GPRS + 2.4GHz Wi-Fi             | No   | No        | Yes     | Yes                       |
| Main_WCDMA + 2.4GHz Wi-Fi            | Yes  | Yes       | Yes     | Yes                       |
| Main_LTE + 2.4GHz Wi-Fi              | Yes  | Yes       | Yes     | Yes                       |
| Main_GSM + BT                        | No   | Yes       | No      | Yes                       |
| Main_GPR + BT                        | No   | No        | No      | Yes                       |
| Main_WCDMA + BT                      | No   | Yes       | No      | Yes                       |
| Main_LTE + BT                        | No   | Yes       | No      | Yes                       |
| Sub_GSM + 2.4GHz Wi-Fi               | Yes  | Yes       | No      | Yes                       |
| Sub_GPRS + 2.4GHz Wi-Fi              | No   | No        | Yes     | Yes                       |
| Sub_WCDMA + 2.4GHz Wi-Fi             | Yes  | Yes       | Yes     | Yes                       |
| Sub_LTE + 2.4GHz Wi-Fi               | Yes  | Yes       | Yes     | Yes                       |
| Sub_GSM + BT                         | No   | Yes       | No      | Yes                       |
| Sub_GPRS + BT                        | No   | No        | No      | Yes                       |
| Sub_WCDMA + BT                       | No   | Yes       | No      | Yes                       |
| Sub_LTE + BT                         | No   | Yes       | No      | Yes                       |

#### Notes:

1. WiFi 2.4G and BT can't transmit simultaneously.
2. The device does not support VoLTE or WiFi VOIP function.
3. The device does not support DTM function. Body-worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
4. Held to ear configurations are not applicable to Bluetooth for this device.
5. Based on KDB447498D01 note 36, when SAR test exclusion is allowed by other published RF exposure KDB procedures, such as the 2.5 cm hotspot mode SAR test exclusion for an edge or surface, then estimated SAR is not required to determine simultaneous SAR test exclusion. Also, based on KDB648474D04 note 6, simultaneous transmission SAR for product specific 10-g SAR requires consideration only when standalone 10-g SAR is required.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### 3.1 Estimated SAR calculation

According to KDB447498 D01v05, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})}/x] \text{ W/kg}$  for test separation distances  $\leq 50 \text{ mm}$ , where  $x = 7.5$  for 1-g SAR and  $x = 18.75$  for 10-g SAR.

When the minimum test separation distance is  $< 5 \text{ mm}$ , a distance of  $5 \text{ mm}$  is applied to determine SAR test exclusion

| mode | position  | max. power (dB) | max. power (mW) | f(GHz) | distance (mm) | x   | Estimated SAR |
|------|-----------|-----------------|-----------------|--------|---------------|-----|---------------|
| BT   | body-worn | 11              | 12.589          | 2.48   | 15            | 7.5 | 0.176 (1g)    |

### 3.2 SPLSR evaluation and analysis

Per KDB447498D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR sum to peak location separation ratio(SPLSR).

The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion.

The ratio is determined by  $(\text{SAR1} + \text{SAR2})^{1.5}/R_i$ , rounded to two decimal digits, and must be  $\leq 0.04$  for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

SAR1 and SAR2 are the highest reported or estimated SAR for each antenna in the pair, and  $R_i$  is the separation distance between the peak SAR locations for the antenna pair in mm.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Simultaneous Transmission Combination

### Main Antenna

| reported SAR WWAN and WLAN 2.4GHz, $\Sigma$ SAR evaluation |           |             |                     |       |              |
|------------------------------------------------------------|-----------|-------------|---------------------|-------|--------------|
| Frequency band                                             | Position  |             | reported SAR / W/kg |       | $\Sigma$ SAR |
|                                                            |           |             | WWAN                | WLAN  | <1.6W/kg     |
| GSM 850                                                    | Head      | Right cheek | 0.028               | 0.108 | 0.136        |
|                                                            |           | Right tilt  | 0.008               | 0.118 | 0.126        |
|                                                            |           | Left cheek  | 0.042               | 0.288 | 0.330        |
|                                                            |           | Left tilt   | 0.008               | 0.418 | 0.426        |
|                                                            | Body-worn | Front       | 0.273               | 0.146 | 0.419        |
|                                                            |           | Back        | 0.224               | 0.316 | 0.540        |
| GPRS 850 (1Dn2UP)                                          | Hotspot   | Front       | 0.429               | 0.309 | 0.738        |
|                                                            |           | Back        | 0.633               | 0.324 | 0.957        |
|                                                            |           | Top         | -                   | 0.278 | -            |
|                                                            |           | Bottom      | 0.331               | -     | -            |
|                                                            |           | Right       | 0.331               | 0.304 | 0.635        |
|                                                            |           | Left        | 0.267               | -     | -            |
| GSM 1900                                                   | Head      | Right cheek | 0.064               | 0.108 | 0.172        |
|                                                            |           | Right tilt  | 0.039               | 0.118 | 0.157        |
|                                                            |           | Left cheek  | 0.106               | 0.288 | 0.394        |
|                                                            |           | Left tilt   | 0.034               | 0.418 | 0.452        |
|                                                            | Body-worn | Front       | 0.237               | 0.146 | 0.383        |
|                                                            |           | Back        | 0.302               | 0.316 | 0.618        |
| GPRS 1900 (1Dn2UP)                                         | Hotspot   | Front       | 0.444               | 0.309 | 0.753        |
|                                                            |           | Back        | 0.525               | 0.324 | 0.849        |
|                                                            |           | Top         | -                   | 0.278 | -            |
|                                                            |           | Bottom      | 1.086               | -     | -            |
|                                                            |           | Right       | 0.021               | 0.304 | 0.325        |
|                                                            |           | Left        | 0.100               | -     | -            |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| reported SAR WWAN and WLAN 2.4GHz, ΣSAR evaluation |           |             |                     |       |          |
|----------------------------------------------------|-----------|-------------|---------------------|-------|----------|
| Frequency band                                     | Position  |             | reported SAR / W/kg |       | ΣSAR     |
|                                                    |           |             | WWAN                | WLAN  | <1.6W/kg |
| WCDMA Band V                                       | Head      | Right cheek | 0.040               | 0.108 | 0.148    |
|                                                    |           | Right tilt  | 0.018               | 0.118 | 0.136    |
|                                                    |           | Left cheek  | 0.081               | 0.288 | 0.369    |
|                                                    |           | Left tilt   | 0.031               | 0.418 | 0.449    |
|                                                    | Body-worn | Front       | 0.080               | 0.146 | 0.226    |
|                                                    |           | Back        | 0.379               | 0.316 | 0.695    |
|                                                    | Hotspot   | Front       | 0.381               | 0.309 | 0.690    |
|                                                    |           | Back        | 0.769               | 0.324 | 1.093    |
|                                                    |           | Top         | -                   | 0.278 | -        |
|                                                    |           | Bottom      | 0.214               | -     | -        |
|                                                    |           | Right       | 0.293               | 0.304 | 0.597    |
|                                                    |           | Left        | 0.104               | -     | -        |
| LTE FDD Band V                                     | Head      | Right cheek | 0.041               | 0.108 | 0.149    |
|                                                    |           | Right tilt  | 0.020               | 0.118 | 0.138    |
|                                                    |           | Left cheek  | 0.065               | 0.288 | 0.353    |
|                                                    |           | Left tilt   | 0.011               | 0.418 | 0.429    |
|                                                    | Body-worn | Front       | 0.184               | 0.146 | 0.330    |
|                                                    |           | Back        | 0.302               | 0.316 | 0.618    |
|                                                    | Hotspot   | Front       | 0.286               | 0.309 | 0.595    |
|                                                    |           | Back        | 0.611               | 0.324 | 0.935    |
|                                                    |           | Top         | -                   | 0.278 | -        |
|                                                    |           | Bottom      | 0.190               | -     | -        |
|                                                    |           | Right       | 0.239               | 0.304 | 0.543    |
|                                                    |           | Left        | 0.102               | -     | -        |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| reported SAR WWAN and WLAN 2.4GHz, ΣSAR evaluation |           |             |                     |       |          |
|----------------------------------------------------|-----------|-------------|---------------------|-------|----------|
| Frequency band                                     | Position  |             | reported SAR / W/kg |       | ΣSAR     |
|                                                    |           |             | WWAN                | WLAN  | <1.6W/kg |
| LTE FDD Band VII                                   | Head      | Right cheek | 0.041               | 0.108 | 0.149    |
|                                                    |           | Right tilt  | 0.039               | 0.118 | 0.157    |
|                                                    |           | Left cheek  | 0.025               | 0.288 | 0.313    |
|                                                    |           | Left tilt   | 0.020               | 0.418 | 0.438    |
|                                                    | Body-worn | Front       | 0.267               | 0.146 | 0.413    |
|                                                    |           | Back        | 0.250               | 0.316 | 0.566    |
|                                                    | Hotspot   | Front       | 0.429               | 0.309 | 0.738    |
|                                                    |           | Back        | 0.425               | 0.324 | 0.749    |
|                                                    |           | Top         | -                   | 0.278 | -        |
|                                                    |           | Bottom      | 1.052               | -     | -        |
|                                                    |           | Right       | 0.083               | 0.304 | 0.387    |
|                                                    |           | Left        | 0.320               | -     | -        |
| LTE TDD Band XXXVIII                               | Head      | Right cheek | 0.018               | 0.108 | 0.126    |
|                                                    |           | Right tilt  | 0.014               | 0.118 | 0.132    |
|                                                    |           | Left cheek  | 0.013               | 0.288 | 0.301    |
|                                                    |           | Left tilt   | 0.011               | 0.418 | 0.429    |
|                                                    | Body-worn | Front       | 0.096               | 0.146 | 0.242    |
|                                                    |           | Back        | 0.089               | 0.316 | 0.405    |
|                                                    | Hotspot   | Front       | 0.169               | 0.309 | 0.478    |
|                                                    |           | Back        | 0.166               | 0.324 | 0.490    |
|                                                    |           | Top         | -                   | 0.278 | -        |
|                                                    |           | Bottom      | 0.393               | -     | -        |
|                                                    |           | Right       | 0.025               | 0.304 | 0.329    |
|                                                    |           | Left        | 0.082               | -     | -        |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| reported SAR WWAN and Bluetooth, $\Sigma$ SAR evaluation |           |       |                     |           |              |
|----------------------------------------------------------|-----------|-------|---------------------|-----------|--------------|
| Frequency band                                           | Position  |       | reported SAR / W/kg |           | $\Sigma$ SAR |
|                                                          |           |       | WWAN                | Bluetooth | <1.6W/kg     |
| GSM 850                                                  | Body-worn | Front | 0.273               | 0.176     | 0.449        |
|                                                          |           | Back  | 0.224               | 0.176     | 0.400        |
| GSM 1900                                                 | Body-worn | Front | 0.237               | 0.176     | 0.413        |
|                                                          |           | Back  | 0.302               | 0.176     | 0.478        |
| WCDMA Band V                                             | Body-worn | Front | 0.080               | 0.176     | 0.256        |
|                                                          |           | Back  | 0.379               | 0.176     | 0.555        |
| LTE FDD Band V                                           | Body-worn | Front | 0.184               | 0.176     | 0.360        |
|                                                          |           | Back  | 0.302               | 0.176     | 0.478        |
| LTE FDD Band VII                                         | Body-worn | Front | 0.267               | 0.176     | 0.443        |
|                                                          |           | Back  | 0.250               | 0.176     | 0.426        |
| LTE TDD Band XXX/III                                     | Body-worn | Front | 0.096               | 0.176     | 0.272        |
|                                                          |           | Back  | 0.089               | 0.176     | 0.265        |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

### Sub Antenna

| reported SAR WWAN and WLAN 2.4GHz, $\Sigma$ SAR evaluation |           |             |                     |       |              |
|------------------------------------------------------------|-----------|-------------|---------------------|-------|--------------|
| Frequency band                                             | Position  |             | reported SAR / W/kg |       | $\Sigma$ SAR |
|                                                            |           |             | WWAN                | WLAN  | <1.6W/kg     |
| GSM 850                                                    | Head      | Right cheek | 1.225               | 0.108 | 1.333        |
|                                                            |           | Right tilt  | 1.035               | 0.118 | 1.153        |
|                                                            |           | Left cheek  | 0.598               | 0.288 | 0.886        |
|                                                            |           | Left tilt   | 0.600               | 0.418 | 1.018        |
|                                                            | Body-worn | Front       | 0.198               | 0.146 | 0.344        |
|                                                            |           | Back        | 0.313               | 0.316 | 0.629        |
| GPRS 850 (1Dn2UP)                                          | Hotspot   | Front       | 0.467               | 0.309 | 0.776        |
|                                                            |           | Back        | 0.671               | 0.324 | 0.995        |
|                                                            |           | Top         | 0.373               | 0.278 | 0.651        |
|                                                            |           | Bottom      | -                   | -     | -            |
|                                                            |           | Right       | -                   | 0.304 | -            |
|                                                            |           | Left        | 0.281               | -     | -            |
| GSM 1900                                                   | Head      | Right cheek | 0.432               | 0.108 | 0.540        |
|                                                            |           | Right tilt  | 0.435               | 0.118 | 0.553        |
|                                                            |           | Left cheek  | 0.152               | 0.288 | 0.440        |
|                                                            |           | Left tilt   | 0.198               | 0.418 | 0.616        |
|                                                            | Body-worn | Front       | 0.111               | 0.146 | 0.257        |
|                                                            |           | Back        | 0.094               | 0.316 | 0.410        |
| GPRS 1900 (1Dn2UP)                                         | Hotspot   | Front       | 0.281               | 0.309 | 0.590        |
|                                                            |           | Back        | 0.285               | 0.324 | 0.609        |
|                                                            |           | Top         | 0.352               | 0.278 | 0.630        |
|                                                            |           | Bottom      | -                   | -     | -            |
|                                                            |           | Right       | -                   | 0.304 | -            |
|                                                            |           | Left        | 0.272               | -     | -            |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| reported SAR WWAN and WLAN 2.4GHz, $\Sigma$ SAR evaluation |           |             |                     |       |              |
|------------------------------------------------------------|-----------|-------------|---------------------|-------|--------------|
| Frequency band                                             | Position  |             | reported SAR / W/kg |       | $\Sigma$ SAR |
|                                                            |           |             | WWAN                | WLAN  | <1.6W/kg     |
| WCDMA Band V                                               | Head      | Right cheek | 1.054               | 0.108 | 1.162        |
|                                                            |           | Right tilt  | 0.786               | 0.118 | 0.904        |
|                                                            |           | Left cheek  | 0.556               | 0.288 | 0.844        |
|                                                            |           | Left tilt   | 0.545               | 0.418 | 0.963        |
|                                                            | Body-worn | Front       | 0.121               | 0.146 | 0.267        |
|                                                            |           | Back        | 0.177               | 0.316 | 0.493        |
|                                                            | Hotspot   | Front       | 0.271               | 0.309 | 0.580        |
|                                                            |           | Back        | 0.397               | 0.324 | 0.721        |
|                                                            |           | Top         | 0.230               | 0.278 | 0.508        |
|                                                            |           | Bottom      | -                   | -     | -            |
|                                                            |           | Right       | -                   | 0.304 | -            |
|                                                            |           | Left        | 0.153               | -     | -            |
| LTE FDD Band V                                             | Head      | Right cheek | 1.193               | 0.108 | 1.301        |
|                                                            |           | Right tilt  | 0.768               | 0.118 | 0.886        |
|                                                            |           | Left cheek  | 0.537               | 0.288 | 0.825        |
|                                                            |           | Left tilt   | 0.518               | 0.418 | 0.936        |
|                                                            | Body-worn | Front       | 0.127               | 0.146 | 0.273        |
|                                                            |           | Back        | 0.186               | 0.316 | 0.502        |
|                                                            | Hotspot   | Front       | 0.260               | 0.309 | 0.569        |
|                                                            |           | Back        | 0.426               | 0.324 | 0.750        |
|                                                            |           | Top         | 0.217               | 0.278 | 0.495        |
|                                                            |           | Bottom      | -                   | -     | -            |
|                                                            |           | Right       | -                   | 0.304 | -            |
|                                                            |           | Left        | 0.204               | -     | -            |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| reported SAR WWAN and WLAN 2.4GHz, ΣSAR evaluation |           |             |                     |       |          |
|----------------------------------------------------|-----------|-------------|---------------------|-------|----------|
| Frequency band                                     | Position  |             | reported SAR / W/kg |       | ΣSAR     |
|                                                    |           |             | WWAN                | WLAN  | <1.6W/kg |
| LTE FDD Band VII                                   | Head      | Right cheek | 0.827               | 0.108 | 0.935    |
|                                                    |           | Right tilt  | 0.390               | 0.118 | 0.508    |
|                                                    |           | Left cheek  | 0.166               | 0.288 | 0.454    |
|                                                    |           | Left tilt   | 0.171               | 0.418 | 0.589    |
|                                                    | Body-worn | Front       | 0.085               | 0.146 | 0.231    |
|                                                    |           | Back        | 0.044               | 0.316 | 0.360    |
|                                                    | Hotspot   | Front       | 0.182               | 0.309 | 0.491    |
|                                                    |           | Back        | 0.080               | 0.324 | 0.404    |
|                                                    |           | Top         | 0.053               | 0.278 | 0.331    |
|                                                    |           | Bottom      | -                   | -     | -        |
|                                                    |           | Right       | -                   | 0.304 | -        |
|                                                    |           | Left        | 0.084               | -     | -        |
| LTE TDD Band XXXVIII                               | Head      | Right cheek | 0.755               | 0.108 | 0.863    |
|                                                    |           | Right tilt  | 0.705               | 0.118 | 0.823    |
|                                                    |           | Left cheek  | 0.317               | 0.288 | 0.605    |
|                                                    |           | Left tilt   | 0.297               | 0.418 | 0.715    |
|                                                    | Body-worn | Front       | 0.090               | 0.146 | 0.236    |
|                                                    |           | Back        | 0.087               | 0.316 | 0.403    |
|                                                    | Hotspot   | Front       | 0.155               | 0.309 | 0.464    |
|                                                    |           | Back        | 0.178               | 0.324 | 0.502    |
|                                                    |           | Top         | 0.099               | 0.278 | 0.377    |
|                                                    |           | Bottom      | -                   | -     | -        |
|                                                    |           | Right       | -                   | 0.304 | -        |
|                                                    |           | Left        | 0.205               | -     | -        |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| reported SAR WWAN and Bluetooth, $\Sigma$ SAR evaluation |           |       |                     |           |              |
|----------------------------------------------------------|-----------|-------|---------------------|-----------|--------------|
| Frequency band                                           | Position  |       | reported SAR / W/kg |           | $\Sigma$ SAR |
|                                                          |           |       | WWAN                | Bluetooth | <1.6W/kg     |
| GSM 850                                                  | Body-worn | Front | 0.198               | 0.176     | 0.374        |
|                                                          |           | Back  | 0.313               | 0.176     | 0.489        |
| GSM 1900                                                 | Body-worn | Front | 0.111               | 0.176     | 0.287        |
|                                                          |           | Back  | 0.094               | 0.176     | 0.270        |
| WCDMA Band V                                             | Body-worn | Front | 0.121               | 0.176     | 0.297        |
|                                                          |           | Back  | 0.177               | 0.176     | 0.353        |
| LTE FDD Band V                                           | Body-worn | Front | 0.127               | 0.176     | 0.303        |
|                                                          |           | Back  | 0.186               | 0.176     | 0.362        |
| LTE FDD Band VII                                         | Body-worn | Front | 0.085               | 0.176     | 0.261        |
|                                                          |           | Back  | 0.044               | 0.176     | 0.220        |
| LTE TDD Band XXX/III                                     | Body-worn | Front | 0.090               | 0.176     | 0.266        |
|                                                          |           | Back  | 0.087               | 0.176     | 0.263        |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

#### 4. Instruments List

| Manufacturer                    | Device                       | Type            | Serial number | Date of last calibration | Date of next calibration |
|---------------------------------|------------------------------|-----------------|---------------|--------------------------|--------------------------|
| Schmid & Partner Engineering AG | Dosimetric E-Field Probe     | EX3DV4          | 3923          | Aug.27,2015              | Aug.26,2016              |
|                                 |                              |                 | 3938          | Oct.01,2015              | Sep.30,2016              |
| Schmid & Partner Engineering AG | System Validation Dipole     | D835V2          | 4d063         | Aug.24,2015              | Aug.23,2016              |
|                                 |                              | D1900V2         | 5d027         | Apr.25,2016              | Apr.24,2017              |
|                                 |                              | D2450V2         | 727           | Apr.19,2016              | Apr.18,2017              |
|                                 |                              | D2600V2         | 1005          | Jan.21,2016              | Jan.20,2017              |
| Schmid & Partner Engineering AG | Data acquisition Electronics | DAE4            | 1374          | Oct.23,2015              | Oct.22,2016              |
|                                 |                              |                 | 1260          | Sep.24,2015              | Sep.23,2016              |
| Schmid & Partner Engineering AG | Software                     | DASY 52 V52.8.8 | N/A           | Calibration not required | Calibration not required |
| Schmid & Partner Engineering AG | Phantom                      | SAM             | N/A           | Calibration not required | Calibration not required |
| Network Analyzer                | Agilent                      | E5071C          | MY46107530    | Jan.07,2016              | Jan.06,2017              |
| Agilent                         | Dielectric Probe Kit         | 85070E          | MY44300677    | Calibration not required | Calibration not required |
| Agilent                         | Dual-directional coupler     | 772D            | MY52180142    | Apr.13,2016              | Apr.12,2017              |
|                                 |                              | 778D            | MY52180302    | Apr.13,2016              | Apr.12,2017              |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

| Manufacturer | Device                   | Type     | Serial number | Date of last calibration | Date of next calibration |
|--------------|--------------------------|----------|---------------|--------------------------|--------------------------|
| Agilent      | RF Signal Generator      | N5181A   | MY50145142    | Feb.19,2016              | Feb.18,2017              |
| Agilent      | Power Meter              | E4417A   | MY51410006    | Jan.07,2016              | Jan.06,2017              |
| Agilent      | Power Sensor             | E9301H   | MY51470001    | Jan.07,2016              | Jan.06,2017              |
|              |                          |          | MY51470002    | Jan.07,2016              | Jan.06,2017              |
| TECPEL       | Digital thermometer      | DTM-303A | TP130073      | Feb.26,2016              | Feb.25,2017              |
| Anritsu      | Radio Communication Test | MT8820C  | 6201061014    | Oct.07,2015              | Oct.06,2016              |
| R&S          | Radio Communication Test | CMW 500  | 125470        | Jul.09,2016              | Jul.08,2017              |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 5. Measurements

Date: 2016/8/1

### GSM 850\_Head\_Le Cheek\_CH 128

Communication System: GSM; Frequency: 824.2 MHz

Medium parameters used:  $f = 824.2$  MHz;  $\sigma = 0.912$  S/m;  $\epsilon_r = 41.833$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.35, 9.35, 9.35); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x131x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.0378 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.145 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.0420 W/kg

**SAR(1 g) = 0.034 W/kg; SAR(10 g) = 0.023 W/kg**

Maximum value of SAR (measured) = 0.0369 W/kg



0 dB = 0.0369 W/kg = -14.32 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**GSM 850\_Body-worn\_Front side\_CH 251\_15mm**

Communication System: GSM; Frequency: 848.8 MHz

Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.999$  S/m;  $\epsilon_r = 54.741$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.269 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.24 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.292 W/kg

**SAR(1 g) = 0.235 W/kg; SAR(10 g) = 0.177 W/kg**

Maximum value of SAR (measured) = 0.265 W/kg



0 dB = 0.265 W/kg = -5.76 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**GPRS 850\_Hotspot\_Back side\_CH 251\_10mm**

Communication System: GPRS(1Dn2Up); Frequency: 848.8 MHz

Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.999$  S/m;  $\epsilon_r = 54.741$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.766 W/kg

**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.38 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.987 W/kg

**SAR(1 g) = 0.580 W/kg; SAR(10 g) = 0.332 W/kg**

Maximum value of SAR (measured) = 0.789 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.38 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.729 W/kg

**SAR(1 g) = 0.516 W/kg; SAR(10 g) = 0.365 W/kg**

Maximum value of SAR (measured) = 0.619 W/kg



0 dB = 0.619 W/kg = -2.08 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/1

**GSM 850\_Head\_Re Cheek\_CH 128**

Communication System: GSM; Frequency: 824.2 MHz

Medium parameters used:  $f = 824.2$  MHz;  $\sigma = 0.912$  S/m;  $\epsilon_r = 41.833$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3938; ConvF(9.35, 9.35, 9.35); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (81x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 1.23 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.74 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.98 W/kg

**SAR(1 g) = 1 W/kg; SAR(10 g) = 0.496 W/kg**

Maximum value of SAR (measured) = 1.44 W/kg



0 dB = 1.44 W/kg = 1.58 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**GSM 850\_Body-worn\_Back side\_CH 190\_15mm**

Communication System: GSM; Frequency: 824.2 MHz

Medium parameters used:  $f = 824.2$  MHz;  $\sigma = 0.973$  S/m;  $\epsilon_r = 54.844$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (81x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.331 W/kg



**Configuration/Body/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.12 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.427 W/kg

**SAR(1 g) = 0.268 W/kg; SAR(10 g) = 0.155 W/kg**

Maximum value of SAR (measured) = 0.340 W/kg



0 dB = 0.340 W/kg = -4.69 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

## GPRS 850\_Hotspot\_Back side\_CH 190\_10mm

Communication System: GPRS(1Dn2Up); Frequency: 836.6 MHz

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.985$  S/m;  $\epsilon_r = 54.792$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.706 W/kg

**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.43 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.00 W/kg

**SAR(1 g) = 0.615 W/kg; SAR(10 g) = 0.335 W/kg**

Maximum value of SAR (measured) = 0.763 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.43 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.02 W/kg

**SAR(1 g) = 0.538 W/kg; SAR(10 g) = 0.287 W/kg**

Maximum value of SAR (measured) = 0.768 W/kg



0 dB = 0.768 W/kg = -1.15 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/3

**GSM 1900\_Head\_Le Cheek\_CH 512**

Communication System: GSM; Frequency: 1850.2 MHz

Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.367$  S/m;  $\epsilon_r = 41.366$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.43, 8.43, 8.43); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x131x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.0817 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.034 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0960 W/kg

**SAR(1 g) = 0.076 W/kg; SAR(10 g) = 0.043 W/kg**

Maximum value of SAR (measured) = 0.0795 W/kg



0 dB = 0.0795 W/kg = -10.99 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/30

**GSM 1900\_Body-worn\_Back side\_CH 512\_15mm**

Communication System: GSM; Frequency: 1850.2 MHz

Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.484$  S/m;  $\epsilon_r = 52.713$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.11, 8.11, 8.11); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (81x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.206 W/kg



**Configuration/Body/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.124 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.369 W/kg

**SAR(1 g) = 0.219 W/kg; SAR(10 g) = 0.121 W/kg**

Maximum value of SAR (measured) = 0.290 W/kg



0 dB = 0.290 W/kg = -5.38 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/30

**GPRS 1900\_Hotspot\_Bottom side\_CH 661\_10mm**

Communication System: GPRS (1Dn2Up); Frequency: 1880 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.507$  S/m;  $\epsilon_r = 52.684$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.11, 8.11, 8.11); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (61x91x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 1.08 W/kg



**Configuration/Body/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.23 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.23 W/kg

**SAR(1 g) = 0.758 W/kg; SAR(10 g) = 0.398 W/kg**

Maximum value of SAR (measured) = 0.992 W/kg



0 dB = 0.992 W/kg = -0.04 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/3

**GSM 1900\_Head\_Re Tilt\_CH 661**

Communication System: GSM; Frequency: 1880 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.392$  S/m;  $\epsilon_r = 41.301$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3923; ConvF(8.43, 8.43, 8.43); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x131x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.602 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.01 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.806 W/kg

**SAR(1 g) = 0.353 W/kg; SAR(10 g) = 0.169 W/kg**

Maximum value of SAR (measured) = 0.550 W/kg



0 dB = 0.550 W/kg = -2.60 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/30

**GSM 1900\_Body-worn\_Front side\_CH 810\_15mm**

Communication System: GSM; Frequency: 1909.8 MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.529$  S/m;  $\epsilon_r = 52.601$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.11, 8.11, 8.11); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (81x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.115 W/kg



**Configuration/Body/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.441 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.143 W/kg

**SAR(1 g) = 0.083 W/kg; SAR(10 g) = 0.045 W/kg**

Maximum value of SAR (measured) = 0.113 W/kg



0 dB = 0.113 W/kg = -9.46 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/30

**GPRS 1900\_Hotspot\_Top side\_CH 661\_10mm**



Communication System: GPRS (1Dn2Up); Frequency: 1880 MHz

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.507 \text{ S/m}$ ;  $\epsilon_r = 52.684$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.11, 8.11, 8.11); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (61x91x1):** Interpolated grid:  $dx=15 \text{ mm}$ ,  $dy=15 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.388 \text{ W/kg}$ **Configuration/Body/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $14.74 \text{ V/m}$ ; Power Drift =  $0.03 \text{ dB}$ Peak SAR (extrapolated) =  $0.485 \text{ W/kg}$ **SAR(1 g) =  $0.285 \text{ W/kg}$ ; SAR(10 g) =  $0.142 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.381 \text{ W/kg}$  $0 \text{ dB} = 0.381 \text{ W/kg} = -4.19 \text{ dBW/kg}$ 

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/1

**WCDMA Band 5\_Head\_Le Cheek\_CH 4132**

Communication System: WCDMA; Frequency: 826.4 MHz

Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.913$  S/m;  $\epsilon_r = 41.821$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3938; ConvF(9.35, 9.35, 9.35); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (81x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.121 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.058 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.137 W/kg

**SAR(1 g) = 0.067 W/kg; SAR(10 g) = 0.041 W/kg**

Maximum value of SAR (measured) = 0.126 W/kg



0 dB = 0.126 W/kg = -9.01 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**WCDMA Band 5\_Body-worn\_Back side\_CH 4233\_15mm**

Communication System: WCDMA; Frequency: 846.6 MHz

Medium parameters used:  $f = 847$  MHz;  $\sigma = 0.996$  S/m;  $\epsilon_r = 54.752$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x111x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.410 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.31 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.480 W/kg

**SAR(1 g) = 0.305 W/kg; SAR(10 g) = 0.194 W/kg**

Maximum value of SAR (measured) = 0.395 W/kg



0 dB = 0.395 W/kg = -4.04 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**WCDMA Band 5\_Hotspot\_Back side\_CH 4233\_10mm**

Communication System: WCDMA; Frequency: 846.6 MHz

Medium parameters used:  $f = 847$  MHz;  $\sigma = 0.996$  S/m;  $\epsilon_r = 54.752$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.845 W/kg

**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.40 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.10 W/kg

**SAR(1 g) = 0.619 W/kg; SAR(10 g) = 0.371 W/kg**

Maximum value of SAR (measured) = 0.866 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.40 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.857 W/kg

**SAR(1 g) = 0.523 W/kg; SAR(10 g) = 0.357 W/kg**

Maximum value of SAR (measured) = 0.698 W/kg



0 dB = 0.698 W/kg = -1.56 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/1

**WCDMA Band 5\_Head\_Re Cheek\_CH 4132**

Communication System: WCDMA; Frequency: 826.4 MHz

Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.913$  S/m;  $\epsilon_r = 41.821$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.35, 9.35, 9.35); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (81x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 1.03 W/kg


**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.64 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.67 W/kg

**SAR(1 g) = 0.841 W/kg; SAR(10 g) = 0.423 W/kg**

Maximum value of SAR (measured) = 1.19 W/kg



0 dB = 1.19 W/kg = 0.74 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**WCDMA Band 5\_Body-worn\_Back side\_CH 4183\_15mm**

Communication System: WCDMA; Frequency: 836.6 MHz

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.985$  S/m;  $\epsilon_r = 54.792$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.230 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.371 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.286 W/kg

**SAR(1 g) = 0.145 W/kg; SAR(10 g) = 0.091 W/kg**

Maximum value of SAR (measured) = 0.233 W/kg



0 dB = 0.233 W/kg = -6.34 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**WCDMA Band 5\_Hotspot\_Back side\_CH 4132\_10mm**

Communication System: WCDMA; Frequency: 826.4 MHz

Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.974$  S/m;  $\epsilon_r = 54.821$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x151x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.570 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.758 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.786 W/kg

**SAR(1 g) = 0.317 W/kg; SAR(10 g) = 0.232 W/kg**

Maximum value of SAR (measured) = 0.599 W/kg



0 dB = 0.599 W/kg = -2.23 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/1

**LTE Band 5 (10MHz)\_Head\_Le Cheek\_CH 20450\_QPSK\_1-25**

Communication System: LTE; Frequency: 829 MHz

Medium parameters used:  $f = 829$  MHz;  $\sigma = 0.916$  S/m;  $\epsilon_r = 41.805$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.35, 9.35, 9.35); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (81x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.0611 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.413 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0720 W/kg

**SAR(1 g) = 0.056 W/kg; SAR(10 g) = 0.043 W/kg**

Maximum value of SAR (measured) = 0.0651 W/kg



0 dB = 0.0651 W/kg = -11.87 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**LTE Band 5 (10MHz)\_Body-worn\_Back side\_CH 20600\_QPSK\_1-25\_15mm**

Communication System: LTE; Frequency: 844 MHz

Medium parameters used:  $f = 844$  MHz;  $\sigma = 0.994$  S/m;  $\epsilon_r = 54.763$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (81x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.261 W/kg



**Configuration/Body/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.01 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.299 W/kg

**SAR(1 g) = 0.260 W/kg; SAR(10 g) = 0.169 W/kg**

Maximum value of SAR (measured) = 0.266 W/kg



0 dB = 0.266 W/kg = -5.75 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

## LTE Band 5 (10MHz)\_Hotspot\_Back side\_CH 20600\_QPSK\_1-25\_10mm

Communication System: LTE; Frequency: 844 MHz

Medium parameters used:  $f = 844$  MHz;  $\sigma = 0.994$  S/m;  $\epsilon_r = 54.763$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (81x141x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.662 W/kg



**Configuration/Body/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.70 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.918 W/kg

**SAR(1 g) = 0.526 W/kg; SAR(10 g) = 0.293 W/kg**

Maximum value of SAR (measured) = 0.699 W/kg



0 dB = 0.699 W/kg = -1.55 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/1

**LTE Band 5 (10MHz)\_Head\_Re Cheek\_CH 20450\_QPSK\_1-25**

Communication System: LTE; Frequency: 829 MHz

Medium parameters used:  $f = 829$  MHz;  $\sigma = 0.916$  S/m;  $\epsilon_r = 41.805$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.35, 9.35, 9.35); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (81x121x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 1.09 W/kg


**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.70 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.79 W/kg

**SAR(1 g) = 0.900 W/kg; SAR(10 g) = 0.442 W/kg**

Maximum value of SAR (measured) = 1.27 W/kg



0 dB = 1.27 W/kg = 1.05 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**LTE Band 5 (10MHz)\_Body-worn\_Back side\_CH 20450\_QPSK\_1-25\_15mm**

Communication System: LTE; Frequency: 829 MHz

Medium parameters used:  $f = 829$  MHz;  $\sigma = 0.979$  S/m;  $\epsilon_r = 54.813$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- ASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x151x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.203 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.34 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.251 W/kg

**SAR(1 g) = 0.142 W/kg; SAR(10 g) = 0.089 W/kg**

Maximum value of SAR (measured) = 0.205 W/kg



0 dB = 0.205 W/kg = -6.87 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**LTE Band 5 (10MHz)\_Hotspot\_Back side\_CH 20450\_QPSK\_1-25\_10mm**

Communication System: LTE; Frequency: 829 MHz

Medium parameters used:  $f = 829$  MHz;  $\sigma = 0.979$  S/m;  $\epsilon_r = 54.813$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x151x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.504 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.63 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.718 W/kg

**SAR(1 g) = 0.331 W/kg; SAR(10 g) = 0.202 W/kg**

Maximum value of SAR (measured) = 0.536 W/kg



0 dB = 0.536 W/kg = -2.71 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/4

**LTE Band 7 (20MHz)\_Head\_Re Cheek\_CH 21350\_QPSK\_1-50**

Communication System: LTE; Frequency: 2560 MHz

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.932$  S/m;  $\epsilon_r = 40.491$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.79, 6.79, 6.79); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (101x161x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.157 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.345 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.0570 W/kg

**SAR(1 g) = 0.032 W/kg; SAR(10 g) = 0.018 W/kg**

Maximum value of SAR (measured) = 0.0446 W/kg



0 dB = 0.0446 W/kg = -13.51 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/5

**LTE Band 7 (20MHz)\_Body-worn\_Front side\_CH 21350\_QPSK\_1-50\_15mm\_**

Communication System: LTE; Frequency: 2560 MHz

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 2.165$  S/m;  $\epsilon_r = 52.203$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (101x171x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.269 W/kg



**Configuration/Body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.355 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.342 W/kg

**SAR(1 g) = 0.216 W/kg; SAR(10 g) = 0.126 W/kg**

Maximum value of SAR (measured) = 0.268 W/kg



0 dB = 0.268 W/kg = -5.72 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/5

**LTE Band 7 (20MHz)\_Hotspot\_Bottom side\_CH 21100\_QPSK\_1-50\_10mm\_**

Communication System: LTE; Frequency: 2535 MHz

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 2.134$  S/m;  $\epsilon_r = 52.244$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Body/Area Scan (71x111x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 1.14 W/kg



**Configuration/Body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.62 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.55 W/kg

**SAR(1 g) = 0.829 W/kg; SAR(10 g) = 0.403 W/kg**

Maximum value of SAR (measured) = 1.19 W/kg



0 dB = 1.19 W/kg = 0.76 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/4

**LTE Band 7 (20MHz)\_Head\_Re Cheek\_CH 21350\_QPSK\_1-99**

Communication System: LTE; Frequency: 2560 MHz

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.932$  S/m;  $\epsilon_r = 40.491$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.79, 6.79, 6.79); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (101x151x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 1.35 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.76 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.94 W/kg

**SAR(1 g) = 0.788 W/kg; SAR(10 g) = 0.393 W/kg**

Maximum value of SAR (measured) = 1.30 W/kg



0 dB = 1.30 W/kg = 1.14 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/5

**LTE Band 7 (20MHz)\_Body-worn\_Front side\_CH 21100\_QPSK\_1-50\_15mm**

Communication System: LTE; Frequency: 2535 MHz

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 2.134$  S/m;  $\epsilon_r = 52.244$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (91x191x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.108 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.359 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.139 W/kg

**SAR(1 g) = 0.081 W/kg; SAR(10 g) = 0.044 W/kg**

Maximum value of SAR (measured) = 0.105 W/kg



0 dB = 0.105 W/kg = -9.78 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/5

**LTE Band 7 (20MHz)\_Hotspot\_Front side\_CH 21350\_QPSK\_1-99\_10mm**

Communication System: LTE; Frequency: 2560 MHz

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 2.165$  S/m;  $\epsilon_r = 52.203$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (91x191x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.222 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.431 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.288 W/kg

**SAR(1 g) = 0.173 W/kg; SAR(10 g) = 0.089 W/kg**

Maximum value of SAR (measured) = 0.217 W/kg



0 dB = 0.217 W/kg = -6.63 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/4

**LTE Band 38 (20MHz)\_Head\_Re Cheek\_CH 38000\_QPSK\_1-0**

Communication System: LTE; Frequency: 2595 MHz

Medium parameters used:  $f = 2595$  MHz;  $\sigma = 1.974$  S/m;  $\epsilon_r = 40.414$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.79, 6.79, 6.79); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (101x161x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.0248 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.7980 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0330 W/kg

**SAR(1 g) = 0.018 W/kg; SAR(10 g) = 0.00876 W/kg**

Maximum value of SAR (measured) = 0.0261 W/kg



0 dB = 0.0261 W/kg = -15.83 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/5

**LTE Band 38 (20MHz)\_Hotspot\_Front side\_CH 38150\_QPSK\_1-0\_15mm**

Communication System: LTE; Frequency: 2610 MHz

Medium parameters used:  $f = 2610$  MHz;  $\sigma = 2.236$  S/m;  $\epsilon_r = 52.119$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (91x181x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.108 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.178 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.136 W/kg

**SAR(1 g) = 0.090 W/kg; SAR(10 g) = 0.053 W/kg**

Maximum value of SAR (measured) = 0.102 W/kg



0 dB = 0.102 W/kg = -9.93 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/5

**LTE Band 38 (20MHz)\_Hotspot\_Bottom side\_CH 38150\_QPSK\_1-0\_10mm**

Communication System: LTE; Frequency: 2610 MHz

Medium parameters used:  $f = 2610$  MHz;  $\sigma = 2.236$  S/m;  $\epsilon_r = 52.119$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (81x151x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.481 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.335 V/m; Power Drift = 0.34 dB

Peak SAR (extrapolated) = 0.649 W/kg

**SAR(1 g) = 0.367 W/kg; SAR(10 g) = 0.164 W/kg**

Maximum value of SAR (measured) = 0.488 W/kg



0 dB = 0.488 W/kg = -3.12 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/4

**LTE Band 38 (20MHz)\_Head\_Re Cheek\_CH 38150\_QPSK\_1-50**

Communication System: LTE; Frequency: 2610 MHz

Medium parameters used:  $f = 2610$  MHz;  $\sigma = 1.995$  S/m;  $\epsilon_r = 40.392$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.79, 6.79, 6.79); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (101x151x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 1.12 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.38 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 1.74 W/kg

**SAR(1 g) = 0.685 W/kg; SAR(10 g) = 0.316 W/kg**

Maximum value of SAR (measured) = 1.14 W/kg



0 dB = 1.14 W/kg = 0.57 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/6

**LTE Band 38 (20MHz)\_Body-worn\_Back side\_CH 38150\_QPSK\_1-50\_15mm**

Communication System: LTE; Frequency: 2610 MHz

Medium parameters used:  $f = 2610$  MHz;  $\sigma = 2.229$  S/m;  $\epsilon_r = 52.042$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (71x151x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.101 W/kg



**Configuration/Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.674 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.130 W/kg

**SAR(1 g) = 0.081 W/kg; SAR(10 g) = 0.042 W/kg**

Maximum value of SAR (measured) = 0.0971 W/kg



0 dB = 0.0971 W/kg = -10.13 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/6

**LTE Band 38 (20MHz)\_Hotspot\_Left side\_CH 38150\_QPSK\_1-50\_10mm**

Communication System: LTE; Frequency: 2610 MHz

Medium parameters used:  $f = 2610$  MHz;  $\sigma = 2.229$  S/m;  $\epsilon_r = 52.042$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (61x151x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.211 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.629 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.287 W/kg

**SAR(1 g) = 0.184 W/kg; SAR(10 g) = 0.091 W/kg**

Maximum value of SAR (measured) = 0.214 W/kg



0 dB = 0.214 W/kg = -6.70 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/31

**WLAN 802.11b\_Head\_Le Tilt\_CH 11**

Communication System: WLAN 2.45G; Frequency: 2462 MHz

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.844$  S/m;  $\epsilon_r = 40.552$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.57, 7.57, 7.57); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (81x161x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.622 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.102 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.23 W/kg

**SAR(1 g) = 0.398 W/kg; SAR(10 g) = 0.135 W/kg**

Maximum value of SAR (measured) = 0.754 W/kg



0 dB = 0.754 W/kg = -1.23 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/31

**WLAN 802.11b\_Body-worn\_Back side\_CH 11\_15mm**

Communication System: WLAN 2.45G; Frequency: 2462 MHz

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.995$  S/m;  $\epsilon_r = 51.204$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.63, 7.63, 7.63); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (91x161x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.185 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.212 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.245 W/kg

**SAR(1 g) = 0.145 W/kg; SAR(10 g) = 0.072 W/kg**

Maximum value of SAR (measured) = 0.180 W/kg



0 dB = 0.180 W/kg = -7.45 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/31

**WLAN 802.11b\_Hotspot\_Back side\_CH 11\_10mm**

Communication System: WLAN 2.45G; Frequency: 2462 MHz

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.995$  S/m;  $\epsilon_r = 51.204$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 – SN3923; ConvF(7.63, 7.63, 7.63); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Head/Area Scan (91x161x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.500 W/kg



**Configuration/Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.221 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.820 W/kg

**SAR(1 g) = 0.315 W/kg; SAR(10 g) = 0.138 W/kg**

Maximum value of SAR (measured) = 0.557 W/kg



0 dB = 0.557 W/kg = -2.54 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 6. SAR System Performance Verification

Date: 2016/8/1

### Dipole 835 MHz\_SN:4d063\_Head

Communication System: CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.921 \text{ S/m}$ ;  $\epsilon_r = 41.782$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.35, 9.35, 9.35); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (51x121x1):** Interpolated grid:  $dx=15 \text{ mm}$ ,  $dy=15 \text{ mm}$ 

Maximum value of SAR (interpolated) = 3.06 W/kg



**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ 

Reference Value = 55.72 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 3.60 W/kg

**SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.54 W/kg**

Maximum value of SAR (measured) = 3.04 W/kg



0 dB = 3.04 W/kg = 4.83 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/2

**Dipole 835 MHz\_SN:4d063\_Body**



Communication System: CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.984 \text{ S/m}$ ;  $\epsilon_r = 54.8$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(9.3, 9.3, 9.3); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (51x111x1):** Interpolated grid:  $dx=15 \text{ mm}$ ,  $dy=15 \text{ mm}$ Maximum value of SAR (interpolated) =  $2.88 \text{ W/kg}$ **Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $54.23 \text{ V/m}$ ; Power Drift =  $0.11 \text{ dB}$ Peak SAR (extrapolated) =  $3.36 \text{ W/kg}$ **SAR(1 g) =  $2.34 \text{ W/kg}$ ; SAR(10 g) =  $1.52 \text{ W/kg}$** Maximum value of SAR (measured) =  $2.89 \text{ W/kg}$  $0 \text{ dB} = 2.89 \text{ W/kg} = 4.60 \text{ dBW/kg}$ 

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/3

**Dipole 1900 MHz\_SN:5d027\_Head**

Communication System: CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.414$  S/m;  $\epsilon_r = 41.252$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.43, 8.43, 8.43); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (41x81x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 14.5 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.35 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 19.1 W/kg

**SAR(1 g) = 9.79 W/kg; SAR(10 g) = 5.09 W/kg**

Maximum value of SAR (measured) = 14.5 W/kg



0 dB = 14.5 W/kg = 11.61 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/30

**Dipole 1900 MHz\_SN:5d027\_Body**

Communication System: CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.522$  S/m;  $\epsilon_r = 52.633$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.11, 8.11, 8.11); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (41x71x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 15.3 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.99 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 18.2 W/kg

**SAR(1 g) = 9.95 W/kg; SAR(10 g) = 5.23 W/kg**

Maximum value of SAR (measured) = 14.3 W/kg



0 dB = 14.3 W/kg = 11.57 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/31

**Dipole 2450 MHz\_SN:727\_Head**

Communication System: CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.831$  S/m;  $\epsilon_r = 40.583$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.57, 7.57, 7.57); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (51x101x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 21.4 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 103.7 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 29.2 W/kg

**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.1 W/kg**

Maximum value of SAR (measured) = 20.9 W/kg



0 dB = 20.9 W/kg = 13.21 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/7/31

**Dipole 2450 MHz\_SN:727\_Body**

Communication System: CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.982$  S/m;  $\epsilon_r = 51.233$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.11, 8.11, 8.11); Calibrated: 2015/8/27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1374; Calibrated: 2015/10/23
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (51x91x1):** Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 23.1 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.5 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 27.1 W/kg

**SAR(1 g) = 13 W/kg; SAR(10 g) = 6.01 W/kg**

Maximum value of SAR (measured) = 20.1 W/kg



0 dB = 20.1 W/kg = 13.03 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/4

**Dipole 2600 MHz\_SN:1005\_Head**

Communication System: CW; Frequency: 2600 MHz

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.981$  S/m;  $\epsilon_r = 40.403$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.79, 6.79, 6.79); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (51x101x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 23.1 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.4 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 32.8 W/kg

**SAR(1 g) = 14.4 W/kg; SAR(10 g) = 6.34 W/kg**

Maximum value of SAR (measured) = 23.1 W/kg



0 dB = 23.1 W/kg = 13.64 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/5

**Dipole 2600 MHz\_SN:1005\_Body**

Communication System: CW; Frequency: 2600 MHz

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.221$  S/m;  $\epsilon_r = 52.135$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (51x61x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 22.7 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.55 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 30.2 W/kg

**SAR(1 g) = 14 W/kg; SAR(10 g) = 6.2 W/kg**

Maximum value of SAR (measured) = 21.8 W/kg



0 dB = 21.8 W/kg = 13.38 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Date: 2016/8/6

**Dipole 2600 MHz\_SN:1005\_Body**

Communication System: CW; Frequency: 2600 MHz

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.219$  S/m;  $\epsilon_r = 52.053$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3938; ConvF(6.89, 6.89, 6.89); Calibrated: 2015/10/1;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2015/9/24
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/Pin=250mW/Area Scan (51x61x1):** Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 22.7 W/kg

**Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:



dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.27 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 30.3 W/kg

**SAR(1 g) = 14 W/kg; SAR(10 g) = 6.22 W/kg**

Maximum value of SAR (measured) = 21.9 W/kg



0 dB = 21.9 W/kg = 13.40 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 7. DAE & Probe Calibration Certificate

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: SGS - TW (Auden)

Certificate No.: DAE4-1374\_Oct15

### CALIBRATION CERTIFICATE

Object: DAE4 - SD 000 D04 BM - SN: 1374

Calibration procedure(s): QA CAL-06.v29  
Calibration procedure for the data acquisition electronics (DAE)

Calibration date: October 23, 2015

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (MATE critical for calibration)

| Primary Standards             | ID #               | Cal Date (Certificate No.) | Scheduled Calibration  |
|-------------------------------|--------------------|----------------------------|------------------------|
| Keithley Multimeter Type 2001 | SN: 0910278        | 09-Sep-15 (No: 17153)      | Sep-16                 |
| Secondary Standards           | ID #               | Check Date (in house)      | Scheduled Check        |
| Auto DAE Calibration Unit     | SE UWS 053 AA 1001 | 06-Jan-15 (in house check) | In house check: Jan-16 |
| Calibrator Box V2.1           | SE UMS 006 AA 1002 | 06-Jan-15 (in house check) | In house check: Jan-16 |

|                |                            |                          |                |
|----------------|----------------------------|--------------------------|----------------|
| Calibrated by: | Name:<br>Dominique Steffen | Function:<br>Technician  | Signature:<br> |
| Approved by:   | Fin Bombard                | Deputy Technical Manager |                |

Issued: October 23, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No.: DAE4-1374\_Oct15

Page 1 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zaughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'etonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

## Glossary

DAE data acquisition electronics  
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

## Methods Applied and Interpretation of Parameters

- **DC Voltage Measurement:** Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- **Connector angle:** The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - **DC Voltage Measurement Linearity:** Verification of the Linearity at  $\pm 10\%$  and  $-10\%$  of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - **Common mode sensitivity:** Influence of a positive or negative common mode voltage on the differential measurement.
  - **Channel separation:** Influence of a voltage on the neighbor channels not subject to an input voltage.
  - **AD Converter Values with inputs shorted:** Values on the internal AD converter corresponding to zero input voltage
  - **Input Offset Measurement:** Output voltage and statistical results over a large number of zero voltage measurements.
  - **Input Offset Current:** Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - **Input resistance:** Typical value for information; DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - **Low Battery Alarm Voltage:** Typical value for information. Below this voltage, a battery alarm signal is generated.
  - **Power consumption:** Typical value for information. Supply currents in various operating modes.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**DC Voltage Measurement**

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 $\mu$ V , full range = -100...+300 mV

Low Range: 1LSB = 61nV , full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X                         | Y                         | Z                         |
|---------------------|---------------------------|---------------------------|---------------------------|
| High Range          | 403.597 $\pm$ 0.02% (k=2) | 403.842 $\pm$ 0.02% (k=2) | 404.121 $\pm$ 0.02% (k=2) |
| Low Range           | 3.98111 $\pm$ 1.50% (k=2) | 3.98638 $\pm$ 1.50% (k=2) | 3.98936 $\pm$ 1.50% (k=2) |

**Connector Angle**

|                                           |                                    |
|-------------------------------------------|------------------------------------|
| Connector Angle to be used in DASY system | 41.0 $^{\circ}$ $\pm$ 1 $^{\circ}$ |
|-------------------------------------------|------------------------------------|

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Appendix (Additional assessments outside the scope of SCS0108)

## 1. DC Voltage Linearity

| High Range        | Reading ( $\mu\text{V}$ ) | Difference ( $\mu\text{V}$ ) | Error (%) |
|-------------------|---------------------------|------------------------------|-----------|
| Channel X + Input | 200033.09                 | -0.21                        | -0.00     |
| Channel X + Input | 20006.43                  | 2.25                         | 0.01      |
| Channel X - Input | -20003.08                 | 2.09                         | -0.01     |
| Channel Y + Input | 200033.11                 | -0.07                        | -0.00     |
| Channel Y + Input | 20001.24                  | -2.89                        | -0.01     |
| Channel Y - Input | -20006.12                 | -0.87                        | 0.00      |
| Channel Z + Input | 200032.98                 | -0.38                        | -0.00     |
| Channel Z + Input | 20001.71                  | -2.35                        | -0.01     |
| Channel Z - Input | -20007.05                 | -1.72                        | 0.01      |

| Low Range         | Reading ( $\mu\text{V}$ ) | Difference ( $\mu\text{V}$ ) | Error (%) |
|-------------------|---------------------------|------------------------------|-----------|
| Channel X + Input | 2000.72                   | 0.10                         | 0.00      |
| Channel X + Input | 200.90                    | 0.07                         | 0.04      |
| Channel X - Input | -198.32                   | 0.99                         | -0.50     |
| Channel Y + Input | 2000.56                   | -0.00                        | -0.00     |
| Channel Y + Input | 199.87                    | -0.82                        | -0.41     |
| Channel Y - Input | -199.92                   | -0.51                        | 0.26      |
| Channel Z + Input | 2000.72                   | 0.21                         | 0.01      |
| Channel Z + Input | 199.48                    | -1.11                        | -0.56     |
| Channel Z - Input | -200.66                   | -1.13                        | 0.57      |

## 2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | Common mode Input Voltage (mV) | High Range Average Reading ( $\mu\text{V}$ ) | Low Range Average Reading ( $\mu\text{V}$ ) |
|-----------|--------------------------------|----------------------------------------------|---------------------------------------------|
| Channel X | 200                            | 6.36                                         | 3.97                                        |
|           | - 200                          | -2.21                                        | -4.56                                       |
| Channel Y | 200                            | 7.13                                         | 6.98                                        |
|           | - 200                          | -8.29                                        | -8.73                                       |
| Channel Z | 200                            | 6.37                                         | 6.35                                        |
|           | - 200                          | -9.60                                        | -8.25                                       |

## 3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | Input Voltage (mV) | Channel X ( $\mu\text{V}$ ) | Channel Y ( $\mu\text{V}$ ) | Channel Z ( $\mu\text{V}$ ) |
|-----------|--------------------|-----------------------------|-----------------------------|-----------------------------|
| Channel X | 200                | -                           | -2.02                       | -1.56                       |
| Channel Y | 200                | 4.68                        | -                           | -1.06                       |
| Channel Z | 200                | 11.09                       | 1.58                        | -                           |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**4. AD-Converter Values with inputs shorted**

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | High Range (LSB) | Low Range (LSB) |
|-----------|------------------|-----------------|
| Channel X | 15850            | 15857           |
| Channel Y | 16166            | 15762           |
| Channel Z | 16101            | 16123           |

**5. Input Offset Measurement**

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10M $\Omega$ 

|           | Average ( $\mu$ V) | min. Offset ( $\mu$ V) | max. Offset ( $\mu$ V) | Std. Deviation ( $\mu$ V) |
|-----------|--------------------|------------------------|------------------------|---------------------------|
| Channel X | 0.61               | -0.78                  | 1.59                   | 0.44                      |
| Channel Y | -0.47              | -2.13                  | 0.46                   | 0.39                      |
| Channel Z | -0.68              | -1.72                  | 0.64                   | 0.41                      |

**6. Input Offset Current**

Nominal Input circuitry offset current on all channels: &lt;251A

**7. Input Resistance** (Typical values for information)

|           | Zeroing (k $\Omega$ m) | Measuring (M $\Omega$ m) |
|-----------|------------------------|--------------------------|
| Channel X | 200                    | 200                      |
| Channel Y | 200                    | 200                      |
| Channel Z | 200                    | 200                      |

**8. Low Battery Alarm Voltage** (Typical values for information)

| Typical values | Alarm Level (VDC) |
|----------------|-------------------|
| Supply (+ Vcc) | +7.9              |
| Supply (- Vcc) | -7.6              |

**9. Power Consumption** (Typical values for information)

| Typical values | Switched off (mA) | Stand by (mA) | Transmitting (mA) |
|----------------|-------------------|---------------|-------------------|
| Supply (+ Vcc) | +0.01             | +6            | +14               |
| Supply (- Vcc) | -0.01             | -8            | -9                |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: SGS - TW (Auden)

Certificate No.: DAE4-1260\_Sep15

### CALIBRATION CERTIFICATE

Object: DAE4 - SD 000 D04 BM - SN: 1260

Calibration procedure(s): QA CAL-06.v29  
Calibration procedure for the data acquisition electronics (DAE)

Calibration date: September 24, 2015

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (NIST critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.) | Scheduled Calibration  |
|-----------------------------|--------------------|----------------------------|------------------------|
| Ketley Multimeter Type 2001 | SN: 0810278        | 09-Sep-15 (No:17153)       | Sep-15                 |
| Secondary Standards         | ID #               | Check Date (in house)      | Scheduled Check        |
| Auto DAE Calibration Unit   | SE UWS 053 AA 1001 | 06-Jan-15 (in house check) | In house check: Jan-16 |
| Calibrator Box V2.1         | SE UMS 006 AA 1002 | 06-Jan-15 (in house check) | In house check: Jan-16 |

Calibrated by: Name: Eric Hainfeld Function: Technician

Approved by: Frn Bornhof Deputy Technical Manager

Signature

Issued: September 24, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

## Glossary

DAE data acquisition electronics  
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

## Methods Applied and Interpretation of Parameters

- **DC Voltage Measurement:** Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- **Connector angle:** The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - **DC Voltage Measurement Linearity:** Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - **Common mode sensitivity:** Influence of a positive or negative common mode voltage on the differential measurement.
  - **Channel separation:** Influence of a voltage on the neighbor channels not subject to an input voltage.
  - **AD Converter Values with inputs shorted:** Values on the internal AD converter corresponding to zero input voltage
  - **Input Offset Measurement:** Output voltage and statistical results over a large number of zero voltage measurements.
  - **Input Offset Current:** Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - **Input resistance:** Typical value for information; DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - **Low Battery Alarm Voltage:** Typical value for information. Below this voltage, a battery alarm signal is generated.
  - **Power consumption:** Typical value for information. Supply currents in various operating modes.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**DC Voltage Measurement**

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 $\mu$ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X                         | Y                         | Z                         |
|---------------------|---------------------------|---------------------------|---------------------------|
| High Range          | 406.043 $\pm$ 0.02% (k=2) | 405.010 $\pm$ 0.02% (k=2) | 405.577 $\pm$ 0.02% (k=2) |
| Low Range           | 3.95755 $\pm$ 1.50% (k=2) | 4.01958 $\pm$ 1.50% (k=2) | 4.00483 $\pm$ 1.50% (k=2) |

**Connector Angle**

|                                           |                |
|-------------------------------------------|----------------|
| Connector Angle to be used in DASY system | 84.5° $\pm$ 1° |
|-------------------------------------------|----------------|

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Appendix (Additional assessments outside the scope of SCS0108)

### 1. DC Voltage Linearity

| High Range        | Reading ( $\mu\text{V}$ ) | Difference ( $\mu\text{V}$ ) | Error (%) |
|-------------------|---------------------------|------------------------------|-----------|
| Channel X + Input | 199996.71                 | -0.71                        | -0.00     |
| Channel X + Input | 20003.42                  | 1.97                         | 0.01      |
| Channel X - Input | -19997.29                 | 3.64                         | -0.02     |
| Channel Y + Input | 199997.03                 | -0.74                        | -0.00     |
| Channel Y + Input | 20002.19                  | 0.75                         | 0.00      |
| Channel Y - Input | -20000.85                 | -0.08                        | 0.00      |
| Channel Z + Input | 199995.02                 | -2.52                        | -0.00     |
| Channel Z + Input | 20000.79                  | -0.63                        | -0.00     |
| Channel Z - Input | -20001.97                 | -1.09                        | 0.01      |

| Low Range         | Reading ( $\mu\text{V}$ ) | Difference ( $\mu\text{V}$ ) | Error (%) |
|-------------------|---------------------------|------------------------------|-----------|
| Channel X + Input | 2001.31                   | 0.02                         | 0.00      |
| Channel X + Input | 201.74                    | 0.05                         | 0.03      |
| Channel X - Input | -197.79                   | 0.49                         | -0.25     |
| Channel Y + Input | 2001.47                   | 0.11                         | 0.01      |
| Channel Y + Input | 201.57                    | -0.09                        | -0.04     |
| Channel Y - Input | -198.16                   | 0.02                         | -0.01     |
| Channel Z + Input | 2001.06                   | -0.19                        | -0.01     |
| Channel Z + Input | 200.35                    | -1.16                        | -0.58     |
| Channel Z - Input | -199.72                   | -1.47                        | 0.74      |

### 2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | Common mode Input Voltage (mV) | High Range Average Reading ( $\mu\text{V}$ ) | Low Range Average Reading ( $\mu\text{V}$ ) |
|-----------|--------------------------------|----------------------------------------------|---------------------------------------------|
| Channel X | 200                            | 1.97                                         | -0.02                                       |
|           | -200                           | 0.99                                         | -1.30                                       |
| Channel Y | 200                            | 13.29                                        | 13.11                                       |
|           | -200                           | -13.69                                       | -13.98                                      |
| Channel Z | 200                            | -0.48                                        | -0.25                                       |
|           | -200                           | -1.06                                        | -1.87                                       |

### 3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | Input Voltage (mV) | Channel X ( $\mu\text{V}$ ) | Channel Y ( $\mu\text{V}$ ) | Channel Z ( $\mu\text{V}$ ) |
|-----------|--------------------|-----------------------------|-----------------------------|-----------------------------|
| Channel X | 200                | -                           | 5.95                        | -2.35                       |
| Channel Y | 200                | 9.12                        | -                           | 6.99                        |
| Channel Z | 200                | 9.45                        | 7.26                        | -                           |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**4. AD-Converter Values with inputs shorted**

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

|           | High Range (LSB) | Low Range (LSB) |
|-----------|------------------|-----------------|
| Channel X | 15911            | 14818           |
| Channel Y | 15818            | 16372           |
| Channel Z | 16044            | 16864           |

**5. Input Offset Measurement**

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10MQ

|           | Average ( $\mu$ V) | min. Offset ( $\mu$ V) | max. Offset ( $\mu$ V) | Std. Deviation ( $\mu$ V) |
|-----------|--------------------|------------------------|------------------------|---------------------------|
| Channel X | -0.60              | -1.69                  | 0.60                   | 0.44                      |
| Channel Y | -0.69              | -3.18                  | 0.27                   | 0.50                      |
| Channel Z | -1.05              | -1.97                  | 0.26                   | 0.49                      |

**6. Input Offset Current**

Nominal input circuitry offset current on all channels: &lt;25fA

**7. Input Resistance** (Typical values for information)

|           | Zeroing (kOhm) | Measuring (MOhm) |
|-----------|----------------|------------------|
| Channel X | 200            | 200              |
| Channel Y | 200            | 200              |
| Channel Z | 200            | 200              |

**8. Low Battery Alarm Voltage** (Typical values for information)

| Typical values | Alarm Level (VDC) |
|----------------|-------------------|
| Supply (+ Vcc) | +7.8              |
| Supply (- Vcc) | -7.8              |

**9. Power Consumption** (Typical values for information)

| Typical values | Switched off (mA) | Stand by (mA) | Transmitting (mA) |
|----------------|-------------------|---------------|-------------------|
| Supply (+ Vcc) | +0.01             | +6            | +14               |
| Supply (- Vcc) | -0.01             | -8            | -9                |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: SGS-TW (Auden)

Certificate No.: EX3-3923\_Aug15

## CALIBRATION CERTIFICATE

Object: EX3DV4 - SN:3923

Calibration procedure(s): QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6  
Calibration procedure for dosimetric E-field probes

Calibration date: August 27, 2015

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in this passed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (N/A/E critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration |
|----------------------------|-----------------|-----------------------------------|-----------------------|
| Power meter E4419B         | GB41293574      | 01-Apr-15 (No. 217-02125)         | Mar-16                |
| Power sensor E4412A        | MY61495057      | 01-Apr-15 (No. 217-02123)         | Mar-16                |
| Reference 3 dB Attenuator  | SN: S5054 (30)  | 01-Apr-15 (No. 217-02129)         | Mar-16                |
| Reference 20 dB Attenuator | SN: S5277 (20a) | 01-Apr-15 (No. 217-02132)         | Mar-16                |
| Reference 30 dB Attenuator | SN: S5129 (30a) | 01-Apr-15 (No. 217-02133)         | Mar-16                |
| Reference Probe ES30V2     | SN: 3015        | 30-Dec-14 (No. ES3-3015 Dec14)    | Dec-15                |
| DAE4                       | SN: 660         | 14-Jan-15 (No. DAE4-660 Jan15)    | Jan-16                |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check       |
| RF generator HF 8648C      | LS3042U01700    | 4-Aug-09 (in house check Apr-13)  | in house check Apr-16 |
| Network Analyzer HP 8750E  | LS37350555      | 18-Oct-01 (in house check Oct-14) | in house check Oct-15 |

|                                                                                                                 | Name          | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Issa Sheng    | Laboratory Technician |           |
| Approved by:                                                                                                    | Kajal Palamid | Technical Manager     |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |           |

Issued: August 27, 2015

Certificate No.: EX3-3923\_Aug15

Page 1 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Recognized by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

#### Glossary:

|                       |                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                   | (tissue simulating liquid                                                                                                                         |
| NORM <sub>x,y,z</sub> | sensitivity in free space                                                                                                                         |
| ConvF                 | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                        |
| DCP                   | diode compression point                                                                                                                           |
| CF                    | crest factor (1/duty_cycle) of the RF signal                                                                                                      |
| A, B, C, D            | modulation dependent linearization parameters                                                                                                     |
| Polarization $\psi$   | $\psi$ rotation around probe axis                                                                                                                 |
| Polarization $\theta$ | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle       | Information used in DASY system to align probe sensor X to the robot coordinate system                                                            |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KOB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>: Assessed for E-field polarization  $\alpha = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristic.
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; V<sub>Rx,y,z</sub>; A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy): In a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the effect of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

Certificate No: EKS-3873, Aug15

Page 2 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

EX3DV4 – SN:3923

August 27, 2015

## Probe EX3DV4

SN:3923

Manufactured: March 8, 2013  
Calibrated: August 27, 2015Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3923

August 27, 2016

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923****Basic Calibration Parameters**

|                                       | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|---------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu V/(V/m)^2$ ) <sup>A</sup> | 0.57     | 0.48     | 0.47     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                 | 103.6    | 96.4     | 101.3    |               |

**Modulation Calibration Parameters**

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu V}$ | C   | D<br>dB | VR<br>mV | Unc <sup>C</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                    | 1.0 | 0.00    | 153.8    | $\pm 3.3 \%$              |
|     |                           | Y | 0.0     | 0.0                    | 1.0 |         | 155.6    |                           |
|     |                           | Z | 0.0     | 0.0                    | 1.0 |         | 157.0    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter; uncertainty not required.

<sup>C</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3923

August 27, 2015

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923****Calibration Parameter Determined in Head Tissue Simulating Media**

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>e</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|------------|-----------|
| 750                  | 41.9                               | 0.89                            | 10.66   | 10.66   | 10.66   | 0.34               | 1.00       | ± 12.0 %  |
| 835                  | 41.5                               | 0.90                            | 10.45   | 10.45   | 10.45   | 0.42               | 0.80       | ± 12.0 %  |
| 900                  | 41.5                               | 0.97                            | 10.07   | 10.07   | 10.07   | 0.35               | 1.00       | ± 12.0 %  |
| 1750                 | 40.1                               | 1.37                            | 8.71    | 8.71    | 8.71    | 0.19               | 1.12       | ± 12.0 %  |
| 1900                 | 40.0                               | 1.40                            | 8.43    | 8.43    | 8.43    | 0.36               | 0.90       | ± 12.0 %  |
| 2000                 | 40.0                               | 1.40                            | 8.48    | 8.48    | 8.48    | 0.35               | 0.80       | ± 12.0 %  |
| 2300                 | 39.5                               | 1.67                            | 8.05    | 8.05    | 8.05    | 0.36               | 0.80       | ± 12.0 %  |
| 2450                 | 39.2                               | 1.80                            | 7.57    | 7.57    | 7.57    | 0.40               | 0.80       | ± 12.0 %  |
| 2600                 | 39.0                               | 1.96                            | 7.45    | 7.45    | 7.45    | 0.39               | 0.80       | ± 12.0 %  |
| 5250                 | 35.9                               | 4.71                            | 5.22    | 5.22    | 5.22    | 0.35               | 1.80       | ± 13.1 %  |
| 5300                 | 35.9                               | 4.76                            | 5.08    | 5.08    | 5.08    | 0.35               | 1.80       | ± 13.1 %  |
| 5600                 | 35.5                               | 5.07                            | 4.78    | 4.78    | 4.78    | 0.40               | 1.80       | ± 13.1 %  |
| 5750                 | 35.4                               | 5.22                            | 4.81    | 4.81    | 4.81    | 0.40               | 1.80       | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 160 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>e</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> AlphaDepth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3923

August 27, 2015

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923****Calibration Parameter Determined in Body Tissue Simulating Media**

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>f</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|------------|-----------|
| 750                  | 55.5                               | 0.96                            | 10.50   | 10.50   | 10.50   | 0.43               | 0.86       | ± 12.0 %  |
| 835                  | 55.2                               | 0.97                            | 10.48   | 10.48   | 10.48   | 0.21               | 1.42       | ± 12.0 %  |
| 900                  | 55.0                               | 1.05                            | 10.33   | 10.33   | 10.33   | 0.30               | 1.08       | ± 12.0 %  |
| 1750                 | 53.4                               | 1.49                            | 8.40    | 8.40    | 8.40    | 0.39               | 0.87       | ± 12.0 %  |
| 1900                 | 53.3                               | 1.52                            | 8.11    | 8.11    | 8.11    | 0.41               | 0.80       | ± 12.0 %  |
| 2000                 | 53.3                               | 1.52                            | 8.31    | 8.31    | 8.31    | 0.29               | 1.02       | ± 12.0 %  |
| 2300                 | 52.9                               | 1.81                            | 7.90    | 7.90    | 7.90    | 0.30               | 0.91       | ± 12.0 %  |
| 2450                 | 52.7                               | 1.95                            | 7.63    | 7.63    | 7.63    | 0.29               | 0.90       | ± 12.0 %  |
| 2600                 | 52.5                               | 2.16                            | 7.49    | 7.49    | 7.49    | 0.25               | 0.95       | ± 12.0 %  |
| 5250                 | 48.9                               | 5.36                            | 4.68    | 4.68    | 4.68    | 0.40               | 1.90       | ± 13.1 %  |
| 5300                 | 48.9                               | 5.42                            | 4.56    | 4.56    | 4.56    | 0.40               | 1.90       | ± 13.1 %  |
| 5600                 | 48.5                               | 5.77                            | 4.10    | 4.10    | 4.10    | 0.45               | 1.90       | ± 13.1 %  |
| 5750                 | 48.3                               | 5.94                            | 4.30    | 4.30    | 4.30    | 0.45               | 1.90       | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 60 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>f</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4-SN:3923

August 27, 2015

**Frequency Response of E-Field**  
(TEM-Cell:ifi110 EXX, Waveguide: R22)Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



EX3DV4- SN:3923

August 27, 2015

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$

f=600 MHz,TEM

f=1800 MHz,R22



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

Certificate No: EX3-3923\_Aug15

Page 8 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488



[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

EX3DV4- SN:3923

August 27, 2015

## Dynamic Range $f(SAR_{head})$ (TEM cell, $f_{eval}=1900\text{ MHz}$ )



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

Certificate No: EX3-3923\_Aug15

Page 9 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488


[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group


EX30V4-SN 3923

August 27, 2015

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid Error ( $\theta, \phi$ ), f = 900 MHz



Certificate No. EX3-3923\_Aug15

Page 10 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

EX3DV4- SN:3923

August 27, 2015

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923****Other Probe Parameters**

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | 123        |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8054 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: **SGS-TW (Auden)**

Certificate No.: **EX3-3938\_Oct15**

## CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3938**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6**  
Calibration procedure for dosimetric E-field probes

Calibration date: **October 1, 2015**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in this closed laboratory facility: environment temperature  $22 \pm 3^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&E critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E3419B         | DB41203874      | 01-Apr-15 (No. 217-02128)         | Mar-16                 |
| Power sensor E4412A        | MY41498087      | 01-Apr-15 (No. 217-02128)         | Mar-16                 |
| Reference 3 dB Attenuator  | SN: S5054 (3a)  | 01-Apr-15 (No. 217-02129)         | Mar-16                 |
| Reference 20 dB Attenuator | SN: S5277 (20a) | 01-Apr-15 (No. 217-02132)         | Mar-16                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 01-Apr-15 (No. 217-02133)         | Mar-16                 |
| Reference Probe ES30V2     | SN: 3013        | 30-Dec-14 (No. ES3-3013_Dec14)    | Dec-15                 |
| DAB4                       | SN: 660         | 14-Jan-15 (No. DAB4-660_Jan15)    | Jan-16                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8940C      | US364200700     | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-16 |
| Network Analyzer HP 8753C  | US37300585      | 19-Oct-01 (in house check Oct-14) | In house check: Oct-15 |

|                                                                                                                 | Name            | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|-----------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Israel Elmagazi | Laboratory Technician |           |
| Approved by:                                                                                                    | Kajsa Pokovic   | Technical Manager     |           |
| Issued: October 2, 2015                                                                                         |                 |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                 |                       |           |

Certificate No.: **EX3-3938\_Oct15**

Page 1 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zürich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'Etalonnage  
**C** Servizio Svizzera di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0106

#### Glossary:

|                        |                                                                                                                                           |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | issue simulating liquid                                                                                                                   |
| NORM <sub>x,y,z</sub>  | sensitivity in free space                                                                                                                 |
| ConvF                  | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                |
| DCP                    | diode compression point                                                                                                                   |
| CF                     | crest factor (1/duty cycle) of the RF signal                                                                                              |
| A, B, C, D             | modulation dependent linearization parameters                                                                                             |
| Polarization $\varphi$ | rotation around probe axis                                                                                                                |
| Polarization $\theta$  | rotation around an axis that is in the plane normal to probe axis (s) (measurement center),<br>i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | information used in DASY system to align probe sensor X to the root coordinate system                                                     |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 8656B4, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>: Assessed for E-field polarization  $N = 0$  (if  $\leq 500$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E-field uncertainty inside TSL (see below ConvF).
- NORM<sub>f</sub><sub>x,y,z</sub>: NORM<sub>x,y,z</sub> \* frequency response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A<sub>x,y,z</sub>, B<sub>x,y,z</sub>, C<sub>x,y,z</sub>, D<sub>x,y,z</sub>, VR<sub>x,y,z</sub>: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM (no uncertainty required).

Certificate No: EXI-3938\_Oct16

Page 2 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

EX3DV4 – SN:3938

October 1, 2015

## Probe EX3DV4

SN:3938

Manufactured: May 2, 2013  
Calibrated: October 1, 2015

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

Certificate No: EX3-3938\_Oct15

Page 3 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

EX3DV4- SN:3938

October 1, 2015

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3938****Basic Calibration Parameters**

|                                                    | Sensor X | Sensor Y | Sensor Z | Unc (k=2)    |
|----------------------------------------------------|----------|----------|----------|--------------|
| Norm ( $\mu\text{V}/(\text{V/m})^2$ ) <sup>A</sup> | 0.52     | 0.57     | 0.34     | $\pm 10.1\%$ |
| DCP (mV) <sup>B</sup>                              | 100.8    | 99.7     | 104.1    |              |

**Modulation Calibration Parameters**

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>C</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 141.3    | $\pm 2.7\%$               |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 147.2    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 128.1    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter; uncertainty not required.

<sup>C</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3938

October 1, 2015

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3938****Calibration Parameter Determined in Head Tissue Simulating Media**

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>e</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth <sup>h</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 750                  | 41.9                               | 0.89                            | 9.69    | 9.69    | 9.69    | 0.19               | 1.67                    | ± 12.0 %  |
| 835                  | 41.5                               | 0.90                            | 9.35    | 9.35    | 9.35    | 0.26               | 1.23                    | ± 12.0 %  |
| 900                  | 41.5                               | 0.97                            | 9.15    | 9.15    | 9.15    | 0.18               | 1.86                    | ± 12.0 %  |
| 1450                 | 40.5                               | 1.20                            | 7.86    | 7.86    | 7.86    | 0.13               | 2.63                    | ± 12.0 %  |
| 1750                 | 40.1                               | 1.37                            | 8.17    | 8.17    | 8.17    | 0.36               | 0.80                    | ± 12.0 %  |
| 1900                 | 40.0                               | 1.40                            | 7.89    | 7.89    | 7.89    | 0.32               | 0.80                    | ± 12.0 %  |
| 2000                 | 40.0                               | 1.40                            | 7.89    | 7.89    | 7.89    | 0.36               | 0.75                    | ± 12.0 %  |
| 2300                 | 39.5                               | 1.67                            | 7.46    | 7.46    | 7.46    | 0.34               | 0.88                    | ± 12.0 %  |
| 2450                 | 39.2                               | 1.80                            | 7.11    | 7.11    | 7.11    | 0.32               | 0.94                    | ± 12.0 %  |
| 2600                 | 39.0                               | 1.96                            | 6.79    | 6.79    | 6.79    | 0.24               | 1.23                    | ± 12.0 %  |
| 5250                 | 35.9                               | 4.71                            | 4.90    | 4.90    | 4.90    | 0.40               | 1.80                    | ± 13.1 %  |
| 5300                 | 35.9                               | 4.76                            | 4.81    | 4.81    | 4.81    | 0.40               | 1.80                    | ± 13.1 %  |
| 5600                 | 35.5                               | 5.07                            | 4.28    | 4.28    | 4.28    | 0.50               | 1.80                    | ± 13.1 %  |
| 5750                 | 35.4                               | 5.22                            | 4.41    | 4.41    | 4.41    | 0.50               | 1.80                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 120, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>e</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3938

October 1, 2015

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3938****Calibration Parameter Determined in Body Tissue Simulating Media**

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>f</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>d</sup> | Depth <sup>e</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 750                  | 55.5                               | 0.96                            | 9.50    | 9.50    | 9.50    | 0.31               | 1.13                    | ± 12.0 %  |
| 835                  | 55.2                               | 0.97                            | 9.30    | 9.30    | 9.30    | 0.28               | 1.26                    | ± 12.0 %  |
| 900                  | 55.0                               | 1.05                            | 9.22    | 9.22    | 9.22    | 0.34               | 1.05                    | ± 12.0 %  |
| 1450                 | 54.0                               | 1.30                            | 7.96    | 7.96    | 7.96    | 0.16               | 2.05                    | ± 12.0 %  |
| 1750                 | 53.4                               | 1.49                            | 7.73    | 7.73    | 7.73    | 0.42               | 0.80                    | ± 12.0 %  |
| 1900                 | 53.3                               | 1.52                            | 7.41    | 7.41    | 7.41    | 0.32               | 0.90                    | ± 12.0 %  |
| 2000                 | 53.3                               | 1.52                            | 7.55    | 7.55    | 7.55    | 0.26               | 1.05                    | ± 12.0 %  |
| 2300                 | 52.9                               | 1.81                            | 7.27    | 7.27    | 7.27    | 0.36               | 0.84                    | ± 12.0 %  |
| 2450                 | 52.7                               | 1.95                            | 7.17    | 7.17    | 7.17    | 0.37               | 0.85                    | ± 12.0 %  |
| 2600                 | 52.5                               | 2.16                            | 6.90    | 6.90    | 6.90    | 0.33               | 0.90                    | ± 12.0 %  |
| 5250                 | 48.9                               | 5.36                            | 4.19    | 4.19    | 4.19    | 0.50               | 1.90                    | ± 13.1 %  |
| 5300                 | 48.9                               | 5.42                            | 4.09    | 4.09    | 4.09    | 0.50               | 1.90                    | ± 13.1 %  |
| 5600                 | 48.5                               | 5.77                            | 3.66    | 3.66    | 3.66    | 0.55               | 1.90                    | ± 13.1 %  |
| 5750                 | 48.3                               | 5.94                            | 3.87    | 3.87    | 3.87    | 0.55               | 1.90                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>f</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>d</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3938

October 1, 2015

**Frequency Response of E-Field**  
(TEM-Cell:ifi110 EXX, Waveguide: R22)Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX30V4-SN-3938

October 1, 2015

Receiving Pattern ( $\phi$ ),  $\theta = 0^\circ$ Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

Certificate No: EX3-3938\_Oct15

Page 8 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279



f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

EX3DV4- SN:3938

October 1, 2015

**Dynamic Range f(SAR<sub>head</sub>)**  
(TEM cell, f<sub>eval</sub> = 1900 MHz)Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)

Certificate No: EX3-3938\_Oct15

Page 9 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488


[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group


EX30V4-SN3938

October 1, 2015

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid Error ( $\phi$ , $\theta$ ), $f = 900 \text{ MHz}$



Certificate No: EX3-3838\_Oct15

Page 10 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

EX3DV4- SN:3938

October 1, 2015

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3938****Other Probe Parameters**

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -28.1      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## 8. Phantom Description

Schmid &amp; Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland  
Phone: +41 1 245 9700, Fax: +41 1 245 9773  
info@speag.com, http://www.speag.com

### Certificate of Conformity / First Article Inspection

|              |                                                              |
|--------------|--------------------------------------------------------------|
| Item         | SAM Twin Phantom V4.0                                        |
| Type No.     | QD 000 P40 C                                                 |
| Series No.   | TP-1150 and higher                                           |
| Manufacturer | SPEAG<br>Zeughausstrasse 43<br>CH-8004 Zurich<br>Switzerland |

#### Tests

The series production process used allows the limitation to test of first articles.

Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1008. Certain parameters have been retested using further series items (called samples) or are tested at each item.

| Test                        | Requirement                                                                                                                                                                                      | Details                                                                  | Units tested                                |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|---------------------------------------------|
| Dimensions                  | Compliant with the geometry according to the CAD model.                                                                                                                                          | IT IS CAD File (*)                                                       | First article, Samples                      |
| Material thickness of shell | Compliant with the requirements according to the standards                                                                                                                                       | 2mm +/- 0.2mm in flat and specific areas of head section                 | First article, Samples, TP-1314 ff.         |
| Material thickness at ERP   | Compliant with the requirements according to the standards                                                                                                                                       | 6mm +/- 0.2mm at ERP                                                     | First article, A3 items                     |
| Material parameters         | Dielectric parameters for required frequencies                                                                                                                                                   | 300 MHz - 6 GHz;<br>Relative permittivity < 5;<br>Loss tangent < 0.05    | Material samples                            |
| Material resistivity        | The material has been tested to be compatible with the liquids defined in the standards if handled and cleaned according to the instructions. Observe technical Note for material compatibility. | DEGMRE based simulating liquids                                          | Pre-series, First article, Material samples |
| Sagging                     | Compliant with the requirements according to the standards. Sagging of the flat section when filled with tissue simulating liquid                                                                | < 1% typical < 0.6% if filled with 155mm of HSL900 and without OUT below | Prototypes, Sample testing                  |

#### Standards

- (1) CENELEC EN 50361
- (2) IEEE Std 1528-2003
- (3) IEC 62209 Part 1
- (4) FCC OET Bulletin 65, Supplement C, Edition 01-01

(\*) The IT IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of the other documents.

#### Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standards [1] to [4].

Date 07.07.2005

s p e a g

Signature / Stamp

Schmid & Partner Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland  
Phone: +41 1 245 9700 / Fax: +41 1 245 9773  
info@speag.com, http://www.speag.com

Doc No: SE1 - QD 000 P40 C -

Page 1 (1)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## 9. System Validation from Original Equipment Supplier

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (BAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: SGS-TW (Auden)

Certificate No: D835V2-4d063\_Aug15

### CALIBRATION CERTIFICATE

Object: D835V2 - SN: 4d063

Calibration procedure(s): QA.CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: August 24, 2015

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)     | Scheduled Calibration |
|-----------------------------|--------------------|--------------------------------|-----------------------|
| Power meter EPM-442A        | GBS7480704         | 07-Oct-14 (No. 217-02920)      | Oct-15                |
| Power sensor HP 8481A       | US37292763         | 07-Oct-14 (No. 217-02920)      | Oct-15                |
| Power sensor HP 8481A       | MY41092317         | 07-Oct-14 (No. 217-02921)      | Oct-15                |
| Reference 20 dB Attenuator  | SN: 5058 (20%)     | 01-Apr-15 (No. 217-02131)      | Mar-16                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 01-Apr-15 (No. 217-02134)      | Mar-16                |
| Reference Probe ES3DV3      | SN: 3205           | 30-Dec-14 (No. ES3-3205_Dec14) | Dec-15                |
| DAE4                        | SN: 601            | 17-Aug-15 (No. DAE4-601_Aug15) | Aug-16                |

| Secondary Standards       | ID #             | Check Date (in house)             | Scheduled Check        |
|---------------------------|------------------|-----------------------------------|------------------------|
| RF generator BAS-SMT-06   | 100005           | 04-Aug-09 (in house check Oct-13) | In house check: Oct-15 |
| Network Analyzer HP 8755E | US37380505 S4206 | 16-Oct-01 (in house check Oct-14) | In house check: Oct-15 |

|                |                         |                                   |               |
|----------------|-------------------------|-----------------------------------|---------------|
| Calibrated by: | Name<br>Michael Weber   | Function<br>Laboratory Technician | Signature<br> |
| Approved by:   | Name<br>Kolja Potornyak | Technician Manager                |               |

Issued: August 25, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D835V2-4d063\_Aug15

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0106

#### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Additional Documentation:

- DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: DB35V2-4d063 Aug15

Page 2 of 2

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 835 MHz $\pm$ 1 MHz    |             |

**Head TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 41.9 $\pm$ 6 % | 0.93 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

**SAR result with Head TSL**

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 2.33 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 9.11 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 1.52 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 5.97 W/kg $\pm$ 16.5 % (k=2) |

**Body TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 56.1 $\pm$ 6 % | 1.02 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

**SAR result with Body TSL**

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 2.40 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 9.28 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 1.57 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 6.11 W/kg $\pm$ 16.5 % (k=2) |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.3 $\Omega$ - 1.7 j $\Omega$ |
| Return Loss                          | - 33.4 dB                      |

**Antenna Parameters with Body TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 47.9 $\Omega$ - 2.7 j $\Omega$ |
| Return Loss                          | - 29.1 dB                      |

**General Antenna Parameters and Design**

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.394 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

**Additional EUT Data**

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | November 27, 2005 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## DASY5 Validation Report for Head TSL

Date: 21.08.2015

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d063**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.93 \text{ S/m}$ ;  $\epsilon_r = 41.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.2, 6.2, 6.2); Calibrated: 30.12.2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 17.08.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 55.92 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.44 W/kg

SAR(1 g) = 2.33 W/kg; SAR(10 g) = 1.52 W/kg

Maximum value of SAR (measured) = 2.73 W/kg




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Impedance Measurement Plot for Head TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## DASY5 Validation Report for Body TSL

Date: 24.08.2015

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d063**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 1.02 \text{ S/m}$ ;  $\epsilon_r = 56.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

### DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.17, 6.17, 6.17); Calibrated: 30.12.2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 17.08.2015
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.07 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.52 W/kg

SAR(1 g) = 2.4 W/kg; SAR(10 g) = 1.57 W/kg

Maximum value of SAR (measured) = 2.81 W/kg




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Impedance Measurement Plot for Body TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **SGS-TW (Auden)**

Certificate No: **D1900V2-5d027\_Apr16**

## CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d027**

Calibration procedure(s) **QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date **April 25, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02282)         | Apr-17                 |
| Type-N mismatch combination | SN: 3047.2 / 06327 | 05-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| DAE4                        | SN: 601            | 30-Dec-15 (No. DAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: GB37480704     | 07-Oct-15 (No. 217-02222)         | in house check: Oct-16 |
| Power sensor HP 8481A       | SN: US37292783     | 07-Oct-15 (No. 217-02222)         | in house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41092317     | 07-Oct-15 (No. 217-02223)         | in house check: Oct-16 |
| RF generator R&S SMT-06     | SN: 100872         | 15-Jun-15 (in house check Jun-15) | in house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: USS7390685     | 16-Oct-01 (in house check Oct-15) | in house check: Oct-16 |

Calibrated by: **Michael Weber** Function: **Laboratory Technician** Signature:

Approved by: **Katja Pokovic** Technical Manager:

Issued: April 26, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D1900V2-5d027\_Apr16

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

## Calibration Laboratory of

Schmid & Partner  
Engineering AG

Zughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

### Glossary:

TSL tissue simulating liquid  
ConvF sensitivity in TSL / NORM x,y,z  
N/A not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 1900 MHz $\pm$ 1 MHz   |             |

**Head TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 40.0           | 1.40 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.0 $\pm$ 6 % | 1.37 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

**SAR result with Head TSL**

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL   | Condition          |                              |
| SAR measured                                            | 250 mW input power | 9.55 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 36.7 W/kg $\pm$ 17.0 % (k=2) |
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.03 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 20.3 W/kg $\pm$ 16.5 % (k=2) |

**Body TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 53.3           | 1.52 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.9 $\pm$ 6 % | 1.49 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

**SAR result with Body TSL**

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL   | Condition          |                              |
| SAR measured                                            | 250 mW input power | 9.83 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 39.7 W/kg $\pm$ 17.0 % (k=2) |
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.21 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.0 W/kg $\pm$ 16.5 % (k=2) |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.8 $\Omega$ + 4.4 j $\Omega$ |
| Return Loss                          | - 27.0 dB                      |

**Antenna Parameters with Body TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 46.5 $\Omega$ + 5.6 j $\Omega$ |
| Return Loss                          | - 23.3 dB                      |

**General Antenna Parameters and Design**

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.196 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

**Additional EUT Data**

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | December 17, 2002 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## DASY5 Validation Report for Head TSL

Date: 25.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d027**

Communication System: UID 0 - C/W; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.37$  S/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

### DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.2, 8.2, 8.2); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.9 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 17.2 W/kg

**SAR(1 g) = 9.55 W/kg; SAR(10 g) = 5.03 W/kg**

Maximum value of SAR (measured) = 14.3 W/kg




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Impedance Measurement Plot for Head TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## DASY5 Validation Report for Body TSL

Date: 25.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d027**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.49$  S/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

### DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.03, 8.03, 8.03); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.2 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 17.2 W/kg

**SAR(1 g) = 9.83 W/kg; SAR(10 g) = 5.21 W/kg**

Maximum value of SAR (measured) = 14.7 W/kg




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Impedance Measurement Plot for Body TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **SGS-TW (Auden)**

Certificate No: **D2450V2-727\_Apr16**

## CALIBRATION CERTIFICATE

Object: **D2450V2 - SN:727**

Calibration procedure(s): **QA CAL-05.V9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **April 19, 2016**

This calibration certificate documents the traceability to national standards, which assure the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $\approx 70\%$ .

Calibration Equipment used (M&T: critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Reference 20 dB Attenuator  | SN: 5038 (20k)     | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| OAE4                        | SN: 601            | 30-Dec-15 (No. OAE4-601_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: 0837480704     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: US37292793     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| Power sensor HP 8481A       | SN: MY41082317     | 07-Oct-15 (No. 217-02222)         | In house check: Oct-16 |
| T/F Generator R&S SMT-06    | SN: 100972         | 15-Jun-15 (in house check Jun-15) | In house check: Oct-16 |
| Network Analyzer HP 8753E   | SN: US37390585     | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

|                |                             |                                        |            |
|----------------|-----------------------------|----------------------------------------|------------|
| Calibrated by: | Name: <b>Michael Weber</b>  | Function: <b>Laboratory Technician</b> | Signature: |
| Approved by:   | Name: <b>Kolja Pokorski</b> | Function: <b>Technical Manager</b>     | Signature: |

Issued: April 20, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D2450V2-727\_Apr16

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
C Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

#### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 8 GHz"

#### Additional Documentation:

- DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz   |             |

**Head TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.0 $\pm$ 6 % | 1.83 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

**SAR result with Head TSL**

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 12.8 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 51.0 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.93 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.7 W/kg $\pm$ 16.5 % (k=2) |

**Body TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.7           | 1.95 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 52.7 $\pm$ 6 % | 1.98 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

**SAR result with Body TSL**

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 12.5 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 49.6 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.86 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 23.3 W/kg $\pm$ 16.5 % (k=2) |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 55.3 $\Omega$ + 2.0 j $\Omega$ |
| Return Loss                          | - 25.4 dB                      |

**Antenna Parameters with Body TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.1 $\Omega$ + 4.8 j $\Omega$ |
| Return Loss                          | - 25.9 dB                      |

**General Antenna Parameters and Design**

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.148 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

**Additional EUT Data**

|                 |                  |
|-----------------|------------------|
| Manufactured by | SPEAG            |
| Manufactured on | January 09, 2003 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## DASY5 Validation Report for Head TSL

Date: 19.04.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 727**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.83$  S/m;  $\epsilon_r = 40$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

### DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvP(7.76, 7.76, 7.76); Calibrated: 31.12.2015
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 112.1 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 25.7 W/kg

SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.93 W/kg

Maximum value of SAR (measured) = 20.8 W/kg




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Impedance Measurement Plot for Head TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: **SGS-TW (Auden)**

Certificate No.: **D2600V2-1005\_Jan16**

## CALIBRATION CERTIFICATE

Object: **D2600V2 - SN: 1005**

Calibration procedure(s): **QA CAL-05.v9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 21, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&E critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | US37392783         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Power sensor HP 8481A       | MY41082917         | 07-Oct-15 (No. 217-02222)         | Oct-16                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 01-Apr-15 (No. 217-02131)         | Mar-16                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 01-Apr-15 (No. 217-02134)         | Mar-16                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-Dec-15 (No. EX3-7349_Dec15)    | Dec-16                 |
| DAE4                        | SN: 801            | 30-Dec-15 (No. DAE4-801_Dec15)    | Dec-16                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| RF generator R&S SMT-06     | 100972             | 15-Jun-15 (in house check Jun-15) | In house check: Jun-16 |
| Network Analyzer HP 8753E   | US37390585 54206   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Leif Klysner** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Technical Manager

Signature

Issued: January 26, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No.: **D2600V2-1005\_Jan16**

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488

[www.tw.sgs.com](http://www.tw.sgs.com)

Member of SGS Group

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zengghausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

#### Glossary:

TSL tissue simulating liquid  
ConvF sensitivity in TSL / NORM x,y,z  
N/A not applicable or not measured

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865684, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Additional Documentation:

- DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.8     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2600 MHz $\pm$ 1 MHz   |             |

**Head TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.0           | 1.96 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 37.3 $\pm$ 6 % | 2.04 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ---            | ---                  |

**SAR result with Head TSL**

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 14.2 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 55.2 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 6.29 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 24.7 W/kg $\pm$ 16.5 % (k=2) |

**Body TSL parameters**

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.5           | 2.16 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 51.6 $\pm$ 6 % | 2.22 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ---            | ---                  |

**SAR result with Body TSL**

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 13.7 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 53.9 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 6.10 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 24.2 W/kg $\pm$ 16.5 % (k=2) |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.2 $\Omega$ - 4.2 j $\Omega$ |
| Return Loss                          | - 27.2 dB                      |

**Antenna Parameters with Body TSL**

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 45.6 $\Omega$ - 3.3 j $\Omega$ |
| Return Loss                          | - 24.8 dB                      |

**General Antenna Parameters and Design**

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.154 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

**Additional EUT Data**

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | December 23, 2006 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## DASY5 Validation Report for Head TSL

Date: 21.01.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1005**

Communication System: UID 0 - CW; Frequency: 2600 MHz

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.04$  S/m;  $\epsilon_r = 37.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.49, 7.49, 7.49); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 114.8 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 30.2 W/kg

**SAR(1 g) = 14.2 W/kg; SAR(10 g) = 6.29 W/kg**

Maximum value of SAR (measured) = 24.0 W/kg




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Impedance Measurement Plot for Head TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## DASY5 Validation Report for Body TSL

Date: 21.01.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1005**

Communication System: UID 0 - CW; Frequency: 2600 MHz

Medium parameters used:  $f = 2600 \text{ MHz}$ ;  $\sigma = 2.22 \text{ S/m}$ ;  $\epsilon_r = 51.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.6, 7.6, 7.6); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.12.2015
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.7 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 28.4 W/kg

SAR(1 g) = 13.7 W/kg; SAR(10 g) = 6.1 W/kg

Maximum value of SAR (measured) = 22.8 W/kg




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Impedance Measurement Plot for Body TSL



- End of 1<sup>st</sup> part of report -

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.