



Appendix A. T-coil Measurement Plots

Table of contents
T-coil Measurement Plots of GSM850
T-coil Measurement Plots of GSM1900
T-coil Measurement Plots of UMTS Band II
T-coil Measurement Plots of UMTS Band IV
T-coil Measurement Plots of UMTS Band V

Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-GSM850-190CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 12.63 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, 12.5, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 36.41 dB

ABM1 comp = -11.62 dBA/m

BWC Factor = 0.15 dB

Location: -25, 0, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-GSM850-190CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 12.93 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 49.81 dB

ABM1 comp = 12.16 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-GSM850-190CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 8.64 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 44.28 dB

ABM1 comp = 8.64 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

(1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB



Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.65 dB

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-GSM1900-661CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 12.76 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, 12.5, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 39.14 dB

ABM1 comp = -9.63 dBA/m

BWC Factor = 0.15 dB

Location: -20.8, 0, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-GSM1900-661CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 13.04 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 53.26 dB

ABM1 comp = 12.11 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-GSM1900-661CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-GSM\GPRS\EGPRS-1TS (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 8.53 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 48.88 dB

ABM1 comp = 8.53 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

(1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB



Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.39 dB

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band II-9400CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 9.69 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, 12.5, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 46.22 dB

ABM1 comp = -2.64 dBA/m

BWC Factor = 0.15 dB

Location: -8.3, 4.2, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band II-9400CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0 \text{ S/m}$, $\varepsilon_r = 1$; $\rho = 0 \text{ kg/m}^3$

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), $z = 3.0$
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 10.88 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 58.98 dB

ABM1 comp = 10.88 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band II-9400CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 7.63 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 56.63 dB

ABM1 comp = 7.63 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB



Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.81 dB

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band IV-1413CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 11.39 dBA/m

BWC Factor = 0.15 dB

Location: 16.7, 12.5, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 48.10 dB

ABM1 comp = 3.90 dBA/m

BWC Factor = 0.15 dB

Location: -4.2, 12.5, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band IV-1413CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 10.56 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 59.80 dB

ABM1 comp = 10.56 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band IV-1413CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 9.77 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 58.71 dB

ABM1 comp = 9.77 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

(1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB



Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.54 dB

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band V-4182CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0 \text{ S/m}$, $\varepsilon_r = 1$; $\rho = 0 \text{ kg/m}^3$

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), $z = 3.0$
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 10.04 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, 8.3, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 48.43 dB

ABM1 comp = 0.48 dBA/m

BWC Factor = 0.15 dB

Location: -8.3, 8.3, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band V-4182CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 9.98 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 46.52

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 58.51 dB

ABM1 comp = 9.55 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 20.8, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-MT2-L03-UMTS Band V-4182CH

DUT: MT2-L03; Type: LTE/UMTS Smart Phone; HUAWEI Ascend Mate2; Serial: SAR1

Communication System: UID 0, HW-UMTS-FDD(WCDMA) (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV2 - 1068; ; Calibrated: 2013-12-10
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn852; Calibrated: 2013-11-27
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 9.44 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 58.14 dB

ABM1 comp = 9.44 dBA/m

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

(1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 95.24

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.74 dB

BWC Factor = 10.80 dB

Location: 8.3, 20.8, 3.7 mm

