



EMC Test Report

Product Name: HUAWEI MediaPad 7 Youth2

Model Number: S7-721w

Report No:SYBH(Z-EMC)105042014

FCC ID: QISS7-721W

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
5. The test report is invalid if not marked with "exclusive stamp for the test report".
6. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
9. Normally, the test report is only responsible for the samples that have undergone the test.
10. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.

Applicant: Huawei Technologies Co., Ltd.

Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Date of Receipt Test Item: May.1, 2014

Start Date of Test: May.4, 2014

End Date of Test: May.8, 2014

Test Result: Pass

**Approved By
(Lab Manager)**

2014-05-09
Date

Liuchunlin
Name




Signature

**Operator
(Test Engineer)**

2014-05-09
Date

Haozy He
Name



Signature

Modification Record

No.	Last Report No.	Modification Description
1	NA	First report

TABLE OF CONTENT

1	General Information	6
1.1	EUT Description	6
1.2	Differences Description	7
1.3	Test Site Information	7
1.4	Applied Standards	7
2	Summary of Results.....	8
3	System Configuration during EMC Test.....	9
3.1	Test Mode	9
3.2	Test System Configuration.....	9
3.3	Cables Used during Test.....	10
3.4	Associated Equipment Used during Test.....	10
4	Electromagnetic Interference (EMI).....	11
4.1	Radiated Disturbance 30MHz to 18GHz	11
4.2	Conducted Disturbance 0.15 MHz to 30MHz.....	13
5	Main Test Instruments.....	14
6	System Measurement Uncertainty	15
7	Test Data and Graph.....	16
7.1	Radiated Disturbance	16
7.2	Conducted Disturbance.....	18

1 General Information

1.1 EUT Description

EUT Description	
Product Name	HUAWEI MediaPad 7 Youth2
Model Number	S7-721w
Serials Number	L4Z0114409000023
Working Voltage	5Vdc
TX Frequency	Bluetooth:2402MHz To 2480MHz WIFI:2412MHz To 2462MHz
RX Frequency	Bluetooth:2402MHz To 2480MHz WIFI:2412MHz To 2462MHz GPS:1570MHz To 1580MHz
HW Version	SH1S7721UM
SW Version	S7-721uV100R001C001
EUT Accessory	
Data cable	Data Cable USB A Male to Micro USB Male
Adapter	BRAND: HUAWEI Model: HW-050200U3W Input voltage: 100V-240V ~50-60Hz, 0.5A Output voltage: +5V $\overline{\text{---}}$ 2A S/N: HWHKAACC1801709
Adapter	BRAND: HUAWEI Model: HW-050100U2W Input voltage: 100V-240V ~50-60Hz, 0.5A Output voltage: +5V $\overline{\text{---}}$ 1A S/N: HWHKAGDC0805119
Rechargeable Li-ion	BRAND: HUAWEI Battery Model: HB3G1 Rated capacity: 4000 mAh Nominal Voltage: $\overline{\text{---}}$ +3.7V Charging Voltage: $\overline{\text{---}}$ +4.2V

Remark: The information of the EUT is declared by the manufacturer. Please refer to the specifications or user manual for details.

1.2 Differences Description

The differences between S7-721u ,S7-721w is :

	S7-721u	S7-721w
PCB	the same	the same
WIFI/BT 2.4G	the same	the same
GSM850/1900	support	Not support
WCDMA1900/850	support	Not support

1.3 Test Site Information

Test Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.4 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15:2013, Subpart B

2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode2 Mode3	CLASS B	Pass	Site1
<u>Conducted Emissions</u> ☒ DC Power Port ☒ AC Power Port ☐ Telecommunication Ports	Mode1 Mode2	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the uncertainty of test system. 2, ☒ The item has been tested; ☐ The item has not been tested.				

During the measurement, the environmental conditions complied with the range listed as below.

Item	Required
Ambient temperature	15°C ~ 35°C
Relative humidity	25% ~ 75%
Atmospheric pressure	86kPa ~ 106kPa

3 System Configuration during EMC Test

3.1 Test Mode

The EUT was configured, installed, arranged and operated in a manner consistent with typical application; the following mode(s) were applied during the compliance test.

Test Mode	
Mode 1:	Adapter (charge) + TF Card + earphone + Camera on +wireless service traffic mode
Mode 2:	Adapter (charge) + TF Card + earphone + Camera on +wireless service IDLE mode
Mode 3:	PC (Power supply and USB copy) + TF card + earphone + wireless service IDLE mode

Remark: If there is more than one adapter, each one should be applied throughout the compliance test respectively, however, only the worst case will be recorded in this report.


Traffic Mode:


State of EUT when switched on and with Radio Resource Control (RRC) connection established

IDLE Mode:

State of EUT when switched on but with no Radio Resource Control (RRC) connection

3.2 Test System Configuration





3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB	1	<3m	shielded
Earphone	1	<3m	unshielded

3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated dateline	Cal interval (month)
PC	X200	Lenovo	3108052581	/	/
TF Card	2G	Kingston	1040RE5672k	/	/

4 Electromagnetic Interference (EMI)

4.1 Radiated Disturbance 30MHz to 18GHz

4.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4-2009. The test distance was 3m. The set-up and test methods were according to ANSI C63.4-2009.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; The emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m. The azimuth range of turntable was 0° to 360°. The receiving antenna has two polarizations V and H.

Measurement bandwidth (RBW) for 30MHz to 1000 MHz: 120 kHz;

Measurement bandwidth (RBW) for 1000MHz to 18000 MHz: 1MHz;

EUT was configured in idle mode and the test performed at worst emission state.

4.1.2 Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance (above 1GHz)

4.1.3 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.
Refer to the section 7.1 of this report for test data.

Test Limits (Class B)				
Frequency of Emission (MHz)	Radiated Limit			
	Unit($\mu\text{V}/\text{m}$)		Unit($\text{dB}\mu\text{V}/\text{m}$)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

4.2 Conducted Disturbance 0.15 MHz to 30MHz

4.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm away from LISN. The set-up and test methods were according to ANSI C63.4-2009. Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector. EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.

Measurement bandwidth (RBW) for 150 kHz to 30 MHz: 9 kHz;

The EUT was set in the shielded chamber and operated under nominal conditions.

4.2.2 Test Setup




Figure 3. Test Set-up of conducted disturbance

4.2.3 Test Results

The EUT has met requirements for Conducted disturbance of power lines.

Refer to the section 7.2 of this report for test data.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP (dBμV)	AV (dBμV)
0.15MHz~0.5MHz	66-56	56-46
0.5MHz-5MHz	56	46
5MHz~30MHz	60	50

5 Main Test Instruments

Main Test Equipments						
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated Deadline	Cal interval
RE	EMI Test receiver	ESU26	100387	R&S	Jun.05, 2014	12
	Broadband Antenna	VULB 9163	9163-491	SCHWARZ BECK	Feb.01, 2015	24
	Horn Antenna	HF907	10305	R&S	Feb.01,2015	24
CE	EMI Test receiver	ESCI	101163	R&S	Dec.23, 2014	12
	Artificial Mains Network	ENV216	100382	R&S	Dec.23, 2014	12
	Artificial Mains Network	ENV216	101176	R&S	Dec.23, 2014	12
Software Information						
Test Item	Software Name	Manufacturer		Version		
RE	EMC 32	R&S		V8.40.0		
CE	EMC 32	R&S		V8.40.0		

6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:


System Measurement Uncertainty		
Items		Extended Uncertainty
RE(30MHz-1GHz)	Field strength (dB μ V/m)	U=4.2dB; k=2
RE(1GHz-18GHz)	Field strength (dB μ V/m)	U=5.3dB; k=2
CE	Disturbance Voltage (dB μ V)	U=2.6dB; k=2

7 Test Data and Graph

Only the worst test results were shown

7.1 Radiated Disturbance

7.1.1 30MHz~1GHz




MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV/m	Transducer dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarisation
31.024000	24.7	14.0	40.0	15.3	100.0	174.0	VERTICAL
38.649280	30.5	15.0	40.0	9.5	100.0	142.0	VERTICAL
88.655360	29.8	11.8	43.5	13.7	375.0	274.0	HORIZONTAL
140.445760	22.6	10.3	43.5	20.9	100.0	47.0	VERTICAL
201.739520	18.6	12.9	43.5	24.9	100.0	324.0	VERTICAL
237.541440	22.4	14.0	46.0	23.6	121.0	95.0	HORIZONTAL

Note:

Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)
The reading level is calculated by software which is not shown in the sheet.

7.1.2 1GHz~18GHz



MEASUREMENT RESULT: PK Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBμV/m	dB	dBμV/m	dB	cm	deg	
1596.786000	32.3	-11.5	74.0	41.7	113.0	190.0	VERTICAL
3288.595334	39.0	-4.3	74.0	35.0	115.0	356.0	VERTICA
7507.376666	47.3	5.6	74.0	26.7	180.0	230.0	VERTICA

MEASUREMENT RESULT: AV Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBμV/m	dB	dBμV/m	dB	cm	deg	
2023.269333	19.7	-9.0	54.0	34.3	100.0	255.0	HORIZONTAL
3965.081334	28.2	-2.2	54.0	25.8	100.0	233.0	VERTICAL
9544.032000	36.5	8.7	54.0	17.5	100.0	97.0	HORIZONTAL


Note:

Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

7.2 Conducted Disturbance

7.2.1 AC Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.182354	44.3	9.7	64.4	20.1	N	FLO
0.515718	42.6	9.7	56.0	13.4	L1	FLO
0.698441	38.8	9.7	56.0	17.2	L1	FLO
1.397006	37.5	9.7	56.0	18.5	L1	FLO
3.275715	38.3	9.7	56.0	17.7	N	FLO
4.030009	38.3	9.8	56.0	17.7	L1	FLO

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.186812	32.5	9.7	54.2	21.7	L1	FLO
0.515906	39.1	9.7	46.0	6.9	L1	FLO
0.699885	35.0	9.7	46.0	11.0	L1	FLO
1.401738	32.6	9.7	46.0	13.4	L1	FLO
3.285908	30.9	9.7	46.0	15.1	N	FLO
16.266701	42.5	10.0	50.0	7.5	L1	FLO

Note:

Level= Reading level+ Transd (cable loss + correction factor)

The reading level is calculated by software which is not shown in the sheet.

-----END-----