



Appendix B. SAR Measurement Plots

Table of contents
WiFi 2450 MHz Body

Test Laboratory: HUAWEI SAR/HAC Lab

S8-301w WiFi 802.11b 1CH Back side 0mm

DUT: S8-301w; Type: HUAWEI MediaPad M1 8.0; Serial: SAR2

Communication System: UID 0, WiFi(802.11a/b/g/n) (0); Frequency: 2412 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.967$ S/m; $\epsilon_r = 52.206$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3744; ConvF(6.91, 6.91, 6.91); Calibrated: 2013-7-26;
- Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn851; Calibrated: 2013-7-31
- Phantom: SAM3; Type: SAM; Serial: TP-1597
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Configuration/Body/Area Scan (10x13x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.08 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.558 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 2.62 W/kg

SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.376 W/kg

Maximum value of SAR (measured) = 1.51 W/kg



Test Laboratory: HUAWEI SAR/HAC Lab

S8-301w WiFi 802.11b 1CH Back side 0mm-repeated

DUT: S8-301w; Type: HUAWEI MediaPad M1 8.0; Serial: SAR2

Communication System: UID 0, WiFi(802.11a/b/g/n) (0); Frequency: 2412 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.967$ S/m; $\epsilon_r = 52.206$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3744; ConvF(6.91, 6.91, 6.91); Calibrated: 2013-7-26;
- Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn851; Calibrated: 2013-7-31
- Phantom: SAM3; Type: SAM; Serial: TP-1597
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Configuration/Body/Area Scan (10x13x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 1.19 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.109 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 2.67 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.383 W/kg

Maximum value of SAR (measured) = 1.55 W/kg

