
Date: 2015.06.30.

1.1.1 GSM850 Head Right Cheek Mid

Medium: HSL900

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.89$ mho/m; $\epsilon_r = 41.478$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(6.55, 6.55, 6.55); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

GSM 850_Right Cheek/Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 6.139 V/m; Power Drift = -0.02 dB

Maximum value of SAR (interpolated) = 0.245 W/kg


GSM 850_Right Cheek/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.139 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.290 mW/g

SAR(1 g) = 0.233 mW/g; SAR(10 g) = 0.179 mW/g

Maximum value of SAR (measured) = 0.245 W/kg



0 dB = 0.245 W/kg = -12.21 dB W/kg

Date: 2015.06.30.

1.1.2 GPRS850 Body Back Side Mid 10mm

Medium: MSL900

Communication System: GPRS FDD(TDMA,GSMK); Communication System Band: GSM 850 (824.0 - 849.0 MHz); Frequency: 836.6 MHz;Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 1.01$ mho/m; $\epsilon_r = 55.858$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(6.2, 6.2, 6.2); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

GPRS 850_Facedown/Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 21.359 V/m; Power Drift = -0.02 dB

Maximum value of SAR (interpolated) = 0.456 W/kg


GPRS 850_Facedown/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm,
dz=5mm

Reference Value = 21.359 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.533 mW/g

SAR(1 g) = 0.437 mW/g; SAR(10 g) = 0.342 mW/g

Maximum value of SAR (measured) = 0.453 W/kg



0 dB = 0.456 W/kg = -6.83 dB W/kg

Date: 2015.06.30.

1.1.3 GSM850 Body Back Side Mid 2# 15mm

Medium: MSL900

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.96$ mho/m; $\epsilon_r = 55.858$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(6.2, 6.2, 6.2); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

GSM 850_Faceup 15mm/Mid 2#/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 19.658 V/m; Power Drift = -0.07 dB

Maximum value of SAR (interpolated) = 0.362 W/kg


GSM 850_Faceup 15mm/Mid 2#/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.658 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.424 mW/g

SAR(1 g) = 0.346 mW/g; SAR(10 g) = 0.269 mW/g

Maximum value of SAR (measured) = 0.361 W/kg



0 dB = 0.362 W/kg = -8.83 dB W/kg

Date: 2015.07.01.

1.1.4 GSM1900 Head Left cheek Mid

Medium: HSL1900

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.74$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: EX3DV4 - SN3881; ConvF(8.09, 8.09, 8.09); Calibrated: 2014.07.22.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

1900_Left GSM Head/1900 GSM Cheek-Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.276 W/kg

1900_Left GSM Head/1900 GSM Cheek-Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.873 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.458 mW/g

SAR(1 g) = 0.252 mW/g; SAR(10 g) = 0.139 mW/g

Maximum value of SAR (measured) = 0.273 W/kg



0 dB = 0.276 W/kg = -11.17 dB W/kg

Date: 2015.07.01.

1.1.5 GPRS1900 Body Back Side Mid 10mm

Medium: MSL1900

Communication System: GPRS FDD(TDMA,GSMK); Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Frequency: 1850.2 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.24$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:Probe: EX3DV4 - SN3881; ConvF(8.25, 8.25, 8.25); Calibrated: 2014.07.22.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

1900_GPRS/GPRS1900 Facedown-Mid/Area Scan (51x51x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.290 W/kg


1900_GPRS/GPRS1900 Facedown-Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.174 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.575 mW/g

SAR(1 g) = 0.303 mW/g; SAR(10 g) = 0.150 mW/g

Maximum value of SAR (measured) = 0.326 W/kg



0 dB = 0.290 W/kg = -10.76 dB W/kg

Date: 2015.07.01.

1.1.6 GSM1900 Body Back Side Mid 15mm

Medium: MSL1900

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.24$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: EX3DV4 - SN3881; ConvF(8.25, 8.25, 8.25); Calibrated: 2014.07.22.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

GSM 1900 Facedown-Mid 15mm/Area Scan (51x51x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.131 W/kg


GSM 1900 Facedown-Mid 15mm/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.167 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.217 mW/g

SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.070 mW/g

Maximum value of SAR (measured) = 0.138 W/kg



0 dB = 0.131 W/kg = -17.68 dB W/kg

Date: 2015.07.01.

1.1.7 WCDMA Head BAND2 Left Cheek Mid #2

Medium: HSL1900

Communication System: UMTS-FDD; Communication System Band: Band 2, UTRA/FDD (1850.0 - 1910.0 MHz); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.74$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: EX3DV4 - SN3881; ConvF(8.09, 8.09, 8.09); Calibrated: 2014.07.22.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 2 _left head cheek/Mid with battery/Area Scan (51x51x1): Interpolated grid:

dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.619 W/kg

UMTS Band 2 _left head cheek/Mid with battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.777 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.964 mW/g

SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.300 mW/g

Maximum value of SAR (measured) = 0.581 W/kg



0 dB = 0.619 W/kg = -4.17 dB W/kg

Date: 2015.07.01.

1.1.8 WCDMA Body BAND2 Back Side Mid 10mm

Medium: MSL1900

Communication System: UMTS-FDD; Communication System Band: Band 2, UTRA/FDD (1850.0 - 1910.0 MHz); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.14$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: EX3DV4 - SN3881; ConvF(8.25, 8.25, 8.25); Calibrated: 2014.07.22.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 2_Back/Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 9.307 V/m; Power Drift = 0.16 dB


UMTS Band 2_Back/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.307 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.747 mW/g

SAR(1 g) = 0.393 mW/g; SAR(10 g) = 0.192 mW/g

Maximum value of SAR (measured) = 0.405 W/kg



0 dB = 0.380 W/kg = -8.39 dB W/kg

Date: 2015.07.01.

1.1.9 WCDMA Body BAND2 Back Side Mid 15mm

Medium: MSL1900

Communication System: UMTS-FDD; Communication System Band: Band 2, UTRA/FDD (1850.0 - 1910.0 MHz); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.14$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: EX3DV4 - SN3881; ConvF(8.25, 8.25, 8.25); Calibrated: 2014.07.22.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 2_Back 15mm/Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 9.307 V/m; Power Drift = -0.05 dB


UMTS Band 2_Back 15mm/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.307 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.555 mW/g

SAR(1 g) = 0.322 mW/g; SAR(10 g) = 0.176 mW/g

Maximum value of SAR (measured) = 0.354 W/kg



0 dB = 0.316 W/kg = -10.00 dB W/kg

Date: 2015.07.01.

1.1.10 WCDMA BAND4 Head Left Cheek Mid 2#

Medium: HSL1800

Communication System: UMTS-FDD; Communication System Band: Band4; Frequency: 1740 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1740$ MHz; $\sigma = 1.315$ mho/m; $\epsilon_r = 40.374$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(5.2, 5.2, 5.2); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 4_left head cheek/Mid with battery/Area Scan (51x51x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.430 W/kg


UMTS Band 4_left head cheek/Mid with battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.531 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.661 mW/g

SAR(1 g) = 0.385 mW/g; SAR(10 g) = 0.221 mW/g

Maximum value of SAR (measured) = 0.418 W/kg



0 dB = 0.430 W/kg = -7.33 dB W/kg

Date: 2015.07.01.

1.1.11 WCDMA BAND4 Body Bottom Side Mid 10mm


Medium: MSL1800

Communication System: UMTS-FDD; Communication System Band: Band4; Frequency: 1740 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1740$ MHz; $\sigma = 1.412$ mho/m; $\epsilon_r = 51.596$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(4.88, 4.88, 4.88); Calibrated: 2014.12.19.;
Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 4_body Faceup/Mid 10mm Bottom/Area Scan (61x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.731 W/kg

UMTS Band 4_body Faceup/Mid 10mm Bottom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm
Reference Value = 21.588 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 1.005 mW/g
SAR(1 g) = 0.578 mW/g; SAR(10 g) = 0.307 mW/g

Maximum value of SAR (measured) = 0.644 W/kg



0 dB = 0.731 W/kg = -2.72 dB W/kg

Date: 2015.07.01.

1.1.12 WCDMA BAND4 Body Front Side Mid 15mm


Medium: MSL1800

Communication System: UMTS-FDD; Communication System Band: Band4; Frequency: 1740 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1740$ MHz; $\sigma = 1.412$ mho/m; $\epsilon_r = 51.596$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(4.88, 4.88, 4.88); Calibrated: 2014.12.19.;
Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 4_body Facedown/Mid/Area Scan (61x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.600 W/kg

UMTS Band 4_body Facedown/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm
Reference Value = 11.597 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.993 mW/g
SAR(1 g) = 0.485 mW/g; SAR(10 g) = 0.311 mW/g

Maximum value of SAR (measured) = 0.646 W/kg



0 dB = 0.600 W/kg = -4.44 dB W/kg

Date: 2015.06.30.

1.1.13 WCDMA Head BAND5 Right Cheek Mid


Medium: HSL900

Communication System: UMTS-FDD; Communication System Band: Band 5, UTRA/FDD (824.0 - 849.0 MHz); Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.89$ mho/m; $\epsilon_r = 41.478$; $\rho = 1000$ kg/m³
Phantom section: Right Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(6.55, 6.55, 6.55); Calibrated: 2014.12.19.;
Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 5_right head cheek/Mid/Area Scan (51x51x1): Interpolated grid: $dx=1.500$ mm,
 $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.207 W/kg

UMTS Band 5_right head cheek/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm,
 $dy=8$ mm, $dz=5$ mm
Reference Value = 15.079 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.245 mW/g
SAR(1 g) = 0.198 mW/g; SAR(10 g) = 0.152 mW/g

Maximum value of SAR (measured) = 0.207 W/kg



0 dB = 0.207 W/kg = -13.70 dB W/kg

Date: 2015.06.30.

1.1.14 WCDMA Body BAND5 Back Side Mid 10mm

Medium: MSL900

Communication System: UMTS-FDD; Communication System Band: Band 5, UTRA/FDD (824.0 - 849.0 MHz); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.96$ mho/m; $\epsilon_r = 55.858$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(6.2, 6.2, 6.2); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 5_body Back/Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.372 W/kg


UMTS Band 5_body Back/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.079 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.424 mW/g

SAR(1 g) = 0.353 mW/g; SAR(10 g) = 0.280 mW/g

Maximum value of SAR (measured) = 0.367 W/kg



0 dB = 0.372 W/kg = -8.60 dB W/kg

Date: 2015.06.30.

1.1.15 WCDMA Body BAND5 Back Side Mid 15mm

Medium: MSL900

Communication System: UMTS-FDD; Communication System Band: Band 5, UTRA/FDD (824.0 - 849.0 MHz); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.96$ mho/m; $\epsilon_r = 55.858$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(6.2, 6.2, 6.2); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

UMTS Band 5_body Back 15mm/Mid/Area Scan (61x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.319 W/kg


UMTS Band 5_body Back 15mm/Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 15.079 V/m; Power Drift = - 0.04 dB

Peak SAR (extrapolated) = 0.370 mW/g

SAR(1 g) = 0.301 mW/g; SAR(10 g) = 0.232 mW/g

Maximum value of SAR (measured) = 0.314 W/kg



0 dB = 0.319 W/kg = -9.92 dB W/kg

Date: 2015.07.02.

1.1.16 WiFi Head Left Cheek Mid

Medium: HSL2450

Communication System: 802.11b WiFi 2.4GHz(DSSS,11Mbps); Communication System Band: 802.11b; Frequency: 2437 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.829$ mho/m; $\epsilon_r = 38.021$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration: Probe: ES3DV3 - SN3203; ConvF(4.55, 4.55, 4.55); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

802.11b-Left Head/left Cheek-Mid/Area Scan (61x81x1): Interpolated grid: dx=1.500 mm,

dy=1.500 mm

Maximum value of SAR (interpolated) = 0.401 W/kg

802.11b-Left Head/left Cheek-Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.464 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.938 mW/g

SAR(1 g) = 0.336 mW/g; SAR(10 g) = 0.150 mW/g

Maximum value of SAR (measured) = 0.358 W/kg



0 dB = 0.401 W/kg = -7.95 dB W/kg

Date: 2015.07.02.

Report No.: WT158002966

Page 29 of 33

1.1.17 WiFi Body Front Side Mid 10mm

Medium: MSL2450

Communication System: 802.11b WiFi 2.4GHz(DSSS,11Mbps); Communication System Band:

802.11b; Frequency: 2442 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2442$ MHz; $\sigma = 2.011$ mho/m; $\epsilon_r = 50.719$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:Probe: ES3DV3 - SN3203; ConvF(4.47, 4.47, 4.47); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

802.11b-10mm/Faceup-Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 5.680 V/m; Power Drift = -0.06 dB

Maximum value of SAR (interpolated) = 0.127 W/kg


802.11b-10mm/Faceup-Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.680 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.211 mW/g

SAR(1 g) = 0.106 mW/g; SAR(10 g) = 0.056 mW/g

Maximum value of SAR (measured) = 0.113 W/kg



0 dB = 0.127 W/kg = -17.95 dB W/kg

Date: 2015.07.02.

Report No.: WT158002966

Page 31 of 33

1.1.18 WiFi Body Front Side Mid 15mm

Medium: MSL2450

Communication System: 802.11b WiFi 2.4GHz(DSSS,11Mbps); Communication System Band:

802.11b; Frequency: 2442 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2442$ MHz; $\sigma = 2.011$ mho/m; $\epsilon_r = 50.719$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:Probe: ES3DV3 - SN3203; ConvF(4.47, 4.47, 4.47); Calibrated: 2014.12.19.;

Electronics: DAE4 Sn876; Calibrated: 2015.03.09.

802.11b-15mm/Facedup-Mid/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 4.023 V/m; Power Drift = 0.04 dB

Maximum value of SAR (interpolated) = 0.0534 W/kg


802.11b-15mm/Facedup-Mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.023 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.087 mW/g

SAR(1 g) = 0.047 mW/g; SAR(10 g) = 0.025 mW/g

Maximum value of SAR (measured) = 0.0512 W/kg



0 dB = 0.0534 W/kg = -25.45 dB W/kg