



SAR TEST REPORT

No. I15Z42860-SEM01

For

Huawei Technologies Co.,Ltd

Smart Phone

Model name: HUAWEI TAG-L13

With

Hardware Version: Ver.A

Software Version: TAG-L13C464B006_A

FCC ID: QISTAG-L13

Issued Date: 2016-01-19



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT
No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191
Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504
Email:cttl_terminals@catr.cn, website:www.chinattl.com



REPORT HISTORY

Report Number	Revision	Issue Date	Description
I15Z42860-SEM01	Rev.0	2016-01-19	Initial creation of test report

TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 TESTING LOCATION	5
1.2 TESTING ENVIRONMENT.....	5
1.3 PROJECT DATA	5
1.4 SIGNATURE.....	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION	8
3.1 APPLICANT INFORMATION	8
3.2 MANUFACTURER INFORMATION	8
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	9
4.1 ABOUT EUT	9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	10
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	10
5 TEST METHODOLOGY	11
5.1 APPLICABLE LIMIT REGULATIONS	11
5.2 APPLICABLE MEASUREMENT STANDARDS.....	11
6 SPECIFIC ABSORPTION RATE (SAR).....	12
6.1 INTRODUCTION.....	12
6.2 SAR DEFINITION	12
7 TISSUE SIMULATING LIQUIDS	13
7.1 TARGETS FOR TISSUE SIMULATING LIQUID	13
7.2 DIELECTRIC PERFORMANCE	13
8 SYSTEM VERIFICATION	19
8.1 SYSTEM SETUP.....	19
8.2 SYSTEM VERIFICATION.....	20
9 MEASUREMENT PROCEDURES	21
9.1 TESTS TO BE PERFORMED	21
9.2 GENERAL MEASUREMENT PROCEDURE.....	23
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR	24
9.4 SAR MEASUREMENT FOR LTE.....	26
9.5 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR	26
9.6 POWER DRIFT.....	27
10 AREA SCAN BASED 1-G SAR.....	28
10.1 REQUIREMENT OF KDB.....	28
10.2 FAST SAR ALGORITHMS	28
11 CONDUCTED OUTPUT POWER.....	29

11.1 MANUFACTURING TOLERANCE	29
11.3 GSM MEASUREMENT RESULT	35
11.4 WCDMA MEASUREMENT RESULT	36
11.5 LTE MEASUREMENT RESULT	38
11.6 WI-FI AND BT MEASUREMENT RESULT	52
12 SIMULTANEOUS TX SAR CONSIDERATIONS	53
12.1 INTRODUCTION	53
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES	53
12.3 SAR MEASUREMENT POSITIONS	53
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	53
13 EVALUATION OF SIMULTANEOUS	55
14 SAR TEST RESULT	56
14.1 SAR RESULTS FOR FAST SAR	57
14.2 SAR RESULTS FOR STANDARD PROCEDURE	67
14.3 WLAN EVALUATION	72
15 SAR MEASUREMENT VARIABILITY	75
16 MEASUREMENT UNCERTAINTY	77
16.1 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHz~3GHz)	77
16.2 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3~6GHz)	78
16.3 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (300MHz~3GHz)	79
16.4 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (3~6GHz)	80
17 MAIN TEST INSTRUMENTS	82
ANNEX A GRAPH RESULTS	83
ANNEX B SYSTEM VERIFICATION RESULTS	131
ANNEX C SAR MEASUREMENT SETUP	142
ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	148
ANNEX E EQUIVALENT MEDIA RECIPES	151
ANNEX F SYSTEM VALIDATION	152
ANNEX G PROBE CALIBRATION CERTIFICATE	153
ANNEX H DIPOLE CALIBRATION CERTIFICATE	164
ANNEX I ACCREDITATION CERTIFICATE	204

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25 °C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg


1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	December 25, 2015
Testing End Date:	December 29, 2015

1.4 Signature



Lin Xiaojun
(Prepared this test report)



Qi Dianyuan
(Reviewed this test report)



Xiao Li
Deputy Director of the laboratory
(Approved this test report)

2 Statement of Compliance

The maximum results of SAR found during testing for Huawei Technologies Co.,Ltd Smart Phone HUAWEI TAG-L13 are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g (W/Kg)	Equipment Class
Head (Separation Distance 0mm)	GSM 850	0.28	PCE
	PCS 1900	0.17	
	UMTS FDD 5	0.44	
	UMTS FDD 4	0.51	
	UMTS FDD 2	0.26	
	LTE Band 2	0.26	
	LTE Band 4	0.51	
	LTE Band 5	0.38	
	LTE Band 7	0.30	
	LTE Band 12	0.19	
	LTE Band 17	0.20	
	WLAN 2.4 GHz	1.18	DTS
Hotspot (Separation Distance 10mm)	GSM 850	0.88	PCE
	PCS 1900	1.46	
	UMTS FDD 5	0.68	
	UMTS FDD 4	1.30	
	UMTS FDD 2	1.44	
	LTE Band 2	1.34	
	LTE Band 4	0.88	
	LTE Band 5	0.57	
	LTE Band 7	1.05	
	LTE Band 12	0.38	
	LTE Band 17	0.29	
	WLAN 2.4 GHz	0.33	DTS
Body-worn (Separation Distance 10mm)	GSM 850	0.88	PCE
	PCS 1900	1.00	
	UMTS FDD 5	0.68	
	UMTS FDD 4	1.05	
	UMTS FDD 2	1.10	
	LTE Band 2	0.98	
	LTE Band 4	0.88	
	LTE Band 5	0.57	
	LTE Band 7	0.51	
	LTE Band 12	0.38	
	LTE Band 17	0.29	
	WLAN 2.4 GHz	0.26	DTS

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm and speech between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The highest reported SAR value is obtained at the case of **(Table 2.1)**, and the values are: **1.46W/kg (1g)**.

Table 2.2: The sum of reported SAR values for main antenna and WLAN

	Position	Main antenna	WLAN	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek	0.41	1.18	1.59
	Right hand, Touch cheek	0.51	0.85	1.36
Maximum reported SAR value for Body	Rear 10mm	1.10	0.26	1.36
	Bottom 10mm	1.46	/	1.46
	Top 10mm	/	0.33	0.33

Table 2.3: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.51	0.13	0.64
Highest reported SAR value for Body	Rear 10mm	1.10	0.07	1.17
	Bottom 10mm	1.46	/	1.46

BT* - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **1.59 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

3 Client Information

3.1 Applicant Information

Company Name:	Huawei Technologies Co.,Ltd
Address /Post:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District Shenzhen China
City:	Shenzhen
Country:	China
Contact Person:	Zhang Xinghai
Email:	zhangxinghai@huawei.com
Telephone:	0086-0755-28970299
Fax	0086-0755-89650226

3.2 Manufacturer Information

Company Name:	Huawei Technologies Co.,Ltd
Address /Post:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District Shenzhen China
City:	Shenzhen
Country:	China
Contact Person:	Zhang Xinghai
Email:	zhangxinghai@huawei.com
Telephone:	0086-0755-28970299
Fax	0086-0755-89650226

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	Smart Phone
Model name:	HUAWEI TAG-L13
Operating mode(s):	GSM 850/1900, WCDMA 850/1700/1900 BT, Wi-Fi, LTE Band 2/4/5/7/17
Tested Tx Frequency:	825 – 848.8 MHz (GSM 850)
	1850.2 – 1910 MHz (GSM 1900)
	826.4–846.6 MHz (WCDMA850 Band V)
	1712.4 – 1752.6 MHz (WCDMA 1700 Band IV)
	1852.4–1907.6 MHz (WCDMA1900 Band II)
	1860 – 1900 MHz (LTE Band 2)
	1720 – 1745 MHz (LTE Band 4)
	824.7 – 848.3 MHz (LTE Band 5)
	2510-2560 MHz(LTE Band 7)
	704 – 711 MHz (LTE Band 12)
	709 – 711 MHz (LTE Band 17)
	2412 – 2462 MHz (Wi-Fi 2.4G)
	2402 – 2480 MHz (Bluetooth)
Tested Rx Frequency:	869.2 – 891.8 MHz (GSM 850)
	1930.2 – 1989.8 MHz (GSM 1900)
	871.4 – 891.6 MHz (WCDMA850 Band V)
	2112.4 – 2152.6 MHz (WCDMA 1700 Band IV)
	1932.4 –1987.6 MHz (WCDMA1900 Band II)
	1940 – 1980 MHz (LTE Band 2)
	2120 – 2145 MHz (LTE Band 4)
	869.7 – 893.3 MHz (LTE Band 5)
	2630 – 2680(LTE Band 7)
	734 – 741 MHz (LTE Band 12)
	739 – 741 MHz (LTE Band 17)
	2412 – 2462 MHz (Wi-Fi 2.4G)
	2402 – 2480 MHz (Bluetooth)
GPRS/EGPRS Multislot Class:	12
GPRS capability Class:	B
WCDMA Category	HSDPA:10
	HSUPA:7
	HSPA+:14
	DC-HSDPA:24
Release Version	GSM: R5
	GPRS: R5
	UMTS: Rel 8

Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Hotspot mode:	Support simultaneous transmission of hotspot and voice(or data)

4.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW	SW Version
EUT1	868881020008151	Ver.A	TAG-L13C464B006_A
EUT2	868881020008169	Ver.A	TAG-L13C464B006_A
EUT3	868881020008177	Ver.A	TAG-L13C464B006_A
EUT4	868881020008318	Ver.A	TAG-L13C464B006_A
EUT5	868881020000125	Ver.A	TAG-L13C464B006_A
EUT6	868881020008862	Ver.A	TAG-L13C464B006_A

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1&2&3&4 and conducted power with the EUT5&6.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	HB3742A0EZC+	/	Sunwoda electronic Co., Ltd.
AE2	Battery	HB3742A0EZC+	/	Scud (Fujian) Electronics Co., Ltd.

*AE ID: is used to identify the test sample in the lab internally.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2013: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

KDB447498 D01: General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v03r01: SAR Measurement Procedures for 3G Devices

KDB941225 D05 SAR for LTE Devices v02r05: SAR Evaluation Considerations for LTE Devices

KDB941225 D06 Hotspot Mode SAR v02r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB865664 D02 RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid


Frequency(MHz)	Liquid Type	Conductivity(σ)	$\pm 5\%$ Range	Permittivity(ϵ)	$\pm 5\%$ Range
750	Head	0.89	0.85~0.93	41.94	39.8~44.0
750	Body	0.96	0.91~1.01	55.5	52.7~58.3
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1750	Head	1.37	1.30~1.44	40.08	38.1~42.1
1750	Body	1.49	1.42~1.56	53.4	50.7~56.1
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3

7.2 Dielectric Performance


Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ϵ	Drift (%)	Conductivity σ (S/m)	Drift (%)
2015-12-25	Head	750 MHz	43.08	2.72	0.912	2.47
	Body	750 MHz	56.98	2.67	0.946	-1.46
2015-12-26	Head	835 MHz	41.12	-0.92	0.921	2.33
	Body	835 MHz	56.23	1.87	0.972	0.21
2015-12-27	Head	1750 MHz	39.53	-1.37	1.331	-2.85
	Body	1750 MHz	52.7	-1.31	1.472	-1.21
2015-12-28	Head	1900 MHz	39.78	-0.55	1.427	1.93
	Body	1900 MHz	54.05	1.41	1.55	1.97
2015-12-29	Head	2450 MHz	38.01	-3.04	1.822	1.22
	Body	2450 MHz	51.63	-2.03	1.974	1.23


Note: The liquid temperature is 22.0°C




Picture 7-1: Liquid depth in the Head Phantom (750 MHz)



Picture 7-2: Liquid depth in the Flat Phantom (750 MHz)




Picture 7-3: Liquid depth in the Head Phantom (835 MHz)




Picture 7-4: Liquid depth in the Flat Phantom (835 MHz)



Picture 7-5: Liquid depth in the Head Phantom (1750 MHz)



Picture 7-6 Liquid depth in the Flat Phantom (1750MHz)



Picture 7-7: Liquid depth in the Head Phantom (1900 MHz)



Picture 7-8 Liquid depth in the Flat Phantom (1900MHz)



Picture 7-9 Liquid depth in the Head Phantom (2450MHz)




Picture 7-10 Liquid depth in the Flat Phantom (2450MHz)

8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2015-12-25	750 MHz	5.36	8.2	5.40	8.28	0.75%	0.98%
2015-12-26	835 MHz	5.86	9.01	6.00	9.24	2.39%	2.55%
2015-12-27	1750 MHz	19.9	36.9	19.56	36.44	-1.71%	-1.25%
2015-12-28	1900 MHz	21.5	40.7	21.96	41.64	2.14%	2.31%
2015-12-29	2450 MHz	24.5	52.5	24.48	52.44	-0.08%	-0.11%

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2015-12-25	750 MHz	5.68	8.64	5.80	8.84	2.11%	2.31%
2015-12-26	835 MHz	6.12	9.29	6.20	9.36	1.31%	0.75%
2015-12-27	1750 MHz	20.3	37.4	20.08	37.40	-1.08%	0.00%
2015-12-28	1900 MHz	21.7	40.4	22.04	41.44	1.57%	2.57%
2015-12-29	2450 MHz	24.4	52.1	23.92	50.76	-1.97%	-2.57%

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1 Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH_n), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	3.0	2.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.0	0.0	21	81

For Release 7

SAR is required for Rel. 7 HSPA+ when SAR is required for Rel. 6 HSPA; otherwise, the 3G SAR test reduction procedure is applied to (uplink) HSPA+ with 12.2 kbps RMC as the primary mode.³⁶ Power is measured for HSPA+ that supports uplink 16 QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.



For Release 8

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

3G SAR Test Reduction Procedure

When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest *reported* SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

9.4 SAR Measurement for LTE

SAR tests for LTE are performed with a base station simulator, Rohde & Schwarz CMW500. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the CMW 500.

It is performed for conducted power and SAR based on the KDB941225 D05.

SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

9.5 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.6 Power Drift

To control the output power stability during the SAR test, DASY5 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in section 14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

11.1 Manufacturing tolerance

Table 11.1: GSM Speech

GSM 850			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	31.5	31.5	31.5
Tune-up (dBm)	32.5	32.5	32.5
GSM 1900			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	28.7	28.7	28.7
Tune-up (dBm)	29.7	29.7	29.7

Table 11.2: GPRS and EGPRS

GSM 850 GPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	31.5	31.5	31.5
	Tune-up (dBm)	32.5	32.5	32.5
2 Txslots	Target (dBm)	30.5	30.5	30.5
	Tune-up (dBm)	31.5	31.5	31.5
3 Txslots	Target (dBm)	28.5	28.5	28.5
	Tune-up (dBm)	29.5	29.5	29.5
4 Txslots	Target (dBm)	27.5	27.5	27.5
	Tune-up (dBm)	28.5	28.5	28.5
GSM 850 EGPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	31.5	31.5	31.5
	Tune-up (dBm)	32.5	32.5	32.5
2 Txslots	Target (dBm)	30.5	30.5	30.5
	Tune-up (dBm)	31.5	31.5	31.5
3 Txslots	Target (dBm)	28.5	28.5	28.5
	Tune-up (dBm)	29.5	29.5	29.5
4 Txslots	Target (dBm)	27.5	27.5	27.5
	Tune-up (dBm)	28.5	28.5	28.5
GSM 850 EGPRS (8PSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	26	26	26
	Tune-up (dBm)	27	27	27
2 Txslots	Target (dBm)	25	25	25
	Tune-up (dBm)	26	26	26
3 Txslots	Target (dBm)	23	23	23
	Tune-up (dBm)	24	24	24

4 Txslots	Target (dBm)	22	22	22
	Tune-up (dBm)	23	23	23
GSM 1900 GPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	28.7	28.7	28.7
	Tune-up (dBm)	29.7	29.7	29.7
2 Txslots	Target (dBm)	26.7	26.7	26.7
	Tune-up (dBm)	27.7	27.7	27.7
3 Txslots	Target (dBm)	24.7	24.7	24.7
	Tune-up (dBm)	25.7	25.7	25.7
4 Txslots	Target (dBm)	22.7	22.7	22.7
	Tune-up (dBm)	23.7	23.7	23.7
GSM 1900 EGPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	28.7	28.7	28.7
	Tune-up (dBm)	29.7	29.7	29.7
2 Txslots	Target (dBm)	26.7	26.7	26.7
	Tune-up (dBm)	27.7	27.7	27.7
3 Txslots	Target (dBm)	24.7	24.7	24.7
	Tune-up (dBm)	25.7	25.7	25.7
4 Txslots	Target (dBm)	22.7	22.7	22.7
	Tune-up (dBm)	23.7	23.7	23.7
GSM 1900 GPRS (8PSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	24.5	24.5	24.5
	Tune-up (dBm)	25.5	25.5	25.5
2 Txslots	Target (dBm)	23.5	23.5	23.5
	Tune-up (dBm)	24.5	24.5	24.5
3 Txslots	Target (dBm)	21.5	21.5	21.5
	Tune-up (dBm)	22.5	22.5	22.5
4 Txslots	Target (dBm)	20.5	20.5	20.5
	Tune-up (dBm)	21.5	21.5	21.5

Table 11.3: WCDMA

WCDMA 850 CS			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	23.5	23.5	23.5
Tune-up (dBm)	24.5	24.5	24.5
HSDPA (sub-test 1~4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	22.5	22.5	22.5
Tune-up (dBm)	23.5	23.5	23.5

HSUPA (sub-test 1/2)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	20.5	20.5	20.5
Tune-up (dBm)	21.5	21.5	21.5
HSUPA (sub-test 3)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21.5	21.5	21.5
Tune-up (dBm)	22.5	22.5	22.5
HSUPA (sub-test 4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	20	20	20
Tune-up (dBm)	21	21	21
HSUPA (sub-test 5)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	22.5	22.5	22.5
Tune-up (dBm)	23.5	23.5	23.5
DC-HSDPA (sub-test 1~2)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21.5	21.5	21.5
Tune-up (dBm)	22.5	22.5	22.5
DC-HSDPA (sub-test 3~4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up (dBm)	22	22	22
HSPA+			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up (dBm)	22	22	22
WCDMA 1700 CS			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	23	23	23
Tune-up (dBm)	24	24	24
HSDPA (sub-test 1~4)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	21.5	21.5	21.5
Tune-up (dBm)	22.5	22.5	22.5
HSUPA (sub-test 1/2)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	20	20	20
Tune-up (dBm)	21	21	21
HSUPA (sub-test 3)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	21	21	21

Tune-up (dBm)	22	22	22
HSUPA (sub-test 4)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	19.5	19.5	19.5
Tune-up (dBm)	20.5	20.5	20.5
HSUPA (sub-test 5)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	21.5	21.5	21.5
Tune-up (dBm)	22.5	22.5	22.5
DC-HSDPA (sub-test 1~2)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21.5	21.5	21.5
Tune-up (dBm)	22.5	22.5	22.5
DC-HSDPA (sub-test 3~4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up (dBm)	22	22	22
HSPA+			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up (dBm)	22	22	22
WCDMA 1900 CS			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22.3	22.3	22.3
Tune-up (dBm)	23.3	23.3	23.3
HSDPA (sub-test 1~4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22	22	22
Tune-up (dBm)	23	23	23
HSUPA (sub-test 1/2)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	20	20	20
Tune-up (dBm)	21	21	21
HSUPA (sub-test 3)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	21	21	21
Tune-up (dBm)	22	22	22
HSUPA (sub-test 4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	19.5	19.5	19.5
Tune-up (dBm)	20.5	20.5	20.5
HSUPA (sub-test 5)			
Channel	Channel 9538	Channel 9400	Channel 9262

Target (dBm)	21.5	21.5	21.5
Tune-up (dBm)	22.5	22.5	22.5
DC-HSDPA (sub-test 1~4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22	22	22
Tune-up (dBm)	23	23	23
HSPA+			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up (dBm)	22	22	22

Table 11.4: LTE

Mode	Target (dBm)	Tune-up (dBm)
LTE Band 2	23	24
LTE Band 4	22.5	23.5
LTE Band 5	22.5	23.5
LTE Band 7	22	23
LTE Band 12	22.5	23.5
LTE Band 17	22.5	23.5

LTE MPR will follow up 3GPP setting as below:

Modulation	Channel bandwidth / Transmission bandwidth (NRB)						MPR (dB)
	1.4MHz	3.0MHz	5MHz	10MHz	15MHz	20MHz	
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	0
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Table 11.5: Bluetooth

GFSK			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4	3	4
Tune-up (dBm)	5	4	5

Table 11.6: WiFi

802.11b

Channel\rate	1Mbps		2Mbps		5.5Mbps		11Mbps	
	dBm	±	dBm	±	dBm	±	dBm	±
1	15.5	1	15.5	1	15.5	1	15.5	1
6	15.5	1	15.5	1	15.5	1	15.5	1
11	15.5	1	15.5	1	15.5	1	15.5	1

802.11g

Channel\rate	6Mbps		9Mbps		12Mbps		18Mbps		24Mbps		36Mbps		48Mbps		54Mbps	
	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±
1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1
6	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1
11	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1	15.5	1

802.11n-20M

Channel\rate	MCS0		MCS1		MCS2		MCS3		MCS4		MCS5		MCS6		MCS7	
	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±
1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1
6	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1
11	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1

802.11n-40M

Channel\rate	MCS0		MCS1		MCS2		MCS3		MCS4		MCS5		MCS6		MCS7	
	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±	dBm	±
1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1
6	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1
11	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1	12.5	1

11.3 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.7: The conducted power measurement results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	31.62	31.55	31.50
GSM 1900MHz	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	28.78	28.64	28.23

Table 11.8: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	31.62	31.54	31.46	-9.03	22.59	22.51	22.43
2 Txslots	30.81	30.77	30.77	-6.02	24.79	24.75	24.75
3Txslots	28.82	28.81	28.82	-4.26	24.56	24.55	24.56
4 Txslots	27.76	27.69	27.73	-3.01	24.75	24.68	24.72
GSM 850 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	31.58	31.51	31.44	-9.03	22.55	22.48	22.41
2 Txslots	30.75	30.71	30.69	-6.02	24.73	24.69	24.67
3Txslots	28.78	28.78	28.77	-4.26	24.52	24.52	24.51
4 Txslots	27.73	27.63	27.67	-3.01	24.72	24.62	24.66
GSM 850 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	25.32	25.41	25.50	-9.03	16.29	16.38	16.47
2 Txslots	24.15	24.37	24.45	-6.02	18.13	18.35	18.43
3Txslots	22.14	22.30	22.48	-4.26	17.88	18.04	18.22
4 Txslots	21.19	21.29	21.39	-3.01	18.18	18.28	18.38
PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	28.82	28.69	28.26	-9.03	19.79	19.66	19.23
2 Txslots	27.29	26.84	26.28	-6.02	21.27	20.82	20.26
3Txslots	25.52	25.07	24.40	-4.26	21.26	20.81	20.14
4 Txslots	23.55	22.98	22.30	-3.01	20.54	19.97	19.29

PCS1900 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	28.81	28.67	28.25	-9.03	19.78	19.64	19.22
2 Txslots	27.27	26.84	26.26	-6.02	21.25	20.82	20.24
3Txslots	25.50	25.05	24.39	-4.26	21.24	20.79	20.13
4 Txslots	23.54	22.97	22.29	-3.01	20.53	19.96	19.28
GSM 1900 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	25.02	24.34	23.67	-9.03	15.99	15.31	14.64
2 Txslots	24.03	23.40	22.74	-6.02	18.01	17.38	16.72
3Txslots	22.16	21.49	20.90	-4.26	17.90	17.23	16.64
4 Txslots	21.09	20.50	19.89	-3.01	18.08	17.49	16.88

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 2Txslot.

11.4 WCDMA Measurement result

Table 11.9: The conducted Power for WCDMA

Item	band	FDDV result		
	ARFCN	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)
WCDMA	\	23.40	23.39	23.37
HSDPA	1	22.42	22.37	22.41
	2	22.44	22.41	22.41
	3	22.52	22.41	22.45
	4	22.41	22.41	22.38
HSUPA	1	20.45	20.41	20.34
	2	20.46	20.35	20.36
	3	21.42	21.36	21.37
	4	19.91	19.81	19.80
	5	22.33	22.35	22.38
DC-HSDPA	1	21.65	21.71	21.53
	2	21.62	21.68	21.51
	3	21.12	21.17	21.09
	4	21.13	21.19	21.05
HSPA+	1	21.18	21.25	21.12

Item	band	FDDIV result		
	ARFCN	1513 (1752.6MHz)	1412 (1732.4MHz)	1312 (1712.4MHz)
WCDMA	\	23.25	23.11	23.56
HSDPA	1	21.45	21.58	21.59
	2	21.48	21.55	21.54
	3	21.45	21.58	21.56
	4	21.46	21.57	21.49
HSUPA	1	19.93	19.88	19.95
	2	19.81	19.85	19.87
	3	20.84	20.69	20.75
	4	19.44	19.49	19.53
	5	21.45	21.43	21.36
DC-HSDPA	1	21.29	21.53	21.43
	2	21.34	21.55	21.42
	3	20.89	21.04	20.98
	4	20.88	21.08	20.95
HSPA+	1	20.98	21.08	21.01
Item	band	FDDII result		
	ARFCN	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)
WCDMA	\	22.88	22.74	22.90
HSDPA	1	21.95	21.76	22.05
	2	21.92	21.71	22.04
	3	21.99	21.76	22.08
	4	21.89	21.71	22.03
HSUPA	1	19.95	19.80	20.06
	2	19.89	19.80	19.97
	3	20.86	20.77	20.99
	4	19.27	19.21	19.57
	5	21.74	21.68	21.88
DC-HSDPA	1	21.95	21.74	21.19
	2	21.92	21.79	21.21
	3	21.38	21.27	21.18
	4	21.34	21.32	21.24
HSPA+	1	21.47	21.37	21.35

11.5 LTE Measurement result

Table 11.10: The conducted Power for LTE

Band 2							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1909.3	24	22.98	0	21.84	1
		1880	24	22.45	0	21.54	1
		1850.7	24	22.82	0	21.81	1
	1RB Middle (3)	1909.3	24	22.90	0	21.86	1
		1880	24	22.85	0	21.85	1
		1850.7	24	22.89	0	21.90	1
	1RB Low (0)	1909.3	24	22.93	0	21.82	1
		1880	24	22.75	0	21.69	1
		1850.7	24	22.79	0	21.95	1
	3RB High (3)	1909.3	24	22.92	0	21.97	1
		1880	24	22.82	0	21.92	1
		1850.7	24	22.95	0	22.06	1
	3RB Middle (1)	1909.3	24	22.85	0	21.93	1
		1880	24	22.73	0	21.85	1
		1850.7	24	22.84	0	21.98	1
	3RB Low (0)	1909.3	24	22.88	0	21.97	1
		1880	24	22.81	0	21.93	1
		1850.7	24	22.92	0	22.07	1
	6RB (0)	1909.3	24	21.90	1	21.07	2
		1880	24	21.77	1	20.97	2
		1850.7	24	21.84	1	21.09	2
3 MHz	1RB High (14)	1908.5	24	22.96	0	22.23	1
		1880	24	22.77	0	21.75	1
		1851.5	24	22.80	0	22.31	1
	1RB Middle (7)	1908.5	24	22.86	0	22.26	1
		1880	24	22.83	0	21.80	1
		1851.5	24	22.82	0	22.37	1
	1RB Low (0)	1908.5	24	22.90	0	22.26	1
		1880	24	22.79	0	21.75	1
		1851.5	24	22.82	0	22.32	1
	8RB High (7)	1908.5	24	21.87	1	20.93	2
		1880	24	21.81	1	20.90	2
		1851.5	24	21.88	1	20.99	2
	8RB Middle (4)	1908.5	24	21.94	1	20.99	2
		1880	24	21.83	1	20.92	2
		1851.5	24	21.88	1	21.02	2

	8RB Low (0)	1908.5	24	21.87	1	20.93	2
		1880	24	21.83	1	20.91	2
		1851.5	24	21.90	1	21.00	2
	15RB (0)	1908.5	24	21.87	1	20.89	2
		1880	24	21.77	1	20.81	2
		1851.5	24	21.85	1	20.90	2
5 MHz	1RB High (24)	1907.5	24	22.94	0	21.76	1
		1880	24	22.77	0	21.78	1
		1852.5	24	22.86	0	21.75	1
	1RB Middle (12)	1907.5	24	22.89	0	21.73	1
		1880	24	22.86	0	21.89	1
		1852.5	24	22.92	0	21.82	1
	1RB Low (0)	1907.5	24	22.97	0	21.78	1
		1880	24	22.86	0	21.85	1
		1852.5	24	22.92	0	21.76	1
	12RB High (13)	1907.5	24	21.89	1	21.00	2
		1880	24	21.84	1	20.95	2
		1852.5	24	21.94	1	21.07	2
	12RB Middle (6)	1907.5	24	21.93	1	21.05	2
		1880	24	21.84	1	20.97	2
		1852.5	24	21.92	1	21.08	2
	12RB Low (0)	1907.5	24	21.86	1	20.97	2
		1880	24	21.83	1	20.95	2
		1852.5	24	21.90	1	21.05	2
	25RB (0)	1907.5	24	21.86	1	20.89	2
		1880	24	21.77	1	20.80	2
		1852.5	24	21.88	1	20.92	2
10 MHz	1RB High (49)	1905	24.5	23.04	0	22.34	1
		1880	24.5	22.80	0	21.77	1
		1855	24.5	22.88	0	22.39	1
	1RB Middle (24)	1905	24.5	22.89	0	22.34	1
		1880	24.5	22.89	0	21.84	1
		1855	24.5	22.91	0	22.45	1
	1RB Low (0)	1905	24.5	22.88	0	22.36	1
		1880	24.5	22.90	0	21.81	1
		1855	24.5	22.93	0	22.41	1
	25RB High (25)	1905	24.5	21.83	1	20.97	2
		1880	24.5	21.77	1	20.93	2
		1855	24.5	21.87	1	21.06	2
	25RB Middle (12)	1905	24.5	21.86	1	21.02	2
		1880	24.5	21.75	1	20.93	2
		1855	24.5	21.87	1	21.07	2

	25RB Low (0)	1905	24.5	21.78	1	20.97	2
		1880	24.5	21.77	1	20.94	2
		1855	24.5	21.86	1	21.05	2
	50RB (0)	1905	24.5	21.85	1	20.96	2
		1880	24.5	21.76	1	20.88	2
		1855	24.5	21.85	1	21.00	2
15 MHz	1RB High (74)	1902.5	24	23.11	0	22.14	1
		1880	24	22.84	0	22.12	1
		1857.5	24	22.88	0	22.34	1
	1RB Middle (37)	1902.5	24	22.83	0	22.34	1
		1880	24	22.86	0	22.16	1
		1857.5	24	22.84	0	22.42	1
	1RB Low (0)	1902.5	24	22.84	0	22.16	1
		1880	24	22.91	0	22.10	1
		1857.5	24	22.97	0	22.40	1
	36RB High (38)	1902.5	24	21.89	1	20.87	2
		1880	24	21.82	1	20.83	2
		1857.5	24	21.82	1	20.87	2
	36RB Middle (19)	1902.5	24	21.84	1	20.85	2
		1880	24	21.84	1	20.84	2
		1857.5	24	21.89	1	20.92	2
	36RB Low (0)	1902.5	24	21.75	1	20.81	2
		1880	24	21.84	1	20.82	2
		1857.5	24	21.88	1	20.90	2
	75RB (0)	1902.5	24	21.84	1	20.88	2
		1880	24	21.84	1	20.85	2
		1857.5	24	21.88	1	20.92	2
20 MHz	1RB High (99)	1900	24	23.10	0	22.20	1
		1880	24	22.82	0	22.33	1
		1860	24	22.98	0	22.18	1
	1RB Middle (50)	1900	24	22.81	0	22.12	1
		1880	24	22.83	0	22.32	1
		1860	24	22.89	0	22.18	1
	1RB Low (0)	1900	24	22.88	0	22.11	1
		1880	24	22.85	0	22.29	1
		1860	24	23.02	0	22.22	1
	50RB High (50)	1900	24	21.81	1	20.88	2
		1880	24	21.76	1	20.82	2
		1860	24	21.92	1	20.92	2
	50RB Middle (25)	1900	24	21.73	1	20.83	2
		1880	24	21.75	1	20.82	2
		1860	24	21.81	1	20.90	2

	50RB Low (0)	1900	24	21.79	1	20.87	2
		1880	24	21.81	1	20.85	2
		1860	24	21.87	1	20.94	2
	100RB (0)	1900	24	21.74	1	20.85	2
		1880	24	21.74	1	20.81	2
		1860	24	21.82	1	20.91	2
Band 4							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1754.3	23.5	22.66	0	21.66	1
		1732.5	23.5	22.69	0	21.69	1
		1710.7	23.5	22.70	0	21.76	1
	1RB Middle (3)	1754.3	23.5	22.77	0	21.75	1
		1732.5	23.5	22.69	0	21.73	1
		1710.7	23.5	22.73	0	21.76	1
	1RB Low (0)	1754.3	23.5	22.65	0	21.66	1
		1732.5	23.5	22.64	0	21.65	1
		1710.7	23.5	22.66	0	21.70	1
	3RB High (3)	1754.3	23.5	22.72	0	21.86	1
		1732.5	23.5	22.72	0	21.88	1
		1710.7	23.5	22.76	0	21.91	1
	3RB Middle (1)	1754.3	23.5	22.61	0	21.78	1
		1732.5	23.5	22.59	0	21.78	1
		1710.7	23.5	22.63	0	21.86	1
	3RB Low (0)	1754.3	23.5	22.71	0	21.87	1
		1732.5	23.5	22.71	0	21.89	1
		1710.7	23.5	22.72	0	21.95	1
	6RB (0)	1754.3	23.5	21.75	1	20.84	2
		1732.5	23.5	21.71	1	20.84	2
		1710.7	23.5	21.74	1	20.88	2
3 MHz	1RB High (14)	1753.5	23.5	22.67	0	22.09	1
		1732.5	23.5	22.69	0	21.74	1
		1711.5	23.5	22.65	0	22.17	1
	1RB Middle (7)	1753.5	23.5	22.69	0	22.19	1
		1732.5	23.5	22.73	0	21.74	1
		1711.5	23.5	22.73	0	22.31	1
	1RB Low (0)	1753.5	23.5	22.65	0	22.14	1
		1732.5	23.5	22.71	0	21.72	1
		1711.5	23.5	22.67	0	22.20	1
	8RB High (7)	1753.5	23.5	21.81	1	20.76	2
		1732.5	23.5	21.76	1	20.76	2
		1711.5	23.5	21.81	1	20.82	2

	8RB Middle (4)	1753.5	23.5	21.75	1	20.76	2
		1732.5	23.5	21.76	1	20.76	2
		1711.5	23.5	21.81	1	20.81	2
	8RB Low (0)	1753.5	23.5	21.82	1	20.78	2
		1732.5	23.5	21.79	1	20.78	2
		1711.5	23.5	21.82	1	20.82	2
	15RB (0)	1753.5	23.5	21.72	1	20.63	2
		1732.5	23.5	21.73	1	20.65	2
		1711.5	23.5	21.78	1	20.71	2
5 MHz	1RB High (24)	1752.5	23.5	22.66	0	21.57	1
		1732.5	23.5	22.71	0	21.78	1
		1712.5	23.5	22.69	0	21.64	1
	1RB Middle (12)	1752.5	23.5	22.77	0	21.69	1
		1732.5	23.5	22.74	0	21.82	1
		1712.5	23.5	22.78	0	21.70	1
	1RB Low (0)	1752.5	23.5	22.71	0	21.63	1
		1732.5	23.5	22.75	0	21.82	1
		1712.5	23.5	22.73	0	21.67	1
	12RB High (13)	1752.5	23.5	21.82	1	20.81	2
		1732.5	23.5	21.81	1	20.82	2
		1712.5	23.5	21.83	1	20.87	2
	12RB Middle (6)	1752.5	23.5	21.78	1	20.79	2
		1732.5	23.5	21.76	1	20.78	2
		1712.5	23.5	21.78	1	20.82	2
	12RB Low (0)	1752.5	23.5	21.80	1	20.81	2
		1732.5	23.5	21.81	1	20.83	2
		1712.5	23.5	21.82	1	20.85	2
	25RB (0)	1752.5	23.5	21.73	1	20.64	2
		1732.5	23.5	21.71	1	20.63	2
		1712.5	23.5	21.75	1	20.67	2
10 MHz	1RB High (49)	1750	23.5	22.70	0	22.15	1
		1732.5	23.5	22.82	0	21.80	1
		1715	23.5	22.76	0	22.25	1
	1RB Middle (24)	1750	23.5	22.74	0	22.29	1
		1732.5	23.5	22.77	0	21.77	1
		1715	23.5	22.80	0	22.33	1
	1RB Low (0)	1750	23.5	22.72	0	22.26	1
		1732.5	23.5	22.86	0	21.85	1
		1715	23.5	22.73	0	22.27	1
	25RB High (25)	1750	23.5	21.76	1	20.81	2
		1732.5	23.5	21.77	1	20.83	2
		1715	23.5	21.82	1	20.86	2

	25RB Middle (12)	1750	23.5	21.72	1	20.76	2
		1732.5	23.5	21.74	1	20.78	2
		1715	23.5	21.77	1	20.85	2
	25RB Low (0)	1750	23.5	21.76	1	20.84	2
		1732.5	23.5	21.76	1	20.80	2
		1715	23.5	21.77	1	20.85	2
	50RB (0)	1750	23.5	21.74	1	20.72	2
		1732.5	23.5	21.75	1	20.74	2
		1715	23.5	21.78	1	20.79	2
15 MHz	1RB High (74)	1747.5	23.5	22.72	0	22.18	1
		1732.5	23.5	22.80	0	22.14	1
		1717.5	23.5	22.79	0	22.24	1
	1RB Middle (37)	1747.5	23.5	22.75	0	22.31	1
		1732.5	23.5	22.76	0	22.10	1
		1717.5	23.5	22.80	0	22.31	1
	1RB Low (0)	1747.5	23.5	22.81	0	22.31	1
		1732.5	23.5	22.87	0	22.08	1
		1717.5	23.5	22.74	0	22.25	1
	36RB High (38)	1747.5	23.5	21.84	1	20.77	2
		1732.5	23.5	21.88	1	20.78	2
		1717.5	23.5	21.92	1	20.83	2
	36RB Middle (19)	1747.5	23.5	21.81	1	20.74	2
		1732.5	23.5	21.84	1	20.71	2
		1717.5	23.5	21.86	1	20.77	2
	36RB Low (0)	1747.5	23.5	21.87	1	20.80	2
		1732.5	23.5	21.90	1	20.80	2
		1717.5	23.5	21.87	1	20.80	2
	75RB (0)	1747.5	23.5	21.83	1	20.77	2
		1732.5	23.5	21.86	1	20.79	2
		1717.5	23.5	21.89	1	20.82	2
20 MHz	1RB High (99)	1745	23.5	22.83	0	22.03	1
		1732.5	23.5	22.82	0	22.34	1
		1720	23.5	22.92	0	22.14	1
	1RB Middle (50)	1745	23.5	22.82	0	22.13	1
		1732.5	23.5	22.74	0	22.28	1
		1720	23.5	22.84	0	22.10	1
	1RB Low (0)	1745	23.5	22.84	0	22.07	1
		1732.5	23.5	22.80	0	22.24	1
		1720	23.5	22.81	0	22.06	1
	50RB High (50)	1745	23.5	21.80	1	20.74	2
		1732.5	23.5	21.84	1	20.79	2
		1720	23.5	21.85	1	20.79	2

	50RB Middle (25)	1745	23.5	21.76	1	20.72	2
		1732.5	23.5	21.77	1	20.71	2
		1720	23.5	21.78	1	20.75	2
	50RB Low (0)	1745	23.5	21.82	1	20.79	2
		1732.5	23.5	21.83	1	20.77	2
		1720	23.5	21.80	1	20.75	2
	100RB (0)	1745	23.5	21.77	1	20.74	2
		1732.5	23.5	21.79	1	20.75	2
		1720	23.5	21.77	1	20.78	2
Band 5							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	848.3	23.5	22.41	0	21.47	1
		836.5	23.5	22.31	0	21.45	1
		824.7	23.5	22.39	0	21.42	1
	1RB Middle (3)	848.3	23.5	22.45	0	21.56	1
		836.5	23.5	22.37	0	21.49	1
		824.7	23.5	22.46	0	21.47	1
	1RB Low (0)	848.3	23.5	22.44	0	21.53	1
		836.5	23.5	22.28	0	21.42	1
		824.7	23.5	22.06	0	21.11	1
	3RB High (3)	848.3	23.5	22.49	0	21.71	1
		836.5	23.5	22.46	0	21.65	1
		824.7	23.5	22.52	0	21.61	1
	3RB Middle (1)	848.3	23.5	22.40	0	21.65	1
		836.5	23.5	22.30	0	21.58	1
		824.7	23.5	22.41	0	21.54	1
	3RB Low (0)	848.3	23.5	22.52	0	21.75	1
		836.5	23.5	22.46	0	21.68	1
		824.7	23.5	22.49	0	21.62	1
	6RB (0)	848.3	23.5	21.50	1	20.68	2
		836.5	23.5	21.37	1	20.59	2
		824.7	23.5	21.42	1	20.57	2
3 MHz	1RB High (14)	847.5	23.5	22.41	0	21.48	1
		836.5	23.5	22.33	0	21.45	1
		825.5	23.5	22.24	0	21.40	1
	1RB Middle (7)	847.5	23.5	22.47	0	22.14	1
		836.5	23.5	22.42	0	21.53	1
		825.5	23.5	22.40	0	21.95	1

	1RB Low (0)	847.5	23.5	22.50	0	21.62	1
		836.5	23.5	22.27	0	21.43	1
		825.5	23.5	22.22	0	21.43	1
	8RB High (7)	847.5	23.5	21.56	1	20.62	2
		836.5	23.5	21.53	1	20.56	2
		825.5	23.5	21.49	1	20.50	2
	8RB Middle (4)	847.5	23.5	21.57	1	20.62	2
		836.5	23.5	21.42	1	20.48	2
		825.5	23.5	21.35	1	20.06	2
	8RB Low (0)	847.5	23.5	21.63	1	20.67	2
		836.5	23.5	21.52	1	20.56	2
		825.5	23.5	21.50	1	20.50	2
	15RB (0)	847.5	23.5	21.58	1	20.52	2
		836.5	23.5	21.43	1	20.38	2
		825.5	23.5	21.03	1	20.31	2
5 MHz	1RB High (24)	846.5	23.5	22.36	0	21.49	1
		836.5	23.5	22.40	0	21.52	1
		826.5	23.5	22.32	0	21.28	1
	1RB Middle (12)	846.5	23.5	22.59	0	21.59	1
		836.5	23.5	22.44	0	21.59	1
		826.5	23.5	22.50	0	21.44	1
	1RB Low (0)	846.5	23.5	22.52	0	21.66	1
		836.5	23.5	22.35	0	21.52	1
		826.5	23.5	22.38	0	21.25	1
	12RB High (13)	846.5	23.5	21.68	1	20.70	2
		836.5	23.5	21.58	1	20.62	2
		826.5	23.5	21.55	1	20.60	2
	12RB Middle (6)	846.5	23.5	21.63	1	20.67	2
		836.5	23.5	21.47	1	20.52	2
		826.5	23.5	21.47	1	20.54	2
	12RB Low (0)	846.5	23.5	21.68	1	20.73	2
		836.5	23.5	21.56	1	20.62	2
		826.5	23.5	21.53	1	20.56	2
	25RB (0)	846.5	23.5	21.54	1	20.48	2
		836.5	23.5	21.42	1	20.39	2
		826.5	23.5	21.45	1	20.38	2
10 MHz	1RB High (49)	844.0	23.5	22.40	0	22.03	1
		836.5	23.5	22.51	0	21.59	1
		829.0	23.5	22.33	0	22.05	1
	1RB Middle (24)	844.0	23.5	22.61	0	22.23	1
		836.5	23.5	22.45	0	21.55	1
		829.0	23.5	22.49	0	22.20	1

	1RB Low (0)	844.0	23.5	22.44	0	21.99	1
		836.5	23.5	22.37	0	21.52	1
		829.0	23.5	22.42	0	21.92	1
	25RB High (25)	844.0	23.5	21.63	1	20.70	2
		836.5	23.5	21.59	1	20.66	2
		829.0	23.5	21.59	1	20.67	2
	25RB Middle (12)	844.0	23.5	21.58	1	20.66	2
		836.5	23.5	21.46	1	20.53	2
		829.0	23.5	21.52	1	20.59	2
	25RB Low (0)	844.0	23.5	21.61	1	20.67	2
		836.5	23.5	21.53	1	20.64	2
		829.0	23.5	21.49	1	20.56	2
	50RB (0)	844.0	23.5	21.57	1	20.59	2
		836.5	23.5	21.49	1	20.50	2
		829.0	23.5	21.51	1	20.52	2
Band 7							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	2567.5	23	21.72	0	21.18	1
		2535	23	21.97	0	20.90	1
		2502.5	23	22.13	0	21.06	1
	1RB Middle (12)	2567.5	23	21.81	0	20.74	1
		2535	23	21.93	0	20.85	1
		2502.5	23	22.10	0	21.02	1
	1RB Low (0)	2567.5	23	21.91	0	20.72	1
		2535	23	22.06	0	20.90	1
		2502.5	23	22.23	0	21.10	1
	12RB High (13)	2567.5	23	20.85	1	19.89	2
		2535	23	21.03	1	20.09	2
		2502.5	23	20.91	1	20.23	2
	12RB Middle (6)	2567.5	23	20.95	1	19.95	2
		2535	23	20.97	1	19.95	2
		2502.5	23	21.15	1	20.14	2
	12RB Low (0)	2567.5	23	21.12	1	19.89	2
		2535	23	20.93	1	20.01	2
		2502.5	23	21.03	1	20.26	2
	25RB (0)	2567.5	23	20.88	1	19.78	2
		2535	23	20.85	1	19.82	2
		2502.5	23	21.08	1	19.98	2

10 MHz	1RB High (49)	2565	23	21.85	0	21.36	1
		2535	23	22.04	0	21.00	1
		2505	23	21.99	0	21.49	1
	1RB Middle (24)	2565	23	21.63	0	21.61	1
		2535	23	21.91	0	20.88	1
		2505	23	22.05	0	21.78	1
	1RB Low (0)	2565	23	21.91	0	21.34	1
		2535	23	22.04	0	21.00	1
		2505	23	22.11	0	21.62	1
	25RB High (25)	2565	23	20.80	1	19.86	2
		2535	23	20.87	1	19.94	2
		2505	23	21.00	1	20.04	2
	25RB Middle (12)	2565	23	20.91	1	19.97	2
		2535	23	20.92	1	19.97	2
		2505	23	21.07	1	20.11	2
	25RB Low (0)	2565	23	20.80	1	19.84	2
		2535	23	20.88	1	19.94	2
		2505	23	21.05	1	20.10	2
	50RB (0)	2565	23	20.89	1	19.89	2
		2535	23	20.96	1	19.96	2
		2505	23	21.04	1	20.02	2
15 MHz	1RB High (75)	2562.5	23	21.89	0	21.35	1
		2535	23	22.07	0	21.39	1
		2507.5	23	22.16	0	21.38	1
	1RB Middle (38)	2562.5	23	21.77	0	21.26	1
		2535	23	21.87	0	21.19	1
		2507.5	23	22.03	0	21.53	1
	1RB Low (0)	2562.5	23	21.94	0	21.32	1
		2535	23	22.12	0	21.34	1
		2507.5	23	22.25	0	21.50	1
	36RB High (38)	2562.5	23	20.88	1	19.79	2
		2535	23	20.96	1	19.89	2
		2507.5	23	21.14	1	20.03	2
	36RB Middle (19)	2562.5	23	20.98	1	19.89	2
		2535	23	20.98	1	19.93	2
		2507.5	23	21.18	1	20.09	2
	36RB Low (0)	2562.5	23	20.85	1	19.75	2
		2535	23	20.96	1	19.88	2
		2507.5	23	21.14	1	20.06	2

	75RB (0)	2562.5	23	20.98	1	19.89	2
		2535	23	21.05	1	19.99	2
		2507.5	23	21.20	1	20.13	2
20 MHz	1RB High (99)	2560	23	21.98	0	21.18	1
		2535	23	22.14	0	21.59	1
		2510	23	22.20	0	21.36	1
	1RB Middle (50)	2560	23	21.83	0	21.09	1
		2535	23	21.84	0	21.38	1
		2510	23	22.06	0	21.31	1
	1RB Low (0)	2560	23	22.08	0	21.24	1
		2535	23	22.08	0	21.54	1
		2510	23	22.23	0	21.47	1
	50RB High (50)	2560	23	20.81	1	19.73	2
		2535	23	20.99	1	19.93	2
		2510	23	21.01	1	19.93	2
	50RB Middle (25)	2560	23	20.89	1	19.83	2
		2535	23	20.96	1	19.89	2
		2510	23	21.08	1	20.00	2
	50RB Low (0)	2560	23	20.78	1	19.70	2
		2535	23	20.95	1	19.88	2
		2510	23	21.04	1	19.99	2
	100RB (0)	2560	23	20.91	1	19.86	2
		2535	23	21.03	1	19.99	2
		2510	23	21.07	1	20.02	2
Band 12							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	715.3	23.5	22.56	0	21.74	1
		707.5	23.5	22.56	0	21.48	1
		699.7	23.5	22.64	0	21.68	1
	1RB Middle (3)	715.3	23.5	22.75	0	21.76	1
		707.5	23.5	22.54	0	21.52	1
		699.7	23.5	22.71	0	21.78	1
	1RB Low (0)	715.3	23.5	22.61	0	21.48	1
		707.5	23.5	22.66	0	21.46	1
		699.7	23.5	22.69	0	21.80	1
	3RB High (3)	715.3	23.5	22.83	0	21.94	1
		707.5	23.5	22.58	0	21.70	1
		699.7	23.5	22.79	0	21.94	1

	3RB Middle (1)	715.3	23.5	22.62	0	21.76	1
		707.5	23.5	22.37	0	21.44	1
		699.7	23.5	22.60	0	21.79	1
	3RB Low (0)	715.3	23.5	22.80	0	21.94	1
		707.5	23.5	22.55	0	21.71	1
		699.7	23.5	22.81	0	21.98	1
	6RB (0)	715.3	23.5	21.62	1	20.74	2
		707.5	23.5	21.40	1	20.18	2
		699.7	23.5	21.56	1	20.76	2
3 MHz	1RB High (14)	714.5	23.5	22.40	0	22.14	1
		707.5	23.5	22.46	0	21.50	1
		700.5	23.5	22.50	0	22.05	1
	1RB Middle (7)	714.5	23.5	22.71	0	22.29	1
		707.5	23.5	22.52	0	21.54	1
		700.5	23.5	22.63	0	22.28	1
	1RB Low (0)	714.5	23.5	22.49	0	22.14	1
		707.5	23.5	22.50	0	21.52	1
		700.5	23.5	22.57	0	22.16	1
	8RB High (7)	714.5	23.5	21.76	1	20.80	2
		707.5	23.5	21.56	1	20.65	2
		700.5	23.5	21.71	1	20.73	2
	8RB Middle (4)	714.5	23.5	21.55	1	20.68	2
		707.5	23.5	21.25	1	20.59	2
		700.5	23.5	21.60	1	20.68	2
	8RB Low (0)	714.5	23.5	21.74	1	20.76	2
		707.5	23.5	21.58	1	20.67	2
		700.5	23.5	21.72	1	20.78	2
	15RB (0)	714.5	23.5	21.57	1	20.49	2
		707.5	23.5	21.20	1	20.65	2
		700.5	23.5	21.59	1	20.54	2
5 MHz	1RB High (24)	713.5	23.5	22.73	0	21.81	1
		707.5	23.5	22.59	0	21.67	1
		701.5	23.5	22.67	0	21.60	1
	1RB Middle (12)	713.5	23.5	22.75	0	21.67	1
		707.5	23.5	22.55	0	21.63	1
		701.5	23.5	22.73	0	21.64	1
	1RB Low (0)	713.5	23.5	22.61	0	21.72	1
		707.5	23.5	22.66	0	21.71	1
		701.5	23.5	22.74	0	21.68	1

	12RB High (13)	713.5	23.5	21.79	1	20.86	2
		707.5	23.5	21.61	1	20.68	2
		701.5	23.5	21.75	1	20.77	2
	12RB Middle (6)	713.5	23.5	21.73	1	20.77	2
		707.5	23.5	21.56	1	20.59	2
		701.5	23.5	21.73	1	20.76	2
	12RB Low (0)	713.5	23.5	21.66	1	20.72	2
		707.5	23.5	21.63	1	20.66	2
		701.5	23.5	21.76	1	20.79	2
	25RB (0)	713.5	23.5	21.70	1	20.62	2
		707.5	23.5	21.57	1	20.50	2
		701.5	23.5	21.68	1	20.60	2
10 MHz	1RB High (49)	711	23.5	22.77	0	21.81	1
		707.5	23.5	22.64	0	21.68	1
		704	23.5	22.55	0	22.16	1
	1RB Middle (24)	711	23.5	22.65	0	22.25	1
		707.5	23.5	22.55	0	22.13	1
		704	23.5	22.66	0	22.28	1
	1RB Low (0)	711	23.5	22.59	0	21.61	1
		707.5	23.5	22.70	0	21.71	1
		704	23.5	22.64	0	22.28	1
	25RB High (25)	711	23.5	21.70	1	20.70	2
		707.5	23.5	21.61	1	20.60	2
		704	23.5	21.60	1	20.58	2
	25RB Middle (12)	711	23.5	21.61	1	20.69	2
		707.5	23.5	21.56	1	20.64	2
		704	23.5	21.64	1	20.70	2
	25RB Low (0)	711	23.5	21.57	1	20.56	2
		707.5	23.5	21.61	1	20.61	2
		704	23.5	21.69	1	20.69	2
	50RB (0)	711	23.5	21.64	1	20.62	2
		707.5	23.5	21.63	1	20.60	2
		704	23.5	21.61	1	20.61	2
Band 17							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	713.5	23.5	22.72	0	21.76	1
		710	23.5	22.59	0	21.65	1
		706.5	23.5	22.61	0	21.50	1
	1RB Middle (12)	713.5	23.5	22.71	0	21.60	1
		710	23.5	22.70	0	21.59	1
		706.5	23.5	22.70	0	21.59	1

	1RB Low (0)	713.5	23.5	22.65	0	21.72	1
		710	23.5	22.66	0	21.71	1
		706.5	23.5	22.67	0	21.56	1
	12RB High (13)	713.5	23.5	21.75	1	20.79	2
		710	23.5	21.67	1	20.74	2
		706.5	23.5	21.67	1	20.67	2
	12RB Middle (6)	713.5	23.5	21.68	1	20.69	2
		710	23.5	21.67	1	20.67	2
		706.5	23.5	21.64	1	20.66	2
	12RB Low (0)	713.5	23.5	21.65	1	20.69	2
		710	23.5	21.65	1	20.69	2
		706.5	23.5	21.65	1	20.67	2
	25RB (0)	713.5	23.5	21.64	1	20.56	2
		710	23.5	21.60	1	20.50	2
		706.5	23.5	21.60	1	20.51	2
10 MHz	1RB High (49)	711	23.5	22.79	0	21.76	1
		710	23.5	22.74	0	21.71	1
		709	23.5	22.65	0	22.18	1
	1RB Middle (24)	711	23.5	22.67	0	22.21	1
		710	23.5	22.71	0	21.69	1
		709	23.5	22.64	0	22.17	1
	1RB Low (0)	711	23.5	22.64	0	21.63	1
		710	23.5	22.62	0	21.60	1
		709	23.5	22.61	0	22.14	1
	25RB High (25)	711	23.5	21.67	1	20.68	2
		710	23.5	21.64	1	20.64	2
		709	23.5	21.65	1	20.69	2
	25RB Middle (12)	711	23.5	21.60	1	20.66	2
		710	23.5	21.61	1	20.68	2
		709	23.5	21.63	1	20.66	2
	25RB Low (0)	711	23.5	21.62	1	20.58	2
		710	23.5	21.60	1	20.57	2
		709	23.5	21.59	1	20.63	2
	50RB (0)	711	23.5	21.64	1	20.63	2
		710	23.5	21.63	1	20.62	2
		709	23.5	21.63	1	20.61	2

11.6 Wi-Fi and BT Measurement result

The output power of BT antenna is as following:

Mode	Conducted Power (dBm)		
	Channel 0 (2402MHz)	Channel 39 (2441MHz)	Channel 78 (2480MHz)
GFSK	4.68	3.70	4.21

The average conducted power for Wi-Fi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1	/	/	/	14.93
6	/	/	/	15.87
11	15.89	15.90	15.97	16.03

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	/	/	/	/	/	/	/	15.10
6	15.80	15.92	15.76	15.85	15.71	15.78	15.70	15.74
11	/	/	/	/	/	/	/	16.01

802.11n (dBm) - HT20 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	/	/	/	/	/	/	/	11.84
6	/	/	/	/	/	/	/	12.91
11	12.30	12.44	12.40	12.23	12.40	13.16	13.16	13.17

802.11n (dBm) – HT40 (2.4G)


Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
3	12.90	12.78	12.90	13.00	12.78	12.87	12.83	12.86
6	/	/	/	12.08	/	/	/	/
9	/	/	/	12.37	/	/	/	/

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter. For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Picture 12.1 Antenna Locations

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	No	No	Yes
WLAN antenna	Yes	Yes	No	Yes	Yes	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	Position	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.402	Head	9.60	5	3.16	Yes
		Body	19.20	5	3.16	Yes
2.4GHz WLAN 802.11 b	2.45	Head	9.58	16.5	44.67	No
		Body	19.17	16.5	44.67	No

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WLAN

	Position	Main antenna	WLAN	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek	0.41	1.18	1.59
	Right hand, Touch cheek	0.51	0.85	1.36
Maximum reported SAR value for Body	Rear 10mm	1.10	0.26	1.36
	Bottom 10mm	1.46	/	1.46
	Top 10mm	/	0.33	0.33

Table 13.2: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.51	0.13	0.64
Highest reported SAR value for Body	Rear 10mm	1.10	0.07	1.17
	Bottom 10mm	1.46	/	1.46

BT* - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Position	F (GHz)	Distance (mm)	Upper limit of power *		Estimated _{1g} (W/kg)
			dBm	mW	
Head	2.441	5	5	3.16	0.13
Body	2.441	10	5	3.16	0.07

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)]·[√f(GHz)/x] W/kg for test separation distances ≤ 50 mm;
where x = 7.5 for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:

According to the above tables, the sum of reported SAR values is < 1.6W/kg So the simultaneous transmission SAR with volume scans is not required.

14 SAR Test Result

We'll perform the head measurement in all bands with the primary battery depending on the evaluation of multi-batteries and retest on highest value point with other batteries. Then, repeat the measurement in the Body test.

Table 14.1: The evaluation of multi-batteries for Head Test

Frequency		Side	Test Position	Battery Type	SAR(1g) (W/kg)	Power Drift(dB)	Battery
MHz	Ch.						
2510	20850	Left	Touch	HB3742A0EZC+ (Scud (Fujian) Electronics Co., Ltd.)	0.249	0.11	Battery1
2510	20850	Left	Touch	HB3742A0EZC+ (Sunwoda electronic Co., Ltd.)	0.326	0.04	Battery2

Note: According to the values in the above table, the **battery1**, is the primary battery. We'll perform the head measurement with this battery and retest on highest value point with others.

Table 14.2: The evaluation of multi-batteries for Body Test

Frequency		Test Position	Spacing (mm)	Battery Type	SAR(1g) (W/kg)	Power Drift(dB)	Battery
MHz	Ch.						
2510	20850	Bottom	10	HB3742A0EZC+ (Scud (Fujian) Electronics Co., Ltd.)	0.880	0.09	Battery1
2510	20850	Bottom	10	HB3742A0EZC+ (Sunwoda electronic Co., Ltd.)	0.562	-0.04	Battery2

Note: According to the values in the above table, the **battery1**, is the primary battery. We'll perform the body measurement with this battery and retest on highest value point with others.

It is determined by user manual for the distance between the EUT and the phantom bottom.

The distance is 10mm and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-gSAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or >1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power in chapter 11.

Table 14.3: Duty Cycle

Duty Cycle	
Speech for GSM850/1900	1:8.3
GPRS&EGPRS 850	1:4
GPRS&EGPRS 1900	1:4
WCDMA & LTE	1:1

14.1 SAR results for Fast SAR

Table 14.1-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.6	190	Left	Touch	/	31.55	32.5	0.095	0.12	0.138	0.17	-0.11
836.6	190	Left	Tilt	/	31.55	32.5	0.072	0.09	0.104	0.13	0.07
848.8	251	Right	Touch	Fig.1	31.62	32.5	0.178	0.22	0.232	0.28	0.16
836.6	190	Right	Touch	/	31.55	32.5	0.126	0.16	0.183	0.23	0.17
824.2	128	Right	Touch	/	31.50	32.5	0.102	0.13	0.148	0.19	0.18
836.6	190	Right	Tilt	/	31.55	32.5	0.078	0.10	0.111	0.14	0.10
848.8	251	Right	Touch	Note	31.62	32.5	0.159	0.19	0.227	0.28	0.01

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.6	190	GPRS (2)	Front	/	30.71	31.5	0.362	0.43	0.511	0.61	-0.01
848.8	251	GPRS (2)	Rear	Fig.2	30.75	31.5	0.576	0.68	0.741	0.88	-0.02
836.6	190	GPRS (2)	Rear	/	30.71	31.5	0.444	0.53	0.626	0.75	0.51
824.2	128	GPRS (2)	Rear	/	30.69	31.5	0.390	0.47	0.549	0.66	-0.04
836.6	190	GPRS (2)	Left	/	30.71	31.5	0.219	0.26	0.326	0.39	0.00
836.6	190	GPRS (2)	Bottom	/	30.71	31.5	0.090	0.11	0.144	0.17	-0.07
848.8	251	EGPRS (2)	Rear	/	30.75	31.5	0.570	0.68	0.734	0.87	-0.03
848.8	251	GPRS (2)	Rear	Note	30.75	31.5	0.517	0.61	0.734	0.87	-0.19

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	Left	Touch	/	28.78	29.7	0.032	0.04	0.055	0.07	0.05
1909.8	810	Left	Tilt	/	28.78	29.7	0.025	0.03	0.044	0.05	0.13
1909.8	810	Right	Touch	/	28.78	29.7	0.066	0.08	0.117	0.14	0.14
1880	661	Right	Touch	Fig.3	28.64	29.7	0.083	0.11	0.136	0.17	0.13
1850.2	512	Right	Touch	/	28.23	29.7	0.076	0.11	0.125	0.18	0.08
1909.8	810	Right	Tilt	/	28.78	29.7	0.023	0.03	0.040	0.05	0.08
1880	661	Right	Touch	Note	28.64	29.7	0.080	0.10	0.134	0.17	0.14

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	GPRS (2)	Front	/	27.29	27.7	0.358	0.39	0.697	0.77	-0.08
1880	661	GPRS (2)	Front	/	26.84	27.7	0.326	0.40	0.597	0.73	-0.07
1850.2	512	GPRS (2)	Front	/	26.28	27.7	0.293	0.41	0.557	0.77	-0.11
1909.8	810	GPRS (2)	Rear	/	27.29	27.7	0.432	0.47	0.816	0.90	-0.01
1880	661	GPRS (2)	Rear	/	26.84	27.7	0.446	0.54	0.822	1.00	-0.11
1850.2	512	GPRS (2)	Rear	/	26.28	27.7	0.395	0.55	0.716	0.99	-0.18
1909.8	810	GPRS (2)	Left	/	27.29	27.7	0.034	0.04	0.059	0.06	-0.06
1909.8	810	GPRS (2)	Bottom	Fig.4	27.29	27.7	0.665	0.73	1.330	1.46	0.00
1880	661	GPRS (2)	Bottom	/	26.84	27.7	0.518	0.63	1.030	1.26	-0.11
1850.2	512	GPRS (2)	Bottom	/	26.28	27.7	0.463	0.64	0.920	1.28	-0.04
1909.8	810	EGPRS (2)	Bottom	/	27.27	27.7	0.651	0.72	1.310	1.45	-0.04
1909.8	810	GPRS (2)	Bottom	Note	27.29	27.7	0.505	0.55	1.040	1.14	-0.09

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.4	4182	Left	Touch	/	23.39	24.5	0.157	0.20	0.229	0.30	-0.13
836.4	4182	Left	Tilt	/	23.39	24.5	0.120	0.15	0.175	0.23	0.07
846.6	4233	Right	Touch	Fig.5	23.37	24.5	0.257	0.33	0.342	0.44	0.08
836.4	4182	Right	Touch	/	23.39	24.5	0.194	0.25	0.287	0.37	0.17
826.4	4132	Right	Touch	/	23.40	24.5	0.163	0.21	0.241	0.31	0.15
836.4	4182	Right	Tilt	/	23.39	24.5	0.124	0.16	0.177	0.23	-0.10
846.6	4233	Right	Touch	Note	23.37	24.5	0.219	0.28	0.310	0.40	0.04

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.4	4182	Front	/	23.39	24.5	0.242	0.31	0.341	0.44	-0.06
846.6	4233	Rear	Fig.6	23.37	24.5	0.406	0.53	0.525	0.68	-0.01
836.4	4182	Rear	/	23.39	24.5	0.323	0.42	0.458	0.59	-0.02
826.4	4132	Rear	/	23.40	24.5	0.270	0.35	0.381	0.49	-0.01
836.4	4182	Left	/	23.39	24.5	0.243	0.31	0.364	0.47	0.02
836.4	4182	Bottom	/	23.39	24.5	0.062	0.08	0.101	0.13	-0.06
846.6	4233	Rear	Note	23.37	24.5	0.358	0.46	0.507	0.66	0.01

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-7: SAR Values (WCDMA 1700 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1732.4	1637	Left	Touch	/	23.11	24	0.198	0.24	0.333	0.41	-0.04
1732.4	1637	Left	Tilt	/	23.11	24	0.132	0.16	0.222	0.27	0.01
1752.6	1738	Right	Touch	/	23.25	24	0.241	0.29	0.406	0.48	0.10
1732.4	1637	Right	Touch	/	23.11	24	0.282	0.35	0.417	0.51	-0.13
1712.4	1537	Right	Touch	Fig.7	23.56	24	0.293	0.32	0.463	0.51	0.11
1732.4	1637	Right	Tilt	/	23.11	24	0.124	0.15	0.212	0.26	0.14
1712.4	1537	Right	Touch	Note	23.56	24	0.194	0.21	0.332	0.37	0.12

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1752.6	1738	Front	/	23.25	24	0.446	0.53	0.810	0.96	0.01
1732.4	1637	Front	/	23.11	24	0.459	0.56	0.820	1.01	-0.09
1712.4	1537	Front	/	23.56	24	0.451	0.50	0.790	0.87	0.05
1752.6	1738	Rear	/	23.25	24	0.519	0.62	0.844	1.00	-0.03
1732.4	1637	Rear	/	23.11	24	0.526	0.65	0.854	1.05	0.00
1712.4	1537	Rear	/	23.56	24	0.521	0.58	0.839	0.93	0.04
1732.4	1637	Left	/	23.11	24	0.124	0.15	0.209	0.26	-0.03
1752.6	1738	Bottom	Fig.8	23.25	24	0.559	0.66	1.090	1.30	0.13
1732.4	1637	Bottom	/	23.11	24	0.504	0.62	0.974	1.20	0.11
1712.4	1537	Bottom	/	23.56	24	0.437	0.48	0.874	0.97	0.10
1752.6	1738	Bottom	Note	23.25	24	0.555	0.66	1.040	1.24	0.01

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-9: SAR Values (WCDMA 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	9800	Left	Touch	/	22.74	23.3	0.067	0.08	0.111	0.13	0.14
1880	9800	Left	Tilt	/	22.74	23.3	0.049	0.06	0.085	0.10	-0.13
1907.6	9938	Right	Touch	/	22.88	23.3	0.121	0.13	0.214	0.24	0.04
1880	9800	Right	Touch	/	22.74	23.3	0.119	0.14	0.210	0.24	0.16
1852.4	9662	Right	Touch	Fig.9	22.90	23.3	0.149	0.16	0.237	0.26	0.13
1880	9800	Right	Tilt	/	22.74	23.3	0.032	0.04	0.055	0.06	0.13
1852.4	9662	Right	Touch	Note	22.90	23.3	0.103	0.11	0.171	0.19	0.12

Note: SAR Values For Battery (HB3742A0Ezc+ (Sunwoda electronic Co., Ltd.))

Table 14.1-10: SAR Values (WCDMA 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1880	9800	Front	/	22.74	23.3	0.329	0.37	0.627	0.71	-0.15
1907.6	9938	Rear	/	22.88	23.3	0.545	0.60	1.000	1.10	0.03
1880	9800	Rear	/	22.74	23.3	0.500	0.57	0.910	1.04	-0.12
1852.4	9662	Rear	/	22.90	23.3	0.522	0.57	0.957	1.05	-0.01
1880	9800	Left	/	22.74	23.3	0.035	0.04	0.061	0.07	0.12
1907.6	9938	Bottom	Fig.10	22.88	23.3	0.653	0.72	1.310	1.44	0.10
1880	9800	Bottom	/	22.74	23.3	0.503	0.57	1.060	1.21	0.04
1852.4	9662	Bottom	/	22.90	23.3	0.495	0.54	1.000	1.10	0.17
1907.6	9938	Bottom	Note	22.88	23.3	0.615	0.68	1.260	1.39	0.02

Note: SAR Values For Battery (HB3742A0Ezc+ (Sunwoda electronic Co., Ltd.))

Table 14.1-11: SAR Values (LTE Band2 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1900	19100	1RB-High	Left	Touch	/	23.1	24	0.053	0.05	0.087	0.11	0.07
1900	19100	1RB-High	Left	Tilt	/	23.1	24	0.050	0.05	0.086	0.11	0.12
1900	19100	1RB-High	Right	Touch	Fig.11	23.1	24	0.127	0.13	0.228	0.28	-0.15
1900	19100	1RB-High	Right	Tilt	/	23.1	24	0.041	0.04	0.067	0.08	0.16
1860	18700	50RB-High	Left	Touch	/	21.92	23	0.049	0.05	0.079	0.10	0.05
1860	18700	50RB-High	Left	Tilt	/	21.92	23	0.040	0.04	0.067	0.09	0.14
1860	18700	50RB-High	Right	Touch	/	21.92	23	0.107	0.11	0.186	0.24	0.05
1860	18700	50RB-High	Right	Tilt	/	21.92	23	0.038	0.04	0.064	0.08	0.13
1900	19100	1RB-High	Right	Tilt	Note	23.10	24	0.083	0.10	0.141	0.17	0.10

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-12: SAR Values (LTE Band2 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1900	19100	1RB_High	Front	/	23.10	24	0.322	0.40	0.627	0.77	-0.06
1900	19100	1RB_High	Rear	/	23.10	24	0.410	0.50	0.769	0.95	-0.03
1880	18900	1RB_High	Rear	/	22.82	24	0.401	0.53	0.750	0.98	-0.02
1860	18700	1RB_High	Rear	/	22.98	24	0.38	0.48	0.706	0.89	0.06
1900	19100	1RB_High	Left	/	23.10	24	0.021	0.03	0.036	0.04	0.18
1900	19100	1RB_High	Bottom	Fig.12	23.10	24	0.538	0.66	1.090	1.34	-0.05
1880	18900	1RB_High	Bottom	/	22.82	24	0.469	0.62	0.950	1.25	-0.07
1860	18700	1RB_High	Bottom	/	22.98	24	0.456	0.58	0.914	1.16	-0.04
1860	18700	50RB_High	Front	/	21.92	23	0.233	0.30	0.425	0.54	0.07
1860	18700	50RB_High	Rear	/	21.92	23	0.311	0.40	0.580	0.74	0.09
1860	18700	50RB_High	Left	/	21.92	23	0.026	0.03	0.046	0.06	0.18
1900	19100	50RB_High	Bottom	/	21.81	23	0.351	0.46	0.698	0.92	0.18
1880	18900	50RB_High	Bottom	/	21.76	23	0.355	0.47	0.701	0.93	0.11
1860	18700	50RB_High	Bottom	/	21.92	23	0.368	0.47	0.733	0.94	-0.02
1860	18700	100RB	Bottom	/	21.82	23	0.364	0.48	0.725	0.95	-0.01
1860	18700	100RB	Rear	/	21.82	23	0.306	0.40	0.571	0.75	0.11
1900	19100	1RB_High	Bottom	Note	23.10	24	0.474	0.58	0.979	1.20	0.04

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-13: SAR Values (LTE Band4 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1720	20050	1RB-High	Left	Touch	/	22.92	23.5	0.172	0.20	0.290	0.33	0.12
1720	20050	1RB-High	Left	Tilt	/	22.92	23.5	0.115	0.13	0.193	0.22	-0.10
1720	20050	1RB-High	Right	Touch	Fig.13	22.92	23.5	0.281	0.32	0.442	0.51	0.13
1720	20050	1RB-High	Right	Tilt	/	22.92	23.5	0.091	0.10	0.157	0.18	0.03
1720	20050	50RB-High	Left	Touch	/	21.85	22.5	0.137	0.16	0.231	0.27	0.09
1720	20050	50RB-High	Left	Tilt	/	21.85	22.5	0.089	0.10	0.149	0.17	0.05
1720	20050	50RB-High	Right	Touch	/	21.85	22.5	0.203	0.24	0.348	0.40	0.14
1720	20050	50RB-High	Right	Tilt	/	21.85	22.5	0.073	0.08	0.126	0.15	0.10
1720	20050	1RB-High	Right	Touch	Note	22.92	23.5	0.193	0.22	0.326	0.37	-0.05

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-14: SAR Values (LTE Band4 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1720	20050	1RB_High	Front	/	22.92	23.5	0.397	0.45	0.659	0.75	0.12
1745	20300	1RB_High	Rear	/	22.83	23.5	0.413	0.48	0.729	0.85	0.06
1732.5	20175	1RB_High	Rear	/	22.82	23.5	0.394	0.46	0.688	0.80	-0.04
1720	20050	1RB_High	Rear	Fig.14	22.92	23.5	0.497	0.57	0.774	0.88	-0.05
1720	20050	1RB_High	Left	/	22.92	23.5	0.092	0.11	0.157	0.18	-0.26
1745	20300	1RB_High	Bottom	/	22.83	23.5	0.371	0.43	0.706	0.82	0.04
1732.5	20175	1RB_High	Bottom	/	22.82	23.5	0.369	0.43	0.695	0.81	0.01
1720	20050	1RB_High	Bottom	/	22.92	23.5	0.389	0.44	0.719	0.82	0.03
1720	20050	50RB_High	Front	/	21.85	22.5	0.328	0.38	0.538	0.62	0.07
1745	20300	50RB_High	Rear	/	21.80	23.5	0.411	0.48	0.682	0.80	0.03
1732.5	20175	50RB_High	Rear	/	21.84	23.5	0.396	0.46	0.677	0.79	0.05
1720	20050	50RB_High	Rear	/	21.85	22.5	0.423	0.49	0.695	0.81	-0.14
1720	20050	50RB_High	Left	/	21.85	22.5	0.085	0.10	0.148	0.17	-0.15
1720	20050	50RB_High	Bottom	/	21.85	22.5	0.296	0.34	0.546	0.63	-0.13
1732.5	20175	100RB	Rear	/	21.79	22.5	0.292	0.34	0.505	0.59	-0.01
1732.5	20175	100RB	Bottom	/	21.79	22.5	0.259	0.30	0.495	0.58	-0.03
1720	20050	1RB_High	Rear	Note	21.85	22.5	0.328	0.38	0.538	0.62	0.07

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-15: SAR Values (LTE Band5 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
844	20600	1RB-Mid	Left	Touch	/	22.61	23.5	0.165	0.20	0.239	0.29	0.09
844	20600	1RB-Mid	Left	Tilt	/	22.61	23.5	0.117	0.14	0.171	0.21	-0.03
844	20600	1RB-Mid	Right	Touch	Fig.15	22.61	23.5	0.236	0.29	0.308	0.38	0.02
844	20600	1RB-Mid	Right	Tilt	/	22.61	23.5	0.105	0.13	0.151	0.19	0.00
844	20600	25RB-High	Left	Touch	/	21.63	22.5	0.132	0.16	0.192	0.23	0.15
844	20600	25RB-High	Left	Tilt	/	21.63	22.5	0.094	0.11	0.137	0.17	0.02
844	20600	25RB-High	Right	Touch	/	21.63	22.5	0.166	0.20	0.244	0.30	0.15
844	20600	25RB-High	Right	Tilt	/	21.63	22.5	0.085	0.10	0.122	0.15	-0.01
844	20600	1RB_Low	Right	Touch	Note	22.61	23.5	0.197	0.24	0.287	0.35	-0.13

Note: SAR Values For Battery (HB3742A0Ezc+ (Sunwoda electronic Co., Ltd.))

Table 14.1-16: SAR Values (LTE Band5 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
844	20600	1RB-Mid	Front	/	22.61	23.5	0.241	0.30	0.340	0.42	0.00
844	20600	1RB-Mid	Rear	Fig.16	22.61	23.5	0.364	0.45	0.467	0.57	-0.02
844	20600	1RB-Mid	Left	/	22.61	23.5	0.176	0.22	0.263	0.32	0.03
844	20600	1RB-Mid	Bottom	/	22.61	23.5	0.053	0.06	0.090	0.11	-0.04
844	20600	25RB-High	Front	/	21.63	22.5	0.191	0.23	0.270	0.33	0.00
844	20600	25RB-High	Rear	/	21.63	22.5	0.253	0.31	0.356	0.43	-0.01
844	20600	25RB-High	Left	/	21.63	22.5	0.139	0.17	0.207	0.25	0.09
844	20600	25RB-High	Bottom	/	21.63	22.5	0.041	0.05	0.070	0.09	-0.12
844	20600	1RB_Low	Rear	Note	22.61	23.5	0.243	0.30	0.350	0.43	0.06

Note: SAR Values For Battery (HB3742A0Ezc+ (Sunwoda electronic Co., Ltd.))

Table 14.1-17: SAR Values (LTE Band7 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
2510	20850	1RB-Low	Left	Touch	Fig.17	22.23	23	0.128	0.15	0.249	0.30	0.11
2510	20850	1RB-Low	Left	Tilt	/	22.23	23	0.030	0.04	0.059	0.07	0.16
2510	20850	1RB-Low	Right	Touch	/	22.23	23	0.040	0.05	0.071	0.09	-0.13
2510	20850	1RB-Low	Right	Tilt	/	22.23	23	0.037	0.04	0.079	0.09	0.10
2510	20850	50RB-Mid	Left	Touch	/	21.08	22	0.102	0.13	0.195	0.24	0.06
2510	20850	50RB-Mid	Left	Tilt	/	21.08	22	0.025	0.03	0.050	0.06	0.01
2510	20850	50RB-Mid	Right	Touch	/	21.08	22	0.031	0.04	0.056	0.07	0.07
2510	20850	50RB-Mid	Right	Tilt	/	21.08	22	0.027	0.03	0.058	0.07	0.12
2510	20850	1RB-Low	Left	Touch	Note	22.30	23	0.112	0.13	0.210	0.25	0.16

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-18: SAR Values (LTE Band7 - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2510	20850	1RB_Low	Front	/	22.23	23	0.222	0.27	0.431	0.51	0.13
2510	20850	1RB_Low	Rear	/	22.23	23	0.203	0.24	0.394	0.47	0.18
2510	20850	1RB_Low	Left	/	22.23	23	0.090	0.11	0.168	0.20	0.02
2560	21350	1RB_Low	Bottom	/	22.08	23	0.370	0.46	0.757	0.94	0.06
2535	21100	1RB_Low	Bottom	/	22.08	23	0.392	0.48	0.818	1.01	0.07
2510	20850	1RB_Low	Bottom	Fig.18	22.23	23	0.425	0.51	0.880	1.05	0.09
2510	20850	50RB_Mid	Front	/	21.08	22	0.183	0.23	0.356	0.44	0.01
2510	20850	50RB_Mid	Rear	/	21.08	22	0.187	0.23	0.373	0.46	0.07
2510	20850	50RB_Mid	Left	/	21.08	22	0.0731	0.09	0.137	0.17	0.04
2510	20850	50RB_Mid	Bottom	/	21.08	22	0.298	0.37	0.629	0.78	-0.02
2510	20850	100RB	Bottom	/	21.07	22	0.316	0.39	0.669	0.83	0.07
2510	20850	1RB_Low	Bottom	Note	22.23	23	0.266	0.32	0.562	0.67	-0.04

Note: SAR Values For Battery (HB3742A0E2C+ (Sunwoda electronic Co., Ltd.))

Table 14.1-19: SAR Values (LTE Band12 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
711	23130	1RB-High	Left	Touch	Fig.19	22.77	23.5	0.092	0.11	0.130	0.15	0.15
711	23130	1RB-High	Left	Tilt	/	22.77	23.5	0.076	0.09	0.108	0.13	0.07
711	23130	1RB-High	Right	Touch	/	22.77	23.5	0.127	0.15	0.157	0.19	0.12
711	23130	1RB-High	Right	Tilt	/	22.77	23.5	0.072	0.08	0.102	0.12	0.01
711	23130	25RB-High	Left	Touch	/	21.70	22.5	0.071	0.09	0.101	0.12	0.14
711	23130	25RB-High	Left	Tilt	/	21.70	22.5	0.059	0.07	0.083	0.10	0.03
711	23130	25RB-High	Right	Touch	/	21.70	22.5	0.081	0.10	0.115	0.14	0.14
711	23130	25RB-High	Right	Tilt	/	21.70	22.5	0.055	0.07	0.078	0.09	0.06
711	23130	1RB-High	Right	Touch	Note	22.77	23.5	0.103	0.12	0.146	0.17	0.18

Note: SAR Values For Battery (HB3742A0EYC+ (Sunwoda electronic Co., Ltd.))

Table 14.1-20: SAR Values (LTE Band12 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
711	23130	1RB-High	Front	/	22.77	23.5	0.156	0.18	0.218	0.26	-0.02
711	23130	1RB-High	Rear	Fig.20	22.77	23.5	0.247	0.29	0.319	0.38	-0.01
711	23130	1RB-High	Left	/	22.77	23.5	0.095	0.11	0.140	0.17	-0.04
711	23130	1RB-High	Bottom	/	22.77	23.5	0.036	0.04	0.058	0.07	-0.10
711	23130	25RB-High	Front	/	21.70	22.5	0.118	0.14	0.165	0.20	-0.03
711	23130	25RB-High	Rear	/	21.70	22.5	0.154	0.19	0.216	0.26	-0.02
711	23130	25RB-High	Left	/	21.70	22.5	0.073	0.09	0.107	0.13	-0.01
711	23130	25RB-High	Bottom	/	21.70	22.5	0.027	0.03	0.044	0.05	-0.01
711	23130	1RB-High	Rear	Note	22.77	23.5	0.227	0.27	0.292	0.35	-0.08

Note: SAR Values For Battery (HB3742A0EYC+ (Sunwoda electronic Co., Ltd.))

Table 14.1-21: SAR Values (LTE Band17 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
711	23800	1RB-High	Left	Touch	/	22.79	23.5	0.105	0.12	0.149	0.18	0.17
711	23800	1RB-High	Left	Tilt	/	22.79	23.5	0.080	0.09	0.113	0.13	-0.06
711	23800	1RB-High	Right	Touch	Fig.21	22.79	23.5	0.134	0.16	0.166	0.20	-0.15
711	23800	1RB-High	Right	Tilt	/	22.79	23.5	0.084	0.10	0.119	0.14	0.07
711	23800	25RB-High	Left	Touch	/	21.67	22.5	0.080	0.10	0.114	0.14	0.13
711	23800	25RB-High	Left	Tilt	/	21.67	22.5	0.062	0.08	0.087	0.11	0.05
711	23800	25RB-High	Right	Touch	/	21.67	22.5	0.082	0.10	0.117	0.14	0.13
711	23800	25RB-High	Right	Tilt	/	21.67	22.5	0.064	0.08	0.090	0.11	0.10
711	23800	1RB-High	Right	Touch	Note	22.79	23.5	0.101	0.12	0.143	0.17	0.15

Note: SAR Values For Battery (HB3742A0Ezc+ (Sunwoda electronic Co., Ltd.))

Table 14.1-22: SAR Values (LTE Band17 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
711	23800	1RB-High	Front	/	22.79	23.5	0.131	0.15	0.183	0.22	-0.02
711	23800	1RB-High	Rear	Fig.22	22.79	23.5	0.187	0.22	0.247	0.29	0.00
711	23800	1RB-High	Left	/	22.79	23.5	0.072	0.08	0.105	0.12	0.01
711	23800	1RB-High	Bottom	/	22.79	23.5	0.033	0.04	0.055	0.06	-0.19
711	23800	25RB-High	Front	/	21.67	22.5	0.102	0.12	0.142	0.17	0.02
711	23800	25RB-High	Rear	/	21.67	22.5	0.134	0.16	0.189	0.23	-0.05
711	23800	25RB-High	Left	/	21.67	22.5	0.058	0.07	0.085	0.10	0.01
711	23800	25RB-High	Bottom	/	21.67	22.5	0.026	0.03	0.043	0.05	-0.08
711	23800	1RB-High	Rear	Note	22.79	23.5	0.16	0.19	0.206	0.21	0.12

Note: SAR Values For Battery (HB3742A0Ezc+ (Sunwoda electronic Co., Ltd.))

14.2 SAR results for Standard procedure

There is zoom scan measurement to be added for the highest measured SAR in each exposure configuration/band.

Table 14.2-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	Right	Touch	Fig.1	31.62	32.5	0.178	0.22	0.232	0.28	0.16

Table 14.2-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	GPRS (2)	Rear	Fig.2	30.75	31.5	0.576	0.68	0.741	0.88	-0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	661	Right	Touch	Fig.3	28.64	29.7	0.083	0.11	0.136	0.17	0.13

Table 14.2-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	GPRS (2)	Bottom	Fig.4	27.29	27.7	0.665	0.73	1.330	1.46	0.00

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
846.6	4233	Right	Touch	Fig.5	23.37	24.5	0.257	0.33	0.342	0.44	0.08

Table 14.2-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
846.6	4233	Rear	Fig.6	23.37	24.5	0.406	0.53	0.525	0.68	-0.01

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-7: SAR Values (WCDMA 1700 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g)	Reported SAR(10g)	Measured SAR(1g)	Reported SAR(1g)	Power Drift
MHz	Ch.						(W/kg)	(W/kg)	(W/kg)	(W/kg)	
1712.4	1537	Right	Touch	Fig.7	23.56	24	0.293	0.32	0.463	0.51	0.11

Table 14.2-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1752.6	1738	Bottom	/	23.25	24	0.559	0.66	1.090	1.30	0.13

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-9: SAR Values (WCDMA 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g)	Reported SAR(10g)	Measured SAR(1g)	Reported SAR(1g)	Power Drift (dB)
MHz	Ch.						(W/kg)	(W/kg)	(W/kg)	(W/kg)	
1852.4	9662	Right	Touch	Fig.9	22.90	23.3	0.149	0.16	0.237	0.26	0.13

Table 14.2-10: SAR Values (WCDMA 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1907.6	9938	Bottom	Fig.10	22.88	23.3	0.653	0.72	1.310	1.44	0.10

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-11: SAR Values (LTE Band2 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1900	19100	1RB-High	Right	Touch	Fig.11	23.1	24	0.127	0.13	0.228	0.28	-0.15

Table 14.2-12: SAR Values (LTE Band2 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1900	19100	1RB_High	Bottom	Fig.12	23.10	24	0.538	0.66	1.090	1.34	-0.05

Table 14.2-13: SAR Values (LTE Band4 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1720	20050	1RB-High	Right	Touch	Fig.13	22.92	23.5	0.281	0.32	0.442	0.51	0.13

Table 14.2-14: SAR Values (LTE Band4 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1720	20050	1RB_High	Rear	Fig.14	22.92	23.5	0.497	0.57	0.774	0.88	-0.05

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-15: SAR Values (LTE Band5 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
844	20600	1RB-Mid	Right	Touch	Fig.15	22.61	23.5	0.236	0.29	0.308	0.38	0.02

Table 14.2-16: SAR Values (LTE Band5 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
844	20600	1RB-Mid	Rear	Fig.16	22.61	23.5	0.364	0.45	0.467	0.57	-0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-17: SAR Values (LTE Band7 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
2510	20850	1RB-Low	Left	Touch	Fig.17	22.23	23	0.128	0.15	0.249	0.30	0.11

Table 14.2-18: SAR Values (LTE Band7 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2510	20850	1RB_Low	Bottom	Fig.18	22.23	23	0.425	0.51	0.880	1.05	0.09

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-19: SAR Values (LTE Band12 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
711	23130	1RB-High	Right	Touch	/	22.77	23.5	0.127	0.15	0.157	0.19	0.12

Table 14.2-20: SAR Values (LTE Band12 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
711	23130	1RB-High	Rear	Fig.20	22.77	23.5	0.247	0.29	0.319	0.38	-0.01

Table 14.2-21: SAR Values (LTE Band17 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
711	23800	1RB-High	Right	Touch	Fig.21	22.79	23.5	0.134	0.16	0.166	0.20	-0.15

Table 14.2-22: SAR Values (LTE Band17 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
711	23800	1RB-High	Rear	Fig.22	22.79	23.5	0.187	0.22	0.247	0.29	0.00

14.3 WLAN Evaluation

According to the KDB248227 D01, SAR is measured for 2.4GHz 802.11b DSSS using the initial test position procedure.

Head Evaluation

Table 14.3-1: SAR Values (WLAN - Head) – 802.11b 5.5Mbps (Fast SAR)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2462	11	Left	Touch	/	16.03	16.5	0.433	0.48	0.809	0.90	-0.05
2462	11	Left	Tilt	/	16.03	16.5	0.305	0.34	0.567	0.63	0.06
2462	11	Right	Touch	/	16.03	16.5	0.323	0.36	0.607	0.68	-0.08
2462	11	Right	Tilt	/	16.03	16.5	0.297	0.33	0.557	0.62	0.03

As shown above table, the initial test position for head is “Left Touch”. So the head SAR of WLAN is presented as below:

Table 14.3-2: SAR Values (WLAN - Head) – 802.11b 5.5Mbps (Full SAR)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2462	11	Left	Touch	Fig.23	16.03	16.5	0.412	0.46	0.899	1.00	-0.05
2462	11	Right	Touch	/	16.03	16.5	0.334	0.37	0.635	0.71	-0.08
2437	6	Left	Touch	/	15.87	16.5	0.341	0.39	0.744	0.86	0.07

Note1: When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg.

Note2: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. A maximum transmission duty factor of 85.0% is achievable for WLAN in this project and the scaled reported SAR is presented as below.

Table 14.3-3: SAR Values (WLAN - Head) – 802.11b 5.5Mbps (Scaled Reported SAR)

Ambient Temperature: 23.0 °C					Liquid Temperature: 22.5 °C		
Frequency		Side	Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g) (W/kg)	Scaled reported SAR (1g) (W/kg)
MHz	Ch.						
2462	11	Left	Touch	85.0%	100%	1.00	1.18
2462	11	Right	Touch	85.0%	100%	0.72	0.85

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.

Table 14.3-4: SAR Values For Battery2 (HB3742A0EZC+ (Sunwoda electronic Co., Ltd.))

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)	Note
MHz	Ch.										
2462	11	Left	Touch	16.03	16.5	0.314	0.35	0.684	0.76	-0.13	Battery2

Body Evaluation

Table 14.3-5: SAR Values (WLAN - Body) – 802.11b 5.5Mbps (Fast SAR)

Ambient Temperature: 23.0 °C											Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)					
MHz	Ch.														
2462	11	Front	/	16.03	16.5	0.084	0.09	0.153	0.17	0.03					
2462	11	Rear	/	16.03	16.5	0.094	0.10	0.175	0.20	0.00					
2462	11	Left	/	16.03	16.5	0.046	0.05	0.098	0.11	0.10					
2462	11	Top	/	16.03	16.5	0.119	0.13	0.231	0.26	0.05					

As shown above table, the initial test position for body is “Top”. So the body SAR of WLAN is presented as below:

Table 14.3-6: SAR Values (WLAN - Body) – 802.11b 5.5Mbps (Full SAR)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2462	11	Top	Fig.24	16.03	16.5	0.133	0.15	0.247	0.28	0.05
2462	11	Rear	/	16.03	16.5	0.104	0.12	0.193	0.22	0.00

Note1: When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg.

Note2: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

Table 14.3-7: SAR Values For Battery (HB3742A0EZC+ (Sunwoda electronic Co., Ltd.))


Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C										
Frequency		Test Position	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)	Note
MHz	Ch.									
2462	11	Top	16.03	16.5	0.181	0.20	0.0997	0.11	0.05	Battery2

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. A maximum transmission duty factor of 85.0% is achievable for WLAN in this project and the scaled reported SAR is presented as below.

Table 14.3-8: SAR Values (WLAN - Body) – 802.11b 5.5Mbps (Scaled Reported SAR)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C						
Frequency		Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g) (W/kg)	Scaled reported SAR (1g) (W/kg)
MHz	Ch.					
2462	11	Top	85.0%	100%	0.28	0.33
2462	11	Rear	85.0%	100%	0.22	0.26

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.



Picture 14.1 The plot of duty factor

15 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Table 15.1: SAR Measurement Variability for Body GSM 1900 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1909.8	810	Bottom	10	1.33	1.32	1.01	/

Table 15.2 SAR Measurement Variability for Body WCDMA 1900 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1907.6	9938	Bottom	10	1.31	1.30	1.01	/

Table 15.3 SAR Measurement Variability for Body WCDMA 1700 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1752.6	1738	Bottom	10	1.09	1.08	1.01	/

Table 15.4 SAR Measurement Variability for Body LTE Band 2 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1900	19100	Bottom	10	1.09	1.08	1.01	/

Table 15.5 SAR Measurement Variability for Body LTE Band 7 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
2510	20850	Bottom	10	0.88	0.86	1.02	/

Table 15.6: SAR Measurement Variability for Head WLAN (1g)

Frequency		Side	Test Position	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
2462	11	Right	Touch	0.899	0.879	1.02	/

16 Measurement Uncertainty

16.1 Measurement Uncertainty for Normal SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	5.5	N	1	1	1	5.5	5.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521

Combined standard uncertainty	$u_c' = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$					9.25	9.12	257
Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$					18.5	18.2	

16.2 Measurement Uncertainty for Normal SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.5	N	1	1	1	6.5	6.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	∞
13	Post-processing	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43

20	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c' = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$						10.8	10.7	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						21.6	21.4	

16.3 Measurement Uncertainty for Fast SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	5.5	N	1	1	1	5.5	5.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	7.0	R	$\sqrt{3}$	1	1	4.0	4.0	∞
Test sample related										
15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞

Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c' = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						10.1	9.95	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						20.2	19.9	

16.4 Measurement Uncertainty for Fast SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.5	N	1	1	1	6.5	6.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	14.0	R	$\sqrt{3}$	1	1	8.1	8.1	∞
Test sample related										

15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						13.3	13.2	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						26.6	26.4	

17 MAIN TEST INSTRUMENTS

Table 17.1: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	E5071C	MY46110673	February 03, 2015	One year
02	Dielectric Probe Kit	85070E	Agilent	No Calibration Requested	
03	Power meter	NRVD	102196	March 03, 2015	One year
04	Power sensor	NRV-Z5	100596		
05	Power sensor	NRV-Z5	100595	September 16, 2015	One year
06	Signal Generator	E4438C	MY49071430	February 02, 2015	One year
07	Amplifier	60S1G4	0331848	No Calibration Requested	
08	Directional Coupler	778D	MY48220584	No Calibration Requested	
09	Directional Coupler	772D	MY46151265	No Calibration Requested	
10	BTS	E5515C	MY50263375	January 30, 2015	One year
11	BTS	CMW500	129942	March 03, 2015	One year
12	E-field Probe	SPEAG EX3DV4	3617	August 26, 2015	One year
13	DAE	SPEAG DAE4	777	August 26, 2015	One year
14	Dipole Validation Kit	SPEAG D835V2	4d069	July 23, 2015	One year
15	Dipole Validation Kit	SPEAG D1750V2	1003	July 16, 2015	One year
16	Dipole Validation Kit	SPEAG D1900V2	5d101	July 23, 2015	One year
17	Dipole Validation Kit	SPEAG D2450V2	853	July 24, 2015	One year

END OF REPORT BODY

ANNEX A Graph Results

850 Right Cheek High

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Head 850 MHz

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 0.901$ mho/m; $\epsilon_r = 43.06$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: EX3DV4 - SN3617 ConvF(9.58, 9.58, 9.58)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.254 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.415 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.291 W/kg

SAR(1 g) = 0.232 W/kg; SAR(10 g) = 0.178 W/kg

Maximum value of SAR (measured) = 0.250 W/kg




Fig.1 850MHz




Fig. 1-1 Z-Scan at power reference point (850 MHz)

850 Body Rear High

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Body 850 MHz

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 0.952$ mho/m; $\epsilon_r = 56.21$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: GSM 850 GPRS Frequency: 848.8 MHz Duty Cycle: 1:4

Probe: EX3DV4 - SN3617 ConvF(9.71, 9.71, 9.71)

Area Scan (121x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.810 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.55 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.930 W/kg

SAR(1 g) = 0.741 W/kg; SAR(10 g) = 0.576 W/kg

Maximum value of SAR (measured) = 0.772 W/kg




Fig.2 850 MHz




Fig. 2-1 Z-Scan at power reference point (850 MHz)

1900 Right Cheek Middle

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters use (interpolated): $f = 1880$ MHz; $\sigma = 1.397$ mho/m; $\epsilon_r = 39.48$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: EX3DV4 - SN3617 ConvF(8.07, 8.07, 8.07)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.175 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.815 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.209 W/kg

SAR(1 g) = 0.136 W/kg; SAR(10 g) = 0.083 W/kg

Maximum value of SAR (measured) = 0.174 W/kg




Fig.3 1900 MHz




Fig. 3-1 Z-Scan at power reference point (1900 MHz)

1900 Body Bottom High

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used (interpolated): $f = 1909.8$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 54.35$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz GPRS Frequency: 1909.8 MHz Duty Cycle: 1:4

Probe: EX3DV4 - SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (121x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.66 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.87 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 2.41 W/kg

SAR(1 g) = 1.33 W/kg; SAR(10 g) = 0.665 W/kg

Maximum value of SAR (measured) = 1.50 W/kg




Fig.4 1900 MHz




Fig.4-1 Z-Scan at power reference point (1900 MHz)

WCDMA 850 Right Cheek High

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Head 850 MHz

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.884$ mho/m; $\epsilon_r = 40.518$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.58, 9.58, 9.58)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.384 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.060 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.449 W/kg

SAR(1 g) = 0.342 W/kg; SAR(10 g) = 0.257 W/kg

Maximum value of SAR (measured) = 0.375 W/kg




Fig.5 WCDMA 850




Fig. 5-1 Z-Scan at power reference point (WCDMA 850)

WCDMA 850 Body Rear High

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Body 850 MHz

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.911$ mho/m; $\epsilon_r = 55.289$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.71, 9.71, 9.71)

Area Scan (121x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.607 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.63 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.669 W/kg

SAR(1 g) = 0.525 W/kg; SAR(10 g) = 0.406 W/kg

Maximum value of SAR (measured) = 0.602 W/kg




Fig.6 WCDMA 850




Fig. 6-1 Z-Scan at power reference point (WCDMA850)

WCDMA 1700 Right Cheek Low

Date: 2015-12-27

Electronics: DAE4 Sn777

Medium: Head 1750 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.124$ mho/m; $\epsilon_r = 37.53$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: WCDMA 1700 Frequency: 1712.4 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(8.34, 8.34, 8.34)

Area Scan (71x111x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.551 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.200 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.690 W/kg

SAR(1 g) = 0.463 W/kg; SAR(10 g) = 0.293 W/kg

Maximum value of SAR (measured) = 0.537 W/kg




Fig.7 1700MHz




Fig. 7-1 Z-Scan at power reference point (1700 MHz)

WCDMA 1700 Body Bottom High

Date: 2015-12-19

Electronics: DAE4 Sn777

Medium: Body 1750 MHz

Medium parameters used (interpolated): $f = 1752.6$ MHz; $\sigma = 1.562$ mho/m; $\epsilon_r = 52.899$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: WCDMA 1700 Frequency: 1752.6 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.96, 7.96, 7.96)

Area Scan (121x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.31 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.93 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.559 W/kg

Maximum value of SAR (measured) = 1.37 W/kg




Fig.8 1700 MHz




Fig. 8-1 Z-Scan at power reference point (1700 MHz)

WCDMA 1900 Right Cheek Low

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.257$ mho/m; $\epsilon_r = 38.98$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: WCDMA 1900 Frequency: 1852.4 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617ConvF(8.07, 8.07, 8.07)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.303 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.194 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.360 W/kg

SAR(1 g) = 0.237 W/kg; SAR(10 g) = 0.149 W/kg

Maximum value of SAR (measured) = 0.298 W/kg




Fig.9 WCDMA1900




Fig. 9-1 Z-Scan at power reference point (WCDMA1900)

WCDMA 1900 Body Bottom High

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used: $f = 1907.6$ MHz; $\sigma = 1.564$ mho/m; $\epsilon_r = 54.146$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: WCDMA 1900 Frequency: 1907.6 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (121x71x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 1.60 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 23.00 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 2.35 W/kg

SAR(1 g) = 1.31 W/kg; SAR(10 g) = 0.653 W/kg

Maximum value of SAR (measured) = 1.49 W/kg




Fig.10 WCDMA1900




Fig. 10-1 Z-Scan at power reference point (WCDMA1900)

LTE Band2 Right Cheek High with QPSK_20M_1RB_High

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.427$ mho/m; $\epsilon_r = 39.78$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band2 Frequency: 1900MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(8.07, 8.07, 8.07)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.313 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.782 V/m; Power Drift = 0.12dB

Peak SAR (extrapolated) = 0.873 W/kg

SAR(1 g) = 0.228 W/kg; SAR(10 g) = 0.127 W/kg

Maximum value of SAR (measured) = 0.272 W/kg




Fig.11 LTE Band2




Fig. 11-1 Z-Scan at power reference point (LTE Band2)

LTE Band2 Body Bottom High with QPSK_20M_1RB_High

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.55$ mho/m; $\epsilon_r = 54.05$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band2 Frequency: 1900 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (121x71x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 1.43 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 25.65 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.96 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.538 W/kg

Maximum value of SAR (measured) = 1.22 W/kg




Fig.12 LTE Band2




Fig. 12-1 Z-Scan at power reference point (LTE Band2)

LTE Band4 Right Cheek Low with QPSK_20M_1RB_High

Date: 2015-12-27

Electronics: DAE4 Sn777

Medium: Head 1750 MHz

Medium parameters used (interpolated): $f = 1720$ MHz; $\sigma = 1.235$ mho/m; $\epsilon_r = 47.91$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band4 Frequency: 1720 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(8.34, 8.34, 8.34)

Area Scan (71x111x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.517 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.660 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.654 W/kg

SAR(1 g) = 0.442 W/kg; SAR(10 g) = 0.281 W/kg

Maximum value of SAR (measured) = 0.517 W/kg




Fig.13 LTE Band4




Fig. 13-1 Z-Scan at power reference point (LTE Band4)

LTE Band4 Body Bottom Low with QPSK_20M_1RB_High

Date: 2015-12-27

Electronics: DAE4 Sn777

Medium: Body 1750 MHz

Medium parameters used (interpolated): $f = 1745$ MHz; $\sigma = 1.329$ mho/m; $\epsilon_r = 51.022$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band4 Frequency: 1720 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.96, 7.96, 7.96)

Area Scan (121x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.966 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.39 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.774 W/kg; SAR(10 g) = 0.497 W/kg

Maximum value of SAR (measured) = 0.915 W/kg




Fig.14 LTE Band4




Fig. 14-1 Z-Scan at power reference point (LTE Band4)

LTE Band5 Right Cheek High with QPSK_10M_1RB_Low

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Head 850 MHz

Medium parameters used (interpolated): $f = 844$ MHz; $\sigma = 0.936$ mho/m; $\epsilon_r = 41.551$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band5 Frequency: 844 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.58, 9.58, 9.58)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.347 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.290 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.387 W/kg

SAR(1 g) = 0.308 W/kg; SAR(10 g) = 0.236 W/kg

Maximum value of SAR (measured) = 0.324 W/kg




Fig.15 LTE Band5




Fig. 15-1 Z-Scan at power reference point (LTE Band5)

LTE Band5 Body Rear High with QPSK_10M_1RB_Low

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Body 850 MHz

Medium parameters used (interpolated): $f = 844$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 57.031$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band5 Frequency: 844 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.71, 9.71, 9.71)

Area Scan (121x71x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.510 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 21.75 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.581 W/kg

SAR(1 g) = 0.467 W/kg; SAR(10 g) = 0.364 W/kg

Maximum value of SAR (measured) = 0.486 W/kg




Fig.16 LTE Band5




Fig. 16-1 Z-Scan at power reference point (LTE Band5)

LTE Band7 Left Cheek Low with QPSK_20M_1RB_Low

Date: 2015-12-29

Electronics: DAE4 Sn777

Medium: Head 2450 MHz

Medium parameters used: $f = 2510$ MHz; $\sigma = 1.922$ mho/m; $\epsilon_r = 39.01$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band7 Frequency: 2510 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.24, 7.24, 7.24)

Area Scan (81x141x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.304 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.543 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.489 W/kg

SAR(1 g) = 0.249 W/kg; SAR(10 g) = 0.128 W/kg

Maximum value of SAR (measured) = 0.311 W/kg




Fig.17 LTE Band7




Fig. 17-1 Z-Scan at power reference point (LTE Band7)

LTE Band7 Body Bottom Low with QPSK_20M_1RB_Low

Date: 2015-12-29

Electronics: DAE4 Sn777

Medium: Body 2450 MHz

Medium parameters used: $f = 2510$ MHz; $\sigma = 2.126$ mho/m; $\epsilon_r = 56.054$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: LTE Band17 Frequency: 2510 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(7.35, 7.35, 7.35)

Area Scan (121x71x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 1.17 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.84 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.70 W/kg

SAR(1 g) = 0.880 W/kg; SAR(10 g) = 0.425 W/kg

Maximum value of SAR (measured) = 0.961 W/kg




Fig.18 LTE Band7




Fig. 18-1 Z-Scan at power reference point (LTE Band7)

LTE Band12 Right Cheek High with QPSK_10M_1RB_High

Date: 2015-12-25

Electronics: DAE4 Sn777

Medium: Head 750 MHz

Medium parameters used (interpolated): $f = 711$ MHz; $\sigma = 0.869$ mho/m; $\epsilon_r = 42.832$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C

Communication System: LTE Band12 Frequency: 711 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.98, 9.98, 9.98)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.169 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.071 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.185 W/kg

SAR(1 g) = 0.157 W/kg; SAR(10 g) = 0.127 W/kg

Maximum value of SAR (measured) = 0.164 W/kg




Fig.19 LTE Band12




Fig. 19-1 Z-Scan at power reference point (LTE Band12)

LTE Band12 Body Rear High with QPSK_10M_1RB_Low

Date: 2015-12-25

Electronics: DAE4 Sn777

Medium: Body 750 MHz

Medium parameters used (interpolated): $f = 711$ MHz; $\sigma = 0.921$ mho/m; $\epsilon_r = 56.574$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C

Communication System: LTE Band12 Frequency: 711 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.76, 9.76, 9.76)

Area Scan (121x71x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.345 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.85 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.402 W/kg

SAR(1 g) = 0.319 W/kg; SAR(10 g) = 0.247 W/kg

Maximum value of SAR (measured) = 0.332 W/kg




Fig.20 LTE Band12




Fig. 20-1 Z-Scan at power reference point (LTE Band12)

LTE Band17 Right Cheek High with QPSK_10M_1RB_High

Date: 2015-10-17

Electronics: DAE4 Sn777

Medium: Head 750 MHz

Medium parameters used (interpolated): $f = 711$ MHz; $\sigma = 0.869$ mho/m; $\epsilon_r = 42.832$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C

Communication System: LTE Band17 Frequency: 711 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.98, 9.98, 9.98)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.186 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.384 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.195 W/kg

SAR(1 g) = 0.166 W/kg; SAR(10 g) = 0.134 W/kg

Maximum value of SAR (measured) = 0.171 W/kg




Fig.21 LTE Band17




Fig. 21-1 Z-Scan at power reference point (LTE Band17)

LTE Band17 Body Rear High with QPSK_10M_1RB_Low

Date: 2015-12-25

Electronics: DAE4 Sn777

Medium: Body 750 MHz

Medium parameters used (interpolated): $f = 711$ MHz; $\sigma = 0.921$ mho/m; $\epsilon_r = 56.574$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C

Communication System: LTE Band17 Frequency: 711 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.76, 9.76, 9.76)

Area Scan (121x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.270 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.40 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.319 W/kg

SAR(1 g) = 0.247 W/kg; SAR(10 g) = 0.187 W/kg

Maximum value of SAR (measured) = 0.258 W/kg




Fig.22 LTE Band17




Fig. 22-1 Z-Scan at power reference point (LTE Band17)

Wifi 802.11b Left Cheek Channel 11

Date: 2015-12-29

Electronics: DAE4 Sn777

Medium: Head 2450 MHz

Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.527$ mho/m; $\epsilon_r = 40.156$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: Wlan 2450 Frequency: 2462 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.24, 7.24, 7.24)

Area Scan (81x141x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.28 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.98 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 2.48 W/kg

SAR(1 g) = 0.899 W/kg; SAR(10 g) = 0.412 W/kg

Maximum value of SAR (measured) = 1.23 W/kg




Fig.23 2450 MHz




Fig. 23-1 Z-Scan at power reference point (2450 MHz)

Wifi 802.11b Body Top Channel 11

Date: 2015-12-29

Electronics: DAE4 Sn777

Medium: Body 2450 MHz

Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 2.226$ mho/m; $\epsilon_r = 53.949$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: Wlan 2450 Frequency: 2462 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.35, 7.35, 7.35)

Area Scan (121x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.296 W/kg

Top Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.72 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.431 W/kg

SAR(1 g) = 0.247 W/kg; SAR(10 g) = 0.133 W/kg

Maximum value of SAR (measured) = 0.275 W/kg




Fig.24 2450 MHz




Fig. 24-1 Z-Scan at power reference point (2450 MHz)

ANNEX B System Verification Results

750MHz

Date: 2015-12-25

Electronics: DAE4 Sn777

Medium: Head 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.912 \text{ mho/m}$; $\epsilon_r = 43.08$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 750 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.98, 9.98, 9.98)

System Validation /Area Scan (81x191x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Reference Value = 49.848 V/m ; Power Drift = -0.09 dB

Fast SAR: SAR(1 g) = 2.08 W/kg ; SAR(10 g) = 1.37 W/kg

Maximum value of SAR (interpolated) = 2.23 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 49.848 V/m ; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 2.88 W/kg

SAR(1 g) = 2.07 W/kg ; SAR(10 g) = 1.35 W/kg

Maximum value of SAR (measured) = 2.19 W/kg



$0 \text{ dB} = 2.19 \text{ W/kg} = 3.40 \text{ dB W/kg}$

Fig.B.1 validation 750MHz 250mW

750MHz

Date: 2015-12-25

Electronics: DAE4 Sn777

Medium: Body750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.946 \text{ mho/m}$; $\epsilon_r = 56.98$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.9°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 750 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(9.76, 9.76, 9.76)

System Validation/Area Scan (81x191x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Reference Value = 51.994 V/m ; Power Drift = -0.06 dB

Fast SAR: SAR(1 g) = 2.24 W/kg ; SAR(10 g) = 1.49 W/kg

Maximum value of SAR (interpolated) = 2.39 W/kg


System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.994 V/m ; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 3.06 W/kg

SAR(1 g) = 2.21 W/kg ; SAR(10 g) = 1.45 W/kg

Maximum value of SAR (measured) = 2.38 W/kg



0 dB = 2.38 W/kg = 3.76 dB W/kg

Fig.B.2 validation 750MHz 250mW

835MHz

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Head 850 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.921 \text{ S/m}$; $\epsilon_r = 41.12$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(9.58, 9.58, 9.58)

System Validation /Area Scan (81x161x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Reference Value = 51.281 V/m ; Power Drift = 0.07 dB

Fast SAR: SAR(1 g) = 2.27 W/kg ; SAR(10 g) = 1.47 W/kg

Maximum value of SAR (interpolated) = 2.50 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.281 V/m ; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 3.58 W/kg

SAR(1 g) = 2.31 W/kg ; SAR(10 g) = 1.50 W/kg

Maximum value of SAR (measured) = 2.53 W/kg



$0 \text{ dB} = 2.53 \text{ W/kg} = 4.03 \text{ dBW/kg}$

Fig.B.3 validation 835MHz 250mW

835MHz

Date: 2015-12-26

Electronics: DAE4 Sn777

Medium: Body 850 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.972 \text{ S/m}$; $\epsilon_r = 56.23$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(9.71, 9.71, 9.71)

System Validation /Area Scan (81x171x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Reference Value = 51.697 V/m ; Power Drift = 0.05 dB

Fast SAR: SAR(1 g) = 2.31 W/kg ; SAR(10 g) = 1.53 W/kg

Maximum value of SAR (interpolated) = 2.51 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.697 V/m ; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 3.52 W/kg

SAR(1 g) = 2.34 W/kg ; SAR(10 g) = 1.55 W/kg

Maximum value of SAR (measured) = 2.53 W/kg



0 dB = 2.53 W/kg = 4.03 dBW/kg

Fig.B.4 validation 835MHz 250mW

1750MHz

Date: 2015-12-27

Electronics: DAE4 Sn777

Medium: Head 1750 MHz

Medium parameters used: $f=1750$ MHz; $\sigma=1.331$ mho/m; $\epsilon_r=39.53$; $\rho=1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 1750 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(8.34, 8.34, 8.34)

System Validation/Area Scan (81x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Reference Value = 92.78 V/m; Power Drift = -0.05 dB

Fast SAR: SAR(1 g) = 8.98 W/kg; SAR(10 g) = 4.79 W/kg

Maximum value of SAR (interpolated) = 10.05 W/kg


System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 92.78 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 15.64 W/kg

SAR(1 g) = 9.11 W/kg; SAR(10 g) = 4.89 W/kg

Maximum value of SAR (measured) = 10.15 W/kg



0 dB = 10.15 W/kg = 10.06 dB W/kg

Fig.B.5 validation 1750MHz 250mW

1750MHz

Date: 2015-12-27

Electronics: DAE4 Sn777

Medium: Body 1750 MHz

Medium parameters used: $f=1750$ MHz; $\sigma = 1.472$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 1750 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(7.96, 7.96, 7.96)

System Validation/Area Scan (81x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Reference Value = 95.477 V/m; Power Drift = -0.03 dB

Fast SAR: SAR(1 g) = 9.45 W/kg; SAR(10 g) = 5.09 W/kg

Maximum value of SAR (interpolated) = 10.34 W/kg


System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 95.477 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 16.29 W/kg

SAR(1 g) = 9.34 W/kg; SAR(10 g) = 5.02 W/kg

Maximum value of SAR (measured) = 10.24 W/kg



0 dB = 10.24 W/kg = 10.10 dB W/kg

Fig.B.6 validation 1750MHz 250mW

1900MHz

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.427$ S/m; $\epsilon_r = 39.78$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 1900 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(8.07, 8.07, 8.07)

System Validation /Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 93.339 V/m; Power Drift = 0.05 dB

Fast SAR: SAR(1 g) = 10.61 W/kg; SAR(10 g) = 5.67 W/kg

Maximum value of SAR (interpolated) = 12.01 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.339 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 19.02 W/kg

SAR(1 g) = 10.41 W/kg; SAR(10 g) = 5.49 W/kg

Maximum value of SAR (measured) = 11.81 W/kg



0 dB = 11.81 W/kg = 10.72 dBW/kg

Fig.B.7 validation 1900MHz 250mW

1900MHz

Date: 2015-12-28

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.550$ S/m; $\epsilon_r = 54.05$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 1900 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(7.74, 7.74, 7.74)

System validation /Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 66.021 V/m; Power Drift = -0.02 dB

Fast SAR: SAR(1 g) = 10.56 W/kg; SAR(10 g) = 5.65 W/kg

Maximum value of SAR (interpolated) = 12.56 W/kg


System validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 66.021 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 19.38 W/kg

SAR(1 g) = 10.36 W/kg; SAR(10 g) = 5.51 W/kg

Maximum value of SAR (measured) = 12.36 W/kg



0 dB = 12.36 W/kg = 10.92 dBW/kg

Fig.B.8 validation 1900MHz 250mW

2450MHz

Date: 2015-12-29

Electronics: DAE4 Sn777

Medium: Head 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.822$ mho/m; $\epsilon_r = 38.01$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 2450 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.24, 7.24, 7.24)

System Validation /Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 90.14 V/m; Power Drift = 0.02 dB

SAR(1 g) = 13.31 W/kg; SAR(10 g) = 6.33W/kg

Maximum value of SAR (interpolated) = 16.61 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.14 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 27.23 W/kg

SAR(1 g) = 13.11 W/kg; SAR(10 g) = 6.12W/kg

Maximum value of SAR (measured) = 16.41 W/kg



0 dB = 16.41W/kg = 12.15 dBW/kg

Fig.B.9 validation 2450MHz 250mW

2450MHz

Date: 2015-12-29

Electronics: DAE4 Sn777

Medium: Body 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.974$ S/m; $\epsilon_r = 51.63$; $\rho = 1000$ kg/m³

Ambient Temperature: 23.0°C Liquid Temperature: 22.5°C

Communication System: CW Frequency: 2450 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3617 ConvF(7.35, 7.35, 7.35)

System Validation/Area Scan (81x101x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Reference Value = 88.947 V/m; Power Drift = -0.03 dB

SAR(1 g) = 12.49 W/kg; SAR(10 g) = 5.80 W/kg

Maximum value of SAR (interpolated) = 14.59W/kg


System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 88.947 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 25.00 W/kg

SAR(1 g) = 12.69 W/kg; SAR(10 g) = 5.98 W/kg

Maximum value of SAR (measured) = 14.79 W/kg



0 dB = 14.79 W/kg = 11.69 dB W/kgz

Fig.B.10 validation 2450MHz 250mW

The SAR system verification must be required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR.


Table B.1 Comparison between area scan and zoom scan for system verification

Date	Band	Position	Area scan (1g)	Zoom scan (1g)	Drift (%)
2015-12-25	750	Head	2.08	2.07	0.48
	750	Body	2.24	2.21	1.36
2015-12-26	835	Head	2.27	2.31	-1.73
	835	Body	2.31	2.34	-1.28
2015-12-27	1750	Head	8.98	9.11	-1.43
	1750	Body	9.45	9.34	1.18
2015-12-28	1900	Head	10.61	10.41	1.92
	1900	Body	10.56	10.36	1.93
2015-12-29	2450	Head	13.31	13.11	1.53
	2450	Body	12.49	12.69	-1.58

ANNEX C SAR Measurement Setup

C.1 Measurement Set-up

The Dasy4 or DASY5 system for performing compliance tests is illustrated above graphically. This system consists of the following items:



Picture C.1 SAR Lab Test Measurement Set-up

- A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY4 or DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

C.2 Dasy4 or DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 or DASY5 software reads the reflection during a software approach and looks for the maximum using 2nd order curve fitting. The approach is stopped at reaching the maximum.

Probe Specifications:

Model:	ES3DV3, EX3DV4
Frequency	10MHz — 6.0GHz(EX3DV4)
Range:	10MHz — 4GHz(ES3DV3)
Calibration:	In head and body simulating tissue at Frequencies from 835 up to 5800MHz
Linearity:	± 0.2 dB(30 MHz to 6 GHz) for EX3DV4 ± 0.2 dB(30 MHz to 4 GHz) for ES3DV3
Dynamic Range:	10 mW/kg — 100W/kg
Probe Length:	330 mm
Probe Tip	
Length:	20 mm
Body Diameter:	12 mm
Tip Diameter:	2.5 mm (3.9 mm for ES3DV3)
Tip-Center:	1 mm (2.0mm for ES3DV3)
Application:	SAR Dosimetry Testing Compliance tests of devices Dosimetry in strong gradient fields



Picture C.2 Near-field Probe



Picture C.3 E-field Probe

C.3 E-field Probe Calibration

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed

in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/ cm².

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m³).

C.4 Other Test Equipment

C.4.1 Data Acquisition Electronics(DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



PictureC.4: DAE

C.4.2 Robot

The SPEAG DASY system uses the high precision robots (DASY4: RX90XL; DASY5: RX160L) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)



Picture C.5 DASY 4



Picture C.6 DASY 5

C.4.3 Measurement Server

The Measurement server is based on a PC/104 CPU board with CPU (dasy4: 166 MHz, Intel Pentium; DASY5: 400 MHz, Intel Celeron), chipdisk (DASY4: 32 MB; DASY5: 128MB), RAM (DASY4: 64 MB, DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.



Picture C.7 Server for DASY 4



Picture C.8 Server for DASY 5

C.4.4 Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce a SAR uncertainty of $\pm 20\%$. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss

POM material having the following dielectric


parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.



Picture C.9-1: Device Holder



Picture C.9-2: Laptop Extension Kit

C.4.5 Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to

Represent the 90th percentile of the population. The phantom enables the dissymmetric evaluation

of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

Shell Thickness: 2 ± 0.2 mm

Filling Volume: Approx. 25 liters

Dimensions: 810 x 1000 x 500 mm (H x L x W)

Available: Special




Picture C.10: SAM Twin Phantom

ANNEX D Position of the wireless device in relation to the phantom

D.1 General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.




w_t Width of the handset at the level of the acoustic

w_b Width of the bottom of the handset


A Midpoint of the width w_t of the handset at the level of the acoustic output

B Midpoint of the width w_b of the bottom of the handset

Picture D.1-a Typical “fixed” case handset Picture D.1-b Typical “clam-shell” case handset




Picture D.2 Cheek position of the wireless device on the left side of SAM



Picture D.3 Tilt position of the wireless device on the left side of SAM

D.2 Body-worn device

A typical example of a body-worn device is a device, wireless enabled PDA or other battery operated wireless device with the ability to transmit while mounted on a person's body using a carry accessory approved by the wireless device manufacturer.




Picture D.4 Test positions for body-worn devices

D.3 Desktop device

A typical example of a desktop device is a wireless enabled desktop computer placed on a table or desk when used.

The DUT shall be positioned at the distance and in the orientation to the phantom that corresponds to the intended use as specified by the manufacturer in the user instructions. For devices that employ an external antenna with variable positions, tests shall be performed for all antenna positions specified. Picture 8.5 show positions for desktop device SAR tests. If the intended use is not specified, the device shall be tested directly against the flat phantom.



Picture D.5 Test positions for desktop devices

D.4 DUT Setup Photos



Picture D.6