



Appendix for test report

1Appendix_A: Effective (Isotropic) Radiated Power Output Data

Part I - Test Results

Test Band	Test Mode	Test Channel	Measured[dBm]	ERP	Limit [dBm]	Verdict
WCDMA850	UMTS/TM1	LCH	23.46	22.6	38.5	PASS
		MCH	23.28	22.41	38.5	PASS
		HCH	23.10	22.23	38.5	PASS

Note1:

a, For getting the ERP (Efficient Radiated Power) or EIRP (Efficient Isotropic Radiated Power) in substitution method, the following formula should be taken to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

$$\text{EIRP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$

b, SGP=Signal Generator Level

Note2: RBW > emission bandwidth, VBW > 3 x RBW.

Detector: RMS



2Appendix_B: Peak-to-Average Ratio

Part I - Test Results

Test Band	Test Mode	Test Channel	Measured[dB]	Limit [dB]	Verdict
WCDMA850	UMTS/TM1	LCH	3.12	13	PASS
		MCH	3.2	13	PASS
		HCH	3.11	13	PASS

3Appendix_C: Modulation Characteristics


Part I - Test Plots

3.1 For UMTS

3.1.1 Test Band = WCDMA850

3.1.1.1 Test Mode = UMTS/TM1

3.1.1.1.1 Test Channel = MCH





4Appendix_D: Bandwidth

Part I - Test Results

Test Band	Test Mode	Test Channel	Occupied Bandwidth [MHz]	Emission Bandwidth [MHz]	Verdict
WCDMA850	UMTS/TM1	LCH	4.16	4.74	Pass
		MCH	4.15	4.73	Pass
		HCH	4.17	4.74	Pass


Part II - Test Plots

4.1 For UMTS

4.1.1 Test Band = WCDMA850


4.1.1.1 Test Mode = UMTS/TM1

4.1.1.1.1 Test Channel = LCH






4.1.1.1.2 Test Channel = MCH





4.1.1.1.3 Test Channel = HCH





5Appendix_E: Band Edges Compliance


Part I - Test Plots

5.1 For UMTS

5.1.1 Test Band = WCDMA850

5.1.1.1 Test Mode = UMTS/TM1

5.1.1.1.1 Test Channel = LCH



5.1.1.1.2 Test Channel = HCH



6Appendix_F: Spurious Emission at Antenna Terminal

NOTE: For the averaged unwanted emissions measurements, the measurement points in each sweep is greater than twice the Span/RBW in order to ensure bin-to-bin spacing of $< RBW/2$ so that narrowband signals are not lost between frequency bins. As to the present test item, the "Measurement Points = $k * (Span / RBW)$ " with k between 4 and 5, which results in an acceptable level error of less than 0.5 dB.


Part I - Test Plots


6.1 For UMTS


6.1.1 Test Band = WCDMA850


6.1.1.1 Test Mode = UMTS/TM1

6.1.1.1.1 Test Channel = LCH












6.1.1.1.2 Test Channel = MCH













6.1.1.1.3 Test Channel = HCH









7Appendix_G: Field Strength of Spurious Radiation

Note:

9kHz~150kHz, VBW = 200Hz, VBW = 600 Hz, Detector: PK

150kHz~30MHz, VBW = 9kHz, VBW = 30k Hz, Detector: PK

30MHz~1GHz, RBW = 100 kHz, VBW = 300 kHz. Detector: PK


Above 1GHz, RBW = 1 MHz, VBW = 3 MHz. Detector: PK

Part I - Test Plots


7.1 For UMTS

7.1.1 Test Band = WCDMA850


7.1.1.1 Test Mode = UMTS/TM1



Copy of RSE-TX-DIRECTOR BELOW 1G_L



Copy of RSE-TX-DIRECTOR BELOW 1G_H



8Appendix_H: Frequency Stability

8.1 For UMTS

8.1.1Frequency Error vs. Voltage:

Test Band	Test Mode	Test Channel	Test Temp.	Test Volt.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Verdict
WCDMA850	UMTS/TM1	LCH	TN	VL	-1.82	-0.0022	PASS
				VN	3.33	0.00403	PASS
				VH	-3.34	-0.00404	PASS
		MCH	TN	VL	-0.67	-0.0008	PASS
				VN	2.43	0.00291	PASS
				VH	-8.03	-0.0096	PASS
		HCH	TN	VL	-4.21	-0.00497	PASS
				VN	-4.06	-0.0048	PASS
				VH	0.35	0.00041	PASS

8.1.2Frequency Error vs. Temperature:

Test Band	Test Mode	Test Channel	Test Volt.	Test Temp.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Verdict
WCDMA850	UMTS/TM1	LCH	VN	-30	-1.97	-0.00238	PASS
				-20	1.4	0.00169	PASS
				-10	0.98	0.00119	PASS
				0	5	0.00605	PASS
				10	-0.46	-0.00056	PASS
				20	4.14	0.00501	PASS
				30	1.27	0.00154	PASS
				40	0.17	0.00021	PASS
				50	3.85	0.00466	PASS
		MCH	VN	-30	1.86	0.00222	PASS
				-20	5.36	0.00641	PASS
				-10	-1.21	-0.00145	PASS
				0	-2.38	-0.00285	PASS
				10	-2.79	-0.00334	PASS
				20	-3.25	-0.00389	PASS
				30	3.25	0.00389	PASS

Test Band	Test Mode	Test Channel	Test Volt.	Test Temp.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Verdict
				40	4.85	0.0058	PASS
				50	-1.08	-0.00129	PASS
		HCH	VN	-30	-4.78	-0.00565	PASS
				-20	-2.82	-0.00333	PASS
				-10	5.13	0.00606	PASS
				0	-2.04	-0.00241	PASS
				10	3.57	0.00422	PASS
				20	2.76	0.00326	PASS
				30	-2.96	-0.0035	PASS
				40	-2.21	-0.00261	PASS
				50	0.09	0.00011	PASS

END