



FCC RF Test Report

**Product Name: HSDPA/HSUPA/UMTS/GSM/GPRS/EDGE
Mobile Phone with Bluetooth;**

Model Number: U2900

**Report No: SYBH(Z-RF)007042012-2001
FCC ID: QISU2900**

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Applicant: Huawei Technologies Co., Ltd.
Address: Huawei Base, Bantian, Longgang District, Shenzhen
518129, P.R. China
Date of Receipt Test Item: Apr.14, 2012
Start Date of Test: Apr.15, 2012
End Date of Test: Apr.28, 2012

Test Result: Pass

Approved By Senior Engineer May.06, 2012 Dai Linjun Dai Linjun
Date Name Signature

Reviewed By May.06, 2012 Cousy Xu Cousy XU
Date Name Signature

Operator May.06, 2012 Huang Qiuliang Huang Qiuliang
Date Name Signature

Contents

1	<u>General Information</u>	5
1.1	APPLIED STANDARD.....	5
1.2	TEST LOCATION.....	5
1.3	TEST ENVIRONMENT CONDITION	5
2	<u>Summary</u>	6
3	<u>Product Description</u>	7
3.1	PRODUCTION INFORMATION	7
3.2	TEST DESCRIPTION.....	8
4	<u>General Test Conditions / Configurations</u>	9
4.1	RF CHANNELS UNDER TEST.....	9
4.2	TEST MODES.....	9
4.3	TEST ENVIRONMENTS	9
4.4	TEST SETUPS.....	10
4.5	TEST CONDITIONS	12
5	<u>Main Test Instruments</u>	14
6	<u>Test Results</u>	15
7	<u>Measurement Uncertainty</u>	16

1 General Information

1.1 Applied Standard

Applied Rules: 47 CFR FCC Part 2:2010, Subpart J
47 CFR FCC Part 22:2010, Subpart H
ANSI/TIA 603C

1.2 Test Location

Test Location 1: Reliability Laboratory of Huawei Technologies Co., Ltd.
Address: Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R.
China

1.3 Test Environment Condition

Ambient Temperature: 20 – 25 °C
Ambient Relative Humidity: 45 – 55 %
Atmospheric Pressure: 101 kPa

2 Summary

Table 1 Summary of results

Cellular Band			
Test Case	FCC Part No.	Requirements	Result
Transmitter Output Power	2.1046 & 22.913	ERP not exceed 7 W	Pass
Modulation Characteristics	2.1047	Digital modulation	Pass
Occupied Bandwidth	2.1049	(Not specified)	Pass
Band Edges Compliance	2.1051 & 22.917	Below -13 dBm/1%*EBW, in 1 MHz range	Pass
Spurious Emission at Antenna Terminals	2.1051 & 22.917	Below -13 dBm/1 kHz, 9 kHz to 150 kHz Below -13 dBm/10 kHz, 150 kHz to 30 MHz Below -13 dBm/100 kHz, 30 MHz to 10 th harmonics	Pass
Field Strength of Spurious Radiation	2.1053 & 22.917	Below -13 dBm/100 kHz	Pass
Frequency Stability	2.1055 & 22.355	Maintained within the tolerances of ± 2.5 ppm	Pass

3 Product Description

3.1 Production Information

3.1.1 General Description

HSDPA/HSUPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth U2900 is subscriber equipment in the WCDMA/GSM system. The UMTS frequency band includes Band I and Band II and Band IV. The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only GSM850 band test data included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, UMTS and GSM/GPRS/EDGE protocol processing, voice, MMS service, AGPS etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

3.1.2 Board

Table 1 Board Information

HSDPA/HSUPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth		
U2900		
Hardware Version	Software Version	Description
Ver.B	HUAWEI U2900V100R001CCUB110	Main board of Mobile Phone

3.1.3 Sub-Assembly

AC/DCAdapter Model	HS-050040U6
Manufacturer	Huawei Technologies Co., Ltd.
Input Voltage	~100-240V 50/60Hz 0.2 A
Output Voltage	 5.0V 400 mA
Rated Power	2W
Serial Number	BYBB2161342, HKABC1778071

3.1.4 Battery Technical Data

Battery Model:	HB5A2
Manufacturer	Huawei Technologies Co., Ltd.
Rated capacity:	1000 mAh
Nominal Voltage:	 3.7 V
Charging Voltage:	 4.2 V
Serial Number	GAGBC28Z752D7486, BAAB927XC1702524

3.2 Test Description

3.2.1 Supported Frequency Range

Characteristics	Description
Downlink	869 to 894 MHz;
Uplink	824 to 849 MHz

3.2.2 Transmitter / Receiver Characteristics

Characteristics	Description
System Type	GSM
TX Output Power (per Antenna Port)	GSM system: 33dBm
Channel Spacing(s) / Bandwidth(s)	GSM system: 200 kHz
Designation of Emissions	GSM system: 246KGXW (GMSK modulation), 255KG7W (8PSK modulation))

3.2.3 Antenna Gain

Antenna Gain(dBi):	-1
Antenna Gain(dBd):	-3.15

3.2.4 Power Supply

	Description
Power Supply Type	Directly Connected to DC /AC Power Supply
Input to Adapter (DC power)	DC Voltage Nominal: $\approx$ +3.7V DC Voltage Range: $\approx$ +3.5 V to +4.2V

4 General Test Conditions / Configurations

4.1 RF Channels under Test

Test Mode	TX / RX	RF Channel		
		Bottom (B)	Middle (M)	Top (T)
TM1/TM2	TX	Channel 128	Channel 192	Channel 251
		824.2MHz	837.0MHz	848.8MHz
	RX	Channel 128	Channel 192	Channel 251
		869.2MHz	882.0MHz	893.8MHz

4.2 Test Modes

Test Mode	Test Modes Description
TM1	GSM/GPRS, GMSK modulation
TM2	EDGE, 8PSK modulation

4.3 Test Environments

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	3.5V
	VN	3.7V
	VH	4.2V


NOTE: VL= lower extreme test voltages
VN= nominal voltage
VH= upper extreme test voltage
TN= nominal temperature

4.4 Test Setups


4.4.1 General Test Setup Configurations

Configuration	Description
Test Antenna Ports	Until otherwise declared, all TX tests are ONLY performed at the main Transmitter antenna port (e.g. TRXA, TXA and so on) of the EUT, and all RX tests are ONLY performed at the main Receiver antenna port (e.g. TRXA, RXA and so on) of the EUT.
Multiple RF Sources	Other than the tested RF source of the EUT, other RF source(s) are disabled or shutdown during measurements.

4.4.2 Test Setup 1




4.4.3 Test Setup 2




4.4.4 Test Setup 3

NOTE: Effective radiated power (ERP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

Step 1: Pre-test



Step 2: Substitution method to verify the maximum ERP



4.5 Test Conditions

Test Case	Test Conditions	
Transmitter Output Power	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1 & Setup 3
	Detector	RMS
	RF Channels (TX)	B, M, T
	Test Mode	TM1/TM2
Modulation Characteristics	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	RF Channels (TX)	M
	Test Mode	TM1/TM2
Occupied Bandwidth	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	PK
	RF Channels (TX)	B, M, T
	Test Mode	TM1/TM2
Band Edges Compliance	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	RMS
	RF Channels (TX)	B, T
	Test Mode	TM1/TM2
Spurious Emission at Antenna Terminals	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	PK
	RF Channels (TX)	B, M, T
	Test Mode	TM1/TM2
Field Strength of Spurious Radiation	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 3
	Detector	PK
	RF Channels (TX)	M
	Test Mode	TM1/TM2
Frequency Stability	Test Configuration	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage; (2) 85%, 100% and 115% of Rated Voltage at Ambient Temperature.
	Test Setup	Test Setup 2



Test Case	Test Conditions	
	RF Channels (TX)	M
	Test Mode	TM1/TM2

5 Main Test Instruments

Table 2 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until
Power supply	KEITHLEY	2303	1288003	Sep.27,2012
Universal Radio Communication Tester	R&S	CMU200	117341	Jan.12.2013
Universal Radio Communication Tester	Agilent	E5515C	MY50260239	Aug.31,2012
Spectrum Analyzer	Agilent	E4440A	MY48250119	Jul.17,2012
Signal Analyzer	R&S	FSQ31	200021	Sep.27,2012
Temperature Chamber	WEISS	WKL64	24600294	Feb.13,2013
Signal generator	Agilent	E8257D	MY49281095	Jul.9.2012
Test receiver	R&S	ESU26	100150	May.29.2012
Tunable Dipole	Schwarzbeck	D69250-UHAP/D69250-VHAP	919/1009	Jan.29.2013
Tunable Dipole	Schwarzbeck	D69250-UHAP/D69250-VHAP	979/917	Jan.29.2013
Horn Antenna	R & S	HF906	100683	May.15, 2012
Horn Antenna	R & S	HF906	100684	Jul.01, 2012
Broadband Antenna	Schwarzbeck	VULB 9163	9163-357	May.15, 2012
Broadband Antenna	Schwarzbeck	VULB 9163	9163-356	May.15, 2012

6 Test Results

No.	Test Item	Test Result
1	Transmitter Output Power	Appendix A
2	Modulation Characteristics	Appendix B
3	Occupied Bandwidth	Appendix C
4	Band Edges Compliance	Appendix D
5	Spurious Emission at Antenna Terminals	Appendix E
6	Field Strength of Spurious Radiation	Appendix F
7	Frequency Stability	Appendix G
8	Photos of Radiated Spurious Emissions	Appendix H

NOTE: The Appendix H only photos of Field Strength of Spurious Radiation, no test data.

7 Measurement Uncertainty

For a 95% confidence level ($k=2$), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item		Extended Uncertainty
Transmitter Output Power	Power (dBm)	U =0.39 dB
Occupied Bandwidth	Magnitude (%)	U=0.2%
Band Edge Compliance	Disturbance Power (dBm)	U=2.0 dB
Conducted Spurious Emissions	Disturbance Power (dBm)	U=2.0 dB
Field Strength of Spurious Radiation	ERP (dBm)	U=4.6 dB (30 MHz – 1GHz) U=3.0 dB (above 1 GHz)
Frequency Stability	Frequency Accuracy (ppm)	U=0.21 ppm

-----The END-----



Appendix A

Transmitter Output Power

According to FCC Part 2.1046 & Part 22.913



Conducted Power of Transmitter

Table 1 Measurement Results

TEST CONDITIONS	RF Output Power (Conducted)					
	Channel128(B) 824.2MHz		Channel192(M) 837.0MHz		Channel251(T) 848.8MHz	
	dBm		dBm		dBm	
T_{nom} / V_{nom}	Measured	Limit	Measured	Limit	Measured	Limit
TM1	32.58	38.50	32.70	38.50	32.76	38.50
TM2	24.36	38.50	24.45	38.50	24.51	38.50



Effective Radiated Power of Transmitter (ERP)

Table 2 Substitution Results

Test Mode	Freq. [MHz]	Meas. Level [dBm]	Substituti on Antenna Type	SGP [dBm]	Substituti on Gain [dBd]	Cable Loss [dB]	Substitution Level (ERP) [dBm]	FCC limit [dBm]	Result
TM1	824.2	29.43	Dipole Ant.	32.91	-2.75	0.6	29.56	38.5	Pass
TM1	837.0	29.55	Dipole Ant.	33.18	-2.87	0.6	29.71	38.5	Pass
TM1	848.8	29.61	Dipole Ant.	33.11	-2.85	0.6	29.66	38.5	Pass
TM2	824.2	21.21	Dipole Ant.	24.7	-2.75	0.6	21.35	38.5	Pass
TM2	837.0	21.3	Dipole Ant.	24.86	-2.87	0.6	21.39	38.5	Pass
TM2	848.8	21.36	Dipole Ant.	24.9	-2.85	0.6	21.45	38.5	Pass

Note: a, For getting the ERP (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

b, SGP=Signal Generator Level

-----The END-----
--




Appendix B

Modulation Characteristics

According to FCC Part 2.1047 & Part22 Subpart H




Channel 192 (TM1:GPRS/GSM)





Channel 192 (TM2:EDGE)



-----The END-----

--



Appendix C

Occupied Bandwidth According to FCC Part 2.1049 & Part 22 Subpart H




Result Table

Table 1 Measurement Results

Test Mode	RF Channel	Occupied Bandwidth [kHz]	Verdict
TM1	128	243.59	Pass
	192	243.59	Pass
	251	245.20	Pass
TM2	128	245.20	Pass
	192	251.61	Pass
	251	254.81	Pass




Channel 128 (TM1:GPRS/GSM)



Date: 12.APR.2012 00:46:46




Channel 128 (TM2:EDGE)



Date: 12.APR.2012 00:40:26




Channel 192 (TM1:GPRS/GSM)



Date: 12.APR.2012 00:47:00




Channel 192 (TM2:EDGE)



Date: 12.APR.2012 00:40:40




Channel 251 (TM1:GPRS/GSM)



Date: 12.APR.2012 00:47:13



Channel 251 (TM2:EDGE)



Date: 12.APR.2012 00:40:53

-----The END-----



Appendix D

Band Edges Compliance


According to FCC Part 2.1051 & Part22 Subpart H



TM1:GPRS/GSM

Left Edge


Channel 128



Date: 12.APR.2012 00:36:34




Right Edge Channel 251



Date: 12.APR.2012 00:36:48




TM2:EDGE Left Edge Channel 128



Date: 12.APR.2012 00:39:25



Right Edge Channel 251



Date: 12.APR.2012 00:40:12

-----The END-----

--




Appendix E

Spurious Emission at Antenna Terminal


According to FCC Part 2.1051 & Part22 Subpart H




TM1:GPRS/GSM Channel 128




Date: 12.APR.2012 00:33:39



Date: 12.APR.2012 00:34:23




Date: 12.APR.2012 00:35:07




Date: 12.APR.2012 00:35:51




Channel 192




Date: 12.APR.2012 00:33:54




Date: 12.APR.2012 00:34:37



Ref 35 dBm Att 45 dB SWT 100 ms 838.333333333 MHz




Date: 12.APR.2012 00:35:21




Date: 12.APR.2012 00:36:05




Channel 251




Date: 12.APR.2012 00:34:08



Date: 12.APR.2012 00:34:52




Date: 12.APR.2012 00:35:36




Date: 12.APR.2012 00:36:20



TM2:EDGE Channel 128




Date: 12.APR.2012 00:41:08




```
* RBW 10 kHz      Marker 1 [T1 ]
* VBW 30 kHz      -32.95 dBm
  SWT 300 ms      197.836538462 kHz
```


Ref	35 dBm	Att	45 dB	SWT	300 ms	197.836538462 kHz
-----	--------	-----	-------	-----	--------	-------------------



Date: 12.APR.2012 00:41:52




Date: 12.APR.2012 00:42:36




Date: 12.APR.2012 00:43:20




Channel 192




Date: 12.APR.2012 00:41:23



Date: 12.APR.2012 00:42:06




Date: 12.APR.2012 00:42:50




Date: 12.APR.2012 00:43:34




Channel 251




Date: 12.APR.2012 00:41:37




Ref	35 dBm	Att	45 dB	SWT	300 ms	197.836538462 kHz
-----	--------	-----	-------	-----	--------	-------------------



Date: 12.APR.2012 00:42:21



Date: 12.APR.2012 00:43:05



Date: 12.APR.2012 00:43:48

-----The END-----


--

Appendix F


Radiated spurious emission

GSM 850


Traffic Mode (9kHz~30MHz)



Traffic Mode (30MHz~3GHz)




Traffic Mode (3GHz~18GHz)




GPRS 850


Traffic Mode (9kHz~30MHz)



Traffic Mode (30MHz~3GHz)




Traffic Mode (3GHz~18GHz)




EDGE 850


Traffic Mode (9kHz~30MHz)



Traffic Mode (30MHz~3GHz)



Traffic Mode (3GHz~18GHz)





Appendix G

Frequency Stability

According to FCC Part 2.1055& Part 22.355



Frequency Error vs. Temperature:

Test Mode	RF Ch.	Volt.	Temp.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Freq. vs. 20 °C [ppm]	Limit [ppm]	Verdict
TM 1	M	100%	-30 °C	-12	-0.0128	---	±2.5	Pass
			-20 °C	15	0.0160	---	±2.5	Pass
			-10 °C	-13	-0.0139	---	±2.5	Pass
			0 °C	-15	-0.0160	---	±2.5	Pass
			10 °C	12	0.0128	---	±2.5	Pass
			20 °C	19	0.0203	---	±2.5	Pass
			30 °C	22	0.0235	---	±2.5	Pass
			40 °C	-17	-0.0181	---	±2.5	Pass
			50 °C	-13	-0.0139	---	±2.5	Pass
TM 2	M	100%	-30 °C	14	0.0149	---	±2.5	Pass
			-20 °C	16	0.0171	---	±2.5	Pass
			-10 °C	12	0.0128	---	±2.5	Pass
			0 °C	15	0.0160	---	±2.5	Pass
			10 °C	-14	-0.0149	---	±2.5	Pass
			20 °C	17	0.0181	---	±2.5	Pass
			30 °C	-9	-0.0096	---	±2.5	Pass
			40 °C	8	0.0085	---	±2.5	Pass
			50 °C	-11	-0.0117	---	±2.5	Pass



Frequency Error vs. Voltage:

Test Mode	RF Ch.	Temp.	Volt.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Freq. vs. 20 °C [ppm]	Limit [ppm]	Verdict
TM 1	M	20 °C	VL	17	0.0181	---	±2.5	Pass
			VN	9	0.0096	---	±2.5	Pass
			VH	-9	-0.0096	---	±2.5	Pass
TM 2	M	20 °C	VL	15	0.0160	---	±2.5	Pass
			VN	-13	-0.0139	---	±2.5	Pass
			VH	18	0.0192	---	±2.5	Pass

-----The END-----