

**Appendix B. SAR Measurement Plots**

Table of contents
GSM850 MHz Head
GSM850 MHz Body
GSM1900 MHz Head
GSM1900 MHz Body
WCDMA850 MHz Head
WCDMA850 MHz Body
WCDMA1700 MHz Head
WCDMA1700 MHz Body
WCDMA1900 MHz Head
WCDMA1900 MHz Body
WiFi 802.11b Head
WiFi 802.11b Body

Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 190CH Left hand touch cheek

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 42.564$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.510 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.817 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.5910

SAR(1 g) = 0.486 mW/g; SAR(10 g) = 0.373 mW/g

Maximum value of SAR (measured) = 0.511 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 190CH Left hand tilt 15 degree

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 42.564$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.409 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.484 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.4830

SAR(1 g) = 0.398 mW/g; SAR(10 g) = 0.308 mW/g

Maximum value of SAR (measured) = 0.418 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 190CH Right hand touch cheek

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 42.564$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.409 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.484 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.4830

SAR(1 g) = 0.544mW/g; SAR(10 g) = 0.420 mW/g

Maximum value of SAR (measured) = 0.418 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 190CH Right hand tilt 15 degree

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 42.564$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.425 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 15.850 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.4940

SAR(1 g) = 0.410 mW/g; SAR(10 g) = 0.317 mW/g

Maximum value of SAR (measured) = 0.430 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 190CH Right hand touch cheek with battery MLCC205997530689(1500mAh)

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 42.564$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.519 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.693 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.6030

SAR(1 g) = 0.499 mW/g; SAR(10 g) = 0.384 mW/g

Maximum value of SAR (measured) = 0.525 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 1TS 190CH Towards Phantom 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.563 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 23.517 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.6710

SAR(1 g) = 0.534 mW/g; SAR(10 g) = 0.411 mW/g

Maximum value of SAR (measured) = 0.557 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 190CH Towards Phantom 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.695 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 26.179 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.8650

SAR(1 g) = 0.676 mW/g; SAR(10 g) = 0.516 mW/g

Maximum value of SAR (measured) = 0.707 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 128CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.963$ mho/m; $\epsilon_r = 54.474$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.186 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 30.902 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.4280

SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.861 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 190CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.015 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 27.694 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 1.2750

SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.761 mW/g

Maximum value of SAR (measured) = 1.067 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 251CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 848.8 MHz

Medium parameters used: $f = 849$ MHz; $\sigma = 0.987$ mho/m; $\epsilon_r = 54.766$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.786 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 28.506 V/m; Power Drift = 0.00084 dB

Peak SAR (extrapolated) = 0.9770

SAR(1 g) = 0.762 mW/g; SAR(10 g) = 0.571 mW/g

Maximum value of SAR (measured) = 0.797 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 190CH Left side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.769 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 28.075 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.0150

SAR(1 g) = 0.715 mW/g; SAR(10 g) = 0.492 mW/g

Maximum value of SAR (measured) = 0.760 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 128CH Right side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.963$ mho/m; $\epsilon_r = 54.474$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.889 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 27.349 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.2250

SAR(1 g) = 0.884 mW/g; SAR(10 g) = 0.622 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.939 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 190CH Right side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.906 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 27.736 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 1.2240

SAR(1 g) = 0.889 mW/g; SAR(10 g) = 0.623 mW/g

Maximum value of SAR (measured) = 0.944 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 251CH Right side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 848.8 MHz

Medium parameters used: $f = 849$ MHz; $\sigma = 0.987$ mho/m; $\epsilon_r = 54.766$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.662 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 23.162 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.9490

SAR(1 g) = 0.677 mW/g; SAR(10 g) = 0.471 mW/g

Maximum value of SAR (measured) = 0.723 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 190CH Bottom side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.162 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.206 V/m; Power Drift = 0.0093 dB

Peak SAR (extrapolated) = 0.2410

SAR(1 g) = 0.154 mW/g; SAR(10 g) = 0.097 mW/g

Maximum value of SAR (measured) = 0.168 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 1TS 190CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.749 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 26.820 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.0660

SAR(1 g) = 0.686 mW/g; SAR(10 g) = 0.463 mW/g

Maximum value of SAR (measured) = 0.746 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 26.820 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.9010

SAR(1 g) = 0.725 mW/g; SAR(10 g) = 0.551 mW/g

Maximum value of SAR (measured) = 0.759 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 128CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.963$ mho/m; $\epsilon_r = 54.474$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.266 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 35.361 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.5520

SAR(1 g) = 1.21 mW/g; SAR(10 g) = 0.910 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.272 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 190CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 54.608$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.178 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 34.061 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 1.9400

SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.677 mW/g

Maximum value of SAR (measured) = 1.137 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 34.061 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 1.3990

SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.823 mW/g

Maximum value of SAR (measured) = 1.150 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 251CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 848.8 MHz

Medium parameters used: $f = 849$ MHz; $\sigma = 0.987$ mho/m; $\epsilon_r = 54.766$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.840 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 28.257 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.2630

SAR(1 g) = 0.781 mW/g; SAR(10 g) = 0.503 mW/g

Maximum value of SAR (measured) = 0.858 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 28.257 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.0150

SAR(1 g) = 0.794 mW/g; SAR(10 g) = 0.595 mW/g

Maximum value of SAR (measured) = 0.831 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 128CH Towards Ground 10mm with battery MLCC205997530689(1500mAh)

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.963$ mho/m; $\epsilon_r = 54.474$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.215 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 34.658 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.4650

SAR(1 g) = 1.15 mW/g; SAR(10 g) = 0.869 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.204 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 1TS 190CH Towards Phantom 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.978$ mho/m; $\epsilon_r = 54.467$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.501 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 22.922 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.6220

SAR(1 g) = 0.495 mW/g; SAR(10 g) = 0.378 mW/g

Maximum value of SAR (measured) = 0.522 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 190CH Towards Phantom 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.978$ mho/m; $\epsilon_r = 54.467$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.683 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 27.427 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.8380

SAR(1 g) = 0.653 mW/g; SAR(10 g) = 0.494 mW/g

Maximum value of SAR (measured) = 0.684 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 128CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.333$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.961 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 31.042 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.1880

SAR(1 g) = 0.931 mW/g; SAR(10 g) = 0.700 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.981 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 190CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.978$ mho/m; $\epsilon_r = 54.467$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.908 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 29.823 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.1460

SAR(1 g) = 0.889 mW/g; SAR(10 g) = 0.666 mW/g

Maximum value of SAR (measured) = 0.932 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 GPRS 2TS 251CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 848.8 MHz

Medium parameters used: $f = 849$ MHz; $\sigma = 0.986$ mho/m; $\epsilon_r = 54.625$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.688 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 25.878 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.8610

SAR(1 g) = 0.661 mW/g; SAR(10 g) = 0.490 mW/g

Maximum value of SAR (measured) = 0.698 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 1TS 190CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.978$ mho/m; $\epsilon_r = 54.467$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.724 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 27.190 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.8760

SAR(1 g) = 0.691 mW/g; SAR(10 g) = 0.521 mW/g

Maximum value of SAR (measured) = 0.723 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 128CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.333$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.030 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 32.352 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.2530

SAR(1 g) = 0.971 mW/g; SAR(10 g) = 0.727 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.026 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 190CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.978$ mho/m; $\epsilon_r = 54.467$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.993 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 32.140 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.2030

SAR(1 g) = 0.931 mW/g; SAR(10 g) = 0.695 mW/g

Maximum value of SAR (measured) = 0.978 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 251CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 848.8 MHz

Medium parameters used: $f = 849$ MHz; $\sigma = 0.986$ mho/m; $\epsilon_r = 54.625$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.694 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 26.487 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.8710

SAR(1 g) = 0.674 mW/g; SAR(10 g) = 0.501 mW/g

Maximum value of SAR (measured) = 0.711 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 128CH Towards Ground 15mm with Headset

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.333$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.535 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 23.468 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.6600

SAR(1 g) = 0.510 mW/g; SAR(10 g) = 0.382 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.537 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM850 EGPRS 2TS 128CH Towards Ground 15mm with battery MLCC205997530689(1500mAh)

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.333$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.013 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 32.565 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.2130

SAR(1 g) = 0.944 mW/g; SAR(10 g) = 0.707 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.992 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 661CH Left hand touch cheek

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.439$ mho/m; $\epsilon_r = 38.402$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.1, 5.1, 5.1); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.381 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.871 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.5780

SAR(1 g) = 0.363 mW/g; SAR(10 g) = 0.222 mW/g

Maximum value of SAR (measured) = 0.391 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 661CH Left hand tilt 15 degree

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.439$ mho/m; $\epsilon_r = 38.402$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.1, 5.1, 5.1); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.226 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.937 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.3430

SAR(1 g) = 0.208 mW/g; SAR(10 g) = 0.116 mW/g

Maximum value of SAR (measured) = 0.229 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 661CH Right hand touch cheek

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.439$ mho/m; $\epsilon_r = 38.402$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.1, 5.1, 5.1); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.348 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.657 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.5600

SAR(1 g) = 0.362 mW/g; SAR(10 g) = 0.221 mW/g

Maximum value of SAR (measured) = 0.396 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 661CH Right hand tilt 15 degree

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.439$ mho/m; $\epsilon_r = 38.402$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.1, 5.1, 5.1); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.236 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.202 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.3710

SAR(1 g) = 0.221 mW/g; SAR(10 g) = 0.121 mW/g

Maximum value of SAR (measured) = 0.248 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 661CH Left hand touch cheek with battery MLCC205997530689(1500mAh)

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.439$ mho/m; $\epsilon_r = 38.402$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.1, 5.1, 5.1); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.272 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.109 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.4180

SAR(1 g) = 0.264 mW/g; SAR(10 g) = 0.160 mW/g

Maximum value of SAR (measured) = 0.287 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 1TS 661CH Towards Phantom 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.334 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.655 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.5130

SAR(1 g) = 0.309 mW/g; SAR(10 g) = 0.189 mW/g

Maximum value of SAR (measured) = 0.333 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Towards Phantom 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.379 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.326 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.6380

SAR(1 g) = 0.379 mW/g; SAR(10 g) = 0.226 mW/g

Maximum value of SAR (measured) = 0.423 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.605 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.690 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.9790

SAR(1 g) = 0.570 mW/g; SAR(10 g) = 0.331 mW/g

Maximum value of SAR (measured) = 0.624 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Right side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (6x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.123 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.478 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.2020

SAR(1 g) = 0.123 mW/g; SAR(10 g) = 0.073 mW/g

Maximum value of SAR (measured) = 0.136 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.478 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.1850

SAR(1 g) = 0.112 mW/g; SAR(10 g) = 0.066 mW/g

Maximum value of SAR (measured) = 0.122 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Left side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (6x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.194 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.906 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.2850

SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.096 mW/g

Maximum value of SAR (measured) = 0.185 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Bottom side 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (7x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.265 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.354 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.4520

SAR(1 g) = 0.270 mW/g; SAR(10 g) = 0.153 mW/g

Maximum value of SAR (measured) = 0.301 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 EGPRS 1TS 661CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.539 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.242 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.8890

SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.305 mW/g

Maximum value of SAR (measured) = 0.572 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 EGPRS 2TS 661CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.550 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.490 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.9610

SAR(1 g) = 0.563 mW/g; SAR(10 g) = 0.329 mW/g

Maximum value of SAR (measured) = 0.613 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Towards Ground 10mm with battery MLCC205997530689(1500mAh)

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.565$ mho/m; $\epsilon_r = 52.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.491 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.415 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.7880

SAR(1 g) = 0.456 mW/g; SAR(10 g) = 0.264 mW/g

Maximum value of SAR (measured) = 0.500 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 1TS 661CH Towards Phantom 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.544$ mho/m; $\epsilon_r = 53.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.213 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.001 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.3190

SAR(1 g) = 0.199 mW/g; SAR(10 g) = 0.124 mW/g

Maximum value of SAR (measured) = 0.214 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Towards Phantom 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.544$ mho/m; $\epsilon_r = 53.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.210 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.967 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.3290

SAR(1 g) = 0.201 mW/g; SAR(10 g) = 0.124 mW/g

Maximum value of SAR (measured) = 0.215 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 GPRS 2TS 661CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.544$ mho/m; $\epsilon_r = 53.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.251 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.754 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.4000

SAR(1 g) = 0.240 mW/g; SAR(10 g) = 0.145 mW/g

Maximum value of SAR (measured) = 0.260 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 EGPRS 1TS 661CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.544$ mho/m; $\epsilon_r = 53.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.260 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.789 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.4120

SAR(1 g) = 0.250 mW/g; SAR(10 g) = 0.151 mW/g

Maximum value of SAR (measured) = 0.272 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 EGPRS 2TS 661CH Towards Ground 15mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.544$ mho/m; $\epsilon_r = 53.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.256 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.867 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.3990

SAR(1 g) = 0.242 mW/g; SAR(10 g) = 0.146 mW/g

Maximum value of SAR (measured) = 0.260 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 661CH Towards Ground 15mm with Headset

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.544$ mho/m; $\epsilon_r = 53.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.247 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.737 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.4000

SAR(1 g) = 0.243 mW/g; SAR(10 g) = 0.147 mW/g

Maximum value of SAR (measured) = 0.261 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 GSM1900 EGPRS 1TS 661CH Towards Ground 15mm with battery MLCC205997530689(1500mAh)

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.544$ mho/m; $\epsilon_r = 53.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.272 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.350 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.4310

SAR(1 g) = 0.250 mW/g; SAR(10 g) = 0.152 mW/g

Maximum value of SAR (measured) = 0.269 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 WCDMA850 4182CH Leftt hand touch cheek

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.934$ mho/m; $\epsilon_r = 43.045$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.355 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 5.247 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.4270

SAR(1 g) = 0.345 mW/g; SAR(10 g) = 0.257 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.364 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 WCDMA850 4182CH Left hand tilt 15 degree

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.934$ mho/m; $\epsilon_r = 43.045$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.309 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 10.467 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.3770

SAR(1 g) = 0.302 mW/g; SAR(10 g) = 0.229 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.318 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 WCDMA850 4182CH Right hand touch cheek

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.934$ mho/m; $\epsilon_r = 43.045$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.386 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 6.702 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.4800

SAR(1 g) = 0.384 mW/g; SAR(10 g) = 0.289 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.405 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 WCDMA850 4182CH Right hand tilt 15 degree

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.934$ mho/m; $\epsilon_r = 43.045$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1); Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.334 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 12.536 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.4020

SAR(1 g) = 0.321 mW/g; SAR(10 g) = 0.244 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.341 mW/g



Test Laboratory: HUAWEI SAR Lab

U8680 WCDMA850 4182CH Right hand touch cheek with battery MLCC205997530689(1500mAh)

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.934$ mho/m; $\epsilon_r = 43.045$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.07, 6.07, 6.07); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Head/Area Scan (8x12x1); Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.384 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.512 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.4500

SAR(1 g) = 0.362 mW/g; SAR(10 g) = 0.273 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)



Test Laboratory: HUAWEI SAR Lab

U8680 WCDMA850 4182CH Towards Ground 10mm

DUT: U8680; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.968$ mho/m; $\epsilon_r = 55.137$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.11, 6.11, 6.11); Calibrated: 9/27/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 2.0, 32.0$
- Electronics: DAE4 Sn852; Calibrated: 11/16/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.797 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 28.488 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.0090

SAR(1 g) = 0.764 mW/g; SAR(10 g) = 0.564 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.805 mW/g

