



# EMC TEST REPORT

**Applicant** Huawei Technologies Co., Ltd.  
**FCC ID** QISVIE-L09  
**Product** Smart Phone  
**Model** VIE-L09  
**Report No.** RHA1602-0013EMC01  
**Issue Date** April 11, 2016

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2015)/ ANSI C63.4 (2014)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Wei Liu*

*Reviewed by: Wei Liu*

*Guangchang Fan*

*Approved by: Guangchang Fan*



**TA Technology (Shanghai) Co., Ltd.**

*No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*



## Table of Contents

|     |                                                   |    |
|-----|---------------------------------------------------|----|
| 1   | Test Laboratory.....                              | 4  |
| 1.1 | Notes of the Test Report .....                    | 4  |
| 1.2 | Test facility .....                               | 4  |
| 1.3 | Testing Location.....                             | 5  |
| 2   | General Description of Equipment under Test ..... | 6  |
| 2.1 | Client Information .....                          | 6  |
| 2.2 | General information.....                          | 6  |
| 2.3 | Applied Standards.....                            | 8  |
| 3   | Test Case Results .....                           | 9  |
| 3.1 | Radiated Emission .....                           | 9  |
| 3.2 | Conducted Emission .....                          | 16 |
| 4   | Main Test Equipment.....                          | 19 |



### Summary of measurement results

| Number                                   | Test Case          | Clause in FCC Rules     | Conclusion |
|------------------------------------------|--------------------|-------------------------|------------|
| 1                                        | Radiated Emission  | 15.109, ANSI C63.4-2014 | PASS       |
| 2                                        | Conducted Emission | 15.107, ANSI C63.4-2014 | PASS       |
| Test Date: March 3, 2016 ~ March 8, 2016 |                    |                         |            |

# 1 Test Laboratory

## 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of TA technology (shanghai) co., Ltd). The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by CNAS or any government agencies.

## 1.2 Test facility

### **CNAS (accreditation number: L2264)**

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

### **FCC (recognition number is 428261)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

### **IC (recognition number is 8510A)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

### **VCCI (recognition number is C-4595, T-2154, R-4113, G-766)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



### 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2 General Description of Equipment under Test

### 2.1 Client Information

|                             |                                                                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant</b>            | Huawei Technologies Co., Ltd.                                                                                                     |
| <b>Applicant address</b>    | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129<br>P.R.China |
| <b>Manufacturer</b>         | Huawei Technologies Co., Ltd.                                                                                                     |
| <b>Manufacturer address</b> | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129<br>P.R.China |

### 2.2 General information

| EUT Description    |                                                                                                                                       |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Device Type:       | Portable Device                                                                                                                       |
| Product Name:      | Smart Phone                                                                                                                           |
| Model Number:      | VIE-L09                                                                                                                               |
| HW Version:        | HL1AVIENNAM                                                                                                                           |
| SW Version:        | A169-L09C900B071                                                                                                                      |
| IMEI:              | 004401725654723                                                                                                                       |
| Antenna Type:      | Internal Antenna                                                                                                                      |
| Used Host Product: | PC: Model: DELL E6430(SN : 32RKWW1)                                                                                                   |
| Test Mode:         | Transfer Data Mode                                                                                                                    |
| EUT Accessory      |                                                                                                                                       |
| Adapter 1          | Manufacturer: HUIZHOU BYD ELECTRONIC CO., LTD.<br>Model: HW-059200UHQ<br>Input power: -100V-240V-5V/9V 2A<br>Output power: 5V/9V DC2A |
| Adapter 2          | Manufacturer: Salcomp (Shenzhen)Co.,Ltd<br>Model: HW-059200UHQ<br>Input power: -100V-240V-5V/9V 2A<br>Output power: 5V/9V DC2A        |
| Battery 1          | Manufacturer: Sunwoda Electronic Co., LTD<br>Model: HB376883ECW                                                                       |



|                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Battery 2                                                                                                                                                                                                                                                                                                                                                                                | Manufacturer: Desay Battery Co., Ltd.<br>Model: HB376883ECW                                    |
| Battery 3                                                                                                                                                                                                                                                                                                                                                                                | Manufacturer: SCUD (FUJIAN) Electronics Co., Ltd<br>Model: HB376883ECW                         |
| USB Cable 1                                                                                                                                                                                                                                                                                                                                                                              | Manufacturer: FOXCONN INTERCONNECT TECHNOLOGY LIMITED.<br>Model: CUDU01B-HC212-EH, 100cm Cable |
| USB Cable 2                                                                                                                                                                                                                                                                                                                                                                              | Manufacturer: LUXSHARE-ICT Co., Ltd.<br>Model: L99UC001-CS-H, 100cm Cable                      |
| USB Cable 3                                                                                                                                                                                                                                                                                                                                                                              | Manufacturer: Chang Shu Honglin Technology Co., Ltd.<br>Model: 130-26988, 100cm Cable          |
| <p>Remark: 1. The information of the EUT is declared by the manufacturer. Please refer to the specifications or user manual for details.</p> <p>2. There is more than one USB cable/ Adapter/ Battery, each one should be applied throughout the compliance test respectively, and however, only the worst case (USB cable 1/ Adapter 1/ Battery 1) will be recorded in this report.</p> |                                                                                                |



## 2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### Test standards

**FCC Code CFR47 Part15B (2015)**

**ANSI C63.4 (2014)**

### 3 Test Case Results

#### 3.1 Radiated Emission

##### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 24°C~26°C   | 45%~50%           | 102.5kPa |

##### Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. During the test, EUT is connected to a laptop via a SD card I/O port. The EUT is used as the peripheral equipment of the PC.

The data is transferred from EUT to PC; PC is connected to server via a long USB cable.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK: RBW=1MHz VBW=3MHz/ Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO


The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

## Test Setup

### Below 1GHz



### Above 1GHz



Note: Area side:2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

**Limits**


| Frequency<br>(MHz)                                                                 | Field Strength<br>(dB $\mu$ V/m) | Detector        |
|------------------------------------------------------------------------------------|----------------------------------|-----------------|
| 30 -88                                                                             | 40.0                             | Quasi-peak      |
| 88-216                                                                             | 43.5                             | Quasi-peak      |
| 216 – 960                                                                          | 46.0                             | Quasi-peak      |
| 960-1000                                                                           | 54.0                             | Quasi-peak      |
| 1000-5 <sup>th</sup> harmonic of the highest<br>frequency or 40GHz, which is lower | 54<br>74                         | Average<br>Peak |

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .  $U = 3.92$  dB.

## Test Results

The following graphs display the maximum values of horizontal and vertical by software.  
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.  
The signal beyond the limit is carrier.




Radiated Emission from 30MHz to 1GHz

| Frequency (MHz) | Quasi-Peak (dBuV/m) | Reading value (dBuV/m) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|---------------------|------------------------|-------------|--------------|---------------|---------------------|-------------|----------------|
| 30.125947       | 17.7                | 40.1                   | 101.0       | V            | 0.0           | -22.4               | 22.3        | 40.0           |
| 59.234144       | 9.7                 | 32.7                   | 100.0       | V            | 300.0         | -23.0               | 30.3        | 40.0           |
| 156.873538      | 14.3                | 43.3                   | 127.0       | H            | 76.0          | -29.0               | 29.2        | 43.5           |
| 214.886000      | 17.9                | 43.5                   | 104.0       | H            | 287.0         | -25.6               | 25.6        | 43.5           |
| 540.641750      | 11.5                | 29.8                   | 124.0       | V            | 82.0          | -18.3               | 34.5        | 46.0           |
| 961.944750      | 16.9                | 29.7                   | 127.0       | V            | 104.0         | -12.8               | 37.1        | 54.0           |

- Remark:** 1. Quasi-Peak = Reading value + Correction factor  
2. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)  
3. Margin = Limit – Quasi-Peak

RE 1G-3GHz PK+AV




Radiated Emission from 1GHz to 3GHz

| Frequency (MHz) | Peak (dBuV/m) | Reading value (dBuV/m) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|---------------|------------------------|-------------|--------------|---------------|---------------------|-------------|----------------|
| 1193.750000     | 41.7          | 49.9                   | 102.0       | H            | 28.0          | -8.2                | 32.3        | 74             |
| 1436.500000     | 42.3          | 49.2                   | 102.0       | H            | 0.0           | -6.9                | 31.7        | 74             |
| 1629.000000     | 44.8          | 49.5                   | 102.0       | H            | 159.0         | -4.7                | 29.2        | 74             |
| 2032.250000     | 46.1          | 49.5                   | 102.0       | V            | 269.0         | -3.4                | 27.9        | 74             |
| 2424.000000     | 48.9          | 49.4                   | 102.0       | H            | 136.0         | -0.5                | 25.1        | 74             |
| 2994.750000     | 53.0          | 55.3                   | 102.0       | V            | 229.0         | -2.3                | 21.0        | 74             |

| Frequency (MHz) | Average (dBuV/m) | Reading value (dBuV/m) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|------------------|------------------------|-------------|--------------|---------------|---------------------|-------------|----------------|
| 1190.000000     | 29.8             | 38.0                   | 102.0       | H            | 62.0          | -8.2                | 24.2        | 54             |
| 1421.000000     | 30.9             | 37.8                   | 102.0       | H            | 56.0          | -6.9                | 23.1        | 54             |
| 1638.250000     | 33.3             | 38.0                   | 102.0       | V            | 129.0         | -4.7                | 20.7        | 54             |
| 1957.000000     | 35.1             | 38.5                   | 102.0       | V            | 157.0         | -3.4                | 18.9        | 54             |
| 2421.500000     | 37.5             | 38.0                   | 102.0       | H            | 0.0           | -0.5                | 16.5        | 54             |
| 2978.250000     | 41.6             | 43.8                   | 102.0       | V            | 194.0         | -2.2                | 12.4        | 54             |

## RE 3-18GHz PK+AV




## Radiated Emission from 3GHz to 18GHz

| Frequency (MHz) | Peak (dBuV/m) | Reading value (dBuV/m) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|---------------|------------------------|-------------|--------------|---------------|---------------------|-------------|----------------|
| 4040.625000     | 40.8          | 41.4                   | 102.0       | V            | 358.0         | -0.6                | 33.2        | 74             |
| 5358.750000     | 43.4          | 47.1                   | 102.0       | V            | 0.0           | -3.7                | 30.6        | 74             |
| 6901.875000     | 46.1          | 53.1                   | 102.0       | V            | 0.0           | -7.0                | 27.9        | 74             |
| 9819.375000     | 47.6          | 59.7                   | 102.0       | H            | 94.0          | -12.1               | 26.4        | 74             |
| 12705.000000    | 51.1          | 66.2                   | 102.0       | H            | 0.0           | -15.1               | 22.9        | 74             |
| 17958.750000    | 60.4          | 85.3                   | 102.0       | H            | 215.0         | -24.9               | 13.6        | 74             |

| Frequency (MHz) | Average (dBuV/m) | Reading value (dBuV/m) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|------------------|------------------------|-------------|--------------|---------------|---------------------|-------------|----------------|
| 3939.375000     | 31.6             | 31.7                   | 102.0       | H            | 56.0          | -0.1                | 22.4        | 54             |
| 5272.500000     | 34.8             | 38.5                   | 102.0       | H            | 186.0         | -3.7                | 19.2        | 54             |
| 6926.250000     | 37.0             | 43.8                   | 102.0       | V            | 204.0         | -6.8                | 17.0        | 54             |
| 9755.625000     | 39.1             | 50.8                   | 102.0       | H            | 228.0         | -11.7               | 14.9        | 54             |
| 12645.000000    | 42.1             | 57.0                   | 102.0       | V            | 160.0         | -14.9               | 11.9        | 54             |
| 18000.000000    | 50.9             | 76.3                   | 102.0       | V            | 57.0          | -25.4               | 3.1         | 54             |

RE 18-26.5GHz PK+AV



Radiated Emission from 18GHz to 26.5GHz

| Frequency (MHz) | Peak (dBuV/m) | Reading value (dBuV/m) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|---------------|------------------------|--------------|---------------|---------------------|-------------|----------------|
| 18382.500000    | 31.7          | 36.5                   | V            | 0.0           | -4.8                | 42.3        | 74             |
| 19422.687500    | 26.5          | 34.3                   | V            | 349.0         | -7.8                | 47.5        | 74             |
| 20555.312500    | 25.3          | 33.4                   | V            | 242.0         | -8.1                | 48.7        | 74             |
| 23283.812500    | 26.4          | 33.5                   | H            | 0.0           | -7.1                | 47.6        | 74             |
| 24666.125000    | 27.4          | 34.5                   | H            | 16.0          | -7.1                | 46.6        | 74             |
| 25237.750000    | 29.1          | 35.2                   | H            | 109.0         | -6.1                | 44.9        | 74             |

| Frequency (MHz) | Average (dBuV/m) | Reading value (dBuV/m) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|------------------|------------------------|--------------|---------------|---------------------|-------------|----------------|
| 18382.500000    | 20.3             | 25.1                   | H            | 41.0          | -4.8                | 33.7        | 54             |
| 19492.812500    | 15.8             | 23.4                   | V            | 44.0          | -7.6                | 38.2        | 54             |
| 21648.625000    | 14.5             | 23.7                   | H            | 195.0         | -9.2                | 39.5        | 54             |
| 22057.687500    | 15.5             | 23.6                   | H            | 58.0          | -8.1                | 38.5        | 54             |
| 24700.125000    | 16.2             | 22.9                   | H            | 83.0          | -6.7                | 37.8        | 54             |
| 25210.125000    | 18.1             | 24.4                   | H            | 195.0         | -6.3                | 35.9        | 54             |

## 3.2 Conducted Emission


### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 24°C ~26°C  | 50%~55%           | 102.5kPa |

### Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line. During the test, EUT is connected to a laptop via a SD card I/O port. The EUT is used as the peripheral equipment of the PC.

### Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

### Limits


| Frequency<br>(MHz)                                | Conducted Limits(dBμV) |            |
|---------------------------------------------------|------------------------|------------|
|                                                   | Quasi-peak             | Average    |
| 0.15 - 0.5                                        | 66 to 56 *             | 56 to 46 * |
| 0.5 - 5                                           | 56                     | 46         |
| 5 - 30                                            | 60                     | 50         |
| *: Decreases with the logarithm of the frequency. |                        |            |

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .  $U = 2.69$  dB.

## Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




### Final Measurement Results

| Frequency<br>MHz | QP Level<br>dBμV | QP Limit<br>dBμV | QP Delta<br>dB | Phase<br>- | PE<br>- |
|------------------|------------------|------------------|----------------|------------|---------|
| 0.22812          | 27.77            | 62.52            | 34.75          | L1         | gnd     |
| 0.4664           | 19.07            | 56.58            | 37.51          | L1         | gnd     |
| 0.75937          | 20.01            | 56.00            | 35.99          | L1         | gnd     |
| 3.775            | 26.55            | 56.00            | 29.45          | L1         | gnd     |
| 5.775            | 26.76            | 60.00            | 33.24          | L1         | gnd     |
| 16.42734         | 21.64            | 60.00            | 38.36          | L1         | gnd     |

| Frequency<br>MHz | AV Level<br>dBμV | AV Limit<br>dBμV | AV Delta<br>dB | Phase<br>- | PE<br>- |
|------------------|------------------|------------------|----------------|------------|---------|
| 0.22812          | 18.61            | 52.52            | 33.91          | L1         | gnd     |
| 0.4664           | 17.31            | 46.58            | 29.27          | L1         | gnd     |
| 0.75937          | 17.64            | 46.00            | 28.36          | L1         | gnd     |
| 3.775            | 20.07            | 46.00            | 25.93          | L1         | gnd     |
| 5.775            | 22.35            | 50.00            | 27.65          | L1         | gnd     |
| 16.42734         | 18.63            | 50.00            | 31.37          | L1         | gnd     |

L line

Conducted Emission from 150 KHz to 30 MHz



### Final Measurement Results

| Frequency<br>MHz | QP Level<br>dBμV | QP Limit<br>dBμV | QP Delta<br>dB | Phase<br>- | PE<br>- |
|------------------|------------------|------------------|----------------|------------|---------|
| 0.45468          | 29.65            | 56.79            | 27.14          | N          | gnd     |
| 0.98203          | 22.52            | 56.00            | 33.48          | N          | gnd     |
| 1.64609          | 26.13            | 56.00            | 29.87          | N          | gnd     |
| 3.42734          | 28.33            | 56.00            | 27.67          | N          | gnd     |
| 5.59921          | 30.04            | 60.00            | 29.96          | N          | gnd     |
| 12.85703         | 29.29            | 60.00            | 30.71          | N          | gnd     |

| Frequency<br>MHz | AV Level<br>dBμV | AV Limit<br>dBμV | AV Delta<br>dB | Phase<br>- | PE<br>- |
|------------------|------------------|------------------|----------------|------------|---------|
| 0.45468          | 28.45            | 46.79            | 18.34          | N          | gnd     |
| 0.98203          | 19.27            | 46.00            | 26.73          | N          | gnd     |
| 1.64609          | 20.16            | 46.00            | 25.84          | N          | gnd     |
| 3.42734          | 20.94            | 46.00            | 25.06          | N          | gnd     |
| 5.59921          | 23.66            | 50.00            | 26.34          | N          | gnd     |
| 12.85703         | 24.21            | 50.00            | 25.79          | N          | gnd     |

N line  
Conducted Emission from 150 KHz to 30 MHz

## 4 Main Test Equipment

| Name                    | Type      | Manufacturer | Serial Number | Last Cal.  | Cal. Due Date |
|-------------------------|-----------|--------------|---------------|------------|---------------|
| EMI Test Receiver       | ESCI      | R&S          | 100948        | 2015-05-22 | 2016-05-21    |
| Signal Analyzer         | FSV30     | R&S          | 100815        | 2015-12-17 | 2016-12-16    |
| Trilog Antenna          | VULB 9163 | SCHWARZBECK  | 9163-201      | 2014-12-06 | 2017-12-05    |
| Horn Antenna            | HF907     | R&S          | 100126        | 2014-12-06 | 2017-12-05    |
| Horn Antenna            | 3160-09   | ETS-Lindgren | 00102643      | 2015-01-30 | 2018-01-29    |
| EMI Test Receiver       | ESCS30    | R&S          | 100138        | 2015-12-17 | 2016-12-16    |
| LISN                    | ENV216    | R&S          | 101171        | 2013-12-18 | 2016-12-17    |
| Bore Sight Antenna mast | 2171B     | ETS          | 00058752      | NA         | NA            |