



SAR TEST REPORT

Product Name	WCDMA Digital Mobile Phone
Model Name	HUAWEI Y221-U33
FCC ID	QISY221-U33
Applicant	Huawei Technologies Co., Ltd.
Manufacturer	Huawei Technologies Co., Ltd.
Date of issue	July 30, 2014

TA Technology (Shanghai) Co., Ltd.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 2 of 220

GENERAL SUMMARY

Reference Standard(s)	FCC 47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices ANSI C95.1, 1992: Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.(IEEE Std C95.1-1991) IEEE Std 1528™-2003: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques. KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r03: SAR Measurement Requirements for 100 MHz to 6 GHz KDB 447498 D01 Mobile Portable RF Exposure v05r02: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies KDB 648474 D04 Handset SAR v01r02: SAR Evaluation Considerations for Wireless Handsets. KDB 941225 D01 SAR test for 3G devices v02: SAR Measurement Procedures CDMA 20001x RTT, 1x Ev-Do, WCDMA, HSDPA/HSPA KDB 941225 D02 HSPA and 1x Advanced v02r02 SAR Guidance for HSPA, HSPA+, DC-HSDPA and 1x-Advanced KDB 941225 D03 Test Reduction GSM_GPRS_EDGE v01:Recommended SAR Test Reduction Procedures for GSM/GPRS/EDGE KDB 941225 D06 Hotspot Mode SAR v01r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities KDB 248227 D01 SAR meas for 802 11 a b g v01r02: SAR Measurement Procedures for 802.11a/b/g Transmitters.
Conclusion	This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 7 of this test report are below limits specified in the relevant standards for the tested bands only. General Judgment: Pass
Comment	The test result only responds to the measured sample.

Approved by Weizhong Yang

Weizhong Yang
Director

Revised by Minbao Ling

Minbao Ling
SAR Manager

Performed by Yi Zhang

Yi Zhang
SAR Engineer

TABLE OF CONTENT

1. General Information	5
1.1. Notes of the Test Report.....	5
1.2. Testing Laboratory	5
1.3. Applicant Information	6
1.4. Manufacturer Information.....	6
1.5. Information of EUT.....	7
1.6. EUT Antenna Locations	9
1.7. The Maximum Reported SAR _{1g}	10
1.8. Test Date	10
2. SAR Measurements System Configuration	11
2.1. SAR Measurement Set-up	11
2.2. DASY5 E-field Probe System	12
2.2.1. EX3DV4 Probe Specification	12
2.2.2. E-field Probe Calibration	13
2.3. Other Test Equipment	13
2.3.1. Device Holder for Transmitters	13
2.3.2. Phantom	14
2.4. Scanning Procedure	14
2.5. Data Storage and Evaluation	16
2.5.1. Data Storage.....	16
2.5.2. Data Evaluation by SEMCAD	16
3. Laboratory Environment.....	18
4. Tissue-equivalent Liquid	19
4.1. Tissue-equivalent Liquid Ingredients.....	19
4.2. Tissue-equivalent Liquid Properties	21
5. System Check.....	22
5.1. Description of System Check.....	22
5.2. System Check Results.....	24
6. Operational Conditions during Test	25
6.1. General Description of Test Procedures	25
6.2. Test Positions.....	25
6.2.1. Against Phantom Head	25
6.2.2. Body Worn Configuration.....	25
6.3. Measurement Variability.....	27
6.4. Test Configuration	28
6.4.1. GSM Test Configuration.....	28
6.4.2. UMTS Test Configuration	29
6.4.3. HSDPA Test Configuration	29
6.4.4. HSUPA Test Configuration	31
6.4.5. WIFI Test Configuration	33

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 4 of 220

7.	Test Results	34
7.1.	Conducted Power Results	34
7.2.	Standalone SAR Test Exclusion Considerations	40
7.3.	SAR Test Results	41
7.3.1.	GSM 850.....	41
7.3.2.	GSM 1900.....	43
7.3.3.	UMTS Band II	45
7.3.4.	UMTS Band V	47
7.3.5.	WIFI	48
7.4.	Simultaneous Transmission Conditions	49
8.	Measurement Uncertainty	55
9.	Main Test Instruments	56
	ANNEX A: Test Layout	57
	ANNEX B: System Check Results	61
	ANNEX C: Plots Results	67
	ANNEX D: Probe Calibration Certificate	172
	ANNEX E: D835V2 Dipole Calibration Certificate	183
	ANNEX F: D1900V2 Dipole Calibration Certificate	191
	ANNEX G: D2450V2 Dipole Calibration Certificate	199
	ANNEX H: DAE4 Calibration Certificate.....	207
	ANNEX I: The EUT Appearances and Test Configuration	210
	ANNEX J: System Validation.....	220

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 5 of 220

1. General Information

1.1. Notes of the Test Report

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L2264.

TA Technology (Shanghai) Co., Ltd. guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at TA Technology (Shanghai) Co., Ltd. at the time of execution of the test.

TA Technology (Shanghai) Co., Ltd. is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. The sample under test was selected by the Client. This report only refers to the item that has undergone the test.

This report alone does not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of **TA Technology (Shanghai) Co., Ltd.** and the Accreditation Bodies, if it applies.

If the electronic report is inconsistent with the printed one, it should be subject to the latter.

1.2. Testing Laboratory

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Yang Weizhong
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	yangweizhong@ta-shanghai.com

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 6 of 220

1.3. Applicant Information

Company: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.4. Manufacturer Information

Company: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District, Shenzhen, 518129, P.R.C

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 7 of 220

1.5. Information of EUT

General Information

Device Type:	Portable Device	
Exposure Category:	Uncontrolled Environment / General Population	
State of Sample:	Prototype Unit	
Product IMEI:	865246020001825	
Hardware Version:	V2.0	
Software Version:	Y221-U33V100R001C00B103	
Antenna Type:	Internal Antenna	
Device Operating Configurations :		
Test Mode(s):	GSM 850/GSM 1900; UMTS Band II/UMTS Band V; 802.11b/g/n HT20/n HT40;	
Test Modulation:	(GSM)GMSK; (UMTS)QPSK; (WIFI)CCK;	
Device Class:	B	
HSUPA UE Category:	6	
HSPA+ UE Downlink Category:	14	
GPRS Multislot Class(12):	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
EGPRS Multislot Class(12):	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
Test Frequency Range(s):	Mode	Tx (MHz)
	GSM 850	824.2 ~ 848.8
	GSM 1900	1850.2 ~ 1909.8
	UMTS Band II	1852.4 ~ 1907.6
	UMTS Band V	826.4 ~ 846.6
	Bluetooth	2402 ~2480
	WIFI	2412 ~2462
Power Class:	GSM 850: 4	
	GSM 1900: 1	
	UMTS Band II/V: 3	
Power Level:	GSM 850: level 5	
	GSM 1900: level 0	
	UMTS Band II/V: all up bits	

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 8 of 220

Auxiliary Equipment Details

Name	Model	Manufacturer	Capacity	S/N
Battery 1	HB5N1H	Huawei Technologies Co., Ltd.	1500mAh	UBDE512X21833664
Battery 2	HB5N1H	Huawei Technologies Co., Ltd.	1500mAh	MLCE507921862477
Battery 3	HB5N1	Huawei Technologies Co., Ltd.	1350mAh	BAAE417G15864625
Battery 4	HB5N1	Huawei Technologies Co., Ltd.	1350mAh	GAGE517L15820440


Name	Model	Manufacturer
Earphone 1	1293#+3283#3.5MM-150	Quancheng
Earphone 2	MEMD1532B528000	Lianchuang
Earphone 3	HA1-3	Goertek

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 9 of 220

1.6. EUT Antenna Locations



Mobile Hotspot Sides for SAR Testing

Mode	Back Side	Front Side	Left Edge	Right Edge	Top Edge	Bottom Edge
GSM 850	Yes	Yes	Yes	Yes	N/A	Yes
GSM 1900	Yes	Yes	Yes	Yes	N/A	Yes
UMTS Band II	Yes	Yes	Yes	Yes	N/A	Yes
UMTS Band V	Yes	Yes	Yes	Yes	N/A	Yes
2.4GHz WLAN	Yes	Yes	N/A	Yes	Yes	N/A

Note: When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 10 of 220

1.7. The Maximum Reported SAR_{1g}

Head SAR Configuration

Mode	Test Position	Channel /Frequency(MHz)	Limit SAR _{1g} 1.6 W/kg	
			Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
GSM 850	Left Cheek	190/836.6	0.656	0.726
GSM 1900	Right Cheek	661/1880	0.619	0.794
UMTS Band II	Right Cheek	9538/1907.6	1.070	1.263
UMTS Band V	Left/Cheek	4183/836.6	0.603	0.713
WiFi(802.11b)	Left/Cheek	11/2462	0.380	0.501

Body Worn Configuration

Mode	Test Position	Channel /Frequency(MHz)	Limit SAR _{1g} 1.6 W/kg	
			Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
GPRS 850, 4 Txslots	Back Side	128/824.2	1.080	1.323
EGPRS 1900, 4 Txslots	Back Side	661/1880	0.974	1.187
UMTS Band II	Back Side	9400/1880	0.980	1.130
UMTS Band V	Back Side	4183/836.6	0.725	0.858
WiFi(802.11b)	Back Side	11/2462	0.320	0.422

Hotspot SAR Configuration

Mode	Test Position	Channel /Frequency(MHz)	Limit SAR _{1g} 1.6 W/kg	
			Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
GPRS 850, 4 Txslots	Back Side	128/824.2	1.080	1.323
EGPRS 1900, 4 Txslots	Back Side	661/1880	0.974	1.187
UMTS Band II	Back Side	9400/1880	0.980	1.130
UMTS Band V	Back Side	4183/836.6	0.725	0.858
WiFi(802.11b)	Back Side	11/2462	0.320	0.422

1.8. Test Date

The test performed from July 9, 2014 to July 14, 2014.

2. SAR Measurements System Configuration

2.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- A unit to operate the optical surface detector which is connected to the EOC.
- The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
- The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003
- DASY5 software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- System validation dipoles allowing to validate the proper functioning of the system.




Figure SAR Lab Test Measurement Set-up

2.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

2.2.1. EX3DV4 Probe Specification

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



Figure .EX3DV4 E-field Probe



Figure . EX3DV4 E-field probe

2.2.2. E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m^3).

2.3. Other Test Equipment

2.3.1. Device Holder for Transmitters

The DASY device holder is designed to cope with the different positions given in the standard.

It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Figure Device Holder

2.3.2. Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden Figure. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness	2±0.1 mm
Filling Volume	Approx. 20 liters
Dimensions	810 x 1000 x 500 mm (H x L x W) Available Special



Figure Generic Twin Phantom

2.4. Scanning Procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

- The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max. $\pm 5\%$.
- The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)
- Area Scan
The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 15 of 220

spacing is set according to FCC KDB Publication 865664. During scan the distance of the probe to the phantom remains unchanged.

After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

- Zoom Scan

After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm.

- Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space.

They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation.

- A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

Table : Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm) $\Delta z_{\text{zoom}}(n)$	Minimum Zoom Scan Volume (mm) (x,y,z)
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≥ 22

2.5. Data Storage and Evaluation

2.5.1. Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “.DAE4”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

2.5.2. Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, a_{i0} , a_{i1} , a_{i2}
	- Conversion factor	ConvF _i
	- Diode compression point	Dcp _i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	
	- Density	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 17 of 220

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c f / d c p_i$$

With V_i = compensated signal of channel i (i = x, y, z)

U_i = input signal of channel i (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp_i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: $E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$

H-field probes: $H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$

With V_i = compensated signal of channel i (i = x, y, z)

$Norm_i$ = sensor sensitivity of channel i (i = x, y, z)
[mV/(V/m)²] for E-field Probes

$ConvF$ = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot})^2 \cdot \sigma / (\rho \cdot 1000)$$

with **SAR** = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

= conductivity in [mho/m]

or [Siemens/m]

= equivalent tissue density

in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

3. Laboratory Environment

Table : The Requirements of the Ambient Conditions

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards.	
Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 19 of 220

4. Tissue-equivalent Liquid

4.1. Tissue-equivalent Liquid Ingredients

The liquid is consisted of water, salt, Glycol, Sugar, Preventol and Cellulose. The liquid has previously been proven to be suited for worst-case. The table 3 and table 4 show the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB 865664 D01.

Table : Composition of the Head Tissue Equivalent Matter

MIXTURE%	FREQUENCY(Brain) 835MHz
Water	41.45
Sugar	56
Salt	1.45
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	f=835MHz $\epsilon=41.5$ $\sigma=0.9$

MIXTURE%	FREQUENCY(Brain) 1900MHz
Water	55.242
Glycol monobutyl	44.452
Salt	0.306
Dielectric Parameters Target Value	f=1900MHz $\epsilon=40.0$ $\sigma=1.40$

MIXTURE%	FREQUENCY(Brain) 2450MHz
Water	62.7
Glycol	36.8
Salt	0.5
Dielectric Parameters Target Value	f=2450MHz $\epsilon=39.2$ $\sigma=1.80$

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 20 of 220

Table : Composition of the Body Tissue Equivalent Matter

MIXTURE%	FREQUENCY(Body) 835MHz
Water	52.5
Sugar	45
Salt	1.4
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	f=835MHz $\epsilon=55.2$ $\sigma=0.97$

MIXTURE%	FREQUENCY (Body) 1900MHz
Water	69.91
Glycol monobutyl	29.96
Salt	0.13
Dielectric Parameters Target Value	f=1900MHz $\epsilon=53.3$ $\sigma=1.52$

MIXTURE%	FREQUENCY(Body) 2450MHz
Water	73.2
Glycol	26.7
Salt	0.1
Dielectric Parameters Target Value	f=2450MHz $\epsilon=52.7$ $\sigma=1.95$

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 21 of 220

4.2. Tissue-equivalent Liquid Properties

Table : Dielectric Performance of Tissue Simulating Liquid

Frequency	Test Date	Temp ℃	Measured Dielectric Parameters		Target Dielectric Parameters		Limit (Within ±5%)	
			ϵ_r	$\sigma(\text{s/m})$	ϵ_r	$\sigma(\text{s/m})$	Dev $\epsilon_r(\%)$	Dev $\sigma(\%)$
835MHz (head)	2014-7-10	21.5	41.4	0.92	41.5	0.90	-0.24	2.22
1900MHz (head)	2014-7-13	21.5	40.5	1.34	40.0	1.40	1.25	-4.29
2450MHz (head)	2014-7-14	21.5	39.1	1.80	39.2	1.80	-0.26	0.00
835MHz (body)	2014-7-9	21.5	55.1	0.99	55.2	0.97	-0.18	2.06
1900MHz (body)	2014-7-11	21.5	53.1	1.52	53.3	1.52	-0.38	0.00
2450MHz (body)	2014-7-14	21.5	52.1	1.99	52.7	1.95	-1.14	2.05

5. System Check

5.1. Description of System Check

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulates were measured every day using the dielectric probe kit and the network analyzer. A system check measurement was made following the determination of the dielectric parameters of the simulates, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system check results (dielectric parameters and SAR values) are given in the table 6 and table 7.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.




Figure System Check Set-up

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 23 of 220

Justification for Extended SAR Dipole Calibrations

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (< -20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB 865664 D01:

Dipole D835V2 SN: 4d020			
Head Liquid			
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)
8/26/2011	-27.7	/	52.9 Ω -3.1 j Ω
8/25/2012	-29.1	5.0%	55.0 Ω -2.9 j Ω
8/24/2013	-26.6	4.1%	55.3 Ω -3.2 j Ω
Body Liquid			
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)
8/26/2011	-25.1	/	48.7 Ω -5.4 j Ω
8/25/2012	-24.3	3.2%	50.6 Ω -4.7 j Ω
8/24/2013	-24.7	1.6%	51.1 Ω -4.5 j Ω

Dipole D1900V2 SN: 5d060			
Head Liquid			
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)
8/31/2011	-22.3	/	52.6 Ω +7.5 j Ω
8/30/2012	-21.7	2.7%	51.4 Ω +7.9 j Ω
8/29/2013	-21.4	4.2%	50.5 Ω + 8.1 j Ω
Body Liquid			
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)
8/31/2011	-21.3	/	47.3 Ω + 7.9 j Ω
8/30/2012	-20.9	1.9%	45.9 Ω + 8.2 j Ω
8/29/2013	-20.4	4.4%	44.8 Ω + 8.4 j Ω

Dipole D2450V2 SN: 786			
Head Liquid			
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)
8/29/2011	-25.5	/	55.0 Ω + 2.4 j Ω
8/28/2012	-26.8	5.1%	56.5 Ω + 2.1 j Ω
8/27/2013	-26.4	3.5%	56.9 Ω + 2 j Ω
Body Liquid			
Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)
8/29/2011	-29.0	/	50.4 Ω + 3.5 j Ω
8/28/2012	-29.9	3.1%	52.1 Ω + 2.9 j Ω
8/27/2013	-28.2	2.8%	52.7 Ω + 2.8 j Ω

Page 24 of 220

Frequency	Test Date	Dielectric Parameters		250mW Measured SAR _{1g}	1W Normalized SAR _{1g}	1W Target SAR _{1g}	Limit (±10% Deviation)
		ε _r	σ(s/m)	(W/kg)			
835MHz	2014-7-9	55.1	0.99	2.41	9.64	9.46	1.90%
1900MHz	2014-7-11	53.1	1.52	9.93	39.72	41.70	-4.75%
2450MHz	2014-7-14	52.1	1.99	12.50	50.00	51.70	-3.29%

Note: 1. The graph results see ANNEX B.
2. Target Values used derive from the calibration certificate

6. Operational Conditions during Test

6.1. General Description of Test Procedures

A communication link is set up with a System Simulator (SS) by air link, and a call is established. The EUT is commanded to operate at maximum transmitting power.

Connection to the EUT is established via air interface with E5515C, and the EUT is set to maximum output power by E5515C. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. The antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the EUT. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the EUT by at least 30 dB.

6.2. Test Positions

6.2.1. Against Phantom Head

Measurements were made in "cheek" and "tilt" positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

6.2.2. Body Worn Configuration

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations.

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. Per FCC KDB Publication 648474 D04, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 26 of 220

different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.3. Measurement Variability

Per FCC KDB Publication 865664 D01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

6.4. Test Configuration

6.4.1. GSM Test Configuration

SAR tests for GSM 850 and GSM 1900, a communication link is set up with a System Simulator (SS) by air link. Using E5515C the power level is set to “5” for GSM 850, set to “0” for GSM 1900. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5. The EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

Output power of reductions:

Table : The allowed power reduction in the multi-slot configuration

Number of timeslots in uplink assignment	Permissible nominal reduction of maximum output power,(dB)
1	0
2	0 to 3,0
3	1,8 to 4,8
4	3,0 to 6,0

6.4.2. UMTS Test Configuration

6.4.2.1. Output power Verification

Maximum output power is verified on the High, Middle and Low channel according to the procedures described in section 5.2 of 3GPP TS 34. 121, using the appropriate RMC or AMR with TPC(transmit power control) set to all up bits for WCDMA/HSDPA or applying the required inner loop power control procedures to the maximum output power while HSUPA is active. Results for all applicable physical channel configuration (DPCCH, DPDCH_n and spreading codes, HSDPA, HSPA) should be tabulated in the SAR report. All configuration that are not supported by the DUT or can not be measured due to technical or equipment limitations should be clearly identified

6.4.2.2. Head SAR Measurements

SAR for head exposure configurations in voice mode is measured using a 12.2kbps RMC with TPC bits configured to all up bits. SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2kbps AMR is less than 1/4 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2kbps AMR with a 3.4 kbps SRB(Signaling radio bearer) using the exposure configuration that results in the highest SAR in 12.2kbps RMC for that RF channel.

6.4.2.3. Body SAR Measurements

SAR for body exposure configurations in voice and data modes is measured using 12.2kbps RMC with TPC bits configured to all up bits. SAR for other spreading codes and multiple DPDCH_n, when supported by the DUT, are not required when the maximum average output of each RF channel, for each spreading code and DPDCH_n configuration, are less than 1/4 dB higher than those measured in 12.2kbps RMC. Otherwise, SAR is measured on the maximum output channel with an applicable RMC configuration for the corresponding spreading code or DPDCH_n using the exposure configuration that results in the highest SAR with 12.2 kbps RMC. When more than 2 DPDCH_n are supported by the DUT, it may be necessary to configure additional DPDCH_n for a DUT using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

6.4.3. HSDPA Test Configuration

SAR for body exposure configurations is measured according to the 'Body SAR Measurements' procedures of that section. In addition, body SAR is also measured for HSDPA when the maximum average output of each RF channel with HSDPA active is at least ¼ dB higher than that measured without HSDPA using 12.2 kbps RMC or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA.

HSDPA should be configured according to the UE category of a test device. The number of HSDSCH/ HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 30 of 220

sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors(β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) should be set according to values indicated in the Table below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Table : Subtests for UMTS Release 5 HSDPA

Sub-set	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (note 1, note 2)	CM(dB) (note 3)	MPR(dB)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (note 4)	15/15 (note 4)	64	12/15 (note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1.A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 8$ ($A_{hs} = 30/15$) with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 7$ ($A_{hs} = 24/15$) with $\beta_{hs} = 24/15 * \beta_c$.

Note3: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TFC1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Table : Settings of required H-Set 1 QPSK in HSDPA mode

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	534
Inter-TTI Distance	TTI's	3
Number of HARQ Processes	Processes	2
Information Bit Payload (N_{INF})	Bits	3202
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	4800
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	9600
Coding Rate	/	0.67
Number of Physical Channel Codes	Codes	5
Modulation	/	QPSK

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 31 of 220

Table : HSDPA UE category

HS-DSCH Category	Maximum HS-DSCH Codes Received	Minimum Inter-TTI Interval	Maximum Transport Bits/HS-DSCH	Total Channel
1	5	3	7298	19200
2	5	3	7298	28800
3	5	2	7298	28800
4	5	2	7298	38400
5	5	1	7298	57600
6	5	1	7298	67200
7	10	1	14411	115200
8	10	1	14411	134400
9	15	1	25251	172800
10	15	1	27952	172800
11	5	2	3630	14400
12	5	1	3630	28800
13	15	1	34800	259200
14	15	1	42196	259200
15	15	1	23370	345600
16	15	1	27952	345600

6.4.4. HSUPA Test Configuration

Body SAR is also measured for HSPA when the maximum average output of each RF channel with HSPA active is at least $\frac{1}{4}$ dB higher than that measured without HSPA using 12.2 kbps RMC or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2, according to the highest body SAR configuration in 12.2 kbps RMC without HSPA.⁴⁰

Due to inner loop power control requirements in HSPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA should be configured according to the β values indicated below as well as other applicable procedures described in the 'WCDMA Handset' and 'Release 5 HSDPA Data Devices' sections of 3 G device.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 32 of 220

Table : Sub-Test 5 Setup for Release 6 HSUPA

Sub-set	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-

DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the

signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the

signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Figure 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Table : HSUPA UE category

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E- DCH TTI (ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	2	2 SF2 & 2 SF4	11484	5.76
	4	4	10		20000	2.00
7 (No DPDCH)	4	8	2	2 SF2 & 2 SF4	22996	?
	4	4	10		20000	?

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4.

UE Categories 1 to 6 supports QPSK only. UE Category 7 supports QPSK and 16QAM. (TS25.306-7.3.0)

6.4.5. WIFI Test Configuration

For WLAN SAR testing, WLAN engineering testing software installed on the DUT can provide continuous transmitting RF signal. The Tx power is set to 19 for 802.11 b mode by software. This RF signal utilized in SAR measurement has almost 100% duty cycle and its crest factor is 1.

For the 802.11b/g/n SAR tests, a communication link is set up with the test mode software for WIFI mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest data rate. Testing at higher data rates is not required when the maximum average output power is less than 0.25dB higher than those measured at the lowest data rate.

802.11b/g/n operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g/n modes are tested on the maximum average output channel.

SAR is not required for 802.11g/n channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 34 of 220

7. Test Results

7.1. Conducted Power Results

Table : Conducted Power Measurement Results

GSM 850		Burst Conducted Power(dBm)			/	Average power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8		128/824.2	190/836.6	251/848.8
GSM		32.53	32.56	32.53	-9.03dB	23.50	23.53	23.50
GPRS (GMSK)	1Txslot	32.45	32.56	32.47	-9.03dB	23.42	23.53	23.44
	2Txslots	31.45	31.52	31.45	-6.02dB	25.43	25.50	25.43
	3Txslots	29.50	29.54	29.42	-4.26dB	25.24	25.28	25.16
	4Txslots	28.62	28.61	28.51	-3.01dB	25.61	25.60	25.50
EGPRS (GMSK)	1Txslot	32.42	32.51	32.45	-9.03dB	23.39	23.48	23.42
	2Txslots	31.42	31.49	31.42	-6.02dB	25.40	25.47	25.40
	3Txslots	29.47	29.47	29.50	-4.26dB	25.21	25.21	25.24
	4Txslots	28.56	28.61	28.57	-3.01dB	25.55	25.60	25.56
EGPRS (8PSK)	1Txslot	32.38	32.50	32.42	-9.03dB	23.35	23.47	23.39
	2Txslots	31.43	31.49	31.43	-6.02dB	25.41	25.47	25.41
	3Txslots	29.49	29.50	29.50	-4.26dB	25.23	25.24	25.24
	4Txslots	28.60	28.64	28.50	-3.01dB	25.59	25.63	25.49
GSM 1900		Burst Conducted Power(dBm)			/	Average power(dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8		512/1850.2	661/1880	810/1909.8
GSM		28.70	28.92	28.94	-9.03dB	19.67	19.89	19.91
GPRS (GMSK)	1Txslot	28.64	28.85	28.85	-9.03dB	19.61	19.82	19.82
	2Txslots	27.62	27.90	27.89	-6.02dB	21.60	21.88	21.87
	3Txslots	25.67	26.06	26.09	-4.26dB	21.41	21.80	21.83
	4Txslots	24.79	25.14	25.20	-3.01dB	21.78	22.13	22.19
EGPRS (GMSK)	1Txslot	28.56	28.86	28.81	-9.03dB	19.53	19.83	19.78
	2Txslots	27.58	27.90	27.90	-6.02dB	21.56	21.88	21.88

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 35 of 220

	3Txslots	25.68	26.06	26.12	-4.26dB	21.42	21.80	21.86
	4Txslots	24.71	25.14	25.24	-3.01dB	21.70	22.13	22.23
EGPRS (8PSK)	1Txslot	28.55	28.85	28.82	-9.03dB	19.52	19.82	19.79
	2Txslots	27.64	27.90	27.90	-6.02dB	21.62	21.88	21.88
	3Txslots	25.69	26.00	26.10	-4.26dB	21.43	21.74	21.84
	4Txslots	24.76	25.12	25.25	-3.01dB	21.75	22.11	22.24

Note:

1) Division Factors

To average the power, the division factor is as follows:

1Txslot = 1 transmit time slot out of 8 time slots

=> conducted power divided by (8/1) => -9.03 dB

2Txslots = 2 transmit time slots out of 8 time slots

=> conducted power divided by (8/2) => -6.02 dB

3Txslots = 3 transmit time slots out of 8 time slots

=> conducted power divided by (8/3) => -4.26 dB

4Txslots = 4 transmit time slots out of 8 time slots

=> conducted power divided by (8/4) => -3.01 dB

2) Average power numbers

The maximum power numbers are marks in bold.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 36 of 220

UMTS Band II		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		9262/1852.4	9400/1880	9538/1907.6
RMC	12.2kbps RMC	22.37	22.38	22.28
	64kbps RMC	22.35	22.33	22.16
	144kbps RMC	22.40	22.34	22.21
	384kbps RMC	22.37	22.35	22.24
HSDPA	Sub - Test 1	22.36	22.37	22.27
	Sub - Test 2	22.33	22.32	22.16
	Sub - Test 3	21.97	21.94	21.81
	Sub - Test 4	22.00	21.95	21.83
HSUPA	Sub - Test 1	20.54	20.57	20.40
	Sub - Test 2	19.04	19.08	18.92
	Sub - Test 3	20.22	20.23	20.18
	Sub - Test 4	19.16	19.17	19.07
	Sub - Test 5	20.56	20.59	20.41
UMTS Band V		Conducted Power (dBm)		
		Channel/Frequency(MHz)		
		4132/826.4	4183/836.6	4233/846.6
RMC	12.2kbps RMC	22.19	22.27	22.30
	64kbps RMC	22.19	22.29	22.31
	144kbps RMC	22.18	22.28	22.30
	384kbps RMC	22.17	22.29	22.33
HSDPA	Sub - Test 1	22.28	22.30	22.19
	Sub - Test 2	22.26	22.24	22.08
	Sub - Test 3	21.89	21.87	21.73
	Sub - Test 4	21.93	21.87	21.75
HSUPA	Sub - Test 1	20.46	20.50	20.32
	Sub - Test 2	18.96	19.01	18.84
	Sub - Test 3	20.14	20.16	20.10
	Sub - Test 4	19.08	19.10	18.99
	Sub - Test 5	20.48	20.52	20.33

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 37 of 220

BT	Conducted Power (dBm)		
	Channel/Frequency(MHz)		
	Ch 0/2402 MHz	Ch 39/2441 MHz	Ch 78/2480 MHz
GFSK(PK)	7.30	7.50	7.50
GFSK(AV)	1.90	2.10	2.00

Mode	Channel/ Frequency(MHz)	Data rate (Mbps)	PK Power (dBm)	AV Power (dBm)
802.11b	1/2412	1	21.70	19.00
		2	21.70	18.80
		5.5	21.60	18.90
		11	21.60	18.50
	6/2437	1	21.90	19.20
		2	21.90	19.10
		5.5	21.90	19.20
		11	21.80	18.60
	11/2462	1	22.10	19.30
		2	22.00	19.20
		5.5	22.10	19.20
		11	22.10	18.90
802.11g	1/2412	6	22.10	11.50
		9	22.10	11.10
		12	22.00	10.60
		18	21.90	10.40
		24	21.80	10.10
		36	21.80	9.70
		48	21.90	9.70
		54	21.70	9.50
	6/2437	6	22.40	11.70
		9	22.40	11.00
		12	22.40	10.80
		18	22.30	10.50
		24	22.30	10.10
		36	22.10	10.00
		48	22.10	9.80
		54	22.10	9.80
	11/2462	6	22.50	11.70
		9	22.50	11.40
		12	22.50	10.90
		18	22.40	10.60

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 38 of 220

		24	22.40	10.60
		36	22.40	10.50
		48	22.30	10.50
		54	22.30	10.40
802.11n HT20	1/2412	MCS0	22.40	11.60
		MCS1	22.40	11.50
		MCS2	22.30	11.30
		MCS3	22.30	11.30
		MCS4	22.20	11.00
		MCS5	22.20	10.70
		MCS6	22.20	10.50
		MCS7	22.10	10.00
	6/2437	MCS0	22.80	11.80
		MCS1	22.80	11.60
		MCS2	22.80	10.80
		MCS3	22.70	10.50
		MCS4	22.60	10.30
		MCS5	22.60	10.00
		MCS6	22.50	9.70
		MCS7	22.50	9.50
	11/2462	MCS0	22.90	11.90
		MCS1	22.90	11.50
		MCS2	22.90	11.30
		MCS3	22.80	10.70
		MCS4	22.80	10.40
		MCS5	22.70	10.00
		MCS6	22.70	9.70
		MCS7	22.60	9.50
802.11n HT40	3/2422	MCS0	23.00	10.10
		MCS1	22.90	10.10
		MCS2	22.90	10.00
		MCS3	22.80	9.90
		MCS4	22.70	9.70
		MCS5	22.60	9.10
		MCS6	22.60	9.10
		MCS7	22.50	9.00
	6/2437	MCS0	23.40	10.30
		MCS1	23.40	10.20
		MCS2	23.30	9.60
		MCS3	23.20	9.20
		MCS4	23.30	8.90
		MCS5	23.20	8.70
		MCS6	23.10	8.30

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 39 of 220

		MCS7	23.10	8.20
	9/2452	MCS0	23.40	10.40
		MCS1	23.40	10.10
		MCS2	23.30	9.80
		MCS3	23.20	9.30
		MCS4	23.20	8.80
		MCS5	23.10	8.70
		MCS6	23.10	8.20
		MCS7	23.00	8.00

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 40 of 220

7.2. Standalone SAR Test Exclusion Considerations

Per FCC KDB 447498 D01, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Band	Configuration	Frequency (MHz)	Maximum Power (dBm)	Separation Distance (mm)	Calculation Result	SAR Exclusion Thresholds	Standalone SAR
Bluetooth	Head	2480	3.5	5	0.70	3.0	No
	Body	2480	3.5	10	0.35	3.0	No
Wifi 2.4GHz	Head	2462	20.5	5	35.34	3.0	Yes
	Body	2462	20.5	10	17.67	3.0	Yes

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 41 of 220

7.3. SAR Test Results

7.3.1. GSM 850

Table : SAR Values [GSM 850 (GSM/GPRS/EGPRS)]

Test Position	Channel/ Frequency (MHz)	Time slot	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left Cheek	190/836.6	GSM	1:8.3	33	32.56	-0.049	0.656	1.11	0.726	Figure13
Left/Tilt	190/836.6	GSM	1:8.3	33	32.56	0.100	0.397	1.11	0.439	Figure14
Right Cheek	190/836.6	GSM	1:8.3	33	32.56	-0.140	0.562	1.11	0.622	Figure15
Right/Tilt	190/836.6	GSM	1:8.3	33	32.56	0.050	0.404	1.11	0.447	Figure16
Worst Case Position of Head With Battery 2										
Left Cheek	190/836.6	GSM	1:8.3	33	32.56	-0.120	0.612	1.11	0.677	Figure17
Worst Case Position of Head With Battery 3										
Left Cheek	190/836.6	GSM	1:8.3	33	32.56	-0.040	0.618	1.11	0.684	Figure18
Worst Case Position of Head With Battery 4										
Left Cheek	190/836.6	GSM	1:8.3	33	32.56	0.060	0.626	1.11	0.693	Figure19
Worst Case Position of Head With SIM2										
Left Cheek	190/836.6	GSM	1:8.3	33	32.56	-0.120	0.610	1.11	0.675	Figure20
Test position of Body (Distance 10mm)										
Back Side	190/836.6	GSM	1:8.3	33	32.56	0.190	0.694	1.11	0.768	Figure21
Front Side	190/836.6	GSM	1:8.3	33	32.56	-0.020	0.505	1.11	0.559	Figure22
Test position of Body (Distance 10mm)										
Back Side	251/848.8	4 Txslots	1:2.07	29.5	28.51	-0.030	0.807	1.26	1.014	Figure23
	190/836.6	4 Txslots	1:2.07	29.5	28.61	-0.050	0.907	1.23	1.113	Figure24
	128/824.2	4 Txslots	1:2.07	29.5	28.62	0.080	0.980	1.22	1.200	Figure25
Front Side	251/848.8	4 Txslots	1:2.07	29.5	28.51	-0.190	0.716	1.26	0.899	Figure26
	190/836.6	4 Txslots	1:2.07	29.5	28.61	0.110	0.784	1.23	0.962	Figure27
	128/824.2	4 Txslots	1:2.07	29.5	28.62	-0.050	0.823	1.22	1.008	Figure28
Left Edge	190/836.6	4 Txslots	1:2.07	29.5	28.61	-0.010	0.302	1.23	0.371	Figure29
Right Edge	190/836.6	4 Txslots	1:2.07	29.5	28.61	0.010	0.399	1.23	0.490	Figure30

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 42 of 220

Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	190/836.6	4 Txslots	1:2.07	29.5	28.61	0.150	0.040	1.23	0.049	Figure31
Worst Case Position of Body With Battery 2 (Distance 10mm)										
Back Side	128/824.2	4 Txslots	1:2.07	29.5	28.62	0.010	1.080	1.22	1.323	Figure32
Worst Case Position of Body With Battery 3 (Distance 10mm)										
Back Side	128/824.2	4 Txslots	1:2.07	29.5	28.62	0.030	1.060	1.22	1.298	Figure33
Worst Case Position of Body With Battery 4 (Distance 10mm)										
Back Side	128/824.2	4 Txslots	1:2.07	29.5	28.62	-0.054	1.000	1.22	1.225	Figure34
Worst Case Position of Body With EGPRS (Distance 10mm)										
Back Side	128/824.2	4 Txslots	1:2.07	29.5	28.56	0.060	1.000	1.24	1.242	Figure35
Worst Case Position of Body With SIM2(Distance 10mm)										
Back Side	128/824.2	4 Txslots	1:2.07	29.5	28.62	-0.130	1.080	1.22	1.323	Figure36
Worst Case Position of SAR (1st Repeated SAR, Distance 10mm)										
Back Side	128/824.2	4 Txslots	1:2.07	29.5	28.62	0.051	1.070	1.22	1.310	Figure37

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is optional for such test configuration(s).
3. When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.
4. When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.
5. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Table : SAR Measurement Variability Results [GSM 850(GSM/GPRS/EGPRS)]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Back Side	128/824.2	1.080	1.070	1.01	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was preformed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 43 of 220

7.3.2. GSM 1900

Table : SAR Values [GSM 1900(GSM/GPRS/EGPRS)]

Test Position	Channel/ Frequency (MHz)	Time slot	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left Cheek	661/1880	GSM	1:8.3	30	28.92	-0.034	0.373	1.28	0.478	Figure38
Left/Tilt	661/1880	GSM	1:8.3	30	28.92	-0.080	0.146	1.28	0.187	Figure39
Right Cheek	661/1880	GSM	1:8.3	30	28.92	0.038	0.539	1.28	0.691	Figure40
Right/Tilt	661/1880	GSM	1:8.3	30	28.92	0.020	0.149	1.28	0.191	Figure41
Worst Case Position of Head With Battery 2										
Right Cheek	661/1880	GSM	1:8.3	30	28.92	0.044	0.541	1.28	0.694	Figure42
Worst Case Position of Head With Battery 3										
Right Cheek	661/1880	GSM	1:8.3	30	28.92	0.023	0.548	1.28	0.703	Figure43
Worst Case Position of Head With Battery 4										
Right Cheek	661/1880	GSM	1:8.3	30	28.92	0.026	0.526	1.28	0.675	Figure44
Worst Case Position of Head With SIM2										
Right Cheek	661/1880	GSM	1:8.3	30	28.92	-0.024	0.619	1.28	0.794	Figure45
Test position of Body (Distance 10mm)										
Back Side	661/1880	GSM	1:8.3	30	28.92	0.150	0.535	1.28	0.686	Figure46
Front Side	661/1880	GSM	1:8.3	30	28.92	-0.040	0.432	1.28	0.554	Figure47
Test position of Body (Distance 10mm)										
Back Side	810/1909.8	4 Txslots	1:2.07	26	25.2	0.025	0.888	1.20	1.068	Figure48
	661/1880	4 Txslots	1:2.07	26	25.14	0.150	0.930	1.22	1.134	Figure49
	512/1850.2	4 Txslots	1:2.07	26	24.79	-0.070	0.748	1.32	0.988	Figure50
Front Side	810/1909.8	4 Txslots	1:2.07	26	25.2	-0.020	0.783	1.20	0.941	Figure51
	661/1880	4 Txslots	1:2.07	26	25.14	-0.140	0.761	1.22	0.928	Figure52
	512/1850.2	4 Txslots	1:2.07	26	24.79	-0.110	0.664	1.32	0.877	Figure53
Left Edge	661/1880	4 Txslots	1:2.07	26	25.14	-0.090	0.134	1.22	0.163	Figure54
Right Edge	661/1880	4 Txslots	1:2.07	26	25.14	0.110	0.215	1.22	0.262	Figure55
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	661/1880	4 Txslots	1:2.07	26	25.14	0.020	0.327	1.22	0.399	Figure56

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 44 of 220

Worst Case Position of Body With Battery 2 (Distance 10mm)										
Back Side	661/1880	4 Txslots	1:2.07	26	25.14	0.120	0.959	1.22	1.169	Figure57
Worst Case Position of Body With Battery 3 (Distance 10mm)										
Back Side	661/1880	4 Txslots	1:2.07	26	25.14	0.130	0.909	1.22	1.108	Figure58
Worst Case Position of Body With Battery 4 (Distance 10mm)										
Back Side	661/1880	4 Txslots	1:2.07	26	25.14	0.070	0.892	1.22	1.087	Figure59
Worst Case Position of Body With EGPRS (Distance 10mm)										
Back Side	661/1880	4 Txslots	1:2.07	26	25.14	-0.010	0.974	1.22	1.187	Figure60
Worst Case Position of Body With SIM2(Distance 10mm)										
Back Side	661/1880	4 Txslots	1:2.07	26	25.14	0.150	0.911	1.22	1.110	Figure61
Worst Case Position of SAR (1 st Repeated SAR, Distance 10mm)										
Back Side	661/1880	4 Txslots	1:2.07	26	25.14	0.170	0.874	1.22	1.065	Figure62

Note: 1.The value with blue color is the maximum SAR Value of each test band.

- Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is optional for such test configuration(s).
- When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.
- When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.
- Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Table : SAR Measurement Variability Results [GSM 1900(GSM/GPRS/EGPRS)]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Back Side	661/1880	0.974	0.874	1.11	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 45 of 220

7.3.3. UMTS Band II

Table : SAR Values [UMTS Band II (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left Cheek	9538/1907.6	RMC 12.2k	1:1	23	22.28	-0.053	0.652	1.18	0.770	Figure63
	9400/1880	RMC 12.2k	1:1	23	22.38	0.100	0.718	1.15	0.828	Figure64
	9262/1852.4	RMC 12.2k	1:1	23	22.37	-0.070	0.625	1.16	0.723	Figure65
Left/Tilt	9400/1880	RMC 12.2k	1:1	23	22.38	0.021	0.283	1.15	0.326	Figure66
Right Cheek	9538/1907.6	RMC 12.2k	1:1	23	22.28	0.180	1.070	1.18	1.263	Figure67
	9400/1880	RMC 12.2k	1:1	23	22.38	0.050	1.090	1.15	1.257	Figure68
	9262/1852.4	RMC 12.2k	1:1	23	22.37	0.031	1.010	1.16	1.168	Figure69
Right/Tilt	9400/1880	RMC 12.2k	1:1	23	22.38	0.150	0.283	1.15	0.326	Figure70
Worst Case Position of Head With Battery 2										
Right/Cheek	9400/1880	RMC 12.2k	1:1	23	22.38	0.023	1.030	1.15	1.188	Figure71
Worst Case Position of Head With Battery 3										
Right/Cheek	9400/1880	RMC 12.2k	1:1	23	22.38	0.025	1.030	1.15	1.188	Figure72
Worst Case Position of Head With Battery 4										
Right/Cheek	9400/1880	RMC 12.2k	1:1	23	22.38	0.140	0.944	1.15	1.089	Figure73
Worst Case Position of SAR (1 st Repeated SAR)										
Right/Cheek	9400/1880	RMC 12.2k	1:1	23	22.38	0.028	0.931	1.15	1.074	Figure74
Test position of Body (Distance 10mm)										
Back Side	9538/1907.6	RMC 12.2k	1:1	23	22.28	0.060	0.941	1.18	1.111	Figure75
	9400/1880	RMC 12.2k	1:1	23	22.38	0.090	0.980	1.15	1.130	Figure76
	9262/1852.4	RMC 12.2k	1:1	23	22.37	0.070	0.929	1.16	1.074	Figure77
Front Side	9538/1907.6	RMC 12.2k	1:1	23	22.28	-0.050	0.793	1.18	0.936	Figure78
	9400/1880	RMC 12.2k	1:1	23	22.38	-0.080	0.825	1.15	0.952	Figure79
	9262/1852.4	RMC 12.2k	1:1	23	22.37	0.060	0.779	1.16	0.901	Figure80
Left Edge	9400/1880	RMC 12.2k	1:1	23	22.38	0.050	0.190	1.15	0.219	Figure81
Right Edge	9400/1880	RMC 12.2k	1:1	23	22.38	0.090	0.307	1.15	0.354	Figure82

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 46 of 220

Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	9400/1880	RMC 12.2k	1:1	23	22.38	0.100	0.396	1.15	0.457	Figure83
Worst Case Position of Body With Battery 2 (Distance 10mm)										
Back Side	9400/1880	RMC 12.2k	1:1	23	22.38	0.130	0.970	1.15	1.119	Figure84
Worst Case Position of Body With Battery 3 (Distance 10mm)										
Back Side	9400/1880	RMC 12.2k	1:1	23	22.38	0.090	0.952	1.15	1.098	Figure85
Worst Case Position of Body With Battery 4 (Distance 10mm)										
Back Side	9400/1880	RMC 12.2k	1:1	23	22.38	0.090	0.954	1.15	1.100	Figure86

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is optional for such test configuration(s).
3. WCDMA mode were tested under RMC 12.2kbps without HSPA (HSDPA/HSUPA) inactive per KDB Publication 941225 D01. HSPA (HSDPA/HSUPA) SAR for body was not required since the average output power of the HSPA (HSDPA/HSUPA) subtests was not more than 0.25 dB higher than the RMC level and the maximum SAR for 12.2kbps RMC was less than 75% SAR limit.
4. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

Table : SAR Measurement Variability Results [UMTS Band II (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Right/Cheek	9400/1880	1.090	0.931	1.17	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 47 of 220

7.3.4. UMTS Band V

Table : SAR Values [UMTS Band V (WCDMA/HSDPA/HSUPA)]

Test Position	Channel/ Frequency (MHz)	Channel Type	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit SAR _{1g} 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left Cheek	4183/836.6	RMC 12.2k	1:1	23	22.27	0.080	0.599	1.18	0.709	Figure87
Left/Tilt	4183/836.6	RMC 12.2k	1:1	23	22.27	0.040	0.358	1.18	0.424	Figure88
Right Cheek	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.040	0.527	1.18	0.623	Figure89
Right/Tilt	4183/836.6	RMC 12.2k	1:1	23	22.27	0.120	0.362	1.18	0.428	Figure90
Worst Case Position of Head With Battery 2										
Left/Cheek	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.048	0.603	1.18	0.713	Figure91
Worst Case Position of Head With Battery 3										
Left/Cheek	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.010	0.577	1.18	0.683	Figure92
Worst Case Position of Head With Battery 4										
Left/Cheek	4183/836.6	RMC 12.2k	1:1	23	22.27	0.036	0.587	1.18	0.694	Figure93
Test position of Body (Distance 10mm)										
Back Side	4233/846.6	RMC 12.2k	1:1	23	22.3	0.010	0.605	1.17	0.711	Figure94
	4183/836.6	RMC 12.2k	1:1	23	22.27	0.020	0.724	1.18	0.857	Figure95
	4132/826.4	RMC 12.2k	1:1	23	22.19	0.020	0.671	1.21	0.809	Figure96
Front Side	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.110	0.559	1.18	0.661	Figure97
Left Edge	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.060	0.331	1.18	0.392	Figure98
Right Edge	4183/836.6	RMC 12.2k	1:1	23	22.27	0.010	0.429	1.18	0.508	Figure99
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.010	0.038	1.18	0.044	Figure100
Worst Case Position of Body With Battery 2 (Distance 10mm)										
Back Side	4183/836.6	RMC 12.2k	1:1	23	22.27	0.020	0.725	1.18	0.858	Figure101
Worst Case Position of Body With Battery 3 (Distance 10mm)										
Back Side	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.030	0.724	1.18	0.857	Figure102
Worst Case Position of Body With Battery 4 (Distance 10mm)										
Back Side	4183/836.6	RMC 12.2k	1:1	23	22.27	-0.030	0.687	1.18	0.813	Figure103

Note: 1. The value with blue color is the maximum SAR Value of each test band.

- Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is optional for such test configuration(s).
- WCDMA mode were tested under RMC 12.2kbps without HSPA (HSDPA/HSUPA) inactive per KDB Publication 941225 D01. HSPA (HSDPA/HSUPA) SAR for body was not required since the average output power of the HSPA (HSDPA/HSUPA) subtests was not more than 0.25 dB higher than the RMC level and the maximum SAR for 12.2kbps RMC was less than 75% SAR limit.
- Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 48 of 220

7.3.5. WIFI

Table : SAR Values(802.11b/g/n)

Test Position	Channel/ Frequency (MHz)	Service	Duty Cycle	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift ± 0.21dB	Limit of SAR 1.6 W/kg			
						Drift (dB)	Measured SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)	Graph Results
Test Position of Head										
Left Cheek	11/2462	DSSS	1:1	20.5	19.30	-0.047	0.379	1.32	0.500	Figure104
Left/Tilt	11/2462	DSSS	1:1	20.5	19.30	0.039	0.262	1.32	0.345	Figure105
Right Cheek	11/2462	DSSS	1:1	20.5	19.30	0.050	0.274	1.32	0.361	Figure106
Right/Tilt	11/2462	DSSS	1:1	20.5	19.30	0.170	0.239	1.32	0.315	Figure107
Worst Case Position of Head With Battery 2										
Left/Cheek	11/2462	DSSS	1:1	20.5	19.30	0.170	0.369	1.32	0.486	Figure108
Worst Case Position of Head With Battery 3										
Left/Cheek	11/2462	DSSS	1:1	20.5	19.30	0.160	0.375	1.32	0.494	Figure109
Worst Case Position of Head With Battery 4										
Left/Cheek	11/2462	DSSS	1:1	20.5	19.30	0.060	0.380	1.32	0.501	Figure110
Test position of Body (Distance 10mm)										
Back Side	11/2462	DSSS	1:1	20.5	19.30	0.110	0.320	1.32	0.422	Figure111
Front Side	11/2462	DSSS	1:1	20.5	19.30	0.034	0.100	1.32	0.132	Figure112
Left Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Right Edge	11/2462	DSSS	1:1	20.5	19.30	0.033	0.194	1.32	0.256	Figure113
Top Edge	11/2462	DSSS	1:1	20.5	19.30	0.140	0.121	1.32	0.160	Figure114
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Worst Case Position of Body With Battery 2 (Distance 10mm)										
Back Side	11/2462	DSSS	1:1	20.5	19.30	0.020	0.320	1.32	0.422	Figure115
Worst Case Position of Body With Battery 3 (Distance 10mm)										
Back Side	11/2462	DSSS	1:1	20.5	19.30	-0.020	0.300	1.32	0.395	Figure116
Worst Case Position of Body With Battery 4 (Distance 10mm)										
Back Side	11/2462	DSSS	1:1	20.5	19.30	-0.099	0.286	1.32	0.377	Figure117

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is optional for such test configuration(s).

3. KDB 248227-SAR is not required for 802.11g/n channels when the maximum average output power is less than $\frac{1}{4}$ dB higher than measured on the corresponding 802.11b channels.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 49 of 220

7.4. Simultaneous Transmission Conditions

Air-Interface	Band (MHz)	Type	Simultaneous Transmissions Note: Not to be tested	Voice Over Digital Transport (Data)
GSM	850	Voice	Yes WIFI or BT	NA
	1900	Voice		NA
	GPRS/EGPRS	Data	Yes WIFI or BT	NA
WCDMA	Band II	Voice	Yes WIFI or BT	NA
	Band V	Voice	Yes WIFI or BT	NA
	HSDPA/HSUPA/RMC/HSPA+	Data	Yes WIFI or BT	NA
WIFI	2480	Data	Yes GSM,GPRS,EGPRS, HSDPA/HSUPA/RMC/HSPA+	Yes
Bluetooth (BT)	2480	Data	Yes GSM,GPRS,EGPRS, HSDPA/HSUPA/RMC/HSPA+	NA

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 50 of 220

When standalone SAR is not required to be measured per FCC KDB 447498 D01, the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} * \frac{\sqrt{f \text{ (GHz)}}}{7.5}$$

Band	Configuration	Frequency (MHz)	Maximum Power (dBm)	Separation Distance (mm)	Estimated SAR (W/kg)
Bluetooth	Head	2480	3.5	5	0.094
	Body	2480	3.5	10	0.047

Per FCC KDB 447498 D01, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. When the sum is greater than the SAR limit, SAR test exclusion is determined by the SAR to peak location separation ratio.

$$\text{Ratio} = \frac{(\text{SAR}_1 + \text{SAR}_2)^{1.5}}{(\text{peak location separation, mm})} < 0.04$$

Simultaneous transimition SAR For Bluetooth and GSM/UMTS

SAR _{1g} (W/kg) Test Position	GSM 850	GSM 1900	UMTS Band II	UMTS Band V	Bluetooth	MAX. ΣSAR _{1g}	Peak location separation ratio
Left, Touch	0.726	0.478	0.828	0.713	0.094	0.922	No
Left, Tilt	0.439	0.187	0.326	0.424	0.094	0.533	No
Right, Touch	0.622	0.794	1.263	0.623	0.094	1.357	No
Right, Tilt	0.447	0.191	0.326	0.428	0.094	0.541	No
Back Side	1.323	1.187	1.130	0.858	0.047	1.370	No
Front Side	1.008	0.941	0.952	0.661	0.047	1.055	No
Left Edge	0.371	0.163	0.219	0.392	0.047	0.439	No
Right Edge	0.490	0.262	0.354	0.508	0.047	0.555	No
Top Edge	N/A	N/A	N/A	N/A	0.047	0.047	No
Bottom Edge	0.049	0.399	0.457	0.044	0.047	0.504	No

Note: 1. The value with blue color is the maximum ΣSAR_{1g} Value.

2. MAX. ΣSAR_{1g} = Unlicensed SAR_{MAX} + Licensed SAR_{MAX}

MAX. ΣSAR_{1g} = 1.370 W/kg < 1.6 W/kg, So the Simultaneous transimition SAR with volum scan are not required for BT and GSM/UMTS antenna.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 51 of 220

Simultaneous transimition SAR For WIFI and GSM/UMTS

SAR _{1g} (W/kg) Test Position	GSM 850	GSM 1900	UMTS Band II	UMTS Band V	WIFI	MAX. ΣSAR _{1g}	Peak location separation ratio
Left, Touch	0.726	0.478	0.828	0.713	0.501	1.329	No
Left, Tilt	0.439	0.187	0.326	0.424	0.345	0.784	No
Right, Touch	0.622	0.794	1.263	0.623	0.361	1.624	Yes
Right, Tilt	0.447	0.191	0.326	0.428	0.315	0.762	No
Back Side	1.323	1.187	1.130	0.858	0.422	1.745	Yes
Front Side	1.008	0.941	0.952	0.661	0.132	1.140	No
Left Edge	0.371	0.163	0.219	0.392	N/A	0.392	No
Right Edge	0.490	0.262	0.354	0.508	0.256	0.764	No
Top Edge	N/A	N/A	N/A	N/A	0.160	0.160	No
Bottom Edge	0.049	0.399	0.457	0.044	N/A	0.457	No
Note: 1. The value with blue color is the maximum ΣSAR _{1g} Value. 2. MAX. ΣSAR _{1g} = Unlicensed SAR _{MAX} + Licensed SAR _{MAX}							

MAX. ΣSAR_{1g} = 1.745W/kg > 1.6 W/kg, so the Simultaneous transimition SAR test exclusion is determine by the SAR to peak location separation ratio.

Simultaneous Transmission for test position of Back Side

SAR _{1g} (W/kg) Test Position	GSM 850	GSM 1900	UMTS Band II	UMTS Band V	WIFI	MAX. ΣSAR _{1g}	Peak location separation ratio
Right, Touch	0.622				0.361	0.983	No
		0.794			0.361	1.155	No
			1.263		0.361	1.624	Yes
				0.623	0.361	0.984	No
Back Side	1.323				0.422	1.745	Yes
		1.187			0.422	1.609	Yes
			1.130		0.422	1.552	No
				0.858	0.422	1.280	No

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 52 of 220


Pair Simultaneous Transmission for GSM 850 Band and Wifi

Reported SAR _{1g} (W/kg)	GSM 850	WIFI	MAX. Σ SAR _{1g}
Test Position			
Back Side	1.323	0.422	1.745

The position SAR_{GSM 850} is (x₁=-18.5, y₁= -15 z₁=-205.5),

The position SAR_{Max.WIFI} is (x₂=-41, y₂=45, z₂= -204.5)

so the distance between the SAR_{Max.GSM 850} and SAR_{Max.WIFI} is 64.09mm.



Ratio =[(Reported SAR_{Max.GSM/UMTS}) 1.323W/kg +(Reported SAR_{Max.WIFI}) 0.422W/kg]^{3/2} /Peak SAR
 Location Separation =1.745^{3/2} /64.09=0.029 < 0.04

So Simultaneous SAR testing for GSM 850 and Wifi is not required.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 53 of 220


Pair Simultaneous Transmission for GSM 1900 Band and Wifi

Reported SAR _{1g} (W/kg)	GSM 1900	WIFI	MAX. Σ SAR _{1g}
Test Position			
Back Side	1.187	0.422	1.609

The position SAR_{GSM 1900} is (x₁=-30.5, y₁=-39 z₁=-204.1),

The position SAR_{Max.WIFI} is (x₂=-41, y₂=45, z₂= -204.5)

so the distance between the SAR_{Max.GSM 1900} and SAR_{Max.WIFI} is 84.65 mm.



Ratio =[(Reported SAR_{Max.GSM/UMTS}) 1.187W/kg +(Reported SAR_{Max.WIFI}) 0.422W/kg]^{3/2} /Peak SAR

Location Separation =1.609^{3/2} /84.65=0.022 < 0.04

So Simultaneous SAR testing for GSM 1900 and Wifi is not required.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 54 of 220


Pair Simultaneous Transmission for UMTS Band II Band and Wifi

Reported SAR _{1g} (W/kg)	UMTS Band II	WIFI	MAX. Σ SAR _{1g}
Test Position			
Right, Touch	1.263	0.361	1.624

The position SAR_{WCDMA II} is (x₁=72.62, y₁= -254.9 z₁=-169.6),

The position SAR_{Max.WIFI} is (x₂=21.63, y₂=-313.8, z₂= -171.8)

so the distance between the SAR_{Max.GSM 850} and SAR_{Max.WIFI} is 77.94mm.



Ratio =[(Reported SAR_{Max.GSM/UMTS}) 1.263W/kg +(Reported SAR_{Max.WIFI}) 0.361W/kg]^{3/2} /Peak SAR

Location Separation =1.624^{3/2} /77.94=0.027< 0.04

So Simultaneous SAR testing for GSM 850 and Wifi is not required.

8. Measurement Uncertainty

The measured SAR were <1.5 W/kg for all frequency bands, therefore per KDB Publication 865664 D01v01r03, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2003 is not required in SAR reports.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 56 of 220

9. Main Test Instruments

Table : List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	Agilent 8753E	US37390326	September 10, 2013	One year
02	Dielectric Probe Kit	Agilent 85070E	US44020115	No Calibration Requested	
03	Power meter	Agilent E4417A	GB41291714	March 9, 2014	One year
04	Power sensor	Agilent N8481H	MY50350004	September 23, 2013	One year
05	Power sensor	E9327A	US40441622	January 1, 2014	One year
06	Signal Generator	HP 8341B	2730A00804	September 9, 2013	One year
07	Dual directional coupler	778D-012	50519	March 24, 2014	One year
08	Dual directional coupler	777D	50146	March 24, 2014	One year
09	Amplifier	IXA-020	0401	No Calibration Requested	
10	BTS	E5515C	MY48360988	November 30, 2013	One year
11	E-field Probe	EX3DV4	3677	November 28, 2013	One year
12	DAE	DAE4	1317	January 16, 2014	One year
13	Validation Kit 835MHz	D835V2	4d020	August 26, 2011	Three years
14	Validation Kit 1900MHz	D1900V2	5d060	August 31, 2011	Three years
15	Validation Kit 2450MHz	D2450V2	786	August 29, 2011	Three years
16	Temperature Probe	JM222	AA1009129	March 13, 2014	One year
17	Hygrothermograph	WS-1	64591	September 26, 2013	One year

*****END OF REPORT *****

ANNEX A: Test Layout



Picture : Specific Absorption Rate Test Layout


TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 58 of 220



Picture : Liquid depth in the flat Phantom (835MHz, 15.4cm depth)




Picture : Liquid depth in the head Phantom (835MHz, 15.3cm depth)

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 59 of 220



Picture : Liquid depth in the flat Phantom (1900 MHz, 15.2cm depth)




Picture : liquid depth in the head Phantom (1900 MHz, 15.3cm depth)

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RXA1406-0163SAR01R1

Page 60 of 220



Picture : Liquid depth in the flat Phantom (2450 MHz, 15.3cm depth)



Picture : Liquid depth in the head Phantom (2450 MHz, 15.4cm depth)

ANNEX B: System Check Results

System Performance Check at 835 MHz Head TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 2014-07-10

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ mho/m}$; $\epsilon_r = 41.4$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 – SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.64 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 54.4 V/m ; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.44 mW/g ; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.64 mW/g




Figure System Performance Check 835MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 62 of 220

System Performance Check at 835 MHz Body TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 2014-07-09

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 55.1$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 – SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.58 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.9 V/m ; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 3.5 W/kg

SAR(1 g) = 2.41 mW/g ; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.6 mW/g




Figure System Performance Check 835MHz 250Mw

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 63 of 220

System Performance Check at 1900 MHz Head TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 2014-07-13

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 – SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 11.3 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 85.5 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.48 mW/g; SAR(10 g) = 4.9 mW/g

Maximum value of SAR (measured) = 10.7 mW/g




Figure System Performance Check 1900MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 64 of 220

System Performance Check at 1900 MHz Body TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 2014-07-11

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 – SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 12.2 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 82.3 V/m; Power Drift = 0.068 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.93 mW/g; SAR(10 g) = 5.25 mW/g

Maximum value of SAR (measured) = 11.3 mW/g




Figure System Performance Check 1900MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 65 of 220

System Performance Check at 2450 MHz Head TSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 786

Date: 2014-07-14

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.80$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 – SN3677; ConvF(7.64, 7.64, 7.64); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 18.2 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.8 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 30 W/kg

SAR(1 g) = 13.7 mW/g; SAR(10 g) = 6.22 mW/g

Maximum value of SAR (measured) = 15.9 mW/g




Figure System Performance Check 2450MHz 250mW

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 66 of 220

System Performance Check at 2450 MHz Body TSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 786

Date: 2014-07-14

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.99$ mho/m; $\epsilon_r = 52.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 – SN3677; ConvF(7.61, 7.61, 7.61); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 16 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 81.2 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 25.4 W/kg

SAR(1 g) = 12.5 mW/g; SAR(10 g) = 6.20 mW/g

Maximum value of SAR (measured) = 14.4 mW/g




Figure System Performance Check 2450MHz 250mW

ANNEX C: Plots Results

GSM 850 Left Cheek Middle (Battery 1)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.702 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.424 V/m; Power Drift = -0.049 dB

Peak SAR (extrapolated) = 0.805 W/kg

SAR(1 g) = 0.656 W/kg; SAR(10 g) = 0.490 W/kg

Maximum value of SAR (measured) = 0.690 W/kg




Figure Left Hand Touch Cheek GSM 850 Channel 190

GSM 850 Left Tilt Middle (Battery 1)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.408 W/kg

Left Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.547 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.491 W/kg

SAR(1 g) = 0.397 W/kg; SAR(10 g) = 0.305 W/kg

Maximum value of SAR (measured) = 0.418 W/kg




Figure Left Hand Tilt 15° GSM 850 Channel 190

GSM 850 Right Cheek Middle (Battery 1)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.600 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.385 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.778 W/kg

SAR(1 g) = 0.562 W/kg; SAR(10 g) = 0.418 W/kg

Maximum value of SAR (measured) = 0.592 W/kg




Figure Right Hand Touch Cheek GSM 850 Channel 190

GSM 850 Right Tilt Middle (Battery 1)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.418 W/kg

Right Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.879 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.495 W/kg

SAR(1 g) = 0.404 W/kg; SAR(10 g) = 0.310 W/kg

Maximum value of SAR (measured) = 0.423 W/kg




Figure Right Hand Tilt 15° GSM 850 Channel 190

GSM 850 Left Cheek Middle (Battery 2)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.649 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.955 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.752 W/kg

SAR(1 g) = 0.612 W/kg; SAR(10 g) = 0.462 W/kg

Maximum value of SAR (measured) = 0.640 W/kg




Figure Left Hand Touch Cheek GSM 850 Channel 190

GSM 850 Left Cheek Middle (Battery 3)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.663 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.002 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.748 W/kg

SAR(1 g) = 0.618 W/kg; SAR(10 g) = 0.469 W/kg

Maximum value of SAR (measured) = 0.646 W/kg




Figure Left Hand Touch Cheek GSM 850 Channel 190

GSM 850 Left Cheek Middle (Battery 4)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.665 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.947 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.759 W/kg

SAR(1 g) = 0.626 W/kg; SAR(10 g) = 0.472 W/kg

Maximum value of SAR (measured) = 0.656 W/kg




Figure Left Hand Touch Cheek GSM 850 Channel 190

GSM 850 Left Cheek Middle (SIM 2)

Date: 2014-07-10

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.638 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.790 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.755 W/kg

SAR(1 g) = 0.610 W/kg; SAR(10 g) = 0.459 W/kg

Maximum value of SAR (measured) = 0.640 W/kg




Figure Left Hand Touch Cheek GSM 850 Channel 190

GSM 850 Back Side Middle (Battery 1)

Date: 2014-07-09

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 55.073$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.715 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.730 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.874 W/kg

SAR(1 g) = 0.694 W/kg; SAR(10 g) = 0.511 W/kg

Maximum value of SAR (measured) = 0.731 W/kg




Figure Body, Back Side, GSM 850 Channel 190

GSM 850 Front Side Middle (Battery 1)

Date: 2014-07-09

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 55.073$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.539 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.732 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.641 W/kg

SAR(1 g) = 0.505 W/kg; SAR(10 g) = 0.375 W/kg

Maximum value of SAR (measured) = 0.536 W/kg




Figure Body, Front Side, GSM 850 Channel 190

GSM 850 GPRS (4Txslots) Back Side High (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 848.8 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 849$ MHz; $\sigma = 1.007$ S/m; $\epsilon_r = 54.952$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side High/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.853 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.667 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.807 W/kg; SAR(10 g) = 0.599 W/kg

Maximum value of SAR (measured) = 0.848 W/kg




Figure Body, Back Side, GSM 850 GPRS (4Txslots) Channel 251

GSM 850 GPRS (4Txslots) Back Side Middle (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 836.6 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 837$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 55.073$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.964 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.245 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.907 W/kg; SAR(10 g) = 0.673 W/kg

Maximum value of SAR (measured) = 0.955 W/kg




Figure Body, Back Side, GSM 850 GPRS (4Txslots) Channel 190

GSM 850 GPRS (4Txslots) Back Side Low (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 824.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.02 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.945 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.23 W/kg

SAR(1 g) = 0.980 W/kg; SAR(10 g) = 0.725 W/kg

Maximum value of SAR (measured) = 1.03 W/kg




Figure Body, Back Side, GSM 850 GPRS (4Txslots) Channel 128

GSM 850 GPRS (4Txslots)Front Side High (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 848.8 MHz;Duty Cycle: 1:2.07491

Medium parameters used: $f = 849$ MHz; $\sigma = 1.007$ S/m; $\epsilon_r = 54.952$; $\rho = 1000$ kg/m³

Ambient Temperature:22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side High/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.768 W/kg

Front Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.256 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.928 W/kg

SAR(1 g) = 0.716 W/kg; SAR(10 g) = 0.528 W/kg

Maximum value of SAR (measured) = 0.756 W/kg




Figure Body, Front Side, GSM 850 GPRS (4Txslots)Channel 251

GSM 850 GPRS (4Txslots)Front Side Middle (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 836.6 MHz;Duty Cycle: 1:2.07491

Medium parameters used: $f = 837$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 55.073$; $\rho = 1000$ kg/m³

Ambient Temperature:22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.821 W/kg

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.594 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.03 W/kg

SAR(1 g) = 0.784 W/kg; SAR(10 g) = 0.576 W/kg

Maximum value of SAR (measured) = 0.829 W/kg




Figure Body, Front Side, GSM 850 GPRS (4Txslots)Channel 190

GSM 850 GPRS (4Txslots)Front Side Low (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 824.2 MHz;Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature:22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.879 W/kg

Front Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.084 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.823 W/kg; SAR(10 g) = 0.601 W/kg

Maximum value of SAR (measured) = 0.875 W/kg




Figure Body, Front Side, GSM 850 GPRS (4Txslots)Channel 128

GSM 850 GPRS (4Txslots)Left Edge Middle (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 836.6 MHz;Duty Cycle: 1:2.07491

Medium parameters used: $f = 837$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 55.073$; $\rho = 1000$ kg/m³

Ambient Temperature:22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Edge Middle/Area Scan (51x151x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.318 W/kg

Left Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.088 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.391 W/kg

SAR(1 g) = 0.302 W/kg; SAR(10 g) = 0.217 W/kg

Maximum value of SAR (measured) = 0.322 W/kg




Figure Body, Left Edge, GSM 850 GPRS (4Txslots)Channel 190

GSM 850 GPRS (4Txslots)Right Edge Middle (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 836.6 MHz;Duty Cycle: 1:2.07491

Medium parameters used: $f = 837$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 55.073$; $\rho = 1000$ kg/m³

Ambient Temperature:22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Edge Middle/Area Scan (51x151x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.425 W/kg

Right Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.756 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.515 W/kg

SAR(1 g) = 0.399 W/kg; SAR(10 g) = 0.284 W/kg

Maximum value of SAR (measured) = 0.424 W/kg




Figure Body, Right Edge, GSM 850 GPRS (4Txslots)Channel 190

GSM 850 GPRS (4Txslots)Bottom Edge Middle (Battery 1)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 836.6 MHz;Duty Cycle: 1:2.07491

Medium parameters used: $f = 837$ MHz; $\sigma = 0.995$ S/m; $\epsilon_r = 55.073$; $\rho = 1000$ kg/m³

Ambient Temperature:22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Bottom Edge Middle/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.0475 W/kg

Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.344 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.0610 W/kg

SAR(1 g) = 0.040 W/kg; SAR(10 g) = 0.025 W/kg

Maximum value of SAR (measured) = 0.0439 W/kg




Figure Body, Bottom Edge, GSM 850 GPRS (4Txslots)annel 190

GSM 850 GPRS (4Txslots) Back Side Low (Battery 2)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 824.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.13 W/kg


Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.396 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.798 W/kg

Maximum value of SAR (measured) = 1.14 W/kg



GSM 850 GPRS (4Txslots) Back Side Low (Battery 3)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 824.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.12 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.136 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.32 W/kg

SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.786 W/kg

Maximum value of SAR (measured) = 1.12 W/kg




Figure Body, Back Side, GSM 850 GPRS (4Txslots) Channel 128

GSM 850 GPRS (4Txslots) Back Side Low (Battery 4)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 824.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.14 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.435 V/m; Power Drift = -0.054 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 1 W/kg; SAR(10 g) = 0.742 W/kg

Maximum value of SAR (measured) = 1.06 W/kg




Figure Body, Back Side, GSM 850 GPRS (4Txslots) Channel 128

GSM 850 EGPRS (4Txslots) Back Side Low (Battery 1)

Date: 2014-07-09

Communication System: EGPRS(4UP); Frequency: 824.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.04 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.458 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 1 W/kg; SAR(10 g) = 0.743 W/kg

Maximum value of SAR (measured) = 1.06 W/kg




Figure Body, Back Side, GSM 850 EGPRS (4Txslots) Channel 128

GSM 850 GPRS (4Txslots) Back Side Low (SIM 2)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 824.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.15 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.309 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.795 W/kg

Maximum value of SAR (measured) = 1.12 W/kg




Figure Body, Back Side, GSM 850 GPRS (4Txslots) Channel 128

GSM 850 GPRS (4Txslots) Back Side Low (1st repeated SAR)

Date: 2014-07-09

Communication System: GPRS(4UP); Frequency: 824.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 55.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.51, 9.51, 9.51); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.14 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.999 V/m; Power Drift = 0.051 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.794 W/kg

Maximum value of SAR (measured) = 1.13 W/kg




Figure Body, Back Side, GSM 850 GPRS (4Txslots) Channel 128

GSM 1900 Left Cheek Middle (Battery 1)

Date: 2014-07-13

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.404 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.311 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 0.565 W/kg

SAR(1 g) = 0.373 W/kg; SAR(10 g) = 0.226 W/kg

Maximum value of SAR (measured) = 0.400 W/kg




Figure Left Hand Touch Cheek GSM 1900 Channel 661

GSM 1900 Left Tilt Middle (Battery 1)

Date: 2014-07-13

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.159 W/kg

Left Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.692 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.234 W/kg

SAR(1 g) = 0.146 W/kg; SAR(10 g) = 0.087 W/kg

Maximum value of SAR (measured) = 0.162 W/kg




Figure Left Hand Tilt 15° GSM 1900 Channel 661

GSM 1900 Right Cheek Middle (Battery 1)

Date: 2014-07-13

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.589 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.567 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 0.867 W/kg

SAR(1 g) = 0.539 W/kg; SAR(10 g) = 0.315 W/kg

Maximum value of SAR (measured) = 0.590 W/kg




Figure Right Hand Touch Cheek GSM 1900 Channel 661

GSM 1900 Right Tilt Middle (Battery 1)

Date: 2014-07-13

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.176 W/kg

Right Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.001 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.222 W/kg

SAR(1 g) = 0.149 W/kg; SAR(10 g) = 0.092 W/kg

Maximum value of SAR (measured) = 0.161 W/kg




Figure Right Hand Tilt 15° GSM 1900 Channel 661

GSM 1900 Right Cheek Middle (Battery 2)

Date: 2014-07-13

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.595 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.662 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 0.855 W/kg

SAR(1 g) = 0.541 W/kg; SAR(10 g) = 0.317 W/kg

Maximum value of SAR (measured) = 0.593 W/kg




Figure Right Hand Touch Cheek GSM 1900 Channel 661

GSM 1900 Right Cheek Middle (Battery 3)

Date: 2014-07-13

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.595 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.736 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.876 W/kg

SAR(1 g) = 0.548 W/kg; SAR(10 g) = 0.321 W/kg

Maximum value of SAR (measured) = 0.602 W/kg




Figure Right Hand Touch Cheek GSM 1900 Channel 661

GSM 1900 Right Cheek Middle (Battery 4)

Date: 2014-07-13

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.578 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.813 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.827 W/kg

SAR(1 g) = 0.526 W/kg; SAR(10 g) = 0.310 W/kg

Maximum value of SAR (measured) = 0.571 W/kg




Figure Right Hand Touch Cheek GSM 1900 Channel 661

GSM 1900 Right Cheek Middle (SIM 2)

Date/Time: 2014-07-15 13:59:24

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.678 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.184 V/m; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 0.994 W/kg

SAR(1 g) = 0.619 W/kg; SAR(10 g) = 0.359 W/kg

Maximum value of SAR (measured) = 0.678 W/kg




Figure Right Hand Touch Cheek GSM 1900 Channel 661

GSM 1900 Back Side Middle (Battery 1)

Date: 2014-07-11

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.602 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.378 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.878 W/kg

SAR(1 g) = 0.535 W/kg; SAR(10 g) = 0.319 W/kg

Maximum value of SAR (measured) = 0.576 W/kg




Figure Body, Back Side, GSM 1900 Channel 661

GSM 1900 Front Side Middle (Battery 1)

Date: 2014-07-11

Communication System: GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.486 W/kg

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.525 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.710 W/kg

SAR(1 g) = 0.432 W/kg; SAR(10 g) = 0.257 W/kg

Maximum value of SAR (measured) = 0.462 W/kg




Figure Body, Front Side, GSM 1900 Channel 661

GSM 1900 GPRS (4Txslots) Back Side High (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1909.8 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.535$ S/m; $\epsilon_r = 52.981$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side High/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.00 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.376 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.888 W/kg; SAR(10 g) = 0.528 W/kg

Maximum value of SAR (measured) = 0.959 W/kg




Figure Body, Back Side, GSM 1900 GPRS (4Txslots) Channel 810

GSM 1900 GPRS (4Txslots) Back Side Middle (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.08 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.565 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.930 W/kg; SAR(10 g) = 0.552 W/kg

Maximum value of SAR (measured) = 1.01 W/kg




Figure Body, Back Side, GSM 1900 GPRS (4Txslots) Channel 661

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 104 of 220

GSM 1900 GPRS (4Txslots) Back Side Low (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1850.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.476$ S/m; $\epsilon_r = 53.266$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.856 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.781 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.22 W/kg

SAR(1 g) = 0.748 W/kg; SAR(10 g) = 0.448 W/kg

Maximum value of SAR (measured) = 0.807 W/kg




Figure Body, Back Side, GSM 1900 GPRS (4Txslots) Channel 512

GSM 1900 GPRS (4Txslots) Front Side High (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1909.8 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.535$ S/m; $\epsilon_r = 52.981$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side High/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.887 W/kg

Front Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.089 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.783 W/kg; SAR(10 g) = 0.462 W/kg

Maximum value of SAR (measured) = 0.832 W/kg




Figure Body, Front Side, GSM 1900 GPRS (4Txslots) Channel 810

GSM 1900 GPRS (4Txslots) Front Side Middle (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.873 W/kg

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.121 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.761 W/kg; SAR(10 g) = 0.450 W/kg

Maximum value of SAR (measured) = 0.814 W/kg




Figure Body, Front Side, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 GPRS (4Txslots) Front Side Low (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1850.2 MHz; Duty Cycle: 1:2.07491

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.476$ S/m; $\epsilon_r = 53.266$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.745 W/kg

Front Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.185 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.664 W/kg; SAR(10 g) = 0.393 W/kg

Maximum value of SAR (measured) = 0.716 W/kg




Figure Body, Front Side, GSM 1900 GPRS (4Txslots) Channel 512

GSM 1900 GPRS (4Txslots) Left Edge Middle (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Edge Middle/Area Scan (51x151x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.156 W/kg

Left Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.953 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.218 W/kg

SAR(1 g) = 0.134 W/kg; SAR(10 g) = 0.080 W/kg

Maximum value of SAR (measured) = 0.144 W/kg




Figure Body, Left Edge, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 GPRS (4Txslots) Right Edge Middle (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Edge Middle/Area Scan (51x151x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.240 W/kg

Right Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.384 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.346 W/kg

SAR(1 g) = 0.215 W/kg; SAR(10 g) = 0.128 W/kg

Maximum value of SAR (measured) = 0.234 W/kg




Figure Body, Right Edge, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 GPRS (4Txslots) Bottom Edge Middle (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Bottom Edge Middle/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.356 W/kg

Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.349 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.535 W/kg

SAR(1 g) = 0.327 W/kg; SAR(10 g) = 0.193 W/kg

Maximum value of SAR (measured) = 0.358 W/kg




Figure Body, Bottom Edge, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 GPRS (4Txslots) Back Side Middle (Battery 2)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.11 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.300 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.959 W/kg; SAR(10 g) = 0.564 W/kg

Maximum value of SAR (measured) = 1.04 W/kg




Figure Body, Back Side, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 GPRS (4Txslots) Back Side Middle (Battery 3)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.04 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.284 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.51 W/kg

SAR(1 g) = 0.909 W/kg; SAR(10 g) = 0.537 W/kg

Maximum value of SAR (measured) = 0.976 W/kg




Figure Body, Back Side, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 GPRS (4Txslots) Back Side Middle (Battery 4)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.02 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.186 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.892 W/kg; SAR(10 g) = 0.527 W/kg

Maximum value of SAR (measured) = 0.963 W/kg




Figure Body, Back Side, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 EGPRS (4Txslots) Back Side Middle (Battery 1)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.13 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.581 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.974 W/kg; SAR(10 g) = 0.575 W/kg

Maximum value of SAR (measured) = 1.04 W/kg




Figure Body, Back Side, GSM 1900 EGPRS (4Txslots) Channel 661

GSM 1900 GPRS (4Txslots) Back Side Middle (SIM 2)

Date: 2014-07-11

Communication System: GPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.01 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.964 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.51 W/kg

SAR(1 g) = 0.911 W/kg; SAR(10 g) = 0.541 W/kg

Maximum value of SAR (measured) = 0.980 W/kg




Figure Body, Back Side, GSM 1900 GPRS (4Txslots) Channel 661

GSM 1900 EGPRS (4Txslots) Back Side Middle (1st repeated SAR)

Date: 2014-07-11

Communication System: EGPRS(4UP); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.937 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.372 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.874 W/kg; SAR(10 g) = 0.522 W/kg

Maximum value of SAR (measured) = 0.944 W/kg




Figure Body, Back Side, GSM 1900 EGPRS (4Txslots) Channel 661

UMTS Band II Left Cheek High (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.438$ S/m; $\epsilon_r = 39.572$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek High/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.715 W/kg

Left Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.494 V/m; Power Drift = -0.053 dB

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.652 W/kg; SAR(10 g) = 0.395 W/kg

Maximum value of SAR (measured) = 0.704 W/kg




Figure Left Hand Touch Cheek UMTS Band II Channel 9538

UMTS Band II Left Cheek Middle (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.762 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.273 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.718 W/kg; SAR(10 g) = 0.435 W/kg

Maximum value of SAR (measured) = 0.766 W/kg




Figure Left Hand Touch Cheek UMTS Band II Channel 9400

UMTS Band II Left Cheek Low (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.389$ S/m; $\epsilon_r = 39.803$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Low/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.695 W/kg

Left Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.602 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.922 W/kg

SAR(1 g) = 0.625 W/kg; SAR(10 g) = 0.393 W/kg

Maximum value of SAR (measured) = 0.667 W/kg




Figure Left Hand Touch Cheek UMTS Band II Channel 9262

UMTS Band II Left Tilt Middle (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.307 W/kg

Left Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.211 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 0.446 W/kg

SAR(1 g) = 0.283 W/kg; SAR(10 g) = 0.169 W/kg

Maximum value of SAR (measured) = 0.307 W/kg




Figure Left Hand Tilt 15° UMTS Band II Channel 9400

UMTS Band II Right Cheek High (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.438$ S/m; $\epsilon_r = 39.572$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek High/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.17 W/kg

Right Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.523 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 1.70 W/kg

SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.623 W/kg

Maximum value of SAR (measured) = 1.17 W/kg




Figure Right Hand Touch Cheek UMTS Band II Channel 9538

UMTS Band II Right Cheek Middle (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.19 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.463 V/m; Power Drift = 0.050 dB

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.640 W/kg

Maximum value of SAR (measured) = 1.19 W/kg




Figure Right Hand Touch Cheek UMTS Band II Channel 9400

UMTS Band II Right Cheek Low (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.389$ S/m; $\epsilon_r = 39.803$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Low/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.10 W/kg

Right Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.648 V/m; Power Drift = 0.031 dB

Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.596 W/kg

Maximum value of SAR (measured) = 1.10 W/kg




Figure Right Hand Touch Cheek UMTS Band II Channel 9262

UMTS Band II Right Tilt Middle (Battery 1)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.319 W/kg

Right Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.463 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.429 W/kg

SAR(1 g) = 0.283 W/kg; SAR(10 g) = 0.173 W/kg

Maximum value of SAR (measured) = 0.311 W/kg




Figure Right Hand Tilt 15° UMTS Band II Channel 9400

UMTS Band II Right Cheek Middle (Battery 2)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.12 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.530 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 1.64 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.599 W/kg

Maximum value of SAR (measured) = 1.12 W/kg




Figure Right Hand Touch Cheek UMTS Band II Channel 9400

UMTS Band II Right Cheek Middle (Battery 3)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.12 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.420 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.598 W/kg

Maximum value of SAR (measured) = 1.12 W/kg




Figure Right Hand Touch Cheek UMTS Band II Channel 9400

UMTS Band II Right Cheek Middle (Battery 4)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.03 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.187 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.944 W/kg; SAR(10 g) = 0.555 W/kg

Maximum value of SAR (measured) = 1.03 W/kg




Figure Right Hand Touch Cheek UMTS Band II Channel 9400

UMTS Band II Right Cheek Middle (1st repeated SAR)

Date: 2014-07-13

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.413$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.15, 8.15, 8.15); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.01 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.090 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.931 W/kg; SAR(10 g) = 0.549 W/kg

Maximum value of SAR (measured) = 1.00 W/kg




Figure Right Hand Touch Cheek UMTS Band II Channel 9400

UMTS Band II Back Side High (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.532$ S/m; $\epsilon_r = 53.111$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side High/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.08 W/kg

Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.392 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.941 W/kg; SAR(10 g) = 0.562 W/kg

Maximum value of SAR (measured) = 1.02 W/kg




Figure Body, Back Side, UMTS Band II Channel 9538

UMTS Band II Back Side Middle (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.11 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.384 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.61 W/kg

SAR(1 g) = 0.980 W/kg; SAR(10 g) = 0.584 W/kg

Maximum value of SAR (measured) = 1.05 W/kg




Figure Body, Back Side, UMTS Band II Channel 9400

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 131 of 220

UMTS Band II Back Side Low (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.477$ S/m; $\epsilon_r = 53.168$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.06 W/kg

Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.720 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.929 W/kg; SAR(10 g) = 0.556 W/kg

Maximum value of SAR (measured) = 1.00 W/kg




Figure Body, Back Side, UMTS Band II Channel 9262

UMTS Band II Front Side High (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.532$ S/m; $\epsilon_r = 53.111$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side High/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.892 W/kg

Front Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.175 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.793 W/kg; SAR(10 g) = 0.472 W/kg

Maximum value of SAR (measured) = 0.844 W/kg




Figure Body, Front Side, UMTS Band II Channel 9538

UMTS Band II Front Side Middle (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side Middle/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.931 W/kg

Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.510 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.825 W/kg; SAR(10 g) = 0.491 W/kg

Maximum value of SAR (measured) = 0.882 W/kg




Figure Body, Front Side, UMTS Band II Channel 9400

UMTS Band II Front Side Low (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.477$ S/m; $\epsilon_r = 53.168$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Front Side Low/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.870 W/kg

Front Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.036 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.779 W/kg; SAR(10 g) = 0.465 W/kg

Maximum value of SAR (measured) = 0.835 W/kg




Figure Body, Front Side, UMTS Band II Channel 9262

UMTS Band II Left Edge Middle (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Edge Middle/Area Scan (51x151x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.205 W/kg

Left Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.528 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.306 W/kg

SAR(1 g) = 0.190 W/kg; SAR(10 g) = 0.112 W/kg

Maximum value of SAR (measured) = 0.207 W/kg




Figure Body, Left Edge, UMTS Band II Channel 9400

UMTS Band II Right Edge Middle (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Edge Middle/Area Scan (51x151x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.344 W/kg

Right Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.221 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.501 W/kg

SAR(1 g) = 0.307 W/kg; SAR(10 g) = 0.181 W/kg

Maximum value of SAR (measured) = 0.338 W/kg




Figure Body, Right Edge, UMTS Band II Channel 9400

UMTS Band II Bottom Edge Middle (Battery 1)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Bottom Edge Middle/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.429 W/kg

Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.764 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.644 W/kg

SAR(1 g) = 0.396 W/kg; SAR(10 g) = 0.234 W/kg

Maximum value of SAR (measured) = 0.433 W/kg




Figure Body, Bottom Edge, UMTS Band II Channel 9400

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RXA1406-0163SAR01R1

Page 138 of 220

UMTS Band II Back Side Middle (Battery 2)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.10 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.311 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 0.970 W/kg; SAR(10 g) = 0.579 W/kg

Maximum value of SAR (measured) = 1.04 W/kg




Figure Body, Back Side, UMTS Band II Channel 9400

UMTS Band II Back Side Middle (Battery 3)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.08 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.293 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.952 W/kg; SAR(10 g) = 0.569 W/kg

Maximum value of SAR (measured) = 1.02 W/kg




Figure Body, Back Side, UMTS Band II Channel 9400

UMTS Band II Back Side Middle (Battery 4)

Date: 2014-07-11

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ S/m; $\epsilon_r = 53.137$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 2; Type: QD000P40CD; Serial: TP1667

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Back Side Middle/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.08 W/kg

Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.313 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.954 W/kg; SAR(10 g) = 0.570 W/kg

Maximum value of SAR (measured) = 1.02 W/kg




Figure Body, Back Side, UMTS Band II Channel 9400

UMTS Band V Left Cheek Middle (Battery 1)

Date: 2014-07-10

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.645 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.278 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.736 W/kg

SAR(1 g) = 0.599 W/kg; SAR(10 g) = 0.448 W/kg

Maximum value of SAR (measured) = 0.628 W/kg




Figure Left Hand Touch Cheek UMTS Band V Channel 4183

UMTS Band V Left Tilt Middle (Battery 1)

Date: 2014-07-10

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.375 W/kg

Left Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.850 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.442 W/kg

SAR(1 g) = 0.358 W/kg; SAR(10 g) = 0.275 W/kg

Maximum value of SAR (measured) = 0.378 W/kg




Figure Left Hand Tilt 15° UMTS Band V Channel 4183

UMTS Band V Right Cheek Middle (Battery 1)

Date: 2014-07-10

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.573 W/kg

Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.125 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.766 W/kg

SAR(1 g) = 0.527 W/kg; SAR(10 g) = 0.378 W/kg

Maximum value of SAR (measured) = 0.554 W/kg




Figure Right Hand Touch Cheek UMTS Band V Channel 4183

UMTS Band V Right Tilt Middle (Battery 1)

Date: 2014-07-10

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Right Tilt Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.379 W/kg

Right Tilt Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.275 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.447 W/kg

SAR(1 g) = 0.362 W/kg; SAR(10 g) = 0.278 W/kg

Maximum value of SAR (measured) = 0.377 W/kg




Figure Right Hand Tilt 15° UMTS Band V Channel 4183

UMTS Band V Left Cheek Middle (Battery 2)

Date: 2014-07-10

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left/Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.650 W/kg

Left/Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.849 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 0.740 W/kg

SAR(1 g) = 0.603 W/kg; SAR(10 g) = 0.452 W/kg

Maximum value of SAR (measured) = 0.633 W/kg




Figure Left Touch Cheek UMTS Band V Channel 4183

UMTS Band V Left Cheek Middle (Battery 3)

Date: 2014-07-10

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 41.357$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.41, 9.41, 9.41); Calibrated: 2013-11-28;

Electronics: DAE4 Sn1317; Calibrated: 2014-01-16

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

Left Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.611 W/kg

Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.321 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.706 W/kg

SAR(1 g) = 0.577 W/kg; SAR(10 g) = 0.436 W/kg

Maximum value of SAR (measured) = 0.603 W/kg




Figure Left Touch Cheek UMTS Band V Channel 4183