

### 3.6 RF Exposure

**RF Exposure Requirements - §15.247(b)(5):** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

**RF Radiation Exposure Limits:** §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307 (b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1903 of this chapter.

| Frequency Range (MHz)                                     | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (minutes) |
|-----------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational / Control Exposures           |                               |                               |                                     |                        |
| 30 - 300                                                  | 61.4                          | 0.163                         | 1.0                                 | 6                      |
| 300 - 1500                                                | --                            | --                            | F/300                               | 6                      |
| 1500 - 100,000                                            | --                            | --                            | 5                                   | 6                      |
| (B) Limits for General Population / Uncontrolled Exposure |                               |                               |                                     |                        |
| 30 - 300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                     |
| 300 - 1500                                                | --                            | --                            | F/1500                              | 30                     |
| 1500 - 100,000                                            | --                            | --                            | 1.0                                 | 30                     |

**Table 1. Limits for Maximum Permissible Exposure (MPE)**

Note: F = Frequency in MHz

**Test Results:** MPE Limit Calculation: the EUT's operating frequencies @ 5745 – 5805 MHz; max conducted peak power from 802.11 a = 25.32 dBm (628.1 mW) with maximum antenna gain of 10 dBi. Therefore, Limit for Uncontrolled exposure: 1 mW/ cm <sup>2</sup>  
Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where, S = Power Density

P = Power Input to antenna (341.2 mW)

G = Antenna Gain (10 numeric)

R = distance to the center of radiation of antenna (20 centimeters)

$$S = 341.2 \times 10 / (4\pi \times 20 \times 20) = 0.679 \text{ mW/ cm}^2$$

Therefore EUT meets the Uncontrolled Exposure limit

**Test Engineer:** Len Knight

**Test Date:** October 31, 2006