



Product Service

**Choose certainty.
Add value.**

Report On

RF Exposure Assessment of the
Cobham Tactical Communications
INCA Repeater

COMMERCIAL-IN-CONFIDENCE

FCC ID: QKE-90136040

Document 75925939 Report 03 Issue 2

July 2014



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

RF Exposure Assessment of the
Cobham Tactical Communications
INCA Repeater

Document 75925939 Report 03 Issue 2

July 2014

PREPARED FOR

Cobham Tactical Communications
Skindbjergvej
Grenaa
8500
Denmark

PREPARED BY

A handwritten signature in black ink, appearing to read 'Maggie Whiting', written over a horizontal line.

Maggie Whiting
Project Manager

APPROVED BY

A handwritten signature in black ink, appearing to read 'Simon Bennett', written over a horizontal line.

Simon Bennett
Authorised Signatory

DATED

03 July 2014

This report has been up-issued to Issue 2 to include the FCC ID.

**CONTENTS**

Section		Page No
1	REPORT SUMMARY	3
1.1	Introduction	4
1.2	Brief Summary of Results	5
1.3	Product Information	7
1.4	Summary	7
2	TEST DETAILS	8
2.1	Rationale for Assessment of the RF Exposure	9
2.2	Defined Limits	10
2.3	Establishing Wavelength and 1/4 Wavelength	10
2.4	Far Field Calculations	11
3	DISCLAIMERS AND COPYRIGHT	12
3.1	Disclaimers and Copyright.....	13



Product Service

SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
Cobham Tactical Communications
INCA Repeater



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Cobham Tactical Communications INCA Repeater to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	Cobham Tactical Communications
Manufacturer	Cobham Tactical Communications
Manufacturing Description	Repeater
Model Number(s)	INCA
Test Specification/Issue/Date	EN 62311:2008 FCC KDB 447498 D01 RSS-102 Issue 4 March 2010 Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard: 2003
Related Document(s)	Council Recommendation 1999/519/EC:1999 FCC CFR 47 Part 1: 2013 FCC CFR 47 Part 2: 2013 Health Canada's Safety Code 6 ARPANSA ICNIRP 1998 National Council on Radiation Protection and Measurements (NRP) - Report No. 86(1986) EN 50383:2002 IEEE Std C95.1-2005 Australian Standard 2772.2 – 1988



1.2 BRIEF SUMMARY OF RESULTS

1.2.1 General Public Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 0.5 m (50cm)	General Public Exposure Limit	Application
1.000	5000	S	1.59 W/m ²	2 W/m ²	ICNIRP
		S	0.159 mW/cm ²	0.2 mW/cm ²	FCC 47 CFR § 1.1310
		S	1.59 W/m ²	2 W/m ²	Canada's RF Safety Code 6
		S	1.59 W/m ²	2 W/m ²	ARPANSA
		E	24.49 V/m	28 V/m	ICNIRP
		E	24.49 V/m	27.5 V/m	FCC 47 CFR § 1.1310
		E	24.49 V/m	28 V/m	Canada's RF Safety Code 6
		E	24.49 V/m	27.4 V/m	ARPANSA
		H	0.06 A/m	0.073 A/m	ICNIRP
		H	0.06 A/m	0.073 A/m	FCC 47 CFR § 1.1310
		H	0.06 A/m	0.073 A/m	Canada's RF Safety Code 6
		H	0.06 A/m	0.0729 A/m	ARPANSA

The calculations have shown that they **meet** the General Public Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at **50cm**, the point of investigation.



1.2.2 Occupational Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 0.5 m (50cm)	Occupational Exposure Limit	Application
1.000	5000	S	1.59 W/m ²	10 W/m ²	ICNIRP
		S	0.159 mW/cm ²	1 mW/cm ²	FCC 47 CFR § 1.1310
		S	1.59 W/m ²	10 W/m ²	Canada's RF Safety Code 6
		S	1.59 W/m ²	10 W/m ²	ARPANSA
		E	24.49 V/m	61 V/m	ICNIRP
		E	24.49 V/m	61.4 V/m	FCC 47 CFR § 1.1310
		E	24.49 V/m	60 V/m	Canada's RF Safety Code 6
		E	24.49 V/m	61.4 V/m	ARPANSA
		H	0.06 A/m	0.16 A/m	ICNIRP
		H	0.06 A/m	0.163 A/m	FCC 47 CFR § 1.1310
		H	0.06 A/m	0.163 A/m	Canada's RF Safety Code 6
		H	0.06 A/m	0.163 A/m	ARPANSA

The calculations have shown that they **meet** the Occupational Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at **50 cm**, the point of investigation.



Product Service

1.3 PRODUCT INFORMATION

1.3.1 Attestation

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

1.3.2 Technical Description

The Equipment under test was a Cobham Tactical Communications INCA Repeater. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the INCA Repeater to demonstrate compliance with the applied test specification(s). The sample assessed was found to comply with the requirements of the applied rules.

1.4 SUMMARY

The RF exposure assessment is based upon the following criteria:

The INCA Repeater operates in the frequency range of 150 – 174 MHz

Gain	0 dBi
Power	5 W
Distance	0.5 m (50 cm)
Duty Cycle	100%



Product Service

SECTION 2

TEST DETAILS



2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in EN50383:2002 Clause 5.2; E-field or H-field calculation. The method of calculation used is defined in EN50383:2002; Clause 8.2.2, 8.2.3 and 8.2.4.

The calculated values have been compared with limits provided in the ICNIRP guidelines.

Calculations can be made in three separate regions, based on distance from the antenna. These are called:

- far-field region,
- radiating near-field region,
- reactive near-field region.

The theory that defines these regions is given in EN50383:2002 Annex A.

Far-field region

As shown in EN50383 Annex A, the far-field calculations are accurate when the distance, r , from an antenna of length D to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

Where, r is the distance from the antenna to the point of investigation.

Radiating near-field region

The radiating near-field region of an antenna of length D as shown in EN50383 Annex A, this region is defined by

$$\frac{\lambda}{4} < r < \frac{2D^2}{\lambda}$$

Reactive near-field region

The reactive near-field region of an antenna as shown in EN50383 Annex A, this region is defined by

$$r \leq \frac{\lambda}{4}$$

Where, r is the distance from the antenna to the point of investigation.

Recommend $\lambda/4$ as the boundary between the radiated near-field and reactive near-field for RF exposure compliance assessment.



2.2 DEFINED LIMITS

Normative Reference: ICNIRP Advice on Limiting Exposure to Electromagnetic Fields (0-300GHz). Table A4, Reference Levels for General Public Exposure to Time Varying Electric & Magnetic Fields. Vol 15 No.2. 2004. The defined limits are in accordance with 47 CFR § 1.1310 Radiofrequency radiation exposure limits.

Reference levels for general public exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 150 MHz		
Power density (W/m ²)	= 2	ICNIRP
Power density (mW/cm ²)	= 0.2	FCC 47 CFR § 1.1310
Power density (W/m ²)	= 2	Canada's RF Safety Code 6
Power density (W/m ²)	= 2	Australian Radiation Protection Series Publication No. 3
E-Field (Vm-1)	= 28	ICNIRP
E-Field (Vm-1)	= 27.5	FCC 47 CFR § 1.1310
E-Field (Vm-1)	= 28	Canada's RF Safety Code 6
E-Field (Vm-1)	= 27.4	Australian Radiation Protection Series Publication No. 3
H-Field (Am-1)	= 0.073	ICNIRP
H-Field (Am-1)	= 0.073	FCC 47 CFR § 1.1310
H-Field (Am-1)	= 0.073	Canada's RF Safety Code 6
H-Field (Am-1)	= 0.0729	Australian Radiation Protection Series Publication No. 3

Reference levels for occupational exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 150 MHz		
Power density (W/m ²)	= 10	ICNIRP
Power density (mW/cm ²)	= 1	FCC 47 CFR § 1.1310
Power density (W/m ²)	= 10	Canada's RF Safety Code 6
Power density (W/m ²)	= 10	Australian Radiation Protection Series Publication No. 3
E-Field (Vm-1)	= 61	ICNIRP
E-Field (Vm-1)	= 61.4	FCC 47 CFR § 1.1310
E-Field (Vm-1)	= 60	Canada's RF Safety Code 6
E-Field (Vm-1)	= 61.4	Australian Radiation Protection Series Publication No. 3
H-Field (Am-1)	= 0.16	ICNIRP
H-Field (Am-1)	= 0.163	FCC 47 CFR § 1.1310
H-Field (Am-1)	= 0.163	Canada's RF Safety Code 6
H-Field (Am-1)	= 0.163	Australian Radiation Protection Series Publication No. 3

2.3 ESTABLISHING WAVELENGTH AND 1/4 WAVELENGTH

Frequency (MHz)	$\lambda = \frac{3 \times 10^8}{f}$		$\frac{\lambda}{4}$	
	m	cm	m	cm
150	2	200	0.5	50
162	1.85185185185185	185.185185185185	0.462962962962963	46.2962962962963
174	1.72413793103448	172.413793103448	0.431034482758621	43.1034482758621



Product Service

2.4 FAR FIELD CALCULATIONS

The following calculations are based on: 0 dBi gain antenna

$P =$ 5 (Watts) or 5000 (milliwatts)
 $G =$ 1.000 (Numeric Gain)
 $r =$ 50 (centimetres) or 0.5 (meters)

The power flux:

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

$S = 1.59 \text{ W/m}^2$
 $S = 0.159 \text{ mW/cm}^2$

The electric field strength:

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

$E = 24.49 \text{ V/m}$

The magnetic field strength:

$$H = \frac{E}{\eta_0}$$

$H = 0.06 \text{ A/m}$

The calculations meet the General Public Exposure Levels described in the ICNIRP Guidelines.
 The calculations meet the General Public Exposure Levels described in the FCC 47CFR§1.1310.
 The calculations meet the General Public Exposure Levels described in the Canada's RF Safety Code 6.
 The calculations meet the General Public Exposure Levels described in the Australian Radiation Protection Series Publication No. 3

The calculations meet the Occupational Exposure Levels described in the ICNIRP Guidelines.
 The calculations meet the Occupational Exposure Levels described in the FCC 47CFR§1.1310
 The calculations meet the Occupational Exposure Levels described in the Canada's RF Safety Code 6
 The calculations meet the Occupational Exposure Levels described in the Australian Radiation Protection Series Publication No. 3



Product Service

SECTION 3

DISCLAIMERS AND COPYRIGHT



Product Service

3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2014 TÜV SÜD Product Service