



# Test Report - RF Exposure Evaluation Report for SAR Exclusion

## Applicant: Escort Incorporated

Approved for Release By:

Signature: Bruno Clavier

Name & Title: Bruno Clavier, General Manager

Date of Signature 10/18/2022

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

## Table of Contents

---

|                                              |   |
|----------------------------------------------|---|
| CUSTOMER INFORMATION.....                    | 3 |
| LOCATION OF TESTING .....                    | 3 |
| 1.1 TEST LABORATORY .....                    | 3 |
| 1.2 TESTING WAS PERFORMED, REVIEWED BY ..... | 4 |
| TEST SAMPLE(S) (EUT/DUT) .....               | 5 |
| 1.3 DESCRIPTION OF THE EUT.....              | 5 |
| HISTORY OF TEST REPORT CHANGES .....         | 8 |



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

## Customer Information

Applicant: Escort Incorporated  
Address: 5440 West Chester Road  
West Chester, Ohio, 45069, United States

## Location of Testing

### 1.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780  
FCC Designation # US1070  
FCC site registration is under A2LA certificate # 0955.01  
ISED Canada test site registration # 2056A  
EU Notified Body # 1177  
For all designations see A2LA scope # 0955.01



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

## 1.2 Testing was performed, reviewed by

Dates of Testing: 9/6/2022-9/7/2022

Signature:

Sr. EMC Engineer  
EMC-003838-NE



Name & Title:

Tim Royer, EMC Engineer

Date of Signature

10/18/2022

Signature:

Name & Title:

Terri Allen, Lab Assistant

Date of Signature

10/18/2022



## Test Sample(s) (EUT/DUT)

The test sample was received: 7/8/2022

### 1.3 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

| Identification    |                               |
|-------------------|-------------------------------|
| FCC ID:           | QKLM13                        |
| Brief Description | Radar Detector with Bluetooth |
| Model(s) #        | MAX360 MKII                   |
| Firmware version  | N/A                           |
| Software version  | N/A                           |
| Serial Number     | N/A                           |

| Technical Characteristics    |                |
|------------------------------|----------------|
| Technology                   | Radar Detector |
| Frequency Range              | 11.7-12.2 GHz  |
| Duty Cycle                   | 100%           |
| Antenna Connector            | N/A            |
| Voltage Rating (AC or Batt.) | 12VAC          |

| Technical Characteristics    |                 |
|------------------------------|-----------------|
| Technology                   | DTS - Bluetooth |
| Frequency Range              | 2402-2480 MHz   |
| RF Output Power (Max)        | 0.00214 W       |
| Duty Cycle                   | 100%            |
| Antenna Connector            | N/A             |
| Voltage Rating (AC or Batt.) | 12VAC           |



## SAR EXCLUSION CALCULATION:

### Section 4.3.1 General SAR test exclusion guidance

Equation:

**For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:**

**$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR,<sup>30</sup> where**

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>31</sup>
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

### RSS 102 Section 2.5 Exemption Limits for Routine Evaluation

Equation:

- below 20 MHz<sup>6</sup> and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

Conclusion: SAR testing is not required.

## MPE

| Frequency Band  | Separation Distance (mm) | Max Power + Tolerance (dBm) | Max Power + Tolerance (mW) | SAR Exclusion Value | Limit for 1-g SAR | Limit for 10-g SAR (Extremities) | SAR Exclusion |
|-----------------|--------------------------|-----------------------------|----------------------------|---------------------|-------------------|----------------------------------|---------------|
| 2400-2483.5 MHz | 5                        | 4.21                        | 2.64                       | 0.83                | 3.0               | 7.5                              | SAR EXEMPT    |



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

### History of Test Report Changes

| Test Report #                    | Revision # | Description                                | Date of Issue |
|----------------------------------|------------|--------------------------------------------|---------------|
| TR_3148-22_RF Exp SAR Exclusion_ | 1          | Initial release                            | 09/23/2022    |
|                                  | 2          | Updated Page 5                             | 10/10/2022    |
|                                  | 3          | Updated Frequency range of BT<br>on Page 5 | 10/18/2022    |



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

---

END OF TEST REPORT

---