




# Test Report

**CURTIS-STRAUS** Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

|                                  |                                                                                                                              |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Report No                        | EO1265-1                                                                                                                     |
| Client                           | Escort Inc.<br>John Kuhn                                                                                                     |
| Address                          | 5440 West Chester Rd.<br>West Chester, OH 45069                                                                              |
| Phone                            | 513-870-8517                                                                                                                 |
| Items tested<br>FCC ID<br>FRN    | PASSPORTMAX WITH BLUETOOTH<br>QKLM5BT<br>0007508732                                                                          |
| Equipment Type<br>Equipment Code | CRD<br>Radar Detector                                                                                                        |
| FCC Rule Parts                   | 47 CRF 15.109(h)                                                                                                             |
| Test Dates                       | May 28, 2014                                                                                                                 |
| Results                          | As detailed within this report                                                                                               |
| Prepared by                      | <br>Tuyen Truong – EMC Engineer           |
| Authorized by                    | <br>Christopher Reynolds – EMC Supervisor |
| Issue Date                       | 7/16/2014                                                                                                                    |
| Conditions of Issue              | This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 7 of this report. |

Curtis-Straus LLC is accredited to ISO/IEC 17025 by A2LA for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation. See our scope of accreditation at the end of this test report. Any opinions or interpretations expressed in this report are outside the scope of our A2LA accreditation as A2LA only accredits testing.

Testing Cert. No. 1627-01



## Contents

|                                                    |   |
|----------------------------------------------------|---|
| Contents.....                                      | 2 |
| Summary.....                                       | 3 |
| Test Methodology.....                              | 3 |
| Product Tested - Configuration Documentation ..... | 4 |
| <i>Statement of Conformity</i> .....               | 5 |
| Test Results .....                                 | 6 |
| Radiated Emissions .....                           | 6 |
| Conditions Of Testing.....                         | 7 |

Form Final Report REV 7-20-07 (DW)

## Summary

This report is an application for Certification of a radar detector operating pursuant to 47 CFR 15.109(h). This report is designed to demonstrate the compliance with the requirements outlined in Part 15 (using the methods outlined in Part 2) of 47 CFR.

We found that the product met the above requirements without modification. The test sample was received in good condition.

## Test Methodology

Radiated emission testing was performed according to the procedures in ANSI C63.4 (2003). The testing was performed at a distance of 1 meter. The device's performance was investigated in the range 11.7-12.2GHz. The radar detector was powered by a variable power supply. Since the device is a hand-held unit, the emissions were maximized around the three orthogonal axes and the maximum reading was recorded. The integrated antenna cannot be maximized separately.

### Release Control Record

| Issue No. | Reason for change | Date Issued  |
|-----------|-------------------|--------------|
| 1         | Original Release  | July 8, 2014 |

**Product Tested - Configuration Documentation**

| EUT Configuration                                                                                                                                                      |                  |                     |                                         |                   |                 |                 |               |                   |                         |                           |  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|---------------------|-----------------------------------------|-------------------|-----------------|-----------------|---------------|-------------------|-------------------------|---------------------------|--|
| <b>Work Order:</b> O1265<br><b>Company:</b> Escort, Inc.<br><b>Company Address:</b> 5440 West Chester Road<br>West Chester, OH 45069<br><b>Contact:</b> Wanda Densford |                  |                     |                                         |                   |                 |                 |               |                   |                         |                           |  |
| <b>MN</b>                                                                                                                                                              |                  |                     | <b>PN</b>                               |                   |                 | <b>FCC ID</b>   |               |                   | <b>SN</b>               |                           |  |
| <b>EUT:</b>                                                                                                                                                            |                  |                     | PASSPORTMAX WITH BLUETOOTH              |                   |                 | 1620X50-0       |               |                   | QKLM5BT                 |                           |  |
| <b>EUT Description:</b>                                                                                                                                                |                  |                     | Windshield Mounted Radar/Laser Detector |                   |                 |                 |               |                   |                         |                           |  |
| <b>Support Equipment:</b>                                                                                                                                              |                  |                     | <b>MN</b>                               |                   |                 | <b>SN</b>       |               |                   |                         |                           |  |
|                                                                                                                                                                        |                  |                     | none                                    |                   |                 |                 |               |                   |                         |                           |  |
| <b>EUT Ports:</b>                                                                                                                                                      |                  |                     |                                         |                   |                 |                 |               |                   |                         |                           |  |
| <b>Port Label</b>                                                                                                                                                      | <b>Port Type</b> | <b>No. of ports</b> | <b>No. Populated</b>                    | <b>Cable Type</b> | <b>Shielded</b> | <b>Ferrites</b> | <b>Length</b> | <b>Max Length</b> | <b>In/Out NEBS Type</b> | <b>Unpopulated Reason</b> |  |
| DC Power/mute button                                                                                                                                                   | RJ11             | 1                   | All                                     | DC pair           | No              | None            | 7ft           | 7ft               | NA                      | NA                        |  |
| Headphone                                                                                                                                                              | 1/8" jack        | 1                   | 1                                       | 2-wired           | No              | No              | 1m            | >3m               | NA                      | NA                        |  |
| USB                                                                                                                                                                    | USB              | 1                   | 1                                       | USB               | Yes             | No              | 1m            | >3m               | NA                      | NA                        |  |
| <b>Software / Operating Mode Description:</b>                                                                                                                          |                  |                     |                                         |                   |                 |                 |               |                   |                         |                           |  |
| EUT is scanning for radar.                                                                                                                                             |                  |                     |                                         |                   |                 |                 |               |                   |                         |                           |  |

## Statement of Conformity

47 CFR 15.109(h) states that “*Radar detectors shall comply with the emissions limits...of [section 15.109(a)] over the frequency range of 11.7-12.2GHz*”. The applicable limit being 500 $\mu$ V/m measured at a distance of 3m. The radar detector has been tested and found to comply with this requirement

# Test Results

## Radiated Emissions

| Radiated Emissions Table                                |                 |                     |                        |                                      |                                         |                   |                                |                                        |                                          |                      |                    |                                            |             |                    |
|---------------------------------------------------------|-----------------|---------------------|------------------------|--------------------------------------|-----------------------------------------|-------------------|--------------------------------|----------------------------------------|------------------------------------------|----------------------|--------------------|--------------------------------------------|-------------|--------------------|
| Date: 5/28/2014 and 7/1/2014                            |                 |                     |                        | Company: Escort, Inc.                |                                         |                   |                                | Work Order: O1265                      |                                          |                      |                    |                                            |             |                    |
| Engineer: Tuyen Truong                                  |                 |                     |                        | EUT Desc: PASSPORTMAX WITH BLUETOOTH |                                         |                   |                                | EUT Operating Voltage/Frequency: 12Vdc |                                          |                      |                    |                                            |             |                    |
| Temp: 24°C                                              |                 |                     |                        | Humidity: 34%                        |                                         |                   |                                | Pressure: 1013mBar                     |                                          |                      |                    |                                            |             |                    |
| Frequency Range: 11.7-12.2 GHz                          |                 |                     |                        |                                      |                                         |                   |                                |                                        | Measurement Distance: 1 m                |                      |                    |                                            |             |                    |
| Notes:                                                  |                 |                     |                        |                                      |                                         |                   |                                |                                        |                                          |                      |                    |                                            |             |                    |
| Antenna Polarization (H/V)                              | Frequency (MHz) | Peak Reading (dBμV) | Average Reading (dBμV) | Preamp Factor (dB)                   | Antenna Factor (dB/m)                   | Cable Factor (dB) | Adjusted Peak Reading (dBμV/m) | Adjusted Avg Reading (dBμV/m)          | 47 CFR §15.109(h)- High Frequency - Peak |                      |                    | 47 CFR §15.109(h) High Frequency - Average |             |                    |
|                                                         |                 |                     |                        |                                      |                                         |                   |                                |                                        | Limit (dBμV/m)                           | Margin (dB)          | Result (Pass/Fail) | Limit (dBμV/m)                             | Margin (dB) | Result (Pass/Fail) |
| h                                                       | 11828.6         | 31.2                | 21.1                   | 19.8                                 | 39.7                                    | 9.6               | 60.7                           | 50.6                                   | 83.5                                     | -22.8                | Pass               | 63.5                                       | -12.9       | Pass               |
| v                                                       | 11828.75        | 32.27               | 21.5                   | 19.8                                 | 39.7                                    | 9.6               | 61.8                           | 51.0                                   | 83.5                                     | -21.7                | Pass               | 63.5                                       | -12.5       | Pass               |
| v                                                       | 11858.53        | 32.38               | 21.1                   | 19.7                                 | 39.6                                    | 9.6               | 61.9                           | 50.6                                   | 83.5                                     | -21.6                | Pass               | 63.5                                       | -12.9       | Pass               |
| h                                                       | 11859.08        | 31.17               | 21.1                   | 19.7                                 | 39.6                                    | 9.6               | 60.7                           | 50.6                                   | 83.5                                     | -22.8                | Pass               | 63.5                                       | -12.9       | Pass               |
| v                                                       | 12037.5         | 31.44               | 19.6                   | 19.7                                 | 39.2                                    | 9.9               | 60.8                           | 49.0                                   | 83.5                                     | -22.7                | Pass               | 63.5                                       | -14.5       | Pass               |
| v                                                       | 11777.5         | 32.21               | 20.0                   | 19.8                                 | 39.7                                    | 8.5               | 60.6                           | 48.4                                   | 83.5                                     | -22.9                | Pass               | 63.5                                       | -15.1       | Pass               |
| h                                                       | 11861.5         | 28.2                | 18.9                   | 19.7                                 | 39.6                                    | 8.6               | 56.7                           | 47.4                                   | 83.5                                     | -26.8                | Pass               | 63.5                                       | -16.1       | Pass               |
| v                                                       | 12102.5         | 32.14               | 19.9                   | 19.7                                 | 39.1                                    | 8.8               | 60.3                           | 48.1                                   | 83.5                                     | -23.2                | Pass               | 63.5                                       | -15.4       | Pass               |
| Table Result: Pass by -12.5 dB Worst Freq: 11828.75 MHz |                 |                     |                        |                                      |                                         |                   |                                |                                        |                                          |                      |                    |                                            |             |                    |
| Test Site: EMI Chamber 1 and 2                          |                 |                     |                        |                                      | Cables: Asset #1505 + 1507; 1506 + 1786 |                   |                                |                                        |                                          |                      |                    |                                            |             |                    |
| Analyzer: Gold                                          |                 |                     |                        |                                      | Preamp: Asset #1517                     |                   |                                |                                        |                                          | Antenna: Orange Horn |                    |                                            |             |                    |

Rev. 5/27/2014

|                                                      |                 |                 |                  |              |              |            |                        |                      |
|------------------------------------------------------|-----------------|-----------------|------------------|--------------|--------------|------------|------------------------|----------------------|
| <b>Spectrum Analyzers / Receivers / Preselectors</b> | <b>Range</b>    | <b>MN</b>       | <b>Mfr</b>       | <b>SN</b>    | <b>Asset</b> | <b>Cat</b> | <b>Calibration Due</b> | <b>Calibrated on</b> |
| Gold                                                 | 100Hz-26.5 GHz  | E4407B          | Agilent          | MY45113816   | 1284         | I          | 3/28/2015              | 3/28/2014            |
| <b>Radiated Emissions Sites</b>                      | <b>FCC Code</b> | <b>IC Code</b>  | <b>VCCI Code</b> | <b>Range</b> |              | <b>Cat</b> | <b>Calibration Due</b> | <b>Calibrated on</b> |
| EMI Chamber 1                                        | 719150          | 2762A-6         | A-0015           | >1GHz        |              | I          | 5/17/2015              | 5/17/2013            |
| EMI Chamber 2                                        | 719150          | 2762A-7         | A-0015           | >1GHz        |              | I          | 5/16/2015              | 5/16/2013            |
| <b>Preamps / Couplers Attenuators / Filters</b>      | <b>Range</b>    | <b>MN</b>       | <b>Mfr</b>       | <b>SN</b>    | <b>Asset</b> | <b>Cat</b> | <b>Calibration Due</b> | <b>Calibrated on</b> |
| 1517 HF Preamp                                       | 1-20GHz         | CS              | CS               | N/A          | 1517         | II         | 9/11/2014              | 9/11/2013            |
| <b>Antennas</b>                                      | <b>Range</b>    | <b>MN</b>       | <b>Mfr</b>       | <b>SN</b>    | <b>Asset</b> | <b>Cat</b> | <b>Calibration Due</b> | <b>Calibrated on</b> |
| Orange Horn                                          | 1-18GHz         | 3115            | EMCO             | 0004-6123    | 390          | I          | 10/2/2014              | 10/2/2013            |
| <b>Meteorological Meters</b>                         |                 | <b>MN</b>       | <b>Mfr</b>       | <b>SN</b>    | <b>Asset</b> | <b>Cat</b> | <b>Calibration Due</b> | <b>Calibrated on</b> |
| Temp./Humidity/Atm. Pressure Gauge                   |                 | 7400 Perception | Davis            | N/A          | 965          | I          | 5/29/2014              | 5/29/2013            |
| TH A#1832                                            |                 | 35519-044       | Control Company  | 130318277    | 1832         | II         | 6/13/2015              | 6/13/2013            |
| TH A#1833                                            |                 | 35519-044       | Control Company  | 130318278    | 1833         | II         | 6/13/2015              | 6/13/2013            |
| <b>Cables</b>                                        | <b>Range</b>    |                 | <b>Mfr</b>       |              |              | <b>Cat</b> | <b>Calibration Due</b> | <b>Calibrated on</b> |
| Asset #1505                                          | 9kHz - 18GHz    |                 | Florida RF       |              |              | II         | 3/7/2015               | 3/7/2014             |
| Asset #1507                                          | 9kHz - 18GHz    |                 | Florida RF       |              |              | II         | 2/23/2015              | 2/23/2014            |
| Asset #1506                                          | 9kHz - 18GHz    |                 | Florida RF       |              |              | II         | 3/7/2015               | 3/7/2014             |
| Asset #1786                                          | 9kHz - 18GHz    |                 | Florida RF       |              |              | II         | 3/15/2015              | 3/15/2014            |

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

## Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names **"BUREAU VERITAS," "BUREAU VERITAS CONSUMER PRODUCTS SERVICES," "BVCPS," "MTL," "ACTS," "MTL-ACTS" and CURTIS-STRAUS** (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only where such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.
14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

The complete list of the Approved Subcontractors Curtis-Straus may use to delegate the performance of work can be provided upon request.  
Rev.160009121(2)\_#684340 v14CS