

FCC TEST REPORT
For
Shenzhen Meian Technology Co.,Ltd .
Alarm control panel
Model No.: ST-IIIB
Additional model No.: LA-S200

Prepared for : Shenzhen Meian Technology Co.,Ltd .
Address : No.32, Lanshui Rd, Longdong, Longgang District, Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, China

Date of receipt of test sample : May 10, 2014
Number of tested samples : 1
Serial number : Prototype
Date of Test : May 10, 2014– June 18, 2014
Date of Report : June 18, 2014

FCC TEST REPORT

FCC CFR 47 PART 22 SUBPART H AND PART 24 SUBPART E

Report Reference No. : LCS1406100284E

Date of Issue : June 18, 2014

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, ChinaFull application of Harmonised standards ☒Testing Location/ Procedure : Partial application of Harmonised standards ☐Other standard testing method ☐**Applicant's Name..... : Shenzhen Meian Technology Co.,Ltd .**Address : No.32, Lanshui Rd, Longdong, Longgang District, Shenzhen,
China**Test Specification**Standard : FCC CFR 47 PART 2, FCC CFR 47 PART 22 SUBPART H
AND PART 24 SUBPART E**Test Report Form No..... : LCSEMC-1.0**

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. : Alarm control panelTrade Mark : 

Model/ Type reference..... : ST-IIIB

Ratings : AC/DC Adapter:DC 15V, 2A
By battery: DC 11.1VResult : **Positive****Compiled by:**

Jacky Li/ File administrators

Supervised by:

Danny Huang/ Technique principal

Approved by:

Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCS1406100284E	<u>June 18, 2014</u> Date of issue
---	---------------------------------------

Type / Model.....	: ST-IIIIB
EUT.....	: Alarm control panel
Applicant.....	: Shenzhen Meian Technology Co.,Ltd .
Address.....	: No.32, Lanshui Rd, Longdong, Longgang District, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shenzhen Meian Technology Co.,Ltd .
Address.....	: No.32, Lanshui Rd, Longdong, Longgang District, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Shenzhen Meian Technology Co.,Ltd .
Address.....	: No.32, Lanshui Rd, Longdong, Longgang District, Shenzhen, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. DESCRIPTION OF DEVICE (EUT)	5
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	6
1.3. EXTERNAL I/O CABLE	6
1.4. DESCRIPTION OF TEST FACILITY	6
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
1.6. MEASUREMENT UNCERTAINTY	7
1.7. TEST ENVIRONMENT	7
2. TEST METHODOLOGY	8
2.1. EUT CONFIGURATION	8
2.2. OBJECTIVE	8
2.3. GENERAL TEST PROCEDURES	8
2.4. TEST MODE	9
3. SYSTEM TEST CONFIGURATION	10
3.1. JUSTIFICATION	10
3.2. EUT EXERCISE SOFTWARE	10
3.3. SPECIAL ACCESSORIES	10
3.4. BLOCK DIAGRAM/SCHEMATICS	10
3.5. EQUIPMENT MODIFICATIONS	10
3.6. TEST SETUP	10
4. SUMMARY OF TEST RESULTS.....	11
5. TEST RESULT	12
5.1. RF OUTPUT POWER	12
5.2. OCCUPIED BANDWIDTH	15
5.2. OCCUPIED BANDWIDTH	15
5.3. SPURIOUS AND HARMONIC EMISSION AT ANTENNA TERMINAL	19
5.4. RADIATED SPURIOUS EMISSIONS MEASUREMENT	26
5.5. FREQUENCY STABILITY OVER TEMPERATURE AND VOLTAGE VARIATIONS	30
5.6. MODULATION CHARACTERISTIC	33
5.7. PEAK-TO-AVERAGE RATIO	33
6. LIST OF MEASURING EQUIPMENTS.....	34
7. MANUFACTURER/ APPROVAL HOLDER DECLARATION	35

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: Alarm control panel
Test Model	: ST-IIIB
Power Supply	: AC/DC Adapter:DC 15V, 2A By battery: DC 11.1V ☒ GSM 850 (U.S.-Band) ☒ PCS 1900 (U.S.-Band)
Support Band	: ☐ UMTS FDD Band II (U.S.-Band) ☐ UMTS FDD Band V (U.S.-Band)
Uplink	: GSM 850: 824.2MHz ~ 848.8MHz PCS 1900: 1850.2MHz ~ 1909.8MHz
Downlink	: GSM 850: 869.2MHz ~ 893.8MHz PCS 1900: 1930.2MHz ~ 1989.8MHz
Type Of Modulation	: GSM/GPRS:GMSK,
Antenna Description	: Integral Antenna, Antenna Gain: 3.0dBi
Software Version	: ST-3_ii
Hardware Version	: V 1.00

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.3. External I/O Cable

Cable Description	Length(M)	From/Port	To
--	--	--	--

1.4. Description of Test Facility

Site Description EMC Lab.

: Accredited by CNAS, June 04, 2010
The Certificate Registration Number. is L4595.

Accredited by FCC, July 14, 2011
The Certificate Registration Number. is 899208.

Accredited by Industry Canada, May. 02, 2011
The Certificate Registration Number. is 9642A-1

Accredited by VCCI, Japan January 30, 2012
The Certificate Registration Number. is C-4260 and R-3804

Accredited by ESMD, April 24, 2012
The Certificate Registration Number. is ARCB0108.

Accredited by UL, June 11, 2012
The Certificate Registration Number. is 100571-492.

Accredited by TUV, November 21, 2012
The Certificate Registration Number. is SCN1081

Accredited by Intertek, December 21, 2012
The Certificate Registration Number. is 2011-RTL-L1-50.

1.5. Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	$\pm 3.10\text{dB}$	(1)
		30MHz~200MHz	$\pm 2.96\text{dB}$	(1)
		200MHz~1000MHz	$\pm 3.10\text{dB}$	(1)
		1GHz~26.5GHz	$\pm 3.80\text{dB}$	(1)
Conduction Uncertainty	:	150kHz~30MHz	$\pm 1.63\text{dB}$	(1)
Power disturbance	:	30MHz~300MHz	$\pm 1.60\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.7. Test environment

All tests were performed under the following environmental conditions:

Condition	Minimum value	Maximum value
Barometric pressure	86kPa	106kPa
Temperature	15 ℃	30 ℃
Relative Humidity	20 %	75 %
Power supply range	$\pm 5\%$ of rated voltages	

2. TEST METHODOLOGY

All tests and measurements indicated in this document were performed in accordance with FCC CFR 47 part 2, FCC CFR 47 part 22 subpart H and part 24 subpart E.

Applicable Standards: TIA/EIA603-C, ANSI C63.4-2003. The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd..

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. Objective

This type approval report is prepared on behalf of **Shenzhen Meian Technology Co.,Ltd .** in accordance with FCC CFR 47 part 2, FCC CFR 47 part 22 subpart H and part 24 subpart E.

The objective is to determine compliance with FCC rules for RF output power, modulation characteristics, occupied bandwidth, spurious emissions at antenna terminal, field strength of spurious radiation, frequency stability, band edge, and conducted and radiated margin.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4

2.4. Test Mode

GSM / GPRS 850: Channel Low (CH128), Channel Mid (CH190) and Channel High (CH251) were chosen for full testing. The test PCL(Power Control Level)/Class is level 5/class 4.

PCS / GPRS 1900: Channel Low (CH512), Channel Mid (CH661) and Channel High (CH810) were chosen for full testing. The test PCL(Power Control Level)/Class is level 0/class 1.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

For the field strength of spurious emission, the worst emission was found in lie-down position (X axis) for GSM /GPRS 850, lie-down position (X axis) for PCS / GPRS 1900, lie-down position (X axis) and the worst case was recorded.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The EUT had been tested under operating condition. EUT staying in continuous transmitting mode.

3.2. EUT Exercise Software

N/A.

3.3. Special Accessories

N/A.

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: 47 CFR FCC Part 22 Subpart H, Part 24 Subpart E			
FCC Rules	Description of Test		Result
§2.1046, §22.913 / §24.232	RF Output Power	Conducted Output Power	Compliant
		Radiated Output Power	
§2.1049, §22.905 §2.917, §24.238	Occupied Bandwidth		Compliant
§2.1053 §2.917, §24.238	Spurious Radiated Emissions		Compliant
§2.1051 §2.917, §24.238	Spurious Emissions at Antenna Terminals		Compliant
§2.917, §24.238	Band Edge		Compliant
§2.1055 §22.355, §24.235	Frequency Stability		Compliant
§15.107 / §15.207	AC power line conducted emissions		Compliant
§1.1310, §2.1091	RF Exposure Information		Compliant
§2.1047	Modulation Characteristics		Compliant
§24.232(d)	Peak-to-Average Ratio		Compliant

5. TEST RESULT

5.1. RF OUTPUT POWER

5.1.1. Standard Applicable

According to FCC §2.1046 and §22.913, the maximum effective radiated power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to FCC §2.1046 and §22.232, mobile and portable stations are limited to 2 Watts and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

5.1.2. Measuring Instruments

Please refer to section 6 of equipments list in this report.

5.1.3. Test Procedures

Conducted method:



Radiated method:

TIA 603-D section 2.2.17

5.1.4. Test Results

Temperature	25°C	Humidity	60%
ATM Pressure:	101.4kPa	Test Engineer	Jacky

Conducted Power:

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
GSM 850	128	824.2	31.24	38.45
	190	836.6	31.23	38.45
	251	848.8	31.20	38.45
GPRS 850 (Slot 1)	128	824.2	30.35	38.45
	190	836.6	30.32	38.45
	251	848.8	30.31	38.45
GPRS 850 (Slot 2)	128	824.2	28.44	38.45
	190	836.6	28.43	38.45
	251	848.8	28.41	38.45
GPRS 850 (Slot 3)	128	824.2	27.20	38.45
	190	836.6	27.18	38.45
	251	848.8	27.16	38.45
GPRS 850 (Slot 4)	128	824.2	26.58	38.45
	190	836.6	26.57	38.45
	251	848.8	26.55	38.45

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
PCS 1900	512	1850.2	28.62	33
	661	1880.0	28.61	33
	810	1909.8	28.59	33
GPRS 1900 (Slot 1)	512	1850.2	27.39	33
	661	1880.0	27.37	33
	810	1909.8	27.36	33
GPRS 1900 (Slot 2)	512	1850.2	26.44	33
	661	1880.0	26.42	33
	810	1909.8	26.41	33
GPRS 1900 (Slot 3)	512	1850.2	25.39	33
	661	1880.0	25.37	33
	810	1909.8	25.33	33
GPRS 1900 (Slot 4)	512	1850.2	24.28	33
	661	1880.0	24.27	33
	810	1909.8	24.25	33

Radiated Power:

The worst test data as follow:

Mode	Channel	Frequency (MHz)	Test Result		Limit (dBm)
			Max. Peak ERP (dBm)	Polarization	
GSM 850	128	824.2	30.22	H	38.45
	190	836.6	30.18	H	38.45
	251	848.8	30.15	H	38.45

Mode	Channel	Frequency (MHz)	Test Result		Limit (dBm)
			Max. Peak EIRP (dBm)	Polarization	
PCS 1900	512	1850.2	27.69	H	33
	661	1880.0	27.65	H	33
	810	1909.8	27.63	H	33

NOTE: All conditions have been tested and we only record the worst results in each bands.

5.2. OCCUPIED BANDWIDTH

5.2.1. Standard Applicable


FCC §2.1049, §22.917, §22.905 and §24.238.

5.2.2. Measuring Instruments

Please refer to section 6 of equipments list in this report.

5.2.3. Test Procedures

The RF output of the transmitter was connected to the wireless communication tester and spectrum analyzer through attenuation.



The -26dB & 99% bandwidth was recorded.

5.2.4. Test Results

Temperature	25°C	Humidity	60%
ATM Pressure:	101.4kPa	Test Engineer	Jacky




The worst test data as follow:

Mode	Channel	Frequency (MHz)	Emission Bandwidth (-26dBc) (kHz)	Occupied Bandwidth (99%) (kHz)
GSM 850	128	824.2	307.177	249.3688
	190	836.6	316.676	242.6848
	251	848.8	317.287	245.4236




Mode	Channel	Frequency (MHz)	Emission Bandwidth (-26dBc) (kHz)	Occupied Bandwidth (99%) (kHz)
PCS 1900	512	1850.2	317.837	245.3345
	661	1880.0	317.374	244.2431
	810	1909.8	313.237	246.6229

NOTE: All conditions have been tested and we only record the worst results in each bands.

Test Plots For GSM 850



Test Plots For PCS 1900



5.3. SPURIOUS AND HARMONIC EMISSION AT ANTENNA TERMINAL

5.3.1. Standard Applicable


FCC §2.1051, §22.917 and §24.238.

5.3.2. Measuring Instruments

Please refer to section 6 of equipments list in this report.

5.3.3. Test Procedures



The RF output of the transmitter was connected to the wireless communication tester and spectrum analyzer through attenuation.




5.3.4. Test Results


Please refer to the following plots.

Transmitting Mode, CH 128, GSM 850





Transmitting Mode, CH 190, GSM 850








Transmitting Mode, CH 251, GSM 850




Transmitting Mode, CH 512, PCS 1900





Transmitting Mode, CH 661, PCS 1900








Transmitting Mode, CH 810, PCS 1900




Test Result of Band Edge Emissions, GSM 850



Test Result of Band Edge Emissions, PCS 1900





NOTE: All conditions have been tested and the power set in the max level, so we only record the worst results in each band.

5.4. RADIATED SPURIOUS EMISSIONS MEASUREMENT

5.4.1. Standard Applicable

FCC §2.1053, §22.917 and §24.238.

5.4.2. Measuring Instruments

Please refer to section 6 of equipments list in this report.

5.4.3. Test Procedures

The EUT was placed on a non-conductive, the measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.


The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission were identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.


$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$


For radiated spurious emissions below 1GHz



For radiated spurious emissions above 1GHz



Substituted Method



5.4.4. Test Results

The worst test data as follow:

30MHz~10GHz

The Worst Test Result For GSM 850, CH 128				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
93.25	-65.44	-13	Pass	H
285.48	-72.45			
882.34	-73.65			
1782.30	-25.45			
2496.32	-23.74			
93.25	-65.26	-13	Pass	V
285.48	-71.47			
882.34	-73.45			
1782.30	-28.45			
2496.32	-24.35			

The Worst Test Result For GSM 850, CH 190				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
93.25	-64.44	-13	Pass	H
285.48	-70.85	-13		
882.34	-72.69	-13		
1795.31	-26.15	-13		
2524.10	-24.62	-13		
93.25	-64.78	-13	Pass	V
285.48	-70.45	-13		
882.34	-72.38	-13		
1795.31	-25.35	-13		
2524.10	-24.24	-13		

The Worst Test Result For GSM 850, CH 251				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
93.25	-64.62	-13	Pass	H
285.48	-71.85	-13		
882.34	-73.45	-13		
1810.36	-26.08	-13		
2543.20	-24.18	-13		
93.25	-64.86	-13	Pass	V
285.48	-70.26	-13		
882.34	-73.28	-13		
1810.36	-26.47	-13		
2543.20	-24.54	-13		

30MHz~20GHz

The Worst Test Result For PCS 1900, CH 512				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
93.25	-66.62	-13	Pass	H
285.48	-70.25	-13		
882.34	-72.62	-13		
3654.25	-27.16	-13		
5430.17	-32.41	-13		
93.25	-66.17	-13	Pass	V
285.48	-66.26	-13		
882.34	-73.47	-13		
3654.25	-26.28	-13		
5430.17	-32.24	-13		

The Worst Test Result For PCS 1900, CH 661				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
93.25	-66.46	-13	Pass	H
285.48	-70.89	-13		
882.34	-73.84	-13		
3784.04	-28.54	-13		
5685.18	-34.65	-13		
93.25	-66.52	-13	Pass	V
285.48	-67.17	-13		
882.34	-74.37	-13		
3784.04	-26.26	-13		
5685.18	-34.24	-13		

The Worst Test Result For PCS 1900, CH 810				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
93.25	-66.25	-13	Pass	H
285.48	-71.74	-13		
882.34	-72.98	-13		
3815.51	-28.62	-13		
5729.14	-34.15	-13		
93.25	-66.75	-13	Pass	V
285.48	-66.21	-13		
882.34	-73.65	-13		
3815.51	-26.47	-13		
5729.14	-34.45	-13		

NOTE : The result below 30MHz is too low, there is only base environmental noise. We Only record the worst results above 30MHz.

5.5. FREQUENCY STABILITY OVER TEMPERATURE AND VOLTAGE VARIATIONS


5.5.1. Standard Applicable

FCC §2.1055, §22.355 and §24.235, Frequency Tolerance: 2.5ppm

5.5.2. Test Procedures

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency.

Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.



5.5.3. Test Results

Pass

The worst test data as follow:

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
15.0	-20	29	0.034664	2.5	Pass
	-10	22	0.026297		
	0	23	0.027492		
	10	21	0.025102		
	20	24	0.028688		
	30	28	0.033469		
	40	19	0.022711		
	50	28	0.033469		
	60	24	0.028688		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error			Result
		Hz	ppm		
15.0	-20	24	0.012766	2.5	Pass
	-10	26	0.013830		
	0	21	0.011170		
	10	20	0.010638		
	20	28	0.014894		
	30	23	0.012234		
	40	21	0.011170		
	50	27	0.014362		
	60	26	0.013830		

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	12.75	27	0.032273	2.5	Pass
	15.00	24	0.028688		
	17.25	21	0.025102		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error			Result
		Hz	ppm		
25	12.75	24	0.012766	2.5	Pass
	15.00	25	0.013230		
	17.25	28	0.014894		

NOTE: All conditions have been tested and we only record the worst results in each bands.

5.6.MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

5.7. PEAK-TO-AVERAGE RATIO

5.7.1. Standard Applicable

According to FCC §2.1046 and §24.232(d), the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

5.7.2. Measuring Instruments

Please refer to section 6 of equipments list in this report.

5.7.3. Test Procedures

The following steps outline the procedure used to measure the Peak-to-Average Ratio from the EUT.

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
 - b. Set EUT in maximum power output, and triggered the burst signal.
 - c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

5.7.4. Test Results

Modes	PCS 1900		
Channel	512	661	810
	Low	Mid	High
Frequency(MHz)	1850.2	1880	1909.8
Peak-To-Average Ratio (dB)	1.34	1.38	1.31

6. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal Date	Due Date
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	June 18,2014	June 17,2015
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	July 18,2013	July 17,2014
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	June 25,2013	June 24,2014
LISN (Support Unit)	EMCO	3819/2NM	9703-1839	9KHz-30MHz	June 25,2013	June 24,2014
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	June 25,2013	June 24,2014
ISN	SCHAFFNER	ISN ST08	21653	9KHz-30MHz	June 25,2013	June 24,2014
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30M-1GHz 3m	June 18,2014	June 17,2015
Amplifier	SCHAFFNER	COA9231A	18667	9kHz-2GHz	June 16,2014	June 15,2015
Amplifier	Agilent	8449B	3008A02120	1GHz-26.5GHz	July 16,2013	July 15,2014
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz-40GHz	July 16,2013	July 15,2014
Spectrum Analyzer	Agilent	E4407B	MY41440292	9k-26.5GHz	July 16,2013	July 15,2014
Loop Antenna	R&S	HFH2-Z2	860004/001	9k-30MHz	June 16,2014	June 15,2015
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	30MHz-1GHz	June 16,2014	June 15,2015
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	June 16,2014	June 15,2015
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz-40GHz	June 16,2014	June 15,2015
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	June 25,2013	June 24,2014
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz-40GHz	June 25,2013	June 24,2014
Spectrum Meter	R&S	FSP 30	100023	9kHz-30GHz	July 16,2013	July 15,2014
Power Meter	R&S	NRVS	100444	DC-40GHz	June 18,2014	June 17,2015
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	June 18,2014	June 17,2015
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	June 18,2014	June 17,2015
AC Power Source	HPC	HPA-500E	HPA-9100024	AC 0~300V	June 18,2014	June 17,2015
DC power Source	GW	GPC-6030D	C671845	DC 1V-60V	June 18,2014	June 17,2015
Temp. and Humidity	Giant Force	GTH-225-20-S	MAB0103-00	N/A	June 18,2014	June 17,2015
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	June 25,2013	June 24,2014
RF CABLE-2m	JYE Bao	RG142	CB)35-2m	20MHz-1GHz	June 25,2013	June 24,2014
Vector signal Generator	R&S	SMU200A	102098	100kHz~6GHz	June 18,2014	June 17,2015
Signal Generator	R&S	SMR40	10016	10MHz~40GHz	July 16,2013	July 15,2014
Universal Radio Communication	R&S	CMU200	112012	N/A	July 18,2013	July 17,2014
Universal Radio Communication	Agilent	SERIES 10 E5515C	GB44510118	N/A	July 18,2013	July 17,2014

Note: All equipment through GRGT EST calibration

7. MANUFACTURER/ APPROVAL HOLDER DECLARATION

The following identical model(s):

LA-S200	--	--	--
---------	----	----	----

Belong to the tested device:

Product description : Alarm control panel

Model name : ST-IIIB

Remark: PCB board, structure and internal of these model(s) are the same,
So no additional models were tested.

-----THE END OF REPORT-----