

FCC and ISED Test Report

Silicon Laboratories Finland Oy

Main Model: MGM270S22A

In accordance with FCC 47 CFR Part 15C and
ISED RSS-247 and ISED RSS-GEN
Technology: (IEEE 802.15.4)



Prepared for: Silicon Laboratories Finland Oy
Bertel Jungin Aukio 3
Alberga Business Park
02600 Espoo
Finland

TUV SUD
SERVICES
(UK) LIMITED
Digitally signed by
TUV SUD SERVICES
(UK) LIMITED
Date: 2025.09.24
14:37:05 +01'00'

FCC ID: QOQ-GM270S IC: 5123A-GM270S

COMMERCIAL-IN-CONFIDENCE

Document 75965039-05 Issue 01

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Steve Marshall	Senior Engineer	Authorised Signatory	08 September 2025

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Thomas Biddlecombe	08 September 2025	
	Mohiuddin Mohammed	08 September 2025	

FCC Accreditation: 492497/UK2010 Octagon House, Fareham Test Laboratory
ISED Accreditation: 12669A/UK0003 Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY / ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on the test pages. A sample of this product was tested to demonstrate limited compliance with FCC 47 CFR Part 15C: 2023, ISED RSS-247: Issue 3 (2023-08) and ISED RSS-GEN: Issue 5 (2018-04) + A2 (2021-02) for the tests detailed in section 1.3. The sample tested was found to comply with the requirements defined in the applied rules.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2025 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited). Results of tests covered by our Flexible UKAS Accreditation Schedule are marked FS (Flexible Scope).

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire
PO15 5RL
United Kingdom



Contents

1 Report Summary2

1.1 Report Modification Record.....2

1.2 Introduction.....2

1.3 Brief Summary of Results3

1.4 Customer Supplied Form4

1.5 Product Information7

1.6 Deviations from the Standard.....7

1.7 EUT Modification Record7

1.8 Test Location8

2 Test Details9

2.1 Emission Bandwidth9

2.2 Maximum Conducted Output Power 15

2.3 Power Spectral Density 18

2.4 Restricted Band Edges..... 21

2.5 Authorised Band Edges 26

2.6 Spurious Radiated Emissions 30

3 Photographs 71

3.1 Test Setup Photographs 71

4 Measurement Uncertainty 77



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
01	First version	08 September 2025

Table 1

1.2 Introduction

Applicant	Silicon Laboratories Finland Oy
Manufacturer	Silicon Laboratories Finland Oy
Model Number(s)	Main Model: MGM270S22A
Serial Number(s)*	xGM270S_S1; xGM270S_S2; xGM270S_S4; xGM270S_S7 & Xgm270S_S8
Hardware Version(s)	1.0
Software Version(s)	Simplicity SDK Suite v2025.6.0
Number of Samples Tested	5
Test Specification/Issue/Date	FCC 47 CFR Part 15C: 2023 ISED RSS-247: Issue 3 (08-2023) ISED RSS-GEN: Issue 5 (04-2018) + A2 (02-2021)
Order Number	6000558262
Date	24-June-2025
Date of Receipt of EUT	26-June-2025
Start of Test	09-July-2025
Finish of Test	24-July-2025
Name of Engineer(s)	Thomas Biddlecombe and Mohiuddin Mohammed
Related Document(s)	ANSI C63.10 (2020)

*The devices supplied for test did not have serial numbers. The manufacturer supplied a "sample identifier" to allow identification for lab test purposes. This was conveyed as a label on the host carrier board. Across this document, "Serial Number", or the "S/N" notation, indicates such sample identification.



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15C and ISED RSS-247 and ISED RSS-GEN is shown below.

Section	Specification Clause			Test Description	Result	Comments/Base Standard
	Part 15C	RSS-247	RSS-GEN			
Configuration and Mode: IEEE 802.15.4 – Conducted Tests (xGM270S_S4)						
2.1	15.247 (a)(2)	5.2	6.7	Emission Bandwidth	Pass	ANSI C63.10 (2020)
2.2	15.247 (b)	5.4	6.12	Maximum Conducted Output Power	Pass	ANSI C63.10 (2020)
2.3	15.247 (e)	5.2	6.12	Power Spectral Density	Pass	ANSI C63.10 (2020)
Configuration and Mode: IEEE 802.15.4 - External dipole whip Antenna (xGM270S_S1 with ANT-2.4-CW-CT-RPS, xGM270S_S2 with ANT-2.4-CW-CT-RPS)						
2.4	15.203			Antenna Requirement	N/T	The device complies with the provisions of this section, as it uses a non-standard antenna jack.
2.5	15.205	3.3	8.10	Restricted Band Edges	Pass	ANSI C63.10 (2020)
2.6	15.247 (d)	5.5		Authorised Band Edges	Pass	ANSI C63.10 (2020)
2.7	15.247 (d) and 15.209	3.3 & 5.5	6.13 & 8.9	Spurious Radiated Emissions	Pass	ANSI C63.10 (2020)
Configuration and Mode: IEEE 802.15.4 – Module's Integral PCB Trace Antenna (xGM270S_S7, XGM270S_S8)						
2.4	15.203			Antenna Requirement	N/T	The device complies with the provisions of this section, as it uses permanently attached integral antennas.
2.5	15.205	3.3	8.10	Restricted Band Edges	Pass	ANSI C63.10 (2020)
2.6	15.247 (d)	5.5		Authorised Band Edges	Pass	ANSI C63.10 (2020)
2.7	15.247 (d) and 15.209	3.3 & 5.5	6.13 & 8.9	Spurious Radiated Emissions	Pass	ANSI C63.10 (2020)

Table 2

Note: For EIRP calculations based on conducted testing, the antenna gain was taken as 2.80 dBi as per the reference external antenna (ANT-2.4-CW-CT-RPS) as this is the highest gain antenna.



1.4 Customer Supplied Form

Equipment Description

Technical Description: (Please provide a brief description of the intended use of the equipment including the technologies the product supports)	Bluetooth Low Energy (LE) and 802.15.4 wireless radio module		
Legal Manufacturer (Technology Owner):	Silicon Laboratories Finland Oy		
Model Name(s):	Main Model: MGM270S22A (supports both BLE and 802.15.4)		
Brand Name:	SILICON LABS		
Hardware Version:	1.0		
Software Version:	Simplicity SDK Suite v2025.6.0		
FCC ID of the product under test – see guidance here	QOQ-GM270S		
IC ID of the product under test – see guidance here	5123A-GM270S		
Device Category	Mobile ☒	Portable ☒	Fixed ☐
Equipment is fitted with an Audio Low Pass Filter	Yes ☐	No ☒	

Table 3

Intentional Radiators

Technology	Bluetooth LE	IEEE 802.15.4
Frequency Range (MHz to MHz)	Advertising mode: 2402 – 2480 Data mode: 2404 – 2478	2405 - 2480
Conducted Declared Output Power (dBm)	6.3	6.3
Antenna Gain (dBi)	Integral antenna: 1.74 Reference external dipole antenna: 2.80	Integral antenna: 1.74 Reference external dipole antenna: 2.80
Supported Bandwidth(s) (MHz) (e.g. 1 MHz, 20 MHz, 40 MHz)	Nominal Channel Bandwidth for 1MBaud PHYs (1Mbps and Coded 125kbps / 500kbps): 1 Nominal Channel Bandwidth for 2MBaud PHY (2Mbps): 2	Nominal Channel Bandwidth: 3.5
Modulation Scheme(s) (e.g. GFSK, QPSK etc)	GFSK	O-QPSK
ITU Emission Designator (see guidance here) (not mandatory for Part 15 devices)		
Bottom Frequency (MHz)	2402 for Adv mode 2404 for Data mode	2405
Top Frequency (MHz)	2402 for Adv mode 2404 for Data mode	2480

Table 4

Un-intentional Radiators

Highest frequency generated or used in the device or on which the device operates or tunes	
Lowest frequency generated or used in the device or on which the device operates or tunes	
Class A Digital Device (Use in commercial, industrial or business environment) ☐	
Class B Digital Device (Use in residential environment only) ☐	

Table 5

AC Power Source

AC supply frequency:		Hz
Voltage		V
Max current:		A
Single Phase ☐ Three Phase ☐		

Table 6

DC Power Source

Nominal voltage:	3.0	V
Extreme upper voltage:	3.8	V
Extreme lower voltage:	1.8	V
Max current:	0.2	A

Table 7

Battery Power Source

Voltage:		V
End-point voltage:		V (Point at which the battery will terminate)
Alkaline ☐ Leclanche ☐ Lithium ☐ Nickel Cadmium ☐ Lead Acid* ☐ *(Vehicle regulated)		
Other ☐	Please detail:	

Table 8

Charging

Can the EUT transmit whilst being charged	Yes ☐ No ☐
---	--

Table 9

Temperature

Minimum temperature:	-40	°C
Maximum temperature:	+105	°C

Table 10

Cable Loss

Adapter Cable Loss (Conducted sample)	Semi-rigid coax cable with SMA connector: 0.2 Optional SMA adapter: add 0.1 when used	dB
--	--	----

Table 11

Antenna Characteristics

Antenna connector (module's RF pin) ☒			State impedance	50	Ohm
Temporary antenna connector ☐			State impedance		Ohm
Integral antenna ☒	Type:	PCB trace	Gain	1.74	dBi
External antenna ☒	Type:	Reference Dipole	Gain	2.80	dBi
For external antenna only: Standard Antenna Jack ☐ If yes, describe how user is prohibited from changing antenna (if not professional installed): Equipment is only ever professionally installed ☒ Non-standard Antenna Jack (module's RF pin) ☒ All part 15 applications will need to show how the antenna gain was derived either from a manufacturer data sheet or a measurement. Where the gain of the antenna is inherently accounted for as a result of the measurement, such as field strength measurements on a part 15.249 or 15.231 device, so the gain does not necessarily need to be verified. However, enough information regarding the construction of the antenna shall be provided. Such information maybe photographs, length of wire antenna etc.					

Table 12

Data in the tables above is provided by the Manufacturer.



1.5 Product Information

1.5.1 Technical Description

Bluetooth Low Energy (LE) and 802.15.4 wireless radio module

1.6 Deviations from the Standard

No deviations from the applicable test standard were made during testing.

1.7 EUT Modification Record

The table below details modifications made to the EUT during the test programme.

The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Model: MGM270S22A, Serial Number: xGM270S_S1,			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: MGM270S22A, Serial Number: xGM270S_S2,			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: MGM270S22A, Serial Number: xGM270S_S4,			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: MGM270S22A, Serial Number: xGM270S_S7,			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: MGM270S22A, Serial Number: xGM270S_S8,			
0	As supplied by the customer	Not Applicable	Not Applicable

Table 13



1.8 Test Location

TÜV SÜD conducted the following tests at our Octagon House Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Configuration and Mode: IEEE 802.15.4		
Emission Bandwidth	Thomas Biddlecombe	UKAS
Maximum Conducted Output Power	Thomas Biddlecombe	UKAS
Power Spectral Density	Thomas Biddlecombe	UKAS
Configuration and Mode: IEEE 802.15.4 - External dipole whip Antenna		
Restricted Band Edges	Mohiuddin Mohammed	UKAS
Authorised Band Edges	Mohiuddin Mohammed	UKAS
Spurious Radiated Emissions	Mohiuddin Mohammed	UKAS
Configuration and Mode: IEEE 802.15.4 – Module's Integral PCB Trace Antenna		
Restricted Band Edges	Mohiuddin Mohammed	UKAS
Authorised Band Edges	Mohiuddin Mohammed	UKAS
Spurious Radiated Emissions	Mohiuddin Mohammed	UKAS

Table 14

Laboratory Address: TÜV SÜD, Octagon House,
Concorde Way, Fareham, Hampshire,
PO15 5RL, United Kingdom

2 Test Details

2.1 Emission Bandwidth

2.1.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (a)(2),
ISED RSS-247, Clause 5.2
ISED RSS-GEN, Clause 6.7

2.1.2 Equipment Under Test and Modification State

Model: MGM270S22A, S/N: xGM270S_S4, - Modification State 0

2.1.3 Date of Test

09-July-2025

2.1.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 6.9.2 for 6 dB BW and 6.9.3 for 99% occupied bandwidth measurements

The EUT was supplied with 3.0 VDC directly with a DC Power Supply Unit (PSU).

2.1.5 Environmental Conditions

Ambient Temperature	22.6 °C
Relative Humidity	48.4 %

2.1.6 Test Results

IEEE 802.15.4

Test Configuration			
Service Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (a)(2) RSS-247 5.2 (a)	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	IEEE 802.15.4 O-QPSK	Duty Cycle (%):	100.0
Antenna Configuration:	SISO	DCCF (dB):	-
Power Configuration:	63 deci-dBm	Peak Antenna Gain (dBi):	-
Supply Voltage:	3.00 VDC	Tx Mode:	Continuous Modulated Stream (PN9)

Test Frequency (MHz)	6 dB Bandwidth (MHz)				Limit (kHz)
	A	B	C	D	
2405	1.656	-	-	-	≥500.0
2445	1.656	-	-	-	≥500.0
2480	1.656	-	-	-	≥500.0

Table 15 - 6 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (kHz)
	A	B	C	D	
2405	2.256	-	-	-	-
2445	2.256	-	-	-	-
2480	2.256	-	-	-	-

Table 16 - 99% Bandwidth Results




Figure 1 - 2405 MHz 99% Bandwidth




Figure 2 - 2405 MHz 6 dB Bandwidth




Figure 3 - 2445 MHz 99% Bandwidth




Figure 4 - 2445 MHz 6 dB Bandwidth




Figure 5 - 2480 MHz 99% Bandwidth




Figure 6 - 2480 MHz 6 dB Bandwidth

FCC 47 CFR Part 15, Limit Clause 15.247(a)(2) and ISED RSS-247, Clause 5.2(a)

The minimum 6 dB Bandwidth shall be at least 500 kHz.

2.1.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 1.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Hygrometer	Rotronic	I-1000	2891	12	02-Dec-2025
GPSDR Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	18-Sep-2025
Digital Multi-meter	Iso-tech	IDM93N	4435	12	06-Mar-2026
MXA Signal Analyser	Keysight Technologies	N9020B	5528	24	18-Sep-2025
Modular Power System Mainframe	Keysight Technologies	N6701C	5835	-	TU
DC Power Module 60V 20A 300W	Keysight Technologies	N6754A	5836	-	O/P Mon
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6350	12	02-Aug-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6638	12	02-Aug-2025

Table 17

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment



2.2 Maximum Conducted Output Power

2.2.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (b),
ISED RSS-247, Clause 5.4
ISED RSS-GEN, Clause 6.12

2.2.2 Equipment Under Test and Modification State

Model: MGM270S22A, S/N: xGM270S_S4, - Modification State 0

2.2.3 Date of Test

09-July-2025

2.2.4 Test Method

The test was performed in accordance with ANSI C63.10 clause 11.9.1.2 Method PKPM1.

The EUT was supplied with 3.0 VDC directly with a DC PSU.

2.2.5 Environmental Conditions

Ambient Temperature	22.6 °C
Relative Humidity	48.4 %

2.2.6 Test Results

IEEE 802.15.4

Test Configuration			
Service Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.1.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	IEEE 802.15.4 O-QPSK	Duty Cycle (%):	100.0
Antenna Configuration:	SISO	DCCF (dB):	-
Active Port(s):	Module's RF Pin for Conducted Measurements via a semi-rigid coax cable + SMA Connector	Peak Antenna Gain (dBi):	2.80
Supply Voltage:	3.00 VDC	Tx Mode:	Continuous Modulated Stream (PN9)

Test Frequency (MHz)	Power Configuration (decibel-milliwatts)	Maximum Conducted Output Power (dBm)	Limit (dBm)	Margin (dB)
2405	63	6.62	30.00	-23.38
2445	63	6.71	30.00	-23.29
2480	63	6.77	30.00	-23.23

Table 18 - FCC Maximum Conducted (peak) Output Power Results

Test Frequency (MHz)	Power Configuration (decibel-milliwatts)	Maximum Conducted Output Power (dBm)	Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
2405	63	6.62	30.00	-23.38	9.42	36.00	-26.58
2445	63	6.71	30.00	-23.29	9.51	36.00	-26.49
2480	63	6.77	30.00	-23.23	9.57	36.00	-26.43

Table 19 - ISSED Maximum Conducted (peak) Output Power Results

FCC 47 CFR Part 15, Limit Clause 15.247 (b)(3)

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

ISSED RSS-247, Limit Clause 5.4 (d)

For DTSS employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e) of the specification.



2.2.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 1.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Hygrometer	Rotronic	I-1000	2891	12	02-Dec-2025
Digital Multi-meter	Iso-tech	IDM93N	4435	12	06-Mar-2026
USB Power Sensor	Boonton	RTP5008	5833	12	26-Jul-2025
Modular Power System Mainframe	Keysight Technologies	N6701C	5835	-	TU
DC Power Module 60V 20A 300W	Keysight Technologies	N6754A	5836	-	O/P Mon
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6350	12	02-Aug-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6638	12	02-Aug-2025

Table 20

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment



2.3 Power Spectral Density

2.3.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (e),
ISED RSS-247, Clause 5.2
ISED RSS-GEN, Clause 6.12

2.3.2 Equipment Under Test and Modification State

Model: MGM270S22A, S/N: xGM270S_S4, - Modification State 0

2.3.3 Date of Test

09-July-2025

2.3.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 11.10.2.

The EUT was supplied with 3.0 VDC directly with a DC PSU.

2.3.5 Environmental Conditions

Ambient Temperature	22.6 °C
Relative Humidity	48.4 %



2.3.6 Test Results

IEEE 802.15.4

Test Configuration			
Service Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	IEEE 802.15.4 O-QPSK	Duty Cycle (%):	100.0
Antenna Configuration:	SISO	DCCF (dB):	-
Active Port(s):	Module's RF Pin for Conducted Measurements via a semi-rigid coax cable + SMA Connector	Peak Antenna Gain (dBi):	2.80
Supply Voltage:	3.00 VDC	Tx Mode:	Continuous Modulated Stream (PN9)

Test Frequency (MHz)	Power Configuration (dec-dBm)	RBW (kHz)	PSD (dBm/RBW)	Limit (dBm/3 kHz)	Margin (dB)
2405	63	100.0	2.84	8.00	-5.16
2445	63	100.0	2.86	8.00	-5.14
2480	63	100.0	3.03	8.00	-4.97

Table 21 - Maximum Power Spectral Density Results

FCC 47 CFR Part 15, Limit Clause 15.247 (e)

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

ISED RSS-247, Limit Clause 5.2(b)

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission



2.3.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 1.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Hygrometer	Rotronic	I-1000	2891	12	02-Dec-2025
GPSDR Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	18-Sep-2025
Digital Multi-meter	Iso-tech	IDM93N	4435	12	06-Mar-2026
MXA Signal Analyser	Keysight Technologies	N9020B	5528	24	18-Sep-2025
Modular Power System Mainframe	Keysight Technologies	N6701C	5835	-	TU
DC Power Module 60V 20A 300W	Keysight Technologies	N6754A	5836	-	O/P Mon
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6350	12	02-Aug-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6638	12	02-Aug-2025

Table 22

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment

2.4 Restricted Band Edges

2.4.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.205
ISED RSS-247, Clause 3.3
ISED RSS-GEN, Clause 8.10

2.4.2 Equipment Under Test and Modification State

Model: MGM270S22A, S/N: xGM270S_S2 - Modification State 0
Model: MGM270S22A, S/N: xGM270S_S8 - Modification State 0

2.4.3 Date of Test

10-July-2025 to 13-July-2025

2.4.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 6.10.5 and 11.12.1.

Plots for average measurements were taken in accordance with ANSI C63.10, clause 11.12.2.5.2.

The following conversion can be applied to convert from dB μ V/m to μ V/m:
 $10^{(\text{Field Strength in dB}\mu\text{V/m}/20)}$.

The EUT was set to transmit a continuous modulated stream of PN9 data, at a configured power level of 63 deci-dBm.

The EUT was supplied with 3 VDC directly with a DC PSU.

2.4.5 Environmental Conditions

Ambient Temperature	19.7 - 23.0 °C
Relative Humidity	50.3 - 65.7 %

2.4.6 Test Results

IEEE 802.15.4 - External dipole whip Antenna (xGM270S_S2 with ANT-2.4-CW-CT-RPS)

Mode	Data Rate/MCS	Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dB μ V/m)	Average Level (dB μ V/m)
802.15.4	Continuous Modulated PN9 Stream	2405	2390	55.10	43.14
802.15.4	Continuous Modulated PN9 Stream	2480	2483.5	63.88	53.53

Table 29




Figure 7 - Bottom_1MHz_RBE, 2405 MHz, Band Edge Frequency 2390 MHz




Figure 8 - TOP_1MHz_RBE, 2480 MHz, Band Edge Frequency 2483.5 MHz

IEEE 802.15.4 - PCB Trace Antenna (XGM270S S8)

Mode	Data Rate/MCS	Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dB μ V/m)	Average Level (dB μ V/m)
802.15.4	Continuous Modulated PN9 Stream	2405	2390	54.24	42.65
802.15.4	Continuous Modulated PN9 Stream	2480	2483.5	63.49	52.74

Table 29




Figure 9 - Bottom_1MHz_RBE, 2405 MHz, Band Edge Frequency 2390 MHz




Figure 10 - TOP_1MHz_RBE, 2480 MHz, Band Edge Frequency 2483.5 MHz

FCC 47 CFR Part 15, Limit Clause 15.209

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at 3 m)
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

Table 23

ISED RSS-GEN, Limit Clause 8.9

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at 3 m)
30 to 88	100
88 to 216	150
216 to 960	200
Above 960*	500

Table 24

*Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

2.4.7 Test Location and Test Equipment Used

This test was carried out in RF Chamber 11 and EMC Chamber 12.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Dual Power Supply Unit	Hewlett Packard	6253A	271	-	O/P Mon
True RMS Multimeter	Fluke	79 Series III	411	12	09-Jan-2026
Power Supply Unit	Farnell	H60-25	1092		O/P Mon
Multimeter	Iso-tech	IDM101	2421	12	07-Nov-2025
Emissions Software	TUV SUD	EmX V3.5.3	5125	-	Software
3m Semi-Anechoic Chamber	Rainford	RF Chamber 11	5136	36	14-Nov-2027
Mast	Maturo	TAM 4.0-P	5158	-	TU
Mast and Turntable Controller	Maturo	Maturo NCD	5159	-	TU
Turntable	Maturo	TT 15WF	5160	-	TU
Antenna (DRG, 1 GHz to 10.5 GHz)	Schwarzbeck	BBHA9120B	5215	12	05-Jul-2026
Pre-Amplifier (1 GHz to 18 GHz)	Schwarzbeck	BBV 9718 C	5350	12	16-Dec-2025
Cable (SMA to SMA, 2 m)	Junkosha	MWX221-02000AMSAMS/A	5517	12	06-Jun-2026
Turntable & Mast Controller	Maturo Gmbh	NCD/498/2799.01	5612	-	TU
Tilt Antenna Mast	Maturo Gmbh	TAM 4.0-P	5613	-	TU
Turntable	Maturo Gmbh	TT1.5SI-2t/894/27991119	5614	-	TU
3m Semi-Anechoic Chamber	MVG	EMC Chamber 12	5621	36	07-Aug-2026
Test Receiver	Rohde & Schwarz	ESW44	5802	12	25-Oct-2025
Cable (2.92 mm(f) to N-Type(m), 2 m)	Junkosha	MWX241-02000KFSNMS/B	6332	12	27-Sep-2025
Humidity & Temperature meter	R.S Components	1364	6347	12	13-Mar-2026
Cable Assy 8m (N to N) 18GHz	Junkosha	MWX221-08000NMSNMS/B	7049	12	01-Jun-2026
Cable (N-Type to N-Type, 8 m)	Junkosha	MWX221-08000NMSNMS/B	7054	12	01-Jun-2026

Table 25

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment



2.5 Authorised Band Edges

2.5.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (d)
ISED RSS-247, Clause 5.5

2.5.2 Equipment Under Test and Modification State

Model: MGM270S22A, S/N: xGM270S_S2 - Modification State 0
Model: MGM270S22A, S/N: xGM270S_S8 - Modification State 0

2.5.3 Date of Test

10-July-2025 to 13-July-2025

2.5.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.10.4.

The EUT was set to transmit a continuous modulated stream of PN9 data, at a configured power level of 63 deci-dBm.

The EUT was supplied with 3 VDC directly with a DC PSU.

2.5.5 Environmental Conditions

Ambient Temperature	19.8 - 21.3 °C
Relative Humidity	49.3 - 60.0 %

2.5.6 Test Results

IEEE 802.15.4 - External dipole whip Antenna (xGM270S_S2 with ANT-2.4-CW-CT-RPS)

Mode	Data Rate/MCS	Frequency (MHz)	Band Edge Frequency (MHz)	Level (dBc)
802.15.4	O-QPSK	2405	2400	-53.20

Table 29




Figure 11 - Bottom_1MHz_ABE, 2405 MHz, Band Edge Frequency 2400 MHz

IEEE 802.15.4 - PCB Trace Antenna (XGM270S S8)

Mode	Data Rate/MCS	Frequency (MHz)	Band Edge Frequency (MHz)	Level (dBc)
802.15.4	O-QPSK	2405	2400	-50.78

Table 29




Figure 12 – Bottom_1MHz_ABE, 2405 MHz, Band Edge Frequency 2400 MHz

FCC 47 CFR Part 15, Limit Clause 15.247 (d)

20 dB below the fundamental measured in a 100 kHz bandwidth using a peak detector. If the transmitter complies with the conducted power limits, based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB below the fundamental instead of 20 dB.

ISED RSS-247, Limit Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

2.5.7 Test Location and Test Equipment Used

This test was carried out in RF Chamber 11 and EMC Chamber 12.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Dual Power Supply Unit	Hewlett Packard	6253A	271	-	O/P Mon
True RMS Multimeter	Fluke	79 Series III	411	12	09-Jan-2026
Power Supply Unit	Farnell	H60-25	1092		O/P Mon
Multimeter	Iso-tech	IDM101	2421	12	07-Nov-2025
Emissions Software	TUV SUD	EmX V3.5.3	5125	-	Software
3m Semi-Anechoic Chamber	Rainford	RF Chamber 11	5136	36	14-Nov-2027
Mast	Maturo	TAM 4.0-P	5158	-	TU
Mast and Turntable Controller	Maturo	Maturo NCD	5159	-	TU
Turntable	Maturo	TT 15WF	5160	-	TU
Antenna (DRG, 1 GHz to 10.5 GHz)	Schwarzbeck	BBHA9120B	5215	12	05-Jul-2026
Pre-Amplifier (1 GHz to 18 GHz)	Schwarzbeck	BBV 9718 C	5350	12	16-Dec-2025
Cable (SMA to SMA, 2 m)	Junkosha	MWX221-02000AMSAMS/A	5517	12	06-Jun-2026
Turntable & Mast Controller	Maturo Gmbh	NCD/498/2799.01	5612	-	TU
Tilt Antenna Mast	Maturo Gmbh	TAM 4.0-P	5613	-	TU
Turntable	Maturo Gmbh	TT1.5SI-2t/894/27991119	5614	-	TU
3m Semi-Anechoic Chamber	MVG	EMC Chamber 12	5621	36	07-Aug-2026
Test Receiver	Rohde & Schwarz	ESW44	5802	12	25-Oct-2025
Cable (2.92 mm(f) to N-Type(m), 2 m)	Junkosha	MWX241-02000KFSNMS/B	6332	12	27-Sep-2025
Cable Assy 8m (N to N) 18GHz	Junkosha	MWX221-08000NMSNMS/B	7049	12	01-Jun-2026
Cable (N-Type to N-Type, 8 m)	Junkosha	MWX221-08000NMSNMS/B	7054	12	01-Jun-2026

Table 26

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment

2.6 Spurious Radiated Emissions

2.6.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.209 and 15.247 (d)
ISED RSS-247, Clause 3.3 and 5.5
ISED RSS-GEN, Clause 6.13 and 8.9

2.6.2 Equipment Under Test and Modification State

Model: MGM270S22A, S/N: xGM270S_S1 - Modification State 0
Model: MGM270S22A, S/N: xGM270S_S7 - Modification State 0

2.6.3 Date of Test

18-July-2025 to 24-July-2025

2.6.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 6.3, 6.5 and 6.6.

For frequencies > 1 GHz, plots for average measurements were taken in accordance with ANSI C63.10, clause 11.12.2.5.2.

The EUT was placed on the non-conducting platform in a manner typical of a normal installation. As the EUT was considered mobile/portable and therefore reasonable to be used in multiple planes, pre-scans were performed with the EUT orientated in X, Y and Z planes with reference to the ground plane.

The plots shown are the characterization of the EUT. The limits on the plots represent the most stringent case for restricted bands, (74/54 dBuV/m) when compared to 20 dBc outside restricted bands. The limits shown have been used as a threshold to determine where further measurements are necessary. Where results are within 10 dB of the limits shown on the plots, further investigation was carried out and reported in results tables.

The following conversion can be applied to convert from dBuV/m to $\mu\text{V/m}$:
 $10^{(\text{Field Strength in dBuV/m}/20)}$

Above 18 GHz, the measurement distance was reduced to 1 m. The limit line was increased by $20 \cdot \text{LOG}(3/1) = 9.54 \text{ dB}$.

At a measurement distance of 1 meter the limit line was increased by $20 \cdot \text{LOG}(3/1) = 9.54 \text{ dB}$.

Where formal measurements have been necessary, the results have been presented in the emissions table.

The EUT was set to transmit a continuous modulated stream of PN9 data, at a configured power level of 63 deci-dBm.

The EUT was supplied with 3 VDC directly with a DC PSU.

2.6.5 Example Test Setup Diagram




Figure 13

2.6.6 Environmental Conditions

Ambient Temperature	19.5 - 22.1 °C
Relative Humidity	56.5 - 72.0 %

2.6.7 Test Results

IEEE 802.15.4 - External dipole whip Antenna (xGM270S_S1 with ANT-2.4-CW-CT-RPS)

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12022.300	48.42	54.00	-5.58	RMS	157	203	Horizontal
16831.032	49.36	54.00	-4.64	RMS	277	296	Vertical

Table 27 - Bottom_802.15.4 - 2405 MHz, 30 MHz to 26 GHz X Orientation

No other emissions found within 10 dB of the limit.




Figure 14 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Horizontal (Peak) X- Orientation




Figure 15 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Horizontal (Peak) X- Orientation




Figure 16 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Vertical (Peak) X- Orientation




Figure 17 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Vertical (Peak) X- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 28 - Middle_802.15.4_ 2445 MHz, 30 MHz to 26 GHz X Orientation

*No emissions found within 10 dB of the limit.




Figure 18 - Middle_802.15.4_ 2445 MHz, 30 MHz to 1 GHz, Horizontal (Peak) X-Orientation




Figure 19 - Middle_802.15.4_ 2445 MHz, 1 GHz to 26 GHz, Horizontal (Peak) X-Orientation




Figure 20 - Middle_802.15.4_2445 MHz, 30 MHz to 1 GHz, Vertical (Peak) X-Orientation




Figure 21 - Middle_802.15.4_2445 MHz, 1 GHz to 26 GHz, Vertical (Peak) X-Orientation

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12397.206	44.06	54.00	-9.94	RMS	190	219	Horizontal
12402.695	46.34	54.00	-7.66	RMS	99	203	Vertical
17356.058	47.65	54.00	-6.35	RMS	281	296	Vertical

Table 29 - Top_802.15.4 -2480 MHz, 30 MHz to 26 GHz X-Orientation

No other emissions found within 10 dB of the limit.




Figure 22 - Top_802.15.4_ 2480 MHz, 30 MHz to 1 GHz, Horizontal (Peak) X-Orientation




Figure 23 - Top_802.15.4_ 2480 MHz, 1 GHz to 26 GHz, Horizontal (Peak) X-Orientation




Figure 24 – Top_802.15.4_2480 MHz, 30 MHz to 1 GHz, Vertical (Peak) X-Orientation




Figure 25 – Top_802.15.4_2480 MHz, 1 GHz to 26 GHz, Vertical (Peak) X-Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12027.751	46.17	54.00	-7.83	RMS	210	151	Vertical

Table 30 - Bottom_802.15.4_2405 MHz, 30 MHz to 26 GHz Y -Orientation

No other emissions found within 10 dB of the limit.




Figure 26 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Y- Orientation




Figure 27 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Y- Orientation




Figure 28 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Vertical (Peak) Y- Orientation




Figure 29 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Vertical (Peak) Y- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 31 - Middle_802.15.4_2445 MHz, 30 MHz to 26 GHz Y -Orientation

*No emissions found within 10 dB of the limit.




Figure 30 - Middle_802.15.4_2445 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Y- Orientation




Figure 31 - Mid_802.15.4_2445 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Y- Orientation




Figure 32 - Mid_802.15.4_2445 MHz, 30 MHz to 1 GHz, Vertical (Peak) Y- Orientation




Figure 33 - Mid_802.15.4_2445 MHz, 1 GHz to 26 GHz, Vertical (Peak) Y- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
17356.150	43.51	54.00	-10.49	RMS	360	150	Vertical

Table 32 – Top_802.15.4 - 2480 MHz, 30 MHz to 26 GHz Y -Orientation

No other emissions found within 10 dB of the limit.




Figure 34 - Top_802.15.4_2480 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Y- Orientation




Figure 35 - Top_802.15.4_2480 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Y- Orientation




Figure 36 - Top_802.15.4_2480 MHz, 30 MHz to 1 GHz, Vertical (Peak) Y- Orientation




Figure 37 - Top_802.15.4_2480 MHz, 1 GHz to 26 GHz, Vertical (Peak) Y- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12022.250	48.90	54.00	-5.10	RMS	216	250	Horizontal

Table 33 – Bottom_802.15.4_2405 MHz, 30 MHz to 26 GHz Z -Orientation

No other emissions found within 10 dB of the limit.




Figure 38 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Z- Orientation




Figure 39 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Z- Orientation




Figure 40 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Vertical (Peak) Z- Orientation




Figure 41 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Vertical (Peak) Z- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12227.650	48.53	54.00	-5.47	RMS	223	229	Horizontal

Table 34 - Middle_802.15.4_2445 MHz, 30 MHz to 26 GHz Z -Orientation
No other emissions found within 10 dB of the limit.




Figure 42 - Middle_802.15.4_2445 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Z- Orientation




Figure 43 - Middle_802.15.4_2445 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Z- Orientation




Figure 44 - Middle_802.15.4_2445 MHz, 30 MHz to 1 GHz, Vertical (Peak) Z- Orientation




Figure 45 - Middle_802.15.4_2445 MHz, 1 GHz to 26 GHz, Vertical (Peak) Z- Orientation

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12402.650	45.39	54.00	-8.61	RMS	196	242	Horizontal
17356.100	45.82	54.00	-8.18	RMS	354	327	Vertical

Table 35 - Top_802.15.4_2480 MHz, 30 MHz to 26 GHz Z -Orientation

No other emissions found within 10 dB of the limit.




Figure 46 - Top_802.15.4_2480 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Z- Orientation




Figure 47 - Top_802.15.4_2480 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Z- Orientation




Figure 48 - Top _802.15.4_2480 MHz, 30 MHz to 1 GHz, Vertical (Peak) Z- Orientation




Figure 49 - Top _802.15.4_2480 MHz, 1 GHz to 26 GHz, Vertical (Peak) Z- Orientation

IEEE 802.15.4 - PCB Trace Antenna (XGM270S S7)

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12022.331	51.12	54.00	-2.88	RMS	213	266	Horizontal
12027.750	48.37	54.00	-5.63	RMS	103	234	Vertical

Table 36 - Bottom_802.15.4 - 2405 MHz, 30 MHz to 26 GHz X -Orientation

No other emissions found within 10 dB of the limit.




Figure 50 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Horizontal (Peak) X- Orientation




Figure 51 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Horizontal (Peak) X- Orientation




Figure 52 - Bottom _802.15.4_2405 MHz, 30 MHz to 1 GHz, Vertical (Peak) X- Orientation




Figure 53 - Bottom _802.15.4_2405 MHz, 1 GHz to 26 GHz, Vertical (Peak) X- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12222.250	47.16	54.00	-6.84	RMS	208	259	Horizontal

Table 37 - Mid_802.15.4_2445 MHz, 30 MHz to 26 GHz X -Orientation

No other emissions found within 10 dB of the limit.




Figure 54 - Mid_802.15.4_2445 MHz, 30 MHz to 1 GHz, Horizontal (Peak) X- Orientation




Figure 55 - Mid_802.15.4_2445 MHz, 1 GHz to 26 GHz, Horizontal (Peak) X- Orientation




Figure 56 - Mid_802.15.4_2485 MHz, 30 MHz to 1 GHz, Vertical (Peak) X- Orientation




Figure 57 - Mid_802.15.4_2445 MHz, 1 GHz to 26 GHz, Vertical (Peak) X- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 38 - Top_802.15.4_2480 MHz, 30 MHz to 26 GHz X -Orientation

*No emissions found within 10 dB of the limit.




Figure 58 - Top_802.15.4_2480 MHz, 30 MHz to 1 GHz, Horizontal (Peak) X- Orientation




Figure 59 - Top_802.15.4_2480 MHz, 1 GHz to 26 GHz, Horizontal (Peak) X- Orientation




Figure 60 - Top _802.15.4_2480 MHz, 30 MHz to 1 GHz, Vertical (Peak) X- Orientation




Figure 61 - Top _802.15.4_2480 MHz, 1 GHz to 26 GHz, Vertical (Peak) X- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 39 - Bottom_802.15.4_2405 MHz, 30 MHz to 26 GHz Y -Orientation

*No emissions found within 10 dB of the limit.




Figure 62 - Bottom_802.15.4_2405 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Y- Orientation




Figure 63 - Bottom_802.15.4_2405 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Y- Orientation




Figure 64 - Bottom _802.15.4_2405 MHz, 30 MHz to 1 GHz, Vertical (Peak) Y- Orientation




Figure 65 - Bottom _802.15.4_2405 MHz, 1 GHz to 26 GHz, Vertical (Peak) Y- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
12222.256	46.77	54.00	-7.23	RMS	183	150	Vertical

Table 40 - Middle_802.15.4_2445 MHz, 30 MHz to 26 GHz Y -Orientation

No other emissions found within 10 dB of the limit.




Figure 66 - Middle_802.15.4_2445 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Y- Orientation




Figure 67 - Middle_802.15.4_2445 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Y- Orientation




Figure 68 - Middle_802.15.4_2485 MHz, 30 MHz to 1 GHz, Vertical (Peak) Y- Orientation




Figure 69 -Middle _802.15.4_2445 MHz, 1 GHz to 26 GHz, Vertical (Peak) Y- Orientation

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 41 - Top_802.15.4_2480 MHz, 30 MHz to 26 GHz Y -Orientation

*No emissions found within 10 dB of the limit.




Figure 70 - Top_802.15.4_2480 MHz, 30 MHz to 1 GHz, Horizontal (Peak) Y- Orientation




Figure 71 - Top_802.15.4_2480 MHz, 1 GHz to 26 GHz, Horizontal (Peak) Y- Orientation