

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

FCC ID: QPKMBJWCAM5A

Page: 1 / 58
Rev.: 00

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C


Test Standard	FCC Part 15.247
Product name	SAPPHIRE PULSE(mother board)
Brand Name	Sapphire
Model No.	B650M
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc.(Wugu Laboratory)

Approved by:



Dally Hong
Sr. Engineer

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 2 / 58
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	April 17, 2025	Initial Issue	ALL	Peggy Tsai

Table of contents

1.	GENERAL INFORMATION	4
1.1	EUT INFORMATION	4
1.2	EUT CHANNEL INFORMATION	5
1.3	ANTENNA INFORMATION	5
1.4	MEASUREMENT UNCERTAINTY.....	6
1.5	FACILITIES AND TEST LOCATION	6
1.6	INSTRUMENT CALIBRATION	7
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT	9
1.8	TEST SET UP DIAGRAM.....	10
1.9	TEST PROGRAM	10
1.10	TEST METHODOLOGY AND APPLIED STANDARDS	10
2.	TEST SUMMERY	11
3.	DESCRIPTION OF TEST MODES.....	12
3.1	THE WORST MODE OF OPERATING CONDITION	12
3.2	THE WORST MODE OF MEASUREMENT	13
3.3	EUT DUTY CYCLE.....	14
4.	TEST RESULT	15
4.1	AC POWER LINE CONDUCTED EMISSION	15
4.2	6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)	18
4.3	OUTPUT POWER MEASUREMENT	23
4.4	POWER SPECTRAL DENSITY	26
4.5	CONDUCTED BAND EDGE AND SPURIOUS EMISSION	29
4.6	RADIATION BANEDGE AND SPURIOUS EMISSION	33
APPENDIX 1 - PHOTOGRAPHS OF EUT		

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Sapphire Technology Limited Unit 1910-1919, 19/F., Tower 2, Grand Central Plaza, 138 Shatin Rural Committee Road, Shatin, N.T., HK.
Manufacturer	Sapphire Technology Limited Unit 1910-1919, 19/F., Tower 2, Grand Central Plaza, 138 Shatin Rural Committee Road, Shatin, N.T., HK.
Equipment	SAPPHIRE PULSE(mother board)
Model No.	B650M
Model Discrepancy	N/A
Trade Name	Sapphire
Received Date	December 27, 2024
Date of Test	February 12 ~ 18, 2025
Power Operation	Powered from AC 120V
HW Version	JAM5MC05 V1.0
FW Version	BIOS AM50D101R3

Remark:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

1.2 EUT CHANNEL INFORMATION

Frequency Range	2402MHz-2480MHz
Modulation Type	GFSK for BLE 1 Mbps GFSK for BLE 2 Mbps
Number of channel	40 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Type	☐ PIFA ☐ PCB ☒ Dipole ☐ Coils
Antenna Brand / Model Name	South star / 301800008709
Antenna Gain	Gain: 3.83 dBi
Antenna Connector	SMA

Notes:

1.The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 2.21 dB
Channel Bandwidth	+/- 2.79 dB
RF output power (Power Meter + Power sensor)	+/- 0.24 dB
Power Spectral density	+/- 2.74 dB
Conducted Bandedge	+/- 2.74 dB
Conducted Spurious Emission	+/- 2.74 dB
Radiated Emission_9kHz-30MHz	+/- 3.492 dB
Radiated Emission_30MHz-200MHz	+/- 3.62 dB
Radiated Emission_200MHz-1GHz	+/- 3.899 dB
Radiated Emission_1GHz-6GHz	+/- 5.063 dB
Radiated Emission_6GHz-18GHz	+/- 5.122 dB
Radiated Emission_18GHz-26GHz	+/- 3.032 dB
Radiated Emission_26GHz-40GHz	+/- 3.271 dB

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	Ben Yang	-
Radiation	Tony Chao	-
RF Conducted	Jerry Chang	-

Remark: The lab has been recognized as the FCC accredited lab. under the KDB 974614 D01 and is listed in the FCC public Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309

1.6 INSTRUMENT CALIBRATION

Conducted FCC/IC/NCC (All)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Cable	Woken	WC12	CC003	2024-06-26	2025-06-25
Cable	Woken	WC12	CC001	2024-06-26	2025-06-25
PXA Signal Analyzer	Keysight	N9030B	MY62291089	2024-10-04	2025-10-03
Power Sensor	Anritsu	MA2411B	1911387	2024-08-30	2025-08-29
Power Sensor	Anritsu	MA2411B	1911386	2024-07-19	2025-07-18
Power Meter	Anritsu	ML2496A	2136002	2024-07-19	2025-07-18
DC Blocks	Marvelous Microwave	MVE6411	MVE-001	2024-08-08	2025-08-07
Software	Radio Test Software Ver. 21				

966A Radiated					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Signal Analyzer	KEYSIGHT	N9010A	MY52220817	2024-03-15	2025-03-14
Active Loop Antenna	SCHWARZBECK	FMZB 1513-60	1513-60-028	2024-12-11	2025-12-10
Thermo-Hygro Meter	WISEWIND	1206	D07	2024-11-26	2025-11-25
Bi-Log Antenna	Sunol Sciences	JB3	A030105	2024-07-12	2025-07-11
Preamplifier	EMEC	EM330	060609	2024-02-21	2025-02-20
Cable	Huber+Suhner	104PEA	20995+21000+182330	2024-08-07	2025-08-06
Horn Antenna	ETC	MCTD 1209	DRH13M02003	2024-12-20	2025-12-19
Preamplifier	HP	8449B	3008A00965	2024-12-18	2025-12-17
Cable	EMCI	EMC101G	221011+221012+221213	2024-10-11	2025-10-10
Attenuator	Mini-Circuits	BW-S9W5	BWS9W5-09-966A-01	2024-02-07 2025-02-06	2025-02-06 2026-02-05
Site Validation	CCS	966A	N/A	2024-08-03	2025-08-02
High Pass Filters	Titan Microwave	T04H30001800070S01	22011402-4	2024-06-12	2025-06-11
Pre-Amplifier	EMCI	EMC184045SE	980860	2024-12-02	2025-12-01
Horn Antenna	SCHWARZBECK	BBHA9170	1047	2024-12-06	2025-12-05
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Software	e3 V9-210616c				

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 8 / 58
Rev.: 00

AC Mains Conduction					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EMI Test Receiver	R&S	ESCI	100064	2024-06-14	2025-06-13
LISN	TESEQ	LN2-16N	22012	2024-02-29	2025-02-27
Cable	Woken	SFL402	185A	2024-07-08	2025-07-07
Software	e3 V6-110812				

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Required.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT


EUT Accessories Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
	N/A					

Support Equipment (Conducted)						
No.	Equipment	Brand	Model	Series No.	FCC ID	
1	HDMI Cable	High Speed	E342987	N/A	N/A	
2	LCD Monitor	Lenovo	A20238FT0	N/A	N/A	

Support Equipment (Conduction)						
No.	Equipment	Brand	Model	Series No.	FCC ID	
1	Monitor	Lenovo	A20238FT0	VKPN2606	N/A	
2	HDMI Cable	High Speed	E342987	N/A	N/A	
3	Power Cable	N/A	N/A	N/A	N/A	
4	Power Cable	N/A	N/A	N/A	N/A	
5	Mouse	Lenovo	MO32BOA	4460028	N/A	
A	Dipole Antenna	South star	301800008709	N/A	N/A	

Support Equipment (RSE)						
No.	Equipment	Brand	Model	Series No.	FCC ID	
1	Monitor	Lenovo	A20238FT0	VKPN2606	N/A	
2	HDMI Cable	High Speed	E342987	N/A	N/A	
3	Power Cable	StarTech	5214-PXT101_3-ND	PXT101_3	N/A	
4	Power Cable	StarTech	5214-PXT101_3-ND	PXT101_3	N/A	
A	Dipole Antenna	South star	301800008709	N/A	N/A	

1.8 TEST SET UP DIAGRAM



1.9 TEST PROGRAM

The EUT connection corresponds to the surrounding fixture control board.
This EUT uses MP tool & RtlBluetoothMP tool to set the frequency, modulation, and power to allow the sample to continuously transmit .(including frequency hopping mode).

1.10 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, KDB 558074.

2. TEST SUMMERY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	Pass
15.247(a)(2)	4.2	6 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)(3)	4.3	Output Power Measurement	Pass
15.247(e)	4.4	Power Spectral Density	Pass
15.247(d)	4.5	Conducted Band Edge	Pass
15.247(d)	4.5	Conducted Spurious Emission	Pass
15.247(d) 15.205, 15.209	4.6	Radiation Band Edge	Pass
15.247(d) 15.205, 15.209	4.6	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	BLE Mode (1Mbps) BLE Mode (2Mbps)
Test Channel Frequencies	1.Lowest Channel : 2402MHz 2.Middle Channel : 2442MHz 3.Highest Channel : 2480MHz

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conduction Emission	
Test Condition	AC Power line conduction emission for line and neutral
Power supply Mode	Mode 1: EUT Power by AC 120V
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by AC(120V)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☒ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by AC(120V)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. AC power line conducted emission were performed the EUT transmit at the highest output power channel as worse case.
3. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Z-Plane) were recorded in this report

3.3 EUT DUTY CYCLE

Temperature: 22.6°C

Test date: February 14, 2025



Humidity: 56% RH

Tested by: Jerry Chang

Mode	Duty Cycle (%) = Ton / (Ton+Toff)	Duty Factor (dB) = 10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
BLE 1M	63.20	1.99	2.53	3.00
BLE 2M	33.60	4.74	4.76	5.00

BLE_1M_LowCH00-2402

BLE_2M_LowCH00-2402



4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.


4.1.3 Test Setup



4.1.4 Test Result

Project No : TM-2412000356P
Operation Mode : BLE
Test Chamber : Conduction
Probe : LINE
Note :

Test Date : 2025-02-12
Temp./Humi. : 23.4°C / 54%
Engineer : Ben.Yang
Test Voltage : AC 120V/60Hz



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Read Level dBμV	Factor dB	Actual FS dBμV	Limit dBμV	Margin dB
0.209	QP	31.72	0.39	32.11	63.23	-31.12
0.209	Average	29.97	0.39	30.36	53.23	-22.87
1.821	QP	22.64	0.18	22.82	56.00	-33.18
1.821	Average	18.59	0.18	18.77	46.00	-27.23
9.884	QP	44.00	0.36	44.36	60.00	-15.64
9.884	Average	42.81	0.36	43.17	50.00	-6.83
11.814	QP	43.18	0.38	43.56	60.00	-16.44
11.814	Average	42.85	0.38	43.23	50.00	-6.77
16.743	QP	27.04	0.44	27.48	60.00	-32.52
16.743	Average	22.41	0.44	22.85	50.00	-27.15
20.774	QP	24.34	0.49	24.83	60.00	-35.17
20.774	Average	21.25	0.49	21.74	50.00	-28.26

Note: 1. Actual FS= Spectrum Read Level + Factor


Note: 2. Margin= Actual FS - Limit

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 17 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Mode : BLE
Test Chamber : Conduction
Probe : NEUTRAL
Note :

Test Date : 2025-02-12
Temp./Humi. : 23.4°C / 54%
Engineer : Ben.Yang
Test Voltage : AC 120V/60Hz



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Read Level dBμV	Factor dB	Actual FS dBμV	Limit dBμV	Margin dB
0.211	QP	31.35	0.36	31.71	63.17	-31.46
0.211	Average	29.37	0.36	29.73	53.17	-23.44
0.558	QP	26.28	0.35	26.63	56.00	-29.37
0.558	Average	5.03	0.35	5.38	46.00	-40.62
1.823	QP	21.02	0.16	21.18	56.00	-34.82
1.823	Average	16.88	0.16	17.04	46.00	-28.96
5.986	QP	25.70	0.27	25.97	60.00	-34.03
5.986	Average	23.53	0.27	23.80	50.00	-26.20
9.680	QP	41.96	0.34	42.30	60.00	-17.70
9.680	Average	40.80	0.34	41.14	50.00	-8.86
12.080	QP	42.19	0.36	42.55	60.00	-17.45
12.080	Average	38.43	0.36	38.79	50.00	-11.21

Note: 1. Actual FS= Spectrum Read Level + Factor

Note: 2. Margin= Actual FS - Limit

4.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

4.2.1 Test Limit

According to §15.247(a)(2),

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------

Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as KDB 558074 D01 and ANSI C63.10: 2013 clause 6.9.2.

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup

Refer to section 1.8.

4.2.4 Test Result

Temperature: 22.6°C

Test date: February 14, 2025

Humidity: 56% RH

Tested by: Jerry Chang

6dB BANDWIDTH

BLE 1M mode

Frequency (MHz)	6dB BW (MHz)	Required BW (MHz)	Result
2402	0.6571	≥ 0.5	PASS
2442	0.6465	≥ 0.5	PASS
2480	0.6594	≥ 0.5	PASS

BLE 2M mode

Frequency (MHz)	6dB BW (MHz)	Required BW (MHz)	Result
2402	1.097	≥ 0.5	PASS
2442	1.098	≥ 0.5	PASS
2480	1.111	≥ 0.5	PASS

BANDWIDTH 99%

BLE 1M mode

Frequency (MHz)	99%Bandwidth (MHz)
2402	1.014
2442	1.0371
2480	1.0256

BLE 2M mode

Frequency (MHz)	99%Bandwidth (MHz)
2402	2.0613
2442	2.057
2480	2.0612


Test Data

6dB BANDWIDTH

OBW BLE 1M LowCH00-2402MHz



OBW BLE 2M LowCH00-2402MHz



OBW BLE 1M MidCH20-2442MHz



OBW BLE 2M MidCH20-2442MHz



OBW BLE 1M HighCH39-2480MHz



OBW BLE 2M HighCH39-2480MHz




BANDWIDTH 99%

IC OBW BLE 1M LowCH00-2402MHz




IC OBW BLE 2M LowCH00-2402MHz



IC OBW BLE 1M MidCH20-2442MHz



IC OBW BLE 2M MidCH20-2442MHz



IC OBW BLE 1M HighCH39-2480MHz



IC OBW BLE 2M HighCH39-2480MHz



4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b)(3),

Peak output power :

FCC

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Limit	☒ Antenna not exceed 6 dBi : 30dBm ☐ Antenna with DG greater than 6 dBi [Limit = 30 – (DG – 6)] ☐ Point-to-point operation
-------	---

Average output power : For reporting purposes only.

4.3.2 Test Procedure

Test method Refer as KDB 558074 D01

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup

Refer to section 1.8.

4.3.4 Test Result

Temperature: 22.6°C

Test date: February 14, 2025

Humidity: 56% RH

Tested by: Jerry Chang

Peak & Average output power :

BLE 1M mode:

CH	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	Required Limit (dBm)
0	2402	default	3.48	30
20	2442	default	3.80	30
39	2480	default	3.75	30
CH	Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Required Limit (dBm)
0	2402	default	3.31	30
20	2442	default	3.61	30
39	2480	default	3.60	30

***Note:**

1.Measured by power meter, cable loss 2.65 dB + Duty cycle factor has been offseted to the power meter for Avg. power and cable loss has been offseted for Peak power measurement.

BLE 2M mode:

CH	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	Required Limit (dBm)
0	2402	default	3.57	30
20	2442	default	3.89	30
39	2480	default	3.91	30
CH	Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Required Limit (dBm)
0	2402	default	3.33	30
20	2442	default	3.66	30
39	2480	default	3.71	30

***Note:**

1. Measured by power meter, cable loss 2.65 dB + Duty cycle factor has been offsetted to the power meter for Avg. power and cable loss has been offsetted for Peak power measurement.

4.4 POWER SPECTRAL DENSITY

4.4.1 Test Limit

According to §15.247(e),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	☒ Antenna not exceed 6 dBi : 8dBm ☐ Antenna with DG greater than 6 dBi [Limit = 8 – (DG – 6)] ☐ Point-to-point operation :
-------	---

4.4.2 Test Procedure

Test method Refer as KDB 558074 D01

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 10kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss was compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

4.4.3 Test Setup

Refer to section 1.8.

4.4.4 Test Result

Temperature: 22.6°C

Test date: February 14, 2025

Humidity: 56% RH

Tested by: Jerry Chang

BLE 1M mode

Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	-13.27	8	PASS
2442	-11.38	8	PASS
2480	-12.03	8	PASS

***Note:**

1.cable loss as 2.65dB that offsets in the spectrum







BLE 2M mode

Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	-12.73	8	PASS
2442	-14.04	8	PASS
2480	-14.83	8	PASS

***Note:**

1.cable loss as 2.65dB that offsets in the spectrum

Test Data



4.5 CONDUCTED BAND EDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d) and RSS-247 section 5.5,

FCC: In any 100 kHz bandwidth outside the authorized frequency band, Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

IC: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

4.5.2 Test Procedure

Test method Refer as KDB 558074 D01

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.5.3 Test Setup

Refer to section 1.8.

4.5.4 Test Result

Temperature: 22.6°C


Test date: February 14, 2025

Humidity: 56% RH


Tested by: Jerry Chang

Test Data Reference Level


Reference Level BLE 1M LowCH00-2402MHz




Reference Level BLE 2M LowCH00-2402MHz



Reference Level BLE 1M MidCH20-2442MHz



Reference Level BLE 2M MidCH20-2442MHz



Reference Level BLE 1M HighCH39-2480MHz



Reference Level BLE 2M HighCH39-2480MHz




Band Edge

Band Edge BLE 1M LowCH00-2402MHz



Band Edge BLE 2M LowCH00-2402MHz



Band Edge BLE 1M HighCH39-2480MHz



Band Edge BLE 2M HighCH39-2480MHz



Spurious Emission

Spurious Emission BLE 1M LowCH00-2402MHz



Spurious Emission BLE 2M LowCH00-2402MHz



Spurious Emission BLE 1M MidCH20-2442MHz



Spurious Emission BLE 2M MidCH20-2442MHz



Spurious Emission BLE 1M HighCH39-2480MHz



Spurious Emission BLE 2M HighCH39-2480MHz



4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4.6.2 Test Procedure

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.
3. Span shall wide enough to full capture the emission measured. The SA from 9KHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.
4. No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz).

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-ane choic chamber, the measurements correspond to those obtained at an open-field test site. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

5. The SA setting following :

- (1) Below 30MHz :

(1.1) 9KHz-490KHz : RBW=200Hz / VBW=1kHz / Sweep=AUTO

(1.2) 490KHz-30MHz : RBW=10kHz / VBW=30kHz / Sweep=AUTO

- (2) 30MHz to 1GHz : RBW = 100kHz, VBW $\geq 3 \times$ RBW, Sweep = Auto,

Detector = Peak, Trace = Max hold.

- (3) Above 1GHz :

(3.1) For Peak measurement : RBW = 1MHz, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(3.2) For Average measurement : RBW = 1MHz, VBW

·If Duty Cycle $\geq 98\%$, VBW=10Hz.

·If Duty Cycle $< 98\%$, VBW=1/T.


6. Data result :

Actual FS=Spectrum Reading Level + Factor


Margin=Actual FS- Limit

4.6.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz




Above 1 GHz



4.6.4 Test Result

Band Edge Test Data

Project No	: TM-2412000356P	Test Date	: 2025-02-12
Operation Band	: BLE_1M	Temp./Humi.	: 24.6/57
Frequency	: 2402 MHz	Antenna Pol.	: VERTICAL
Operation Mode	: Bandedge	Engineer	: Tony.Chao
EUT Pol	: H	Test Chamber	: 966A
Setting	:		



Trace: 1


Freq	Read	Factor	Actual	Limit	Margin	Detector
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2375.17	33.87	6.34	40.21	54.00	-13.79	Average
2389.90	45.18	6.43	51.61	74.00	-22.39	Peak
2402.00	98.91	6.49	105.40	--	--	Peak
2402.00	98.31	6.49	104.80	--	--	Average
2487.77	32.98	6.85	39.83	54.00	-14.17	Average
2494.02	43.26	6.85	50.11	74.00	-23.89	Peak

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 38 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2402 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Trace: 1						
Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2314.00	33.07	6.46	39.53	54.00	-14.47	Average
2323.48	44.06	6.37	50.43	74.00	-23.57	Peak
2402.00	86.01	6.49	92.50	--	--	Peak
2402.00	85.39	6.49	91.88	--	--	Average
2488.77	42.85	6.85	49.70	74.00	-24.30	Peak
2500.01	33.44	6.84	40.28	54.00	-13.72	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 39 / 58
Rev: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Trace: 1						
Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2311.75	43.72	6.48	50.20	74.00	-23.80	Peak
2371.42	33.38	6.31	39.69	54.00	-14.31	Average
2480.00	98.69	6.78	105.47	--	--	Peak
2480.00	98.19	6.78	104.97	--	--	Average
2483.53	40.14	6.82	46.96	54.00	-7.04	Average
2487.03	45.41	6.84	52.25	74.00	-21.75	Peak

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 40 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A



Trace: 1


Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2311.75	43.32	6.48	49.80	74.00	-24.20	Peak
2332.97	32.98	6.33	39.31	54.00	-14.69	Average
2480.00	85.26	6.78	92.04	--	--	Peak
2480.00	84.76	6.78	91.54	--	--	Average
2499.51	33.42	6.84	40.26	54.00	-13.74	Average
2500.01	43.45	6.84	50.29	74.00	-23.71	Peak

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 41 / 58
Rev: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Trace: 1						
Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2375.45	33.67	6.34	40.01	54.00	-13.99	Average
2387.93	45.95	6.42	52.37	74.00	-21.63	Peak
2402.00	99.16	6.49	105.65	--	--	Peak
2402.00	96.85	6.49	103.34	--	--	Average
2486.35	43.19	6.83	50.02	74.00	-23.98	Peak
2492.35	32.91	6.86	39.77	54.00	-14.23	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 42 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Trace: 1						
Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2331.98	43.35	6.34	49.69	74.00	-24.31	Peak
2386.94	32.95	6.41	39.36	54.00	-14.64	Average
2402.00	86.30	6.49	92.79	--	--	Peak
2402.00	83.88	6.49	90.37	--	--	Average
2486.35	43.02	6.83	49.85	74.00	-24.15	Peak
2499.84	33.32	6.84	40.16	54.00	-13.84	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 43 / 58
Rev: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Trace: 1						
Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2377.44	33.32	6.35	39.67	54.00	-14.33	Average
2381.44	43.55	6.38	49.93	74.00	-24.07	Peak
2480.00	98.95	6.78	105.73	--	--	Peak
2480.00	96.48	6.78	103.26	--	--	Average
2483.85	51.95	6.82	58.77	74.00	-15.23	Peak
2483.85	41.54	6.82	48.36	54.00	-5.64	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 44 / 58
Rev: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A



Trace: 1

Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2329.48	43.45	6.35	49.80	74.00	-24.20	Peak
2374.95	32.89	6.33	39.22	54.00	-14.78	Average
2480.00	85.54	6.78	92.32	--	--	Peak
2480.00	83.17	6.78	89.95	--	--	Average
2483.85	33.64	6.82	40.46	54.00	-13.54	Average
2499.84	42.75	6.84	49.59	74.00	-24.41	Peak


Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 45 / 58
Rev.: 00

TX Test Data

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-18
Temp./Humi. : 24.5/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read		Actual	Limit		Detector
-----	Level	Factor	FS	@3m	Margin	Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
46.60	48.94	-14.53	34.41	40.00	-5.59	Peak
218.50	42.89	-12.55	30.34	46.00	-15.66	Peak
249.00	43.24	-11.40	31.84	46.00	-14.16	Peak
415.00	41.45	-6.31	35.14	46.00	-10.86	Peak
581.00	45.56	-3.24	42.32	46.00	-3.68	Peak
747.00	45.02	-0.33	44.69	46.00	-1.31	Peak

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 46 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-18
Temp./Humi. : 24.5/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
249.00	45.26	-11.40	33.86	46.00	-12.14	Peak
415.00	38.47	-6.31	32.16	46.00	-13.84	Peak
532.80	36.54	-3.92	32.62	46.00	-13.38	Peak
581.00	44.35	-3.24	41.11	46.00	-4.89	Peak
747.00	40.16	-0.33	39.83	46.00	-6.17	Peak
913.00	35.65	1.61	37.26	46.00	-8.74	Peak

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 47 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	37.18	1.98	39.16	74.00	-34.84	Peak
4804.00	28.68	1.98	30.66	54.00	-23.34	Average
7206.00	34.16	8.82	42.98	74.00	-31.02	Peak
7206.00	26.27	8.82	35.09	54.00	-18.91	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 48 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	36.01	1.98	37.99	74.00	-36.01	Peak
4804.00	28.45	1.98	30.43	54.00	-23.57	Average
7206.00	34.48	8.82	43.30	74.00	-30.70	Peak
7206.00	26.53	8.82	35.35	54.00	-18.65	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 49 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	36.41	2.69	39.10	74.00	-34.90	Peak
4884.00	28.07	2.69	30.76	54.00	-23.24	Average
7326.00	34.92	9.27	44.19	74.00	-29.81	Peak
7326.00	26.43	9.27	35.70	54.00	-18.30	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 50 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	34.96	2.69	37.65	74.00	-36.35	Peak
4884.00	28.57	2.69	31.26	54.00	-22.74	Average
7326.00	34.84	9.27	44.11	74.00	-29.89	Peak
7326.00	26.39	9.27	35.66	54.00	-18.34	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 51 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	37.92	3.71	41.63	74.00	-32.37	Peak
4960.00	31.55	3.71	35.26	54.00	-18.74	Average
7440.00	34.68	9.27	43.95	74.00	-30.05	Peak
7440.00	26.86	9.27	36.13	54.00	-17.87	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 52 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	36.10	3.71	39.81	74.00	-34.19	Peak
4960.00	28.14	3.71	31.85	54.00	-22.15	Average
7440.00	34.18	9.27	43.45	74.00	-30.55	Peak
7440.00	26.37	9.27	35.64	54.00	-18.36	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 53 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	36.81	1.98	38.79	74.00	-35.21	Peak
4804.00	28.26	1.98	30.24	54.00	-23.76	Average
7206.00	34.86	8.82	43.68	74.00	-30.32	Peak
7206.00	26.14	8.82	34.96	54.00	-19.04	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 54 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	37.10	1.98	39.08	74.00	-34.92	Peak
4804.00	28.14	1.98	30.12	54.00	-23.88	Average
7206.00	34.50	8.82	43.32	74.00	-30.68	Peak
7206.00	26.23	8.82	35.05	54.00	-18.95	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 55 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	37.80	2.69	40.49	74.00	-33.51	Peak
4884.00	27.28	2.69	29.97	54.00	-24.03	Average
7326.00	35.57	9.27	44.84	74.00	-29.16	Peak
7326.00	26.32	9.27	35.59	54.00	-18.41	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 56 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	35.78	2.69	38.47	74.00	-35.53	Peak
4884.00	27.38	2.69	30.07	54.00	-23.93	Average
7326.00	33.62	9.27	42.89	74.00	-31.11	Peak
7326.00	26.32	9.27	35.59	54.00	-18.41	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 57 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	35.83	3.71	39.54	74.00	-34.46	Peak
4960.00	28.82	3.71	32.53	54.00	-21.47	Average
7440.00	33.73	9.27	43.00	74.00	-31.00	Peak
7440.00	26.44	9.27	35.71	54.00	-18.29	Average

Project No: TM-2412000356P
Report No.: TMWK2412004716KR

Page: 58 / 58
Rev.: 00

Project No : TM-2412000356P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : H
Setting :

Test Date : 2025-02-12
Temp./Humi. : 24.6/57
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A



Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	35.51	3.71	39.22	74.00	-34.78	Peak
4960.00	27.64	3.71	31.35	54.00	-22.65	Average
7440.00	32.13	9.27	41.40	74.00	-32.60	Peak
7440.00	26.14	9.27	35.41	54.00	-18.59	Average

- End of Test Report -