

The Handheld KeyTerminal is a battery operated small reader to be operated single-handed for keymotion™ technology. Its key functions are authorisation verification and value debiting.



Picture may vary from actual product

Features

- Data carrier compatible with all SKIDATA™ Systems with keymotion™ technology
- Single hand operation
- Rigid design; applicable for outdoor uses
- Large display for simple user guidance
- Powerful microprocessor for application programs

Versions, Accessories

937340000	ASx70KT KeyTerminal
937340010	ASx70KT/DH (with backlit display)
937340030	ASx70KT/C KeyTerminal

Technical Characteristics

Data Carriers	keycard, Swatch Access, KeyBand, KeyRing, GORE-TEX® Glove, GemFree, ISO 15693
Measures	175 x 92 x 37 mm (l x w x h)
Weight	0.3 kg
Input Voltage	9V DC
Power consumption	5 W typ.
Interface	RS 232
Temperature Range	Operation: -10°C to +40°C; when charging: +5°C to +40°C
Colour	Blue RELIUS E-14-45, Orange (PANTONE 151 C)
Radio Frequency	125 KHz / 13 MHz
Display	4 rows at 20 characters each, non-backlit (graphical resolution 120 x 32 pixels, backlighting optional)
Keypad	16 keys, silicon rubber
Rechargeable battery cell	Li-Ion 3.7 V / 200 mAh
Standards	EN 300330-2, EN 301489-3, Pacemaker Safety VDE 0848-3-1
Safety Class	IP 31

Please note the instructions for battery recharging!

