

Report on the FCC and IC Testing of the
SKIDATA AG
RFID Reader Module. Model: SD906
In accordance with FCC 47 CFR Part 15C and
Industry Canada RSS-210 and Industry Canada
RSS-GEN

Prepared for: SKIDATA AG
Untersbergstrasse 40
5083 Grödig
Österreich

FCC ID: QSS-SD905
IC: 6215A-SD905



Product Service

Choose certainty.
Add value.

COMMERCIAL-IN-CONFIDENCE

Date: 2018-03-08
Document Number: TR-69575-25066-01 | Edition: 02

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Project Management	Matthias Stumpe	2018-07-09	
Authorised Signatory	Martin Steindl	2018-07-09	

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Product Service document control rules.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15C and Industry Canada RSS-210 and Industry Canada RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Matthias Stumpe	2018-07-09	

Laboratory Accreditation

DAKKS Reg. No. D-PL-11321-11-02

Laboratory recognition

Registration No. BNetzA-CAB-16/21-15

Industry Canada test site registration

3050A-2

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15C, Industry Canada RSS-210 and Industry Canada RSS-GEN:2016, Edition 09 (08-2016) and Edition 04 (11-2014).

DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD Product Service with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD Product Service. No part of this document may be reproduced without the prior written approval of TÜV SÜD Product Service. © 2018 TÜV SÜD Product Service.



Contents

1 **Report Summary 2**

1.1 Report Modification Record..... 2

1.2 Introduction..... 2

1.3 Brief Summary of Results..... 3

1.4 Application Form..... 4

1.5 Deviations from the Standard..... 4

1.6 EUT Modification Record 4

1.7 Test Location 4

2 **Test Details 5**

2.1 20 dB Bandwidth 5

2.2 Frequency Tolerance Under Temperature Variations..... 8

2.3 Field Strength of any Emission..... 10

2.4 AC Power Line Conducted Emissions 16

2.5 Exposure of Humans to RF Fields 19

3 **Photographs 24**

3.1 Equipment Under Test (EUT)..... 24

4 **Measurement Uncertainty 27**



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be Editioned to the holders of each copy in the form of a complete document.

Edition	Description of Change	Date of Edition
1	First Edition	2018-03-08
2	ICES changed to IC	2018-07-09

Table 1

1.2 Introduction

Applicant	SKIDATA AG
Manufacturer	SKIDATA AG
Model Number(s)	SD906
Serial Number(s)	R173000147
Hardware Version(s)	PCB: 906, HW vers.: 1, Variant: 2
Software Version(s)	Firmware: 1.31
Number of Samples Tested	1
Test Specification/Edition/Date	FCC 47 CFR Part 15C, Industry Canada RSS-210 and Industry Canada RSS-GEN:2016, Edition 09 (08-2016) and Edition 04 (11-2014)
Test Plan/Edition/Date	---
Order Number	1036822, 1042726
Date	
Date of Receipt of EUT	2017-10-27
Start of Test	2018-01-10
Finish of Test	2018-02-14
Name of Engineer(s)	Matthias Stumpe
Related Document(s)	ANSI C63.10 (2013)



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15C and Industry Canada RSS-210 and Industry Canada RSS-GEN is shown below.

Section	Specification Clause	Test Description	Result	Comments/Base Standard
Configuration and Mode: Normal operation - Continuous polling without RFID Tag card				
2.1	15.215 (c), N/A and 6.6	20 dB Bandwidth	Pass	ANSI C63.10 (2013)
2.2	15.225 (e), B.1 to B.9 and 6.11.	Frequency Tolerance Under Temperature Variations	Pass	ANSI C63.10 (2013)
2.3	15.225 (a)(b)(c)(d), B.1 to B.9, 6.4 and 6.5.	Field Strength of any Emission	Pass	ANSI C63.10 (2013)
2.4	15.207, N/A and 8.8	AC Power Line Conducted Emissions	Pass	ANSI C63.10 (2013)
2.5	---	Exposure of Humans to RF Fields	Pass	---

Table 2



1.4 Application Form

1.4.1 Technical Description

The Equipment Under Test (EUT) was a SKIDATA AG SD906 RFID Reader Module. The SS906 functions as a built-in interface between a SKIDATA device and contactless data carriers (RFID). Data communication between the SD906 and the other device is provided by means of a USB connection.

1.5 Deviations from the Standard

1.6 EUT Modification Record

The table below details modifications made to the EUT during the test programme. The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Serial Number: R173000147			
0	As supplied by the customer	Not Applicable	Not Applicable
1	Antenna coil has been replaced by a resistor for conducted emission test.	Applicant	2018-01-31

Table 3

1.7 Test Location

TÜV SÜD Product Service conducted the following tests at our Straubing Test Laboratory.

Test Name	Name of Engineer(s)
Configuration and Mode: Normal operation - Continuous polling without RFID Tag card	
20 dB Bandwidth	Matthias Stumpe
Frequency Tolerance Under Temperature Variations	Matthias Stumpe
Field Strength of any Emission	Matthias Stumpe
AC Power Line Conducted Emissions	Matthias Stumpe

Table 4

Office Address:

Äußere Frühlingstraße 45
94315 Straubing
Germany



2 Test Details

2.1 20 dB Bandwidth

2.1.1 Specification Reference

FCC 47 CFR Part 15C, Industry Canada RSS-210 and Industry Canada RSS-GEN, Clause 15.215 (c), N/A and 6.6

2.1.2 Equipment Under Test and Modification State

SD906, S/N: R173000147 - Modification State 0

2.1.3 Date of Test

2018-01-11

2.1.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.9.1.

2.1.5 Environmental Conditions

Ambient Temperature 21,0 °C
Relative Humidity 34,0 %

2.1.6 Test Results

Normal operation - Continuous polling without RFID Tag card

Frequency (MHz)	20 dB Bandwidth (Hz)	99% Occupied Bandwidth (Hz)	F _{LOWER} (MHz)	F _{UPPER} (MHz)
13.56 MHz	8 kHz	99 kHz	13.55594	13.56394

Table 5




Figure 1 - 20 dB Bandwidth




Figure 2 - 99% Occupied Bandwidth

FCC 47 CFR Part 15, Limit Clause 15.215 (c)

The 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.



Industry Canada RSS 210 and Industry Canada RSS GEN, Limit Clause

None specified.

2.1.7 Test Location and Test Equipment Used

This test was carried out in Semi anechoic room - cabin no. 8.

Instrument	Manufacturer	Type No	T-ID	Calibration Period (months)	Calibration Due
TRILOG Antenna	Schwarzbeck	VULB 9163	19691	24	2020-12-31
EMI test receiver	Rohde & Schwarz	ESW26	28268	12	2018-06-30

Table 6

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment

N/A - Not Applicable



2.2 Frequency Tolerance Under Temperature Variations

2.2.1 Specification Reference

FCC 47 CFR Part 15C, Industry Canada RSS-210 and Industry Canada RSS-GEN, Clause 15.225 (e), B.1 to B.9 and 6.11.

2.2.2 Equipment Under Test and Modification State

SD906, S/N: R173000147 - Modification State 0

2.2.3 Date of Test

2018-01-15

2.2.4 Environmental Conditions

Ambient Temperature 21,0 °C
Relative Humidity 28,0 %

2.2.5 Test Results

Normal operation - Continuous polling without RFID Tag card

Temperature	Voltage	Measured Frequency (MHz)	Frequency Deviation (%)	Frequency Error (ppm)
-40.0 °C	5.00 V DC	13.560071 MHz	0.00053	5.25
-30.0 °C	5.00 V DC	13.560105 MHz	0.00077	7.74
-20.0 °C	5.00 V DC	13.560116 MHz	0.00086	8.57
-10.0 °C	5.00 V DC	13.560101 MHz	0.00075	7.46
0.0 °C	5.00 V DC	13.560075 MHz	0.00055	5.53
+10.0 °C	5.00 V DC	13.560060 MHz	0.00044	4.42
+20.0 °C	5.00 V DC	13.560060 MHz	0.00044	4.42
+30.0 °C	5.00 V DC	13.560026 MHz	0.00019	1.93
+40.0 °C	5.00 V DC	13.559985 MHz	-0.00011	-1.11
+50.0 °C	5.00 V DC	13.559970 MHz	-0.00022	-2.21
+60.0 °C	5.00 V DC	13.559955 MHz	-0.00033	-3.32
+70.0 °C	5.00 V DC	13.559955 MHz		



FCC 47 CFR Part 15, Limit Clause 15.225 (e)

The frequency tolerance of the carrier signal shall be maintained within ± 0.01 % of the operating frequency.

Industry Canada RSS-210, Limit Clause B.6

Carrier frequency stability shall be maintained to $\pm 0.01\%$ (± 100 ppm)

2.2.6 Test Location and Test Equipment Used

This test was carried out in Non shielded room.

Instrument	Manufacturer	Type No	T-ID	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	ESPI	19578	12	2018-09-30
Climatic test chamber	ESPEC	PL-2J	18843	24	2019-03-31

Table 9

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment

N/A - Not Applicable



2.3 Field Strength of any Emission

2.3.1 Specification Reference

FCC 47 CFR Part 15C, Industry Canada RSS-210 and Industry Canada RSS-GEN, Clause 15.225 (a)(b)(c)(d), B.1 to B.9, 6.4 and 6.5.

2.3.2 Equipment Under Test and Modification State

SD906, S/N: R173000147 - Modification State 0

2.3.3 Date of Test

2018-01-10

2.3.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.3, 6.4 and 6.5.

Measurements were made at a distance of 3 m. The limit lines shown on the plot were extrapolated from either 300 m or 30 m to the measurement distance of 3 m in accordance with ANSI C63.10 Clause 6.4.4.2.

2.3.5 Environmental Conditions

Ambient Temperature 21,0 °C
Relative Humidity 27,0 %

2.3.6 Test Results

Normal operation - Continuous polling without RFID Tag card, Carrier Results

Frequency (MHz)	Quasi-Peak Level (dBµV/m) at 3m	Quasi-Peak Level (dBµV/m) at 30m	Quasi-Peak Level (µV/m) at 3m	Quasi-Peak Level (µV/m) at 30m
13.56 MHz	79.25	39.25	9173	91.73

Table 10




Figure 3 - Plot of the Fundamental - 13.56 MHz




Figure 4 - 9 kHz to 30 MHz

No emissions were detected within 6 dB of the limit.



Frequency (MHz)	Quasi Peak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
40.6800	34.05	40.00	5.95	1000.0	120.000	154.0	V	-115.0	14.2
54.2400	36.14	40.00	3.86	1000.0	120.000	150.0	V	-152.0	15.3
81.3600	36.01	40.00	3.99	1000.0	120.000	226.0	H	-175.0	8.8
135.6000	34.60	43.50	8.90	1000.0	120.000	261.0	H	3.0	10.3

Table 11 - Emissions Results – 30 MHz to 1 GHz




Figure 5 - 30 MHz to 1 GHz



FCC 47 CFR Part 15, Limit Clause 15.225 (a)(b)(c)(d)

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 m.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 m.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 m.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

FCC 47 CFR Part 15, Limit Clause 15.209

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 to 0.490	2400/F (kHz)	300
0.490 to 1.705	24000/F (kHz)	30
1705 to 30	30	30
30 to 88	100**	3
88 to 216	150**	3
216 to 960	200**	3
Above 960	500	5

Table 12 - FCC Radiated Emission Limit

Industry Canada RSS-210, Limit Clause B.6

The field strength of any emission shall not exceed the following limits:

- (a) 15.848 mW/m (84 dBμV/m) at 30 m, within the band 13.553 – 13.567 MHz.
- (b) 334 μV/m (50.5 dBμV/m) at 30 m, withing the bands 13.410 – 13.553 MHz and 13.567 – 13.710 MHz.
- (c) 106 μV/m (40.5 dBμV/m) at 30 m, within the bands 13.110 – 13.410 MHz and 13.710 – 14.010 MHz.
- (d) RSS-GEN general field strength limits for frequencies outside the band 13.110 – 14.010 MHz.

Industry Canada RSS-GEN, Limit Clause

Frequency	Electric Field Strength (μV/m)	Magnetic Field Strength (H-Field) (μA/m)	Measurement Distance (m)
9 - 490 kHz	2,400/F (F in kHz)	2,400/377F (F in kHz)	300
490 - 1,705 kHz	24,000/F (F in kHz)	24,000/377F (F in kHz)	30
1,705 kHz - 30 MHz	30	N/A	30

Table 13 - Industry Canada Radiated Emission Limit - Less than 30 MHz

Frequency (MHz)	Field Strength (μV/m at 3 m)
30 - 88	100
88 - 216	150
216 - 960	200
> 960	500

Table 14 - Industry Canada Radiated Emission Limit - 30 MHz to 1 GHz

2.3.7 Test Location and Test Equipment Used

This test was carried out in Semi anechoic room - cabin no. 8.

Instrument	Manufacturer	Type No	T-ID	Calibration Period (months)	Calibration Due
Loop antenna	Rohde & Schwarz	HFH2-Z2	18876	24	2018-07-31
TRILOG Antenna	Schwarzbeck	VULB 9163	19691	24	2020-12-31
EMI test receiver	Rohde & Schwarz	ESW26	28268	1	



2.4 AC Power Line Conducted Emissions

2.4.1 Specification Reference

FCC 47 CFR Part 15C, Industry Canada RSS-210 and Industry Canada RSS-GEN, Clause 15.207, N/A and 8.8

2.4.2 Equipment Under Test and Modification State

SD906, S/N: R173000147 - Modification State 1

2.4.3 Date of Test

2018-02-14

2.4.4 Environmental Conditions

Ambient Temperature 22,0 °C
Relative Humidity 28,0 %

2.4.5 Test Results

Normal operation - Continuous polling without RFID Tag card

Applied supply Voltage: 115 V AC
Applied supply frequency: 60 Hz

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Line	Corr. (dB)
15.718000	45.21	---	60.00	14.79	1000.0	N	0.3
16.046000	---	37.77	50.00	12.23	1000.0	N	0.3
16.102000	46.49	---	60.00	13.51	1000.0	N	0.3
16.486000	---	37.55	50.00	12.45	1000.0	N	0.3
16.486000	46.03	---	60.00	13.97	1000.0	N	0.3
---	---	---	---	---	---	L1	---

Table 15 - Live Line Emissions Results




Figure 6 – Live- and Neutral-Line 150 kHz to 30 MHz



FCC 47 CFR Part 15, Limit Clause 15.207 and Industry Canada RSS-GEN, Limit Clause 8.8

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

Table 16

*Decreases with the logarithm of the frequency.

2.4.6 Test Location and Test Equipment Used

This test was carried out in Shielded room - cabin no. 4.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
EMI test receiver	Rohde & Schwarz	100008	19730	12	2018-10-31
V-network	Rohde & Schwarz	894785/005	18919	36	2019-10-31

Table 17

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment

N/A - Not Applicable



Product Service

2.5 Exposure of Humans to RF Fields

2.5.1 Specification Reference

IC RSS-Gen Issue 4, section 3.2

2.5.2 Guide

IC RSS-102 Issue 5, section 2.5

2.5.3 Equipment Under Test and Modification State

SD906, S/N: R173000147 - Modification State 0

2.5.4 Date of Test

2018-01-11

2.5.5 Test Results

Exposure of Humans to RF Fields	Applicable	Declared by applicant	Measured	Exemption
The antenna is				
☐ detachable				
The conducted output power (CP in watts) is measured at the antenna connector: $CP = \dots\dots\dots \text{ W}$ The effective isotropic radiated power (EIRP in watts) is calculated using ☐ the numerical antenna gain: $G = \dots\dots\dots$ $EIRP = G \cdot CP \Rightarrow EIRP = \dots\dots\dots \text{ W}$ ☐ the field strength¹ in V/m: $FS = \dots\dots\dots \text{ V/m}$ $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \dots\dots\dots \text{ W}$ with: Distance between the antennas in m: $D = \dots\dots\dots \text{ m}$			☐	
☒ not detachable				
A field strength measurement has been performed with dormakaba registration unit 90 04 to determine the effective isotropic radiated power (EIRP in watts) given by 13.56 MHz $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = 5.4 \mu\text{W}$ with: Field strength in V/m: $FS = 9.2 \text{ mV/m}$ Distance between the two antennas in m: $D = 3 \text{ m}$			☒	☒
Selection of output power				
The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.): $TP = 25.4 \mu\text{W}$				

¹ The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses.

If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.



Exposure of Humans to RF Fields (continued)	Applicable	Declared by applicant	Measured	Exemption
Separation distance between the user and the transmitting device is				
☒ less than or equal to 20 cm		☐		
☐ greater than 20 cm				
Transmitting device is				
☐ in the vicinity of the human head		☐		
☐ body-worn				



SAR evaluation										
SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in the table. For controlled use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation in the table are multiplied by a factor of 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in the table are multiplied by a factor of 2.5. If the operating frequency of the device is between two frequencies located in the table, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required. For medical implants devices, the exemption limit for routine evaluation is set at 1 mW. The output power of a medical implants device is defined as the higher of the conducted or e.i.r.p to determine whether the device is exempt from the SAR evaluation.										
Frequency (MHz)	Exemption limits (mW) ² at separation distance of									
	• 5 mm	10 mm	15 mm	20 mm	25 mm	30 mm	35 mm	40 mm	45 mm	• 50 mm
• 300 ³	71	101	132	162	193	223	254	284	315	345
450	52	70	88	106	123	141	159	177	195	213
835	17	30	42	55	67	80	92	105	117	130
1900	7	10	18	34	60	99	153	225	316	431
2450	4	7	15	30	52	83	123	173	235	309
3500	2	6	16	32	55	86	124	170	225	290
5800	1	6	15							



Carrier frequency: f = 13.56 MHz				
Distance: d = 5 mm				
Transmitter output power: TP = 25.4 μW				
Limit: TP_{limit} = 71 mW				☒
☐ SAR evaluation is documented in test report no. ...				

2.5.6 Test Location and Test Equipment Used

This test was carried out in a non shielded room.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Electromagnetic radiation meter	Narda Safety	EMR-200	19590	36	2019-10-31
Electric field probe	Narda Safety	Type 8.3	19591	36	2019-10-31
Magnetic field probe	Narda Safety	Type 12.1	19592	36	2019-10-31

Table 18



Product Service

3 Photographs

3.1 Equipment Under Test (EUT)

Figure 7



Figure 8



Figure 9




Figure 10

Figure 11

4 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

Radio Testing			
Test Name	kp	Expanded Uncertainty	Note
Occupied Bandwidth	2.0	$\pm 1.14 \%$	2
RF-Frequency error	1.96	$\pm 1 \cdot 10^{-7}$	7
RF-Power, conducted carrier	2	$\pm 0.079 \text{ dB}$	2
RF-Power uncertainty for given BER	1.96	$+0.94 \text{ dB} / -1.05$	7
RF power, conducted, spurious emissions	1.96	$+1.4 \text{ dB} / -1.6 \text{ dB}$	7
RF power, radiated			
25 MHz – 4 GHz	1.96	$+3.6 \text{ dB} / -5.2 \text{ dB}$	8
1 GHz – 18 GHz	1.96	$+3.8 \text{ dB} / -5.6 \text{ dB}$	8
18 GHz – 26.5 GHz	1.96	$+3.4 \text{ dB} / -4.5 \text{ dB}$	8
40 GHz – 170 GHz	1.96	$+4.2 \text{ dB} / -7.1 \text{ dB}$	8
Spectral Power Density, conducted	2.0	$\pm 0.53 \text{ dB}$	2
Maximum frequency deviation			
300 Hz – 6 kHz	2	$\pm 2,89 \%$	2
6 kHz – 25 kHz	2	$\pm 0.2 \text{ dB}$	2
Maximum frequency deviation for FM	2	$\pm 2,89 \%$	2
Adjacent channel power 25 MHz – 1 GHz	2	$\pm 2.31 \%$	2
Temperature	2	$\pm 0.39 \text{ K}$	4
(Relative) Humidity	2	$\pm 2.28 \%$	2
DC- and low frequency AC voltage			
DC voltage	2	$\pm 0.01 \%$	2
AC voltage up to 1 kHz	2	$\pm 1.2 \%$	2
Time	2	$\pm 0.6 \%$	2

Table 19



Radio Interference Emission Testing			
Test Name	kp	Expanded Uncertainty	Note
Conducted Voltage Emission			
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB	1
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB	1
100 kHz to 200 MHz (50Ω/5μH AMN)	2	± 3.6 dB	1
Discontinuous Conducted Emission			
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB	1
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB	1
Conducted Current Emission			
9 kHz to 200 MHz	2	± 3.5 dB	1
Magnetic Fieldstrength			
9 kHz to 30 MHz (with loop antenna)	2	± 3.9 dB	1
9 kHz to 30 MHz (large-loop antenna 2 m)	2	± 3.5 dB	1
Radiated Emission			
Test distance 1 m (ALSE)			
9 kHz to 150 kHz	2	± 4.6 dB	1
150 kHz to 30 MHz	2	± 4.1 dB	1
30 MHz to 200 MHz	2	± 5.2 dB	1
200 MHz to 2 GHz	2	± 4.4 dB	1
2 GHz to 3 GHz	2	± 4.6 dB	1
Test distance 3 m			
30 MHz to 300 MHz	2	± 4.9 dB	1
300 MHz to 1 GHz	2	± 5.0 dB	1
1 GHz to 6 GHz	2	± 4.6 dB	1
Test distance 10 m			
30 MHz to 300 MHz	2	± 4.9 dB	1
300 MHz to 1 GHz	2	± 4.9 dB	1
Radio Interference Power			
30 MHz to 300 MHz	2	± 3.5 dB	1
Harmonic Current Emissions			4
Voltage Changes, Voltage Fluctuations and Flicker			4

Table 20



Immunity Testing			
Test Name	kp	Expanded Uncertainty	Note
Electrostatic Discharges			4
Radiated RF-Field			
Pre-calibrated field level	2	+32.2 / -24.3 %	5
Dynamic feedback field level	2.05	+21.2 / -17.5 %	3
Electrical Fast Transients (EFT) / Bursts			4
Surges			4
Conducted Disturbances, induced by RF-Fields			
via CDN	2	+15.1 / -13.1 %	6
via EM clamp	2	+42.6 / -29.9 %	6
via current clamp	2	+43.9 / -30.5 %	6
Power Frequency Magnetic Field	2	+20.7 / -17.1 %	2
Pulse Magnetic Field			4
Voltage Dips, Short Interruptions and Voltage Variations			4
Oscillatory Waves			4
Conducted Low Frequency Disturbances			
Voltage setting	2	± 0.9 %	2
Frequency setting	2	± 0.1 %	2
Electrical Transient Transmission in Road Vehicles			4

Table 21

Note 1:

The expanded uncertainty reported according to CISPR 16-4-2:2003-11 is based on a standard uncertainty multiplied by a coverage factor of $k_p = 2$, providing a level of confidence of $p = 95.45\%$

Note 2:

The expanded uncertainty reported according to UKAS Lab 34 (Edition 1, 2002-08) is based on a standard uncertainty multiplied by a coverage factor of $k_p = 2$, providing a level of confidence of $p = 95.45\%$

Note 3:

The expanded uncertainty reported according to UKAS Lab 34 (Edition 1, 2002-08) is based on a standard uncertainty multiplied by a coverage factor of $k_p = 2.05$, providing a level of confidence of $p = 95.45\%$

Note 4:

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95% confidence.



Product Service