

Electromagnetic Emission

FCC MEASUREMENT REPORT

CERTIFICATION OF COMPLIANCE

FCC Part 15 Certification Measurement

PRODUCT : LCD Monitor
MODEL/TYPE NO : OR1503SH
FCC ID : QTMOR1503SH
APPLICANT : Yuri Electronics Co., Ltd.
122-6, Youngcheon-ri, Dongtan-myeon, Hwaseong-si,
Gyeonggi-do, Korea
Attn.: Oh, Jong-bok / R&D Manager
MANUFACTURER : Yuri Electronics Co., Ltd.
122-6, Youngcheon-ri, Dongtan-myeon, Hwaseong-si,
Gyeonggi-do, Korea
FCC CLASSIFICATION : Class B personal computers and peripherals
FCC RULE PART(S) : FCC Part 15 Subpart B
FCC PROCEDURE : Certification
Brand NAME : TopSync
TEST REPORT No. : ETLE060425.176
DATES OF TEST : August 01, 2006
REPORT ISSUE DATE : August 23, 2006
TEST LABORATORY : ETL Inc. (FCC Registration Number : 95422)

This LCD Monitor, Model OR1503SH has been tested in accordance with the measurement procedures specified in ANSI C63.4-2003 at the ETL/EMC Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart B:

I attest to the accuracy of data. All measurement herein was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.


Chon Sik, Kim / Chief Engineer

ETL Inc.

#584 Sangwhal-ri, Ganam-myeon, Yaju-gun, Gyeonggi-do, 469-885, Korea
Tel : 82-2-858-0786 Fax : 82-2-858-0788

Table of Contents

FCC Measurement Report

1. Introduction
2. Product Information
3. Description of Tests
4. Test Condition
5. Test Results
 - 5.1 Summary of Test Results
 - 5.2 Conducted Emissions Measurement
 - 5.3 Radiated Emissions Measurement
 - 5.4 Antenna Power Conduction Measurement
 - 5.5 Picture Sensitivity
 - 5.6 Noise figure measurement
6. Sample Calculation
7. List of test Equipment used for Measurement

Appendix A. FCC ID Label and Location

Appendix B. Test Setup Photographs

Appendix C. External Photographs

Appendix D. Internal Photographs

Appendix E. Block Diagram

Appendix F. User Manual

FCC MEASUREMENT REPORT

Scope – Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

General Information

Applicant Name : Yuri Electronics Co., Ltd.

Address : 122-6, Youngcheon-ri, Dongtan-myeon, Hwaseong-si,
Gyeonggi-do, Korea

Attention : Oh, Jong-bok / R&D Manager

- **EUT Type** : LCD Monitor
- **Model Number** : OR1503SH
- **FCC ID** : QTMOR1503SH
- **S/N** : N/A
- **FCC Rule Part(s)** : FCC Part 15 Subpart B
- **Test Procedure** : ANSI C63.4-2003
- **FCC Classification** : Class B personal computers and peripherals
- **Dates of Tests** : August 01, 2006
- **Place of Tests** : ETL Inc.
EMC Testing Lab. (FCC Registration Number : 95422)
#584, Sangwhal-ri, Ganam-myeon, Yaju-gun,
Gyeonggi-do, 469-885, Korea
Tel : 82-2-858-086 Fax : 82-2-858-0788
- **Test Report No.** : ETLE060425.176

1. INTRODUCTION

The measurement test for radiated and conducted emission test were conducted at the open area test site of E-RAE Testing Laboratory Inc. facility located at #584, Sangwhal-ri, Ganam-myeon, Yoju-gun, Gyeonggi-do, 469-885, Korea. The site is constructed in conformance with the requirements of the ANSI C63.4-2003 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 m and 10 m site configurations. Detailed description of test facility was found to be in compliance with the requirements of Section 2.948 FCC Rules according to the ANSI C63.4-2003 and registered to the Federal Communications Commission (Registration Number : 95422).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2003) was used in determining radiated and conducted emissions from the Yuri Electronics Co., Ltd., Model: OR1503SH.

2. PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the Yuri Electronics Co., Ltd., Model: OR1503SH.

2.2 General Specification

Spec.		Details
Screen size		15 Inch
Display size		304 mm x 228 mm
Screen coating		Anti-glare & Hand-Coating
Pixel pitch		0,297 mm x 0,297 mm
Brightness		250 cd/m ²
Contrast scaling		450:1
Viewing angle		65/65/50/60 (left/right/up/down)
Response time		Tf=11 ms, Tr=5 ms
Input signal		Analog RGB 0,7 Vp-p, Audio in, S-Video in, BNC in
Speaker(Optional)		2 W x 2 W
H-Frequency		30 kHz – 61 kHz
V-Frequency		55 Hz – 75 Hz
Resolution		1024 x 768 @ 75 Hz
Panel color		16,7 M colors
Power Consumption		30 W (Normal mode) 5 W (Power –sawing mode)
Product size		464 x 240 x 440 (W x D x H)
Weight	Monitor	4,27 kg
	Package	6,3 kg

3. DESCRIPTION OF TESTS

3.1 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with section 11, "Measurement of Information Technology Equipment" of ANSI C63.4-2003. The measurements were performed over the frequency range of 0,15 MHz to 30 MHz using a 50 Ω / 50uH LISN as the input transducer to a Spectrum Analyzer or a Test Receiver. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 9 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

The line-conducted emission test is conducted inside a shielded anechoic chamber room with 1 m x 1,5 m x 0,8 m wooden table which is placed 40 cm away from the vertical wall and 1,5 m away from the side wall of the chamber room. Two LISN are bonded to the shielded room. The EUT is powered from the LISN and the support equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1,2 cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the LISN. Non-inductive bundling to a 1 m length shortened all interconnecting cables more than 1 m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the EMI Test Receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0,15 MHz to 30 MHz. The bandwidth of the spectrum analyzer was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

Photographs of the worst-case emission can be seen in photographs of conducted emission test setup in Appendix B.

3. DESCRIPTION OF TESTS

3.2 Radiated Emission Measurement

Radiated emission measurements were made in accordance with section 11, "Measurement of Information Technology Equipment" of ANSI C63.4-2003. The measurements were performed over the frequency range of 30 MHz to 1 GHz using antenna as the input transducer to a spectrum analyzer or a field intensity meter. The measurements were made with the detector set for "Quasi-peak" within a bandwidth of 120 kHz.

Preliminary measurements were made at 3 m using broadband antennas, and spectrum analyzer to determine the frequency producing the maximum emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 MHz to 1 000 MHz using Log-Bicon antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site at 3 m. The test equipment was placed on a wooden turn-table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR Quasi-peak mode and the bandwidth of the receiver was set to 120 kHz or 1MHz depending on the frequency of type of signal. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0,8 m high nonmetallic 1 m x 1,5 m table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

4. TEST CONDITION

4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the EUT and the supported equipments were installed to meet FCC requirement and operated in a manner and which tends to maximize its emission level in a typical application.

4.2 EUT operation

Operating Mode	The worst operating condition
Stand-by mode	X
640 * 480 Vf = 75 Hz, Full "H" pattern display mode	X
800 * 600 Vf = 75 Hz, Full "H" pattern display mode	X
1024 * 768 Vf = 75 Hz, Full "H" pattern display mode	◎


◎ : Worst case investigated during the test.

4.3 Support Equipment Used

Description	Model Name	Serial No.	Manufacturer	FCC ID
LCD MONITOR (EUT)	OR1503SH	N/A	ORION COMMUNICATION CO., LTD.	N/A
PC	DHM	H9MB71S	Dell Asia Pacific Sdn.	N/A
Adapter	123-124000-I3	6Y145182C	Xiang Fa Electronics	N/A
Printer	Color cap 330	11-03098	Lexmark International	N/A
Keyboard	ACK-260A	909251875	PC BANK	N/A
Mouse	SWW-23	N/A	A4 TECH	N/A
DVD Player	DVR-530C	N/A	Ellion Digital	N/A

4. TEST CONDITION

4.4 The setup drawing(s)



_____ : Data Line
 _____ : Power Line

4. TEST CONDITION

4.5 Type of Cables Used

Device from	Device to	Type of Cable	Length(m)	Type of shield
EUT	Computer	RGB in	1,5	Shielded
EUT	Computer	Audio in	1,5	Shielded
EUT	DVD Player	Audio in	3,0	Shielded
EUT	DVD Player	S-VIDEO in	1,5	Shielded
EUT	DVD Player	S-VIDEO out	1,5	Shielded
EUT	DVD Player	TV CVBS IN	3,0	Shielded
EUT	DVD Player	BNC out	3,0	Shielded
EUT	Adapter	DC Input	1,2	Shielded
DVD Player	Power Socket	Non-detachable Power	1,5	Unshielded
Computer	Keyboard	PS/2	1,5	Shielded
Computer	Mouse	PS/2	1,5	Shielded
Computer	Power Socket	AC Input	1,2	Unshielded

5. TEST RESULTS

5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

FCC Rule	Measurement Required	Result
15.107	Conducted Emission Measurement	Passed by 12,4 dB
15.109	Radiated Emission Measurement	Passed by 3,1 dB

The data collected shows that the **Yuri Electronics Co., Ltd. / LCD Monitor / OR1503SH** complied with technical requirements of above rules part 15.107 and 15.109 Class B Limits and CISPR Publication 22.

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

5. TEST RESULTS

5.2 Conducted Emissions Measurement

EUT	LCD Monitor / OR1503SH (SN :N/A)
Limit apply to	FCC Part 15. 107(CISPR Pub.22 Class B)
Test Date	August 01, 2006
Operating Condition	1024 * 768 Vf = 75Hz, Full "H" pattern display mode
Result	Passed by 12,4 dB

Conducted Emission Test Data

The following table shows the highest levels of conducted emissions on both polarizations of hot and neutral line.

Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth : 9 kHz)

Frequency [MHz]	Result [dB μ V]		Phase (*H/**N)	Limit [dB μ V]		Margin [dB]	
	Quasi-peak	Average		Quasi-peak	Average	Quasi-peak	Average
0,154	35,9	27,4	N	65,7	55,7	29,8	28,3
0,189	51,7	39,9	N	64,1	54,1	12,4	14,2
0,255	39,7	31,3	N	61,6	51,6	21,9	20,3
4,425	34,7	23,7	N	56,0	46,0	21,3	22,3
4,545	34,8	23,8	H	56,0	46,0	21,2	22,2
4,610	37,0	28,6	H	56,0	46,0	19,0	17,4
5,052	35,5	28,4	H	60,0	50,0	24,5	21,6
14,782	32,7	29,8	H	60,0	50,0	27,3	20,2
16,177	32,1	26,2	H	60,0	50,0	27,9	23,8

NOTES: 1. * H: HOT Line , **N: Neutral Line

2. Margin value = Limit – Result


3. Measurement were performed at the AC Power Inlet in the frequency band of 150 kHz ~ 30 MHz according to the FCC Part 15 and CISPR 22 Class B




Test Engineer: Kug Kyoung, Yoon

Line: HOT Line

Limit : — Quasi-Peak
— Average



Line: Neutral Line



Quasi-peak ○ Average ◇

5. TEST RESULTS

5.3. Radiated Emissions Measurement

EUT	LCD Monitor / OR1503SH (SN :N/A)
Limit apply to	FCC Part 15. 109(CISPR Pub.22 Class B)
Test Date	August 01, 2006
Operating Condition	1024 * 768 Vf = 75Hz, Full "H" pattern display mode
Result	Passed by 3,1 dB

Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 120 kHz)

Frequency [MHz]	Reading [dB μ V]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB μ V]	Emission Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
62,72	16,01	V	8,57	2,12	26,70	30,0	3,30
99,53	13,63	V	9,25	2,72	25,60	30,0	4,40
126,80	11,99	V	11,11	3,20	26,30	30,0	3,70
148,62	11,60	V	11,67	3,53	26,80	30,0	3,20
157,50	11,56	V	11,68	3,66	26,90	30,0	3,10
216,11	12,35	V	9,94	4,41	26,70	30,0	3,30
446,70	8,32	V	15,92	7,16	31,40	37,0	5,60
520,93	8,04	V	17,62	7,94	33,60	37,0	3,40
573,96	4,06	H	18,30	8,64	31,00	37,0	6,00
581,03	4,05	H	18,34	8,71	31,10	37,0	5,90
596,94	5,09	H	18,44	8,87	32,40	37,0	4,60
630,52	4,77	H	19,38	9,15	33,30	37,0	3,70

NOTES : * H : Horizontal polarization , ** V : Vertical polarization

Result = Reading + Antenna factor + Cable loss

Margin value = Limit - Result

The measurement was performed for the frequency range 30 MHz ~ 1 000 MHz according to the CISPR 22 Class B



Test Engineer: Kug Kyoung, Yoon

6. SAMPLE CALCULATION

Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

$$dB(\mu V) = 20 \log_{10} (\mu V)$$

$$dB\mu V = dBm + 107$$

Example : @ 157,50 MHz

$$\text{Class B Limit} = 31,7 \mu V/m = 30 \text{ dB } \mu V/m$$

$$\text{Reading} = 11,56 \text{ dB } \mu V$$

$$\text{Antenna Factor + Cable Loss} = 11,68 + 3,66 = 15,34 \text{ dB } \mu V/m$$

$$\text{Total} = 26,90 \text{ dB } \mu V/m$$

$$\text{Margin} = 30 - 26,9 = 3,1 \text{ dB}$$

$$= 3,1 \text{ dB below Limit}$$

7. List of test equipments used for measurements

Test Equipment		Model	Mfg.	Serial No.	Cal. Due Date
☒	EMI TEST Receiver	ESVS 10	R & S	835165/001	07-04-25
☒	EMI TEST Receiver	ESPI	R & S	100478	06-10-17
☒	LISN	3816-2	EMCO	1002	06-10-17
☒	LISN	3825/2	EMCO	9208-1995	07-04-06
☒	LogBicon Antenna	VULB9165	Schwarz Beck	2023	07-07-24
☒	Turn-Table	DETT-03	Daeil EMC	-	N/A
☒	Antenna Master	DEAM-03	Daeil EMC	-	N/A

End of Test Report