

Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: QVHDBWIFIBLE05

Items to be covered by <i>Single modular transmitters.</i>	Answer from applicant
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	The modular has a shielding Case. Please refer to EUT Photo.
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	Modulation/buffering for data inputs is embedded within the MT7931AN Mediatek chip set
3. The module must contain power supply regulation on the module	Power supply regulation is embedded within the MT7931AN Mediatek chip set
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	Antenna is permanently attached. And no external amplifier will be used with this modular
5. The module must demonstrate compliance in a stand-alone configuration.	This modular is tested under stand-alone configuration. Please refer to Test setup photo.
6. The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748).	The modular transmitter is labelled with its own FCC ID number. Please refer to label sample and label location.
7. The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	The module complies with this requirement. Please refer to user manual.
8. The module must comply with RF exposure requirements.	The device complies with this requirement. Please refer to RF exposure report.

Items to be covered by <i>Split modular transmitters.</i>	Answer from applicant
1. The modular transmitter must comply with all requirements of a single modular transmitter except for items (1) & (5) of the above single modular approval requirements.	N/A
2. Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signalling amplitude of 150 mV peak-to-peak.	N/A
3. Control information and other data may be exchanged between the transmitter control elements and radio front end.	N/A
4. The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.	N/A
5. Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of	N/A



operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization.

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or authorized representative): Mike Partridge

Date: 24 May 2023

Signature:

A handwritten signature in blue ink, appearing to read "Mike Partridge".

Revision Record Sheet:

Revision	Section number	Page number	Date	Remark(s)	issued by
5		1	28-12-2022	History sheet added	WJJ

Issued/modified by : Willem Jan Jong
Function : Team Lead
Revision : 5
Date : 28-12-2022

Verified by : Axel Gase
Function : Quality Manager
Date : 28-12-2022

Released by : Axel Gase
Function : Manager Quality Assurance
Date of release: : 28-12-2022